

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281709

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

WALLS; Bruce Michael et al.

HEADGEAR ASSEMBLY FOR BREATHING INTERFACE

Abstract

An interface and headgear assembly includes a headgear assembly. The headgear assembly has a first strap configured to connect to the interface. A crown strap can be adjusted along a length of the first strap. In some configurations, the crown strap has a first portion and a second portion that are adjustably connected. The crown strap can be removably connected to the first strap using bridge regions of the first portion and the second portion.

Inventors: WALLS; Bruce Michael (Auckland, NZ), FAITHFULL; Rex Gordon (Auckland, NZ), HUANG; Wen Dong (Auckland, NZ), GARDIOLA; Arvin San Jose (Auckland, NZ), YOUNG; Jeremy Owen (Auckland, NZ)

Applicant: Fisher & Paykel Healthcare Limited (Auckland, NZ)

Family ID: 1000008629304

Appl. No.: 19/096579

Filed: March 31, 2025

Related U.S. Application Data

parent US continuation 18466435 20230913 parent-grant-document US 12311110 child US 19096579

parent US continuation 16036567 20180716 parent-grant-document US 11786688 child US 18466435

parent US continuation 15037304 20160517 parent-grant-document US 10039894 WO continuation PCT/IB2014/066374 20141127 child US 16036567

us-provisional-application US 61909936 20131127

us-provisional-application US 61990479 20140508

Publication Classification

Int. Cl.: A61M16/06 (20060101); **A61M16/08** (20060101)

U.S. Cl.:

CPC A61M16/0683 (20130101); **A61M16/0816** (20130101); A61M16/0666 (20130101)

Background/Summary

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

[0001] Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference herein and made a part of the present disclosure.

BACKGROUND OF THE INVENTION

Field

[0002] The present disclosure generally relates to headgear for respiratory devices, such as breathing masks. More particularly, the present disclosure relates to such headgear in which a strap extends circumferentially around a head.

Description of the Related Art

[0003] Headgear is used to secure an interface or breathing mask to the face of the user. The headgear can have any number of configurations. In general, the headgear is used to apply a force vector to the interface that opposes the forces generated by the interface while supplying breathing gases to the user. Not all users, however, have the same experience with any single form of headgear and, from time to time, any individual user may wish to change the user experience with the headgear being used by the user.

SUMMARY

[0004] Thus, it is an object of the disclosure to provide patients with a headgear assembly that might be easier to use or that is easily reconfigurable, or at least provide the public with a useful choice.

[0005] In some configurations, an interface and headgear assembly include an interface comprising a frame and a seal supported by the frame. A headgear assembly is removably connected to the interface. The headgear includes a first strap configured to connect at a first end to the interface and at a second end to the interface. A crown strap is connected to the first strap. The crown strap comprises a first bridge region and a second bridge region. The first bridge region defines a first passage that receives the first strap and the second bridge region defines a second passage that receives the first strap. Each of the first bridge region and the second bridge region is adjustable in position relative to the first strap.

[0006] In some configurations, each of the first bridge region and the second bridge region comprises multiple supporting components configured to secure the first bridge region and the second bridge region, respectively, to the first strap.

[0007] In some configurations, the supporting components comprise a first loop and a second loop configured to receive the strap of the interface and headgear assembly.

[0008] In some configurations, each of the first and second loops is an interrupted loop.

[0009] In some configurations, each of the first and second loops comprises an upper portion and a lower portion defining a slot therebetween.

[0010] In some configurations, a width of a passageway defined by each of the first and second loops is smaller at the upper portion than at a lower portion.

[0011] In some configurations, the assembly further comprises at least one medial member positioned between the first loop and the second loop and extending vertically upward from a lower

lip of the first bridge region.

[0012] In some configurations, the at least one medial member supports the first strap at a relatively higher position than a position of the first strap at the first and second loops.

[0013] In some configurations, the at least one medial member comprises a lower medial member and an upper medial member and the first strap can be engaged with either of the lower or upper medial members to adjust an effective length of the first strap.

[0014] In some configurations, the crown strap comprises a first strap region and a second strap region, the first strap region and the second strap region being removably coupled together.

[0015] In some configurations, the first strap region and the second strap region are coupled by an adjustment mechanism.

[0016] In some configurations, the adjustment mechanism comprises a plurality of apertures and one or more posts that are selectively engageable with the plurality of apertures.

[0017] In some configurations, the adjustment mechanism comprises two or more slots and a plurality of ridges that are selectively engageable with the one or more slots.

[0018] In some configurations, the adjustment mechanism comprises one or more slots and one or more wedges or flaps that are selectively engageable with the one or more slots.

[0019] In some configurations, the first strap is constructed from a stretchable material.

[0020] In some configurations, the first strap is a tubular-knitted elastic strap.

[0021] In some configurations, the crown strap is constructed from a substantially non-stretchable material.

[0022] In some configurations, at least a strap region of the crown strap is constructed from a flexible material.

[0023] In some configurations, the material of the strap region has sufficient rigidity such that it is capable of substantially maintaining its shape.

[0024] In some configurations, the assembly comprises a sleeve on the first strap.

[0025] In some configurations, a surface of the sleeve that contacts a user in use comprises grip-enhancing features.

[0026] In some configurations, a removable crown strap assembly is removably connected to the first strap.

[0027] In some configurations, the removable crown strap assembly comprises a first portion and a second portion.

[0028] In some configurations, the first portion and the second portion can be connected with an adjustment mechanism.

[0029] In some configurations, the first portion comprises a first strap region and a first bridge region and the second portion comprises a second strap region and a second bridge region.

[0030] In some configurations, the first bridge region defines a first passage that removably receives the first strap and the second bridge region defines a second passage that removably receives the first strap.

[0031] In some configurations, an interface and headgear assembly can be provided. The interface can comprise a frame and a seal supported by the frame. A headgear assembly can be removably connected to the interface. The headgear can comprise a first strap configured to connect at a first end to the interface and at a second end to the interface. A removable crown strap assembly can be removably connected to the first strap. The removable crown strap assembly comprises a first portion and a second portion. The first portion and the second portion can be connected with an adjustment mechanism. The first portion comprises a first strap region and a first bridge region and the second portion comprises a second strap region and a second bridge region. The first bridge region defines a first passage that removably receives the first strap and the second bridge region defines a second passage that removably receives the first strap.

[0032] In some configurations, a removable crown strap assembly can be configured for use with an interface and headgear assembly. The removable crown strap assembly comprises a first bridge

region and a second bridge region configured to receive a strap of the interface and headgear assembly.

[0033] In some such configurations, the first bridge region comprises multiple supporting components configured to secure the first bridge region to the strap of the interface and headgear assembly. In some such configurations, the supporting components comprise a first interrupted loop and a second interrupted loop configured to receive the strap of the interface and headgear assembly. In some such configurations, a medial member is positioned between the first interrupted loop and the second interrupted loop and extends vertically upward from a lower lip of the first bridge region. In some such configurations, the removable crown strap assembly comprises a first strap region and a second strap region with the first strap region and the second strap region being removably coupled together. In some such configurations, the first strap region and the second strap region are coupled by an adjustment mechanism.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] These and other features, aspects and advantages of the present disclosure will now be described with reference to the drawings of preferred embodiments, which embodiments are intended to illustrate and not to limit the disclosure, and in which figures:

[0035] FIGS. 1A and 1B are a partially exploded view of an interface and headgear assembly that is arranged and configured in accordance with certain features, aspects and advantages of the present disclosure.

[0036] FIG. 2 is a front perspective view of the headgear of FIG. 1A.

[0037] FIG. 3 is a rear perspective view of the headgear of FIG. 1A.

[0038] FIG. 4 is a right side view of the headgear of FIG. 1A.

[0039] FIG. 5 is a rear view of the headgear of FIG. 1A.

[0040] FIG. 6 is a left side view of the headgear of FIG. 1A.

[0041] FIG. 7 is a top view of the headgear of FIG. 1A.

[0042] FIG. 8 is a front view of the headgear of FIG. 1A.

[0043] FIG. 9 is a bottom view of the headgear of FIG. 1A.

[0044] FIG. 10 is a rear perspective of a removable crown strap assembly of the headgear of FIG. 1A.

[0045] FIG. 11 is a right view of the removable crown strap assembly of FIG. 10.

[0046] FIG. 12 is a rear view of the removable crown strap assembly of FIG. 10.

[0047] FIG. 13 is a top view of the removable crown strap assembly of FIG. 10.

[0048] FIG. 14 is a side view of a rear strap of the headgear of FIG. 1A.

[0049] FIG. 15 is a side view of the rear strap of FIG. 14 with a rear sleeve removed.

[0050] FIG. 16 is a perspective view of the headgear assembly of FIG. 1A shown positioned on a head of a user.

[0051] FIG. 17 is a perspective view of a latch adjustment mechanism for adjusting a rear strap.

[0052] FIG. 18 is a perspective view of a snap adjustment mechanism for adjusting a rear strap.

[0053] FIG. 19 is a perspective view of a telescoping arm adjustment mechanism for adjusting a rear strap.

[0054] FIG. 20 is a perspective view of a further arrangement for adjusting a rear strap.

[0055] FIG. 21 is a perspective view of a crown strap adjustment configuration.

[0056] FIG. 22 is a perspective view of another crown strap adjustment configuration.

[0057] FIG. 23 is a perspective view of a headgear assembly.

[0058] FIG. 24 is another perspective view of the headgear assembly of FIG. 23.

[0059] FIG. 25 is a side elevation view of the headgear assembly of FIG. 23.

[0060] FIG. **26** is a rear elevation view of the headgear assembly of FIG. **23**.
[0061] FIG. **27** is a side elevation view of the headgear assembly of FIG. **23**.
[0062] FIG. **28** is a top view of the headgear assembly of FIG. **23**.
[0063] FIG. **29** is a front elevation view of the headgear assembly of FIG. **23**.
[0064] FIG. **30** is a bottom view of the headgear assembly of FIG. **23**.
[0065] FIG. **31** is a perspective view of a crown strap assembly of the headgear assembly of FIG. **23**.
[0066] FIG. **32** is a front view of the crown strap assembly of FIG. **31**.
[0067] FIG. **33** is an enlarged view of a portion of the crown strap assembly of FIG. **31**.
[0068] FIG. **34** is a perspective view of a headgear assembly.
[0069] FIG. **35** is another perspective view of the headgear assembly of FIG. **34**.
[0070] FIG. **36** is a side elevation view of the headgear assembly of FIG. **34**.
[0071] FIG. **37** is a rear elevation view of the headgear assembly of FIG. **34**.
[0072] FIG. **38** is a side elevation view of the headgear assembly of FIG. **34**.
[0073] FIG. **39** is a top view of the headgear assembly of FIG. **34**.
[0074] FIG. **40** is a front elevation view of the headgear assembly of FIG. **34**.
[0075] FIG. **41** is a bottom view of the headgear assembly of FIG. **34**.
[0076] FIG. **42** is a side view of a crown strap assembly of the headgear assembly of FIG. **34**.
[0077] FIG. **43** is a rear view of the crown strap assembly of FIG. **42**.
[0078] FIG. **44** is an enlarged sectioned view of a portion of the crown strap assembly of FIG. **42**.
[0079] FIG. **45** is a perspective view of the crown strap assembly of FIG. **42**.

DETAILED DESCRIPTION

[0080] FIGS. **1A** and **1B** illustrate an interface and headgear assembly **100** that is arranged and configured in accordance with certain features, aspects and advantages of the present disclosure. The assembly **100** features an interface **102** that is removably connectable with a headgear assembly **104**.

[0081] The patient interface **102** can be any suitable type of patient interface. Examples of suitable types of patient interfaces include face masks, oral masks, nasal masks, nasal pillows masks, nasal cannulae, combinations of oral and nasal masks, tracheal masks, and the like. The illustrated interface **102** is a nasal pillows mask that includes a mask frame **106**.

[0082] In the illustrated configuration, the mask frame **106** and the headgear assembly **104** can be joined together using any suitable technique. In the illustrated configuration, a post and hook system **108** is used to join the patient interface **102** and the headgear assembly **104**. In the illustrated system **108**, the mask frame **106** can include a post **110** or the like while the headgear assembly **104** can include a hook **112**. The hook **112** can be joined to the post **110** to connect the headgear assembly **104** to the mask frame **106** and the hook **112** can be separated from the post **110** to decouple the headgear assembly **104** from the mask frame **106**.

[0083] The headgear assembly **104** generally comprises a main strap **114**. The main strap **114** can be configured to extend around the back of the head or neck of the wearer. The main strap **114** can have any suitable configuration and can be formed of any suitable material. In some configurations, the main strap **114** can be formed of a stretchable material. In some configurations, the main strap **114** comprises a tubular-knitted elastic strap. In some configurations, the main strap **114** can be of any configuration described in WO2010/131189, published on Nov. 18, 2010, or WO2011/059346, published on May 19, 2011, each of which is hereby incorporated by reference in its entirety. The main strap **114** provides an easy donning of the interface and headgear assembly **100** because the main strap **114** allows the wearer to simply stretch the main strap **114** and fit the interface and headgear assembly **100** to the head.

[0084] In the illustrated configuration, the main strap **114** comprises two ends **116**. With continued reference to FIG. **1**, each of the two ends **116** can be connected to a corresponding hook **112**. Two different types of hook members **118A**, **118B** are illustrated in FIGS. **1A** and **1B**. Additional types

of hook members **118C**, **118D**, **118E** are illustrated in FIGS. **17-19**. Any suitable hook member can be used. The hook members **118A**, **118B**, **118C**, **118D**, **118E** preferably facilitate easy connection to and disconnection from the interface **102**. In some configurations, the hook members **118A**, **118B**, **118C**, **118D**, **118E** support smooth rotation during fitting or connection. In other words, the hook members **118A**, **118B**, **118C**, **118D**, **118E** can rotate into position relative to the posts **110**.

[0085] One of the hook members **118A** is designed to create a fixed length to the main strap **114**. In other words, a position of the first of the two hook members **118A** on or relative to the main strap **114** is not adjustable. The hook member **118A** can capture at least a portion of the main strap **114** or can be secured to the main strap **114** in any other suitable manner. In some configurations, the hook members **118A** is an assembly that is overmoulded into position onto the main strap **114**.

[0086] The second of hook members **118B** is adjustable relative to the main strap **114** and allows the length of the main strap **114** to be adjusted. In the illustrated configuration, the hook member **118B** includes an opening through which the end **116** of the main strap **114** can be threaded before being doubled back and secured to itself. In the illustrated configuration, a hook and loop fastener **120** can be used. The hook and loop fastener **120** can include a hook tab that is secured to the main strap **114**. In some configurations, the hook tab can be ultrasonically welded, or RF welded, to a nylon, polyester or similar covered substrate, which can form a portion of the main strap **114**. In some configurations, the hook portion of the hook and loop fastener **120** can be positioned on the end of the strap **114** with the loop portion being positioned on the portion of the strap between the two ends of the strap **114**.

[0087] With reference to FIG. **17**, the third of the hook members **118C** is designed to be adjustable and allows the length of the main strap **114** to be adjusted. The main strap **114** feeds through a first latch component **180** and a second latch component **182**. The first latch component **180** and the second latch component can be pivotally connected, for example but without limitation. The position of the hook member **118C** along the main strap **114** can be adjusted until the first latch component **180** and the second latch component **182** are pivoted to a locked position. When in the locked position, the hook member **118C** is secured in position along the main strap **114**. When in the unlocked position, the hook member **118C** can be adjusted along the main strap **114** such that the length of the main strap **114** can be increased and decreased.

[0088] With reference to FIG. **18**, the fourth of the hook members **118D** also is designed to be adjustable and allows the length of the main strap **114** to be adjusted among a plurality of predetermined lengths. In the illustrated configuration, the main strap **114** includes a plurality of snaps **190**. The snaps **190** away from the end of the main strap **114** cooperate with a portion that is positioned on the end of the main strap **114**. As such, the portion that is positioned on the end of the main strap **114** can be moved among the plurality of the snaps **190** to allow for adjustment. In some configurations, the main strap **114** can be provided with two or three different set points (e.g., to correspond to large, medium and small sizes). Other configurations also are possible keeping in mind the goal of providing for simple, yet effective, adjustability.

[0089] With reference to FIG. **19**, the fifth of the hook members **118E** is adjustable and allows the length of the main strap **114** to be adjusted through a telescoping mechanism **200**. The telescoping mechanism **200** generally comprises an outer sleeve member **202** and an inner arm **204**. In the illustrated configuration, the outer sleeve member **202** is secured to the strap **114** while the inner arm **204** is secured to a hook element **206**. In some configurations, the orientation is switched. The outer sleeve member **202** can define an inner passage. The inner passage can include one or more ridges. The inner arm **204** can include one or more recesses. In some configurations, the outer sleeve member can have recesses on the inner passage while the inner arm includes ridges. Other configurations also are possible. By squeezing the outer sleeve member **202**, the inner arm **204** can translate relative to the outer sleeve member **202**. In some configurations, the outer sleeve **202** is squeezed in a direction that is generally normal or perpendicular to the interlocking recesses and ridges such that squeezing the outer sleeve **202** results in movement of a portion of the outer sleeve

202 away from the inner arm **204**. Accordingly, the illustrated configuration provides adjustability. The adjustability provides a plurality of set points depending upon the distance between the ridges and the recesses. Other detent arrangements, locks and retention arrangements can also be used.

[0090] In some configurations, such as that illustrated in FIG. **23**, the adjustability can be provided through the use of buckles **230** or the like. The strap **114** can be threaded through the hooks **112** and secured to a desired length by threading through the buckles **230**. Other suitable configurations also can be used keeping in mind a desire to provide adjustability to the length of the strap **114**.

[0091] As shown in FIG. **15**, in some configurations, the main strap **114** can be used without any further components. In other words, the main strap **114** can be secured to the interface **102** and provide a retention force to maintain the interface **102** in position for use. In such configurations, the main strap **114** may also comprise the hook members **118A** (or the hook members **118B**).

[0092] With reference to FIG. **14**, to enhance comfort, a sleeve **122** can be positioned along the main strap **114** between the ends **116**. The sleeve **122** can be configured in any suitable manner and the sleeve can be formed of any suitable material. In some configurations, the sleeve **122** is repositionable along the main strap **114** in any location between the ends **116**. In some configurations, the sleeve **122** is secured to the main strap **114** and cannot be removed and/or cannot be moved along the length of the main strap **114**.

[0093] The sleeve **122** can be formed of polyester, nylon, micro fibre, fleece, or any other suitable materials, including those that are quick drying and/or moisture wicking. In some configurations, the sleeve **122** forms a flattened tube-like structure that defines an elongate passage that terminates at openings **124**. In configurations in which the sleeve **122** is removable, the openings **124** can be sufficiently large or flexible to accommodate the hook members **118A**, **118B**. In configurations using the removable hook members **118B**, however, the openings **124** need not be sufficiently large or flexible to accommodate the hook members **118B**. The main strap **114** can be inserted into one of the openings **124** and passed through the passage.

[0094] The illustrated sleeve **122** also has a contact surface **126**. The contact surface **126** is the surface that will be directly in contact with the wearer. In the illustrated configuration, the contact surface **126** is enlarged relative to the corresponding surface of the main strap **114**. In the illustrated configuration, the contact surface **126** and the opposite surface both can provide an elongate flattened surface. By providing an elongate flattened surface, labeling can be positioned on the sleeve **122**, which can be used to provide guidance for the proper orientation of the main strap **114** when donning the interface and headgear assembly **100**. In some configurations, the contact surface **126** can be provided with surface texturing or the like to enhance gripping on short haired or bald headed patients.

[0095] With reference again to FIG. **1**, the headgear assembly **104** also can comprise a crown strap assembly **130**. In some configurations, the crown strap assembly **130** can be selectively coupled to and decoupled from the main strap **114**. By including a detachable crown strap assembly **130**, the headgear assembly **104** can provide more options to the user, which can enhance the individualized comfort and/or support sought by users. In addition, using the crown strap assembly **130** can improve stability of the headgear assembly **104**. Moreover, because the crown strap assembly **130** is designed to pass over the top of the head of the user, using the crown strap assembly **130** can reduce slippage of the main strap **114** during use.

[0096] Turning now to FIGS. **10-13**, the crown strap assembly **130** is shown separated from the main strap **114**. In the illustrated configuration, the crown strap assembly **130** is adjustable. Accordingly, the illustrated crown strap assembly **130** comprises a first portion **132** and a second portion **134**. The first portion **132** and the second portion **134** can be adjustably connected. In the illustrated configuration, an adjustment mechanism **136** couples the first portion **132** and the second portion **134**. The first portion **132** connects to the main strap **114** and the second portion **134** while the second portion **134** connects to the main strap **114** and the first portion **132**. In other words, the first portion **132** and the second portion **134** are connected to the main strap **114** and to

each other. In other configurations, the crown strap **130** is not adjustable and can be constructed as a single piece.

[0097] The adjustment mechanism **136** in the configuration illustrated in FIG. **1A** comprises a plurality of apertures **138** and one or more posts **140**. In some configurations, two posts **140** are provided and three apertures **138** are provided. The illustrated configuration provides at least three different settings such that the adjustment mechanism **136** provides three different length or height settings for the crown strap assembly **130**. That is, a change in length of the crown strap **130** changes a height of ends of the crown strap **130** on a user's head in use. Other types of adjustment mechanisms and other numbers of settings can be used.

[0098] The posts **140** can comprise a stem and a head portion. The head portion of the posts **140** can be very closely sized or slightly oversized relative to the aperture **138**. The apertures **138** can snap fit over the head portions of the posts **140**. In such a manner, a secure coupling can be provided.

[0099] Other manners of securing the first portion **132** and the second portion **134** together also can be used. For example, as shown in FIG. **21**, the adjustment mechanism **136** can include two or more slots **210** and a plurality of transverse ridges **212**. In the illustrated configuration, the first portion **132** comprises two parallel slots **210**. The slots **210** do not extend the full width of the first portion **132**. By being generally parallel, the slots **210** can interact with the ridges **212** of the second portion **134**. In some configurations, however, the slots **210** may not be generally parallel. The ridges **212** can extend the full width or at least some portion of the width of the second portion **134**. By spacing the ridges **212** at desired increments, a plurality of discrete and predetermined sizes can be defined for the crown strap assembly **130**.

[0100] With reference to FIG. **22**, another adjustment mechanism **136** is illustrated. In the illustrated configuration, the first portion **132** can include one or more wedges or flaps **220** while the second portion **134** can include corresponding slots **222**. In some configurations, the same number of wedges/flaps **220** and slots **222** can be used (e.g., 3 wedges/flaps **220** and 3 slots **222**). In some configurations, fewer wedges/flaps **220** than slots **222** can be provided. In some configurations, more wedges/flaps **220** than slots **222** can be provided. The illustrated configuration provides for adjustability between discrete and predetermined sizes for the crown strap assembly **130**. In some configurations, three or four sizes can be provided.

[0101] With reference to FIG. **34**, a further adjustment mechanism **136** is illustrated. In the illustrated configuration, the first portion **132** includes a loop **152** that defines a passageway. The second portion **134** can extend into the passageway defined by the loop **152**. In the illustrated configuration, the loop **152** can include a tang **232**, tab or the like. The tang **232** can extend into the passageway defined by the loop **152**. The tang **232** is deflectable and, together with a plurality of ridges or recesses **234**, can define a ratchet mechanism **236**. The ratchet mechanism **236** can resist expansion of the crown strap assembly **130** while allowing adjustability to shorten the crown strap assembly **130**. In some configurations, with enough force applied to the first portion **132** and the second portion **134**, the crown strap assembly **130** can be lengthened by overpowering the ratchet mechanism **236**. In some configurations, a release can be provided to move the tang **232** and allow lengthening of the crown strap assembly **130**. Other configurations can be used keeping in mind a desire for a relatively secure adjustment mechanism, such as any suitable detent arrangement, for example.

[0102] The first portion **132** of the crown strap assembly **130** comprises a first bridge region **142** and a first strap region **144**. The second portion **134** of the crown strap assembly **130** similarly comprises a second bridge region **146** and a second strap region **148**. In some configurations, the first portion **132** and the second portion **134** are generally symmetrical to each other with the exception of the region that defines the adjustment mechanism **136**. Other configurations are possible.

[0103] The first strap region **144** comprises the apertures **138** and, as shown in FIG. **6**, may have

reduction in width somewhere along its length. In the illustrated configuration, the first strap region **144** comprises a tapering zone **150** such that a first width of the first strap region **144** is smaller than a second width of the first strap region **144** that is closer to the first bridge region **142**. The second strap region **148** comprises at least one loop **152**. In the illustrated configuration, the loop **152** is positioned at an end of the second strap region **148** furthest from the second bridge region **146**. The loop **152** serves to somewhat restrain the first strap region **144** at a location between the posts **140** of the second strap region **148** against significant movement away from the second strap region **148**.

[0104] In some configurations, the loop **152** defines a passage that has a width. The width of the passage is smaller than the second width of the first strap region **144** and larger than the first width of the first strap region **144**. In such configurations, the structure that defines the loop **152** serves to limit the degree to which the first strap region **144** can move along the second strap region **148**. Other configurations also are possible. In addition, the location of features on any strap region can be reversed such that elements shown on one strap region can be positioned on the other. For example, the loop **152** is shown on the second strap region **148** in FIG. 1A and the loop **152** is shown on the first strap region in FIGS. 21 and 22.

[0105] With continued reference to FIG. 10, the second strap region **148** comprises one or more ribs **154**. The illustrated ribs **154** are elongate members that extend along the lateral edge of at least a portion of the second strap region **148**. The illustrated ribs **154** extend to and connect with the loop **152**. The ribs **154** can taper such that a height of the ribs **154** reduces in a direction away from the loop **152**. The narrower portion of the first strap region **144** can fit between the ribs **154**. In some configurations, the ribs **154** in the region that will receive the first strap region **144** can be commensurate with the thickness of the first strap region **144**. By making the two commensurate, the top of the ribs **154** and the top surface of the first strap region **144** can be generally flush.

[0106] With continued reference to FIG. 10, the second bridge region **146** will be described. The first bridge region **142** is generally configured the same as the second bridge region **146**. In the illustrated configurations, the first and second bridge regions **142**, **146** are generally mirror images of each other. Other configurations are possible.

[0107] As described above, the illustrated crown strap assembly **130** is configured for use with a single main strap **114**. In some configurations, the main crown strap assembly **130** can be configured to connect with more than one main strap.

[0108] In the illustrated configurations, the second bridge region **146** defines a strap passage **156**. In some configurations, the passage **156** can be defined by three supporting components **158**. The supporting components **158** are spaced apart along a length of the second bridge region **146**. In some configurations, two of the three supporting components **158** are configured to secure the main strap **114** against significant upward movement relative to the second bridge region **146** while the third of the three supporting components **158** is configured to secure the main strap **114** against significant downward movement relative to the second bridge region **146**. In some configurations, all three of the supporting components **158** are configured to secure the main strap against significant downward movement relative to the second bridge region **146**.

[0109] With continued reference to FIG. 10, at least two of the three supporting components **158** can define interrupted loops **160**. The interrupted loops **160** can include a slotted gap or the like. In the illustrated configuration, the slotted gap or the like can be positioned along an upper portion of the associated loop **160**. Each slotted gap can be sized and configured to allow threading of the main strap **114** into the corresponding loop **160**. In the illustrated configuration, the loops **160** are flattened loops with two shorter ends connected to two longer ends and the slotted gap is positioned along one of the two longer ends while the other of the longer ends is defined by a main body **162** of the second strap region **148**.

[0110] The main body **162** of the second bridge region **146** extends between the loops **160** and connects the loops **160** to the second strap region **148**. A lower lip **164** extends outward from a

lower portion of the main body **162**. The lower lip **164** can further resist downward movement of the main strap **114** relative to the second strap region **148**. The lower lip **164** can extend outward away from the main body **162** to a degree that generally is commensurate with the outer surface of the loops **160** such that the lower lip **164** and the loops are generally flush with each other. The lower lip **164** can extend between the supporting components **158** and, in some configurations, can fill the spaces between the supporting components **158**.

[0111] With continued reference to FIG. **10**, the main body **162** also defines one or more apertures **166**. In the illustrated configuration, the aperture **166** is positioned generally equidistantly to the two ends of the second strap region **148**. In some configurations, the aperture **166** is positioned generally equidistantly to the two ends of the main body **162**. The aperture **166** can be positioned in the junction between the second strap region **148** and the second bridge region **146**. Other configurations are possible.

[0112] In the illustrated configuration, the medial member **168** of the three supporting components **158** can at least partially overlap with the aperture **166**. In the illustrated configuration, the medial member **168** is positioned fully within a region defined as an extension of the outer bound of the aperture **166** (see FIG. **11**). In some configurations, the medial member **168** is positioned such that at least a portion of the aperture extends further toward the ends of the second bridge region **146** relative to the ends of the medial member **168**. The medial member **168** can extend upward away from the lower lip **164**. The medial member **168** can extend upward away from the lower lip **164** a distance that is at least about one-half of a height of the main strap **114**.

[0113] In some configurations, such as that shown in FIG. **20**, at least one of the bridge region **142**, **146** and the associated strap region **144**, **148** includes a second medial member **174**. The second medial member **174** can be positioned vertical higher than the medial member **168**. In some configurations, the second medial member **174** can be positioned vertically above the medial member **168**. In some configurations, the second medial member **174** can be sized and configured identically or substantially identically to the medial member **168**.

[0114] In some configurations, the second medial member **174** can define a strap-accommodating passage between the second medial member **174** and the at least one of the bridge region **142**, **146** and the associated strap region **144**, **148**. The second medial member **174** advantageously provides further adjustability for the headgear assembly **104**. The strap **114** can be supported by one of the medial member **168** or the second medial member **174**. By moving the strap **114** to the second medial member **174** from the medial member **168**, the strap **114** can be effectively shortened. While the illustrated configuration illustrates two medial members **168**, **174** on each side of the headgear assembly **104**, more than two medial members can be provided on one or both sides of the headgear assembly **104**.

[0115] In the illustrated configuration, the second bridge region **146** arcs upward. In other words, as shown in FIG. **11**, a central region **170** is vertically higher than ends **172** of the second bridge region **146**. In the illustrated configuration, uppermost portions of the ends **172** are positioned lower than a lowermost portion of the central region **170**. The second bridge region **146** can be configured such that the top of the ear can be bypassed while maintaining a desired headgear vector for the interface **102** being supported by the headgear. Such an example is illustrated in FIG. **16**, for example but without limitation. Moreover, the elongated main body **162** provides arms that reduce pivotal movement of the main strap **114** and the vertical extent of the main body **162** combined with the three supporting components can minimize twisting in the main strap **114**. Other configurations are possible.

[0116] In use, the main strap **114** can be threaded through the slots in the loops **160** and slid into a gap defined between the medial member **168** and the main body **162** such that the main strap **114** is positioned within the loops **160** and supported by the combination of the main body **162** and the medial member **168**. Such a configuration is shown in FIGS. **1-9**. In this manner, the user of the headgear can adjust the headgear to a desired configuration by adding the strap, removing the strap

or resizing the strap.

[0117] With reference to FIGS. **23-33**, another configuration for the bridge regions will be described. As illustrated, the headgear assembly **104** comprises the crown strap assembly **130**. The crown strap assembly **130** includes the first portion **132** and the second portion **134** that can be secured together in any suitable manner. However, as described above, the crown strap **130** can be a single member or otherwise fixed in length. In the illustrated arrangement, the first portion **132** includes the first bridge region **142** and the first strap region **144**. The second portion **132** includes the second bridge region **146** and the second strap region **148**. Each of these components can be configured in accordance with any of the description herein.

[0118] The first bridge region **142** and the second bridge region **146** can be the same as each other or can be different from each other. In the illustrated configuration, the first and second bridge regions **142**, **146** are mirror images of each other. As such, only one will be described but the description applies to each.

[0119] The illustrated bridge region **142**, **146** defines a passageway that accommodates the strap **114**. In some configurations, the passageway is linear. In some configurations, the passageway includes a bend. In some configurations, the passageway includes two linear portions that are connected with a bend.

[0120] In the illustrated configuration, the bridge region **142** comprises an inner wall **240** and an outer wall **242** that are connected together. The inner wall **240** and the outer wall **242** generally combine to define a loop that defines the passageway. The inner wall **240** preferably is an extension of the strap region **144**, **148** because the inner wall **240** will be adjacent to the head of the user in use.

[0121] At least a portion of the loop is interrupted to define an insertion path for the strap **114**. In the illustrated configuration, the outer wall **242** includes a slot **244** that interrupts the outer wall **242**. The slot **244** is sized, positioned and configured to allow the strap **114** to be threaded into position within the passageway. The slot **244** can be generally straight or horizontal. In some configurations, the slot **244** can be slightly arcuate. In some configurations, the slot **244** can be slightly arcuate with a higher mid-portion than the outer portions. In some configurations, the inner wall may be interrupted. In some configurations, an upper or lower portion of the loop may be interrupted. However, by interrupting the inner wall **240** or the outer wall **242**, the slot **244** can be positioned along the longer surface of the strap while also allowing the strap **114** to be secured in the vertical directions (i.e., up and down along the user's head).

[0122] With reference now to FIG. **33**, the outer wall **242**, as a result of the slot **244**, includes an upper portion **246** and a lower portion **248** in the illustrated configuration. In some configurations, the upper portion **246** is slightly less open than the lower portion **248**. In other words, the distance between the outer wall **242** and the inner wall **240** is greater at the lower portion **248** than at the upper portion **246**. Moreover, in the illustrated configuration, the gap that defines the passageway for the strap **114** is larger at the lower portion **248** than at the upper portion **246**. Such a configuration assists in assembly of the strap **114** into the slot **244** and/or help in retention of the strap **114** within the slot **244**.

[0123] With reference now to FIGS. **34-45**, a further configuration for the bridge regions will be described. As illustrated, the headgear assembly **104** comprises the crown strap assembly **130**. The crown strap assembly **130** includes the first portion **132** and the second portion **134** that can be secured together in any suitable manner. The first portion **132** includes the first bridge region **142** and the first strap region **144**. The second portion **132** includes the second bridge region **146** and the second strap region **148**. Each of these components can be configured in accordance with any of the description herein.

[0124] The first bridge region **142** and the second bridge region **146** can be the same as each other or can be different from each other. In the illustrated configuration, the first and second bridge regions **142**, **146** are mirror images of each other. As such, only one will be described but the

description applies to each.

[0125] The illustrated bridge region **142**, **146** defines a passageway that accommodates the strap **114**. The passageway in the arrangement shown in FIGS. **34-45** differs from the passageways described above. In the arrangement shown in FIGS. **34-45**, the passageway is defined by two generally vertical slots **260** (see FIG. **42**). The two slots **260** are defined by two outer posts **262** and an intermediate portion **264**. The strap **114** can be threaded through the slots **260**, which allows adjustment of the location of the crown strap assembly **130** along the strap **114**.

[0126] In the illustrated configuration, the outer posts **262** are connected to each other. The outer posts **262** can be connected with an upper member **266** and a lower member **268**. The outer posts **262**, upper member **266** and lower member **268** can define a frame into which the strap **114** threads. The frame can be a complete (i.e., gapless) frame. As such, the intermediate portion **264** can be interrupted to enable insertion of the strap **114**. In some configurations, one or more of the posts **262** can be interrupted. In some configurations, one or more of the upper member **266** and the lower member **268** can be interrupted. In the illustrated configuration, the intermediate portion **264** is separated into two components by a slot or gap **270**. In some configurations, the gap **270** can be positioned such that a single intermediate member is formed. In the illustrated configuration, the gap **270** is positioned such that two intermediate members **272**, **274** are formed. In the illustrated configuration, the gap **270** is positioned such that two intermediate members **272**, **274** having approximately the same length are formed. Such a configuration is desired for providing a secure connection with the strap **114**. Moreover, as shown in FIG. **44**, the two intermediate member **272**, **274** can have different shapes such that insertion of the strap **114** is made easier. For example, one member may be slightly splayed open relative to the other member, similar to the arrangement illustrated in FIG. **33**, for example. In the illustrated configuration, the lower member **274** is splayed open slightly more than the upper member **272**. Other configurations are possible.

[0127] With reference to FIG. **43**, the intermediate members **272**, **274** can protrude inwardly. In other words, the intermediate members **272**, **274** can protrude toward the head of the user in use relative to the outer posts **262**, for example. As shown in FIG. **44**, the intermediate members **272**, **274** can protrude toward the user yet still overlap with the outer posts **262**. In some configurations, the intermediate members **272**, **274** can be flush with the outer posts **262** on a user-side surface. In some configurations, the intermediate members **272**, **274** can protrude outwardly from the outer posts **262** (i.e., away from the user in use). The illustrated configuration facilitates insertion of the strap **114** through the gap **270** and into position relative to the intermediate portion **264**.

[0128] Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise”, “comprising”, and the like, are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense, that is to say, in the sense of “including, but not limited to”.

[0129] Reference to any prior art in this specification is not, and should not be taken as, an acknowledgement or any form of suggestion that that prior art forms part of the common general knowledge in the field of endeavor in any country in the world.

[0130] The invention may also be said broadly to consist in the parts, elements and features referred to or indicated in the specification of the application, individually or collectively, in any or all combinations of two or more of said parts, elements or features.

[0131] Where, in the foregoing description reference has been made to integers or components having known equivalents thereof, those integers are herein incorporated as if individually set forth.

[0132] It should be noted that various changes and modifications to the presently preferred embodiments described herein will be apparent to those skilled in the art. Such changes and modifications may be made without departing from the spirit and scope of the invention and without diminishing its attendant advantages. For instance, various components may be repositioned as desired. It is therefore intended that such changes and modifications be included within the scope of the invention. Moreover, not all of the features, aspects and advantages are

necessarily required to practice the present invention. Accordingly, the scope of the present invention is intended to be defined only by the claims that follow.

Claims

1. (canceled)
 2. A headgear assembly, comprising a main strap, the main strap comprising a first end and a second end, wherein each of the first end and the second end is connected to a corresponding one of a first hook and a second hook, wherein each of the first hook and the second hook is configured to connect to an interface, and wherein at least one of the first hook and the second hook is an adjustable hook member that allows a length of the main strap to be adjusted through a telescoping mechanism, wherein the telescoping mechanism comprises an outer sleeve member and an inner arm, and wherein the telescoping mechanism is configured such that squeezing the outer sleeve member permits the inner arm to translate relative to the outer sleeve member.
 3. The headgear assembly of claim 2, wherein each of the first hook and the second hook is an adjustable hook member that allows the length of the main strap to be adjusted through a telescoping mechanism.
 4. The headgear assembly of claim 2, wherein the outer sleeve member is secured to the main strap and the inner arm is secured to a hook element.
 5. The headgear assembly of claim 2, wherein the outer sleeve member defines an inner passage.
 6. The headgear assembly of claim 5, wherein the inner passage includes one of one or more ridges or one or more recesses.
 7. The headgear assembly of claim 6, wherein the inner arm includes the other of the one or more ridges or the one or more recesses.
 8. The headgear assembly of claim 7, wherein the outer sleeve member is configured to be squeezed in a direction that is perpendicular to the one of the one or more ridges and the one or more recesses, such that squeezing the outer sleeve member results in movement of a portion of the outer sleeve member away from the inner arm.
 9. The headgear assembly of claim 7, wherein the telescoping mechanism provides a plurality of set points depending upon a distance between the one or more ridges and the one or more recesses.
 10. The headgear assembly of claim 2, wherein each of the first hook and the second hook is configured to join to a post on a mask frame of the interface to connect the headgear assembly to the mask frame.
 11. The headgear assembly of claim 2, wherein the headgear assembly further comprises a crown strap assembly.
 12. The headgear assembly of claim 11, wherein the crown strap assembly is detachable from the main strap.
 13. The headgear assembly of claim 12, wherein the crown strap assembly comprises a first portion and a second portion adjustably connected to one another.
 14. The headgear assembly of claim 2, wherein the main strap is formed of a stretchable material.
 15. The headgear assembly of claim 14, wherein the main strap comprises a tubular-knitted elastic strap.
 16. The headgear assembly of claim 2, further comprising a sleeve on the main strap between the first end and the second end of the main strap.
 17. The headgear assembly of claim 16, wherein a contact surface of the sleeve that contacts a user in use comprises grip-enhancing features.
-