

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282058

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

HAN; Yoojun et al.

CONNECTION STRUCTURE

Abstract

An embodiment of the present disclosure relates to a connection structure for connecting a robot arm capable of three-axis movement and a dispensing module for dispensing a solution in a predetermined amount. The connection structure includes: a first member including a robot arm connection part and a first shaft connection part; a second member coupled to the robot arm connection part by a main shaft, which includes a dispensing module connection part and a second shaft connection part; and a tilting member coupled to the first shaft connection part and the second shaft connection part. The tilting member is configured to tilt the second member at a predetermined angle with respect to the first member during solution dispensing, and moves at an angle about the first shaft while pushing the second shaft. The second member is pushed by the tilting member to move at an angle about the main shaft.

Inventors: HAN; Yoojun (Anyang-si, Gyeonggi-do, KR), CHO; Deog Pill (Seoul, KR), JEONG; Won-Seok (Seoul, KR), LIM; Hyun-jin (Seoul, KR)

Applicant: SEEGENE, INC. (Seoul, KR)

Family ID: 88519352

Assignee: SEEGENE, INC. (Seoul, KR)

Appl. No.: 18/860242

Filed (or PCT Filed): April 19, 2023

PCT No.: PCT/KR2023/005309

Foreign Application Priority Data

KR 10-2022-0051994

Apr. 27, 2022

Publication Classification

Int. Cl.: B25J15/00 (20060101); **B25J9/14** (20060101); **B25J17/02** (20060101)

U.S. Cl.:

CPC B25J15/0019 (20130101); **B25J9/144** (20130101); **B25J17/0241** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is the U.S. national phase of International Application No. PCT/KR2023/005309, filed on Apr. 19, 2023, which claims priority to Korean Patent Application No. 10-2022-0051994, filed on Apr. 27, 2022, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0002] The present disclosure relates to a connection structure for connecting a dispensing module to a robot arm.

BACKGROUND OF THE INVENTION

[0003] One type of molecular diagnostic kit product involves putting various reagents required for nucleic acid isolation and detection into tubes, which are then boxed and sold. In order to manufacture such a product, a process is required in which bulk reagents are divided into individual tubes and dispensed in small amounts using a dispensing module.

[0004] Here, the dispensing module is a device configured to accurately quantify and dispense a small amount of a solution of 1 ml or less into a tube, a well plate, or the like. When a small amount of solution is dispensed vertically into a tube using the dispensing module, liquid droplets may splatter and scatter or bubbles may be formed. Since the amount of reagent dispensed into each individual tube is quite small, the loss of liquid droplets can have a significant effect on the total remaining amount of reagent in the tube. Therefore, it is preferable to incline the tube or the pipette of the dispensing module, allowing the solution to flow along the wall of the tube.

[0005] In this case, while it is possible to tilt the pipette when automatically dispensing the solution using a robot arm capable of rotational movement, it is inefficient to use such an expensive robot arm solely to implement the tilting operation.

[0006] In addition, when dispensing is performed using an orthogonal robot arm with limited movement along the X, Y, and Z axes, it is not possible to tilt the pipette, and thus a separate operation is required to precisely adjust the pipette or tilt the tube during solution dispensing. However, in this case, the operation speed slows down, making it unsuitable for application in a product production process.

SUMMARY OF THE INVENTION

[0007] In this background, the present disclosure provides a connection structure configured to implement a tilting function of a dispensing module while connecting the dispensing module to an orthogonal robot arm.

[0008] To achieve these and other advantages and in accordance with the purpose of the present disclosure, there is provided a connection structure for connecting a robot arm capable of three-axis movement and a dispensing module for dispensing a solution in a predetermined amount, the connection structure including: a first member including a robot arm connection part connected to the robot arm and a first shaft connection part protruding from the robot arm connection part in a first direction; a second member coupled to the robot arm connection part by a main shaft, the second member including a dispensing module connection part connected to the dispensing module and a second shaft connection part protruding from the dispensing module connection part in the

first direction; and a tilting member having one end coupled to the first shaft connection part by a first shaft and the other end coupled to the second shaft connection part by a second shaft, the tilting member configured to tilt the second member by a predetermined angle with respect to the first member during solution dispensing, wherein the tilting member is configured to move at an angle about the first shaft while pushing the second shaft, and the second member is configured to be pushed by the tilting member to move at an angle about the main shaft.

[0009] In an embodiment of the present disclosure, the tilting member may be a connection structure including: a cover coupled to the first shaft connection part by the first shaft such that an upper portion of the tilting member is spaced apart from a lower portion of the first shaft connection part by a predetermined distance; a housing coupled to the cover and having a hollow inner space formed therein; and a piston configured to separate the inner space into an upper space and a lower space and moves in the direction of the lower space or the upper space based on air pressure injected into the upper space or the lower space, wherein when air pressure is applied to the upper space, the piston is configured to move in the direction of the lower space to push the second shaft so as to tilt the second member with respect to the first member, and when air pressure is applied to the lower space, the piston is configured to move in the direction of the upper space to pull the second shaft to restore the second member with respect to the first member.

[0010] In an embodiment of the present disclosure, the piston may be a connection structure including: a piston body configured to separate the inner space of the housing into the upper space and the lower space; and a piston rod having one end coupled to the piston body and the other end extending outside the housing to be coupled to the second shaft connection part by the second shaft.

[0011] In an embodiment of the present disclosure, the connection structure may further include at least one tilt angle adjustment member disposed to pass through the first shaft connection part and may include an upper protruding portion protruding upward from the first shaft connection part and a lower protruding portion protruding downward from the first shaft connection part, wherein the lower protruding portion is configured to contact a top surface of the cover to restrict a tilting angle of the tilting member and the second member when the tilting member operates.

[0012] In an embodiment of the present disclosure, the tilt angle adjustment member may further include an adjustment element configured to adjust a protrusion length of the lower protruding portion as the adjustment element engages with the upper protruding portion.

[0013] In an embodiment of the present disclosure, an angle at which the second member is tilted with respect to the first member may be greater than 0° and less than or equal to 10° .

[0014] In an embodiment of the present disclosure, the first member may have an insertion groove through which the robot arm is inserted and coupled.

[0015] In an embodiment of the present disclosure, an end portion of the lower protruding portion may have a rounded shape.

[0016] In an embodiment of the present disclosure, the cover may include a seating portion having a groove or hole shape, which contacts the end portion of the lower protruding portion during the operation of the tilting member.

[0017] According to an aspect of the present disclosure, the connection structure of the present disclosure may implement a tilting operation of the dispensing module with a simple structure while using an orthogonal robot arm capable of moving along the X, Y, and Z axes.

[0018] In addition, the connection structure enables high-speed control of the tilting operation of the dispensing module by implementing a tilting operation by employing a piston structure that reciprocates between two predetermined points.

[0019] Furthermore, the connection structure has a function that allows fine adjustment of the tilting angle of the dispensing module, so that the dispensing module may be tilted at various angles depending on the situation.

[0020] It should be understood that the effects of the present disclosure are not limited to those

described above, and include all effects that can be inferred from the configuration of the invention as described in the detailed description or the claims of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] FIG. 1 is a perspective view illustrating a state in which a dispensing module is connected to a robot arm by using a connection structure according to an embodiment of the present disclosure.

[0022] FIG. 2 is an exploded view illustrating a state in which the connection structure, the robot arm, and the dispensing module according to an embodiment of the present disclosure are disassembled.

[0023] FIG. 3 is a perspective view of a connection structure according to an embodiment of the present disclosure, as viewed from one direction.

[0024] FIG. 4 is a perspective view of a connection structure according to an embodiment of the present disclosure, as viewed from another direction.

[0025] FIG. 5 is an exploded view of a connection structure according to an embodiment of the present disclosure.

[0026] FIG. 6 is an exploded view of a tilting member according to an embodiment of the present disclosure.

[0027] FIG. 7 is a partially enlarged view of FIG. 4 according to an embodiment of the present disclosure.

[0028] FIGS. 8(a) and 8(b) are views illustrating the operation of the tilting member before and after activation, respectively, according to the embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE INVENTION

[0029] Hereinafter, the present disclosure will be described in detail with reference to an embodiment and exemplary drawings. These embodiments are provided only for more specifically describing the present disclosure, and it will be apparent to those skilled in the art that the scope of the present disclosure is not limited by these embodiments according to the gist of the present disclosure.

[0030] In addition, in assigning reference numerals to components in each drawing, it should be noted that the same components are denoted by the same reference numerals as possible, even if they are illustrated in different drawings. Moreover, in describing the present disclosure, when it is determined that a detailed description of a related known configuration or function may obscure the gist of the present disclosure, the detailed description thereof will be omitted.

[0031] In addition, in describing the components of the present disclosure, terms such as first, second, A, B, (a), (b), (i), (ii), and the like may be used. Such terms are only for distinguishing the components from other components, and are not intended to limit the essence, sequence, or order of the respective components. When a component is described as being “connected”, “coupled”, or “linked” to another component, it can be understood that the component may be directly connected or linked to the other component, however, it can also be understood that another component may be “connected”, “coupled”, or “linked” between each of the components.

[0032] Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings.

[0033] FIG. 1 is a perspective view illustrating a state in which a dispensing module is connected to a robot arm by using a connection structure according to an embodiment of the present disclosure, and FIG. 2 is an exploded view illustrating a state in which the connection structure, the robot arm, and the dispensing module according to an embodiment of the present disclosure are disassembled.

[0034] As shown in FIGS. 1 and 2, the present disclosure relates to a connection structure **10** for connecting a dispensing module **30** to a robot arm **20**. More specifically, the present invention may be a connection structure **10** configured to connect the dispensing module **30** to the robot arm **20** and implement a tilting function of the dispensing module **30** with a simple structure.

[0035] Here, the robot arm **20** may be an orthogonal robot arm capable of three-axis movement along the X, Y, and Z axes. In addition, the dispensing module **30** may be a device configured to accurately quantify a small amount of a solution of **1 ml** or less and dispense the quantified solution to a tube, a well plate, or the like. At this time, a plurality of pipettes for the aspiration or dispensing of a solution such as a liquid reagent, a sample, or the like may be mounted on the dispensing module **30**, and the dispensing module **30** may be configured to aspirate or dispense the solution to the plurality of tubes simultaneously or sequentially using the plurality of pipettes.

[0036] FIG. 3 is a perspective view of a connection structure according to an embodiment of the present disclosure, as viewed from one direction, FIG. 4 is a perspective view of the connection structure according to an embodiment of the present disclosure, as viewed from another direction, FIG. 5 is an exploded view of the connection structure according to an embodiment of the present disclosure, and FIG. 6 is an exploded view of a tilting member according to an embodiment of the present disclosure.

[0037] Referring to FIGS. 1 to 6, a connection structure **10** of the present disclosure includes a first member **100**, a second member **200**, and a tilting member **300**.

[0038] A robot arm **20** is connected to the first member **100**. In addition, the first member **100** is axially coupled to each of the second member **200** and the tilting member **300**. The dispensing module **30** may be detachably connected to the second member **200**.

[0039] More specifically, the first member **100** is configured to include a robot arm connection part **110** axially coupled to the second member **200**, and a first shaft connection part **120** axially coupled to the tilting member **300**. At this time, the robot arm connection part **110** and the first shaft connection part **120** may be integrally formed, or may be formed in a manner where separate components are coupled together.

[0040] An insertion groove **111** through which an insertion protrusion of the robot arm **20** is inserted and coupled may be formed at an upper portion of the robot arm connection part **110**. The robot arm connection part **110** may be coupled to the second member **200** in a downward direction by the main shaft X1.

[0041] The first shaft connection part **120** may protrude from the robot arm connection part **110** in a first direction, and may be coupled to the tilting member **300** in the downward direction by the first shaft X2. The first direction may be a direction perpendicular to the main shaft X1. In order to tilt the second member **200** with respect to the first member **100** about the main shaft X1, the first shaft connection part **120** and the second shaft connection part **220** axially coupled to the tilting member **300** may protrude in a direction perpendicular to the main shaft X1. In addition, in order to avoid interference with the dispensing module **30** coupled to the dispensing module connection part **210** of the second member **200**, the first shaft connection part **120** and the second shaft connection part **220** may protrude in a direction opposite to the direction in which the dispensing module **30** is coupled to the dispensing module connection part **210**.

[0042] The dispensing module **30** is detachably connected to the second member **200**. In addition, the second member **200** is axially coupled to each of the first member **100** and the tilting member **300**.

[0043] More specifically, the second member **200** includes a dispensing module connection part **210** axially coupled to the first member **100**, and a second shaft connection part **220** axially coupled to the tilting member **300**. At this time, the dispensing module connection part **210** and the second shaft connection part **220** may be integrally formed, or may be formed in a manner where separate components are coupled together.

[0044] The dispensing module connection part **210** may be formed in a substantially plate shape so

as to be coupled to the dispensing module **30** in a surface-to-surface manner. At this time, various coupling methods such as screw coupling, adhesion, and the like may be applied to the coupling between the dispensing module connection part **210** and the dispensing module **30**. The dispensing module connection part **210** may be coupled to the first member **100** in an upward direction by the main shaft **X1**.

[0045] The second shaft connection part **220** may protrude from the dispensing module connection part **210** in the first direction, and may be coupled to the tilting member **300** in the upward direction by the first shaft **X2**. The first direction in which the second shaft connection part **220** protrudes, is the same direction in which the first shaft connection part **120** protrudes from the robot arm connection part **110**. In other words, the first shaft connection part **120** and the second shaft connection part **220** protrude in the same direction and are coupled to the tilting member **300**.

[0046] The tilting member **300** is axially coupled to each of the first member **100** and the second member **200**. At this time, the tilting member **300** is configured to tilt the second member **200** by a predetermined angle with respect to the first member **100** during solution dispensing. That is, the tilting member **300** functions to tilt the dispensing module **30** connected to the second member **200** during the solution dispensing so that the solution in the pipette flows along the inner wall of the tube. Here, the tilting operation may be a slant movement, which refers to an operation that involves a slight degree of inclination.

[0047] The upper end of the tilting member **300** is coupled to the first shaft connection part **120** by the first shaft **X2**, and the lower end of the tilting member **300** is coupled to the second shaft connection part **220** by the second shaft **X3**. That is, the tilting member **300** may be positioned between the first shaft connection part **120** and the second shaft connection part **220**. The tilting member **300** extends in the downward direction during the operation, and accordingly, is moved at an angle about the first shaft **X2** while pushing the second shaft **X3**. Further, the second member **200** is pushed by the tilting member **300** to be moved at an angle about the main shaft **X1**.

[0048] The main shaft **X1**, the first shaft **X2**, and the second shaft **X3** may be disposed parallel to each other. As described above, since the first member **100**, the second member **200**, and the tilting member **300** are connected to each other through the main shaft **X1**, the first shaft **X2**, and the second shaft **X3** that are parallel to each other, it is possible for the second member **200** and the tilting member **300** to move at an angle with respect to the fixed first member **100** during the operation of the tilting member **300**.

[0049] Meanwhile, referring to FIGS. 5 and 6, the tilting member **300** includes a cover **310**, a housing **320**, a piston **330**, and an air injection port **340**.

[0050] The cover **310** may be coupled to the first shaft connection part **120** by the first shaft **X2** through a pair of extended portions **312** such that a top surface of the cover **310** is spaced apart from a lower portion of the first shaft connection part **120** by a predetermined distance.

[0051] The housing **320** may be coupled to the cover **310** at a lower side of the cover **310**, and may have a hollow inner space. In addition, communication holes **323a** and **323b** may be formed in the housing **320** so that air may be introduced into the inner space or air may be discharged from the inner space.

[0052] Meanwhile, the piston **330** may be provided in the inner space of the housing **320**.

[0053] The piston **330** separates the inner space of the housing **320** into an upper space **321** and a lower space **322**, and one end of the piston **330** is connected to the second member **200**, more specifically, the second shaft connection part **220** through the second shaft **X3**. At this time, the piston **330** moves upward or downward due to the pressure of the air, that is, air pressure injected into the upper space **321** or the lower space **322**.

[0054] The upper injection port **340a** is connected to the upper communication hole **323a** to apply air pressure to the upper space **321** of the housing **320**, and the lower injection port **340b** is connected to the lower communication hole **323b** to apply air pressure to the lower space **322** of the housing **320**.

[0055] In other words, when air pressure is applied to the upper space **321**, the piston **330** pushes the second shaft **X3** while moving downward, that is, in the direction of the lower space, thereby tilting the second member **200** with respect to the first member **100**. In addition, when air pressure is applied to the lower space **322**, the piston **330** moves upward, that is, in the direction of the upper space, and pulls the second shaft **X3** to restore the second member **200** with respect to the first member **100**.

[0056] Meanwhile, the piston **330** includes a piston body **331** and a piston rod **332**.

[0057] The piston body **331** separates the inner space of the housing **320** into the upper space **321** and the lower space **322**, and moves upward or downward by the air pressure applied to the inner space. At this time, the piston body **331** may be formed in a shape corresponding to a cross-sectional shape of the inner space of the housing **320**.

[0058] The piston rod **332** may have one end coupled to the piston body **331** and the other end extending outside the housing **320** to be coupled to the second shaft connection part **220** by the second shaft **X3**. That is, depending on the movement of the piston body **331** due to the air pressure, the piston rod **332** tilts the second member **200** while pushing the second shaft **X3** or pulling the second shaft **X3**.

[0059] As described above, in the present disclosure, the pneumatic cylinder structure is applied to the tilting member **300** to move the second shaft **X3**, but the present disclosure is not limited thereto, and other cylinder structures that can move the second shaft **X3**, aside from air pressure, may also be applied.

[0060] FIG. **7** is a partially enlarged view of FIG. **4** according to an embodiment of the present disclosure, and FIGS. **8(a)** and **8(b)** are views illustrating the operation of the tilting member before and after activation, respectively, according to an embodiment of the present disclosure.

[0061] Referring to FIGS. **6** to **8**, the connection structure **10** of the present disclosure may further include one or more tilt angle adjustment members **400**. The tilt angle adjustment member **400** is disposed to vertically pass through the first shaft connection part **120** of the first member **100**, and is configured to restrict the tilting angle of the second member **200** with respect to the first member **100** during the operation of the tilting member **300**.

[0062] At this time, the tilt angle adjustment member **400** includes a first tilt angle adjustment member **400a** that restricts the tilting angle when the piston rod **332** tilts the second member **200** while pushing the second shaft **X3**. In addition, the tilt angle adjustment member **400** includes a second tilt angle adjustment member **400b** that restricts the restoring angle when the piston rod **332** pulls the second shaft **X3** to restore the second member **200**.

[0063] The first tilt angle adjustment member **400a** may be disposed at a proximal side from the robot arm connection part **110**, and the second tilt angle adjustment member **400b** may be disposed at a distal side from the robot arm connection part **110**.

[0064] Meanwhile, the first tilt angle adjustment member **400a** may include a first pass-through element **410a** having a rod shape and vertically passing through the first shaft connection part **120** and coupled to the first shaft connection part **120**. When the first pass-through element **410a** is coupled to the first shaft connection part **120**, an upper protruding portion **411a** protruding upward from the first shaft connection part **120** and a lower protruding portion **412a** protruding downward from the first shaft connection part **120** may be formed.

[0065] Here, when the piston rod **332** tilts the second member **200** while pushing the second shaft **X3**, the lower protruding portion **412a** comes into contact with the top surface of the cover **310** to restrict the tilting angle of the tilting member **300** and the second member **200** with respect to the first member **100**.

[0066] In addition, the first tilt angle adjustment member **400a** may include a first adjustment element **420a** that adjusts a protrusion length of the lower protruding portion **412a** as the first adjustment element **420a** is engaged with the upper protruding portion **411a**. That is, if the protrusion length of the lower protruding portion **412a** increases according to the degree of

adjustment of the first adjustment element **420a**, the moving range in which the cover **310** contacts the lower protruding portion **412a** decreases, and thus the tilting angle decreases. On the other hand, if the protrusion length of the lower protruding portion **412a** is reduced according to the degree of adjustment of the first adjustment element **420a**, the moving range in which the cover **310** is brought into contact with the lower protruding portion **412a** is increased, thereby increasing the tilting angle.

[0067] As described above, as the first pass-through element **410a** and the first adjustment element **420a** of the first tilt angle adjustment member **400a** are provided, the tilting angle of the second member **200** with respect to the first member **100** is controlled, which enables the tilting member **300** and the second member **200** to move at an angle. At this time, according to an embodiment, the angle at which the second member **200** is tilted with respect to the first member **100** may be set to be greater than 0° and less than or equal to 20°, and preferably, greater than 0° and less than or equal to 10°.

[0068] Meanwhile, the second tilt angle adjustment member **400b** may include a second pass-through element **410b** having a rod shape and vertically passing through the first shaft connection part **120** and coupled to the first shaft connection part **120**. When the second pass-through element **410b** is coupled to the first shaft connection part **120**, an upper protruding portion **411b** protruding upward from the first shaft connection part **120** and a lower protruding portion **412b** protruding downward from the first shaft connection part **120** may be formed.

[0069] Here, when the piston rod **332** pulls the second shaft **X3** to restore the second member **200**, the lower protruding portion **412b** comes into contact with the top surface of the cover **310** to restrict the restoring angle of the tilting member **300** and the second member **200** with respect to the first member **100**.

[0070] In addition, the second tilt angle adjustment member **400b** may include a second adjustment element **420b** that adjusts a protrusion length of the lower protruding portion **412b** as the second adjustment element **420b** is engaged with the upper protruding portion **411b**. That is, if the protrusion length of the lower protruding portion **412b** increases according to the degree of adjustment of the second adjustment element **420b**, the moving range in which the cover **310** contacts the lower protruding portion **412b** decreases, and thus, the restoring angle decreases. On the other hand, if the protrusion length of the lower protruding portion **412b** is reduced according to the degree of adjustment of the second adjustment element **420b**, the moving range in which the cover **310** is brought into contact with the lower protruding portion **412b** is increased, thereby increasing the restoring angle.

[0071] According to an embodiment, the end portions of the lower protruding portions **412a** and **412b** may have a downwardly convex rounded shape. In addition, a top surface of the cover **310** may be provided with a seating portion **311** having a groove or hole shape at a position where the lower protruding portions **412a** and **412b** come into contact. Accordingly, when the tilting member **300** operates and the lower protruding portions **412a** and **412b** come into contact with the cover **310**, it allows for an increase in the contact area to reduce the impact force.

[0072] As described above, the connection structure **10** of the present disclosure may implement the tilting operation of the dispensing module **30** with a simple structure while using the orthogonal robot arm **20** capable of moving in the X, Y, and Z axes.

[0073] In addition, the connection structure **10** enables high-speed control of the tilting operation of the dispensing module **30** by implementing a tilting operation by employing a piston structure that reciprocates between two predetermined points.

[0074] Furthermore, the connection structure **10** has a function that allows fine adjustment of the tilting angle of the dispensing module **30**, so that the dispensing module **30** may be tilted at various angles depending on the situation.

[0075] The above description of the present disclosure is for illustration, and those of ordinary skill in the art to which the present disclosure pertains will understand that the present disclosure can be

easily modified into other specific forms without changing the technical spirit or essential features of the present disclosure. Therefore, it should be understood that the embodiments described above are exemplary and not restrictive in all aspects. For example, each component described in a single form may be implemented separately, and likewise, components described as separate may be implemented in a combined form.

[0076] The scope of the present disclosure is indicated by the following claims, and it should be interpreted that all changes or modifications derived from the meaning and scope of claims and the equivalent concept thereof are included in the scope of the present disclosure.

Claims

1. A connection structure for connecting a robot arm capable of three-axis movement and a dispensing module for dispensing a solution in a predetermined amount, the connection structure comprising: a first member comprising a robot arm connection part connected to the robot arm and a first shaft connection part protruding from the robot arm connection part in a first direction; a second member coupled to the robot arm connection part by a main shaft, the second member comprising a dispensing module connection part connected to the dispensing module and a second shaft connection part protruding from the dispensing module connection part in the first direction; and a tilting member having one end coupled to the first shaft connection part by a first shaft and the other end coupled to the second shaft connection part by a second shaft, the tilting member configured to tilt the second member by a predetermined angle with respect to the first member during solution dispensing, wherein the tilting member is configured to move at an angle about the first shaft while pushing the second shaft, and the second member is configured to be pushed by the tilting member to move at an angle about the main shaft.
2. The connection structure of claim 1, wherein the tilting member comprises: a cover coupled to the first shaft connection part by the first shaft such that a top surface of the cover is spaced apart from a lower portion of the first shaft connection part by a predetermined distance; a housing coupled to the cover and having a hollow inner space formed therein; and a piston configured to separate the inner space into an upper space and a lower space and move in the direction of the lower space or the upper space based on air pressure injected into the upper space or the lower space, wherein when air pressure is applied to the upper space, the piston is configured to move in the direction of the lower space to push the second shaft to tilt the second member with respect to the first member, and when air pressure is applied to the lower space, the piston is configured to move in the direction of the upper space to pull the second shaft to restore the second member with respect to the first member.
3. The connection structure of claim 2, wherein the piston comprises: a piston body configured to separate the inner space of the housing into the upper space and the lower space; and a piston rod having one end coupled to the piston body and the other end extending outside the housing to be coupled to the second shaft connection part by the second shaft.
4. The connection structure of claim 2, further comprising at least one tilt angle adjustment member disposed to pass through the first shaft connection part and comprising an upper protruding portion protruding upward from the first shaft connection part and a lower protruding portion protruding downward from the first shaft connection part, wherein the lower protruding portion is configured to contact a top surface of the cover to restrict a tilting angle of the tilting member and the second member.
5. The connection structure of claim 4, wherein the tilt angle adjustment member further comprises an adjustment element configured to adjust a protrusion length of the lower protruding portion as the adjustment element engages with the upper protruding portion.
6. The connection structure of claim 1, wherein an angle at which the second member is tilted with respect to the first member is greater than 0° and less than or equal to 10°.

7. The connection structure of claim 1, wherein the first member has an insertion groove through which the robot arm is inserted and coupled.
8. The connection structure of claim 4, wherein an end portion of the lower protruding portion has a rounded shape.
9. The connection structure of claim 8, wherein the cover comprises a seating portion having a groove or hole shape, which contacts the end portion of the lower protruding portion during the operation of the tilting member.
-