

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283458

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Park; Myoung Chul

LONG-LIFE NON-CONTACT PUMP

Abstract

The inventive concept provides long-life non-contact pump including a pump cylinder having a certain pumping space, an inlet valve and an outlet valve respectively located at a part of the pump cylinder to prevent backflow of a fluid and to allow the fluid to flow in and out, a bellows provided in the pumping space of the pump cylinder and varying a volume of the pumping space to pump the fluid flowing in/out along the inlet and outlet, and a reciprocating drive unit provided on the outside of the cylinder cover to cause a reciprocating driving of the piston along the connected reciprocating rod. Accordingly, airtightness in a pumping operation without friction between parts may be maintained, the generation of foreign substances in the fluid due to friction may be prevented, and the replacement life of consumables may be improved.

Inventors: Park; Myoung Chul (Hwaseong-si,, KR)

Applicant: Park; Myoung Chul (Hwaseong-si,, KR)

Family ID: 78505124

Appl. No.: 18/274149

Filed (or PCT Filed): December 20, 2021

PCT No.: PCT/KR2021/019382

Foreign Application Priority Data

KR 10-2021-0012467

Jan. 28, 2021

Publication Classification

Int. Cl.: F04B43/00 (20060101); F04B43/107 (20060101)

U.S. Cl.:

Background/Summary

TECHNICAL FIELD

[0001] The disclosure relates to a non-contact pump, and more particularly, to a long-life non-contact pump capable of maintaining airtightness during a pumping operation without friction between parts, preventing the generation of foreign substances in a fluid due to friction, having improved lifespan and reducing replacement costs for consumables, increasing the operation rate of equipment, allowing replacement of consumables more easily, and capable of being applied in various industrial fields.

BACKGROUND ART

[0002] In general, as shown in FIG. 1, a piston reciprocating pump includes an inlet valve 1 for preventing backflow of a fluid at an inlet through which the fluid enters the pump; an outlet valve 2 for preventing backflow of the fluid from the outlet through which the fluid is discharged from the inside of the pump; a pump cylinder 3 having a space for accommodating the fluid inside the pump; a piston 4 that expands and contracts a space so that the fluid may enter and exit the pump cylinder 3; a sealing member 5 for sealing the pump cylinder 3 so that the fluid does not leak between the pump cylinder 3 and the piston 4; a sealing guide 6, a fluid injection container 7 for injecting a fluid to reduce wear of the sealing member 5; and a pumping drive unit 8 in which the piston 4 performs a reciprocating motion.

[0003] The piston reciprocating pump has a structure such that when a volume inside the pump cylinder 3 increases, a corresponding fluid enters the pump through the inlet valve 1, and when the volume inside the pump cylinder 3 decreases, the corresponding fluid is discharged to the outside of the piston reciprocating pump through the outlet valve 2.

[0004] In the case of an existing piston reciprocating pump, a material used for sealing is worn out by the reciprocating motion and friction between the piston 4 and the pump cylinder 3, and thus, the material should be replaced with a consumable after a certain number of operations.

[0005] Therefore, as the production capacity of equipment improves and the number of operations increases, the replacement cycle of related consumables is gradually shortened. Depending on the production capacity of the equipment, consumables are replaced once every 1 to 2 weeks on some production lines.

[0006] In other words, like the structure of a piston reciprocating pump, in a structure in which a gap between the pump cylinder 3 and the piston 4 is sealed so as not to allow the fluid to leak and the piston 4 reciprocates while rubbing the sealing member 5, it is necessary to make a surface where the piston 4 rubs the sealing member 5 more smooth or increase the replacement cycle of consumables by selecting a material with less frictional force and wear for the sealing member 5.

[0007] However, processing a contact surface and changing the sealing member 5 may have limitations in increasing the lifespan of consumables to several times or more in a structure in which materials undergo a friction operation.

[0008] In addition, as the replacement period is shortened, the frequency of replacing consumables by workers by stopping the equipment increases, which results in loss for a manufacturer, such as the increase in consumables costs, equipment downtime, and labor costs.

[0009] In addition, when consumables are replaced, there are many replacement works and parts to be replaced such as disassembling and lubricant injection into the sealing member 5, the sealing guide 6, and the fluid injection container 7, and in assembling the sealing member 5 and the sealing guide 6, if the sealing member 5 is damaged or not tightly assembled in a correct position, because

the skills of workers are different from each other, there may be a problem in that easiness of replacement work and maintenance may not be achieved.

[0010] In particular, Korean Registered Patent Publication No. 10-1449047 discloses that, in using a bellows material as a resin material, in order to prevent severe deformation of the bellows due to external pressure, the bellows includes an incompressible indirect medium including a fluid such as oil to maintain the pressure in the bellows.

[0011] That is, in using a resin-based fluid in a structure for pumping a small amount of fluid, deformation occurs when the fluid is compressed, and an incompressible medium must be filled for 48 hours to compensate for the deformation.

[0012] In addition, in order to apply an incompressible indirect medium inside the bellows, a configuration of a complicated structure is required, and thus, the manufacturing costs and product prices increase.

[0013] In addition, in a piston reciprocating pump, foreign substances may be generated due to friction of the sealing materials during the reciprocating operation, and there is a drawback in that the foreign substances may flow into the fluid. Thus, the piston reciprocating pump may have an improper structure for pumping fluids such as medical fluids or chemical fluids and maintain the purity thereof.

[0014] Therefore, due to the improvement of production capacity of the existing battery manufacturing process, the replacement cycle of consumables in related equipment is shortened, the cycles of stopping the operation of equipment and replacing consumables are shortened, and thus, equipment for addressing these problems is required.

DISCLOSURE

Technical Problem

[0015] In order to solve the above problems, the disclosure provides a long-life non-contact pump having a pump structure in which a bellows is applied, the long-life non-contact pump may maintain airtightness during pumping operations without friction between parts, prevent generation of foreign substances in a fluid by friction, reduce replacement costs by improving the lifespan of consumables, increase the operation rate of equipment, and replace consumables more easily than before, and may be applied to various industrial fields.

Technical Solution

[0016] According to an aspect of the disclosure, a long-life non-contact pump includes a pump cylinder having a certain pumping space for accommodating introduced fluid and intaking/discharging the fluid through a pumping operation along an inlet and an outlet formed on both sides thereof, the pump cylinder including an outlet valve that is provided on an outlet side and prevents backflow of the fluid when the fluid flows in along the inlet and an inlet valve that is provided on an inlet side and prevents backflow of the fluid when the fluid is discharged along the outlet, a bellows provided in the pumping space of the pump cylinder and varying a volume of the pumping space so as to pump the fluid flowing in/out along the inlet and outlet, a piston that closes one end of the bellows and moves together with the bellows, a reciprocating rod that is integrally connected to the piston and extends outward of the pump cylinder to expand and contract the bellows by reciprocally driving together with the movement of the piston, a cylinder cover that closes a part of the pump cylinder, and fixes the other end of the bellows, and through which the reciprocating rod passes, and a reciprocating drive unit provided on the outside of the cylinder cover to drive the piston reciprocally along the connected reciprocating rod.

[0017] Here, the bellows may include a first bellows pipe including rubber and having a vacuum space therein, a volume of which is variable to be expendable and contractable, and a second bellows pipe formed on the outside of the first bellows pipe and including a thin metal plate so that the rigidity of the first bellows pipe is maintained against repeated volume changes.

[0018] The cylinder cover may further include a vacuum line for forming a vacuum in the vacuum space formed inside the bellows.

[0019] The drain hole of the cylinder cover may further include a leak sensor coupled to the drain hole and configured to detect fluid entering the vacuum space when the bellows is damaged, to confirm the fluid entering the vacuum space from the outside, and to remove the entering fluid.

[0020] The long-life non-contact pump may further include, on a part of the pump cylinder, a temperature sensor configured to sense the temperature of the fluid flowing in/out of the pumping space by the pumping of the bellows.

[0021] The long-life non-contact pump may further include, on one part of the pump cylinder, a temperature sensor configured to sense the temperature of the fluid flowing in/out of the pumping space by the pumping of the bellows.

Advantageous Effects

[0022] The long-life non-contact pump having the configuration described above may have the following advantages.

[0023] First, in a pumping operation, there is an effect of improving the consumable replacement cycle by improving the structure of compression/expansion pumping operation using a metal bellows without friction between parts that maintain airtightness, so that the replacement cycle of consumables that are replaced every week or after several weeks in an existing pump is increased to few months.

[0024] Second, there is an effect of solving inconveniences by increasing the existing short consumable replacement cycle, reducing costs of loss due to consumable replacement, and increasing the operating rate of the pump.

[0025] Third, the number of consumables to be replaced is less compared to the existing pump, and the replacement method is simple and easy.

[0026] Fourth, the long-life non-contact pump may be readily applied to various industrial fields such as semiconductors, displays, and chemicals other than the battery manufacturing industry.

Description

DESCRIPTION OF DRAWINGS

[0027] FIG. 1 is a diagram showing a piston reciprocating pump of the related art; and

[0028] FIGS. 2 to 4 are diagrams showing configurations and operating states of a long-life non-contact pump according to an embodiment.

BEST MODE

[0029] Specific aspects and specific technical features of the inventive concept become more apparent from the following detailed description and examples taken in conjunction with the accompanying drawings. In the specification, in giving reference numerals to components of each drawing, it should be noted that like components have like numerals as much as possible even if they are displayed on different drawings.

[0030] In addition, in describing the embodiments of the inventive concept, when practical descriptions with respect to related known functions and configurations may unnecessarily make the scope of the inventive concept unclear, the descriptions thereof are omitted.

[0031] In addition, in describing the components of the inventive concept, terms are only used to distinguish one component from another component, and the nature, order, or order of the component are not limited by the terms. When a component is described as being “connected”, “coupled” or “connected” to another component, the component may be directly connected or connected to that other component, but another component between each component. It should be understood that elements may be “connected”, “coupled” or “connected”.

[0032] Hereinafter, an embodiment of the inventive concept will be described in detail with reference to the accompanying drawings.

[0033] As shown in FIGS. 2 to 4, a long-life non-contact pump of the inventive concept may be

configured by including a pump cylinder **100** configured to inject fluid (electrolyte or battery liquid) into a battery, a bellows **200** provided inside the pump cylinder **100** and configured to perform a pumping operation through compression and expansion, a reciprocating drive unit **400** configured to control the pumping operation of the bellows **200**, and a cylinder cover **300** that closes the pump cylinder **100** and the bellows **200** to prevent leakage of the battery liquid.

[0034] The pump cylinder **100** includes, on both sides thereof, an inlet **103** having an inlet valve **110** for introducing fluid and preventing backflow of the fluid, and an outlet **105** having an outlet valve **120** for discharging the fluid and preventing backflow of the fluid, and has a predetermined pumping space **101** in which the fluid is accommodated.

[0035] In other words, the pump cylinder **100** intakes/discharges fluid through the pumping operation along the inlet **103** and the outlet **105** formed on both sides thereof, includes the outlet valve **120** that is provided in the outlet **105** to prevent backflow of the discharging fluid when the fluid flows in through the inlet **103** and the inlet valve **110** that is provided in the inlet **103** to prevent the flow of fluid into the cylinder when the fluid is discharged through the outlet **105**, and the predetermined pumping space **101** in which the introduced fluid is accommodated.

[0036] In addition, the bellows **200** is provided in the predetermined pumping space **101** of the pump cylinder **100** to vary a volume of the predetermined pumping space **101** so that fluid is pumped to flow in/out through the inlet **103** and the outlet **105**.

[0037] That is, the bellows **200** may include a first bellows pipe **200a** including rubber and having a vacuum space **201** therein, a volume of which is variable, that is, expendable and contractable, and a second bellows pipe **200b** formed on the outside of the first bellows pipe **200a** by including a thin metal plate so that the rigidity of the first bellows pipe **200a** is maintained against repeated volume changes.

[0038] On the other hand, although the second bellows pipe **200b** includes a metal, if the second bellows pipe **200b** may be replaced with a material having the same elasticity and airtightness as the first bellows pipe **200a**, the bellows **200** may only be configured with the second bellows pipe **200b**.

[0039] At this time, in order to minimize stress caused by sufficient volume change and repetitive operation of the pumping space **101**, the second bellows pipe **200b** to which a thin metal plate welding bellows is applied may increase the effect of the sufficient volume of fluid and the repeated lifespan.

[0040] At this time, the bellows **200** may include the second bellows pipe **200b** that is stretchable and provided in the pumping space **101**, a piston **410** closing one end of the second bellows pipe **200b**, and a fixing flange **210** fixed to an inside of the cylinder cover **300** at the same time as closing the other end of the second bellows pipe **200b**.

[0041] That is, the piston **410** may move together with the bellows **200** by closing the one end of the bellows **200**.

[0042] In addition, a reciprocating rod **420** is integrally connected to the piston **410** and extends outward of the pump cylinder **100**, and thus, may vary the volume of the bellows **200** through reciprocating movement along with the moving of the piston **410**.

[0043] The cylinder cover **300** may be configured to close a part of the pump cylinder **100**, to fix the other end of the bellows **200**, and to pass the reciprocating rod **420** therethrough.

[0044] At this time, the cylinder cover **300** may further include a vacuum line **310** for forming a vacuum in the vacuum space **201** formed inside the bellows **200**.

[0045] In addition, the reciprocating drive unit **400** is provided outside the cylinder cover **300** to reciprocally drive the piston **410** along the connected reciprocating rod **420**. On the other hand, the reciprocating rod **420** is connected between the piston **410** of the bellows **200** and the reciprocating driving unit **400**, and one end of the reciprocating rod **420** is fixed on the piston **410** of the bellows **200** to vary the volume of the bellows **200**.

[0046] Then, the reciprocating drive unit **400** is coupled to the outside of the cylinder cover **300**,

and may reciprocally drive the piston **410** by connecting the reciprocating rod **420**.

[0047] A temperature sensor **130** that detects a temperature of fluid flowing in/out of the pumping space **101** may be included in one portion of the pump cylinder **100**.

[0048] Finally, a pressure sensor **140** that senses pressure of the fluid flowing in/out of the pumping space **101** may be included in one portion of the pump cylinder **100**.

[0049] That is, the inlet **103** through which fluid enters the pumping space **101** of the pump cylinder **100** and the inlet valve **110** preventing backflow of the fluid in the inlet **103** are provided on one side of the pump cylinder **100**, and the outlet **105** through which fluid is discharged from the pumping space **101** of the pump cylinder **100** and the outlet valve **120** preventing backflow of fluid into the outlet **105** are formed on the other side of the pump cylinder **100**, and thus, fluid may be continuously pumped and supplied to a battery.

[0050] The volume stretchable bellows **200** is provided so that fluid flows in/out of the pumping space **101** of the pump cylinder **100**, and to form a vacuum in the vacuum space **201** of the bellows **200**, the vacuum line **310** connecting an inside of the bellows **200** to the outside of the cylinder cover **300** with a hole of a certain size is formed.

[0051] At the center of the cylinder cover **300**, a rod guide **220** that is coupled to the reciprocating rod **420** by a bushing and guides precise reciprocating of the reciprocating rod **420** during a pumping operation of the bellows **200** may further be provided.

[0052] Here, the reciprocating rod **420** fixed to the piston **410** of the bellows **200** and reciprocally driven for expansion/contraction of the bellows **200** is sequentially configured, and the rod guide **220** that guides the reciprocating rod **420** to be able to reciprocate precisely is provided at the center of the cylinder cover **300**.

[0053] In the case when the bellows **200** is damaged due to the end of its service life, in order to detect fluid leaking into the vacuum space **201** of the bellows **200**, a leak sensor **330** may further be provided.

[0054] Here, the leak sensor **330** may be provided in the drain hole **320** of the cylinder cover **300** to remove fluid in the vacuum space **201** according to a detection signal of the leak sensor **330** by closing the drain hole **320** that discharges fluid entering the vacuum space **201** when the bellows **200** is damaged.

[0055] When the temperature of fluid to be pumped is changed, a discharge volume of the fluid is changed due to the change in the density of the fluid, and thus, the temperature sensor **130** may give an alarm by sensing the temperature or correct the volume change.

[0056] The pressure sensor **140** may measure and manage pressure of fluid in the pump cylinder **100** when intaking and discharging the fluid and manage optimal pumping conditions during intake and discharge of the fluid.

[0057] The present inventive concept may further propose a sealing member **240** that couples the bellows **200**, the rod guide **220**, and the reciprocating drive unit **400**, and that assembles the pump cylinder **100**, the bellows **200**, and the cylinder cover **300** for airtightness.

[0058] Here, the sealing member **240** may include a first sealing **241** provided between the pump cylinder **100** and a fixed flange **210**, a second sealing **243** provided between the fixed flange **210** and the cylinder cover **300**, and a third sealing **245** provided between the cylinder cover **300** and the reciprocating rod **420**.

[0059] The long-life non-contact pump of the inventive concept configured as described above has a structure and connection relationship as follows.

[0060] First, the pumping space **101** between the pump cylinder **100** and the bellows **200** is filled with a fluid.

[0061] Therefore, the fluid enters an inside of the pump cylinder **100** through the inlet valve **110** and is discharged through the outlet valve **120**, and the bellows **200** may pump the corresponding fluid.

[0062] Here, the inlet valve **110** and the outlet valve **120** may each include a check valve built

therein to prevent backflow of fluid.

[0063] Between the pump cylinder **100** and the bellows **200** and between the cylinder cover **300**, airtightness of coupled parts is maintained by the sealing member **240**, thereby preventing leakage of fluid.

[0064] The vacuum line **310** is connected to the vacuum space **201** of the bellows **200** to maintain a constant vacuum state, and when the reciprocating rod **420** is in a forward position by the driving of the reciprocating drive unit **400**, the piston **410** locates in side directions of the inlet valve **110** and the outlet valve **120**.

[0065] At this time, in a state when the piston **410** of the bellows **200** is maximally advanced, the bellows **200** is maximally extended, and thus, the pumping space **101** of the pump cylinder **100** has a minimum volume.

[0066] On the other hand, in a stand-by state before fluid flows in, when the reciprocating rod **420** is driven backward by the reciprocating drive unit **400**, the piston **410** of the bellows **200** starts a backward driving in a direction away from the inlet valve **110** and the outlet valve **120**, and then, fluid flows into the pump cylinder **100** by opening the inlet valve **110**.

[0067] When the backward driving is completed, when closing the inlet valve **110**, the piston **410** of the bellows **200** is in a state of minimal backward motion, and the pumping space **101** of the pump cylinder **100** forms a maximum volumetric space in a state when a volume of the bellows **200** is reduced to the minimum.

[0068] On the other hand, in a state when the fluid intake operation is completed, when the reciprocating rod **420** moves forward by the reciprocating drive unit **400** in a standby state before fluid discharge, the piston **410** of the bellows **200** moves forward in a direction close to the inlet valve **110** and the outlet valve **120**, and when the forward movement starts, the outlet valve **120** is opened and the fluid is discharged from the pumping space **101** of the pump cylinder **100** through the outlet valve **120**.

[0069] At this time, when the forward movement is completed, the outlet valve **120** maintains a closed state and returns (to the closed state?) after the discharge of fluid is completed.

[0070] The long-life non-contact pump of the inventive concept may pump the corresponding fluid by repeating a standby state before fluid discharge and a standby state before fluid introduction by the driving of the reciprocating drive unit **400**.

[0071] On the other hand, in the case of the vacuum space **201** of the bellows **200**, the leak sensor **330**, one side thereof is sealed, is installed on a lower part of the cylinder cover **300** to maintain a vacuum state of the vacuum space **201**.

[0072] The thin metal plate of the bellows **200** may undergo accumulation of fatigue while the bellows **200** repeats an expansion/contraction variable operation.

[0073] At this time, when the service life of the thin metal plate of the bellows **200** is over due to the accumulation of fatigue, gaps may be generated where the thin metal plate is welded or where fatigue is accumulated, and even if fluid leaks into the vacuum state pumping space **101** of the pump cylinder **100**, when a small amount of fluid starts leaking due to beginning of crack generation in the thin metal plate of the bellows **200**, the fluid starts to fill a lower part of the vacuum space **201** of the bellows **200**, and the drain hole **320** is filled with the fluid.

[0074] On the other hand, when the drain hole **320** is filled with fluid, even if gaps are generated in the bellows **200**, the leak sensor **330** may check, give an alarm to the equipment, and thus, damage to the equipment due to the damage of the bellows **200** may be prevented, and at the same time, the replacement time of consumables may be informed.

[0075] A discharging quantity of fluid may be determined by a volume change of the pumping space **101** of the pump cylinder **100** at a forward position and a backward position of the bellows **200**, and thus, the supply amount may be determined.

[0076] On the other hand, it may be confirmed that a discharge weight of the fluid changes on the basis of the same volume as the density of the fluid changes as the temperature of the fluid

changes, and if the volume of fluid is corrected as much as the weight of the volume change due to the density change according to temperature condition changes or if there is an alarm setting function for the temperature change, the quality of the product manufactured by using the long-life non-contact pump may increase.

[0077] In addition, the temperature sensor **130** configured to measure a temperature of fluid in the pumping space **101** of the pump cylinder **100** is included in the long-life non-contact pump to compensate and control a reciprocating driving amount of the bellows **200** by measuring the temperature of the fluid filled in the pumping space **101** and calculating the volume change according to the temperature change, and thus, a dangerous situation may be identified by detecting the temperature change of the equipment.

[0078] The pressure sensor **140** may measure and manage pressure at the time of intake and discharge the internal fluid of the pump cylinder **100** to manage an optimal pumping condition during intake and discharge fluid.

[0079] In other words, the pressure sensor **140** may confirm whether the amount of fluid flowing into the pump is constant or not by checking whether the intake/discharge pressure is constant at each discharge, and check whether the inlet valve **110** and the outlet valve **120**, that perform a role of preventing backflow in the inlet **103** and the outlet **105** through which fluid is introduced and discharged, are properly operated or not.

[0080] Therefore, it is possible to pump an accurate amount of fluid by maintaining a constant pressure at each intake or discharge, and when the intake and discharge pressures change, a situation in which the amount of introduced and discharged fluid is changed or each check valve of the inlet **103** and the outlet **105** needs to be inspected may be notified.

[0081] In the case of the long-life non-contact pump of the inventive concept, in a fluid pumping operation for supplying fluid to a battery, in order to prevent wear caused by contact and friction, which is a problem for the service life of existing pumps, it is possible to extend the lifetime of consumables by developing a structure to which the bellows **200** may be applied.

[0082] Therefore, the design life of the bellows **200** is about millions of cycles, and the effect of improving the lifespan is more than 10 times greater than before, and the production capacity of the production line for injecting fluid into the battery may be extended by 6 to 12 months more than before.

[0083] Therefore, in order to minimize the deformation of the bellows **200** when the bellows **200** is a stretched or stopped state, when the pressure in the vacuum space **201** of the bellows **200** is the same as the external pressure by performing a vacuuming process, sagging at the central part of the bellows **200** due to its own weight when the bellows **200** is horizontally installed or vibration of the bellows **200** due to the reciprocating motion of the bellows **200** may be minimized.

[0084] On the other hand, by maintaining a vacuum condition in the vacuum space **201** of the bellows **200**, the bellows **200** may have minimum deformation due to differential pressure with the outside, increase the precision of inflow/outflow of fluid through a shape, and control a more stable pumping amount.

[0085] In addition, the leak sensor **330** may prevent an equipment body from being damaged by a load even if the fluid leaks inside due to the damage of the bellows **200**.

[0086] Therefore, by greatly improving the pumping structure by applying the bellows **200** to the long-life non-contact pump of the inventive concept and the structure in which the stretchable pumping operation using the bellows **200** without friction between parts that maintain airtightness, compared to the existing pumps, hundreds of thousands of consumable replacement cycles may be improved to millions of cycles, and consumables that currently need to be replaced every week or several weeks may be replaced after several months or more.

[0087] In addition, when replacing consumables, only one bellows **200** or a small number of parts need to be replaced, the replacement work may be relatively easy compared to the existing method, and thus, operators may easily learn how to replace consumables and replace them in a short time

because the replacement method is simpler than in the existing pump and the number of replacement parts is small.

[0088] In the long-life non-contact pump of the inventive concept, when a small amount of fluid starts leaking due to crack generation begins in the thin metal plate of the bellows **200**, the leak is immediately detected by the leak sensor **330**, and thus, the replacement time may be known before the fluid leaks out of the pump, there is a great advantage in preventing a safety accident such as equipment contamination or fire accident.

[0089] Also, in addition to the fluid injection process for automobiles, the fluid pump may be applied to various industrial fields, such as semiconductors, displays, chemicals, pharmaceutical companies, etc. and effects may be expected, and the bellows **200** may be applied according to characteristics of each fluid by forming the bellows **200** using a material such as a resin-based or special material instead of a metal.

[0090] By providing the inventive concept configured as above descriptions, a manufacturing process requires a product having a longer replacement cycle of consumables, but a piston-operated pump may be used because there is no suitable product, and the replacement cycle of consumables may be greatly extended by using a structure of a different concept other than the contact-type airtightness, which is a disadvantage of piston pumps.

[0091] First, in pumping operations, the long-life non-contact pump has a structural feature wherein the stretchable pumping operation is performed using a bellows without friction between parts that maintain airtightness, and thus, as the number of pumping increases from hundreds of thousands to millions of times, the replacement cycle of consumables may further be extended than before.

[0092] Second, it is possible to cope with the replacement cycle of consumables that are currently replaced every few weeks may be replaced once every few months.

[0093] Third, it is possible to solve the inconvenience by supplementing the short consumable replacement cycle, greatly reduce the cost loss due to the replacement of consumables by the manufacturer and increase the operation rate of the equipment.

[0094] Fourth, when replacing consumables, only one bellows or a small number of parts need to be replaced, and the replacement work is relatively easy compared to the existing method, the number of parts to be replaced is small, and because the replacement method is simple compared to the existing pump, the operator may easily learn the replacement method and replace consumables in a short time.

[0095] The terms and words used in the present specification described above and claims should not be construed as being limited to conventional or dictionary meanings, and based on the principle that the present inventor may appropriately define the concept of terms in order to explain his/her invention in the best way, it should be interpreted as meaning and concept consistent with the technical spirit of the inventive concept.

[0096] Therefore, the configurations shown in the drawings and embodiments described in this specification are only one of the most preferred embodiments of the inventive concept, and do not represent all of the technical ideas of the inventive concept, and thus, it should be understood that there may be various equivalents and modifications that may be substituted for the inventive concept at the time of the application.

INDUSTRIAL APPLICABILITY

[0097] A pumping fluid using a long-life non-contact pump may be applied to various industrial fields, such as semiconductors, displays, chemicals, pharmaceutical companies, food, cosmetics, etc. and a better pumping effect may be expected, and the bellows **200** may be applied according to characteristics of each fluid by forming the bellows **200** using a material such as a resin-based or special material instead of a metal.

Claims

1. A long-life non-contact pump comprising: a pump cylinder having a certain pumping space for accommodating introduced fluid and receiving/discharging the fluid through a pumping operation via an inlet and an outlet formed on both sides thereof, the pump cylinder including an outlet valve that is provided on an outlet side and prevents backflow of the fluid when the fluid flows in along the inlet and an inlet valve that is provided on an inlet side and prevents backflow of the fluid when the fluid is discharged along the outlet; a bellows provided in the pumping space of the pump cylinder and varying a volume of the pumping space so as to pump the fluid flowing in/out along the inlet and outlet; a piston that closes one end of the bellows and moves together with the bellows; a reciprocating rod that is integrally connected to the piston and extends outward of the pump cylinder to expand and contract the bellows by reciprocally driving together with a movement of the piston; a cylinder cover that closes a part of the pump cylinder and fixes the other end of the bellows, and through which the reciprocating rod passes; and a reciprocating drive unit provided on the outside of the cylinder cover to drive the piston reciprocally along the connected reciprocating rod, wherein a vacuum space is formed, and vacuum is maintained inside the bellows through a vacuum line formed in the cylinder cover.
 2. The long-life non-contact pump of claim 1, wherein the bellows includes: a first bellows pipe including rubber and having a vacuum space therein, a volume of which is variable and capable of expending and contracting; and a second bellows pipe formed on the outside of the first bellows pipe and including a thin metal plate so that a rigidity of the first bellows pipe is maintained against repeated volume changes.
 3. The long-life non-contact pump of claim 1, further comprising: a drain hole for discharging the fluid entering the vacuum space in the cylinder cover; and a leak sensor coupled to the drain hole and configured to detect the fluid entering the vacuum space when the bellows is damaged, to confirm that the fluid entered the vacuum space from the outside, and to remove the entering fluid.
 4. The long-life non-contact pump of claim 1, further comprising, on a part of the pump cylinder, a temperature sensor configured to sense a temperature of the fluid flowing in/out of the pumping space by pumping of the bellows.
 5. The long-life non-contact pump of claim 1, further comprising on a part of the pump cylinder, a pressure sensor configured to sense a pressure of the fluid flowing in/out of the pumping space by pumping of the bellows.
-