

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283583

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Jiang; Tao et al.

LED FILAMENT AND LED LIGHT BULB

Abstract

An LED light filament includes an LED section, first and second conductive electrodes, a conductive portion and a first solder layer. The LED section includes LED chips. The first conductive electrode and the second conductive electrode are disposed at two ends of the LED section. The conductive portion is electrically connected between the LED chips. An LED chip among the plurality of LED chips has an electrical connecting portion, the one end portion of the conductive portion is connected to the electrical connecting portion and the first solder layer is disposed on the end portion of the conductive portion, and the end portion of the conductive portion is sandwiched between the electrical connecting portion of the LED chip and the first solder layer.

Inventors: Jiang; Tao (Jiaxing, CN), Xiaong; Aiming (Jiaxing, CN), Liu; Fayong (Jiaxing, CN), Wang; Yongnan (Jiaxing, CN), Huang; Bao (Jiaxing, CN), Wang; Zhikun (Jiaxing, CN), Jiang; Chengyang (Jiaxing, CN)

Applicant: ZHEJIANG SUPER LIGHTING ELECTRONIC APPLIANCE CO., LTD.
(Jinyun City, CN)

Family ID: 96948890

Appl. No.: 19/220123

Filed: May 28, 2025

Related U.S. Application Data

parent US continuation 18813874 20240823 parent-grant-document US 12359779 child US 19220123

parent US continuation 18126000 20230324 parent-grant-document US 12007077 child US 18642164

parent US continuation 17356576 20210624 parent-grant-document US 11525547 child US 17900897

parent US continuation 16914461 20200628 parent-grant-document US 11085591 child US

17356576
parent US continuation 16840469 20200406 parent-grant-document US 10711951 child US
16914461
parent US continuation 16505732 20190828 parent-grant-document US 10677396 child US
16840469
parent US continuation-in-part 18642164 20240422 parent-grant-document US 12313227 child US
18813874
parent US continuation-in-part 17408519 20210823 parent-grant-document US 11686436 child US
18126000
parent US continuation-in-part 16894913 20200608 parent-grant-document US 11421827 child US
17408519
parent US continuation-in-part 16748070 20200121 parent-grant-document US 10784428 child US
16894913
parent US continuation-in-part 17900897 20220901 parent-grant-document US 11629825 child US
18126000

Publication Classification

Int. Cl.: **F21K9/64** (20160101); **F21K9/232** (20160101); **F21V23/06** (20060101); **F21Y103/10**
(20160101); **F21Y115/10** (20160101)

U.S. Cl.:

CPC **F21K9/64** (20160801); **F21K9/232** (20160801); **F21V23/06** (20130101); **F21Y2103/10**
(20160801); **F21Y2115/10** (20160801)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of application Ser. No. 18/813,874, filed on 2024 Aug. 23, which is a continuation-in-part (CIP) of application Ser. No. 18/642,164, filed on 2024 Apr. 22. [0002] This application also claims priority under 35 U.S.C. § 119 (a) to Chinese Patent Application No. 201910497661.2 filed on 2019 Jun. 10; No. 201510502630.3 filed on 2015 Aug. 17; No. 201510966906.3 filed on 2015 Dec. 19; No. 201610041667.5 filed on 2016 Jan. 22; No. 201610272153.0 filed on 2016 Apr. 27; No. 201610394610.3 filed on 2016 Jun. 3; No. 201610586388.7 filed on 2016 Jul. 22; No. 201610544049.2 filed on 2016 Jul. 7; No. 201610936171.4 filed on 2016 Nov. 1; No. 201611108722.4 filed on 2016 Dec. 6; No. 201610281600.9 filed on 2016 Apr. 29; No. 201710024877.8 filed on 2017 Jan. 13; No. 201710079423.0 filed on 2017 Feb. 14; No. 201710138009.2 filed on 2017 Mar. 9; No. 201710180574.5 filed on 2017 Mar. 23; No. 201710234618.8 filed on 2017 Apr. 11; No. 201410510593.6 filed on 2014 Sep. 28; No. 201510053077.X filed on 2015 Feb. 2; No. 201510316656.9 filed on 2015 Jun. 10; No. 201510347410.8 filed on 2015 Jun. 19; No. 201510489363.0 filed on 2015 Aug. 7; No. 201510555889.4 filed on 2015 Sep. 2; No. 201710316641.1 filed on 2017 May 8; No. 201710839083.7 filed on 2017 Sep. 18; No. 201710883625.0 filed on 2017 Sep. 26; No. 201730450712.8 filed on 2017 Sep. 21; No. 201730453239.9 filed on 2017 Sep. 22; No. 201730453237.X filed on 2017 Sep. 22; No. 201730537542.7 filed on 2017 Nov. 3; No. 201730537544.6 filed on 2017 Nov. 3; No. 201730520672.X filed on 2017 Oct. 30; No. 201730517887.6 filed on 2017 Oct. 27; No. 201730518659.0 filed on 2017 Oct. 27; No. 201730489929.X filed on 2017 Oct. 16; No. 201711434993.3 filed on 2017 Dec. 26; No.

2017114777.3 filed on 2017 Dec. 29; No. 201810031786.1 filed on 2018 Jan. 12; No. 201810065369.9 filed on 2018 Jan. 23; No. 201810343825.1 filed on 2018 Apr. 17; No. 201810344630.9 filed on 2018 Apr. 17; No. 201810501350.4 filed on 2018 May 23; No. 201810498980.0 filed on 2018 May 23; No. 201810573314.9 filed on 2018 Jun. 6; No. 201810836433.9 filed on 2018 Jul. 26; No. 201810943054.X filed on 2018 Aug. 17; No. 201811005536.7 filed on 2018 Aug. 30; No. 201811005145.5 filed on 2018 Aug. 30; No. 201811079889.1 filed on 2018 Sep. 17; No. 201811277980.4 filed on 2018 Oct. 30; No. 201811285657.1 filed on 2018 Oct. 31; No. 201811378173.1 filed on 2018 Nov. 19; No. 201910060475.2 filed on 2019 Jan. 22; No. 201811378189.2 filed on 2018 Nov. 19; No. 201811549205.X filed on 2018 Dec. 18; No. 201911057715.X filed on 2019 Nov. 1; No. 201911234236.0 filed on 2019 Dec. 5; No. 202010856691.0 filed on 2020 Aug. 24; No. 202010904065.4 filed on 2020 Sep. 1; No. 202010912636.9 filed on 2020 Sep. 3; No. 202011313059.8 filed on 2020 Nov. 20; No. 202110108853.7 filed on 2021 Jan. 27; No. 202110779145.6 filed on 2021 Jul. 9; No. 202311381406.4 filed on 2023 Oct. 23; No. 202410121595.X filed on 2024 Jan. 29, each of which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0003] The present disclosure relates to a lighting field, and more particularly to an LED filament and its application in an LED light bulb.

RELATED ART

[0004] Incandescent bulbs have been widely used for homes or commercial lighting for decades. However, incandescent bulbs are generally with lower efficiency in terms of energy application, and about 90% of energy input can be converted into a heat form to dissipate. In addition, because the incandescent bulb has a very limited lifespan (about 1,000 hours), it needs to be frequently replaced. These traditional incandescent bulbs are gradually replaced by other more efficient lighting devices, such as fluorescent lights, high-intensity discharge lamps, light-emitting diodes (LEDs) lights and the like. In these electric lamps, the LED light lamp attracts widespread attention in its lighting technology. The LED light lamp has the advantages of long lifespan, small in size, environmental protection and the like, therefore the application of the LED light lamp continuously grows.

[0005] In recent years, LED light bulbs with LED filaments have been provided on the market. At present, LED light bulbs using LED filaments as illumination sources still have the following problems to be improved.

[0006] Firstly, an LED hard filament is provided with a substrate (for example, a glass substrate) and a plurality of LED chips disposed on the substrate. However, the illumination appearance of the LED light bulbs relies on multiple combinations of the LED hard filaments to produce the better illumination appearances. The illumination appearance of the single LED hard filament cannot meet the general needs in the market. A traditional incandescent light bulb is provided with a tungsten filament, the uniform light emitting can be generated due to the natural bendable property of the tungsten filament. In contrast, the LED hard filament is difficult to achieve such uniform illumination appearances. There are many reasons why LED hard filaments are difficult to achieve the uniform illumination appearance. In addition to the aforementioned lower bendable property, one of the reasons is that the substrate blocks the light emitted by the LED chip, and furthermore the light generated by the LED chip is displayed similar to a point light source which causes the light showing concentrated illumination and with poor illumination uniformity. In other words, a uniform distribution of the light emitted from LED chip produces a uniform illumination appearance of the LED filament. On the other hand, the light ray distribution similar to a point light source may result in uneven and concentrated illumination.

[0007] Secondly, there is one kind of LED soft filament, which is similar to the structure of the

above-mentioned LED hard filament and is employed a flexible printed circuit substrate (hereinafter referred to FPC) instead of the glass substrate to enable the LED filament having a certain degree of bending. However, by utilizing the LED soft filament made of the FPC, the FPC has a thermal expansion coefficient different from that of the silicon gel coated covering the LED soft filament, and the long-term use causes the displacement or even degumming of the LED chips. Moreover, the FPC may not be beneficial to flexible adjustment of the process conditions and the like. Besides, during bending the LED soft filament it has a challenge in the stability of the metal wire bonded between LED chips. When the arrangement of the LED chips in the LED soft filament is dense, if the adjacent LED chips are connected by means of metal wire bonding, it is easy to cause the stress to be concentrated on a specific part of the LED soft filament when the LED soft filament is bent, thereby the metal wire bonding between the LED chips are damaged and even broken.

[0008] In addition, the LED filament is generally disposed inside the LED light bulb, and in order to present the aesthetic appearance and also to make the illumination of the LED filament more uniform and widespread, the LED filament is bent to exhibit a plurality of curves. Since the LED chips are arranged in the LED filaments, and the LED chips are relatively hard objects, it is difficult for the LED filaments to be bent into a desired shape. Moreover, the LED filament is also prone to cracks due to stress concentration during bending.

[0009] In order to increase the aesthetic appearance and make the illumination appearance more uniform, an LED light bulb has a plurality of LED filaments, which are disposed with different placement or angles. However, since the plurality of LED filaments need to be installed in a single LED light bulb, and these LED filaments need to be fixed individually, the assembly process will be more complicated and the production cost will be increased.

[0010] In addition, since the driving requirements for lighting the LED filament are substantially different from for lighting the conventional tungsten filament lamp. Therefore, for LED light bulbs, how to design a power supply circuitry with a stable current to reduce the ripple phenomenon of the LED filament in an acceptable level so that the user does not feel the flicker is one of the design considerations. Besides, under the space constraints and the premises of achieving the required light efficiency and the driving requirements, how to design a power supply circuitry with the structure simply enough to embed into the space of the lamp head is also a focus of attention.

[0011] Patent No. CN202252991U discloses the light lamp employing with a flexible PCB board instead of the aluminum heat dissipation component to improve heat dissipation. Wherein, the phosphor is coated on the upper and lower sides of the LED chip or on the periphery thereof, and the LED chip is fixed on the flexible PCB board and sealed by an insulating adhesive. The insulating adhesive is epoxy resin, and the electrodes of the LED chip are connected to the circuitry on the flexible PCB board by gold wires. The flexible PCB board is transparent or translucent, and the flexible PCB board is made by printing the circuitry on a polyimide or polyester film substrate. Patent No. CN105161608A discloses an LED filament light-emitting strip and a preparation method thereof. Wherein the LED chips are disposed without overlapped, and the light-emitting surfaces of the LED chips are correspondingly arranged, so that the light emitting uniformity and heat dissipation is improved accordingly. Patent No. CN103939758A discloses that a transparent and thermally conductive heat dissipation layer is formed between the interface of the carrier and the LED chip for heat exchange with the LED chip. According to the aforementioned patents, which respectively use a PCB board, adjust the chips arrangement or form a heat dissipation layer, the heat dissipation of the filament of the lamp can be improved to a certain extent correspondingly; however, the heat is easy to accumulate due to the low efficiency in heat dissipation. The last one, Publication No. CN204289439U discloses an LED filament with omnidirectional light comprising a substrate mixed with phosphors, at least one electrode disposed on the substrate, at least one LED chip mounted on the substrate, and encapsulated the LED chip. The substrate formed by the silicone resin contained with phosphors eliminates the cost of glass or sapphire as a substrate, and the LED filament equipping with this kind of substrate avoids the

influence of glass or sapphire on the light emitting of the LED chip. The 360-degree light emitting is realized, and the illumination uniformity and the light efficiency are greatly improved. However, due to the fact that the substrate is formed by silicon resin, the defect of poor heat resistance is a disadvantage.

SUMMARY

[0012] It is noted that the present disclosure includes one or more inventive solutions currently claimed or not claimed, and in order to avoid confusion between the illustration of these embodiments in the specification, a number of possible inventive aspects herein may be collectively referred to “present/the invention.”

[0013] A number of embodiments are described herein with respect to “the invention.” However, the word “the invention” is used merely to describe certain embodiments disclosed in this specification, whether or not in the claims, is not a complete description of all possible embodiments. Some embodiments of various features or aspects described below as “the invention” may be combined in various ways to form an LED light bulb or a portion thereof.

[0014] In view of this, an LED filament is provided. The LED filament comprises an LED section, a first conductive electrode, a second conductive electrode, a conductive portion and a first solder layer. The LED section comprises a plurality of LED chips connected in series and a light conversion layer wrapping the plurality of LED chips. The first conductive electrode is disposed at one of two ends of the LED section and electrically connected to the plurality of LED chips, and a portion of the first conductive electrode is wrapped by the light conversion layer. The second conductive electrode is disposed at the other end of the LED section and electrically connected to the plurality of LED chips, and a portion of the second conductive electrode is wrapped by the light conversion layer. The conductive portion is electrically connected between two adjacent LED chips and comprises two end portions. The first solder layer is disposed on one end portion of the conductive portion. An LED chip among the plurality of LED chips has an electrical connecting portion, the one end portion of the conductive portion is connected to the electrical connecting portion and the first solder layer is disposed on the end portion of the conductive portion, and the end portion of the conductive portion is sandwiched between the electrical connecting portion of the LED chip and the first solder layer.

[0015] In some embodiments, a projection area of the first solder layer on the electrical connecting portion of the LED chip is larger than a projection area of a bonding region between the conductive portion and the electrical connecting portion of the LED chip.

[0016] In some embodiments, the end portion of the conductive portion, the electrical connecting portion of the LED chip, and the first solder layer together form a joining portion, the joining portion has a meshy surface, and a plurality of bulges and a plurality of indents are alternately arranged on the meshy surface.

[0017] In some embodiments, the plurality of LED chips further comprises a first row of LED chips and a second row of LED chips, the first row of LED chips and the second row of LED chips are connected in parallel, the LED chips of the first row of LED chips are connected in series, the LED chips of the second row of LED chips connected in series, and the first row of LED chips and the second row of LED chips are alternately arranged along a width direction of the LED filament.

[0018] In some embodiments, further comprising a second solder layer, wherein the second solder layer is made of the solder material, and the end portion of the conductive portion is sandwiched between the first solder layer and the second solder layer.

[0019] In some embodiments, each of a projection area of the first solder layer on the electrical connecting portion of the LED chip and a projection area of the second solder layer on the electrical connecting portion of the LED chip is larger than a projection area of a bonding region between the conductive portion and the first solder layer, and between the conductive portion and the second solder layer on the electrical connecting portion of the LED chip.

[0020] In some embodiments, a projection area of a bonding region between the conductive portion

and the second solder layer is smaller than the projection area of the first solder layer, and the projection area of the first solder layer is smaller than the projection area of the second solder layer. [0021] In some embodiments, the conductive portion has a first bent portion and a second bent portion, and the conductive portion extends from the electrical connecting portion along a first direction of the LED chip, extends toward a second direction of the LED chip through the first bent portion, and extends toward a third direction of the LED chip through the second bent portion, and wherein the first direction, the second direction, and the third direction are different directions. [0022] In some embodiments, the first direction is a height direction of the LED chip, the second direction is a width direction of the LED chip, and the third direction is a length direction of the LED chip.

[0023] In some embodiments, the plurality of LED chips further comprises a first row of LED chips and a second row of LED chips, the first row of LED chips and the second row of LED chips are connected in parallel, the LED chips of the first row of LED chips are connected in series, the LED chips of the second row of LED chips connected in series, and the first row of LED chips and the second row of LED chips are alternately arranged along a width direction of the LED filament. [0024] According to another embodiment, an LED light bulb is provided. The LED light bulb comprises a lamp housing, a bulb base, a stem, two conductive supports, a driving circuit, and a flexible LED filament. The lamp housing has a central axis. The bulb base is connected to the lamp housing. The stem is disposed in the lamp housing along the central axis of the lamp housing. The two conductive supports are disposed in the lamp housing and have opposite polarities. The driving circuit is disposed in the bulb base and electrically connected to the two conductive supports. The flexible LED filament is disposed in the lamp housing and electrically connected to the two conductive supports. The flexible LED filament comprises an LED section, a first conductive electrode, a second conductive electrode, a conductive portion and a first solder layer. The LED section comprises a plurality of LED chips connected in series and a light conversion layer wrapping the plurality of LED chips. The first conductive electrode is disposed at one of two ends of the LED section and electrically connected to the plurality of LED chips and one of the two conductive supports, and a portion of the first conductive electrode is wrapped by the light conversion layer. The second conductive electrode is disposed at the other end of the LED section and electrically connected to the plurality of the LED chips and the other one of the two conductive supports, and a portion of the second conductive electrode is wrapped by the light conversion layer. The conductive portion is electrically connected between two adjacent LED chips and comprises two end portions. An LED chip among the plurality of LED chips has an electrical connecting portion, the one end portion of the conductive portion is connected to the electrical connecting portion and the first solder layer is disposed on the end portion of the conductive portion, and the end portion of the conductive portion is sandwiched between the electrical connecting portion of the LED chip and the first solder layer.

[0025] In some embodiments, a projection area of the first solder layer on the electrical connecting portion of the LED chip is larger than a projection area of a bonding region between the conductive portion and the electrical connecting portion of the LED chip.

[0026] In some embodiments, the end portion of the conductive portion, the electrical connecting portion of the LED chip, and the first solder layer together form a joining portion, the joining portion has a meshy surface, and a plurality of bulges and a plurality of indents are alternately arranged on the meshy surface.

[0027] In some embodiments, the plurality of LED chips further comprises a first row of LED chips and a second row of LED chips, the first row of LED chips and the second row of LED chips are connected in parallel, the LED chips of the first row of LED chips are connected in series, the LED chips of the second row of LED chips connected in series, and the first row of LED chips and the second row of LED chips are alternately arranged along a width direction of the LED filament.

[0028] In some embodiments, further comprising a second solder layer, wherein the second solder

layer is made of the solder material, and the end portion of the conductive portion is sandwiched between the first solder layer and the second solder layer.

[0029] In some embodiments, each of a projection area of the first solder layer on the electrical connecting portion of the LED chip and a projection area of the second solder layer on the electrical connecting portion of the LED chip is larger than a projection area of a bonding region between the conductive portion and the first solder layer, and between the conductive portion and the second solder layer on the electrical connecting portion of the LED chip.

[0030] In some embodiments, a projection area of a bonding region between the conductive portion and the second solder layer is smaller than the projection area of the first solder layer, and the projection area of the first solder layer is smaller than the projection area of the second solder layer.

[0031] In some embodiments, the conductive portion has a first bent portion and a second bent portion, and the conductive portion extends from the electrical connecting portion along a first direction of the LED chip, extends toward a second direction of the LED chip through the first bent portion, and extends toward a third direction of the LED chip through the second bent portion, and wherein the first direction, the second direction, and the third direction are different directions.

[0032] In some embodiments, the first direction is a height direction of the LED chip, the second direction is a width direction of the LED chip, and the third direction is a length direction of the LED chip.

[0033] In some embodiments, the plurality of LED chips further comprises a first row of LED chips and a second row of LED chips, the first row of LED chips and the second row of LED chips are connected in parallel, the LED chips of the first row of LED chips are connected in series, the LED chips of the second row of LED chips connected in series, and the first row of LED chips and the second row of LED chips are alternately arranged along a width direction of the LED filament.

[0034] To make the above and other objects, features, and advantages of the present invention clearer and easier to understand, the following embodiments will be described in detail with reference to the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0035] The present invention will become more readily apparent to those ordinarily skilled in the art after reviewing the following detailed description and accompanying drawings, in which:

[0036] FIG. 1 is a perspective view of the LED filament with partial sectional view in accordance with an embodiment of the present invention;

[0037] FIG. 2A to FIG. 2F are cross sectional views of various LED filaments in accordance with the present invention;

[0038] FIG. 3 is a perspective view of the LED filament with partial sectional view in accordance with an embodiment of the present invention;

[0039] FIG. 4A is a cross sectional view of an LED filament in accordance with an embodiment of the present invention;

[0040] FIG. 4B to FIG. 4G are cross sectional views of various LED filaments in accordance with the present invention;

[0041] FIG. 5 is a cross sectional view of an LED filament with multiple layers in accordance with an embodiment of the present invention;

[0042] FIG. 6 is a cross sectional view of an LED filament with multiple layers in accordance with an embodiment of the present invention;

[0043] FIG. 7 is a cross sectional view of an LED filament with multiple layers in accordance with an embodiment of the present invention;

[0044] FIG. 8 is a cross sectional view of an LED filament with multiple layers in accordance with

an embodiment of the present invention;

[0045] FIG. **9** is a cross sectional view of an LED filament with multiple layers in accordance with an embodiment of the present invention;

[0046] FIG. **10** is a cross sectional view of an LED filament in accordance with an embodiment of the present invention;

[0047] FIG. **11** is a cross sectional view of the structure of an LED filament in accordance with an embodiment of the present invention;

[0048] FIG. **12** is a cross sectional view of the structure of an LED filament in accordance with an embodiment of the present invention;

[0049] FIG. **13A** to FIG. **13F** are schematic top views of a plurality of embodiments in accordance with the present invention;

[0050] FIG. **14** is a schematic structural view of an LED chip bonding wire of an embodiment in accordance with the present invention;

[0051] FIG. **15A** illustrates a perspective view of an LED light bulb according to the third embodiment of the instant disclosure;

[0052] FIG. **15B** illustrates an enlarged cross-sectional view of the dashed-line circle of FIG. **15A**;

[0053] FIG. **15C** is a projection of a top view of an LED filament of the LED light bulb of FIG. **15A**;

[0054] FIG. **16A** is a perspective view of an LED light bulb according to an embodiment of the present invention;

[0055] FIG. **16B** is a front view of an LED light bulb of FIG. **16A**;

[0056] FIG. **16C** is a top view of the LED light bulb of FIG. **16A**;

[0057] FIG. **16D** is the LED filament shown in FIG. **16B** presented in two dimensional coordinate system defining four quadrants;

[0058] FIG. **16E** is the LED filament shown in FIG. **16C** presented in two dimensional coordinate system defining four quadrants;

[0059] FIG. **17A** to FIG. **17D** are respectively a perspective view, a side view, another side view and a top view of an LED light bulb in accordance with an embodiment of the present invention;

[0060] FIG. **18A** to FIG. **18D** are respectively a perspective view, a side view, another side view and a top view of an LED light bulb in accordance with an embodiment of the present invention;

[0061] FIG. **19A** to FIG. **19C** are schematic circuit diagrams of an LED filament in accordance with an embodiment of the present invention;

[0062] FIG. **20A** to FIG. **20C** are schematic circuit diagrams of an LED filament in accordance with another embodiment of the present invention;

[0063] FIG. **21A** to FIG. **21D** are schematic circuit diagrams of an LED filament in accordance with another embodiment of the present invention;

[0064] FIG. **22A** to FIG. **22E** are schematic circuit diagrams of an LED filament in accordance with another embodiment of the present invention;

[0065] FIG. **23** is a block diagram of a power supply module of an LED light bulb in accordance with an embodiment of the present invention;

[0066] FIG. **24A** is a schematic diagram of a rectifying circuit in accordance with an embodiment of the present invention;

[0067] FIG. **24B** is a schematic diagram of a rectifying circuit in accordance with another embodiment of the present invention;

[0068] FIG. **25A** is a schematic diagram of a filtering circuit in accordance with an embodiment of the present invention;

[0069] FIG. **25B** is a schematic diagram of a filtering circuit in accordance with another embodiment of the present invention;

[0070] FIG. **26** is a block diagram of a driving circuit in accordance with an embodiment of the present invention;

[0071] FIG. **27A** to FIG. **27D** are schematic diagrams showing signal waveforms of a driving circuit in accordance with various embodiments of the present invention;

[0072] FIG. **28A** is a perspective diagram of a driving circuit in accordance with an embodiment of the present invention;

[0073] FIG. **28B** is a perspective diagram of a driving circuit in accordance with another embodiment of the present invention;

[0074] FIG. **29** is a cross-sectional view of an LED filament according to an embodiment of the present disclosure;

[0075] FIG. **30** is a schematic structural diagram of another embodiment of an LED filament according to this application;

[0076] FIG. **31** is a schematic structural diagram of another embodiment of an LED filament according to this application;

[0077] FIG. **32** is a schematic structural diagram of another embodiment of an LED filament according to this application;

[0078] FIG. **33** to FIG. **35B** are schematic structural diagrams of a plurality of embodiments of an LED filament according to this application;

[0079] FIG. **36** is a top view of an embodiment of an LED filament with a top layer removed according to this application;

[0080] FIG. **37A** is a schematic structural diagram of an embodiment of an LED filament according to this application;

[0081] FIG. **37B** is a top view of FIG. **37A**;

[0082] FIG. **37C** is a schematic partial cross-sectional view of a position A-A in FIG. **37A**;

[0083] FIG. **38A** to FIG. **38E** are schematic diagrams of a first embodiment of a method for manufacturing an LED filament according to this application;

[0084] FIG. **39** is a schematic diagram of an LED light bulb according to an embodiment of this application;

[0085] FIG. **40A** is a schematic diagram of a lamp cap according to an embodiment of this application;

[0086] FIG. **40B** is a schematic diagram of a cross section A-A in FIG. **40A**;

[0087] FIG. **41A** is a schematic diagram of a lamp cap according to an embodiment of this application;

[0088] FIG. **41B** is a schematic diagram of an embodiment of a cross section B-B in FIG. **41A**;

[0089] FIG. **41C** is a schematic diagram of an embodiment of a cross section B-B in FIG. **41A**;

[0090] FIG. **42A** to FIG. **42D** are respectively a schematic diagram, a side view, another side view, and a top view of an LED light bulb according to an embodiment of this application;

[0091] FIG. **43** is a partially perspective schematic view of the LED filament of the disclosure in an embodiment;

[0092] FIG. **44** is a cross-sectional schematic view along line 2-2 in FIG. **43**;

[0093] FIG. **45** to FIG. **49** are schematic views of arrangements of the LED chips and the electrodes of the disclosure in different embodiments;

[0094] FIG. **50** is a structural schematic view of the conductive portion of the disclosure in an embodiment;

[0095] FIG. **51** is a structural schematic view of the second joining portion in related art;

[0096] FIG. **52A** is a structural schematic view of the second joining portion of the disclosure in an embodiment;

[0097] FIG. **52B** is a cross-sectional structural schematic view of the second joining portion of the disclosure in FIG. **52A**;

[0098] FIG. **53A** is a structural schematic view of the second joining portion of the disclosure in an embodiment;

[0099] FIG. **53B** is a cross-sectional structural schematic view of the second joining portion of the

disclosure in FIG. 53A;
[0100] FIG. 54A and FIG. 54B are schematic views of the cutting position of the second end of the conductive portion of the related art;
[0101] FIG. 55 is a structural schematic view of the first joining portion of the related art;
[0102] FIG. 56 is a structural schematic view of the first joining portion of the disclosure in an embodiment;
[0103] FIG. 57A and FIG. 57B are partially schematic views of the first end of the conductive portion of the related art at different viewing angles;
[0104] FIG. 58A and FIG. 58B are partially schematic views of the first end of the conductive portion of the disclosure in an embodiment;
[0105] FIG. 59A and FIG. 59B are partially structural schematic views of the LED filament of the disclosure in an embodiment at different viewing angles;
[0106] FIG. 60 is a schematic view of the slant arrangement of the LED chips of the disclosure in an embodiment;
[0107] FIG. 61 is a structural schematic view of the connection between the LED chip and the electrode of the disclosure in an embodiment; and
[0108] FIG. 62A to FIG. 62C are structural schematic views of the connection between the LED chip and its corresponding electrode through two conductive portions of the disclosure in an embodiment at different viewing angles.

DETAILED DESCRIPTION

[0109] The present disclosure provides a novel LED filament and its application the LED light bulb. The present disclosure will now be described in the following embodiments with reference to the drawings. The following descriptions of various embodiments are presented herein for purpose of illustration and giving examples only. This invention is not intended to be exhaustive or to be limited to the precise form disclosed. These example embodiments are just that—examples—and many implementations and variations are possible that do not require the details provided herein. It should also be emphasized that the disclosure provides details of alternative examples, but such listing of alternatives is not exhaustive. Furthermore, any consistency of detail between various examples should not be interpreted as requiring such detail—it is impracticable to list every possible variation for every feature described herein. The language of the claims should be referenced in determining the requirements of the invention.

[0110] It will be understood that when an element is referred to as being “connected” or “coupled” to or “on” another element, it can be directly connected or coupled to or on the other element or intervening elements may be present. In contrast, when an element is referred to as being “directly connected” or “directly coupled,” or “immediately connected” or “immediately coupled” to another element, there are no intervening elements present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.). However, the term “contact,” as used herein refers to a direct connection (i.e., touching) unless the context indicates otherwise.

[0111] Embodiments described herein will be described referring to plan views and/or cross-sectional views by way of ideal schematic views. Accordingly, the exemplary views may be modified depending on manufacturing technologies and/or tolerances. Therefore, the disclosed embodiments are not limited to those shown in the views, but include modifications in configuration formed on the basis of manufacturing processes. Therefore, regions exemplified in figures may have schematic properties, and shapes of regions shown in figures may exemplify specific shapes of regions of elements to which aspects of the invention are not limited.

[0112] Spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element's or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in

addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly. In the disclosure, the terms “horizontal”, “vertical” and “parallel” are defined to include a range of $\pm 10\%$ on the standard definitions. For example, “vertical” usually indicates 90 degrees relative to a reference line, but in the disclosure, “vertical” indicates to include from 80 degrees to 100 degrees. [0113] Terms such as “same,” “equal,” “planar,” or “coplanar,” as used herein when referring to orientation, layout, location, position, shapes, sizes, amounts, or other measures do not necessarily mean an exactly identical orientation, layout, location, position, shape, size, amount, or other measure, but are intended to encompass nearly identical orientation, layout, location, position, shapes, sizes, amounts, or other measures within acceptable variations that may occur, for example, due to manufacturing processes. The term “substantially” may be used herein to emphasize this meaning, unless the context or other statements indicate otherwise. For example, items described as “substantially the same,” “substantially equal,” or “substantially planar,” may be exactly the same, equal, or planar, or may be the same, equal, or planar within acceptable variations that may occur, for example, due to manufacturing processes.

[0114] Terms such as “about” or “approximately” may reflect sizes, orientations, or layouts that vary only in a small relative manner, and/or in a way that does not significantly alter the operation, functionality, or structure of certain elements. For example, a range from “about 0.1 to about 1” may encompass a range such as a 0%-5% deviation around 0.1 and a 0% to 5% deviation around 1, especially if such deviation maintains the same effect as the listed range.

[0115] Unless expressly stated otherwise, comparative quantitative terms (such as “above” and “below”) are intended to encompass equivalent concepts. As an example, “above” can mean not only “greater than” in the mathematical sense, but also “equal to”.

[0116] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which the present invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and the present application, and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0117] FIG. 1 is a perspective with a partially cross sectional view showing an embodiment of a light emitting part of the present invention. The present invention will be described below with an LED filament as a light emitting part. However, the embodiment in which the LED filament of the LED light bulb of the present invention may be implemented is not limited thereto. And any LED filament can be bent with various shapes and therefore capable of emitting an omni-directional light that should be regarded as an equivalent replacement element for the light emitting part of the present invention. The LED filament **100** includes a plurality of LED chip units **102**, **104**, wires **140**, at least two conductive electrodes **110**, **112**, and a light conversion layer **120** (in a particular embodiment, the light conversion layer may be referred to a silicone layer). The LED chip units **102**, **104** and the conductive electrodes **110**, **112** are electrically connected by the wires **140**, respectively. The phosphors in the light conversion layer **120** absorbs certain radiation (such as light) and emits the light. The LED filament **100** emitting light rays when the conductive electrodes **110**, **112** are powered on (voltage source or current source). In the present embodiment, the light emitted by the LED filament can be substantially 360 degrees and similar to the illumination of the point light source. Therefore, once the LED filament of the embodiment of the present invention is applied to an LED light bulb, the illumination with omni-directional light can be achieved.

[0118] As shown in FIG. 1, the cross sectional shape of the LED filament **100** of the present invention is rectangular, but the cross sectional shape of the LED filament **100** is not limited

thereto. The cross sectional shape of the LED filament **100** may be triangular, circular, elliptical, polygonal, rhombus, or even square with the corners as chamfered or rounded.

[0119] The LED chip units **102**, **104**, or named with the LED section **102**, **104**, may be composed of a single LED chip, or two LED chips. Of course, it may also include multiple LED chips, that is, equal to or greater than three LED chips.

[0120] FIG. 2A to FIG. 2F are cross sectional views showing various embodiments of the LED filament in accordance with the present invention. As shown in FIG. 2A, the LED filament includes the LED chip units **102**, **104**, the conductive electrodes **110**, **112**, and the wires. The difference between the present embodiment and the previous embodiment is the light conversion layer **120** in the present embodiment is provided with a first light conversion layer **121** and a base layer **122**. The upper surface of the base layer **122** is attached with a plurality of copper foils **116** and the LED chip units **102** and **104**. The copper foils **116** are located between two adjacent LED chip units **102**, **104**. Wherein, the conductive electrodes **110**, **112** are disposed corresponding to the LED chip units **102**, **104**, and the LED chip units **102**, **104** and the copper foil **116**, the LED chip units **102**, **104** and the conductive electrodes **110**, **112** are electrically connected by wires respectively. The LED chip is provided with a p-junction and an n-junction, wherein the conductive wires comprise a first wire **141** used for connecting the LED chip units **102**, **104** with the conductive electrodes **110**, **112**, and a second wire **142** used for connecting the LED chip units **102**, **104** with the copper foil **116**. The first light conversion layer **121** covers a single LED chip unit and the first wire **141** and the second wire **142** connecting to the LED chip unit. The number of the first light conversion layers **121** is the same as the number of the LED chip unit. The LED light bulb employs the LED filament as aforementioned designs, the heat dissipation function and the light emitting efficiency of the LED filament are improved due to the thermal radiation area is increased. Furthermore, because the probability of the wire disconnection is reduced, the reliability of the LED light bulb product is increased, and also the brightness and illuminated appearance of the LED filament with bending curve is achieved.

[0121] According to present embodiment, each of the LED chip units **102**, **104** includes two LED chips, and of course, may also include a plurality of LED chips, that is, equal to or greater than three LED chips. The exterior shape of the LED chip can be a strip type, but the present invention is not limited thereto. The strip type LED chip has fewer conductive electrodes, reducing the possibility of shielding the light emitted by the LED chip. The LED chip units **102** and **104** are connected in series and the conductive electrodes **110** and **112** are disposed at two ends of the connected LED chip units, and a portion of each of the conductive electrodes **110** and **112** is exposed outside the first light conversion layer **121**. Each of the six sides of every LED chip in the LED chip units **102**, **104** is covered by the first light conversion layer **121**, that is, six sides of the LED chip of the LED units **102**, **104** are covered by a first light conversion layer **121**, and the coverage of the first light conversion layer **121** may be partial overlap or as wrap but not limited to direct contact with the LED chip. Preferably, in the present embodiment, each of the six sides of the LED chip of the LED chip units **102**, **104** directly contacts the first light conversion layer **121**. However, in the implementation, the first light conversion layer **121** may cover merely one of the six sides of each of the LED chip of the LED chip units **102**, **104**, that is, the first light conversion layer **121** directly contacts the one side such as a top or a bottom side. Similarly, the first light conversion layer **121** can directly contact at least one side of the two conductive electrodes **110**, **112** or the copper foil **116**.

[0122] The wire is a gold wire or an aluminum wire, and the combination of the copper foil **116** and the gold wire to provide the LED filament having a stabilized and a flexible conductive structure. The copper foil **116** can be replaced by any other conductive material. The width or/and length of the opening of the copper foil **116** is larger than the contour of the LED chip units **102**, **104** and further to define the positions of the LED chip units **102**, **104**. Furthermore, at least two of the six faces of the LED chip units **102**, **104** are contacted and covered by the first light conversion

layer **121**. By utilizing the copper foil **116** and the wire as linkage, a plurality of the LED chip units **102** and **104** are interconnected in series, in parallel or in a combination of both. Then, the front end and the rear end of the interconnected LED chip units **102**, **104** are respectively connected to the two conductive electrodes **110**, **112** disposing on the base layer **122**, and the conductive electrodes **110**, **112** are electrically connected to the power supply to provide the electricity for emitting the LED chip units **102**, **104**.

[0123] The first light conversion layer **121** covers two ends of the copper foil **116**, wherein the covering area or the average thickness of the first conversion layer **121** disposing on each of the two ends of the copper foil **116** are substantially the same or not equal. The first light conversion layer **121** covers the upper surface of the copper foil **116** with an area ratio about 30 to 40 percent. In an embodiment of the present invention, as shown in the FIG. 2B, the first light conversion layer **121** may cover the entire copper foil **116** disposing between the two adjacent first light conversion layers. Wherein the covering area or the average thickness of the first conversion layer **121** disposing on the two ends of the copper foil **116** and on the middle of the copper foil **116** are not equal. The first light conversion layer **121** covering the middle surface of the copper foil has a thickness in a range of about 30 to 50 micron (μm). The surface of the first light conversion layer **121** is an arc shape, and the height of the arc shape gradually decreases from the middle to both sides with respect to the base layer **122**, and the angle between each of two sides of the curved shape and the base layer **122** is an acute angle or an obtuse angle.

[0124] The first light conversion layer **121** includes a phosphor gel or a phosphor film. At least a portion of each of the six sides of the LED chip units **102**, **104** directly contacts the first light conversion layer **121** and/or one or both sides of each of the LED chip unit **102**, **104** are bonded to the first light conversion layer **121** through the glue. In the aforementioned embodiment, the six sides the LED chip units **102**, **104** are all covered by the first light conversion layer **121** and/or partially direct contacted with the first light conversion layer **121**. Both embodiments have equivalent concept. In some embodiments, the foregoing glue may also incorporate with phosphors to increase the overall light conversion efficiency. The glue is usually also a silicone gel. The difference between the glue and the silicon gel is the glue generally mixed with silver powder or heat dissipating powder to improve the thermal conductivity.

[0125] As shown in FIG. 2C, the difference from the aforementioned embodiment is that the lower surface of the base layer **122** is covered by a second light conversion layer **123** with a uniform thickness. The upper surface and the lower surface of the base layer **122** are opposite to each other. As shown in FIG. 2D, the second light conversion layer **123** covering the lower surface of the base layer **122** has an inclined side or an inclined side with an arc shape. The lower surface of the base layer **122** covering by the second light conversion layer **123**, the LED filament therefore can generate fluorescence with more yellow light and less blue light. Therefore, the difference in color temperature between the front and back surfaces of the LED chip units **102** and **104** can be reduced. Thereby, the color temperature of emitting light from both sides of the LED chip units **102** and **104** is closer.

[0126] In one embodiment, as shown in FIG. 2E, the first light conversion layer **121** covers two adjacent LED chip units **102**, **104**, a copper foil **116** is located between two adjacent LED chip units **102**, **104**, and the first wire **141** and the second wire **142** connecting between the LED chip units **102** and **104**. In one embodiment, a silver plating layer **118** is disposed on the upper surface of the copper foil **116**, and a portion of the copper foil **116** located at the ends of the LED filament and extending beyond the base layer **122** can serve as the conductive electrodes **110**, **112**. The silver plating layer **118** not only has good electrical conductivity but also has the effect of increasing light reflection. The surface of the silver plating layer **118** can be selectively provided with a solder mask layer (not shown), and the thickness of the solder mask layer is 30~50 μm . The solder mask layer is obtained by an OSP (Organic Solderability Preservatives) process. The solder mask layer has functions of oxidation resistance, thermal shock resistance, and moisture resistance.

[0127] In another embodiment of the present invention, as shown in FIG. 2F, the LED filament **200** has LED chip units **102**, **104**, conductive electrodes **110**, **112**, wires **140**, and a light conversion layer **120**. The copper foil **116** is located between the adjacent two LED chip units **102**, **104**, the conductive electrodes **110**, **112** are arranged corresponding to the LED chip units **102**, **104**, and the LED chip units **102**, **104** and the copper foil **116**, the LED chip units **102**, **104** and the conductive electrodes **110**, **112** are electrically connected by wire **140** respectively. The light conversion layer **120** is disposed on the LED chip units **102**, **104** and at least two sides of conductive electrodes **110**, **112**. The light conversion layer **120** exposes a portion of each of the conductive electrodes **110**, **112** of the LED filament, and the light conversion layer **120** includes a phosphor layer **124** and a silicon layer **125**. The phosphor layer **124** directly contacts the surfaces of the LED chip unit **102**, **104**. In the phosphors spraying process, the phosphors may be sprayed on the surfaces of the LED chip unit **102**, **104**, the copper foil **116**, the conductive electrodes **110**, **112** and the wire **140** by electrostatic spraying to form the phosphor layer **124**. Then, the vacuum coating method can be used to dispose a silicon layer **125** on the phosphor layer **124**, wherein the silicon layer **125** does not contain phosphor. The thickness of the phosphor layer **124** and the silicon layer **125** are equal or unequal. The thickness of the phosphor layer **124** and silicon layer **125** respectively is about 30 to 70 micron (um) and 30 to 50 micron (um). In another embodiment, the surfaces of the LED chip units **102**, **104**, the copper foil **116**, the conductive electrodes **110**, **112**, and the wires **140** may be covered with a transparent resin layer, and the transparent resin layer does not contain phosphors, and then covered by phosphors powder on the transparent resin layer. The thickness of the transparent resin layer and the phosphor layer are equal or unequal, and the thickness of the transparent resin layer is about 30 to 50 micron (um).

[0128] According to the structure of the LED filament **100** described above, as shown in FIG. 3, an LED filament **200** comprises a plurality of LED sections **202**, **204**, a plurality of conductive sections **230**, at least two conductive electrodes **210**, **212** and a light conversion layer **220**. The conductive section **230** is located between two adjacent LED sections **202**, **204**. The two conductive electrodes **210**, **212** are disposed on the LED filament **200** correspondingly and electrically connected to each of the LED sections **202**, **204**. The adjacent two LED sections **202**, **204** are electrically connected to each other through the conductive section **230**. Each of the LED sections **202**, **204** includes at least two LED chips that are electrically connected to each other. The light conversion layer **220** covers the LED sections **202**, **204**, the conductive sections **230** and the conductive electrodes **210**, **212**, and a part of each of the two electrodes **210**, **212** is exposed respectively. The LED filament **200** further includes a plurality of circuit films **240** (also referred to as light-transmitting circuit films). The LED chips **202** and **204** and the conductive electrodes **210** and **212** are electrically connected to each other through the circuit film **240**, and the light conversion layer **220** covers the circuit film **240**. The length of the circuit film **240** is less than the length of the conductor **230a**, or the shortest distance between two LED chips respectively located in two adjacent LED sections **202**, **204** is greater than the distance between two adjacent LED chips in the LED section **202/204**.

[0129] Referring to FIG. 4A to FIG. 4G, FIG. 4A is a schematic structural view of another embodiment of an LED filament of the present invention. As shown in FIG. 4A, the LED filament **400** has a light conversion layer **420**, LED sections **402**, **404**, conductive electrodes **410**, **412**, and a conductive section **430** for electrically connecting adjacent two LED sections **402**, **404**. Each of the LED sections **402**, **404** includes at least two LED chips **442** that are electrically connected to each other by the wires **440**. In the present embodiment, the conductive section **430** includes at least one conductor **430a** that connects the adjacent LED sections **402**, **404**, wherein the shortest distance between the two LED chips **442** respectively located in the two adjacent LED sections **402**, **404** is greater than the distance between two adjacent LED chips **442** within the one LED section **402/404**. Therefore, it is ensured that when the two LED sections **402**, **404** are bent, the conductive section **430** is not easily broken due to the stress of bending. The length of the wire **440** is less than

the length of the conductor **430a**. The light conversion layer **420** is coated on at least two sides of the LED chip **442** and conductive electrodes **410**, **412**, and a portion of each of the conductive electrodes **410**, **412** is not coated with the light conversion layer **420**. The light conversion layer **420** may have at least one top layer **420a** (or upper layer) and one base layer **420b** (or lower layer). In the present embodiment, the top layer **420a** and the base layer **420b** are disposed on the opposing surface of the LED chip **442** and conductive electrodes **410**, **412**, and a portion of each of the conductive electrodes **410**, **412** is excluded. It should be particularly noted that the thickness, diameter or width of the top layer **420a** in the LED sections **402**, **404** or the conductive section **430** described pertaining to FIG. 4A to FIG. 4G refers to the radial direction of the LED filament. The thickness of the top layer **420a** is the distance between its outer surface to the interface of the top layer **420a** and the base layer **420b**, or the distance from its outer surface and the interface of the LED chip **442** or the conductor **430a** and the base layer **420b**, wherein the outer surface of the top layer **420a** is a surface away from the base layer.

[0130] In the present embodiment, the top layer **420a** and the base layer **420b** may be composed of different particles or particle densities according to the requirements or designed structures. For example, in the case where the main emitting surface of the LED chip **442** is toward to the top layer **420a** but not the base layer **420b**, the base layer **420b** may be composed of light scattering particles to increase the light dispersion. Thereby the brightness of the base layer **420b** can be maximized, or even the brightness that can be produced close to the top layer **420a**. In addition, the base layer **420b** may also be composed of phosphor particles with high density to increase the hardness of the base layer **420b**. In the manufacturing process of the LED filament **400**, the base layer **420b** may be prepared first, and then the LED chip **442**, the wire **440** and the conductor **430a** are disposed on the base layer **420b**. Since the base layer **420b** has a hardness that can support the subsequent manufacturing process of the LED chips and the wires, therefore the yield and the firmness of the LED chips **442**, the wires **440**, and the conductors **430a** disposed on the base layer **420b** can be improved and resulted in less or even no sink or skew. Finally, the top layer **420a** is overlaid on the base layer **420b**, the LED chip **442**, the wires **440**, and the conductor **430a**.

[0131] As shown in FIG. 4B, in the present embodiment, the conductive section **430** is also located between the two adjacent LED sections **402**, **404**, and the plurality of LED chips **442** in the LED sections **402**, **404** are electrically connected to each other through the wires **440**. However, the conductor **430a** in the conductive section **430** in FIG. 4B is not in the form of a wire but in a sheet or film form. In some embodiments, the conductor **430a** can be a copper foil, a gold foil, or other materials that can conduct electrical conduction. In the present embodiment, the conductor **430a** is attached to the surface of the base layer **420b** and contact with the top layer **420a**, that is, located between the base layer **420b** and the top layer **420a**. Moreover, the conductive section **430** and the LED sections **402**, **404** are electrically connected by wires **450**, that is, the two closest LED chips **442** respectively located in the adjacent two LED sections **402**, **404** are electrically connected by the wires **450** and the conductors **430a** of the conductive section **430**. Wherein, the length of the conductive section **430** is greater than the distance between two adjacent LED chips of one LED sections **402**, **404**, and the length of the wire **440** in the LED sections **402**, **404** is less than the length of the conductor **430a**. This design ensures that the conductive section **430** has good bendability. Assuming that the maximum thickness of the LED chip in the radial direction of the filament is H, the thickness of the conductive electrode and the conductor **430a** in the radial direction of the filament is around 0.5H to 1.4H, preferably around 0.5H to 0.7H. This ensures the wire bonding process can be carried out while ensures the quality of the LED filament and the precision of the wire bonding process, thereby the LED filament has good strength and the stability of the product is improved.

[0132] As shown in FIG. 4C, in the present embodiment, the LED sections **402**, **404** and the conductive section **430** of the LED filament have different structural features. In the present embodiment, the LED sections **402**, **404** and the conductive section **430** have different widths,

thicknesses, or diameters in the radial direction of the LED filaments. As shown in FIG. 4C, the conductive section **430** is relatively thinner compared to the LED sections **402**, **404**, therefore it is helpful to the LED filament curling to various curves. In the present embodiment, the base layer **420b** is substantially uniform in width, thickness or diameter in the radial direction of the LED filament, whether in the LED sections **402**, **404** or in the conductive section **430**. And, the top layer **420a** has different widths, thicknesses or diameters in the radial direction of the LED filaments for the LED section **402**, **404** and the conductive section **430**. As shown in FIG. 4C, the top layer **420a** of the LED sections **402**, **404** has a maximum diameter D2 in the radial direction of the LED filament, while the top layer **420a** of the conductive section **430** has the largest diameter D1 in the radial direction of the LED filament, D2 will be greater than D1. The diameter of the top layer **420a** is gradually reduced from the LED sections **402**, **404** toward to the conductive section **430**, and is gradually increased from the conductive section **430** toward to adjacent LED sections **402**, **404**, so that the top layer **420a** is conformably covered the LED filament and forms a smooth concave-convex curve along the axial direction of the LED filament.

[0133] As shown in FIG. 4D, in the present embodiment, the top layer **420a** of the LED sections **402**, **404** has the largest diameter (or maximum thickness) in the radial direction of the LED filament and the diameter of the top layer **420a** is gradually reduced from the LED sections **402**, **404** to the conductive section **430**, and a portion of the conductor **430a** (for example, the intermediate portion) is not covered by the top layer **420a**. The base layer **420b**, whether in the LED sections **402**, **404** or in the conductive section **430**, has substantially the same width, thickness or diameter in the radial direction of the LED filament. In the present embodiment, the number of LED chips **442** in each of the LED sections **402**, **404** may be different. For example, some LED sections **402**, **404** have only one LED chip **442**, and some LED sections **402**, **404** have two or more LED chips **442**. In addition to the number of the LED chip **442** designing in each LED section **402**, **402** is different, the types of the LED chip **442** may also be different. It is acceptable as well that the number of the LED chip **442** designing in each LED section **402**, **402** is consistent, and the types of the LED chip **442** is different.

[0134] As shown in FIG. 4E, in the present embodiment, the top layer **420a** is substantially uniform in width, thickness or diameter in the radial direction of the LED filament, whether in the LED sections **402**, **404** or in the conductive section **430**. A portion of the base layer **420b** has been recessed or hollowed out corresponding to a portion of at least one conductor **430a**, for example, the intermediate portion of the at least one conductor **430a** is not covered by the base layer **420b**, and at least one of the other conductors **430a** is completely covered by the base layer **420b**.

[0135] As shown in FIG. 4F, in the present embodiment, the top layer **420a** is substantially uniform in width, thickness or diameter in the radial direction of the LED filament, whether in the LED sections **402**, **404** or in the conductive section **430**. A portion of the base layer **420b** has been recessed or hollowed out corresponding to a portion of each conductor **430a**, for example, the intermediate portion of the conductor **430a** is not covered by the base layer **420b**.

[0136] As shown in FIG. 4G, in the present embodiment, the top layer **420a** of the LED sections **402**, **404** has the largest diameter in the radial direction of the LED filament, and the diameter of the top layer **420a** is gradually decreased from the LED sections **402**, **404** to the conductive section **430**. Moreover, a portion of the conductor **430a** (for example, the middle portion) is not covered by the top layer **420a**, and a portion of the base layer **420b** is recessed or hollowed out such that a portion of the conductor **430a** (for example, the intermediate portion) is not covered by the base layer **420b**. In other words, at least a portion of the conductor **430a** at the opposite sides thereof are not covered by the top layer **420a** and the base layer **420b**, respectively.

[0137] As described above with respect to the embodiments of FIG. 4E to FIG. 4G, when the base layer **420b** has a recession region or hollow region corresponding to a part of or all of the conductive sections **430**, and the recession region or the hollow region may be in the form of a slit or a groove. Therefore, the conductor **430a** is not completely exposed and the conductive section

430 can be provided with better bendability.

[0138] FIG. 5 illustrates another embodiment of an LED filament layered structure. In the present embodiment, the LED sections **402**, **404**, the gold wires **440**, and the top layer **420a** are disposed on both sides of the base layer **420b**, that is, the base layer **420b** is located between the two top layers **420a**. The conductive electrodes **410**, **412** are respectively disposed at both ends of the base layer **420b**. As shown in the figure, the LED sections **402**, **404** in the upper and lower top layers **420a** can be connected to the same conductive electrode **410/412** by gold wires **440**, in this way, the light ray distribution can be more uniform. Moreover, the gold wire **440** may be bent with posture to reduce the impact force, the posture may be, for example, slightly M-shape, curve or straight shape.

[0139] FIG. 6 illustrates another embodiment of the LED filament layered structure of the present invention. As shown in FIG. 6, the light conversion layer of LED filament **400** includes a top layer **420a** and a base layer **420b**. Each side of the LED sections **402**, **404** is in direct contact with the top layer **420a**, and the base layer **420b** is not in contact with the LED sections **402**, **404**. In the manufacturing process, the base layer **420b** can be formed in advance, and the LED sections **402**, **404** and the top layer **420a** are formed successively.

[0140] In another embodiment, as shown in FIG. 7, the base layer **420b** of the LED filament **400** is formed with a wavy surface accompanying undulations, then the LED sections **402**, **404** are disposed thereon and consequently are inclined to different directions. Thus, the LED filament has a broader light emitting angle. That is to say, from the side view, the LED sections are arranged with different angles with respect to the horizontal plane rather than in parallel to the horizontal plane, wherein the horizontal plane is defined by the interface of the bottom surface of the base layer and the surface of the carrier, and the carrier is used to provide the supporting in the manufacturing process. Furthermore, the configured height/angle/direction between each LED section can also be different. In other words, a plurality of LED sections are connected in series and not aligning in a straight line. In this way, the filament **400** has the effect of increasing the emitting angle and the uniformity of the light without being bent or curved.

[0141] In the LED filament structure as shown in FIG. 8, the filament **400** includes at least one LED section **402**, **404**, at least one pair of conductive electrodes **410**, **412**, a plurality of gold wires **440**, a light conversion layer **420**, and at least one conductive section **430** electrically connecting the two adjacent LED sections **402**, **404**. Wherein each of the LED sections **402**, **404** includes at least two LED chips **142** that are electrically connected to each other by wires **440**. The light conversion layer **420** includes a base layer **420a** and a top layer **420b**, and a copper foil **460** having a plurality of openings is attached to the base layer **420a**. The upper surface of the copper foil **460** may further have a silver plating layer **461**, and the copper foil located at each end of the LED filament as a conductive electrode **410**, **412** and extending beyond the light conversion layer **420**. Subsequently, the LED sections **402**, **404** can be disposed to the base layer **420a** by means of die bond paste or the like. Thereafter, a phosphor glue or phosphor film is applied to coat the LED sections **402**, **404**, gold wire **440**, conductive section **430**, and a portion of the conductive electrodes **410**, **412** to form a light conversion layer **420**. The width or/and length of the opening of the copper foil **460** is greater than that of the LED chip **442**, defining the position of the LED chip. At least two of the six faces of the LED chip, generally five faces in the present embodiment, being covered by the phosphor glue. In the present embodiment, the combination of copper foil **460** and the gold wire **440** provides a solid conductive structure and also maintaining the flexibleness of the LED filament. Besides, the silver plating layer **461** has an effect of increasing light reflection in addition to good electrical conductivity.

[0142] In the LED filament package structure as shown in FIG. 9, the LED filament **400** is similar to the LED filament disclosed in FIG. 8, and the difference is that: (1) the LED chip **442** used for the filament **400** is a flip chip having the same solder pad height, wherein the solder pad is directly connected to the silver plating layer **461**; (2) the length of the opening of the LED filament

described aforementioned (that is, the length in the axial direction of the LED filament) must be greater than the LED chip **442** in order to accommodate the LED chip **442**, furthermore, the LED chip **442** of the LED filament in the present embodiment is located corresponding to the opening **432** and above the copper foil **460**/silver plating layer **461**, therefore the length of the LED chip **442** is greater than the opening **432**. The present embodiment omits the step of gold wire bonding in compared to the previous embodiment.

[0143] The LED filament structures as shown in FIG. **9** can be employed. The feature of the LED filament structure is that the LED chip is used as flip-chip configuration, that is, the original height of the different solder pads is processed to the same height, usually the lower N-pole extension is processed to the same height as the P-pole.

[0144] The connection mode between the conductor in the conductive section and the light conversion layer is described as follows. Referring to FIG. **10**, in the LED filament structure shown in FIG. **10**, the LED filament **400** has a light conversion layer **420**, the LED sections **402**, **404**, the conductive electrodes **410**, **412**, and at least one conductive section **430**. The conductive section **430** is located between adjacent LED sections **402** and **404**. The LED sections **402** and **404** include at least two LED chips **442** electrically connected to each other through the wires **440**. In the present embodiment, the conductive section **430** includes a conductor **430a**. The conductive section **430** and the LED sections **402**, **404** are electrically connected by wires **450**, that is, two LED chips respectively located in the adjacent two LED sections **402**, **404** and closest to the conductive section **430** are electrically connected to each other through the wires **450** connecting with the conductor **430a** in the conductive section **430**. The length of the conductive section **430** is greater than the distance between two adjacent LED chips in one single LED sections **402**, **404**, and the length of the wire **440** is less than the length of the conductor **430a**. The light conversion layer **420** is disposed on at least one side of the LED chip **442** and the conductive electrode **410**, **412**, and a part of the two conductive electrodes is exposed from the light conversion layer. The light conversion layer **420** includes at least a top layer **420a** and a base layer **420b**. In the present embodiment, the LED sections **402**, **404**, the conductive electrodes **410**, **412**, and the conductive section **430** are all attached to the base layer **420b**.

[0145] The conductor **430a** can be a copper foil or other electrically conductive material. The upper surface of the conductor **430a** may further have a silver plating layer, and subsequently, the LED chip **442** may be attached to the base layer **420b** by means of die bond paste or the like. Thereafter, a phosphor glue or phosphor film is applied to coat over the LED chip **442**, the wires **440**, **450**, and a portion of the conductive electrodes **410**, **412** to form a light conversion layer **420**. At least two of the six faces of the LED chip, generally five faces in the present embodiment, being covered by the phosphor glue. The wires **440**, **450** may be gold wires. In the present embodiment, the combination of copper foil **460** and the gold wire **440** provides a solid conductive structure and also maintaining the flexibility of the LED filament. Besides, the silver plating layer **461** has an effect of increasing light reflection in addition to good electrical conductivity.

[0146] The structure as shown in FIG. **11** discloses a copper foil **460** is disposed between the two LED chips **442**, and a silver plating layer **461** is disposed on the copper foil. The copper foil **460** is electrically connected to the LED chips **442** through the wire **440**.

[0147] The structure as shown in FIG. **12** discloses: (1) the LED chip used for the LED filament is a flip chip having the same solder pad height and the solder pad is directly connected to the silver plating layer; (2) the length of the aforementioned opening (e.g., opening **432** in FIG. **9**) of the LED filament in the longitudinal direction of the LED filament must be greater than the length of the LED chip to accommodate the LED chip, and the LED chip **442** of the LED filament of the present embodiment corresponds to the opening **432** is located above the copper foil **460** and the silver plating layer **461**, so the length of the LED chip **442** is greater than the length of the opening.

[0148] According to the aforementioned embodiments of the present invention, since the LED filament structure is provided with at least one LED section and at least one conductive section,

when the LED filament is bent, the stress is easily concentrated on the conductive section. Therefore, the breakage probability of the gold wire connected between the adjacent LED chips is reduced during bending. Thereby, the quality of the LED filament and its application is improved. In addition, the conductive section employs a copper foil structure, which reduces the length of the metal wire bonding and further reduces the breakage probability of the metal wire during bonding. In other embodiments of the invention, in order to improve the bendability of the conductive section, and further prevent the conductor from damaged when the LED filament is bent. The conductor in the LED filament conductive section may be in a shape of “M” or wave profile for providing better flexibility in extending of the LED filament.

[0149] Next, a chip bonding design relating to an LED filament will be described. FIG. 13A is a top view of an embodiment of the LED filament **300** in an unbent state in accordance with the present invention. The LED filament **300** includes a plurality of LED chip units **302**, **304**, a conductor **330a**, and at least two conductive electrodes **310**, **312**. The LED chip units **302** and **304** may be a single LED chip, or may include a plurality of LED chips, that is, equal to or greater than two LED chips.

[0150] The conductor **330a** is located between the adjacent two LED chip units **302**, **304**, the LED chip units **302**, **304** are at different positions in the Y direction, and the conductive electrodes **310**, **312** are disposed corresponding to the LED chip units **302**, **304** and electrically connected to the LED chip units **302** and **304** through the wires **340**. The adjacent two LED chip units **302** and **304** are electrically connected to each other through the conductor **330a**. The angle between the conductor **330a** and the LED filament in the longitudinal direction (X direction) is 30° to 120° , preferably 60° to 120° . In the related art, the direction of the conductor **330a** is parallel to the X direction, and the internal stress acting on the cross sectional area of the conductor is large when the filament is bent at the conductor. Therefore, the conductor **330a** is disposed at a certain angle with the X direction and it can effectively reduce the internal stress thereof. The wire **340** is at an angle, parallel, vertical or any combination with the X direction. In the embodiment, the LED filament **300** includes two wires **340**, one wire **340** is parallel to the X direction, and the other wire **340** has an angle of 30° to 120° with respect to the X direction. The LED filament **300** emits light after its conductive electrodes **310**, **312** are powered with voltage source or current source.

[0151] FIG. 13B to FIG. 13D show the case where the conductor **330a** is 90° with respect to the X direction, that is, the conductor **330a** is perpendicular to the X direction, which can reduce the internal stress on the conductor cross sectional area when the filament is bent. In some embodiment the wire **340** both in parallel and vertically with respect to the X direction are combined in an LED filament, as shown in FIG. 13B, the LED filament **300** includes two wires **340**, one wire **340** being parallel to the X direction and the other wire **340** being perpendicular to the X direction.

[0152] As shown in FIG. 13C, the difference from the embodiment shown in FIG. 13B is that the wire **340** is perpendicular to the X direction, and the bendability duration between the conductive electrodes **310**, **312** and the LED chip units **302**, **304** is improved. Further, since the conductor **330a** and the wire **340** are simultaneously arranged to be perpendicular to the X direction, the LED filament can have good bendability at any position.

[0153] FIG. 13E is a top view of the LED filament **300** in an unbent state in accordance with one embodiment of the present invention. FIG. 13E differs from the embodiment shown in FIG. 13C is that, in the X direction, the LED chip unit **304** is between two adjacent LED chip units **302**, and no overlap with the LED chip unit **302** in the projection in the Y direction, so that when the LED filament is bent at the conductor **330a**, the LED chip is not damaged, thereby improving the stability of the LED light bulb product quality.

[0154] FIG. 13F is a top view showing an embodiment of the LED filament **300** in an unbent state. In the present embodiment, the LED chip units **302** and **304** are single LED chips, and the width of the LED chip units **302** and **304** is parallel to the X direction. Preferably, the LED chip units **302** and **304** are at substantially the same position in the Y direction, so that the overall width of the

LED filament **300** is smaller, thereby shortening the heat dissipation path of the LED chip and improving the thermal dissipation effect. The adjacent two LED chip units **302** and **304** are connected by a conductor **330a**, and the angle between the conductor **330a** and the X direction is 30° to 120° , which reduces the internal stress on the cross sectional area of the wire and also improves the bendability of the wire when the LED filament **300** is bent. In other embodiments, the LED chip unit longitudinally may have an angle with the X direction as the conductor **330a**, which may further reduce the overall width of the LED filament **300**.

[0155] When the wire bonding process of the face up chip is carried out along the x direction, for example, the bonding wire and the bonding conductor are gold wires, the quality of the bonding wire is mainly determined by the stress at the five points A, B, C, D, and E as shown in FIG. **14**. The point A is the junction of the soldering pad **4401** and the gold ball **4403**, point B is the junction of the gold ball **4403** and the gold wire **440**, point C is between the two segments of the gold wire **440**, point D is the gold wire **440** and the two solder butted joints **4402**, and the point E is between the two solder butted joints **4402** and the surface of the chip **442**. Because of point B is the first bending point of the gold wire **440**, and the gold wire **440** at the point D is thinner, thus gold wire **440** is frangible at points B and D. So that, for example, in the implementation of the structure of the LED filament **300** package, the top layer **420a** needs to cover points B, C and D. If one of the six faces of the LED chip **442** farthest from the base layer **420b** is defined as the upper surface of the LED chip **442**, the distance from the upper surface of the LED chip **442** to the surface of the top layer **420a** is in a range of around 100 to 200 μm .

[0156] The LED filament structure in the aforementioned embodiments is mainly applicable to the LED light bulb product, so that the LED light bulb can achieve the omni-directional light illuminating effect through the flexible bending characteristics of the single LED filament. The specific embodiment in which the aforementioned LED filament applied to the LED light bulb is further explained below.

[0157] Please refer to FIG. **15A**. FIG. **15A** illustrates a perspective view of an LED light bulb according to the third embodiment of the present disclosure. According to the third embodiment, the LED light bulb **20c** comprises a lamp housing **12**, a bulb base **16** connected with the lamp housing **12**, two conductive supports **51a**, **51b** disposed in the lamp housing **12**, a driving circuit **518** electrically connected with both the conductive supports **51a**, **51b** and the bulb base **16**, a stem **19**, supporting arms **15** and a single LED filament **100**.

[0158] The lamp housing **12** is a material which is preferably light transmissive or thermally conductive, such as, glass or plastic, but not limited thereto. In implementation, the lamp housing **12** may be doped with a golden yellow material or its surface coated with a yellow film to absorb a portion of the blue light emitted by the LED chip to reduce the color temperature of the light emitted by the LED light bulb **20c**. In other embodiments of the present invention, the lamp housing **12** includes a layer of luminescent material (not shown), which may be formed on the inner surface or the outer surface of the lamp housing **12** according to design requirements or process feasibility, or even integrated in the material of the lamp housing **12**. The luminescent material layer comprises low reabsorption semiconductor nanocrystals (hereinafter referred to as quantum dots), the quantum dots comprises a core, a protective shell and a light absorbing shell, and the light absorbing shell is disposed between the core and the protective shell. The core emits the emissive light with emission wavelength, and the light absorbing shell emits the excited light with excitation wavelength. The emission wavelength is longer than the excitation wavelength, and the protective shell provides the stability of the light.

[0159] The LED filament **100** shown in FIG. **15A** is bent to form a contour resembling to a circle while being observed from the top view of FIG. **15A**. According to the embodiment of FIG. **15A**, the LED filament **100** is bent to form a wave shape from side view. The shape of the LED filament **100** is novel and makes the illumination more uniform. In comparison with a LED bulb having multiple LED filaments, single LED filament **100** has less connecting spots. In implementation,

single LED filament **100** has only two connecting spots such that the probability of defect soldering or defect mechanical pressing is decreased.

[0160] The stem **19** has a stand **19a** extending to the center of the bulb shell **12**. The stand **19a** supports the supporting arms **15**. The first end of each of the supporting arms **15** is connected with the stand **19a** while the second end of each of the supporting arms **15** is connected with the LED filament **100**.

[0161] Please refer to FIG. **15B** which illustrates an enlarged cross-sectional view of the dashed-line circle of FIG. **15A**. The second end of each of the supporting arms **15** has a clamping portion **15a** which clamps the body of the LED filament **100**. The clamping portion **15a** may, but not limited to, clamp at either the wave crest or the wave trough. Alternatively, the clamping portion **15a** may clamp at the portion between the wave crest and the wave trough. The shape of the clamping portion **15a** may be tightly fitted with the outer shape of the cross-section of the LED filament **100**. The dimension of the inner shape (through hole) of the clamping portion **15a** may be a little bit smaller than the outer shape of the cross-section of the LED filament **100**. During manufacturing process, the LED filament **100** may be passed through the inner shape of the clamping portion **15a** to form a tight fit. Alternatively, the clamping portion **15a** may be formed by a bending process. Specifically, the LED filament **100** may be placed on the second end of the supporting arm **15** and a clamping tooling is used to bend the second end into the clamping portion to clamp the LED filament **100**.

[0162] The supporting arms **15** may be, but not limited to, made of carbon steel spring to provide with adequate rigidity and flexibility so that the shock to the LED light bulb caused by external vibrations is absorbed and the LED filament **100** is not easily to be deformed. Since the stand **19a** extending to the center of the bulb shell **12** and the supporting arms **15** are connected to a portion of the stand **19a** near the top thereof, the position of the LED filaments **100** is at the level close to the center of the bulb shell **12**. Accordingly, the illumination characteristics of the LED light bulb **20c** are close to that of the traditional light bulb including illumination brightness. The illumination uniformity of LED light bulb **20c** is better. In the embodiment, at least a half of the LED filaments **100** is around a center axle of the LED light bulb **20c**. The center axle is coaxial with the axle of the stand **19a**.

[0163] In the embodiment, the first end of the supporting arm **15** is connected with the stand **19a** of the stem **19**. The clamping portion of the second end of the supporting arm **15** is connected with the outer insulation surface of the LED filaments **100** such that the supporting arms **15** are not used as connections for electrical power transmission. In an embodiment where the stem **19** is made of glass, the stem **19** would not be cracked or exploded because of the thermal expansion of the supporting arms **15** of the LED light bulb **20c**. Additionally, there may be no stand in an LED light bulb. The supporting arm **15** may be fixed to the stem or the bulb shell directly to eliminate the negative effect to illumination caused by the stand.

[0164] The supporting arm **15** is thus non-conductive to avoid a risk that the glass stem **19** may crack due to the thermal expansion and contraction of the metal filament in the supporting arm **15** under the circumstances that the supporting arm **15** is conductive and generates heat when current passes through the supporting arm **15**.

[0165] In different embodiments, the second end of the supporting arm **15** may be directly inserted inside the LED filament **100** and become an auxiliary piece in the LED filament **100**, which can enhance the mechanical strength of the LED filament **100**. Relative embodiments are described later.

[0166] The inner shape (the hole shape) of the clamping portion **15a** fits the outer shape of the cross section of the LED filament **100**; therefore, based upon a proper design, the cross section of the LED filament **100** may be oriented to face towards a predetermined orientation. For example, as shown in FIG. **15B**, the LED filament **100** comprises a top layer **420a**, LED chips **104**, and a base layer **420b**. The LED chips **104** are aligned in line along the axial direction (or an elongated

direction) of the LED filament **100** and are disposed between the top layer **420a** and the base layer **420b**. The top layer **420a** of the LED filament **100** is oriented to face towards ten o'clock in FIG. **15B**. A lighting face of the whole LED filament **100** may be oriented to face towards the same orientation substantially to ensure that the lighting face of the LED filament **100** is visually identical. The LED filament **100** comprises a main lighting face **Lm** and a subordinate lighting face **Ls** corresponding to the LED chips. If the LED chips in the LED filament **100** are wire bonded and are aligned in line, a face of the top layer **420a** away from the base layer **420b** is the main lighting face **Lm**, and a face of the base layer **420b** away from the top layer **420a** is the subordinate lighting face **Ls**. The main lighting face **Lm** and the subordinate lighting face **Ls** are opposite to each other. When the LED filament **100** emits light, the main lighting face **Lm** is the face through which the largest amount of light rays passes, and the subordinate lighting face **Ls** is the face through which the second largest amount of light rays passes. In the embodiment, there is, but is not limited to, a conductive foil **530** formed between the top layer **420a** and the base layer **420b**, which is utilized for electrical connection between the LED chips. In the embodiment, the LED filament **100** wriggles with twists and turns while the main lighting face **Lm** is always towards outside. That is to say, any portion of the main lighting face **Lm** is towards the bulb shell **12** or the bulb base **16** and is away from the stem **19** at any angle, and the subordinate lighting face **Ls** is always towards the stem **19** or towards the top of the stem **19** (the subordinate lighting face **Ls** is always towards inside).

[0167] The LED filament **100** shown in FIG. **15A** is curved to form a circular shape in a top view while the LED filament is curved to form a wave shape in a side view. The wave shaped structure is not only novel in appearance but also guarantees that the LED filament **100** illuminates evenly. In the meantime, the single LED filament **100**, comparing to multiple LED filaments, requires less joint points (e.g., pressing points, fusing points, or welding points) for being connected to the conductive supports **51a**, **51b**. In practice, the single LED filament **100** (as shown in FIG. **15A**) requires only two joint points respectively formed on the two conductive electrodes, which effectively lowers the risk of fault welding and simplifies the process of connection compared to the mechanically connection in the tightly pressing manner.

[0168] Please refer to FIG. **15C**. FIG. **15C** is a projection of a top view of an LED filament of the LED light bulb **20c** of FIG. **15A**. As shown in FIG. **15C**, in an embodiment, the LED filament may be curved to form a wave shape resembling a circle observed in a top view to surround the center of the light bulb or the stem. In different embodiments, the LED filament observed in the top view can form a quasi-circle or a quasi U shape.

[0169] As shown in FIG. **15B** and FIG. **15C**, the LED filament **100** surrounds with the wave shape resembling a circle and has a quasi-symmetric structure in the top view, and the lighting face of the LED filament **100** is also symmetric, e.g., the main lighting face **Lm** in the top view may face outwardly; therefore, the LED filament **100** may generate an effect of an omnidirectional light due to a symmetry characteristic with respect to the quasi-symmetric structure of the LED filament **100** and the arrangement of the lighting face of the LED filament **100** in the top view. Whereby, the LED light bulb **20c** as a whole may generate an effect of an omnidirectional light close to a 360 degrees illumination. Additionally, the two joint points may be close to each other such that the conductive supports **51a**, **51b** are substantially below the LED filament **100**. Visually, the conductive supports **51a**, **51b** keeps a low profile and is integrated with the LED filament **100** to show an elegance curvature.

[0170] Please refer to FIG. **16A** and FIG. **16B**. FIG. **16A** is a perspective view of an LED light bulb according to an embodiment of the present invention. FIG. **16B** is a front view (or a side view) of an LED light bulb of FIG. **16A**. The LED light bulb **20d** shown in FIG. **16A** and FIG. **16B** is analogous to the LED light bulb **20c** shown in FIG. **15A**. As shown in FIG. **16A** and FIG. **16B**, the LED light bulb **20d** comprises a bulb shell **12**, a bulb base **16** connected to the bulb shell **12**, two conductive supports **51a**, **51b** disposed in the bulb shell **12**, supporting arms **15**, a stem **19**, and one

single LED filament **100**. The stem **19** comprises a stem bottom and a stem top opposite to each other. The stem bottom is connected to the bulb base **16**. The stem top extends to inside of the bulb shell **12** (e.g., extending to the center of the bulb shell **12**) along an elongated direction of the stem **19**. For example, the stem top may be substantially located at a center of the inside of the bulb shell **12**. In the embodiment, the stem **19** comprises the stand **19a**. Herein the stand **19a** is deemed as a part of the whole stem **19** and thus the top of the stem **19** is the same as the top of the stand **19a**. The two conductive supports **51a**, **51b** are connected to the stem **19**. The LED filament **100** comprises a filament body and two conductive electrodes **506**. The two conductive electrodes **506** are at two opposite ends of the filament body. The filament body is the part of the LED filament **100** without the conductive electrodes **506**. The two conductive electrodes **506** are respectively connected to the two conductive supports **51a**, **51b**. The filament body is around the stem **19**. An end of the supporting arm **15** is connected to the stem **19** and another end of the supporting arm **15** is connected to the filament body.

[0171] Please refer to FIG. **16C**. FIG. **16C** is a top view of the LED light bulb **20d** of FIG. **16A**. As shown in FIG. **16B** and FIG. **16C**, the filament body comprises a main lighting face **Lm** and a subordinate lighting face **Ls**. Any portion of the main lighting face **Lm** is towards the bulb shell **12** or the bulb base **16** at any angle, and any portion of the subordinate lighting face **Ls** is towards the stem **19** or towards the top of the stem **19**, i.e., the subordinate lighting face **Ls** is towards inside of the LED light bulb **20d** or towards the center of the bulb shell **12**. In other words, when a user observes the LED light bulb **20d** from outside, the user would see the main lighting face **Lm** of the LED filament **100d** at any angle. Based upon the configuration, the effect of illumination is better.

[0172] According to different embodiments, the LED filament **100** in different LED light bulbs (e.g., the LED light bulb **20a**, **20b**, **20c**, or **20d**) may be formed with different shapes or curves while all of the LED filaments **100** are configured to have symmetry characteristic. The symmetry characteristic has the benefit of creating an even, wide distribution of light rays, so that the LED light bulb is capable of generating an omnidirectional light effect. The symmetry characteristic of the LED filament **100** is discussed below.

[0173] The definition of the symmetry characteristic of the LED filament **100** may be based on four quadrants defined in a top view of an LED light bulb. The four quadrants may be defined in a top view of an LED light bulb (e.g., the LED light bulb **20c** shown in FIG. **15A**), and the origin of the four quadrants may be defined as a center of a stem/stand of the LED light bulb in the top view (e.g., a center of the top of the stand **19a** shown in FIG. **15A**). The LED filament of the LED light bulb (e.g., the LED filament **100** shown in FIG. **15A**) in the top view may be presented as an annular structure, shape or, contour. The LED filament presented in the four quadrants in the top view may be symmetric.

[0174] For example, the brightness presented by a portion of the LED filament in the first quadrant in the top view is symmetric with that presented by a portion of the LED filament in the second quadrant, in the third quadrant, or in the fourth quadrant in the top view while the LED filament operates. In some embodiments, the structure of a portion of the LED filament in the first quadrant in the top view is symmetric with that of a portion of the LED filament in the second quadrant, in the third quadrant, or in the fourth quadrant in the top view.

[0175] In addition, an emitting direction of a portion of the LED filament in the first quadrant in the top view is symmetric with that of a portion of the LED filament in the second quadrant, in the third quadrant, or in the fourth quadrant in the top view.

[0176] In another embodiment, an arrangement of LED chips in a portion of the LED filament in the first quadrant (e.g., a density variation of the LED chips in the portion of the LED filament in the first quadrant) in the top view is symmetric with an arrangement of LED chips in a portion of the LED filament in the second quadrant, in the third quadrant, or in the fourth quadrant in the top view.

[0177] In another embodiment, a power configuration of LED chips with different power in a

portion of the LED filament in the first quadrant in the top view is symmetric with a power configuration of LED chips with different power in a portion of the LED filament in the second quadrant, in the third quadrant, or in the fourth quadrant in the top view.

[0178] In another embodiment, refractive indexes of segments of a portion of the LED filament in the first quadrant in the top view are symmetric with refractive indexes of segments of a portion of the LED filament in the second quadrant, in the third quadrant, or in the fourth quadrant in the top view while the segments may be defined by distinct refractive indexes.

[0179] In another embodiment, surface roughness of segments of a portion of the LED filament in the first quadrant in the top view are symmetric with surface roughness of segments of a portion of the LED filament in the second quadrant, in the third quadrant, or in the fourth quadrant in the top view while the segments may be defined by distinct surface roughness.

[0180] The LED filament presented in the four quadrants in the top view may be in point symmetry (e.g., being symmetric with the origin of the four quadrants) or in line symmetry (e.g., being symmetric with one of the two axis the four quadrants).

[0181] A tolerance (a permissible error) of the symmetric structure of the LED filament in the four quadrants in the top view may be up to 20%-50%. For example, in a case that the structure of a portion of the LED filament in the first quadrant is symmetric with that of a portion of the LED filament in the second quadrant, a designated point on portion of the LED filament in the first quadrant is defined as a first position, a symmetric point to the designated point on portion of the LED filament in the second quadrant is defined as a second position, and the first position and the second position may be exactly symmetric or be symmetric with 20%-50% difference.

[0182] In addition, a length of a portion of the LED filament in one of the four quadrants in the top view is substantially equal to that of a portion of the LED filament in another one of the four quadrants in the top view. The lengths of portions of the LED filament in different quadrants in the top view may also have 20%-50% difference.

[0183] The definition of the symmetry characteristic of the LED filament **100** may be based on four quadrants defined in a side view, in a front view, or in a rear view of an LED light bulb. In the embodiments, the side view may include a front view or a rear view of the LED light bulb. The four quadrants may be defined in a side view of an LED light bulb (e.g., the LED light bulb **20c** shown in FIG. **15A**). In such case, an elongated direction of a stand (or a stem) from the bulb base **16** towards a top of the bulb shell **12** away from the bulb base **16** may be defined as the Y-axis, and the X-axis may cross a middle of the stand (e.g., the stand **19a** of the LED light bulb **20c** shown in FIG. **15A**) while the origin of the four quadrants may be defined as the middle of the stand. In different embodiment, the X-axis may cross the stand at any point, e.g., the X-axis may cross the stand at the top of the stand, at the bottom of the stand, or at a point with a certain height (e.g., 2/3 height) of the stand.

[0184] In addition, portions of the LED filament presented in the first quadrant and the second quadrant (the upper quadrants) in the side view may be symmetric (e.g., in line symmetry with the Y-axis) in brightness, and portions of the LED filament presented in the third quadrant and the fourth quadrant (the lower quadrants) in the side view may be symmetric (e.g., in line symmetry with the Y-axis) in brightness; however, the brightness of the portions of the LED filament presented in the upper quadrants in the side view may be asymmetric with that of the portions of the LED filament presented in the lower quadrants in the side view.

[0185] In some embodiments, portions of the LED filament presented in the first quadrant and the second quadrant (the upper quadrants) in the side view may be symmetric (e.g., in line symmetry with the Y-axis) in structure; portions of the LED filament presented in the third quadrant and the fourth quadrant (the lower quadrants) in the side view may be symmetric (e.g., in line symmetry with the Y-axis) in structure. In addition, an emitting direction of a portion of the LED filament in the first quadrant in the side view is symmetric with that of a portion of the LED filament in the second quadrant in the side view, and an emitting direction of a portion of the LED filament in the

third quadrant in the side view is symmetric with that of a portion of the LED filament in the fourth quadrant in the side view.

[0186] In another embodiment, an arrangement of LED chips in a portion of the LED filament in the first quadrant in the side view is symmetric with an arrangement of LED chips in a portion of the LED filament in the second quadrant in the side view, and an arrangement of LED chips in a portion of the LED filament in the third quadrant in the side view is symmetric with an arrangement of LED chips in a portion of the LED filament in the fourth quadrant in the side view.

[0187] In another embodiment, a power configuration of LED chips with different power in a portion of the LED filament in the first quadrant in the side view is symmetric with a power configuration of LED chips with different power in a portion of the LED filament in the second quadrant in the side view, and a power configuration of LED chips with different power in a portion of the LED filament in the third quadrant in the side view is symmetric with a power configuration of LED chips with different power in a portion of the LED filament in the fourth quadrant in the side view.

[0188] In another embodiment, refractive indexes of segments of a portion of the LED filament in the first quadrant in the side view are symmetric with refractive indexes of segments of a portion of the LED filament in the second quadrant in the side view, and refractive indexes of segments of a portion of the LED filament in the third quadrant in the side view are symmetric with refractive indexes of segments of a portion of the LED filament in the fourth quadrant in the side view while the segments may be defined by distinct refractive indexes.

[0189] In another embodiment, surface roughness of segments of a portion of the LED filament in the first quadrant in the side view are symmetric with surface roughness of segments of a portion of the LED filament in the second quadrant in the side view, and surface roughness of segments of a portion of the LED filament in the third quadrant in the side view are symmetric with surface roughness of segments of a portion of the LED filament in the fourth quadrant in the side view while the segments may be defined by distinct surface roughness.

[0190] Additionally, the portions of the LED filament presented in the upper quadrants in the side view may be asymmetric with the portions of the LED filament presented in the lower quadrants in the side view in brightness. In some embodiments, the portion of the LED filament presented in the first quadrant and the fourth quadrant in the side view is asymmetric in structure, in length, in emitting direction, in arrangement of LED chips, in power configuration of LED chips with different power, in refractive index, or in surface roughness, and the portion of the LED filament presented in the second quadrant and the third quadrant in the side view is asymmetric in structure, in length, in emitting direction, in arrangement of LED chips, in power configuration of LED chips with different power, in refractive index, or in surface roughness. In order to fulfill the illumination purpose and the requirement of omnidirectional lamps, light rays emitted from the upper quadrants (the portion away from the bulb base **16**) in the side view should be greater than those emitted from the lower quadrants (the portion close to the bulb base **16**). Therefore, the asymmetric characteristic of the LED filament of the LED light bulb between the upper quadrants and the lower quadrants in the side view may contribute to the omnidirectional requirement by concentrating the light rays in the upper quadrants.

[0191] A tolerance (a permissible error) of the symmetric structure of the LED filament in the first quadrant and the second quadrant in the side view may be 20%-50%. For example, a designated point on portion of the LED filament in the first quadrant is defined as a first position, a symmetric point to the designated point on portion of the LED filament in the second quadrant is defined as a second position, and the first position and the second position may be exactly symmetric or be symmetric with 20%-50% difference.

[0192] In addition, a length of a portion of the LED filament in the first quadrant in the side view is substantially equal to that of a portion of the LED filament in the second quadrant in the side view. A length of a portion of the LED filament in the third quadrant in the side view is substantially

equal to that of a portion of the LED filament in the fourth quadrant in the side view. However, the length of the portion of the LED filament in the first quadrant or the second quadrant in the side view is different from the length of the portion of the LED filament in the third quadrant or the fourth quadrant in the side view. In some embodiment, the length of the portion of the LED filament in the third quadrant or the fourth quadrant in the side view may be less than that of the portion of the LED filament in the first quadrant or the second quadrant in the side view. The lengths of portions of the LED filament in the first and the second quadrants or in the third and the fourth quadrants in the side view may also have 20%-50% difference.

[0193] Please refer to FIG. 16D. FIG. 16D is the LED filament **100** shown in FIG. 16B presented in two dimensional coordinate system defining four quadrants. The LED filament **100** in FIG. 16D is the same as that in FIG. 16B, which is a front view (or a side view) of the LED light bulb **20d** shown in FIG. 2A. As shown in FIG. 2B and FIG. 2D, the Y-axis is aligned with the stand **19a** of the stem (i.e., being along the elongated direction of the stand **19a**), and the X-axis crosses the stand **19a** (i.e., being perpendicular to the elongated direction of the stand **19a**). As shown in FIG. 16D, the LED filament **100** in the side view can be divided into a first portion **100p1**, a second portion **100p2**, a third portion **100p3**, and a fourth portion **100p4** by the X-axis and the Y-axis. The first portion **100p1** of the LED filament **100** is the portion presented in the first quadrant in the side view. The second portion **100p2** of the LED filament **100** is the portion presented in the second quadrant in the side view. The third portion **100p3** of the LED filament **100** is the portion presented in the third quadrant in the side view. The fourth portion **100p4** of the LED filament **100** is the portion presented in the fourth quadrant in the side view.

[0194] As shown in FIG. 16D, the LED filament **100** is in line symmetry. The LED filament **100** is symmetric with the Y-axis in the side view. That is to say, the geometric shape of the first portion **100p1** and the fourth portion **100p4** are symmetric with that of the second portion **100p2** and the third portion **100p3**. Specifically, the first portion **100p1** is symmetric to the second portion **100p2** in the side view. Particularly, the first portion **100p1** and the second portion **100p2** are symmetric in structure in the side view with respect to the Y-axis. In addition, the third portion **100p3** is symmetric to the fourth portion **100p4** in the side view. Particularly, the third portion **100p3** and the fourth portion **100p4** are symmetric in structure in the side view with respect to the Y-axis.

[0195] In the embodiment, as shown in FIG. 16D, the first portion **100p1** and the second portion **100p2** presented in the upper quadrants (i.e., the first quadrant and the second quadrant) in the side view are asymmetric with the third portion **100p3** and the fourth portion **100p4** presented in the lower quadrants (i.e., the third quadrant and the fourth quadrant) in the side view. In particular, the first portion **100p1** and the fourth portion **100p4** in the side view are asymmetric, and the second portion **100p2** and the third portion **100p3** in the side view are asymmetric. According to an asymmetry characteristic of the structure of the filament **100** in the upper quadrants and the lower quadrants in FIG. 16D, light rays emitted from the upper quadrants to pass through the upper bulb shell **12** (the portion away from the bulb base **16**) would be greater than those emitted from the lower quadrants to pass through the lower bulb shell **12** (the portion close to the bulb base **16**) in order to fulfill the illumination purpose and the requirement of omnidirectional lamps.

[0196] Based upon symmetry characteristic of LED filament **100**, the structures of the two symmetric portions of the LED filament **100** in the side view (the first portion **100p1** and the second portion **100p2** or the third portion **100p3** and the fourth portion **100p4**) may be exactly symmetric or be symmetric with a tolerance in structure. The tolerance (or a permissible error) between the structures of the two symmetric portions of the LED filament **100** in the side view may be 20%-50% or less.

[0197] The tolerance can be defined as a difference in coordinates, i.e., x-coordinate or y-coordinate. For example, if there is a designated point on the first portion **100p1** of the LED filament **100** in the first quadrant and a symmetric point on the second portion **100p2** of the LED filament **100** in the second quadrant symmetric to the designated point with respect to the Y-axis,

the absolute value of y-coordinate or the x-coordinate of the designated point may be equal to the absolute value of y-coordinate or the x-coordinate of the symmetric point or may have 20% difference compared to the absolute value of y-coordinate or the x-coordinate of the symmetric point.

[0198] For example, as shown in FIG. 16D, a designated point (x_1, y_1) on the first portion **100p1** of the LED filament **100** in the first quadrant is defined as a first position, and a symmetric point (x_2, y_2) on the second portion **100p2** of the LED filament **100** in the second quadrant is defined as a second position. The second position of the symmetric point (x_2, y_2) is symmetric to the first position of the designated point (x_1, y_1) with respect to the Y-axis. The first position and the second position may be exactly symmetric or be symmetric with 20%-50% difference. In the embodiment, the first portion **100p1** and the second portion **100p2** are exactly symmetric in structure. In other words, x_2 of the symmetric point (x_2, y_2) is equal to negative x_1 of the designated point (x_1, y_1) , and y_2 of the symmetric point (x_2, y_2) is equal to y_1 of the designated point (x_1, y_1) .

[0199] For example, as shown in FIG. 16D, a designated point (x_3, y_3) on the third portion **100p3** of the LED filament **100** in the third quadrant is defined as a third position, and a symmetric point (x_4, y_4) on the fourth portion **100p4** of the LED filament **100** in the fourth quadrant is defined as a fourth position. The fourth position of the symmetric point (x_4, y_4) is symmetric to the third position of the designated point (x_3, y_3) with respect to the Y-axis. The third position and the fourth position may be exactly symmetric or be symmetric with 20%-50% difference. In the embodiment, the third portion **100p3** and the fourth portion **100p4** are symmetric with a tolerance (e.g., a difference in coordinates being less than 20%) in structure. In other words, the absolute value of x_4 of the symmetric point (x_4, y_4) is unequal to the absolute value of x_3 of the designated point (x_3, y_3) , and the absolute value of y_4 of the symmetric point (x_4, y_4) is unequal to the absolute value of y_3 of the designated point (x_3, y_3) . As shown in FIG. 16D, the level of the designated point (x_3, y_3) is slightly lower than that of the symmetric point (x_4, y_4) , and the designated point (x_3, y_3) is slightly closer to the Y-axis than the symmetric point (x_4, y_4) is. Accordingly, the absolute value of y_4 is slightly less than that of y_3 , and the absolute value of x_4 is slightly greater than that of x_3 .

[0200] As shown in FIG. 16D, a length of the first portion **100p1** of the LED filament **100** in the first quadrant in the side view is substantially equal to a length of the second portion **100p2** of the LED filament **100** in the second quadrant in the side view. In the embodiment, the length is defined along an elongated direction of the LED filament **100** in a plane view (e.g., a side view, a front view, or a top view). For example, the first portion **100p1** elongates in the first quadrant in the side view shown in FIG. 16D to form a reversed “V” shape with two ends respectively contacting the X-axis and the Y-axis, and the length of the first portion **100p1** is defined along the reversed “V” shape between the X-axis and the Y-axis.

[0201] In addition, a length of the third portion **100p3** of the LED filament **100** in the third quadrant in the side view is substantially equal to a length of fourth portion **100p4** of the LED filament **100** in the fourth quadrant in the side view. Since the third portion **100p3** and the fourth portion **100p4** are symmetric with respect to the Y-axis with a tolerance in structure, there may be a slight difference between the length of the third portion **100p3** and the length of fourth portion **100p4**. The difference may be 20%-50% or less.

[0202] As shown in FIG. 16D, an emitting direction of a designated point of the first portion **100p1** and an emitting direction of a symmetric point of the second portion **100p2** symmetric to the designated point are symmetric in direction in the side view with respect to the Y-axis. In the embodiment, the emitting direction may be defined as a direction towards which the LED chips face. Since the LED chips face the main lighting face L_m , the emitting direction may also be defined as the normal direction of the main lighting face L_m . For example, the designated point (x_1, y_1) of the first portion **100p1** has an emitting direction ED which is upwardly in FIG. 16D, and the symmetric point (x_2, y_2) of the second portion **100p2** has an emitting direction ED which is

upwardly in FIG. 16D. The emitting direction ED of the designated point (x1, y1) and the emitting direction ED of the symmetric point (x2, y2) are symmetric with respect to the Y-axis. In addition, the designated point (x3, y3) of the third portion **100p3** has an emitting direction ED towards a lower-left direction in FIG. 16D, and the symmetric point (x4, y4) of the fourth portion **100p4** has an emitting direction ED towards a lower-right direction in FIG. 16D. The emitting direction ED of the designated point (x3, y3) and the emitting direction ED of the symmetric point (x4, y4) are symmetric with respect to the Y-axis.

[0203] Please refer to FIG. 16E. FIG. 16E is the LED filament **100** shown in FIG. 16C presented in two dimensional coordinate system defining four quadrants. The LED filament **100** in FIG. 16E is the same as that in FIG. 16C, which is a top view of the LED light bulb **20d** shown in FIG. 16A. As shown in FIG. 16C and FIG. 16E, the origin of the four quadrants is defined as a center of a stand **19a** of the LED light bulb **20d** in the top view (e.g., a center of the top of the stand **19a** shown in FIG. 16A). In the embodiment, the Y-axis is vertical, and the X-axis is horizontal in FIG. 16E. As shown in FIG. 16E, the LED filament **100** in the top view can be divided into a first portion **100p1**, a second portion **100p2**, a third portion **100p3**, and a fourth portion **100p4** by the X-axis and the Y-axis. The first portion **100p1** of the LED filament **100** is the portion presented in the first quadrant in the top view. The second portion **100p2** of the LED filament **100** is the portion presented in the second quadrant in the top view. The third portion **100p3** of the LED filament **100** is the portion presented in the third quadrant in the top view. The fourth portion **100p4** of the LED filament **100** is the portion presented in the fourth quadrant in the top view.

[0204] In some embodiments, the LED filament **100** in the top view may be symmetric in point symmetry (being symmetric with the origin of the four quadrants) or in line symmetry (being symmetric with one of the two axis the four quadrants). In the embodiment, as shown in FIG. 16E, the LED filament **100** in the top view is in line symmetry. In particular, the LED filament **100** in the top view is symmetric with the Y-axis. That is to say, the geometric shape of the first portion **100p1** and the fourth portion **100p4** are symmetric with that of the second portion **100p2** and the third portion **100p3**. Specifically, the first portion **100p1** is symmetric to the second portion **100p2** in the top view. Particularly, the first portion **100p1** and the second portion **100p2** are symmetric in structure in the top view with respect to the Y-axis. In addition, the third portion **100p3** is symmetric to the fourth portion **100p4** in the top view. Particularly, the third portion **100p3** and the fourth portion **100p4** are symmetric in structure in the top view with respect to the Y-axis.

[0205] Based upon symmetry characteristic of LED filament **100**, the structures of the two symmetric portions of the LED filament **100** in the top view (the first portion **100p1** and the second portion **100p2** or the third portion **100p3** and the fourth portion **100p4**) may be exactly symmetric or be symmetric with a tolerance in structure. The tolerance (or a permissible error) between the structures of the two symmetric portions of the LED filament **100** in the top view may be 20%-50% or less.

[0206] For example, as shown in FIG. 16E, a designated point (x1, y1) on the first portion **100p1** of the LED filament **100** in the first quadrant is defined as a first position, and a symmetric point (x2, y2) on the second portion **100p2** of the LED filament **100** in the second quadrant is defined as a second position. The second position of the symmetric point (x2, y2) is symmetric to the first position of the designated point (x1, y1) with respect to the Y-axis. The first position and the second position may be exactly symmetric or be symmetric with 20%-50% difference. In the embodiment, the first portion **100p1** and the second portion **100p2** are exactly symmetric in structure. In other words, x2 of the symmetric point (x2, y2) is equal to negative x1 of the designated point (x1, y1), and y2 of the symmetric point (x2, y2) is equal to y1 of the designated point (x1, y1).

[0207] For example, as shown in FIG. 16E, a designated point (x3, y3) on the third portion **100p3** of the LED filament **100** in the third quadrant is defined as a third position, and a symmetric point (x4, y4) on the fourth portion **100p4** of the LED filament **100** in the fourth quadrant is defined as a

fourth position. The fourth position of the symmetric point (x_4 , y_4) is symmetric to the third position of the designated point (x_3 , y_3) with respect to the Y-axis. The third position and the fourth position may be exactly symmetric or be symmetric with 20%-50% difference. In the embodiment, the third portion **100p3** and the fourth portion **100p4** are symmetric with a tolerance (e.g., a difference in coordinates being less than 20%) in structure. In other words, x_4 of the symmetric point (x_4 , y_4) is unequal to negative x_3 of the designated point (x_3 , y_3), and y_4 of the symmetric point (x_4 , y_4) is unequal to y_3 of the designated point (x_3 , y_3). As shown in FIG. 16E, the level of the designated point (x_3 , y_3) is slightly lower than that of the symmetric point (x_4 , y_4), and the designated point (x_3 , y_3) is slightly closer to the Y-axis than the symmetric point (x_4 , y_4) is. Accordingly, the absolute value of y_4 is slightly less than that of y_3 , and the absolute value of x_4 is slightly greater than that of x_3 .

[0208] As shown in FIG. 16E, a length of the first portion **100p1** of the LED filament **100** in the first quadrant in the top view is substantially equal to a length of the second portion **100p2** of the LED filament **100** in the second quadrant in the top view. In the embodiment, the length is defined along an elongated direction of the LED filament **100** in a plane view (e.g., a top view, a front view, or a top view). For example, the second portion **100p2** elongates in the second quadrant in the top view shown in FIG. 16E to form a reversed “L” shape with two ends respectively contacting the X-axis and the Y-axis, and the length of the second portion **100p2** is defined along the reversed “L” shape.

[0209] In addition, a length of the third portion **100p3** of the LED filament **100** in the third quadrant in the top view is substantially equal to a length of fourth portion **100p4** of the LED filament **100** in the fourth quadrant in the top view. Since the third portion **100p3** and the fourth portion **100p4** are symmetric with respect to the Y-axis with a tolerance in structure, there may be a slight difference between the length of the third portion **100p3** and the length of fourth portion **100p4**. The difference may be 20%-50% or less.

[0210] As shown in FIG. 16E, an emitting direction of a designated point of the first portion **100p1** and an emitting direction of a symmetric point of the second portion **100p2** symmetric to the designated point are symmetric in direction in the top view with respect to the Y-axis. In the embodiment, the emitting direction may be defined as a direction towards which the LED chips face. Since the LED chips face the main lighting face L_m , the emitting direction may also be defined as the normal direction of the main lighting face L_m . For example, the designated point (x_1 , y_1) of the first portion **100p1** has an emitting direction ED towards the right in FIG. 16E, and the symmetric point (x_2 , y_2) of the second portion **100p2** has an emitting direction ED towards left in FIG. 16E. The emitting direction ED of the designated point (x_1 , y_1) and the emitting direction ED of the symmetric point (x_2 , y_2) are symmetric with respect to the Y-axis. In addition, the designated point (x_3 , y_3) of the third portion **100p3** has an emitting direction ED towards a lower-left direction in FIG. 16E, and the symmetric point (x_4 , y_4) of the fourth portion **100p4** has an emitting direction ED towards a lower-right direction in FIG. 16E. The emitting direction ED of the designated point (x_3 , y_3) and the emitting direction ED of the symmetric point (x_4 , y_4) are symmetric with respect to the Y-axis. In addition, an emitting direction ED of any designated point of the first portion **100p1** and an emitting direction ED of a corresponding symmetric point of the second portion **100p2** symmetric to the designated point are symmetric in direction in the top view with respect to the Y-axis. An emitting direction ED of any designated point of the third portion **100p3** and an emitting direction ED of a corresponding symmetric point of the fourth portion **100p4** symmetric to the designated point are symmetric in direction in the top view with respect to the Y-axis.

[0211] Definition of the omni-directional light depends on regions and varies over time. Depending on different institutions and countries, LED light bulbs which claim omni-directional light may need to meet different standards. For example, page 24 of the ENERGY STAR Program Requirements for Lamps (bulbs)—Eligibility Criteria Version 1.0 defines that an omnidirectional

lamp in base-on position has to emit at least 5% of total flux (lm) in 135° to 180° zone, that 90% of measured intensity values may vary by no more than 25% from the average of all measured values in all planes, and that luminous intensity (cd) is measured within each vertical plane at a 5° vertical angle increment (maximum) from 0° to 135°. Japanese JEL 801 requires luminous flux of an LED lamp within a 120 degrees zone about a light axis shall not be less than 70% of total flux. Because the above embodiment possesses a symmetrical arrangement of LED filament, an LED light bulb with the LED filament is able to meet various standards of omni-directional lamps.

[0212] Referring to FIG. 17A, FIG. 17B, FIG. 17C and FIG. 17D, FIG. 17A illustrates a schematic diagram of an LED light bulb **40a** according to an embodiment of the present invention, FIG. 17B to FIG. 17D are a side view, another side view and the top view of the LED light bulb, respectively. In the present embodiment, the LED light bulb **40a** includes a lamp housing **12**, a bulb base **16** connected to the lamp housing **12**, a stem **19**, and a single LED filament **100**. Moreover, the LED light bulb **40a** and the single LED filament **100** disposed in the LED light bulb **40a** can refer to related descriptions of the previous embodiments, wherein the same or similar components and the connection relationship between components is no longer detailed.

[0213] In the present embodiment, the stem **19** is connected to the bulb base **16** and located in the lamp housing **12**, the stem **19** has a stand **19a** extending vertically to the center of the lamp housing **12**, the stand **19a** is located on the central axis of the bulb base **16**, or is located on the central axis of the LED light bulb **40a**. The LED filament **100** is disposed around the stand **19a** and is located within the lamp housing **12**, and the LED filament **100** can be coupled to the stand **19a** through a cantilever to maintain a predetermined curve and shape. Wherein a detailed description of the cantilever can be referenced to the previous embodiment and the drawings. The LED filament **100** includes two conductive electrodes **110**, **112** at both ends, a plurality of LED sections **102**, **104** and a plurality of conductive sections **130**. As shown in FIG. 17A to FIG. 17D, in order to separate the conductive section **130** and the LED sections **102**, **104** in the drawing, the plurality of the conductive sections **130** of the LED filament **100** is illustrated as points or small segments, which is only for the illustrations. It is easier to understand, and not for any limitation, and the subsequent embodiments are similar to the related drawings by the point or small segment distribution of the conductive section **130** to distinguish from the LED sections **102**, **104**. As described in various previous embodiments, each of the LED sections **102**, **104** can include a plurality of LED chips connected to each other, and each of the conductive sections **130** can include a conductor. Each conductive section **130** is located between adjacent two LED sections **102**, **104**. The conductors in each conductive section **130** connect the LED chips in the adjacent two LED sections **102**, **104**, and the LED chips in the two LED sections **102** adjacent to the two conductive electrodes **110**, **112** are respectively connected to the two conductive electrodes **110**, **112**. The stem **19** can be connected to the two conductive electrodes **110**, **112** by means of conductive brackets, details of the conductive brackets can be referred to the previous embodiment and the drawings.

[0214] As shown in FIG. 17A to FIG. 17D, the LED filament **100** comprises two first conductive sections **130**, one second conductive sections **130'**, and four LED sections **102**, **104**, and every two adjacent LED sections **102**, **104** are connected through the bending first and second conductive section **130**, **130'**. Moreover, since the first and second conductive sections **130**, **130'** have better bendability than that of the LED sections **102**, **104**, the first and second conductive sections **130**, **130'** between the two adjacent LED sections **102**, **104** can be bent severely, so that the angle between the two adjacent LED sections **102**, **104** can be smaller, for example, the included angle can reach 45 degrees or less. In the present embodiment, each LED section **102**, **104** is slightly curved or not bent compared to the first and second conductive sections **130**, **130'**, so that a single LED filament **100** in the LED light bulb **40a** can be bent severer because of the first and second conductive sections **130**, **130'**, and the curling change in bending is more significant. Moreover, the LED filament **100** can be defined as a piece following each bending conductive sections **130**, **130'**, and each LED section **102**, **104** is formed into a respective piece.

[0215] As shown in FIG. 17B and FIG. 17C, each of the first and second conductive sections **130**, **130'** and the two adjacent LED sections **102**, **104** is composed to form a U-shaped or V-shaped bent structure, that is, the U-shaped or V-shaped bent structure formed by each of the first and second conductive sections **130**, **130'** and the adjacent two LED sections **102**, **104** is bent with two pieces, and the two LED sections **102**, **104** are respectively formed the two pieces. In the present embodiment, the LED filament **100** is bent into four pieces by the first and second conductive sections **130**, **130'**, the four LED sections **102**, **104** are respectively formed the four pieces. Also, the number of LED sections **102**, **104** is one more than the number of the conductive sections **130**, **130'**.

[0216] As shown in FIG. 17B, in the present embodiment, the conductive electrodes **110**, **112** are located between the highest point and the lowest point of the LED filament **100** in the Z direction. The highest point is located at the highest first conductive section **130** in the Z direction, and the lowest point is located at the lowest second conductive section **130'** in the Z direction. The lower second conductive section **130'** and the higher first conductive section **130** are defined with the conductive electrodes **110**, **112** as being close to or away from the bulb base **16**. Referring to FIG. 17B, in the YZ plane, the positions of the conductive electrodes **110**, **112** may constitute a line LA showing with dotted line, there are two first conductive sections **130** above the line LA, and one second conductive sections **130'** below the line LA. In other words, in the Z direction, the number of the first conductive sections **130** positioned above the line LA to which the conductive electrodes **110**, **112** are connected may be one more than the number of the second conductive section **130'** positioned below the line LA. It is also contemplated that relative to the conductive electrodes **110**, **112** as a whole, the number of the first conductive sections **130** away from the bulb base **16** is one more than the number of the second conductive section **130'** near the bulb base **16**. Further, if the LED filament **100** is projected on the YZ plane (refer to FIG. 17B), the line LA connected by the conductive electrodes **110**, **112** has at least one intersection with the projection of the LED sections **102**, **104**. In the YZ plane, the lines LA connected by the conductive electrodes **110**, **112** respectively intersect the projections of the two LED sections **104**, so that the line LA and the projection of the adjacent two LED sections **104** have two intersections.

[0217] As shown in FIG. 17C, if the LED filament **100** is projected on the XZ plane, the projections of the opposing two LED sections **102**, **104** overlap each other. In some embodiments, the projections of the opposing two LED sections **102**, **104** on a particular plane may be parallel to each other.

[0218] As shown in FIG. 17D, if the LED filament **100** is projected on the XY plane, the projections of the conductive electrodes **110**, **112** on the XY plane can be connected in a straight line LB showing with dotted line, and the projections of the first and second conductive sections **130**, **130'** on the XY plane are not intersected or overlapped with the line LB, and the projections of the first and second conductive sections **130**, **130'** on the XY plane are respectively located on one side of the line LB. For example, as showing in FIG. 17D, the projections of the first conductive sections **130** on the XY plane are above the line LB.

[0219] As shown in FIG. 17B to FIG. 17D, in the present embodiment, and the projection lengths of the LED filament **100** on the projection planes perpendicular to each other can have a designed proportion, so that the illumination is more uniform. For example, the projection of the LED filament **100** on the first projection surface, such as the XY plane, has a length L1, the projection of the LED filament **100** on the second projection surface, such as the YZ plane, has a length L2, and the projection of the LED filament **100** on the third projection planes, such as the XZ plane, has a length L3. The first projection plane, the second projection plane and the third projection plane are perpendicular to each other, and the normal line of the first projection plane is parallel to the axis of the LED light bulb **40a** from the center of the lamp housing **12** to the center of the bulb base **16**. Further, the projection of the LED filament **100** on the XY plane as shown in FIG. 17D, and the projection thereof will be similar to an inverted and deformed U shape, and the total length of the

projection of the LED filament **100** on the XY plane is the length **L1**. The projection of the LED filament **100** on the YZ plane as shown in FIG. **17B**, the projection thereof will be similar to the inverted and deformed W shape, and the total length of the projection of the LED filament **100** on the YZ plane is the length **L2**. The projection of the LED filament **100** on the XZ plane can be as shown in FIG. **17C**, the projection of which will be similar to an inverted V shape, and the total length of the projection of the LED filament **100** on the XZ plane is the length **L3**. In the present embodiment, the length **L1**, the length **L2**, and the length **L3** are approximately in a ratio of 1:1:0.9. In some embodiments, the length **L1**, the length **L2**, and the length **L3** are approximately in a ratio of 1:(0.5 to 1):(0.6 to 0.9). For example, if the ratio of the length **L1**, the length **L2**, and the length **L3** is closer to 1:1:1, the illumination uniformity of the single LED filament **100** in the LED light bulb **40a** is better, and the omni-directional light appearance is better.

[0220] In some embodiments, the projected length of the LED filament **100** in the XZ plane or in the YZ plane is, for example but not limited thereto, a minimum of the height difference between the first conductive section **130** and the second conductive section **130'** in the Z direction multiply by the number of LED sections **102**, **104**, or a minimum of the height difference of the LED filament **100** in the Z direction multiply by the number of LED sections **102**, **104**. In the present embodiment, the total length of the LED filament **100** is about 7 to 9 times the total length of the first conductive section **130** or the second conductive section **130'**.

[0221] In the present embodiment, the LED filament **100** can be bent at the positions of the first and second conductive sections **130**, **130'** to form various curves, so that not only the overall aesthetic appearance of the LED light bulb **40a** can be increased but also the light emitting of the LED light bulb **40a** can be more uniform, and the better illumination is achieved.

[0222] Referring to FIG. **18A** to FIG. **18D**, FIG. **18A** is a perspective diagram of an LED light bulb **40h** according to an embodiment of the present invention, and FIG. **18B** to FIG. **18D** are respectively side view, another side view, and top view of the FIG. **18A**. In the present embodiment, the LED light bulb **40h** includes a lamp housing **12**, a bulb base **16** connected to the lamp housing **12**, a stem **19**, a stand **19a**, and a single LED filament **100**. The LED filament **100** includes two conductive electrodes **110**, **112** at two ends, a plurality of LED sections **102**, **104** and a single conductive section **130**. Moreover, the LED light bulb **40h** and the single LED filament **100** disposed in the LED light bulb **40h** can refer to related descriptions of the previous embodiments, wherein the same or similar components and the connection relationship between components is no longer detailed.

[0223] Referring to FIG. **18A** to FIG. **18D**, in the present invention, the LED filament section **100** includes one conductive section **130**, two LED sections **102**, **104**, and between two adjacent LED sections **102**, **104** is connected by the conductive section **130**. Wherein the LED filament **100** having a circular arc at the highest point of the bending curvature, that is, each of the LED sections **102**, **104** respectively having a circular arc at the highest point of the LED filament **100**, and the conductive section also exhibits a circular arc at the low point of the LED filament. Moreover, the LED filament **100** can be defined as having a plurality of sections, each of the sections is connected between the first and second conductive sections **130**, and each LED section **102**, **104** is formed into a respective section.

[0224] Moreover, since the LED filament **100** is equipped with a flexible base layer, the flexible base layer preferably is made by an organosilicon-modified polyimide resin composition, and thus the LED sections **102**, **104** themselves also have a certain degree of bendability. In the present embodiment, the two LED sections **102**, **104** are respectively bent to form in the shape like an inverted deformed U letter, and the conductive section **130** is located between the two LED sections **102**, **104**, and the degree of the bending of the conductive section **130** is the same as or greater than the degree of the bending of the LED sections **102**, **104**. In other words, the two LED sections **102**, **104** of the LED filament are respectively bent at the high point to form in the shape like an inverted deformed U letter and have a bending radius value at **R1**, and the conductive

section **130** is bent at a low point of the LED filament **100** and has a bending radius value at **R2**, wherein the value **R1** is the same as or greater than the value **R2**. Through the configuration of the conductive section **130**, the LED filament **100** disposing in a limited space can be realized with a small radius bending of the LED filament **100**. In one embodiment, the bending points of the LED sections **102**, **104** are at the same height in the Z direction. Further, in the Z direction, the stand **19a** of the present embodiment has a lower position than the stand **19a** of the previous embodiment, and the height of the present stand **19a** is corresponding to the height of the conductive section **130**. For example, the lowest portion of the conductive section **130** can be connected to the top of the stand **19a** so that the overall shape of the LED filament **100** is not easily deformed. In various embodiments, the conductive sections **130** may be connected to the stand **19a** through the perforation of the top of the stand **19a**, or the conductive sections **130** may be glued to the top of the stand **19a** to connect with each other, but are not limited thereto. In an embodiment, the conductive section **130** and the stand **19a** may be connected by a guide wire, for example, a guide wire connected to the conductive section **130** is drawn at the top of the stand **19a**.

[0225] As shown in FIG. **18B**, in the present embodiment, the height of the conductive section **130** is higher than the two conductive electrodes **110**, **112** in the Z direction, and the two LED sections **102**, **104** are respectively shaped upward from the two conductive electrodes **110**, **112** to the highest point and then are bent down to connect with the conductive section **130**. As shown in FIG. **185C**, in the present embodiment, the contour of the LED filament **100** in the XZ plane is similar to the V letter, that is, the two LED sections **102**, **104** are respectively shaped obliquely upward and outward and are bent respectively at the highest point and then obliquely inwardly to connect with the conductive section **130**. As shown in FIG. **18D**, in the present embodiment, the LED filament **100** has a contour in the shape like S letter in the XY plane. As shown in FIG. **18B** and FIG. **18D**, in the present embodiment, the conductive section **130** is located between the conductive electrodes **110**, **112**. As shown in FIG. **18D**, in the XY plane, the main bending points of the LED sections **102**, **104**, and the conductive electrodes **110**, **112** are substantially on the circumference centered on the conductive section **130**.

[0226] In this embodiment, as shown in FIG. **18A** to FIG. **18D**, the LED light bulb includes a lamp housing **12**, a lamp cap **16** connected to the lamp housing **12**, at least two conductive brackets disposed in the lamp housing **12**, a supporting arm (not shown), a stem **19**, and a single LED filament **100**. The stem **19** includes a stem bottom portion and a stem top portion that are opposite to each other. The stem bottom portion is connected to the lamp cap **16**. The stem top portion extends to the inside of the lamp housing **12**, for example, the stem top portion may be located approximately at the center of the lamp housing **12**. The conductive brackets are connected to the stem **19**. The LED filament **100** includes a filament body and two filament electrodes (electrodes or conductive electrodes) **110**, **112**. The two filament electrodes **110**, **112** are located at two opposite ends of the filament body. The filament body is the other portion of the LED filament **100** excluding the filament electrodes **110**, **112**. The two filament electrodes **110**, **112** are connected to the two conductive brackets, respectively. One end of the supporting arm is connected to the stem **19**, and the other end is connected to the filament body.

[0227] During the manufacturing process of traditional bulbs, in order to avoid a tungsten wire burning in the air thereby causing the oxidative fracture failure, a glass structure with a horn shape (hereinafter refer to as “horn stem”) is designed to be disposed at the opening of the glass lamp housing and then the horn stem is sintered and sealed to the glass lamp housing. Then, a vacuum pump is connected to the lamp housing through the port of the horn stem to replace the air inside the lamp housing with nitrogen so as to suppress the combustion and oxidation of the tungsten wire inside the lamp housing. Eventually, the port of the horn stem will be sintered and sealed.

Therefore, the vacuum pump can pump out the air inside the lamp housing and substitute it with all nitrogen or a combination of nitrogen and helium in a proper ratio through the stem, to improve the thermal conductivity of the gas inside the lamp housing and remove water mist hidden in the air at

the same time. In one embodiment, the air may alternatively be pumped out and substitute it with a combination of nitrogen and oxygen or nitrogen and air in a proper ratio. The content of oxygen or air is 1-10% of the volume of the lamp housing, preferably 1-5%. When a base layer contains saturated hydrocarbons, during the use of the LED light bulb, the saturated hydrocarbons will generate free radicals under the effect of light, heat, stress, etc. The generated free radicals or activated molecules will combine with oxygen to form peroxide free radicals. Thus, filling the lamp housing with oxygen can improve the heat and light resistance of the base layer containing the saturated hydrocarbons.

[0228] In the manufacturing process of the LED light bulb, in order to increase the refractive index of the lamp housing **12** to the light emitted by the LED filament, some foreign matter, for example, rosin, may be attached to an inner wall of the lamp housing **12**. The average thickness of the foreign matter deposited per square centimeter of the inner wall area of the lamp housing **12** is 0.01-2 mm, and the thickness of the foreign matter is preferably 0.01-0.5 mm. In one embodiment, the content of the foreign matter per square centimeter of the inner wall area of the lamp housing **12** is 1-30% of the content of the foreign matter on the inner wall of the entire lamp housing **12**, preferably 1-10%. For example, the content of the foreign matter may be adjusted by vacuum drying the lamp housing. In another embodiment, some impurities may be left in the gas filled in the lamp housing **12**. The content of the impurities in the gas filled is 0.1-20% of the volume of the lamp housing **12**, preferably 0.1-5%. For example, the content of the impurities may be adjusted, for example, by a method of vacuum drying to the lamp housing. Because the gas filled contains a small amount of impurities, the light emitted by the LED filament is emitted or refracted by the impurities to increase a luminous angle, which is beneficial to improving the luminous effect of the LED filament.

[0229] A Cartesian coordinate system having an X-axis, a Y-axis and a Z-axis is oriented for the LED light bulb, where the Z-axis is parallel to the stem **19**, and the total length of the projection of the LED filament **100** on the XY plane, YZ plane and XZ plane is respectively the length L1, length L2, and length L3. In the present embodiment, the length L1, the length L2, and the length L3 are approximately in a ratio of 0.8:1:0.9. In some embodiments, the length L1, the length L2, and the length L3 are approximately in a ratio of (0.5 to 0.9):1:(0.6 to 1), the ratio of the length L1, the length L2, and the length L3 is closer to 1:1:1, the illumination uniformity of the LED filament **100** in the LED light bulb **40a** is better, and the omni-directional light appearance is better. The LED filament **100** has at least one first bending point and at least two second bending points when the LED filament is bent. The at least one first bending point and the at least two second bending points are arranged alternately, and the height of any one of the at least one first bending point on the Z-axis is greater than that of any one of the at least two second bending points. In one embodiment, the distances between any of two adjacent first bending points on the Y-axis and the X-axis are equal, and the LED filament has a neat and beautiful appearance. In one embodiment, a distance between any of two adjacent first bending points on the Y-axis or the X-axis has a maximum value D1 and a minimum value D2, where the range of D2 is from 0.5D1 to 0.9D1, and the luminous flux distribution on each plane is relatively consistent. Assuming that a diameter of the lamp cap **16** is R1 (referring to FIG. **18B**), a maximum diameter of the lamp housing **12** or a maximum horizontal spacing of the lamp housing **12** in the YZ-plane is R2 (referring to FIG. **18B**), a maximum width in the Y-axis direction on the YZ-plane (referring to FIG. **18B**) or a maximum width in the X-axis direction on the XZ-plane (referring to FIG. **18C**) of the LED filament **100** is R3, then R3 is between R1 and R2, that is, $R1 < R3 < R2$. When the LED filament is bent, the distance between adjacent first bending points and/or adjacent second bending points in the Z-axis direction is wide, which is beneficial to improving the heat dissipation effect of the LED filament. In the manufacturing process of the LED light bulb, the LED filament **100** may be placed into an inner space of the lamp housing **12** in a manner of folding first, and then the LED filament **100** may be stretched in the lamp housing **12** manually or mechanically, so that a maximum length of

the LED filament **100** on the XZ-plane satisfies the above-mentioned relationship.

[0230] As shown in FIG. **18A** to FIG. **18D**, in this embodiment, the LED filament **100** has one conductive section **130** and two LED sections **102**, **104**, and every two adjacent LED sections **102**, **104** are connected to each other by the conductive section **130**. The bent portion of the LED filament **100** at the highest point has an arc shape, that is, the LED sections **102**, **104** respectively has an arc shape at the highest point of the LED filament **100**, and the conductive section **130** shows an arc shape at a low point of the LED filament **100** as well. The LED filament **100** may be configured to have a structure where each bent conductive section **130** is followed by one segment, and each LED section **102**, **104** is formed into are respective section.

[0231] Moreover, since the base layer as a flexible substrate (preferably made of a silicone-modified polyimide resin composition) is adopted by the LED filament **100**, the silicone-modified polyimide resin composition includes organosilicon-modified polyimide, a thermal curing agent, heat dissipation particles, and phosphor. In this embodiment, two LED sections **102**, **104** are respectively bent to form an inverted U shape, the conductive section **130** is located between the two LED sections **102**, **104** and the bending degree of the conductive section **130** is the same as or greater than that of the LED sections **102/104**. That is, the two LED sections **102**, **104** are respectively bent at a high point of the LED filament to form an inverted U shape and have a bending radius r_1 , the conductive section **130** is bent at a low point of the LED filament **100** and has a bending radius r_2 , and r_1 is greater than r_2 . Through the configuration of the conductive section **130**, the LED filament **100** can be bent with a small radius of gyration in a limited space. In one embodiment, the bending points of the LED section **102** and the LED section **104** are at the same height in the Z direction, the LED filament **100** has a certain symmetry in some directions, so the light distribution of the LED light bulb may be more uniform. In one embodiment, the bending points of the LED section **102** and the LED section **104** are at different height in the Z direction, the height of the bending points of the LED section **102** is greater than that the bending points of the LED section **104**, in the case of the same LED filament length, when the LED filament is placed in the lamp housing in this way, part of the LED filament will be more biased towards the lamp housing, so the heat dissipation of the LED filament is better. In addition, in the Z direction, a stand **19a** of this embodiment has a smaller height than a stand **19a** of the previous embodiment, and the height of the stand **19a** of this embodiment corresponds to the height of the conductive section **130** or the stand **19a** is presumably in contact with part of the conductor section **130**. For example, the lowest portion of the conductive section **130** may be connected to the top portion of the stand **19a**, so that the overall shape of the LED filament **100** is not easily deformed. In different embodiments, the conductive section **130** may pass through a through hole of the top portion of the stand **19a** to be connected to the stand **19a**, or the conductive section **130** may be attached to the top portion of the stand **19a** to be connected to the stand **19a**, but it is not limited thereto. In one embodiment, the conductive section **130** may be connected to the stand **19a** by a conductive wire, for example, the conductive wire is extended from the top portion of the stand **19a** and connected to the conductive section **130**.

[0232] As shown in FIG. **18B**, in this embodiment, in the Z direction, the height of the conductive section **130** is greater than that of the two electrodes **110**, **112**. The two LED sections **102** may be seen as the two electrodes **110** and **112** extending upward to the highest point respectively and then bending down and further extending to connect to the conductive section **130**. As shown in FIG. **18C**, in this embodiment, the outline of the LED filament **100** in the XZ-plane is similar to a V shape, that is, the two LED sections **102**, **104** respectively extend upward and outward obliquely, and respectively extend downward and inward obliquely to the conductive section **130** after being bent at the highest points. As shown in FIG. **18D**, in this embodiment, the outline of the LED filament **100** in the XY-plane has an S shape. As shown in FIG. **18B** and FIG. **18D**, in this embodiment, the conductive section **130** is located between the electrodes **110**, **112**. As shown in FIG. **18D**, in this embodiment, in the XY-plane, the bending point of the LED section **102**, the

bending point of the LED section **104**, and the electrodes **110**, **112** are substantially located on a circumference of a circle taking the conductive section **130** (or the stem **19** or the stand **19a**) as a center. For example, in the XY-plane, the bending point of the LED section **102** and the bending point of the LED section **104** are located on the same circumference of a circle taking the stem **19** or the stand **19a** as a center. In some embodiments, in the XY-plane, the bending point of the LED section **102**, the bending point of the LED section **104**, and the electrodes **110**, **112** are located on the same circumference of a circle taking the stem **19** or the stand **19a** as a center.

[0233] In this embodiment, as shown in FIG. **18A** to FIG. **18D**, the LED bulb includes a lamp housing **12**, a bulb base **16** connected to the lamp housing **12**, a stem **19**, and a single LED filament **100** where the stem **19**, and the single LED filament **100** are in the lamp housing **12**. The stem **19** includes a stem bottom and a stem top (or stand **19a** or pole **19a**) opposite to the stem bottom. The stem bottom is connected to the bulb base **16**, and the stem top extends into the interior of the lamp housing **12** (e.g., the stem top may be extended into approximately the center of the lamp housing **12**). The LED filament **100** includes a filament body and two filament electrodes **110** and **112**. The two filament electrodes **110** and **112** are located at opposite ends of the filament body. The filament body is the part of the LED filament **100** that excludes the filament electrodes **110** and **112**.

[0234] During the manufacturing process of traditional bulbs, in order to avoid a tungsten wire burning in the air thereby causing the oxidative fracture failure, a glass structure with a horn shape (hereinafter refer to as “horn stem”) is designed to be disposed at the opening of the glass lamp housing and then the horn stem is sintered and sealed to the glass lamp housing. Then, a vacuum pump is connected to the lamp housing through the port of the horn stem to replace the air inside the lamp housing with nitrogen so as to suppress the combustion and oxidation of the tungsten wire inside the lamp housing. Eventually, the port of the horn stem will be sintered and sealed.

Therefore, the vacuum pump can be applied to replace the air inside the lamp housing with full nitrogen or to configure a moderate ratio of nitrogen and helium inside the lamp housing through the stem to improve the thermal conductivity of the gas in the lamp housing and to remove the water mist in the air at the same time. In one embodiment, the gas inside the lamp housing can also be replaced with a moderate ratio of nitrogen and oxygen or a moderate ratio of nitrogen and air. The oxygen or air content is 1% to 10%, preferably 1% to 5% of the volume of the lamp housing. When the base layer contains saturated hydrocarbons, during the use of the LED bulbs, the saturated hydrocarbons will generate free radicals under the effect of light, heat, stress, etc. The generated free radicals or activated molecules will combine with oxygen to form peroxide radicals. Thus, the lamp housing filled with oxygen may increase thermal resistance and light resistance of the base layer having saturated hydrocarbons.

[0235] During the manufacturing process of the LED bulb, in order to increase the refractive index of the lamp housing **12** to the light emitted by the LED filament, some impurities, such as rosin, may be attached to the inner wall of the lamp housing **12**. The lamp housing **12** can be vacuum dried to reduce the impurity content in the inner wall of the lamp housing **12** or in the gas filled in the lamp housing **12**. After the lamp housing **12** is vacuum dried, the average thickness of the impurity deposition per square centimeter of the inner wall area of the lamp housing **12** is 0.01 to 2 mm, and the thickness of the impurity is preferably 0.01 to 0.5 mm. In one embodiment, the content of the impurity per square centimeter of the inner wall area of the lamp housing **12** accounts for 1% to 30%, preferably 1% to 10% of the content of the impurity on the inner wall of the entire lamp housing **12**. The content of the impurity can be adjusted, for example, by a method of vacuum drying to the lamp housing **12**. In another embodiment, a part of impurities may be left in the gas of the lamp housing **12**, and the content of impurities in the gas is 0.1% to 20%, preferably 0.1 to 5%, of the volume of the lamp housing **12**. The impurity content may be adjusted by the method of vacuum drying to the lamp housing **12**. Because a small amount of impurities is contained in the filling gas, the light emitted by the LED filament is scattered or refracted by the impurities, and thus the light emitting angle may be increased, which is beneficial to improving the

light emitting effect of the LED filament. Furthermore, since the impurity content in the filling gas is low, the heat transfer effect is increased, and the heat dissipation effect of the LED light bulb is improved. Finally, by further reducing the impurity content in the base layer **240b** (for example, the silicone-modified polyimide resin composition), the strength of the base layer **240b** is increased, thereby effectively increasing the service life of the LED filament.

[0236] A Cartesian coordinate system having an X-axis, a Y-axis and a Z-axis is oriented for the LED light bulb, where the Z-axis is parallel to the stem **19**, and the LED filament **100** has at least two first bending point and at least one second bending points when the LED filament is bent. The at least two first bending point and the at least one second bending points are arranged alternately, and the height of any one of the at least two first bending point on the Z-axis is greater than that of any one of the at least one second bending points. In one embodiment, the distances between any of two adjacent first bending points on the Y-axis or on the Z-axis are equal. Therefore, the appearance of the LED filament can be neat and beautiful. In an embodiment, the distance between the two adjacent first bending points on the Y-axis or on X-axis has a maximum value $D1$ and a minimum value $D2$, where the range of $D2$ is from $0.5D1$ to $0.9D1$, and the light flux distribution on each plane is relatively consistent. Let (1) the diameter of the bulb base **16** be $R1$ (shown in FIG. **18A**), (2) the maximum diameter of the lamp housing **12** or the maximum horizontal distance between the lamp housings **12** in the Y-Z plane be $R2$ (shown in FIG. **18B**), and (3) the maximum width of the LED filament **100** in the Y-axis direction on the Y-Z plane (shown in FIG. **18B**) or the maximum width in the X-axis direction on the X-Z plane be $R3$ (shown in FIG. **18C**). Specifically, FIG. **18B** and FIG. **18C** are merely illustrative, and the magnitude of $R1$, $R2$, and $R3$ is such that $R3$ is between $R1$ and $R2$, that is, $R1 < R3 < R2$, and is not a visual magnitude as shown in FIG. **18B** and FIG. **18C**. When the LED filament is bent, the distance between adjacent first bending points and/or adjacent second bending points in the Z-axis direction is wide, which is beneficial to improving the heat dissipation effect of the LED filament. In the manufacturing process of the LED bulb, the LED filament **100** can be folded into the inner space of the lamp housing **12** first, and then the filament **100** can be manually or mechanically extended in the lamp housing **12** so that the maximum length of the filament **100** on the X-Z plane satisfies the above-mentioned relationship.

[0237] As shown in FIG. **18A** to FIG. **18D**, in this embodiment, the LED filament **100** has one conductor section **130** and two LED sections **102** and **104**. The two adjacent LED sections **102** and **104** are connected through the conductor section **130**. The bent portion of the LED filament **100** at the highest point has an arc shape. That is, the LED sections **102** and **104** show arc shapes respectively at the highest point of the LED filament **100**. The conductor section **130** shows an arc shape at the lower point of the LED filament as well. The LED filament **100** may be configured to have a structure where each bent conductor section **130** is followed by one segment, and each LED sections **102,104** is formed into a respective section.

[0238] Moreover, since a flexible substrate (preferably made of a silicone-modified polyimide resin composition) is adopted by the LED filament **100**, the LED sections **102** and **104** also have a certain degree of bending ability. In this embodiment, the two LED sections **102** are respectively bent to form an inverted U shape, and the conductor section **130** is located between the two LED sections **102**, and the degree of bending of the conductor section **130** is the same as or greater than that of the LED section **102**. That is, the two LED sections **102** are respectively bent at the higher point of the LED filament **100** to form an inverted U shape and have a bent radius $r1$. The conductor section **130** is bent at the lower point of the LED filament **100** and has a bent radius $r2$, where $r1$ is greater than $r2$. The arrangement of the conductor sections **130** enables the LED filament **100** to achieve a bending with a small turning radius in a limited space. In one embodiment, the bending points of the LED section **102** and that of the LED section **104** are at the same height in the Z direction. In addition, the height of the pole **19a** corresponds to the height of the conductor section **130**. For example, the lowest portion of the conductor section **130** may be connected to the top of the pole **19a**, so that the overall shape of the LED filament **100** may not be

easily deformed. In different embodiments, the conductor sections **130** may be connected to the pole **19a** by passing through a hole on the top of the pole **19a**, or the conductor sections **130** may be connected to the pole **19a** by being glued on the top of the pole **19a**, but is not limited thereto. In one embodiment, the conductor section **130** and the pole **19a** may be connected by a conductive wire. For example, a conductive wire is extended from the top of the pole **19a** and connected to the conductor section **130**.

[0239] As shown in FIG. **18B**, in this embodiment, in the Z direction, the height of the conductor section **130** is higher than that of the two electrodes **110** and **112**. The two LED sections **102** may be seen as the two electrodes **110** and **112** extending upward to the highest point respectively and then bending down and further extending to connect to the conductor section **130**. As shown in FIG. **18C**, in this embodiment, the outline of the LED filament **100** in the X-Z plane is similar to a V shape, that is, the two LED sections **102** are extended obliquely upward and outward respectively, and are bent at the highest point then extended downwardly and inwardly to the conductor section **130**. As shown in FIG. **18D**, in this embodiment, the outline of the LED filament **100** in the X-Y plane has an S shape. As shown in FIG. **18B** and FIG. **18D**, in this embodiment, the conductor section **130** is located between the electrodes **110** and **112**. As shown in FIG. **18D**, in this embodiment, in the X-Y plane, the bending point of the LED section **102**, the bending point of the LED section **104**, and the electrodes **110**, **112** are located substantially on a circumference of a circle taking the conductor section **130** as a center.

[0240] The meaning of the term “a single LED filament” and “a single strip LED filament” as used in the present invention is mainly composed of the aforementioned conductive section, the LED section, the connection between thereof, the light conversion layer (including the consecutive top layer or the bottom layer, with continuous formation to cover or support all the components), and two conductive electrodes electrically connected to the conductive brackets of the LED light bulb disposing at both ends of the LED filament, which is the single LED filament structure referred to in the present invention.

[0241] In some embodiments, LED filament **100** may have multiple LED sections. At least part or all of LED chips on a single LED section are electrically connected in series. Different LED sections are electrically connected in parallel. Anode and cathode of each LED section may serve as a positive electrode and negative electrodes of the LED filament, respectively. The negative electrodes separately connect with two or more of the conductive supports (e.g., conductive supports **51a**, **51b** in FIG. **15A**) and finally connect to a power module (such as power module **518** in FIG. **15A**). As shown in FIG. **19A**, which is a schematic circuit diagram of the LED filament according to some embodiments of the present invention, LED filament **100** in this embodiment has two LED sections **402**, **404**. Each LED section **402**, **404** includes one or more LED chips. LED chips in a single LED section are electrically connected in series. Two LED sections **402**, **404** have respective current paths after they have been electrically connected (i.e. in parallel). In detail, in this embodiment, anodes of LED sections **402**, **404** are electrically connected together to serve as a positive electrode **P1** of LED filament **100**. Cathodes of LED section **402** and **404** serve as a first negative electrode **N1** and a second negative electrode **N2**, respectively. Positive electrode **P1**, first negative electrode **N1** and second negative electrode **N2** are separately electrically connected to the power module through conductive supports such as conductive supports **51a**, **51b** and power module **518** shown in FIG. **15A**.

[0242] In more detail, the connection relationship between positive electrode **P1**, first negative electrode **N1** and second negative electrode **N2** may be shown as FIG. **19B** or FIG. **19C**, in which FIG. **19B** and FIG. **19C** are two schematic views of electrical connections of the LED filament according to some embodiments of the present invention. Please refer to FIG. **19B** first. In this embodiment, positive electrode **P1** of LED filament **100** is electrically connected to a first output terminal (also called “positive output terminal”) of power module **518**. First and second negative electrodes **N1**, **N2** of LED filament **100** are electrically connected together and then jointly

electrically connected to a second output terminal (also called “negative output terminal”) of power module **518**. Further refer to FIG. **19A**, under the electrical relationship shown in FIG. **19B**, LED sections **402**, **404** can be deemed as being electrically connected to the output terminals of power module **518** in parallel. Thus, all LED sections **402**, **404** are driven by driving voltage **V1** between the first and second output terminals. Under a precondition of LED sections **402**, **404** having identical or similar chips number and arrangement, the driving current from power module **518** will evenly dividedly flow to each of LED sections **402**, **404**. As a result, LED sections **402**, **404** can present approximately even intensity and/or color temperature.

[0243] Please further refer to FIG. **19C**. In this embodiment, positive electrode **P1** of LED filament **100** is electrically connected to the first output terminal of power module **518**, first negative electrode **N1** of LED filament **100** is electrically connected to the second output terminal (also called “first negative output terminal”) of power module **518**, and the second negative electrode **N2** of LED filament **100** is electrically connected to the third output terminal (also called “second negative output terminal”) of power module **518**. Driving voltage **V1** is formed between the first output terminal and the second output terminal of power module **518**, and another driving voltage **V2** is formed between the first output terminal and the third output terminal of power module **518**. Referring to FIG. **19A** together, under the electrical relationship shown in FIG. **19C**, LED section **402** is electrically connected between the first output terminal and the second output terminal, and LED section **404** is electrically connected between the first output terminal and the third output terminal. As a result, LED sections **402** and **404** can be deemed as being driven by driving voltages **V1**, and **V2**, respectively. In such an arrangement, the driving currents provided by power module **518** to LED sections **402**, **404** can be independently controlled by adjusting output voltages **V1** and **V2**, so as to make LED sections **402**, **404** separately generate corresponding intensity and/or color temperature. In other words, dimming the different LED sections individually on a single LED filament can be implemented by design and control of the power module based on the arrangement of FIG. **19C**.

[0244] In some embodiments, the second and third output terminals of power module **518** can be electrically connected together through a resistor, and either of the second and third output terminals of the power module **518** is electrically connected to a ground terminal. By this arrangement, negative output terminals with different levels can be obtained to generate two different driving voltages **V1** and **V2**. In some embodiments, levels of the second and third output terminals can be controlled by a circuit. The present invention is not limited thereto.

[0245] FIG. **20A** is a schematic circuit diagram of the LED filament according to some embodiments of the present invention. In this embodiment, LED filament **100**, which is similar to the one shown in FIG. **19A**, has two LED sections **402**, **404**, and thus the details of the LED sections **402**, **404** will not be repeated herein. A main difference between this embodiment and the embodiment shown in FIG. **19A** is that cathodes of LED sections **402**, **404** of this embodiment are electrically connected together to serve as negative electrode **N1** of the LED filament, and anodes of LED sections **402**, **404** serve as first positive electrode **P1** and second positive electrode **P2** of LED filament **100**, respectively. Negative electrode **N1**, first positive electrode **P1** and second positive electrode **P2** of LED filament **100** are electrically connected to the power module through conductive supports, such as conductive supports **51a**, **51b** and power module **518** shown in FIG. **15A**.

[0246] The electrical relationship between negative electrode **N1**, first positive electrode **P1** and second positive electrode **P2** of LED filament **100** and the power module may be shown in FIG. **20B** or FIG. **20C**. FIG. **20B** and FIG. **20C** are two schematic views of electrical connections of the LED filament according to two different embodiments. Please refer to FIG. **20B** first. In this embodiment, a first positive electrode **P1** and a second positive electrode **P2** of LED filament **100** are electrically connected together and jointly electrically connected to a first output terminal (also called “positive output terminal”) of power module **518**. Negative electrode **N1** of LED filament **100**

is electrically connected to a second output terminal (also called “negative output terminal”) of power module **518**. Further refer to FIG. **20A**, under the electrical relationship shown in FIG. **20B**, LED sections **402**, **404** can be deemed as being electrically connected to the output terminals of power module **518** in parallel. Thus, all LED sections **402**, **404** are driven by driving voltage **V1** between the first and second output terminals. Under a precondition of LED sections **402**, **404** having identical or similar chips number and arrangement, the driving current from power module **518** will evenly dividedly flow to each of LED sections **402**, **404**. As a result, LED sections **402**, **404** can present approximately even intensity and/or color temperature. This arrangement is equivalent to that of the embodiment shown in FIG. **20B**.

[0247] Please further refer to FIG. **20C**. In this embodiment, positive electrode **P1** of LED filament **100** is electrically connected to the first output terminal of power module **518**, second positive electrode **P2** of LED filament **100** is electrically connected to the second output terminal (also called “second positive output terminal”) of power module **518**, and negative electrode **N1** of LED filament **100** is electrically connected to the third output terminal (also called “negative output terminal”) of power module **518**. Driving voltage **V1** is formed between the first output terminal and the third output terminal of power module **518**, and another driving voltage **V2** is formed between the second output terminal and the third output terminal of power module **518**. Please further refer to FIG. **20A**. Under the electrical relationship shown in FIG. **20C**, LED section **402** is electrically connected between the first output terminal and the third output terminal, and LED section **404** is electrically connected between the second output terminal and the third output terminal. As a result, LED sections **402** and **404** can be deemed as being driven by driving voltages **V1**, and **V2**, respectively. In such an arrangement, the driving currents provided by power module **518** to LED sections **402**, **404** can be independently controlled by adjusting output voltages **V1**, **V2** so as to make LED sections **402**, **404** separately generate corresponding intensity and/or color temperature. In other words, in the arrangement of FIG. **20C**, a dimming function can be implemented to a single LED filament by design and control of the power module.

[0248] FIG. **21A** is a schematic circuit diagram of the LED filament according to some embodiments of the present invention. In this embodiment, LED filament **100** has three LED sections **402**, **404**, **406** as shown in FIG. **21A**. In detail, LED filament **100** of this embodiment is based on FIG. **19A** and adds LED section **406** (also deemed as being based on FIG. **20A** and adding LED section **404** in FIG. **21A**, wherein LED section **406** in FIG. **21A** corresponds to LED section **404** in FIG. **20A**). The arrangement of LED sections **402**, **404** can refer to the above embodiments, it will not be repeated here. In this embodiment, the arrangement of LED section **406**, which is identical or similar to that of LED section **402** or **404**, includes one or more LED chips. The LED chips are electrically connected in series. Three LED sections **402**, **404**, **406** have respective current paths after they have been electrically connected (i.e. in parallel). In detail, in this embodiment, cathodes of LED sections **406** and **402** are electrically connected together (i.e. cathodes of LED sections **402**, **406** jointly serve as a first negative electrode **N1**). And anode of LED section **406** serves as a second positive electrode **P2** of LED filament **100**. In other words, In this embodiment, LED filament **100** further includes second positive electrode **P2** formed by connecting to the anode of LED section **406** other than first positive electrode **P1**, first negative electrode **N1** and second negative electrode **N2**.

[0249] In this embodiment, under the arrangement of LED filament **100**, the electrical relationship between LED filament **100** and the power module may be shown in FIG. **21B** to FIG. **21D** to implement the current sharing drive control or sectional independent control. FIG. **20B** and FIG. **20C** are two schematic views of electrical connections of two embodiments of the LED filament. Please refer to FIG. **20B** first. In this embodiment, a first positive electrode **P1** and a second positive electrode **P2** of LED filament **100** are electrically connected together and jointly electrically connected to a first output terminal (also called “positive output terminal”) of power module **518**. First negative electrode **N1** and second negative electrode **N2** of LED filament **100**

are electrically connected together and electrically connected to a second output terminal (also called “negative output terminal”) of power module **518**. Further refer to FIG. **21A**, under the electrical relationship shown in FIG. **21B**, LED sections **402**, **404**, **406** can be deemed as being electrically connected to the output terminals of power module **518** in parallel. Thus, all LED sections **402**, **404**, **406** are driven by driving voltage V_1 between the first and second output terminals. Under a precondition of LED sections **402**, **404**, **406** having identical or similar chips number and arrangement, the driving current from power module **518** will evenly dividedly flow to each of LED sections **402**, **404**, **406**. As a result, LED sections **402**, **404**, **406** can present approximately even intensity and/or color temperature. This arrangement is equivalent to that of the embodiment shown in FIGS. **19B** and **20B**.

[0250] Please further refer to FIG. **21C**. In this embodiment, first positive electrode **P1** and second positive electrode **P2** of LED filament **100** are electrically connected together and jointly electrically connected to the first output terminal (also called “first positive output terminal”) of power module **518**, first negative electrode **N1** of LED filament **100** is electrically connected to the second output terminal (also called “first negative output terminal”) of power module **518**, and second negative electrode **N2** of LED filament **100** is electrically connected to the third output terminal (also called “second negative output terminal”) of power module **518**. Under such an arrangement, both first positive electrode **P1** and second positive electrode **P2** can be deemed as the same terminal. Thus, the whole circuit is equivalent to FIG. **19C**. Related control manner, functions and effects can refer to the description of FIG. **19C**. The arrangement of this embodiment can make a single filament have a two-stage dimming effect.

[0251] Please further refer to FIG. **21D**. In this embodiment, first positive electrode **P1** of LED filament **100** is electrically connected to the first output terminal (also called “first positive output terminal”) of power module **518**, second positive electrode **P2** of LED filament **100** is electrically connected to the second output terminal (also called “second positive output terminal”) of power module **518**, first negative electrode **N1** of LED filament **100** is electrically connected to the third output terminal (also called “first negative output terminal”), and second negative electrode **N2** is electrically connected to fourth output terminal (also called “second negative output terminal”) of power module **518**. Further refer to FIG. **21A**, under such an arrangement shown in FIG. **21D**, LED section **402** is electrically connected between the first and third terminals, LED section **404** is electrically connected between the first and fourth output terminals, and LED section **406** is electrically connected between the second and third terminals. Thus, LED sections **402**, **404**, **406** can be deemed as being driven by driving voltages V_1 , V_2 , V_3 , respectively. In such an arrangement, the driving currents provided by power module **518** to LED sections **402**, **404**, **406** can be independently controlled by adjusting output voltages V_2 , V_2 , V_3 so as to make LED sections **402**, **404**, **406** separately generate corresponding intensity and/or color temperature. The arrangement of this embodiment can make a single filament have a three-stage dimming effect.

[0252] FIG. **22A** is a schematic circuit diagram of an embodiment of the LED filament of the present invention. In this embodiment, LED filament **100** has four LED sections **402**, **404**, **406**, **408** as shown in FIG. **22A**. In detail, LED filament **100** of this embodiment is based on FIG. **21A** and further includes LED section **408**. The arrangement of LED sections **402**, **404**, **406** can refer to the above embodiments, it will not be repeated here. In this embodiment, the arrangement of LED section **408**, which is identical or similar to that of LED section **402**, **404** or **406**, includes one or more LED chips. The LED chips are electrically connected in series. Three LED sections **402**, **404**, **406**, **408** have respective current paths after they have been electrically connected (i.e. in parallel). In detail, cathodes of LED sections **408** and **404** are electrically connected together (i.e. cathodes of LED sections **402**, **406** jointly serve as a second negative electrode **N2**). And anode of LED section **408** serves as a third positive electrode **P3** of LED filament **100**. In other words, In this embodiment, LED filament **100** further includes third positive electrode **P3** formed by connecting to the anode of LED section **408** other than first positive electrode **P1**, second positive electrode

P2, first negative electrode **N1** and second negative electrode **N2**.

[0253] In this embodiment, under the arrangement of LED filament **100**, the electrical relationship between LED filament **100** and the power module may be shown in FIG. **22B** to FIG. **22E** to implement the current sharing drive control or sectional independent control. FIG. **22B** to FIG. **22E** are four schematic views of electrical connections of four embodiments of the LED filament. Please refer to FIG. **22B** first. In this embodiment, a first positive electrode **P1**, a second positive electrode **P2** and a third positive electrode **P3** of LED filament **100** are electrically connected together and jointly electrically connected to a first output terminal (also called “positive output terminal”) of power module **518**. First negative electrode **N1** and second negative electrode **N2** of LED filament **100** are electrically connected together and electrically connected to a second output terminal (also called “negative output terminal”) of power module **518**. Further refer to FIG. **22A**, under the electrical relationship shown in FIG. **22B**, LED sections **402**, **404**, **406**, **408** can be deemed as being electrically connected to the output terminals of power module **518** in parallel. Thus, all LED sections **402**, **404**, **406**, **408** are driven by driving voltage **V1** between the first and second output terminals. Under a precondition of LED sections **402**, **404**, **406**, **408** having identical or similar chips number and arrangement, the driving current from power module **518** will evenly dividedly flow to each of LED sections **402**, **404**, **406**, **408**. As a result, LED sections **402**, **404**, **406** can present approximately even intensity and/or color temperature. This arrangement is equivalent to that of the embodiment shown in FIG. **19B**, FIG. **20B**, and FIG. **21B**.

[0254] Please further refer to FIG. **22C**. In this embodiment, first positive electrode **P1**, second positive electrode **P2** and third positive electrode **P3** of LED filament **100** are electrically connected together and jointly electrically connected to the first output terminal (also called “first positive output terminal”) of power module **518**, first negative electrode **N1** of LED filament **100** is electrically connected to second output terminal (also called “first negative output terminal”) of power module **518**, and second negative electrode **N2** of LED filament **100** is electrically connected to the third output terminal (also called “second negative output terminal”) of power module **518**. Under such an arrangement, first positive electrode **P1**, second positive electrode **P2** and third positive electrode **P3** can be deemed as the same terminal. Thus, the whole circuit is equivalent to FIG. **19C**. Related control manner, functions and effects can refer to the description of FIG. **19C**. The arrangement of this embodiment can make a single filament have a two-stage dimming effect.

[0255] Please further refer to FIG. **22D**. In this embodiment, first positive electrode **P1** and second positive electrode **P2** of LED filament **100** are electrically connected to the first output terminal (also called “first positive output terminal”) of power module **518**, third positive electrode **P3** of LED filament **100** is electrically connected to the second output terminal (also called “second positive output terminal”) of power module **518**, first negative electrode **N1** of LED filament **100** is electrically connected to the third output terminal (also called “first negative output terminal”), and second negative electrode **N2** is electrically connected to the fourth output terminal (also called “second negative output terminal”) of power module **518**. Under such an arrangement, first positive electrode **P1** and second positive electrode **P2** can be deemed as the same terminal. Thus, the whole circuit is equivalent to FIG. **21D**. Related control manner, functions and effects can refer to the description of FIG. **21D**. The arrangement of this embodiment can make a single filament have a three-stage dimming effect.

[0256] Please further refer to FIG. **22E**. In this embodiment, first positive electrode **P1** of LED filament **100** is electrically connected to the first output terminal (also called “first positive output terminal”) of power module **518**, second positive electrode **P2** of LED filament **100** is electrically connected to the second output terminal (also called “second positive output terminal”) of power module **518**, third positive electrode **P3** of LED filament **100** is electrically connected to the third output terminal (also called “third positive output terminal”) of power module **518**, first negative electrode **N1** of LED filament **100** is electrically connected to the fourth output terminal (also

called “first negative output terminal”), and second negative electrode N2 is electrically connected to the fifth output terminal (also called “second negative output terminal”) of power module **518**. Under such an arrangement, a driving voltage V1 is formed between the first output terminal and the fourth output terminal of power module **518**, another driving voltage V2 is formed between the first output terminal and the fifth output terminal of power module **518**, still another driving voltage V3 is formed between the second output terminal and the fourth output terminal of power module **518**, and yet another driving voltage V4 is formed between the third output terminal and the fifth output terminal of power module **518**. Further refer to FIG. 22A, under the electrical relationship shown in FIG. 22E, LED section **402** is electrically connected between the first and fourth terminals, LED section **404** is electrically connected between the first and fifth output terminals, LED section **406** is electrically connected between the second and fourth terminals, and LED section **408** is electrically connected between the third and fifth output terminals. Thus, LED sections **402**, **404**, **406**, **408** can be deemed as being driven by driving voltages V1, V2, V3, V4, respectively. In such an arrangement, the driving currents provided by power module **518** to LED sections **402**, **404**, **406**, **408** can be independently controlled by adjusting output voltages V2, V2, V3, V4 so as to make LED sections **402**, **404**, **406**, **408** separately generate corresponding intensity and/or color temperature. The arrangement of this embodiment can make a single filament have a four-stage dimming effect.

[0257] In sum, according to the abovementioned embodiments, the description has clearly disclosed a strip of filament with multiple dimming control by two, three or four LED sections. According to the description, a person having ordinary skill in the art can easily implement a strip of filament with multiple dimming control by five or more LED sections.

[0258] Next part of the present disclosure will describe the circuit design of the driving circuit of the filament bulb. From circuit perspective, power module **518** in FIG. 15A may be represented by a circuit block **5200** (below described and referred to as “power module **5200**”) as shown in FIG. 23. FIG. 23 is a circuit block diagram of a power module of an LED filament bulb according to some embodiments of present invention. Referring to FIG. 23, power module **5200** includes a rectifying circuit **5210**, a filtering circuit **5220**, and a driving circuit **5230**. Rectifying circuit **5210** is coupled to a first pin **5201** and a second pin **5202**, also known as external connection terminals, to receive and then rectify an external driving signal Pin, in order to output a rectified signal Srec through a first rectifying output terminal **5211** and a second rectifying output terminal **5212**. In different embodiments, external driving signal Pin may be an AC driving signal, an AC power supply signal (such as a power grid signal), or even a DC signal, which choices each typically do not affect operations of the LED filament bulb. When the LED filament bulb is designed to emit light or light up based on a DC signal, rectifying circuit **5210** in power module **5200** may be omitted. In a configuration without rectifying circuit **5210**, first rectifying output terminal **5211** and second rectifying output terminal **5212** would be directly coupled to input terminals (as **5211** and **5212**) of filtering circuit **5220**.

[0259] Filtering circuit **5220** is coupled to rectifying circuit **5210** in order to filter rectified signal Srec, that is, input terminals of filtering circuit **5220** are coupled to first rectifying output terminal **5211** and second rectifying output terminal **5212** to receive and then filter rectified signal Srec, in order to output a filtered signal Sflr through a first filtering output terminal **5221** and a second filtering output terminal **5222**. First rectifying output terminal **5211** may be regarded as a first filtering input terminal and second rectifying output terminal **5212** may be regarded as a second filtering input terminal, of filtering circuit **5220**. In this embodiment, filtering circuit **5220** may filter out ripples in rectified signal Srec, to make the waveform of produced filtered signal Sflr smoother than that of rectified signal Srec. Besides, circuit configuration of filtering circuit **5220** may be set to realize filtering with respect to a certain or specific (band of) frequency, to filter out frequency response or output energy at a certain or specific frequency in response to external driving signal Pin.

[0260] Driving circuit **5230** is coupled to filtering circuit **5220**, to receive and then perform power conversion to filtered signal **Sflr**, in order to generate a driving power **Sdrv**, that is, input terminals of driving circuit **5230** are coupled to first filtering output terminal **5221** and second filtering output terminal **5222** to receive filtered signal **Sflr** and then generate driving power **Sdrv** used for driving LED filament module **100** for emitting light. First filtering output terminal **5221** may be regarded as a first driving input terminal and second filtering output terminal **5222** may be regarded as a second driving input terminal, of driving circuit **5230**. Driving power **Sdrv** generated by driving circuit **5230** is then provided to LED filament module **100** through a first driving output terminal and a second driving output terminal, to enable an LED filament (as **100**) of LED filament module **100** to light up in response to driving power **Sdrv**. Some embodiments of rectifying circuit **5210**, filtering circuit **5220**, and driving circuit **5230** of power module **5200** in possible configurations are presented and described below, but the invention is not limited thereto.

[0261] FIG. **24A** is a circuit diagram of a rectifying circuit according to some embodiments of present invention. Referring to FIG. **24A**, rectifying circuit **5310** is a bridge rectifier including diodes **5311-5314** used for performing (full-wave) rectification to a received signal. Diode **5311** has an anode coupled to a second rectifying output terminal **5212**, and a cathode coupled to a second pin **5202**. Diode **5312** has an anode coupled to second rectifying output terminal **5212**, and a cathode coupled to a first pin **5201**. Diode **5313** has an anode coupled to second pin **5202**, and a cathode coupled to a first rectifying output terminal **5211**. And diode **5314** has an anode coupled to first pin **5201**, and a cathode coupled to first rectifying output terminal **5211**. In this embodiment, diodes **5311-5314** may be referred to as first diode **5311**, second diode **5312**, third diode **5313**, and fourth diode **5314**.

[0262] Operations of rectifying circuit **5310** when first and second pins **5201** and **5202** receive an AC signal as external driving signal **Pin** are described as follows. During the AC signal's positive half cycle, assuming the voltage level at first pin **5201** being higher than that at second pin **5202**, diodes **5311** and **5314** operate in a forward-biased state to conduct current, while diodes **5312** and **5313** are cut off as being reverse-biased, which states of the four diodes form a circuit loop between the first and second pins **5201** and **5202**. Under the configuration of the diodes during the AC signal's positive half cycle, an input current from or caused by the AC signal flows through first pin **5201**, diode **5314**, and first rectifying output terminal **5211** in sequence into a later-stage load, and after which flows through second rectifying output terminal **5212**, diode **5311**, and second pin **5202** in sequence, out of the LED filament bulb. Accordingly, during the AC signal's negative half cycle, the voltage level at first pin **5202** is higher than that at second pin **5201**, so diodes **5312** and **5313** operate in a forward-biased state to conduct current, while diodes **5311** and **5314** are cut off as being reverse-biased, which states of the four diodes form a circuit loop between first and second pins **5201** and **5202**. Under the configuration of the diodes during the AC signal's negative half cycle, an input current from or caused by the AC signal flows through second pin **5202**, diode **5313**, and first rectifying output terminal **5211** in sequence into a later-stage load, and after which flows through second rectifying output terminal **5212**, diode **5312**, and first pin **5201** in sequence, out of the LED filament bulb. Therefore, no matter during the AC signal's positive or negative half cycle, the positive polarity of rectified signal **Srec** output by rectifying circuit **5310** remains at first rectifying output terminal **5211** and the negative polarity of rectified signal **Srec** remains at second rectifying output terminal **5212**. According to the above description of operations, the rectified signal output by rectifying circuit **5210** is a full-wave rectified signal.

[0263] Operations of rectifying circuit **5310** when first and second pins **5201** and **5202** are coupled to a DC power supply to receive a DC signal therefrom as external driving signal **Pin** are described as follows. When first pin **5201** is coupled to the positive electrode, and second pin **5202** is coupled to the negative electrode, of the DC power supply, diodes **5311** and **5314** operate in a forward-biased state to conduct current, while diodes **5312** and **5313** are cut off as being reverse-biased, which states of the four diodes form a circuit loop between first and second pins **5201** and **5202**. In

this case the circuit configuration and operations of rectifying circuit **5310** are the same as those of rectifying circuit **5310** under and during the above-described AC signal's positive half cycle. On the other hand, when first pin **5201** is coupled to the negative electrode, and second pin **5202** is coupled to the positive electrode, of the DC power supply, diodes **5312** and **5313** operate in a forward-biased state to conduct current, while diodes **5311** and **5314** are cut off as being reverse-biased, which states of the four diodes form a circuit loop between first and second pins **5201** and **5202**. In this case the circuit configuration and operations of rectifying circuit **5310** are the same as those of rectifying circuit **5310** under and during the above-described AC signal's negative half cycle.

[0264] From the above description, it is known that no matter whether rectifying circuit **5310** in this embodiment receives an AC signal or a DC signal, rectifying circuit **5310** can properly output rectified signal Srec.

[0265] Besides, in some embodiments, a capacitor Cx may be disposed between input terminals of rectifying circuit **5310**, wherein capacitance of capacitor Cx may be for example 47 nF and capacitor Cx may be used to reduce EMI (: electromagnetic interference) effects of power module **5200**.

[0266] FIG. **24B** is a circuit diagram of a rectifying circuit according to some embodiment of present invention. Referring to FIG. **24B**, rectifying circuit **5410** includes diodes **5411** and **5412** used for performing (half-wave) rectification to a received signal. Diode **5411** has an anode coupled to second pin **5202**, and a cathode coupled to first rectifying output terminal **5211**. Diode **5412** has an anode coupled to first rectifying output terminal **5211**, and a cathode coupled to first pin **5201**. Depending on practical applications involving rectifying circuit **5210**, second rectifying output terminal **5212** may be omitted or grounded. In this embodiment, diodes **5411** and **5412** may be referred to as a first diode **5411** and a second diode **5412**.

[0267] Next, in a similar vein, what follows are descriptions of operations of rectifying circuit **5410** under the two operational situations of when the received signal is an AC signal and when the received signal is a DC signal, respectively.

[0268] Operations of rectifying circuit **5410** when first and second pins **5201** and **5202** receive an AC signal as external driving signal Pin are described as follows. During the AC signal's positive half cycle, assuming the input voltage level at first pin **5201** from the AC signal being higher than that at second pin **5202**, diodes **5411** and **5412** are in a reverse-biased state, so rectifying circuit **5410** ceases to output rectified signal Srec, or rectified signal Srec output by rectifying circuit **5410** is at a zero level. On the other hand, during the AC signal's negative half cycle, the input voltage level at first pin **5201** from the AC signal is lower than that at second pin **5202**, so diodes **5411** and **5412** operate in a forward-biased state to conduct current, causing the AC signal to flow through diode **5411** and first rectifying output terminal **5211** into a later-stage load, after which the current of the AC signal flowing out through second rectifying output terminal **5212**, another circuit of the LED filament bulb, or a ground terminal. According to the above description of operations, the rectified signal output by rectifying circuit **5410** is a half-wave rectified signal.

[0269] Operations of rectifying circuit **5410** when first and second pins **5201** and **5202** are coupled to a DC power supply to receive a DC signal as external driving signal Pin are described as follows. When first pin **5201** is coupled to the positive electrode, and second pin **5202** is coupled to the negative electrode, of the DC power supply, diodes **5411** and **5412** are cut off as being reverse-biased, so rectifying circuit **5410** ceases to output rectified signal Srec. On the other hand, when first pin **5201** is coupled to the negative electrode, and second pin **5202** is coupled to the positive electrode, of the DC power supply, diodes **5411** and **5412** operate in a forward-biased state to conduct current forming a circuit loop, so in this case the circuit configuration and operations of rectifying circuit **5410** are the same as those of rectifying circuit **5410** under and during the above-described AC signal's negative half cycle. From this description, in this embodiment, when first pin **5201** is coupled to the negative electrode, and second pin **5202** is coupled to the positive electrode,

of the DC power supply, the rectifying circuit **5410** can still operate normally.

[0270] FIG. **25A** is a circuit diagram of a filtering circuit according to some embodiments of present invention. Referring to FIG. **25A**, the filtering circuit **5320** includes an inductor **5321**, resistors **5322** and **5323**, and capacitors **5324** and **5325**. Inductor **5321** has a first end coupled to first rectifying output terminal **5211**, and has a second end coupled to a first filtering output terminal **5221**. So inductor **5321** is electrically connected between first rectifying output terminal **5211** and first filtering output terminal **5221** in series. Resistor **5322** has a first end coupled to first rectifying output terminal **5211** and the first end of inductor **5321**, and has a second end coupled to first filtering output terminal **5221** and the second end of inductor **5321**. So resistor **5322** and inductor **5321** are electrically connected in parallel. Resistor **5323** has a first end coupled to first filtering output terminal **5221** and the second end of inductor **5321**. Capacitor **5324** has a first end coupled to first filtering output terminal **5221** and the second end of inductor **5321**, and has a second end coupled to second rectifying output terminal **5212** and second filtering output terminal **5222**, wherein second rectifying output terminal **5212** and second filtering output terminal **5222** may be regarded as the same terminal and/or a ground terminal GND. Capacitor **5325** has a first end coupled to a second end of resistor **5323**, and has a second end coupled to second rectifying output terminal **5212** and second filtering output terminal **5222**. Under the structure and configuration of filtering circuit **5320** in this embodiment, filtering circuit **5320** can perform low-pass filtering to rectified signal S_{rec} , to filter out high-frequency components of rectified signal S_{rec} so as to produce a filtered signal S_{flr} then output through first and second filtering output terminals **5221** and **5222**.

[0271] FIG. **25B** is a circuit diagram of a filtering circuit according to some embodiments of the present invention. Referring to FIG. **25B**, filtering circuit **5420** comprises a π -shape filtering circuit and includes an inductor **5421**, capacitors **5422**, **5423**, and **5424**, and resistors **5425** and **5426**. Inductor **5421** has a first end coupled to first rectifying output terminal **5211**, and has a second end coupled to a first filtering output terminal **5221**. So inductor **5421** is electrically connected between first rectifying output terminal **5211** and first filtering output terminal **5221** in series. Capacitor **5422** has a first end coupled to first rectifying output terminal **5211** and first end of inductor **5421**, and has a second end coupled to second rectifying output terminal **5212** and a second filtering output terminal **5222**, so the first end of capacitor **5422** is coupled to first filtering output terminal **5221** through inductor **5421**. Capacitor **5423** has a first end coupled to first filtering output terminal **5221** and the second end of inductor **5421**, and has a second end coupled to second rectifying output terminal **5212** and second filtering output terminal **5222**, so the first end of capacitor **5423** is coupled to first rectifying output terminal **5211** through inductor **5421**. Capacitor **5424** has a first end coupled to first filtering output terminal **5221** and the second end of inductor **5421**, and has a second end coupled to first ends respectively of resistors **5425** and **5426**, whose respective second ends are coupled to second rectifying output terminal **5212** and second filtering output terminal **5222**.

[0272] By way of structural equivalence, the positional structure of inductor **5421** and capacitor **5423** of filtering circuit **5420** is similar to that of inductor **5321** and capacitor **5324** of filtering circuit **5320**. Compared to filtering circuit **5320** in FIG. **25A**, filtering circuit **5420** further includes capacitor **5422**, which is similar to inductor **5421** and capacitor **5423** in having a low-pass filtering function. So compared to filtering circuit **5320** in FIG. **25A**, filtering circuit **5420** has better ability to filter out high-frequency components, which ability causes the waveform of its output filtered signal S_{flr} to be smoother.

[0273] Inductors **5321** and **5421** in the above embodiments each have an inductance preferably in the range of about 10 nH~10 mH. And capacitors **5324**, **5325**, **5422**, **5423**, and **5424** each have a capacitance preferably in the range of about 100 pF~1 μ F.

[0274] FIG. **26** is a circuit diagram of a driving circuit according to some embodiments of the present invention. Referring to FIG. **26**, the driving circuit **5330** includes a switching control circuit

5331 and a conversion circuit **5332**, for performing power conversion based on, or in a mode of being, a current source, in order to drive the LED filament module to emit light. Conversion circuit **5332** includes a switching circuit PSW (which may be referred to as a power switch) and an energy storage circuit ESE. And conversion circuit **5332** is coupled to first and second filtering output terminals **5221** and **5222** to receive and then convert filtered signal Sflr, under the control by switching control circuit **5331**, into a driving power Sdrv to be output at a first and a second driving output terminals **5231** and **5232** for driving the LED filament module. Under the control by switching control circuit **5331**, driving power Sdrv output by conversion circuit **5332** comprises a steady current, causing the LED filament module to steadily emit light. Besides, driving circuit **5330** may further include a biasing circuit **5333**, which may be configured to generate working voltage Vcc based on voltage on an input power line of the power module, wherein working voltage Vcc is provided to and used by switching control circuit **5331**, so that switching control circuit **5331** can be activated and then operate in response to working voltage Vcc.

[0275] Next, operations of driving circuit **5330** are further described with reference to the illustrating signal waveforms shown in FIG. 27A to FIG. 27D. FIG. 27A FIG. 27D are signal waveform diagrams related to and in different embodiments of operating the driving circuit (**5230/5330**). FIG. 27A and FIG. 27B illustrate signal waveforms and control situation in an embodiment of operating driving circuit **5330** in a continuous-conduction mode (CCM). FIG. 27C and FIG. 27D illustrate signal waveforms and control situation in an embodiment of operating driving circuit **5330** in a discontinuous-conduction mode (DCM). In the signal-waveform diagrams, the horizontal axis represents time, which is denoted by “t”, and the vertical axis represents the variable of voltage or current depending on which type of signal is being described or referred to.

[0276] Switching control circuit **5331** in this embodiment is configured to perform real-time regulation or adjusting of the duty cycle of a lighting control signal Slc according to current operational states of the LED filament bulb, in order to turn on or turn off switching circuit PSW according to or in response to lighting control signal Slc. Switching control circuit **5331** can determine or judge a current operational state of the LED filament bulb by detecting one or more of an input voltage (such as a voltage level on first pin **5201** or second pin **5202**, on first rectifying output terminal **5211**, or on first filtering output terminal **5221**), an output voltage (such as a voltage level on first driving output terminal **5231**), an input current (such as a current on the input power line or flowing through rectifying output terminal **5211/5212** and filtering output terminal **5221/5222**), and an output current (such as a current flowing through driving output terminal **5231/5232** or through switching circuit PSW). Energy storage circuit ESE is configured to alternate or switch its operation between being charged with energy and discharging energy, according to the state of switching circuit PSW being turned on or turned off, in order to maintain or make a driving current ILED received by the LED filament module be stable above a predefined current value Ipred. Lighting control signal Slc has a fixed signal period Tlc and a signal amplitude, wherein the pulse on time (such as Ton1, Ton2, or Ton3, and also referred to as a pulse width) during each of signal period Tlc may be adjusted according to control needs. And the duty cycle of lighting control signal Slc is the ratio of the pulse on time to signal period Tlc. For example, if pulse on time Ton1 is 40% of signal period Tlc, this means the duty cycle of lighting control signal Slc during first signal period Tlc is 0.4.

[0277] FIG. 27A illustrates variations in signal waveforms during multiple consecutive signal periods Tlc related to operating driving circuit **5330** when driving current ILED is below predefined current value Ipred. Referring to both FIG. 26 and FIG. 27A, specifically, during first signal period Tlc, switching circuit PSW conducts current during pulse on time Ton1 when lighting control signal Slc is at a high level. So during pulse on time Ton1, in addition to generating driving current ILED for LED filament module **100** according to input power supply received from first filtering output terminal **5221** and second filtering output terminal **5222**, conversion circuit **5332** electrically charges energy storage circuit ESE through conducting switching circuit PSW so as to

gradually increase a current signal I_L flowing through energy storage circuit ESE. In other words, during pulse on time T_{on1} , energy storage circuit ESE is electrically charged to store energy in response to the input power supply received from first filtering output terminal **5221** and second filtering output terminal **5222**.

[0278] Subsequently, upon the end of pulse on time T_{on1} , switching circuit PSW is turned off or not conducting in response to lighting control signal S_{lc} being at a low level. During the time that switching circuit PSW is turned off, the input power supply received from first filtering output terminal **5221** and second filtering output terminal **5222** is not provided to the LED filament module, but instead energy storage circuit ESE discharges electrical energy to generate driving current I_{LED} for the LED filament module, wherein current signal I_L flowing through energy storage circuit ESE gradually decreases due to the energy discharging. Therefore, even when lighting control signal S_{lc} is at a low level, that is, when switching circuit PSW is turned off or disabled, driving circuit **5330** continues to provide electrical power to the LED filament module due to the energy discharging from and by energy storage circuit ESE. In other words for this case, no matter whether switching circuit PSW is turned on or turned off, driving circuit **5330** will continually provide a stable driving current I_{LED} to the LED filament module, wherein the current value of driving current I_{LED} during first signal period T_{lc} is about I_1 as shown in FIG. **27A**.

[0279] During first signal period T_{lc} , switching control circuit **5331** judges that current value I_1 of driving current I_{LED} is below a predefined current value I_{pred} , according to a current detection signal indicative of a working state of the LED filament. Thus upon entering into second signal period T_{lc} , switching control circuit **5331** adjusts the pulse on time of lighting control signal S_{lc} into T_{on2} , which is equal to pulse on time T_{on1} plus a unit duration t_1 .

[0280] During second signal period T_{lc} , operations of switching circuit PSW and energy storage circuit ESE are similar to their operations during the previous or first signal period T_{lc} . The difference(s) in operations between two signal periods T_{lc} is mainly that since pulse on time T_{on2} is longer than pulse on time T_{on1} , the charging time and discharging time of energy storage circuit ESE during second signal period T_{lc} are longer and shorter respectively than their counterparts during first signal period T_{lc} , causing an average value I_2 of driving current I_{LED} provided by driving circuit **5330** during second signal period T_{lc} higher than current value I_1 and closer to predefined current value I_{pred} .

[0281] Similarly, since at this stage current value I_2 of driving current I_{LED} is still below predefined current value I_{pred} , during third signal period T_{lc} switching control circuit **5331** again adjusts the pulse on time of lighting control signal S_{lc} into T_{on3} , which is equal to pulse on time T_{on2} plus unit duration t_1 or equal to pulse on time T_{on1} plus duration t_2 of 2 unit durations t_1 . During third signal period T_{lc} , operations of switching circuit PSW and energy storage circuit ESE are similar to their operations during each of first two signal periods T_{lc} . Because pulse on time T_{on3} is further longer than pulse on time T_{on2} , the current value of driving current I_{LED} provided by driving circuit **5330** during third signal period T_{lc} is raised to I_3 approximately reaching predefined current value I_{pred} . Afterwards, since current value I_3 of driving current I_{LED} during third signal period T_{lc} has reached predefined current value I_{pred} , switching control circuit **5331** maintains a constant duty cycle of lighting control signal S_{lc} , to maintain the current value of driving current I_{LED} continually at predefined current value I_{pred} .

[0282] FIG. **27B** illustrates variations in signal waveforms during multiple consecutive signal periods T_{lc} related to operating driving circuit **5330** when driving current I_{LED} is above predefined current value I_{pred} . Referring to both FIG. **26** and FIG. **27B**, specifically, during first signal periods T_{lc} shown in FIG. **27B**, switching circuit PSW conducts current during pulse on time T_{on1} when lighting control signal S_{lc} is at a high level. So during pulse on time T_{on1} , in addition to generating driving current I_{LED} for LED filament module **18** according to input power supply received from first filtering output terminal **5221** and second filtering output terminal **5222**, conversion circuit **5332** electrically charges energy storage circuit ESE through conducting

switching circuit PSW so as to gradually increase a current signal IL flowing through energy storage circuit ESE. In other words, during pulse on time Ton1, energy storage circuit ESE is electrically charged to store energy in response to the input power supply received from first filtering output terminal 5221 and second filtering output terminal 5222.

[0283] Subsequently, upon the end of pulse on time Ton1, switching circuit PSW is turned off or not conducting in response to lighting control signal Slc being at a low level. During the time that switching circuit PSW is turned off, the input power supply received from first filtering output terminal 5221 and second filtering output terminal 5222 is not provided to LED filament module 100, but instead energy storage circuit ESE discharges electrical energy to generate driving current ILED for LED filament module 100, wherein current signal IL flowing through energy storage circuit ESE gradually decreases due to the energy discharging. Therefore, even when lighting control signal Slc is at a low level, that is, when switching circuit PSW is turned off or disabled, driving circuit 5330 continues to provide electrical power to LED filament module 100 due to the energy discharging from and by energy storage circuit ESE. In other words for this case, no matter whether switching circuit PSW is turned on or turned off, driving circuit 5330 will continually provide a stable driving current ILED to LED filament module 100, wherein the current value of driving current ILED during first signal period Tlc is about 14 as shown in FIG. 27B.

[0284] During first signal period Tlc, switching control circuit 5331 judges that current value I4 of driving current ILED is above a predefined current value Ipred, according to a current detection signal Sdet. Thus upon entering into second signal period Tlc, switching control circuit 5331 adjusts the pulse on time of lighting control signal Slc into Ton2, which is equal to pulse on time Ton1 minus a unit duration t1.

[0285] During second signal period Tlc, operations of switching circuit PSW and energy storage circuit ESE are similar to their operations during previous or first signal period Tlc. The difference(s) in operations between two signal periods Tlc is mainly that since pulse on time Ton2 is shorter than pulse on time Ton1, the charging time and discharging time of energy storage circuit ESE during second signal period Tlc are shorter and longer respectively than their counterparts during first signal period Tlc, causing an average value 15 of driving current ILED provided by driving circuit 5330 during second signal period Tlc lower than current value 14 and closer to predefined current value Ipred.

[0286] Similarly, since at this stage current value 15 of driving current ILED is still above predefined current value Ipred, during third signal period Tlc switching control circuit 5331 again adjusts the pulse on time of lighting control signal Slc into Ton3, which is equal to pulse on time Ton2 minus unit duration t1 or equal to pulse on time Ton1 minus duration t2 of 2 unit durations t1. During third signal period Tlc, operations of switching circuit PSW and energy storage circuit ESE are similar to their operations during each of first two signal periods Tlc. Because pulse on time Ton3 is further shorter than pulse on time Ton2, the value of driving current ILED provided by driving circuit 5330 during third signal period Tlc is lowered to 16 approximately reaching predefined current value Ipred. Afterwards, since current value 16 of driving current ILED during third signal period Tlc has reached predefined current value Ipred, switching control circuit 5331 maintains a constant duty cycle of lighting control signal Slc, to maintain the current value of driving current ILED continually at predefined current value Ipred.

[0287] From the above descriptions of the embodiments of both FIG. 27A and FIG. 27B, it's seen that driving circuit 5330 adjusts the pulse width or pulse on time of lighting control signal Slc for each of consecutive signal periods Tlc, in a stepping manner depending on the level of driving current ILED in relation to predefined current value Ipred, to gradually bring the value of driving current ILED above or below predefined current value Ipred to approach or be closer to predefined current value Ipred, so as to realize outputting of a stable or constant current.

[0288] In addition, the above embodiments of FIG. 27A and FIG. 27B are examples of operating driving circuit 5330 in a continuous-conduction mode, wherein when switching circuit PSW is

turned off energy storage circuit ESE does not discharge current to the extent that current signal IL flowing through energy storage circuit ESE decreases to zero. By using driving circuit **5330** operating in the continuous-conduction mode to provide power for the LED filament module, the electrical power provided to the LED filament module is relatively stable and is not likely to cause signal ripples.

[0289] Next are descriptions of embodiments of a control situation of operating driving circuit **5330** in a discontinuous-conduction mode. Referring to both FIG. **26** and FIG. **27C**, the signal waveforms and operations of the driving circuit **5330** shown by FIG. **27C** are similar to those shown by FIG. **27A**. The difference(s) between the two embodiments of FIG. **27C** and FIG. **27A** is mainly that because driving circuit **5330** in this embodiment of FIG. **27C** operates in a discontinuous-conduction mode, when switching circuit PSW is turned off or disabled by lighting control signal Slc being at a low level energy storage circuit ESE discharges current to the extent that current signal IL flowing through energy storage circuit ESE decreases to zero, followed by energy storage circuit ESE being charged again upon starting of next signal period Tlc. Apart from this difference, description of other operations of this embodiment of FIG. **27C** can be referred to the above description of the embodiment of FIG. **27A** and so is not repeated again.

[0290] Then referring to both FIG. **26** and FIG. **27D**, the signal waveforms and operations of driving circuit **5330** shown by FIG. **27D** are similar to those shown by FIG. **27B**. The difference(s) between the two embodiments of FIG. **27D** and FIG. **27B** is mainly that because driving circuit **5330** in this embodiment of FIG. **27D** operates in a discontinuous-conduction mode, when switching circuit PSW is turned off or disabled by lighting control signal Slc being at a low level energy storage circuit ESE discharges current to the extent that current signal IL flowing through energy storage circuit ESE decreases to zero, followed by energy storage circuit ESE being charged again upon starting of next signal period Tlc. Apart from this difference, description of other operations of this embodiment of FIG. **27D** can be referred to the above description of the embodiment of FIG. **27B** and so is not repeated again.

[0291] By using driving circuit **5330** operating in the discontinuous-conduction mode to provide power for the LED filament module, energy or power loss incurred in performing power conversion by driving circuit **5330** can be reduced, thereby resulting in a higher conversion efficiency. The following are descriptions to introduce and further explain several concrete circuit examples of driving circuit **5330**.

[0292] FIG. **28A** is a circuit diagram of a driving circuit according to some embodiments of the present invention. Referring to FIG. **28A**, in this embodiment, driving circuit **5430** comprises a buck DC-to-DC converter circuit, including a controller **5431**, an output circuit **5432**, a biasing circuit **5433** and a sampling circuit **5434**. Driving circuit **5430** is coupled to first filtering output terminal **5221** and second filtering output terminal **5222** to convert received filtered signal Sflr to driving power Sdrv for driving the LED filament module coupled between first and second driving output terminals **5231** and **5232**.

[0293] Controller **5431** includes for example an integrated-circuit chip, which has a drain-terminal or drain pin Pdrn, a source-terminal or source pin Pcs, an power pin Pvcc, a voltage sampling pin Pln, an overvoltage protection pin Povp, and a ground pin Pgnd. Drain pin Pdrn is coupled to output circuit **5432**. Source pin Pcs is coupled to second filtering output terminal **5222** and ground terminal GND through a resistor Rs. Power pin Pvcc and overvoltage protection pin Povp are coupled to biasing circuit **5433**. Voltage sampling pin Pln is coupled to sampling circuit **5434**. And ground pin Pgnd is coupled to second filtering output terminal **5222** and ground terminal GND.

[0294] In this embodiment of FIG. **28A**, the above-mentioned switching circuit or power switch (PSW) of conversion circuit **5332** is for example integrated in controller **5431**, and has first and second terminals electrically connected to drain pin Pdrn and source pin Pcs respectively. Therefore, controller **5431** can determine current conduction or cutoff at or through drain pin Pdrn, source pin Pcs, and/or corresponding current path(s), by controlling switching of its internal

switching circuit between, or into one of, conduction and cutoff states. In some other embodiments, the above-mentioned switching circuit is a discrete device disposed external to controller **5431**. In applications using a discrete device as switching circuit, definitions or connection-structure of pins of controller **5431** would be adjusted accordingly, such as setting drain pin Pdrn as a pin to be electrically connected to a control terminal of the discrete switching circuit instead and for providing a lighting control signal.

[0295] Output circuit **5432** includes a diode **D1**, an inductor **L1**, a capacitor Co, and a resistor Ro, wherein inductor **L1** and capacitor Co act as (part of) the energy storage circuit (ESE) of conversion circuit **5332**. Diode **D1** acts as a freewheeling diode; has its anode coupled to drain pin Pdrn of controller **5431** so as to be coupled through drain pin Pdrn to the first or drain terminal of the switching circuit (PSW) within controller **5431**; and has its cathode coupled to first driving output terminal **5231**. Inductor **L1** has a first end coupled to the anode of the diode **D1** and the drain pin Pdrn of the controller **5431**, and has a second end coupled to first filtering output terminal **5221** and second driving output terminal **5232**. Resistor Ro and capacitor Co are electrically connected in parallel and coupled between first and second driving output terminals **5231** and **5232**. In this embodiment, first filtering output terminal **5221** and second driving output terminal **5232** can be regarded as the same terminal.

[0296] In this embodiment of FIG. **28A**, the controller **5431** is configured to control current conduction or cutoff on a path between drain pin Pdrn and source pin Pcs. When there is current conduction on the path between drain pin Pdrn and source pin Pcs, a current flows from first filtering output terminal **5221** into driving circuit **5430**, and flows through inductor **L1** and drain pin Pdrn into controller **5431**, and then flows through source pin Pc and second filtering output terminal **5222** to ground terminal GND. In this case of current conduction, the current flowing through inductor **L1** increases with time and causes inductor **L1** to be in a state of storing electrical energy; while the voltage across capacitor Co decreases with time and causes capacitor Co to be in a state of releasing electrical energy in order to maintain the LED filament module as emitting light. On the other hand, when the path between drain pin Pdrn and source pin Pcs is in a cutoff state or not conducting current, inductor **L1** is in a state of releasing or discharging electrical energy and the current flowing through inductor **L1** decreases with time. In this cutoff case the current flowing through inductor **L1** flows through diode **D1**, first driving output terminal **5231**, the LED filament module, second driving output terminals **5232**, and then back to inductor **L1**, forming a current flyback; and capacitor Co is in a state of storing electrical energy with its voltage increasing with time.

[0297] It should be noted that capacitor Co may be omitted. When capacitor Co is omitted, and there is current conduction on the path between drain pin Pdrn and source pin Pcs, a current flowing through inductor **L1** doesn't flow through first filtering output terminal **5221** and second driving output terminal **5232**, so the LED filament module does not emit light. But when the path between drain pin Pdrn and source pin Pcs is in a cutoff state, a current flowing through inductor **L1** flows through freewheeling diode **D1** to the LED filament module to cause the LED filament to emit light. By adjusting or controlling the duration of light emission by the LED filament and the magnitude of current flowing through the LED filament module, an average luminance of the emitted light stable above a defined value can be achieved, so as to achieve a favorable function of emitting stable light. Apart from the above, since driving circuit **5430** of this embodiment takes a non-isolation power-conversion structure, feedback control, if any, of switching circuit or power switch (PSW) performed by controller **5431** may be based on detecting a magnitude of current flowing through the switching circuit or power switch.

[0298] In another aspect, driving circuit **5430** keeps the current flowing through the LED module without variety, so for some LED modules (for example, white, red, blue and green LED modules), it can be improved that color temperature changes with current. In other words, the LED module can keep color temperature constant under different current intensity. Inductor **L1** which serves as

an energy storage circuit releases stored energy when the switching circuit turns off. This makes not only the LED filament keep lighting but also the current in the LED filament does not suddenly drop to the lowest value. When the switching circuit turns on again, it is unnecessary that both current and voltage goes from the lowest value to the highest value. Thereby, discontinuous lighting of LED filament can be avoided to cause the luminance of the LED filament being varied, to decrease the lowest conducting cycle and to raise the driving frequency.

[0299] Biasing circuit **5433** includes capacitor **C1** and resistors **R1-R4**. A first end of capacitor **C1** is electrically connected to power pin **Pvcc**. A second end of capacitor **C1** is electrically connected to second filtering output terminal **5222** and ground terminal **GND**. A first end of resistor **R1** is electrically connected second driving output terminal **5232**. A first end of resistor **R2** is electrically connected to a second end of resistor **R1**. A second end of resistor **R2** is electrically connected to the first end of capacitor **C1** and power pin **Pvcc**. A first end of resistor **R3** is electrically connected a second end of resistor **R1** and the first end of resistor **R2**. A second end of resistor **R3** is electrically connected to overvoltage protection pin **Povp** of controller **5431**. A first end of resistor **R4** is electrically connected to the second end of resistor **R3**. A second end of resistor **R4** is electrically connected to both second filtering output terminal **5222** and ground terminal **GND**.

[0300] Resistors **R1** and **R2** acquire a voltage of second driving output terminal **5232** to generate working voltage **Vcc**. Working voltage **Vcc** is stabilized by capacitor **C1** and transmitted to power pin **Pvcc** for being used by controller **5431**. Resistors **R3** and **R4** acquire or sample a voltage of second driving output terminal **232** by voltage division so that controller **5431** can determine if the overvoltage protection function should be executed or not according to the voltage of overvoltage protection pin **Povp**.

[0301] Sampling circuit **5434** includes capacitor **C2** and resistors **R5-R7**. A first end of capacitor **C2** is electrically connected to voltage sampling pin **Pln**. A second end of capacitor **C2** is electrically connected to both second filtering output terminal **5222** and ground terminal **GND**. A first end of resistor **R5** is electrically connected to both first filtering output terminal **5221** and second driving output terminal **5232**. A first end of resistor **R6** is electrically connected to a second end of resistor **R5**. A second end of resistor **R6** is electrically connected to both second filtering output terminal **5222** and ground terminal **GND**. A first end of resistor **R7** is electrically connected to both the second end of resistor **R7** and the first end of resistor **R6**. A second end of resistor **R7** is electrically connected to both voltage sampling pin **Pln** and the first end of capacitor **C2**.

[0302] Resistors **R5** and **R6** acquire or sample a voltage of the power line (i.e. the voltage of first filtering output terminal **5221**) by voltage division. The sampled voltage is transmitted to voltage sampling pin **Pln** of controller **5431** through resistor **R7**. Capacitor **C2** is used for stabilizing a voltage of voltage sampling pin **Pin**.

[0303] Please refer to FIG. **28B**, which is a schematic circuit diagram of the driving circuit according to some embodiments of the present invention. In this embodiment, a boost DC-to-DC converter serves as the driving circuit **5530** as an example, which includes controller **5531**, output circuit **5532**, biasing circuit **5533** and sampling circuit **5534**. The driving circuit is electrically connected to both first filtering output terminal **5221** and second filtering terminal **5222** for converting the received filtered signal **Sflr** into a driving power **Sdrv** to drive the LED filament module electrically connected between first and second driving output terminals **5231** and **5232**. In addition, driving circuit **5530** is further electrically connected to first rectifying output terminal **5211** for acquiring voltage of the power line (or bus line) to generate working voltage **Vcc**.

[0304] Controller **5531** may be an integrated circuit or a chip including drain pin **Pdrn**, source pin **Pcs**, power pin **Pvcc**, overvoltage protection pin **Povp** and ground pin **Pgnd**. Drain pin **Pdrn** is electrically connected to output circuit **5532**. Source pin **Pcs** is electrically connected to second filtering output terminal **5222**, second driving output terminal **5532** and ground terminal **GND** through capacitor **Cs**. Power pin **Pvcc** is electrically connected to biasing circuit **5533**. Overvoltage protection pin **Povp** is electrically connected to sampling circuit **5534**. Ground pin **Pgnd** is

electrically connected to both biasing circuit **5533** and sampling circuit **5534**.

[0305] In this embodiment, the switching circuit/power switch (PSW) may be integrated in controller **5531**, and the first end and the second end of the switching circuit are electrically connected to drain pin Pdrn and source pin Pcs, respectively. In other words, controller **5531** can determine switch-on or switch-off of a current path related to drain pin Pdrn and source pin Pcs by controlling the switching state of the switching circuit within controller **5531**. In other embodiments, the switching circuit may also be a discrete element which is not integrated into controller **5531**. Under such a situation using a discrete element as a switching circuit, definition of pinout of controller **5531** will be correspondingly adjusted. For example, drain pin Pdrn can be adjusted to connect to a control end of the switching circuit and to serve as a pin providing a lighting control signal.

[0306] Output circuit **5532** includes diode **D1**, inductor **L1**, capacitor Co and resistor Ro. Both inductor **L1** and capacitor **C1** serve as an energy storage circuit (ESE) of the converting circuit. Diode **D1** serves as a freewheeling diode, whose anode is electrically connected to drain pin Pdrn of controller **5531** by connecting drain pin Pdrn to the first end/drain of the switching circuit in controller **5531**. The cathode of diode **D1** is electrically connected to first driving output terminal **5231**. The first end of inductor **L1** is electrically connected to first filtering output terminal **5221**. The second end of inductor **L1** is electrically connected to both drain pin Pdrn of controller **431** and the anode of diode **D1**. Resistor Ro and capacitor Co are electrically connected in parallel and electrically connected between first driving output terminal **5231** and second driving output terminal **5232**. In this embodiment, first filtering output terminal **5221** is electrically connected to first driving output terminal **5231** via both diode **D1** and inductor **L1**.

[0307] Controller **5531** controls switch-on and switch-off between drain pin Pdrn and source pin Pcs. When circuit between drain pin Pdrn and source pin Pcs is switched on, current will flow in first filtering output terminal **5521** to controller **5531** via inductor **L1** and drain pin Pdrn, and finally flow to ground terminal GND via source pin Pcs, capacitor Cs and second filtering output terminal **5222**. At this time, current flowing through inductor **L1** increases with time and inductor **L1** is in a status of energy storing. Meanwhile, capacitor Co is in a status of energy releasing to drive the LED filament module to emit light. When drain pin Pdrn and source pin Pcs are switched off, inductor **L1** is in a status of energy releasing, and the current in inductor **L1** decreases with time. The current in inductor **L1** flows to capacitor Co and the LED filament via diode **D1**. At this time, capacitor Co is in a status of energy storing.

[0308] It is noted that capacitor Co may be omitted. When capacitor Co is omitted and drain pin Pdrn and source pin Pcs are switched on, the current in inductor **L1** does not flow through first driving output terminal **5231** and second driving output terminal **5232** to make the LED filament module not light. When drain pin Pdrn and source pin Pcs are switched off, the current in inductor **L1** flows to the LED filament module via freewheeling diode **D1** to light up the LED filament. By controlling lighting time of the LED filament and magnitude of the current flowing therethrough, the average intensity of the LED filament can be stabilized at a predetermined value to obtain an effect of identically stable lighting.

[0309] Biasing circuit **5533** includes diode **D2**, capacitor **C1** and resistor **R1**. The anode and the cathode of diode **D1** are electrically connected to first rectifying output terminal **5211** and first driving output terminal **5231**, respectively. The first end and the second end of capacitor **C1** are electrically connected to power pin Pvcc and ground pin Pgnd, respectively. The first end of resistor **R1** is electrically connected to cathodes of diodes **D1** and **D2** and first driving output terminal **5231**. The second end of resistor **R1** is electrically connected to the first end of capacitor **C1** and power pin Pvcc. Resistor **R1** acquires a voltage of first driving output terminal **5231** to generate a working voltage Vcc. Working voltage Vcc is stabilized by capacitor **C1** and transmitted to power pin Pvcc of controller **5431** for being used by controller **5431**.

[0310] Sampling circuit **5534** includes resistor **R2-R5**. The first end and the second end of resistor

R2 are electrically connected to first driving output terminal 5231 and overvoltage protection pin Povp, respectively. Resistors R3 and R4 are electrically connected in parallel. The first ends of resistors R3 and R4 are electrically connected to ground pin Pgnd. The second ends of resistors R3 and R4 are electrically connected to second filtering output terminal 5222, second driving output terminal 5232 and ground terminal GND. The first end and the second end of resistor R5 are electrically connected to ground pin Pgnd and both the second end of resistor R2 and overvoltage protection terminal Povp.

[0311] Resistors R2 to R5 acquire or sample a voltage of the output voltage (i.e. the voltage of first driving output terminal 5231) by voltage division. The sampled voltage is transmitted to overvoltage protection pin Povp of controller 5531. As a result, controller 5531 can determine if the overvoltage protection function should be executed or not according to a voltage of overvoltage protection pin Povp.

[0312] Additionally, driving circuits 5430, 5530 is shown by a single-stage DC-to-DC power conversion circuit as an example, but not limited to this. For example, driving circuit 5330 can be a two-stage power conversion circuit which includes an active power factor correction circuit and a DC-to-DC converter.

[0313] Please refer to FIG. 47. FIG. 47 illustrates a cross-sectional view of an LED filament 400g according to an embodiment of the present disclosure. Please refer to FIG. 29. FIG. 29 illustrates a cross-sectional view of an LED filament 400g according to an embodiment of the present disclosure. As shown in FIG. 29, in the embodiment, the LED filament 400g is analogous to and can be referred to the LED filament 100 comprising the top layer 420a and the base layer 420b. A difference between the LED filament 400g and 100 is that the top layer 420a of the LED filament 400g is further divided into two layers, a phosphor glue layer 4201a and a transparent layer 4202a. The phosphor glue layer 4201a may be the same as the top layer 420a and comprises an adhesive 422, phosphors 424, and inorganic oxide nanoparticles 426. The transparent layer 4202a comprises an adhesive 422" only. The transparent layer 4202a may be of highest transmittance than other layers and can protect the phosphor glue layer 4201a. In some embodiments (not shown), the transparent layer 4202a encloses the phosphor glue layer 4201a, i.e., all sides of the phosphor glue layer 4201a except the one adjacent to the phosphor film layer 4201b are covered by the transparent layer 4202a.

[0314] In addition, the base layer 420b of the LED filament 400g is further divided into two layers, a phosphor glue layer 4201b and a transparent layer 4202b. The phosphor glue layer 4201b may be the same as the base layer 420b and comprises an adhesive 422', phosphors 424', and inorganic oxide nanoparticles 426'. The transparent layer 4202b comprises an adhesive 422" only. The transparent layer 4202b may be of highest transmittance than other layers and can protect the phosphor glue layer 4201b. In some embodiments (not shown), the transparent layer 4202b encloses the phosphor glue layer 4201b, i.e., all sides of the phosphor glue layer 4201b except the one adjacent to the phosphor film layer 4201a are covered by the transparent layer 4202b.

[0315] The transparent layers 4202a, 4202b not only protect the phosphor glue layer 4201a and the phosphor film layer 4201b but also strengthen the whole structure of the LED filament. Preferably, the transparent layers 4202a, 4202b may be thermal shrink film with high transmittance.

[0316] In some embodiments, the transparent layers 4202a, 4202b may be analogous to the aforementioned external transparent layer enclosing the entire enclosure (e.g., the phosphor film layers 4201a, 4201b) of the LED filament 400g and defines segments by distinct refractive indexes on the axial direction of the LED filament 400g. That is to say, the transparent layers 4202a, 4202b may have different compositions with different refractive indexes on different portions on the axial direction of the LED filament 400g.

[0317] In another embodiment, the aforementioned external transparent layer (e.g., the transparent layers 4202a, 4202b of FIG. 29) may be divided into segments on the axial direction of the LED filament by their thickness. The thickness of the external transparent layers of the segments of the

LED filaments on the axial direction of the LED filament may be different from one another. The thickness of the external transparent layers of the segments of the LED filaments may be symmetric in the top view or in the side view. The symmetric thickness can be referred to the above discussion regarding the symmetric refractive indexes and the symmetric surface roughness.

[0318] As shown in FIG. 30 to FIG. 36, FIG. 37A to FIG. 37C, and FIG. 38A to FIG. 38E, an LED filament includes a light conversion layer **220/420**, LED chip units **202/204** (or LED sections **402/404**), and electrodes (or conductive electrodes) **210, 212/410, 412**. The light conversion layer **220/420** wraps the LED chip units **202/204** (or LED sections **402/404**) and parts of the electrodes (or conductive electrodes) **210, 212/410, 412**, and parts of the electrodes (or conductive electrodes) **210, 212/410, 412** are exposed outside the light conversion layer **220/420**, the adjacent LED chip units **202, 204** (or LED sections **402, 404**) are electrically connected to each other, and the LED chip units **202/204** (or LED sections **402/404**) and the electrodes (or conductive electrodes) **210, 212/410, 412** are electrically connected. The LED filament includes at least two LED chips **442**, the two adjacent LED chips **442** are electrically connected to each other, the LED chip units **202/204** (or LED sections **402/404**) include at least one LED chip **442** with an upper surface and a lower surface opposite to each other, the light conversion layer **420** includes a top layer **420a** and a carrying layer, and the top layer **420a** and the carrying layer may separately be a layered structure having at least one layer. The layered structure may be selected from: a phosphor glue with high plasticity (relative to a phosphor film), a phosphor film with low plasticity, a transparent layer, or any combination of the three. The phosphor glue/phosphor film includes the following components: organosilicon-modified polyimide and/or glue. The phosphor glue/phosphor film may also include phosphor and inorganic oxide nanoparticles (or heat dissipation particles). The transparent layer may be composed of light-transmitting resin (such as silica glue and polyimide) or a combination thereof. The glue may be, but is not limited to, silica glue. In one embodiment, materials of the top layer **420a** and the carrying layer are the same. In one embodiment, the carrying layer includes a base layer, and in the height direction of the LED filament, the height of the top layer is greater than the height of the base layer. The base layer includes an upper surface and a lower surface opposite to each other, and the top layer includes an upper surface and a lower surface opposite to each other, where the upper surface of the base layer is in contact with a part of the lower surface of the top layer; the upper surface of the LED chip is close to the upper surface of the top layer relative to the lower surface of the LED chip, and the distance from the lower surface of the LED chip to the lower surface of the base layer is less than the distance from the lower surface of the LED chip to the upper surface of the top layer, because the thermal conductivity of the top layer is greater than the thermal conductivity of the base layer, and the heat transfer from the LED chip to the outer surface of the base layer is shorter, so the heat is not easy to collect, and the heat dissipation effect of the LED filament is good. In one embodiment, if the LED filament is supplied with electrical power no more than 8 W, when the LED filament is lit, at least 4 lm luminous flux of light is emitted every millimeter of a LED filament length on average or a filament body length on average or a top layer length on average. In one embodiment, there are at least two LED chips every millimeter of a LED filament length on average or a filament body length on average or a top layer length on average. In an environment at 25° C., the temperature of the LED filament is not greater than the junction temperature when the LED filament is lit for 15,000 h.

[0319] FIG. 30 is a schematic structural diagram of an embodiment of an LED filament according to this application. An LED filament **400** includes: a light conversion layer **420**, LED sections **402/404**, and electrodes **410/412**. The LED sections **402/404** have at least one LED chip **442**. In the LED filament, the two adjacent LED chips are electrically connected to each other, and the LED chips and the electrodes **410/412** are electrically connected. For example, the electrical connection may be achieved by using a circuit film or a first conductive wire in FIG. 31 described below. The light conversion layer **420** includes a top layer **420a** and a carrying layer, the carrying layer

includes a base layer **420b** and a transparent layer **420c**, and the base layer **420b** is located between the top layer **420a** and the transparent layer **420c** (at least located on a certain section of the LED filament **400**). In one embodiment, the base layer **420b** includes an upper surface and a lower surface opposite to each other, the upper surface of the base layer **420b** is in contact with a part of the top layer **420a**, and the lower surface of the base layer **420b** is in contact with the transparent layer **420c**. In some embodiments, a part of the lower surface of the base layer **420b** is in contact with the transparent layer **420c**, and the transparent layer **420c** supports a part of the base layer **420b**, thereby enhancing the strength of the base layer **420b** and facilitating die bonding, and the part of the base layer **420b** that is not covered by the transparent layer **420c** can allow heat generated by some LED chips **442** to be directly dissipated through the base layer **420b**. In this embodiment, the total length of the base layer **420b** is the same as the total length of the top layer **420a**. In one embodiment, the total length of the transparent layer **420c** is 5-100% of the total length of the base layer **420b**. In one embodiment, the length of the transparent layer **420c** is less than that of the base layer **420b**, the total length of the transparent layer **420c** is 10-80% of the total length of the base layer **420b**. In one embodiment, the total length of the transparent layer **420c** is 10-50% of the total length of the base layer **420b**. When the LED filament is thinner (for example, the width of the LED filament is $\leq 120\ \mu\text{m}$), the heat dissipation area of the LED chips **442** is relatively reduced. By providing the transparent layer **420c** located below the base layer **420b**, on the one hand, the deformation of the base layer **420b** caused by heating can be reduced; and on the other hand, the transparent layer **420c** can assist in supporting the LED chips **442**, helping die bonding. In one embodiment, the transparent layer **420c** includes a first transparent layer **420c1** and a second transparent layer **420c2**. The first transparent layer **420c1** and the second transparent layer **420c2** both extend in the length direction of the LED filament **400**. The first transparent layer **420c1** extends from one end of the base layer **420b**, the second transparent layer **420c2** extends from the other end of the base layer **420b**, and the extending direction of the first transparent layer **420c1** is opposite to the extending direction of the second transparent layer **420c2**. In one embodiment, the light conversion layer **420** has a first end and a second end opposite to the first end. In one embodiment, the LED chips **442** are located between the first end and the second end of the light conversion layer **420**. If the LED chip **442** closest to the first end is denoted as LED chip **n1**, then LED chips from the first end to the second end are sequentially LED chip **n2**, LED chip **n3**, . . . , and LED chip **nm**, where **m** is an integer and $m \leq 800$. In one embodiment, the value of **m** is $50 \leq m \leq 300$. In the length direction of the LED filament **400**, the length of the first transparent layer **420c1**/the second transparent layer **420c2** is at least greater than the distance from the first end of the light conversion layer **420a** to the LED chip **n2**. There is a gap between the first transparent layer **420c1** and the second transparent layer **420c2**. In the length direction of the LED filament **400**, the distance between the first transparent layer **420c1** and the second transparent layer **420c2** is greater than the length of the first transparent layer **420c1** and/or the second transparent layer **420c2**. When the LED filament **400** is bent, the electrode **410/412** is prone to be separated from the light conversion layer **420**, or the part where the light conversion layer **420** is in contact with the electrode **410/412** is prone to cracks. The first transparent layer **420c1** and the second transparent layer **420c2** can perform structural reinforcement on the part where the light conversion layer **420** is in contact with the electrodes **410,412**, which prevents the part where the light conversion layer **420** is in contact with the electrodes **410,412** from cracks.

[0320] FIG. **31** is a schematic structural diagram of another embodiment of an LED filament according to this application. As shown in FIG. **32**, an LED filament **400** includes: a light conversion layer **420**, LED sections **402, 404**, electrodes **410, 412**, and conductive sections **430** configured to electrically connect two adjacent LED sections **402, 404**. The LED sections **402, 404** include at least two LED chips **442**, and two adjacent LED chips **442** are electrically connected to each other by a first conductive wire **440**. In this embodiment, the conductive section **430** includes a conductor **430a** connecting the LED sections **402, 404**. The shortest distance between two LED

chips **442** respectively located in two adjacent LED sections **402**, **404** is greater than the distance between two adjacent LED chips **442** in the LED section **402/404**, and the length of the first conductive wire **440** is less than the length of the conductor **430a**. Therefore, it is ensured that, when bending occurs between the two LED sections **402**, **404**, the conductive section **430** is not easily broken due to the stress generated. The light conversion layer **420** is coated on at least two sides of the LED chips **442**/the electrodes **410**, **412**. Parts of the electrodes **410**, **412** are exposed outside the light conversion layer **420**. The light conversion layer **420** has a top layer **420a** and a carrying layer as an upper layer and a lower layer of the LED filament **400** respectively. In this embodiment, the carrying layer includes a base layer **420b**, and the base layer **420b** includes an upper surface and a lower surface opposite to the upper surface. The upper surface of the base layer **420b** is close to the top layer **420a** relative to the lower surface of the base layer **420b**. The LED sections **402/404** and parts of the electrodes **410/412** are disposed on the upper surface of the base layer **420b**, or at least one side of the LED sections **402/404** is in contact (direct contact or indirect contact) with the upper surface of the base layer **420b**.

[0321] As shown in FIG. 32, in this embodiment, the conductive section **430** is also located between the two adjacent LED sections **402**, **404**, and a plurality of the LED chips **442** in the LED sections **402**, **404** are electrically connected to each other by the first conductive wires **440**. However, the conductor **430a** in the conductive section **430** in FIG. 32 is not in the form of a conductive wire but in a sheet or film form. In some embodiments, the conductor **430a** may be copper foil, gold foil, or other materials that can perform electrical conduction. In this embodiment, the conductor **430a** is attached to the surface of the base layer **420b** and adjacent to the top layer **420a**, that is, located between the base layer **420b** and the top layer **420a**. Moreover, the conductive section **430** and the LED sections **402**, **404** are electrically connected by second conductive wires **450**, that is, the two LED chips **442** respectively located in two adjacent LED sections **402**, **404** and having the shortest distance from the conductive section **430** are electrically connected to the conductor **430a** in the conductive section **430** by the second conductive wires **450**. The length of the conductive section **430** is greater than the distance between two adjacent LED chips **442** in one LED section **402/404**, and the length of the first conductive wire **440** is less than the length of the conductor **430a**. This design ensures that the conductive section **430** has good bendability because the conductive section **430** has a relatively long length. Assuming that a maximum thickness of the LED chip **442** in the radial direction of the filament is H , the thickness of the electrodes **410**, **412** and the conductor **430a** in the radial direction of the LED filament is $0.5H$ to $1.4H$, preferably $0.5H$ to $0.7H$. Due to the height difference between the LED chip **442** and the electrode **410/412**, the LED chip **442** and the conductor **430a**, it can ensure the wire bonding process can be carried out while ensures the quality of the wire bonding process (that is, having good strength), thereby improving the stability of the product.

[0322] As shown in FIG. 33, an LED filament **400** includes: a light conversion layer **420**, LED sections **402**, **404**, electrodes **410**, **412**, and conductive sections **430** configured to electrically connect two adjacent LED sections **402**, **404**. The LED section **402**, **404** includes at least one LED chip **442**. The conductive section **430** and the LED section **402**, **404** are electrically connected by a second conductive wire **450**, that is, the two LED chips **442** respectively located in two adjacent LED sections **402**, **404** and having the shortest distance from the conductive section **430** are electrically connected to the conductor **430a** in the conductive section **430** by the second conductive wires **450**. The LED chips **442** are electrically connected to each other by the first conductive wire **440**. The conductive section **430** includes the conductor **430a** connecting the LED sections **402**, **404**. For example, the conductor **430a** is a conductive metal sheet or metal strip, such as a copper sheet or an iron sheet. The shortest distance between two LED chips **442** respectively located in two adjacent LED sections **402**, **404** is greater than the distance between two adjacent LED chips **442** in the LED section **402/404**, and the length of the first conductive wire **440** is less than the length of the conductor **430a**. Therefore, it is ensured that, when bending occurs between

the two LED sections **402,404**, the conductive section **430** has a large force area, and the conductive section **430** is not easily broken due to the stress generated. The light conversion layer **420** covers at least two sides of the LED chips **442**/the electrodes **410, 412**. Parts of the electrodes **410, 412** are exposed outside the light conversion layer **420**. The light conversion layer **420** includes a top layer **420a** and a carrying layer, the carrying layer includes a base layer **420b** and a transparent layer **420c**, and the base layer **420b** is located between the top layer **420a** and the transparent layer **420c**. The base layer **420b** and the top layer **420a** cover at least two sides of the LED chips **442**. The thermal conductivity of the transparent layer **420c** is greater than the thermal conductivity of the base layer **420b**. The thickness of the base layer **420b** in the radial direction of the LED filament **400** is less than or equal to the thickness of the conductor **430a** in the radial direction of the LED filament **400**. When the LED filament is thinner (for example, the width of the LED filament is $<120\ \mu\text{m}$), the heat dissipation area of the LED chips is relatively reduced. By providing the transparent layer **420c** located below the base layer **420b**, on the one hand, the deformation of the base layer **420b** caused by heating can be reduced, and on the other hand, the transparent layer **420c** can assist in supporting the LED chips **442**, helping die bonding. For example, the transparent layer **420c** may be a hard substrate such as an alumina ceramic plate or a sapphire substrate, or a soft substrate with high thermal conductivity (for example, the thermal conductivity $\geq 2.0\ \text{W}/(\text{m}\cdot\text{K})$). A translucent alumina ceramic plate or a transparent sapphire substrate facilitates the penetration of the light emitted by the LED chips **442** toward the transparent layer **420c**, thereby realizing omnidirectional light of the LED filament **400**. In this embodiment, the top layer **420a**, the base layer **420b**, and the transparent layer **420c** wrap the conductor **430a**. On one hand, the impact of the external environment on the conductor **430a** is reduced, and on the other hand, the carrying capacity of the conductor **430a** in electrical connection is improved, and the stability of the electrical connection when the conductor **430a** is bent is improved. In some embodiments, the thickness of the base layer **420b** in the height direction of the LED filament **400** is less than or equal to the thickness of the conductor **430a** in the height direction of the LED filament **400**. The heat conduction path of the heat generated by the LED chips **442** to the transparent layer **420c** is short, improving the heat dissipation effect of the LED filament **400**. In other embodiments, the thickness of the transparent layer **420c** in the height direction of the LED filament **400** is greater than the thickness of the base layer **420b** in the height direction of the LED filament **400**. The heat conduction path of the heat generated by the LED chips **442** to the transparent layer **420c** is short, such that the heat dissipation effect of the LED filament **400** is improved. In some embodiments, the absolute value of the height difference between the LED chip **442** and the conductor **430a** in the height direction of the LED filament **400** is greater than the height of the LED chip **442** in the height direction of the LED filament **400**. When the LED filament **400** is bent, the second conductive wire **450** is less deformed after being stretched under force, and the second conductive wire **450** is not prone to be broken. In some embodiments, the base layer **420b** is in contact with at least one side of the LED chips **442** and one side of the conductive section **430**. In this embodiment, the LED chips **442** and the conductors **430a** are located on different sides of the base layer **420b**.

[0323] Referring to FIG. 34 to FIG. 35B, in some embodiments, the conductor **430a** includes a covering portion **430b** and an exposed portion **430c**, and the length of the exposed portion **430c** in the axial direction of the LED filament **400** is less than the distance between adjacent LED chips **442** in any LED section **402/404**. When the LED filament **400** is bent, the exposed portion **430c** is slightly deformed under force with a small bending region and a small deformation degree, which is beneficial to keeping a bending shape of the LED filament **400**. As shown in FIG. 34, the exposed portion **430c** includes a first exposed portion **430c1** and a second exposed portion **430c2**, the portion of the top layer **420a** where the conductor **430a** is exposed is the first exposed portion **430c1**, and the portion of the transparent layer **420c** where the conductor **430a** is exposed is the second exposed portion **430c2**. The length of the first exposed portion **430c1** in the axial direction

(length direction) of the LED filament **400** is greater than or equal to the length of the second exposed portion **430c2** in the axial direction of the LED filament **400** to ensure the stability of the electrical connection and the uniform force when the conductor **430a** is bent. As shown in FIG. 35A, the exposed portion only includes the first exposed portion **430c1**. The length of the first exposed portion **430c1** in the axial direction of the LED filament is less than or equal to the distance between adjacent LED chips in any LED section **402/404**. When the LED filament **400** is bent, the stress generated during the bending is concentrated on the conductive section **430**, which reduces the risk of breakage of the conductive wires **440** connecting adjacent LED chips **442**. As shown in FIG. 35B, the exposed portion only includes the second exposed portion **430c2**, which can relieve stress concentration of the conductors **430a**. The length of the second exposed portion **430c2** in the axial direction of the LED filament **400** is less than or equal to the distance between adjacent LED chips **442** in any LED section **402/404**. Since a part of the conductors **430a** are located between adjacent transparent layers **420c**, the stability of the support of the transparent layers **420c** to the conductors **430a** can be ensured.

[0324] Referring to FIG. 36, an LED filament **400** has: a light conversion layer **420**, LED sections **402, 404**, electrodes **410, 412**, and conductive sections **430** configured to electrically connect two adjacent LED sections **402, 404**. The LED section **402, 404** includes at least one LED chip **442**. The conductive section **430** and the LED section **402, 404** are electrically connected by a second conductive wire **450**, that is, the two LED chips **442** respectively located in two adjacent LED sections **402, 404** and having the shortest distance from the conductive section **430** are electrically connected to the conductor **430a** in the conductive section **430** by the second conductive wires **450**. The conductive section **430** includes the conductor **430a** connecting the LED sections **402, 404**. For example, the conductor **430a** is a conductive metal sheet or metal strip, such as a copper sheet or an iron sheet. The shortest distance between two LED chips **442** respectively located in two adjacent LED sections **402, 404** is greater than the distance between two adjacent LED chips **442** in the LED section **402/404**, the two adjacent LED chips **442** are electrically connected to each other by the first conductive wire **440**, and the length of the first conductive wire **440** is less than the length of the conductor **430a**. When bending occurs between the two LED sections **402, 404**, the conductive section **430** has a large force area, and the conductive section **430** is not easily broken due to the stress generated. The light conversion layer **420** covers at least two sides of the LED chips **442**/the electrodes **410, 412**. Parts of the electrodes **410, 412** are exposed outside the light conversion layer **420**. The light conversion layer **420** includes a top layer (not shown) and a carrying layer. The carrying layer includes a base layer **420b** and a transparent layer **420c**. The LED chips **442** in the LED section **402/404** are arranged along the radial direction of the LED filament (or the width direction of the LED filament). Each LED chip **442** in the LED section **402/404** is connected to the conductor **430a** and/or the electrode **410/412**. In this embodiment, the widths of the base layer **420b** and the transparent layer **420c** in the radial direction of the LED filament are equal, the contact area between the base layer **420b** and the transparent layer **420c** is large, and there is no delamination between the base layer **420b** and the transparent layer **420c**. In other embodiments, the width of the base layer **420b** in the radial direction of the LED filament is less than the width of the transparent layer **420c** in the radial direction of the LED filament, the top layer (not shown) is in contact with the base layer **420b** and the transparent layer **420c**, and the thickness of the base layer **420b** is less than the thickness of the top layer. The heat emitted by the LED chips **442** is conducted to the top layer and the transparent layer **420c** at the same time through the base layer **420b**, thereby improving the heat dissipation efficiency of the LED filament. Besides, the top layer and the transparent layer **420c** completely wrap the base layer **420b**, which can protect the base layer **420b** from the external environment, and further can reduce the probability of the breakage of the second conductive wires **450** due to the protection from a plurality of sides of the top layer when the LED filament is bent, improving the yield of the product.

[0325] Still referring to FIG. 37A to FIG. 37C, FIG. 37A is a schematic three-dimensional partial cross-sectional view of an embodiment of an LED filament according to this application, FIG. 37B is a bottom view of FIG. 37A, and FIG. 37C is a schematic partial cross-sectional view of a position A-A in FIG. 37A. An LED filament **300** includes a plurality of LED chip units **202**, **204**, at least two conductive electrodes **210**, **212**, and a light conversion layer **220**. The LED chip units **202**, **204** are electrically connected to each other. The conductive electrodes **210**, **212** are configured corresponding to the LED chip units **202**, **204** and are electrically connected to the LED chip units **202**, **204** by first conductive portions **240**. The light conversion layer **220** wraps the LED chip units **202**, **204** and the conductive electrodes **210**, **212**, and exposes at least parts of the two conductive electrodes **210**, **212**. The light conversion layer **220** includes silica glue, phosphor, and heat dissipation particles. In some embodiments, the LED chip unit **202/204** includes at least one LED chip. The concentration of phosphor corresponding to each surface of the LED chip is the same, so that the light conversion rate of each surface is the same, and the light uniformity of the LED filament is good.

[0326] The LED chip unit **202/204** includes at least one LED chip, and the LED chip unit **202/204** has a first electrical connecting portion **206a** and a second electrical connecting portion **206b**. In the length direction of the LED filament, the distance between first connecting portions **206a** of two adjacent LED chip units is greater than the distance between the two adjacent LED chip units. In some embodiments, in the length direction of the LED filament, the distance between the first connecting portion **206a** and the second connecting portion **206b** of two adjacent LED chip units **202**, **204** is greater than the distance between the two adjacent LED chip units **202**, **204**, and at least a part of the first electrical connecting portion **206a** and the second electrical connecting portion **206b** is in contact with the light conversion layer **220**. The first electrical connecting portion **206a** and the second electrical connecting portion **206b** are located on the same side of the LED chip unit **202/204**.

[0327] In one embodiment, the second electrical connecting portion **206b** of the LED chip unit **202** is electrically connected to the first electrical connecting portion **206a** of the LED chip unit **204**. For example, the second electrical connecting portion **206b** of the LED chip unit **202** may be electrically connected to the first electrical connecting portion **206a** of the LED chip unit **204** by the second conductive portion **260**. The second conductive portion **260** has an end point a and an end point b, a line connecting the end point a and the end point b forms a straight line ab, and the straight line ab intersects the length direction p of the LED filament. In some embodiments, the light conversion layer **220** includes a top layer and a carrying layer (not shown). The top layer wraps the LED chip units **202**, **204** and the conductive electrodes **210**, **212**, and exposes at least parts of the two conductive electrodes **210**, **212**. The carrying layer includes a base layer. The base layer includes an upper surface and a lower surface opposite to the upper surface. The upper surface of the base layer is close to the top layer relative to the lower surface of the base layer. At least one of the first conductive portion **240** and the second conductive portion **260** is in contact (direct contact or indirect contact) with the upper surface of the base layer. When the LED filament is bent, the curvature radius of the base layer after being bent under force is relatively small, and the first conductive portion and the second conductive portion are not prone to be broken. In one embodiment, the first electrical connecting portion **206a** and the second electrical connecting portion **206b** are in contact (direct contact or indirect contact) with the upper surface of the base layer. The LED chip unit may be a flip chip or a mini LED chip. The mini LED refers to an LED with a package size of 0.1-0.2 mm, also referred to as the mini light emitting diode. When the LED chip unit is electrically connected, for example, the second electrical connecting portion **206b** of the LED chip unit **202** may be a positive connection point, and the first electrical connecting portion **206a** of the LED chip unit **204** may be a negative connection point, the second electrical connecting portion **206b** of the LED chip unit **202** is electrically connected to the first electrical connecting portion **206a** of the LED chip unit **204** by the second conductive portion **260**. In another

example, the second electrical connecting portion **206b** of the LED chip unit **202** may be a negative connection point, and the first electrical connecting portion **206a** of the LED chip unit **204** may be a positive connection point, the second electrical connecting portion **206b** of the LED chip unit **202** is electrically connected to the first electrical connecting portion **206a** of the LED chip unit **204** by the second conductive portion **260**. The first conductive portion **240** and the second conductive portion **260** may be in the form of wires or films, such as copper wires, gold wires, circuit films, or copper foil.

[0328] FIG. **38A** to FIG. **38E** are schematic diagrams of one embodiment of a method for manufacturing an LED filament according to this application. The method for manufacturing an LED filament includes the following steps:

[0329] **S20**. Lay LED chip units **202**, **204** and conductive electrodes **210**, **212** on a carrier **280** (as shown in FIG. **38A**).

[0330] **S22A**. Coat the portion where the LED chip units **202**, **204** and the conductive electrodes **210**, **212** are not in contact with the carrier **280** with a top layer **220a**, and then cure (or solidify) the LED chip units **202**, **204** and the conductive electrodes **210**, **212** that are coated with the top layer **220a**, so that the top layer **220a** is cured and covers the LED chip units **202**, **204** and the conductive electrodes **210**, **212** on the carrier, and at least parts of the two conductive electrodes **210**, **212** are exposed (as shown in FIG. **38B**). The curing procedure is, for example, but not limited to, heating or ultraviolet (UV) irradiation.

[0331] **S22B**. There are several ways to flip the LED chip units **202**, **204** and the conductive electrodes **210**, **212** that are coated with the top layer **220a**, one is that the LED chip units **202**, **204** and the conductive electrodes **210**, **212** are only disposed on the carrier **280** with no adhesion therebetween and therefore can be flipped directly, and the flipped semi-finished product may be laid on the carrier **280**.

[0332] The other is that, if there is a glue-like substance, such as a photoresist used in a semiconductor process or easy-to-remove die-bonding glue, for adhesion between the carrier **280** and the LED chip units **202**, **204** and the conductive electrodes **210**, **212**, after being properly baked, the glue-like substance has the effect of temporarily fixing the LED chip units **202**, **204** and the conductive electrodes **210**, **212** on the carrier **280**. Therefore, before or after the LED chip units **202**, **204** and the conductive electrodes **210**, **212** that are coated with the top layer **220a** are flipped, the photoresist coated on the carrier **280** may be cleaned with acetone, or the die-bonding glue on the carrier may be removed with a corresponding solvent, so that the LED chip units **202**, **204** and the conductive electrodes **210**, **212** that are coated with the top layer **220a** can be separated from the carrier **280**. In addition, washing may be further performed to remove residual photoresist or die-bonding glue.

[0333] **S24**. Electrically connect adjacent LED chip units **202**, **204**, and the LED chip units **202/204** with the conductive electrodes **210**, **212** (as shown in FIG. **38C**).

[0334] **S26**. After step **S24**, coat the portion where the LED chip units **202**, **204** and the conductive electrodes **210**, **212** are not coated with the top layer **220a** with a base layer **220b**, and perform curing after the coating is completed (as shown in FIG. **38D**).

[0335] After step **S26**, another step **S28** of cutting the LED chip units **202**, **204** and the conductive electrodes **210**, **212** that are wrapped with a light conversion layer **220** as cutting positions shown by dashed lines in FIG. **38E** may be included. In this way, a strip-shaped element after cutting is the LED filament **300**. The cutting method of step **S28** is not limited to FIG. **38E**, and every two adjacent columns of LED chip units **202**, **204** may be cut into a single LED filament.

[0336] In the method for manufacturing an LED filament in this embodiment, the top layer **220a** and the base layer **220b** may be made of phosphor and silica glue in the same proportion. If the top layer **220a** and the base layer **220b** further contain oxidized nanoparticles, the proportions of phosphor, silica glue, and oxidized nanoparticles in the top layer **220a** and the base layer **220b** are the same. In other words, the materials of the top layer **220a** and the base layer **220b** are the same,

and the top layer **220a** and the base layer **220b** are distinguished only for the convenience of description. Certainly, in other embodiments, the proportions of phosphor, silica glue, and oxidized nanoparticles in the top layer **220a** and the base layer **220b** may be different.

[0337] Referring to FIG. **39**, FIG. **39** is a schematic diagram of an LED light bulb **40i** according to an embodiment of this application. The LED light bulb **40i** in this embodiment has the same basic structure as the LED light bulb **40h** in FIG. **18A** to FIG. **18D**, including a lamp housing **12**, a lamp cap **16** connected to the lamp housing **12**, at least two conductive brackets disposed in the lamp housing **12**, a supporting arm (not shown), a stem **19**, and a single LED filament **100**. The difference is that the LED light bulb **40i** in this embodiment does not have a stand **19a**. The stem **19** includes an inflation pipe, and the gas in the lamp housing **12** is filled through the inflation pipe. As shown in FIG. **39**, in the Z-axis direction, the shortest distance from the LED filament **100** (or the bending point of the LED section **102/104**) to the lamp housing **12** is **H1**, the shortest distance from the conductive section **130** to the stem **19** of the LED filament **100** is **H2**, and **H1** is less than or equal to **H2**, the bending point of the LED section **102/104** is closer to the lamp housing, so the heat dissipation path of the LED filament is short, thereby improving the heat dissipation effect of the LED light bulb. In one embodiment, **H1** is greater than **H2**, the LED filament is approximately located in the middle area of the lamp housing, and the luminous effect of the light bulb is better.

[0338] Referring to FIG. **40A** and FIG. **40B**, FIG. **40A** is a schematic structural diagram of a lamp cap according to an embodiment of this application, and FIG. **40B** is a schematic diagram of a cross section A-A in FIG. **40A**. In this embodiment, a power component **20** is disposed in a lamp cap **16**, the power component **20** includes a substrate **201**, a heating element (an element that generates more heat during operation, such as an IC or a resistor) and a non-heat-resistant element (such as an electrolytic capacitor) are disposed on the substrate **201**, the lamp cap **16** has an inner surface and an outer surface opposite to the inner surface, the outer surface of the lamp cap **16** is away from the power component **20**, the heating element is closer to the inner surface of the lamp cap **16** than the non-heat-resistant element, an insulation sheet **202** is disposed on the heating element, and the insulation sheet **202** is in contact with the inner surface of the lamp cap **16**, for example, the insulation sheet **202** may be in contact with the inner surface of the lamp cap **16** by welding or using fasteners. In one embodiment, the heating element is integrally encapsulated into a component, a heat dissipation sheet is disposed on the component, and the heat dissipation sheet is in contact with the inner surface of the lamp cap **16**. For example, after an IC and a rectifier bridge are encapsulated into a component, the heat dissipation sheet is in contact with the inner surface of the lamp cap **16** by welding or using fasteners, and the heat dissipation sheet may be welded to the inner surface of the lamp cap **16** as a negative wire.

[0339] In another embodiment, the substrate **201** is in direct contact with the inner surface of the lamp cap **16**. Compared with the indirect contact between the substrate and the lamp cap through glue, the direct contact can improve the heat dissipation effect of the light bulb based on the reduction of heat transfer media.

[0340] In another embodiment, the heating element is covered with a heat conduction glue. For example, the substrate **201** has a first surface **2011** and a second surface **2012**, the second surface **2012** is away from the LED filament, the heating element and the non-heat-resistant element are respectively located on the first surface **2011** and the second surface **2012**, and the first surface **2011** is covered with the heat conduction glue, the heat generated by the heating element may be transferred to the lamp cap **16** through the heat conduction glue, thereby improving the heat dissipation effect of the LED light bulb.

[0341] Referring to FIG. **41A** to FIG. **41C**, FIG. **41A** is a schematic diagram of a lamp cap according to an embodiment of this application, FIG. **41B** is a schematic diagram of an embodiment of a cross section B-B in FIG. **41A**, and FIG. **41C** is a schematic diagram of an embodiment of a cross section B-B in FIG. **41A**. In another embodiment, as shown in FIG. **41A**, a heat conduction portion **203** is disposed on the inner surface of the lamp cap **16**, the heat

conduction portion **203** may be a net bag accommodating the heating element or a metal member in contact with the heating element, the thermal conductivity of the heat conduction portion **203** is greater than or equal to the thermal conductivity of the lamp cap **16**, and the heat generated by the heating element may be quickly transferred to the lamp cap **16** through the heat conduction portion **203**, thereby improving the heat dissipation effect of the LED light bulb.

[0342] In another embodiment, each surface of the power component **20** is covered with the heat conduction glue, and a part of the heat conduction glue is in contact with the inner surface of the lamp cap **16**. For example, a flexible substrate may be used to be integrally mounted in the lamp cap **16** by pouring the heat conduction glue into the lamp cap **16**. The power component is entirely covered with the heat conduction glue to increase the heat dissipation area, thereby greatly improving the heat dissipation effect of the LED light bulb.

[0343] In another embodiment, as shown in FIG. **41C**, the substrate **201** is parallel to the axial direction of the lamp cap **16** or the axial direction of the stem **19** in FIG. **18A** to FIG. **18D**, FIG. **39**, and FIG. **42A** to FIG. **42D**, since all the heating elements can be placed on the side of the substrate **201** close to the lamp cap **16**, the heat generated by the heating elements can be quickly transferred to the lamp cap **16**, thereby improving the heat dissipation efficiency of the power component; in addition, heating elements and non-heat-resistant elements can be separately arranged on the different surfaces of the substrate **201**, it can reduce the influence of the heat generated by the heating element on the heat-resistant element, and improve the overall reliability and life of the power component. In one embodiment a heating element (an element that generates more heat during operation, such as an IC or a resistor) and a non-heat-resistant element (such as an electrolytic capacitor) are disposed on the substrate **201**. The heating element is closer to the inner surface of the lamp cap **16** than other electronic elements (such as non-heat-resistant elements or other non-heat sensitive elements, for example, a capacitor). Therefore, compared with other electronic elements, the heating element has a shorter heat transfer distance from the lamp cap **16**, which is more conducive to the heat generated by the heating element during operation being conducted to the lamp cap **16** for heat dissipation, thereby improving the heat dissipation efficiency of the power component **20**.

[0344] As shown in FIG. **39** to FIG. **41A** through FIG. **41C**, the projections of the inflation pipe and the substrate **201** on the XY-plane overlap. In some embodiments, the projections of the inflation pipe and the substrate **201** on the XZ-plane and/or YZ-plane are separated (or do not overlap), or in the height direction of the lamp cap **16** (or Z-axis direction), there is a certain distance between the inflation pipe and the substrate **201**, so the inflation pipe and the substrate **201** are not in contact with each other, and thereby increasing the accommodation space of the power component and improving the utilization rate of the substrate **201**. In addition, when the substrate **201** is in contact with the inner surface of the lamp cap **16**, a cavity is formed between the first surface **2011** of the substrate **201** and the stem **19**, and the heat generated by the heating element located on the first surface of the substrate **201** may be transferred through the cavity, which reduces the thermal impact on the non-heat-resistant element located on the second surface, thereby increasing the service life of the power component.

[0345] Referring to FIG. **42A** to FIG. **42D**, FIG. **42A** to FIG. **42D** are schematic diagrams of an LED light bulb **40j** according to an embodiment of this application. The LED light bulb **40j** in this embodiment has the same basic structure as the LED light bulb **40h** in FIG. **18A** to FIG. **18D**, including a lamp housing **12**, a lamp cap **16** connected to the lamp housing **12**, at least two conductive brackets disposed in the lamp housing **12**, at least one supporting arm **15**, a stem **19**, and an LED filament **100**, and the supporting arms **15** are not shown in FIG. **42B** and FIG. **42C**. The stem **19** includes the stand **19a**. Each supporting arm **15** includes a first end and a second end that are opposite to each other. The first end of each supporting arm **15** is connected to the stand **19a**, and the second end of each supporting arm **15** is connected to the LED filament **100**. The LED light bulb shown in FIG. **42C** is different from the light bulb shown in FIG. **18A** to FIG. **18D** in

that the height of the stand **19a** is greater than the distance between a bottom portion of the stand **19a** and the conductive section **130** in the Z-axis direction, and the stand **19a** comprises the bottom portion of the stand **19a** and the top portion of the stand **19a** opposite to each other, where the bottom portion of the stand **19a** is closer to the inflation pipe. As shown in FIG. **42D**, in the XY-plane, the central angle corresponding to the arc where at least two bending points of the LED filament **100** are located ranges from 170° to 220° , so that there is a proper distance between bending points of the LED section **102**, **104** to ensure the heat dissipation effect of the LED filament **100**. At least one supporting arm **15** is located at the bending point of the LED filament **100**, for example, at the bending point of the LED section **102/104**. Each supporting arm **15** has an intersection with the LED filament **100**. On the XY-plane, at least two intersections are located on a circumference of a circle taking the stem **19** (or the stand **19a**) as a center, the LED filament has certain symmetry, and the luminous flux in all directions is roughly the same, so that the Light bulb can emit light evenly. In one embodiment, at least one intersection and the bending point of the conductive section **130** form a straight line La, and the intersection on the straight line La and the electrode **110/112** of the LED filament form a straight line Lb. The range of the angle α between the straight line La and the straight line Lb is $0^{\circ} < \alpha < 90^{\circ}$, preferably $0^{\circ} < \alpha < 60^{\circ}$, so that the LED sections have a proper spacing after bending, and have good light emission and heat dissipation effects. The LED section has a curvature radius at the bending point. For example, the LED section **102** has a curvature radius $r3$ at the bending point, the LED section **104** has a curvature radius $r4$ at the bending point, $r3$ is equal to $r4$, and the light is uniform on each plane. Certainly, it is also possible to set $r3$ to be greater than $r4$ or $r3$ to be less than $r4$ to meet lighting requirements and/or heat dissipation requirements in some specific directions. The conductive section **130** has a curvature radius $r5$ at the bending point, $r5$ is less than a maximum value of $r3$ and $r4$, that is, $r5 < \max(r3, r4)$, so that the LED filament **100** is not easy to break, and there is a certain distance between the LED sections **102**, **104** that are closer to the stem to prevent the heat generated by the two LED sections **102**, **104** from affecting each other.

[0346] In one embodiment, the LED section **102/104** includes a first section and a second section. The first section is extending upward (the direction of the top portion of the lamp housing **12**) from the electrode **110/112** to the bending point, and the second section is extending downward (the direction of the lamp cap **16**) from the bending point to the conductive section **130** connecting two LED sections **102**, **104**. The first section and the second section to the lamp housing **12** respectively have a first distance and a second distance that are opposite to each other, and the first distance is less than the second distance. In the first distance direction, the base layer of the LED filament **100** is close to the lamp housing **12**, and the top layer of the LED filament **100** is away from the lamp housing **12**. For example, in FIG. **42B**, the first section of the LED section **104** to the lamp housing **12** has a first distance $d1$ and a second distance $d2$, and the first distance $d1$ is less than the second distance $d2$. In the first distance $d1$ direction, the base layer of the LED filament **100** is close to the lamp housing **12**, and the top layer of the LED filament **100** is away from the lamp housing **12**.

When the LED filament **100** is bent, the conductive wire in the LED filament **100** has a small bending stress and is not easy to break, improving the production quality of the LED light bulb **40j**.

[0347] Referring to FIG. **18A** to FIG. **18D** and FIG. **42A** to FIG. **42D**, a plane A divides the lamp housing **12** into an upper portion and a lower portion, and the lamp housing **12** has the largest width at the plane A. For example, a plane figure formed by R2 (maximum horizontal spacing) in FIG. **18B** is located on the plane A, and when there is an intersection between the stem **19** and the plane A, the lamp housing **12** has a lamp housing top portion and a lamp housing bottom portion that are opposite to each other, the lamp housing bottom portion is close to the lamp cap **12**, and the length of the LED filament located between the lamp housing top portion and the plane A (or in the height direction of the LED light bulb, the distance from the highest point of the LED filament to the plane A) is less than the length of the LED filament located between the plane A and the lamp housing bottom portion (or in the height direction of the LED light bulb, the distance from the

lowest point of the LED filament to the plane A). Because when there is an intersection between the stem **19** and the plane A, the inner diameter of the lamp housing **12** above the top portion of the stem **19** is small and the volume for accommodating gas is small, if a large part of the LED filament is located on the top portion of the stem **19**, the overall heat dissipation effect of the LED filament is affected, thereby reducing the product quality. When there is a distance between the stem **19** and the plane A, and the distance from a stem top portion to the plane A is less than the height of the stand **19a**, the stem **19** includes a stem bottom portion and a stem top portion opposite to each other, the stem bottom portion is connected to the lamp cap **16**, the stem top portion extends to the direction of the lamp housing top portion, and the length of the LED filament located between the stem top portion and the lamp housing top portion (or the distance between the highest point of the LED filament and the stem top portion) is less than the length of the LED filament located between the stem top portion and the lamp housing bottom portion (or the distance between the stem top portion and the lowest point of the LED filament). Most of the LED filament can be indirectly supported by the stem **19**, so as to ensure the stability of the LED filament shape during the transportation of the LED light bulb. In some embodiments, when there is a distance between the stem **19** and the plane A, and the distance from the stem top portion to the plane A is greater than the height of the stand **19a**, the stem **19** includes a stem bottom portion and a stem top portion opposite to each other, the stem bottom portion is connected to the lamp cap **12**, the stem top portion extends to the direction of the lamp housing top portion, and the length of the LED filament located between the stem top portion and the lamp housing top portion is greater than the length of the LED filament located between the stem top portion and the lamp housing bottom portion. Since the volume of gas contained between the stem top portion and the lamp housing bottom portion is large, and most of the LED filament is located between the stem top portion and the lamp housing bottom portion, which facilitates the heat dissipation of the LED filament.

[0348] Please refer to FIG. **43** and FIG. **44**. FIG. **43** is a partially perspective schematic view of the LED filament of the disclosure in an embodiment and FIG. **44** is a cross-sectional schematic view along line A-A in FIG. **43**. As shown in FIG. **43** and FIG. **44**, the LED filament **10** includes at least one LED chip (at least two LED chips **101**, **102** are shown in the figure as an example), at least one electrode (at least two electrodes **103**, **104** are shown in the figure as an example), a light conversion layer **105** (in a specific embodiment, the light conversion layer can be called “plastic layer” or “silica gel layer”) and a conductive portion **106**. Adjacent LED chips **101**, **102** are electrically connected by the conductive portion **106** to implement an electric connection between the LED chips **101**, **102**. The conductive portion **106** is electrically connected between the LED chip **101** or **102** and the electrode **103** or **104** to implement an electric connection between the LED chip **101** or **102** and the electrode **103** or **104**. The light conversion layer **105** wraps the LED chips **101**, **102**, the conductive portion **106** and at least part of the electrodes **103**, **104**.

[0349] After the electrodes **103**, **104** have been connected to a power source (a voltage source or a current source), the LED filament **10** can emit light. As shown in FIG. **43** and FIG. **44**, a cross-section of the LED filament **10** is configured into, but not limited to, a rectangular shape, while a triangular, circular, oval, polygonal, or rhombic shape is also available, and the cross-section of the LED filament **10** may even be an irregular shape such as a square with chamfered or rounded corners.

[0350] In an embodiment, the light conversion layer **105** includes silica gel and fluorescent powders, and the light conversion layer **105** may further include heat dispersing particles. For example, the heat dispersing particles may be nanometer oxide particles such as, but not limited to, nanometer particles formed by aluminum oxide (Al.sub.2O.sub.3), silicon oxide (SiO.sub.2), zirconia (ZrO.sub.2), titanium oxide (TiO.sub.2), calcium oxide (CaO), strontium oxide (SrO) or barium oxide (BaO).

[0351] In an embodiment, as shown in FIG. **43** and FIG. **44**, the light conversion layer **105** includes a top layer **1051** and a carrying layer **1052** (in specific embodiments, the carrying layer can be

called base layer). The top layer **1051** wraps the LED chips **101**, **102**, the conductive portion **106** and the electrodes **103**, **104** with at least exposing part of the two electrodes **103**, **104** (or exposing at least part of the two electrodes **103**, **104**). The carrying layer **1052** includes an upper surface and a lower surface opposite to the upper surface. In comparison with the lower surface of the carrying layer, the upper surface **1052** of the carrying layer **1052** is adjacent to the top layer **1051**. In some examples, each of the top layer **1051** and the carrying layer **1052** may be a layered structure with at least one layer. Preferably, in some embodiments, the layered structure may be one of fluorescent powder glue with high plasticity (in comparison with fluorescent powder film), fluorescent powder film with low plasticity, and a transparent layer, or the layered structure may be a combination of at least any two thereof. The fluorescent powder glue or the fluorescent powder film includes the following components: silica gel-modified polyimide and/or glue. The fluorescent powder glue/film may also include fluorescent powder and inorganic oxide nanoparticles (or heat dispersing particles). The transparent layer can be made of light-transmitting resin (such as silica gel or polyimide) or a combination thereof. The glue can be, but is not limited to, silica gel. It should be understood that the above-mentioned structure and composition of the top layer **1051** and the carrying layer **1052** are only examples. In other examples, the top layer **1051** and the carrying layer **1052** may have the same or different structures and/or compositions to form a variety of LED filaments with different properties.

[0352] In an embodiment, in the height direction of the LED filament **10** (the Z-axis direction in FIG. **43** and FIG. **44**), the height of the top layer **1051** is greater than the height of the carrying layer **1052**. The top layer **1051** includes an upper surface and a lower surface opposite thereto. The upper surface of the carrying layer **1052** is in contact with at least part of the lower surface of the top layer **1051**. The LED chip **101**, **102** includes an upper surface and a lower surface opposite thereto. The upper surface of the LED chip **101**, **102** is closer to the upper surface of the top layer **1051** than the lower surface of the LED chip **101**, **102**. The distance between the lower surface of the LED chip **101**, **102** and the lower surface of the carrying layer **1052** is less than the distance between the lower surface of the LED chip **101**, **102** and the upper surface of the top layer **1051**, i.e., the path of the heat generated by the LED chips **101**, **102** being conducted to the outer surface of the carrying layer **1052** is shorter, so that heat is hard to be accumulated, thereby allowing the LED filament to obtain a better heat-dissipation effect.

[0353] To increase the combination strength of the top layer **1051** and the carrying layer **1052**, in some embodiments, the contact area, shapes or interfaces of the top layer **1051** and the carrying layer **1052** may be properly adjusted to make the junction surface between these two layers be not a single plane. In an example, at least part of the contact surfaces of the top layer **1051** and the carrying layer **1052** form surfaces which match with each other. Such matching may be engaging, for example, surfaces which engage with each other may be wavy or jagged. In another example, the upper surface of the carrying layer **1052** may also be configured with higher roughness to enhance the combination strength with the top layer **1051**. In still another example, the carrying layer **1052** may be provided with multiple via holes to make the top layer **1051** penetrate the carrying layer **1052** to increase the contact area between the top layer **1051** and the carrying layer **1052**. Furthermore, after the top layer **1051** penetrates the via holes, the top layer **1051** may further extend to the other side of the carrying layer **1052**. Therefore, the top and the bottom of the carrying layer **1052** are held by the top layer **1051**, so that the connection between the carrying layer **1052** and the top layer **1051** is similar to pivoting.

[0354] It is noted that the top layer **1051** as shown in FIG. **43** and FIG. **44** disposed on the upper surface of the carrying layer **1052** is an exemplary structure of the light conversion layer **105** only. The top layer **1051** and the carrying layer **1052** may also be disposed to be other connecting manners. For example, the carrying layer **1052** may be provided with a receiving groove in the length direction of the LED filament (the Y-axis direction in FIG. **43** and FIG. **44**), the LED chips **101**, **102** are disposed on the bottom of the receiving groove, and the top layer **1051** is filled in the

receiving groove. For another, the carrying layer **1052** is configured as six surfaces wrapping the LED chips **101**, **102** (i.e., the LED chips **101**, **102** are wrapped in the central portion of the carrying layer **1052**), and the top layer **1051** wraps the carrying layer **1052**. The disclosure does not limit the structure of the light conversion layer **105**.

[0355] The LED chips **101**, **102** are wrapped in the light conversion layer **105**. The LED filament may include one, two, or more LED chips (i.e., three or more than three). The shape of the LED chip may be of, but not limited to, a strip shape. A strip-shaped chip may have less electrodes to reduce the opportunity of shading the light emitted from an LED. In addition, surfaces of the LED chips **101**, **102** may be coated with a transparent conductive indium tin oxide (ITO). The ITO layer is helpful to even distribution of current and improvement of luminous efficiency of the LED chips **101**, **102**. In detail, the length-width ratio of the LED chip may be configured into 2:1 to 10:1, for example, but not limited to, 14×28 or 10×20. In addition, the LED chips **101**, **102** may adopt LED chips with large power operated with a low current, so that the LED chips **101**, **102** can still have sufficient intensity under the condition of keeping a low current density, and the LED chips **101**, **102** will not generate a large amount of heat to further improve the overall luminous efficiency.

[0356] The LED chip **101**, **102** itself may adopt a sapphire substrate or a light-permeable transparent substrate, such that the substrate of the LED chip **101**, **102** will not shade the light emitted from the LED chip **101**, **102**. In other words, the LED chip **101**, **102** itself can emit light from its periphery.

[0357] The LED chips are electrically connected with each other. As shown in FIG. **43** and FIG. **44**, adjacent LED chips **101**, **102** are electrically connected with each other through the conductive portion **106**. Take FIG. **43** and FIG. **44** as an example, each LED chip **101**, **102** may be electrically connected in series, but the electric connection is not limited thereto; the electrical connection may also be done in parallel first and then in series. For example, but not limited to, two LED chips **101**, **102** are first connected in parallel, and then two parallel-connected chips **101**, **102** are then connected in series. An embodiment in which two LED chips are first connected in series and then two series-connected chips are then connected in parallel is also available.

[0358] The electrodes **103**, **104** are disposed to correspond to the LED chips **101**, **102** and are correspondingly electrically connected to the LED chips **101**, **102**. As shown in FIG. **43** and FIG. **44**, each LED chip **101**, **102** is arranged in a row and adjacent LED chips **101**, **102** adopt an electric connection in series. The two electrodes **103**, **104** are disposed at two ends of the LED filament to be separately connected with two ends of the LED chips **101**, **102**. Each electrode **103**, **104** is partially exposed from the light conversion layer **105**. The arrangement of the electrodes **103**, **104** and the LED chips **101**, **102** is not limited thereto.

[0359] Please refer to FIG. **45** to FIG. **49**, which are schematic views of arrangements of the LED chips and the electrodes in different embodiments.

[0360] In the embodiment shown in FIG. **45**, adjacent LED chips **101**, **102** still adopt an electric connection in series, but multiple LED chips **101**, **102** are divided into two rows to be disposed on the LED filament **10** (i.e., adjacent LED chips **101**, **102** are alternately arranged in the width direction of the filament **10** (the X-axis direction in FIG. **45**), in other words, the LED chips **101**, **102** located at different rows of the two rows of LED chips **101**, **102** are incompletely superposed when viewed from a lateral side of the filament, or the superposing area is less than 100%), and the two rows of LED chips **101**, **102** are respectively arranged along the length direction of the LED filament **10** (the Y-axis direction in FIG. **45**). Adjacent LED chips **101**, **102** are connected with each other through the conductive portion **106**. In FIG. **45**, the two electrodes **103**, **104** are disposed at two ends of the LED filament **10** to be connected with two ends of the LED chips **101**, **102** through the conductive portion **106**. Each electrode **103**, **104** is partially exposed from the light conversion layer **105**. In the embodiment shown in FIG. **45**, the LED chips **101**, **102** has a length size w_c along the length direction of the LED filament **10**. The ratio of the sum of lengths w_c of all LED chips **101**, **102** (i.e., $\sum w_c$) to the length of the LED filament **10** is greater than 0.5, 0.6, 0.65 or 0.7 to

guarantee the arrangement density of the LED chips **101**, **102** in the length direction of the LED filament **10** so as to increase the total luminous flux and reduce the graininess of light emission. Because the adjacent LED chips **101**, **102** are alternately arranged in the width direction of the LED filament **10**, a better bendability can be obtained under the condition of the LED chips **101**, **102** having the same intervals. Contrarily, in the case that the ratio of the sum of lengths w_c of all LED chips **101**, **102** (i.e., w_c) to the length of the LED filament **10** is greater than 0.5, 0.6, 0.65 or 0.7 and the LED chips **101**, **102** are arranged in a single row, the LED filament **10** may have poor bendability, so that the LED filament cannot be bent properly and the shape of the LED filament **10** will be limited.

[0361] In the embodiment shown in FIG. **46**, the multiple LED chips **101**, **102** are arranged into an inverted-U shape or an n-shape, and the adjacent LED chips **101**, **102** adopt an electric connection in series. The electrodes **103**, **104** are arranged at the open end of the inverted-U shape or the n-shape and respectively electrically connected to corresponding one of the LED chips **101**, **102**. From the perspective view, the two electrodes **103**, **104** are disposed at an end of the LED filament **10** (the end corresponds to the open end of the inverted-U shape or the n-shape) and are partially exposed from the light conversion layer **105**.

[0362] In some embodiments, as shown in FIG. **47** and FIG. **48**, the multiple LED chips **101**, **102** may also be arranged into at least two substantially parallel rows (two rows are shown in FIG. **47** and FIG. **48** as an example). Each row of LED chips **101**, **102** is respectively electrically connected in series. The two electrodes **103**, **104** are disposed at two ends of the at least two rows of LED chips **101**, **102** and respectively connected to each row of LED chips **101**, **102** to form a configuration in which two LED chips are first connected in series and then two series-connected chips are then connected in parallel. FIG. **47** and FIG. **48** adopt two electrodes as an example, but the disclosure is not limited thereto, three or four electrodes may be available, for example, one of the electrodes **103**, **104** in FIG. **47** or FIG. **48** is replaced with two independent sub-electrodes, the two sub-electrodes are respective positive terminals of an electric power and the remained electrode is a common ground terminal, or all of two electrode in FIG. **47** or FIG. **48** are replaced with two sub-electrodes to match with different applications.

[0363] In the embodiment shown in FIG. **48**, one of the rows of LED chips, which is the closest to an end of the LED filament, is referred to as LED chip a.sub.1, and the LED chips in this row from an end of the LED filament to the other end are referred to as a.sub.1, a.sub.2, a.sub.3, . . . , and a.sub.m (m is an integer). The other one of the rows of LED chips, which is the closest to an end of the LED filament, is referred to as LED chip b.sub.1, and the LED chips in this row from an end of the LED filament to the other end are referred to as b.sub.1, b.sub.2, b.sub.3, . . . , and b.sub.n (n is an integer). In the length direction of the LED filament **10** (the Y-axis direction in FIG. **48**), LED chip b.sub.n is between LED chip a.sub.n and LED a.sub.n+1 (for example, when viewing from the length direction, LED chip b.sub.1 is between LED chip a.sub.1 and LED chip a.sub.2, and LED chip b.sub.2 is between LED chip a.sub.2 and LED chip a.sub.3). Further, the projection of LED chip b.sub.n in the width direction of the LED filament **10** and the projection of LED chip a.sub.n in the width direction of the LED filament **10** (the X-axis direction in FIG. **48**) do not have an overlapping area. In other words, in some embodiments, one row of LED chips and the other row of LED chips are alternately arranged in the width direction (the X-axis direction in FIG. **48**). Of course, in some embodiments, the projection of LED chip b.sub.n in the width direction of the LED filament **10** and the projection of LED chip a.sub.n in the width direction of the LED filament **10** (the X-axis direction in FIG. **48**) have a certain overlapping area, but the overlapping area is less than 100%. It should be understood that FIG. **48** adopts two rows of LED chips, which have the same numbers, to serve as an example. In actual applications, the numbers of two rows of LED chips are not necessarily the same or different, i.e., the maximum of n may be greater than, less than, or equal to the maximum of m, as long as one row of LED chips, which has a less number and a corresponding number of LED chips in the other row are alternately arranged or at least

partially alternately arranged with each other. The remaining LED chips of the row having a greater number are still extending and arranged along the length direction of the LED filament. In one embodiment, as shown in FIG. 48, the plurality of LED chips further comprises a first row of LED chips and a second row of LED chips, the first row of LED chips and the second row of LED chips are connected in parallel, the LED chips of the first row of LED chips are connected in series, the LED chips of the second row of LED chips connected in series, and the first row of LED chips and the second row of LED chips are alternately arranged along a width direction of the LED filament **10**.

[0364] Under the arrangement of the same number of LED chips, the longer the LED filament is, the larger the interval between two adjacent LED chips is. After the LED filament is lit, light spots (or called graininess) seen by the naked eye will become more obvious to seriously affect viewing comfort of users. In addition, the LED filaments with the same length, the greater the number of LED chips is, the smaller the interval between two LED chips is, and heat generated by adjacent LED chips will be affected mutually. To guarantee that the LED filament has a great effect of light emission and heat dissipation performance, the embodiment shown in FIG. 48 adopts two rows of LED chips connected in parallel, and the LED chips in one row and the LED chips in the other row are alternately arranged in the width direction of the LED filament, so that the light emitted by one row of LED chips can complement light spots generated by the other row of LED chips to improve the light-emitting effect of the LED filament. In addition, in comparison with an LED filament with the same LED filament length and the same number of LED ships, an interval between two adjacent LED chips in each row of LED chips is larger, so heat generated by adjacent LED chips will be hard to be affected mutually and the junction temperature of the LED filament lowers.

[0365] Moreover, as shown in FIG. 49, on the condition of the arrangement of the LED chips as shown in FIG. 48, the projections of LED chips in one row and LED chips in the other row have an overlapping area in the length direction of the LED filament **10** (the Y-axis direction in FIG. 49) so as to reduce the width of the LED filament to make both the width of the LED filament closer to a conventional tungsten filament lamp, thereby allowing the LED filament to be more pretty when being bent or wound. In detail, each of LED chip a.sub.m and LED b.sub.n has multiple sides. In the length direction of the LED filament **10**, a side of LED chip b.sub.n is between the same sides of LED chip a.sub.n and LED chip a.sub.n+1 (for example, in FIG. 49, a side of LED chip b.sub.1 is between a side an of LED chip a.sub.1 and a side a.sub.21 of LED chip a.sub.2). In some embodiments, the side an faces the side a.sub.21. In some embodiments, in the width direction of the LED filament **10** (for example, the X-axis direction in FIG. 49), widths of LED chip a.sub.m and LED chip b.sub.n are w_a and w_b , respectively. The width w of the LED filament **10** is not less than the sum of w_a and w_b , i.e., $w \geq w_a + w_b$.

[0366] In any embodiment shown in FIG. 43 to FIG. 49, adjacent LED chips **101**, **102** are electrically connected with each other through the conductive portion **106**, and the LED chips **101**, **102** and the electrodes **103**, **104** are electrically connected with each other through the conductive portion **106**, too. The conductive portion **106** may be a conductive metal wire, conductive film, or conductive metallic sheet. In the following embodiments, the conductive portion **106** is configured into a conductive metal wire as an example, which should not be deemed as a limitation to the disclosure. A conductive metal wire serving as the conductive portion **106** as an example, the diameter of the conductive metal wire may be configured to be between 0.5 mil and 1.5 mil and may be a single metal wire such as a gold wire, a silver wire, an aluminum wire or a copper wire or an alloy wire made of two or more metals with a certain proportion such as a gold-silver alloy wire.

[0367] The connection between the conductive portion **106** and the LED chips **101**, **102** and the connection between the conductive portion **106** and the electrodes **103**, **104** are fixed connections. In detail, the LED chips **101**, **102** is provided with a first electrical connecting portion and a second electrical connecting portion (for example, the electrical connecting portion may be a solder joint or pad). The first end of the conductive portion **106** is fixed on the second electrical connecting

portion of an LED chip **101**, and the second end is fixed on the first electrical connecting portion of another LED chip **102** adjacent to the LED chip **101**, so as to implement an electrical connection or signal connection between adjacent LED chips **101**, **102**. The electrode **103**, **104** is also provided with an electrical connecting portion (for example, the electrical connecting portion may be a solder joint or pad). The first end and the second end of the conductive portion **106** are respectively fixed to the electrode **103**, **104** and the electrical connecting portion of the LED chip **101**, **102** adjacent to the electrode **103**, **104**, so as to implement an electrical connection or signal connection between the electrodes **103**, **104** and the LED chips **101**, **102**.

[0368] In some embodiments, the conductive portion **106** is formed by wiring. The wiring is formed by wire bonding. In some embodiments, a wire and a corresponding electrical connecting portion are connected and fixed with each other using thermocompression bonding, ultrasonic bonding or thermosonic bonding to form each conductive portion **106** in the LED filament **10**. These bonding methods require applying pressure to the wire.

[0369] Specifically, the wire bonding may be implemented using a wire bonding machine (which may be referred to as a wire soldering machine). The wire bonding machine is provided with a ceramic capillary which has a through hole (also referred to as wire hole) allowing the wire to pass through. The wire is heated in front of the ceramic capillary using a firing member to form a ball-shaped article, and the ceramic capillary brings the ball-shaped article to move downward to correspond to the electrical connecting portion to be connected (for example, the second electrical connecting portion of an LED chip) to apply pressure on the wire to form the first joining portion (or also referred to as the first soldering point), so that the fixation of the first end of the conductive portion is implemented. Then, the ceramic capillary is moved toward another electrical connecting portion to be connected (for example, the first electrical connecting portion of another LED chip adjacent to the LED chip) along a constant trace, thereby forming the arc shape of the conductive portion. Further, the ceramic capillary again moves downward to correspond to the electrical connecting portion to apply pressure on the wire to form the second joining portion (or also referred to as the second soldering point), so that the fixation of the second end of the conductive portion is implemented. Thereafter, the ceramic capillary is moved laterally to cut the wire and a wire bonded conductive portion can be formed. In other words, during the wire bonding process, the wire is between the LED chip and the ceramic capillary or between the electrode and the ceramic capillary, and by using the ceramic capillary to apply pressure on the wire, the wire and the LED chip (or the electrode) can be bonded.

[0370] It is noted that the wire is referred to the material used for forming the conductive portion such as a conductive metal wire, and the conductive portion formed thereby is a conductive metal wire, too. In addition, the disclosure refers to the region formed by joining the wire and the electrical connecting portion as “joining portion”. To distinguish different joining portions, during the process of forming a conductive portion, the region formed by joining the start point of the wire and the electrical connecting portion is referred to as first joining portion (or first soldering joint), the region formed by joining the end point of the wire and the electrical connecting portion is referred to as second joining portion (or second soldering joint), an end of the conductive portion, which is connected to the first joining portion, is defined as a first end of the conductive portion, and an end of the conductive portion, which is connected to the second joining portion, is defined as a second end of the conductive portion.

[0371] Referring to FIG. **50**, a structural schematic view of the conductive portion, according to one embodiment of the present disclosure is shown. FIG. **50** shows the conductive portion **106** connected between adjacent LED chips **101** and **102** as an example. The conductive portion **106** may also be connected between the LED chip **101**, **102** and the electrode **103**, **104**. After the conductive portion **106** has been formed, the connection quality of the conductive portion **106** primarily depends upon three positions B, C, and D in FIG. **50**. That is, an unreliable connection in the conductive portion **106** mainly results from poor quality at the positions B, C, or D. Position B

is the junction of the first end of the conductive portion **106** and the first joining portion **1061**. Position D is the junction of the second end of the conductive portion **106** and the second joining portion **1062**, and position C is the line segment of the conductive portion **106** (i.e., the region between position B and position D).

[0372] As known to the inventor, the conductive portion **106** may be formed using bond stick on ball (BSOB) technique. Take FIG. 50 as an example, a solder ball is placed on the first electrical connecting portion of the LED chip **102** in advance, the first joining portion **1061** is formed when bonding, and then the second joining portion **1062** is formed. The second joining portion **1062** is formed by pressing the wire on the solder ball to be joined so as to form the second joining portion **1062** as shown in FIG. 51. The second joining portion **1062** has a meshy surface. The surface of the second joining portion **1062** forms an obviously highly staggered region, which can be specifically said to be a bulge structure and an indent structure, according to some embodiments. The first height difference T1 between the highest point of the bulge structure and the lowest point of the indent structure is between 5 μm and 15 μm , i.e., $5 \leq T_{\text{sub.1}} \leq 15 \mu\text{m}$, in some embodiments. The height difference between the bulge structure and the indent structure in the position D may also be called T.sub.1, and $5 \mu\text{m} \leq T_{\text{sub.1}} \leq 15 \mu\text{m}$, in some embodiments.

[0373] In other embodiments of the present disclosure, the conductive portion **106** formed by the BWB (Ball Wire Bonding), as shown in FIG. 50. It is also necessary to place a solder ball on the first electrical connecting portion of the LED chip **102** in advance. During the bonding process, the first joining portion **1061** is formed first, followed by the formation of the second joining portion **1062**. The second joining portion **1062** is formed by pressing the wire to be bonded on the solder ball that has been placed on the first electrical connecting portion. Another solder ball is then soldered and pressed thereon to form the second joining portion **1062**, creating a three-layer structure with the conductive portion **106** being sandwiched between two solders. (See FIG. 52A for a schematic view of the second joining portion, according to one embodiment of the present disclosure). FIG. 52B is a corresponding cross-sectional schematic view. As a result, the second end of the conductive portion is protected by the solder ball to effectively prevent the conductive portion from fracturing at position D. The process involves bonding a solder ball onto a corresponding position of the LED chip **102** and pressing the solder ball to form the required shape. Then, the conductive portion **106** is bonded on a side of the first solder ball that is away from the LED chip **102**. Finally, a second solder ball is bonded on a side of the conductive portion **106** that is away from the first solder ball in order to fix the conductive portion **106** and the LED chip **102**, and ultimately form the second joining portion **1062**. The LED chip **102** is bonded with the melted solder first. In the electrical connection, the current is conducted from the conductive portion **106** to the solder (i.e., the first solder ball) bonded with the LED chip **102** first, and then conducted to the LED chip **102**. In other words, in one embodiment, as shown in FIG. 52A and FIG. 52B, the second solder ball is formed as a second solder layer, and the end portion of the conductive portion **106** is between the first solder layer and the second solder layer.

[0374] In some embodiments, when the first solder ball, the conductive portion **106** and the second solder ball are bonded to the LED chip **102**, the projection area of the flattened first solder ball (or first solder layer) and the flattened second solder ball (or second solder layer) on the LED chip **102** after soldering are larger than the projection area of the bonding region between the first solder layer, the second solder layer, and the conductive portion **106** on the LED chip **102**, such that the flattened first solder ball and the flattened second solder ball wrap the conductive portion **106** and the bonding region between the first solder layer and the conductive portion **106** as well as the bonding region between the second solder layer and the conductive portion **106**. The first flattened solder ball and the second flattened solder ball are at least partially bonded, so the two flattened solder balls after soldering can completely wrap the bonding region of the conductive portion **106** to increase the strength of the bonding region of the conductive portion **106** to avoid fracture. In one embodiment, as shown in FIG. 52A and FIG. 52B, each of a projection area of the first solder

layer on the electrical connecting portion of the LED chip **102** and a projection area of the second solder layer on the electrical connecting portion of the LED chip **102** is larger than a projection area of a bonding region between the conductive portion **106** and the first solder layer, and between the conductive portion **106** and the second solder layer on the electrical connecting portion of the LED chip **102**.

[0375] In some embodiments, the projection area of the bonding region between the conductive portion **106** and the solder balls on the LED chip is smaller than the projection area of the first flattened solder ball on the LED chip, and the projection area of the first flattened solder ball on the LED chip is smaller than the projection area of the second flattened solder ball on the LED chip. The second flattened solder ball completely covers the bonding region between the first flattened solder ball and the conductive portion **106** on the LED chip **102**. The flattened second solder ball is at least partially directly bonded to the LED chip **102**. In one embodiment, as shown in FIG. 52A and FIG. 52B, a projection area of a bonding region between the conductive portion **106** and the electrical connecting portion of the LED chip **102** is smaller than the projection area of the first solder layer, and the projection area of the first solder layer is smaller than the projection area of the second solder layer.

[0376] In other some embodiments of the disclosure, the conductive portion **106** is formed by the BBOS (Bond Ball on Stitch) technique. In FIG. 50A and FIG. 50B, when bonding, the first joining portion **1061** is formed first. Then the ceramic capillary is moved to apply pressure and bond the wire to the first electrical connecting portion of the LED chip **102**. Subsequently, another solder ball is formed on the wire, resulting in the formation of the second joining portion **1062**, as shown in FIG. 53A and FIG. 53B (FIG. 53A is a structural schematic view of the second joining portion **1062**, according to an embodiment, and FIG. 53B is a cross-sectional schematic view corresponding to FIG. 53A). FIG. 52B is a corresponding cross-sectional schematic view. Thus, the second end of the conductive portion is still covered by a solder layer to greatly improve the problem of fracture of the conductive portion at position D and increase the efficiency of wire soldering. In one embodiment, the first electrical connecting portion of the LED chip **102** is configured as a positive electrode (also called anode), and the second electrical connecting portion of the LED chip **102** is configured as a negative electrode (also called cathode). That is, in one embodiment, the first joining portion **1061** is formed on the negative electrode of the LED chip **101**, and the second joining portion **1062** is formed on the positive electrode of the LED chip **102**. In one embodiment, the conductive portion **106** is bonded with the LED chip **102** first, and then a solder ball is bonded on a side of the conductive portion **106**, which is away from the LED chip **102** to finally form the second joining portion **1062**. The projection area of the solder on the LED chip **102** is larger than the projection area of the bonding region between the conductive portion **106** and the LED chip **102**, so that the bonding region between the conductive portion **106** and the LED chip **102** can be completely wrapped on the LED chip **102**. That is, the conductive portion **106** itself is bonded to the LED chip **102**, and the LED chip is further wrapped by a solder ball. Therefore, two fixations are provided to increase firmness and reduce the number of processing steps, according to one embodiment. In one embodiment, as shown in FIG. 53A and FIG. 53B, the solder ball is formed as a first solder layer, and the end portion of the conductive portion **106** is between the electrical connecting portion of the LED chip **101** and the first solder layer. In one embodiment, as shown in FIG. 53A and FIG. 53B, a projection area of the first solder layer on the electrical connecting portion of the LED chip **101** is larger than a projection area of a bonding region between the conductive portion **106** and the electrical connecting portion of the LED chip **101**.

[0377] Further, in any of the embodiments using the ceramic capillary to apply pressure to the wire to perform bonding, if a portion of the loading surface of the ceramic capillary is above an edge of the LED chip **102**, the position at which the wire is applied with a pressure will bear a stronger cutting force caused by the edge of the LED chip **102** and the wire is thus easy to be fractured. FIG.

54A and **FIG. 54B** are schematic views of the cutting phenomenon of the second end of the conductive portion above an edge of the LED chip **102**. In **FIG. 54A** and **FIG. 54B**, the cutting phenomenon is marked by a circle M. When the bonding position is excessively adjacent to an edge of the LED chip, the lower portion of the wire at which the wire is applied with the pressure will correspond to or adjacent to the edge of the LED chip or the edge of the electrode, wherein the height of the edge may have a sudden change. Accordingly, the junction of the second end of the conductive portion **106** will be affected by cutting forces and raise fracture.

[0378] Accordingly, in any of the embodiments adopting the manner which using the ceramic capillary to apply pressure on the wire to implement wiring, the second joining portion may be further arranged on the LED chip (or the electrode) with a first preset distance to the edge of the LED chip (or the electrode). In the embodiment, the edge of the LED chip (or the electrode) is referred to the edge of the LED chip (or the electrode) corresponding to the intersection side of the projection of the LED chip (or the electrode) and the conductive portion in the height direction of the LED filament. A first preset distance exists between the second joining portion and the LED chip (or the electrode). In other words, in wiring, the position of the wire, which is applied with a pressure, is provided with a flat loading surface which can eliminate the cutting effect to greatly reduce the risk of fracture of the wire. Take **FIG. 53A** and **FIG. 53B** as an example, a first preset distance wd exists between the second joining portion **1062** and the edge of the LED chip **102**. The junction of the second joining portion **1062** formed on the positive electrode of the LED chip **102** and the conductive portion **106** gradually inclines or rises from the near end toward the distal end (i.e., extending from the positive electrode of the LED chip **102** toward the conductive portion **106**) to form a joining slope or a joining ramp or form a joining portion which gradually becomes thicker and thicker from the near end toward the distal end, so as to eliminate the problem of sudden change of the height of the edge shown in **FIG. 54A** and **FIG. 54B**. The junction of the second joining portion **1062** of the positive electrode of the LED chip **102** and the conductive portion **106** forms a complete loading surface of the second joining portion **1062**. In comparison with **FIG. 54B**, the second joining portion **1062** moves forward by a certain distance toward the inside of the LED chip, so that the lower side of the wire in **FIG. 53A** is a complete loading surface and no cutting occurs at position D to further reduce the risk of fracture of the wire.

[0379] In **FIG. 53A** and **FIG. 53B**, it should be understood that the distance between the edge of the second joining portion **1062** and the edge of the LED chip (or the electrode) stands for the first preset distance. For example, the first preset distance of the second joining portion may be configured within a range between 20 μm and 60 μm , preferably, in some embodiments, between 30 μm and 50 μm , such as 30 μm , 35 μm , 40 μm , 45 μm or 50 μm . Of course, in other embodiments, the first preset distance may also be the distance between the center point of the second joining portion **1062** and the edge of the LED chip (or the electrode) in which a length corresponding to the radius of the second joining portion is added under the circumstance shown in **FIG. 53A** and **FIG. 53B**. For example, the first preset distance of the second joining portion may be configured within a range between 20 $\mu\text{m}+R1$ and 60 $\mu\text{m}+R1$, preferably, in some embodiments, a range between 30 $\mu\text{m}+R1$ and 50 $\mu\text{m}+R1$, such as 30 $\mu\text{m}+R1$, 35 $\mu\text{m}+R1$, 40 $\mu\text{m}+R1$, 45 $\mu\text{m}+R1$ or 50 $\mu\text{m}+R1$, where $R1$ stands for the radius of the second joining portion.

[0380] In some embodiments, the second joining portion is formed by using the ceramic capillary to continuously apply pressure on the wire after the ceramic capillary moves downward to the electrical connecting portion to be connected on the LED chip (or the electrode), therefore, in some embodiments, by arranging a second preset distance between the electrical connecting portion on the LED chip (or the electrode) and the edge of the LED chip (or the electrode), the second joining portion can also be arranged on the LED chip (or the electrode) with keeping the first preset distance between the edge of the LED chip (or the electrode) and the second joining portion. There is no necessary relationship between the first preset distance and the second preset distance. The first preset distance may be greater than, equal to, or less than the second preset distance. In some

embodiments, a distance between the edge of the electrical connecting portion and the edge of the LED chip (or the electrode) may be used to stand for the second preset distance. For example, the second preset distance may be configured within a range between 20 μm and 60 μm , preferably, in some embodiments, between 30 μm and 50 μm , such as 30 μm , 35 μm , 40 μm , 45 μm or 50 μm . In other embodiments, a distance between the center of the electrical connecting portion and the edge of the LED chip (or the electrode) may be used to stand for the second preset distance. For example, the second preset distance may be configured within a range between 20 $\mu\text{m}+\text{R2}$ and 60 $\mu\text{m}+\text{R2}$, preferably, in some embodiments, between 30 $\mu\text{m}+\text{R2}$ and 50 $\mu\text{m}+\text{R2}$, such as 30 $\mu\text{m}+\text{R2}$, 35 $\mu\text{m}+\text{R2}$, 40 $\mu\text{m}+\text{R2}$, 45 $\mu\text{m}+\text{R2}$ or 50 $\mu\text{m}+\text{R2}$, where R2 stands for the radius of the electrical connecting portion, for example, the radius R2 of the electrical connecting portion may be configured within a range between 25 μm and 35 μm such as 25 μm , 30 μm or 35 μm .

[0381] During the process of forming the first joining portion, malfunctions will occur during the electronic flame-off ball formation to result in serious damage at position B. As shown in FIG. 55, which is a structural schematic view of the first joining portion, in the region defined by a dotted line, the wire is seriously misaligned with the first joint portion. Fracture easily occurs in the misaligned region. Thus, in some embodiments of the disclosure, the conductive portion adopts a silver conductive metal wire. During the process of forming the first joining portion, the electronic flame-off ball formation is proper and no damage occurs at position B. As shown in FIG. 56, which is a structural schematic view of the first joining portion of the disclosure in an embodiment, the wire extends upward from the first joint portion without any misalignment.

[0382] Furthermore, as shown in FIG. 50, the conductive portion **106** extends between the first joining portion **1061** and the second joining portion **1062** and has a certain arc portion. Please refer to FIG. 57A and FIG. 57B, which are partially schematic views of the first end of the conductive portion of the related art at different viewing angles. The first joining portion **1061** is formed on the surface of the LED chip **101**. The conductive portion **106** extends upward along the first joining portion **1061**, and an included angle of approximately 90 degrees is between the conductive portion **106** and the surface at which the first joining portion **1061** is. That is, the conductive **106** extends from the first joining portion **1061** substantially along the height direction of the LED chip (the Z-axis direction in FIG. 57A and FIG. 57B). The conductive portion **106** further has a bent portion **1063** (or called bent point). The bent portion **1063** makes the conductive portion **106** extend from the height direction of the LED chip toward the length direction of the LED chip (the Y-axis direction in FIG. 57A and FIG. 57B).

[0383] In the arc portion of the conductive portion **106** shown in FIG. 50, FIG. 57A, and FIG. 57B, the start orientation of the bent portion **1063** is to correspond to the height direction of the LED chip (i.e., correspondingly toward the direction of the first joining portion **1061** or the Z-axis direction in FIG. 57A) and then is bent toward the length direction of the LED chip (the Y-axis direction in FIG. 57A). Such an arc structure makes the joint position (position B) of the conductive portion **106** and the first joining portion **1061** be a fulcrum of the bent portion **1063**, and the force exerted to the bent portion **1063** will be eventually delivered to position B. Therefore, in the process of producing or using the LED filament, fracture at position B will occur to cause malfunctions of the LED filament when the LED filament is vibrated, bent, or fell down which makes the bent portion **1063** bear a force.

[0384] Therefore, in some embodiments of the disclosure, structural design is applied to the arc portion of the conductive portion to address the issue of the fracture of position B. In one embodiment, the conductive portion includes at least two bent portions to make the conductive portion be extending along at least two different planes (or along at least three different direction). In some embodiments, the conductive portion has a first bent portion and a second bent portion to make the conductive portion have a part perpendicular to the LED chip **101** (or along the height direction of the LED chip **101**) and a part parallel to the LED chip **101**.

[0385] Please refer to FIG. 58A and FIG. 58B, which are partially schematic views of the first end

of the conductive portion of present invention in an embodiment. As shown, the conductive portion **106** extends upward from the first joining portion **1061** (it can be understood as an angle of approximately 90 degrees is between the conductive portion **106** and the surface at which the first joining portion **1061** is) and bent along the width direction of the LED chip **101** to form a first bent portion **1064**, and the conductive portion **106** further extends and is bent along the length direction of the LED chip **101** to form a second bent portion **1065**. In other words, in some embodiments, the conductive portion **106** has the first bent portion **1064** and the second bent portion **1065**. The conductive portion **106** extends upward from the first joining portion **1061** and extends toward the width direction of the LED chip **101** through the first bent portion **1064** and toward the length direction of the LED chip **101** through the second bent portion **1065**. The conductive portion extending upward from the first joining portion **1061** may also be understood as the conductive portion **106** extending from the first joining portion **1061** substantially along the height direction or perpendicular to the LED chip **101** (the Z-axis direction in FIG. 58A and FIG. 58B). The conductive portion **106** extending toward the width direction of the LED chip **101** may also be understood as substantially extending along the width direction of the LED chip **101**. In one embodiment, as shown in FIG. 58A and FIG. 58B, an end portion of the conductive portion **106** is connected to the electrical connecting portion, the conductive portion **106** has a first bent portion **1064** and a second bent portion **1065**, and the conductive portion **106** extends from the electrical connecting portion along a first direction of the LED chip **101**, extends toward a second direction of the LED chip **101** through the first bent portion **1064**, and extends toward a third direction of the LED chip **101** through the second bent portion **1065**, and wherein the first direction, the second direction, and the third direction are different directions. In some embodiments, the first direction is a height direction of the LED chip, the second direction is a width direction of the LED chip, and the third direction is a length direction of the LED chip.

[0386] In comparison with the structure shown in FIG. 57A and FIG. 57B, the conductive portion **106** shown in FIG. 58A and FIG. 58B, the region between the first bent portion **1064** and the second bent portion **1065** may serve as a buffering region for buffering or dispersing force exerted to the conductive portion **106** to avoid or reduce deformation of the conductive portion **106** to prevent fracture at position B. In detail, the first bent portion **1064** and the second bent portion **1065** shown in FIG. 58A and FIG. 58B may adjust the extension direction of the conductive portion **106** from a direction perpendicular to the chip into along the width direction of the chip and then further adjust the extension direction of the conductive portion **106** into along the length direction of the chip. Such configuration will affect neither the connection between the conductive portion **106** and adjacent two LED chips nor the connection between the LED chip and the electrode. However, such configuration makes the conductive portion **106** form an arc outswing, i.e., a correspondingly buffering region, and the force apply to the conductive portion **106** will be released in the buffering region (in other words, the force is shunted into different directions) without being transmitted to the first bent portion **1064** or with only a very small part being transmitted to the first bent portion **1064** and subsequent position B. Therefore, there is no main stress applied on the easy-to-fracture region of the conductive portion, so that the conductive portion **106** would not fracture easily.

[0387] Further, the height D1 of the first bent portion **1064** (i.e., the height between the first bent portion **1064** and the surface of the LED chip) is configured within a range between 80 um and 120 um. The length D2 of the buffering region (i.e., the length between the first bent portion **1064** and the second bent portion **1065**) is configured within a range between 100 um and 120 um.

[0388] FIG. 59A and FIG. 59B are structural schematic views of the LED filament according to an embodiment of present invention. The conductive portion **106** has a first portion **1066**, a second portion **1067** connected to the first portion **1066**, and a third portion **1068** connected to the second portion **1067**. When the first portion **1066** is projected on a corresponding LED chip (or the electrode) along the height or thickness direction of the LED filament (the Z axis direction shown

in FIG. 59A and FIG. 59B), the first portion **1066** is completely within the LED chip (or the electrode). In other words, the first portion **1066** does not exceed the edge of the corresponding LED chip (or the electrode) along the length direction of the LED filament (the Y axis direction shown in FIG. 66A and FIG. 59B). When the second portion **1067** is projected on corresponding two adjacent LED chips (or an LED chip and an electrode connected to the LED chip) connected through the conductive portion **106** along the length direction of the LED filament, the second portion **1067** is between the corresponding two adjacent LED chips (or the LED chip and the electrode). In other words, the second portion **1067** is between the corresponding two adjacent LED chips (or an LED chip and an electrode connected to the LED chip) along the length direction of the LED filament which indicates that the second portion **1067** is between the edges of the two adjacent LED chips (or the edges of the LED chip and the electrode). The third portion **1068** corresponds to the second end of the conductive portion **106**, and the third portion **1068** is used to be connected to the LED chip **102** (or the electrode). It can also be understood that, when the third portion **1068** is projected on the corresponding LED chip (or the electrode) along the height or thickness direction of the LED filament, the third portion **1068** is completely within the LED chip (or the electrode). In other words, the third portion **1068** does not exceed the edge of the corresponding LED chip (or the electrode) in the length direction of the LED filament.

[0389] In some embodiments, the first portion **1066** corresponds to the first end of the conductive portion **106**, one end of the first portion **1066** is connected to the LED chip **101** (or the electrode), and the other end of the first portion **1066** is connected to the second portion **1067**, and the other end of the first portion **1066** does not exceed the corresponding LED chip **101** (or the electrode) in the length direction of the LED filament. Further, the first portion **1066** includes the first bent portion **1064** and the second bent portion **1065** as shown in FIG. 58A and FIG. 58B.

[0390] In some embodiments, the ratio of the length of the first portion **1066** to the distance between the junction of the first portion **1066** and the LED chip and the edge of the LED chip in the length direction of the LED chip (the projection length of the first portion **1066** in the height or thickness direction of the LED filament) is greater than 1.15, 1.2, 1.3 or 1.4 to reduce the risk of fracture of the junction of the first portion **1066** and the LED chip when the first portion **1066** is pulled.

[0391] In some embodiments, the ratio of the length of the first portion **1066** to the distance between the junction of the first portion **1066** and the LED chip and the edge of the first portion **1066** in the length direction of the LED chip (the projection length of the first portion **1066** in the height or thickness direction of the LED filament) is less than 2. If the first portion **1066** is too long, the first portion **1066** will have a larger bending extent or occupy a space in the height or thickness direction of the LED filament. This will adversely affect the LED filament (for example, a larger bending extent may cause a greater inner stress in the first portion **1066** to occupy a space in the height or thickness of the LED filament; a thicker light conversion layer would be required to cover the LED filament).

[0392] In some embodiments, the ratio of the length of the first portion **1066** to the projection length of the first portion **1066** in the height or thickness direction of the LED filament is greater than the ratio of the length of the second portion **1067** to the projection length of the second portion **1067** in the height or thickness direction of the LED filament. It is expressed by a formula: $L1/T1 > L2/T2$, where **L1** is the length of the first portion **1066**, **T1** is the projection length of the first portion **1066** in the height or thickness direction of the LED filament, **L2** is the length of the second portion **1067**, and **T2** is the projection length of the second portion **1067** in the height or thickness direction of the LED filament. Usually, when the LED filament is bent, the junction of the first portion **1066** and the LED chip (or the electrode) is easier to be fractured because of being pulled. As a result, the risk of fracture of the junction of the first portion **1066** and the LED chip (or the electrode) can be further reduced by configuring $L1/T1 > L2/T2$.

[0393] The length of the third portion **1068** adopts the length of the first portion **1066** in any

embodiment, which can be referred to the descriptions about the first portion **1066**, and the description of the third portion **1068** is omitted.

[0394] When the LED filament is bent, the second portion **1067** of the conductive portion **106** is a main bending region (parts at which the LED chips are located are not easy to be bent). To reduce the risk of fracture of the second portion **1067** when the LED filament is bent, the length of the second portion **1067** is configured to be greater than the distance between two adjacent LED chips (or an LED chip and an electrode) corresponding thereto. That is, the length of the second portion **1067** is configured to be greater than the projection length of the second portion **1067** in the height or thickness direction of the LED filament, so as to provide a greater margin to the conductive portion **106** when the LED filament is bent to avoid fracture.

[0395] In some embodiments, the ratio of the length of the second portion **1067** to the distance between corresponding two adjacent LED chips (or an LED chip and an electrode) (or the projection length of the second portion **1067** in the height or thickness direction of the LED filament) is greater than 1.1, 1.2, 1.3, or 1.4. Therefore, when the LED filament is bent, the second portion **1067** has a sufficient length to be bent and deformed, thereby preventing the second portion **1067** from fracturing.

[0396] In some embodiments, the ratio of the length of the second portion **1067** to the distance between corresponding two adjacent LED chips (or an LED chip and an electrode) (or the projection length of the second portion **1067** in the height or thickness direction of the LED filament) is less than 2. If the length of the second portion **1067** is configured to be too long, it is disadvantageous to the covering performance of the light conversion layer, or even the conductive portion **106** may be exposed from the light conversion layer. In addition, the excessively long second portion **1067** may also cause material waste.

[0397] In some embodiments, the second portion **1067** has at least two bending points to make the conductive portion **106** appear substantially wavy (w-shaped or m-shaped). As shown in FIG. 59A, the second portion **1067** has a first bending point **1067a** and a second bending point **1067b**. The surface on which the junction between the LED chip and the conductive portion is located serves as a base plane. The first bending point **1067a** is below the first joining portion **1061** or the second joining portion **1062**, and the second bending point **1067b** is above the first joining portion **1061** or the second joining portion **1062**. Therefore, after the second portion **1067** is connected to the first portion **1066**, the second portion **1067** extends to the first bending point **1067a** on a descendent trend, then taking the first bending point **1067a** as a turning point, the second portion **1067** extends to the second bending point **1067b** on a rising trend, and finally taking the second bending point **1067b** as another turning point, the second portion **1067** extends on a descendent trend to be connected to the third portion **1068** to make the conductive portion **106** appear wavy (an inverted-w-shaped or m-shaped). Accordingly, such configuration further makes the conductive portion **106** have greater elongation and thus the conductive portion **106** is not easy to fracture.

[0398] In some embodiments, please refer to FIG. 60, which is a schematic view of the slant arrangement of the LED chips **101** of the invention in an embodiment, as shown, two adjacent LED chips **101** are arranged aslant. The slant arrangement indicates that the two adjacent LED chips **101** are arranged slant relative to the length direction of the LED filament with long sides of two adjacent LED chips **101** being kept parallel. That is, the two LED chips **101** are aslant arranged with the same slant angle so as to reduce the arc span of the conductive portion connected between the adjacent LED chips by 1/3, and the elongation of the conductive portion becomes larger to reduce the risk of fracture of the conductive portion between the LED chips. Further, the slant angle of the LED chip may be configured within a range between 10° and 20°, where the slant angle is an included angle between the long side of the LED chip and the length direction of the filament as angle α in FIG. 60.

[0399] The conductive portion used to be connected between the LED chip and the electrode is easy to fracture at position C. For example, in an embodiment of being provided with multiple

rows of LED chips and two rows of LED chips which are close to the electrode having different distances, as shown in FIG. 48 and FIG. 49, two rows of LED chips are alternately arranged, and the distance between the LED chip b.sub.n and the electrode 104 is obviously less than the distance between the LED chip a.sub.m and the electrode 104. The arc span of the conductive portion 106 directly connected between the LED chip a.sub.m and the electrode 104 is obviously greater than the arc span of the conductive portion 106 directly connected between the LED chip b.sub.n and the electrode 104. Therefore, in comparison with the conductive portion 106 between the LED chip b.sub.n and the electrode 104, the elongation of the arc of the conductive portion 106 between the LED chip a.sub.m and the electrode 104 is small, and thus the conduction portion is easy to fracture.

[0400] Therefore, in some embodiments, at least the LED chips which are near the electrode and to be connected to the electrode are configured to have a common solder joint so as to decrease the length of the conductive portion and thus reduce the risk of fracture of the conductive portion between the LED chip and the electrode. Please refer to FIG. 61, which is a structural schematic view of the connection between the LED chip and the electrode of the invention in an embodiment. The LED chip a.sub.m is a chip in the first row of chips, which is the closest to the electrode 104, and the LED chip b.sub.n is a chip in the second row of chips, which is the closest to the electrode 104. Two ends of a conductive portion 106 are respectively connected to the first electrical connecting portion of the LED chip a.sub.m and the first electrical connecting portion of the LED chip b.sub.n to make the LED chip a.sub.m and the LED chip b.sub.n have a common-electrode (which may be a common-cathode or a common-anode, the common-electrode is common-cathode when the first electrical connecting portion is configured as an cathode, and the common-electrode is common-anode when the first electrical connecting portion is configured as an anode). That is, the first electrical connecting portion of the LED chip b.sub.n serves as a common-electrode connecting point and another conductive portion 106 is used to be connected between the common-electrode connecting point and the electrode 104. Under this configuration, the arc span required by the conductive portion 106 connected with the LED chip a.sub.m greatly decreases (by almost one second) to reduce the risk of fracture of the conductive portion between the chip and the electrode.

[0401] In addition, other solutions may be adopted to improve the problem of fracture of the conductive portion between the LED chip and the electrode. In some embodiments, the LED chip and the electrode corresponding thereto are connected with each other through at least two conductive portions. Each conductive portion has at least two bending points to form at least two bending regions. The bending regions of the at least two conductive portions are alternately arranged in the height or thickness direction of the LED filament. In some embodiments, the at least two conductive portions may be configured as the structure of the conductive portion mentioned in any above embodiment. Please refer to FIG. 57A and FIG. 57B and related descriptions thereto, as long as the connecting position of the at least two conductive portions is correspondingly adjusted.

[0402] Please refer to FIG. 62A to FIG. 62C, which are structural schematic views of the connection between the LED chip and the corresponding electrode through two conductive portions of the invention in an embodiment at different viewing angles. For the sake of description, two conductive portions are respectively referred to a first conductive portion 106' and a second conductive portion 106''. The first end of the first conductive portion 106' is connected to the LED chip 101, and the second end is connected to the electrode 104. The first end of the second conductive portion 106'' is connected to the electrode 104, and the second end is connected to the LED chip 101. The first conductive portion 106' has a first bending point 1067a' and a second bending point 1067b'. The first bending point 1067a' correspondingly forms a first bending region with an upward opening (it may also be understood that the first conductive portion 106' extends toward the first bending point 1067a' on a descendent trend first, and then taking the first bending point 1067a' as a turning point, the first conductive portion 106' extends on a rising trend to form

the first bending region). The second bending point **1067b'** correspondingly forms a second bending region with a downward opening (it may also be understood that the first conductive portion **106'** extends on a rising trend first, and then taking the second bending point **1067b'** as a turning point, the first conductive portion **106'** extends on a descendent trend to form the second bending area). The second conductive portion **106''** has a first bending point **1067a''** and a second bending point **1067b''**. The first bending point **1067a''** correspondingly forms a first bending region with an upward opening (it may also be understood that the second conductive portion **106''** extends toward the first bending point **1067a''** on a descendent trend first, and then taking the first bending point **1067a''** as a turning point, the second conductive portion **106''** extends on a rising trend to form the first bending region). The second bending point **1067b''** correspondingly forms a second bending region with a downward opening (it may also be understood that the second conductive portion **106''** extends on a rising trend first, and then taking the second bending point **1067b''** as a turning point, the second conductive portion **106''** extends on a descendent trend to form the second bending area). In other words, in one embodiment, as shown in FIG. 62A, FIG. 62B, and FIG. 62C, the first conductive portion **106'** firstly extends downwards and then upwards by taking the first bending point **1067a'** as a first turning point, and the first conductive portion **106'** then extends upwards and then downwards by taking the second bending point **1067b'** as a second turning point; the second conductive portion **106''** firstly extends upwards and then downwards by taking the first bending point **1067a''** as a first turning point, and the second conductive portion **106''** then extend downwards and then upwards by taking the second bending point **1067b''** as a second turning point. In this embodiment, the start point of the first conductive portion **106'** is at LED chip **101** and the end point of the first conductive portion **106'** is at the electrode **104**. On the contrary, the start point of the second conductive portion **106''** is at the electrode **104** and the end point of the first conductive portion **106''** is at LED chip **101**. Because the first conductive portion **106'** and the second conductive portion **106''** are connected between the LED chip **101** and the electrode **104** on contrary descendent and rising trends, after connection, the first bending region formed by the first bending point **1067a'** of the first conductive portion **106'** and the second bending region formed by the second bending point **1067b''** of the second conductive portion **106''** are correspondingly alternately arranged along the height direction of the LED chips. Likewise, the second bending region formed by the second bending point **1067b'** of the first conductive portion **106'** and the first bending region formed by the first bending point **1067a''** of the second conductive portion **106''** are correspondingly alternately arranged along the height direction of the LED chips. It should be understood that this the alternately arrangement along the height direction of the LED chips does not necessarily require that two bending regions must absolutely align with each other in the height or thickness direction of the LED filament as long as the overall bending trends of the two bending region are alternately arranged.

[0403] The forming positions and manners of the bending points of the first conductive portion **106'** and the second conductive portion **106''** may be referred to the descriptions of FIG. 59A and FIG. 59B, and related descriptions are omitted. The connection and arc structure of the first end of the first conductive portion **106'** and the LED chip **101** may adopt the structure described in any embodiment shown in FIG. 57A to FIG. 58B. The connection and arc structure of the first end of the second conductive portion **106''** and the electrode **104** may adopt the structure described in any embodiment shown in FIG. 57A to FIG. 58B with no more repeat. Further, the first conductive portion **106'** and the second conductive portion **106''** may have more bending points. For example, as shown in FIG. 62B, the second conductive portion **106''** further has a third bending point **1067c''**, and the second conductive portion **106''** is continuously connected to the LED chip **101** through the third bending point **1067c''**.

[0404] In any embodiment disposed with at least two conductive portions connected between the LED chip and the electrode corresponding thereto, the bending areas of the at least two conductive portions are alternately arranged in the height or thickness direction of the LED filament so as to

form complementarity to implement force dispersion and jointly bearing to avoid fracture of the conductive portion between the electrode and the LED chip.

[0405] As shown in FIG. 62C, the distance between one of the at least two conductive portions, which is close to the edge of the LED filament (the first conductive portion **106'** in FIG. 52B) and the edge of the electrode is configured to be greater than or equal to 30 μm , preferably, in some embodiments, greater than or equal to 50 μm .

[0406] As shown in FIG. 62A, from the length direction of the LED filament, the height difference $h_{\text{sub.1}}$ (i.e., the first turning point distance along the height direction) between the first bending point **1067a'** of the first conductive portion **106'** and the joining portion of the corresponding chip (the joining portion of the LED chip **101** shown in FIG. 62A) is configured within $40 \mu\text{m} \pm 5\%$. The height difference $h_{\text{sub.2}}$ (i.e., the second turning point distance along the height direction) between the second bending point **1067b'** of the first conductive portion **106'** and the joining portion of the corresponding chip (the joining portion of the LED chip **101** shown in FIG. 62A) is configured within $75 \mu\text{m} \pm 5\%$. From the height or thickness of the LED filament, the first bending point **1067a'** of the first conductive portion **106'** is below the surface of the chip (the surface of the chip is a surface which is connected to the first conductive portion **106'**) ranging between 30 μm and 100 μm in height direction (the height of the first turning point in FIG. 62A). The second bending point **1067b'** of the first conductive portion **106'** is above the surface of the chip (the surface of the chip is a surface which is connected to the first conductive portion **106'**) ranging between 100 μm and 160 μm in height direction (the height of the second turning point in FIG. 62A).

[0407] As shown in FIG. 62B, from the length direction of the LED filament, the horizontal distance $S1$ (i.e., the first turning point distance along the length direction) between the first bending point **1067a''** of the second conductive portion **106''** and the joining portion of the corresponding electrode **104** is configured within $40 \mu\text{m} \pm 5\%$. The horizontal distance $S2$ (i.e., the second turning point distance along the length direction) between the second bending point **1067b''** of the second conductive portion **106''** and the joining portion of the corresponding electrode **104** is configured within $75 \mu\text{m} \pm 5\%$. The horizontal distance $S3$ (i.e., the third turning point distance along the length direction) between the third bending point **1067c''** of the second conductive portion **106''** and the joining portion of the corresponding electrode **104** is configured within $90 \mu\text{m} \pm 5\%$. From the height or thickness of the LED filament, the first bending point **1067a''** of the second conductive portion **106''** (the LED chip **101** in FIG. 62B) is below the surface of the chip (the surface of the chip connected to the second conductive portion **106''**) ranging between 30 μm and 100 μm in height direction (the height of the first turning point in FIG. 62B). The second bending point **1067b''** of the second conductive portion **106''** (the LED chip **101** in FIG. 62B) is above the surface of the chip (the surface of the chip connected to the second conductive portion **106''**) ranging between 80 μm and 120 μm (the height of the second turning point in FIG. 62B).

[0408] It should be understood that, for an LED filament, an electrode needs to be connected with multiple LED chips through the conductive portion and different LED chips need to be connected with different electrodes. The invention does not necessarily require that the connection between the LED chip and the corresponding electrode must adopt the same structure, any person having ordinary skill in the art may adopt combinations of the above manners. For example, as shown in FIG. 62A and FIG. 62B, near the electrode **104**, the connection with the LED **101** which is away from the electrode **104** adopts a two-wire manner, and the connection with the LED **101** which is adjacent to the electrode **104** still adopts a one-wire manner. Of course, the disposition shown in FIG. 62A and FIG. 62B, which uses at least two conductive portions, can also be used to connect two adjacent LED chips. The disclosure does not make any limitation for this.

[0409] The invention further provides a connecting method between two chips and a connecting method between a chip and an electrode. A structure corresponding to the LED filament provided by anyone of the embodiments of the disclosure can be formed by the methods. Please refer to the aforementioned descriptions of FIGS. 1-27C with no more repeat.

[0410] The invention further provides an LED filament lamp, which is disposed with the LED filament provided by anyone of the embodiments of the disclosure. Please refer to the aforementioned descriptions of FIG. 1 to FIG. 62C about the LED filament with no more repeat. In detail, the LED filament may be bent or deformed to be disposed in the LED filament lamp. For example, the LED filament lamp is a bulb lamp.

[0411] The invention further provides an LED bulb, which includes a lamp housing, a bulb base connected with the lamp housing. The lamp housing is disposed with at least one supporting arm, a stem and an LED filament. The stem includes a stand. Each supporting arm includes a first end and a second end opposite to each other. The first end of the supporting arm is connected to the stand. The second end of the supporting arm is connected to the LED filament. The LED filament may be configured into the LED filament provided by anyone of the embodiments of the disclosure. Please refer to FIG. 1 to FIG. 62C with no more repeat. The LED bulb may also be other structures, for example, the LED bulb includes a lamp housing, a bulb base connected with the lamp housing. The lamp housing is disposed with a stem and an LED filament.

[0412] The various embodiments of the present invention described above may be arbitrarily combined and transformed without being mutually exclusive, and are not limited to a specific embodiment. For example, some features as described in the embodiment shown in FIG. C although not described in the embodiment shown in FIG. A, those features may be included in the embodiment of FIG. A. That is, those skilled in the art can apply some features of the FIG. A to the embodiment shown in the FIG. C without additional creativity. Or alternatively, although the invention has illustrated various creation schemes by taking the LED light bulb as an example, it is obvious that these designs can be applied to other shapes or types of light bulb without additional creativity, such as LED candle bulbs, and the like.

[0413] The invention has been described above in terms of the embodiments, and it should be understood by those skilled in the art that the present invention is not intended to limit the scope of the invention. It should be noted that variations and permutations equivalent to those of the embodiments are intended to be within the scope of the present invention. Therefore, the scope of the invention is defined by the scope of the appended claims.

Claims

1. An LED filament, comprising: an LED section comprising a plurality of LED chips connected in series and a light conversion layer wrapping the plurality of LED chips; a first conductive electrode disposed at one of two ends of the LED section and electrically connected to the plurality of LED chips, wherein a portion of the first conductive electrode is wrapped by the light conversion layer; a second conductive electrode disposed at the other one of the two ends of the LED section and electrically connected to the plurality of LED chips, wherein a portion of the second conductive electrode is wrapped by the light conversion layer; a conductive portion electrically connected between two adjacent LED chips, the conductive portion comprising two end portions; and a first solder layer disposed on one end portion of the conductive portion, wherein an LED chip among the plurality of LED chips has an electrical connecting portion, the one end portion of the conductive portion is connected to the electrical connecting portion and the first solder layer is disposed on the end portion of the conductive portion, and the end portion of the conductive portion is sandwiched between the electrical connecting portion of the LED chip and the first solder layer.
2. The LED filament according to claim 1, wherein a projection area of the first solder layer on the electrical connecting portion of the LED chip is larger than a projection area of a bonding region between the conductive portion and the electrical connecting portion of the LED chip.
3. The LED filament according to claim 2, wherein the end portion of the conductive portion, the electrical connecting portion of the LED chip, and the first solder layer together form a joining

portion, the joining portion has a meshy surface, and a plurality of bulges and a plurality of indents are alternately arranged on the meshy surface.

4. The LED filament according to claim 3, wherein the plurality of LED chips further comprises a first row of LED chips and a second row of LED chips, the first row of LED chips and the second row of LED chips are connected in parallel, the LED chips of the first row of LED chips are connected in series, the LED chips of the second row of LED chips connected in series, and the first row of LED chips and the second row of LED chips are alternately arranged along a width direction of the LED filament.

5. The LED filament according to claim 2, further comprising a second solder layer, wherein the second solder layer is made of the solder material, and the end portion of the conductive portion is sandwiched between the first solder layer and the second solder layer.

6. The LED filament according to claim 5, wherein each of a projection area of the first solder layer on the electrical connecting portion of the LED chip and a projection area of the second solder layer on the electrical connecting portion of the LED chip is larger than a projection area of a bonding region between the conductive portion and the first solder layer, and between the conductive portion and the second solder layer on the electrical connecting portion of the LED chip.

7. The LED filament according to claim 6, wherein a projection area of a bonding region between the conductive portion and the second solder layer is smaller than the projection area of the first solder layer, and the projection area of the first solder layer is smaller than the projection area of the second solder layer.

8. The LED filament according to claim 2, wherein the conductive portion has a first bent portion and a second bent portion, and the conductive portion extends from the electrical connecting portion along a first direction of the LED chip, extends toward a second direction of the LED chip through the first bent portion, and extends toward a third direction of the LED chip through the second bent portion, and wherein the first direction, the second direction, and the third direction are different directions.

9. The LED filament according to claim 8, wherein the first direction is a height direction of the LED chip, the second direction is a width direction of the LED chip, and the third direction is a length direction of the LED chip.

10. The LED filament according to claim 9, wherein the plurality of LED chips further comprises a first row of LED chips and a second row of LED chips, the first row of LED chips and the second row of LED chips are connected in parallel, the LED chips of the first row of LED chips are connected in series, the LED chips of the second row of LED chips connected in series, and the first row of LED chips and the second row of LED chips are alternately arranged along a width direction of the LED filament.

11. An LED light bulb, comprising: a lamp housing with a central axis; a bulb base connected to the lamp housing; a stem disposed in the lamp housing along the central axis of the lamp housing; two conductive supports disposed in the lamp housing, the two conductive supports having opposite polarities; a driving circuit disposed in the bulb base and electrically connected to the two conductive supports; and a flexible LED filament disposed in the lamp housing and electrically connected to the two conductive supports, the flexible LED filament comprising: an LED section comprising a plurality of LED chips connected in series and a light conversion layer wrapping the plurality of LED chips; a first conductive electrode disposed at one of two ends of the LED section and electrically connected to the plurality of LED chips and one of the two conductive supports, wherein a portion of the first conductive electrode is wrapped by the light conversion layer; a second conductive electrode disposed at the other one of the two ends of the LED section and electrically connected to the plurality of LED chips and the other one of the two conductive supports, wherein a portion of the second conductive electrode is wrapped by the light conversion layer; a conductive portion electrically connected between two adjacent LED chips, the conductive

portion comprising two end portions; and a first solder layer disposed on one end portion of the conductive portion, wherein an LED chip among the plurality of LED chips has an electrical connecting portion, the one end portion of the conductive portion is connected to the electrical connecting portion and the first solder layer is disposed on the end portion of the conductive portion, and the end portion of the conductive portion is sandwiched between the electrical connecting portion of the LED chip and the first solder layer.

12. The LED light bulb according to claim 11, wherein a projection area of the first solder layer on the electrical connecting portion of the LED chip is larger than a projection area of a bonding region between the conductive portion and the electrical connecting portion of the LED chip.

13. The LED light bulb according to claim 12, wherein the end portion of the conductive portion, the electrical connecting portion of the LED chip, and the first solder layer together form a joining portion, the joining portion has a meshy surface, and a plurality of bulges and a plurality of indents are alternately arranged on the meshy surface.

14. The LED light bulb according to claim 13, wherein the plurality of LED chips further comprises a first row of LED chips and a second row of LED chips, the first row of LED chips and the second row of LED chips are connected in parallel, the LED chips of the first row of LED chips are connected in series, the LED chips of the second row of LED chips connected in series, and the first row of LED chips and the second row of LED chips are alternately arranged along a width direction of the LED filament.

15. The LED light bulb according to claim 12, further comprising a second solder layer, wherein the second solder layer is made of the solder material, and the end portion of the conductive portion is sandwiched between the first solder layer and the second solder layer.

16. The LED light bulb according to claim 15, wherein each of a projection area of the first solder layer on the electrical connecting portion of the LED chip and a projection area of the second solder layer on the electrical connecting portion of the LED chip is larger than a projection area of a bonding region between the conductive portion and the first solder layer, and between the conductive portion and the second solder layer on the electrical connecting portion of the LED chip.

17. The LED light bulb according to claim 16, wherein a projection area of a bonding region between the conductive portion and the second solder layer is smaller than the projection area of the first solder layer, and the projection area of the first solder layer is smaller than the projection area of the second solder layer.

18. The LED light bulb according to claim 12, wherein the conductive portion has a first bent portion and a second bent portion, and the conductive portion extends from the electrical connecting portion along a first direction of the LED chip, extends toward a second direction of the LED chip through the first bent portion, and extends toward a third direction of the LED chip through the second bent portion, and wherein the first direction, the second direction, and the third direction are different directions.

19. The LED light bulb according to claim 18, wherein the first direction is a height direction of the LED chip, the second direction is a width direction of the LED chip, and the third direction is a length direction of the LED chip.

20. The LED light bulb according to claim 19, wherein the plurality of LED chips further comprises a first row of LED chips and a second row of LED chips, the first row of LED chips and the second row of LED chips are connected in parallel, the LED chips of the first row of LED chips are connected in series, the LED chips of the second row of LED chips connected in series, and the first row of LED chips and the second row of LED chips are alternately arranged along a width direction of the LED filament.
