

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284213

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

HU; Cheng-Kang et al.

SYSTEM OF REMOVING PARTICLES FROM PELLICLE

Abstract

A method of removing a particle from a pellicle includes moving a nozzle over a surface of a membrane of the pellicle to a location of the particle. A droplet of a liquid material is dispensed from the nozzle to cover the particle on the surface of the membrane. A contact of the droplet with the nozzle is monitored and maintained. The droplet carrying the particle is horizontally dragged along the surface of the membrane toward an edge thereof by the nozzle using the surface tension of the droplet. The droplet carrying the particle is sucked off from the edge of the membrane by a vacuum pump, thereby automatically and safely removing the particle without damaging the pellicle.

Inventors: HU; Cheng-Kang (Hsinchu, TW), CHEN; Yin Yuan (Hsinchu, TW), WEN; Ya-Chieh (Hsinchu, TW), LIU; Hsu-Shui (Hsinchu, TW), PAI; Jiun-Rong (Hsinchu, TW)

Applicant: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Family ID: 1000008629168

Assignee: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Appl. No.: 19/219578

Filed: May 27, 2025

Related U.S. Application Data

parent US division 18138012 20230421 parent-grant-document US 12346034 child US 19219578

Publication Classification

Int. Cl.: G03F7/00 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] The present application is a divisional of U.S. application Ser. No. 18/138,012 filed Apr. 21, 2023, the entire contents of which are incorporated herein by reference.

BACKGROUND

[0002] During an integrated circuit (IC) design, a number of layout patterns of the IC, for different steps of IC processing, are generated on a substrate. The patterns may be produced by projecting, e.g., imaging, patterns of a mask on a photo resist layer of a wafer. A lithography process transfers the patterns of the mask to the photoresist layer of the substrate such that etching, implantation, or other steps are applied only to predefined regions of the substrate. Transferring the patterns of the mask to the photoresist layer may be performed e.g., using an extreme ultraviolet (EUV) radiation source to expose the photoresist layer of the substrate.

Description

BRIEF DESCRIPTION OF THE DRAWING

[0003] The present disclosure is best understood from the following detailed description when read with the accompanying figures. It is emphasized that, in accordance with the standard practice in the industry, various features are not drawn to scale and are used for illustration purposes only. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

[0004] FIG. 1 shows a schematic view of an extreme ultraviolet (EUV) lithography system with a laser produced plasma (LPP) EUV radiation source in accordance with some embodiments of the present disclosure.

[0005] FIG. 2 shows a schematic view of an EUV lithography exposure tool in accordance with some embodiments of the present disclosure.

[0006] FIGS. 3A and 3B show cross-sectional views of a reflective reticle structure and projecting the reflective reticle structure on a semiconductor device in accordance with some embodiments of the present disclosure.

[0007] FIG. 4 shows a membrane of a pellicle having a border in accordance with some embodiments of the present disclosure.

[0008] FIG. 5 shows a pellicle cleaning system in accordance with some embodiments of the present disclosure.

[0009] FIGS. 6A, 6B, 6C and 6D show Automated Optical Inspection (AOI) devices in accordance with some embodiments of the present disclosure.

[0010] FIGS. 7A, 7B, 7C, 7D and 7E show some sequential operations of removing a particle from a pellicle in accordance with some embodiments of the present disclosure.

[0011] FIG. 8 shows a schematic view of a pellicle cleaning apparatus in accordance with some embodiments of the present disclosure.

[0012] FIGS. 9A and 9B show various nozzle structures of a pellicle cleaning apparatus in accordance with some embodiments of the present disclosure.

[0013] FIG. 10 shows a flowchart of a method of removing a particle from a pellicle in accordance with an embodiment of present disclosure.

[0014] FIG. 11 shows a flowchart of a method of removing a particle from a pellicle in accordance with another embodiment of present disclosure.

[0015] FIGS. 12A and 12B illustrate an apparatus for removing particles from a pellicle of a reticle in accordance with some embodiments of the present disclosure.

DETAILED DESCRIPTION

[0016] The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

[0017] Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly. In addition, the term “being made of” may mean either “comprising” or “consisting of.” In the present disclosure, a phrase “one of A, B and C” means “A, B and/or C” (A, B, C, A and B, A and C, B and C, or A, B and C), and does not mean one element from A, one element from B and one element from C, unless otherwise described.

[0018] A pellicle is a thin transparent film stretched over a frame that is attached with an adhesive over one side of a reticle to protect the reticle from damage, dust, and/or moisture. Thus, it is desirable that the pellicle is highly transparent to the radiation source of the lithography process. In EUV lithography, the pellicle is desirable to be clean (e.g., free of particles), to be highly transparent in the EUV wavelength region, and to have high durability.

[0019] When the reticle is covered by a pellicle, the particles sit on the pellicle instead of the reticle and, thus, when the reticle is imaged on a substrate, the particles that are not in the plane of the reticle do not create a focused image on the substrate. In the present disclosure, the terms of reticle, mask, and photomask are used interchangeably. The pellicle is about 25 nm to about 125 nm thick layer of material that is transparent to the UV radiation source, e.g., transparent to the DUV or EUV radiation source, of the lithography process. In some embodiments, the pellicle is made of SiC, polysilicon, silicon nitride, metallic films or graphene. In some embodiments, when the pellicle is placed, e.g., mounted, on top of the reticle, the pellicle is placed on top of a plurality of studs or fixtures and a distance between about 2 mm to about 5 mm is created between the reticle and the pellicle.

[0020] In the present disclosure, in some embodiments, a method of removing a particle from a pellicle includes moving a nozzle over a surface of a membrane of the pellicle to a location of the particle. A droplet of a liquid material is dispensed from the nozzle to cover the particle on the surface of the membrane. A contact of the droplet with the nozzle is monitored and maintained. The droplet carrying the particle is horizontally dragged along the surface of the membrane toward an edge thereof by the nozzle using the surface tension of the droplet. The droplet carrying the particle is sucked off from the edge of the membrane by a vacuum pump, thereby automatically and safely removing the particle without damaging the pellicle.

[0021] In the present disclosure, in some embodiments, a system of removing a particle from a

pellicle includes a support stage for holding the pellicle; a nozzle to dispense a droplet of a liquid material to cover the particle on a surface of a membrane of the pellicle; a robot arm to move the nozzle; a vacuum pump located on an edge of the membrane to suck off the droplet; a distance detector to detect a distance between the nozzle and the surface; and a processor controller coupled to the robot arm, the vacuum pump, the particle detector, and the distance detector. The processor controller controls the robot arm to horizontally move the nozzle to the location of the particle, to lower the nozzle toward the membrane until the distance reaching a threshold distance, and to horizontally drag the droplet and the particle toward the membrane edge by the nozzle using the surface tension of the droplet; and to activate the vacuum pump to suck off the droplet and the particle from the edge of the membrane, thereby automatically and safely removing the particle without damaging the pellicle.

[0022] FIG. 1 shows a schematic view of an EUV lithography system with a laser produced plasma (LPP) EUV radiation source in accordance with some embodiments of the present disclosure. The EUV lithography system includes an EUV radiation source **100** (an EUV light source) to generate EUV radiation, an exposure device **200**, such as a scanner, and an excitation laser source **300**. As shown in FIG. 1, in some embodiments, the EUV radiation source **100** and the exposure device **200** are installed on a main floor MF of a clean room, while the excitation laser source **300** is installed in a base floor BF located under the main floor. Each of the EUV radiation source **100** and the exposure device **200** are placed over pedestal plates PP1 and PP2 via dampers DMP1 and DMP2, respectively. The EUV radiation source **100** and the exposure device **200** are coupled to each other by a coupling mechanism, which may include a focusing unit. In some embodiments, a lithography system includes the EUV radiation source **100** and the exposure device **200**.

[0023] The lithography system is an EUV lithography system designed to expose a resist layer by EUV light (also interchangeably referred to herein as EUV radiation). The resist layer is a material sensitive to the EUV light. The EUV lithography system employs the EUV radiation source **100** to generate EUV light, such as EUV light having a wavelength ranging between about 1 nm and about 50 nm. In one particular example, the EUV radiation source **100** generates an EUV light with a wavelength centered at about 13.5 nm. In the present embodiment, the EUV radiation source **100** utilizes a mechanism of laser-produced plasma (LPP) to generate the EUV radiation.

[0024] The exposure device **200** includes various reflective optical components, such as convex/concave/flat mirrors, a mask holding mechanism including a mask stage, and wafer holding mechanism, e.g., a substrate holding mechanism. The EUV radiation generated by the EUV radiation source **100** is guided by the reflective optical components onto a mask secured on the mask stage. In some embodiments, the mask stage includes an electrostatic chuck (e-chuck) to secure the mask. Because gas molecules absorb EUV light, the lithography system for the EUV lithography patterning is maintained in a vacuum or a-low pressure environment to avoid EUV intensity loss. The exposure device **200** is described in more details with respect to FIG. 2. In some embodiments, a mask is transferred into the exposure device **200**. As noted, the exposure device **200** is maintained under a vacuum environment and the mask is mounted over a substrate, with a photo resist layer disposed on the substrate. The mask has a pellicle mounted over the reticle. After transferring the mask with the pellicle into the exposure device **200**, the air pressure in the enclosure between the reticle and the pellicle is equalized with the vacuum environment of the exposure device **200** through the holes in the mounting fixture (the frame). The EUV radiation generated by the EUV radiation source **100** is directed by the optical components to project the mask on the photo resist layer of the substrate. In some embodiments, after the exposure of the mask on the photo resist layer of the substrate, the reticle with the pellicle is transferred out of the exposure device **200**. After transferring the reticle with the pellicle out of the exposure device **200**, the air pressure in the enclosure between the reticle and the pellicle is equalized with the atmospheric pressure outside the exposure device **200** through the holes in the mounting fixture.

[0025] In addition, the term resist and photoresist are used interchangeably. In some embodiments,

the mask is a reflective mask. In some embodiments, the mask includes a substrate with a suitable material, such as a low thermal expansion material or fused quartz. In various examples, the material includes TiO_2 doped SiO_2 , or other suitable materials with low thermal expansion. The mask includes multiple reflective layers (ML) deposited on the substrate. The ML includes a plurality of film pairs, such as molybdenum-silicon (Mo/Si) film pairs (e.g., a layer of molybdenum above or below a layer of silicon in each film pair). Alternatively, the ML may include molybdenum-beryllium (Mo/Be) film pairs, or other suitable materials that are configurable to highly reflect the EUV light. The mask may further include a capping layer, such as ruthenium (Ru), disposed on the ML for protection. The mask further includes an absorption layer, such as a tantalum boron nitride (TaBN) layer, deposited over the ML. The absorption layer is patterned to define a layer of an integrated circuit (IC). Alternatively, another reflective layer may be deposited over the ML and is patterned to define a layer of an integrated circuit, thereby forming an EUV phase shift mask. The mask is described with respect to FIG. 3A.

[0026] The exposure device **200** includes a projection optics module for imaging the pattern of the mask on to a semiconductor substrate with a resist coated thereon secured on a substrate stage of the exposure device **200**. The projection optics module generally includes reflective optics. The EUV radiation (EUV light) directed from the mask, carrying the image of the pattern defined on the mask, is collected by the projection optics module, thereby forming an image on the resist.

[0027] In various embodiments of the present disclosure, the semiconductor substrate is a semiconductor wafer, such as a silicon wafer or other type of wafer to be patterned. The semiconductor substrate is coated with a resist layer sensitive to the EUV light in presently disclosed embodiments. Various components including those described above are integrated together and are operable to perform lithography exposing processes. The lithography system may further include other modules or be integrated with (or be coupled with) other modules.

[0028] As shown in FIG. 1, the EUV radiation source **100** includes a droplet generator **115** and a LPP collector mirror **110**, enclosed by a chamber **105**. The droplet generator **115** generates a plurality of target droplets DP, which are supplied into the chamber **105** through a nozzle **117**. In some embodiments, the target droplets DP are tin (Sn), lithium (Li), or an alloy of Sn and Li. In some embodiments, the target droplets DP each have a diameter in a range from about 10 microns (μm) to about 100 μm . For example, in an embodiment, the target droplets DP are tin droplets, each having a diameter of about 10 μm , about 25 μm , about 50 μm , or any diameter between these values. In some embodiments, the target droplets DP are supplied through the nozzle **117** at a rate in a range from about 50 droplets per second (i.e., an ejection-frequency of about 50 Hz) to about 50,000 droplets per second (i.e., an ejection-frequency of about 50 kHz). For example, in an embodiment, target droplets DP are supplied at an ejection-frequency of about 50 Hz, about 100 Hz, about 500 Hz, about 1 kHz, about 10 kHz, about 25 kHz, about 50 kHz, or any ejection-frequency between these frequencies. The target droplets DP are ejected through the nozzle **117** and into a zone of excitation ZE (e.g., a target droplet location) at a speed in a range from about 10 meters per second (m/s) to about 100 m/s in various embodiments. For example, in an embodiment, the target droplets DP have a speed of about 10 m/s, about 25 m/s, about 50 m/s, about 75 m/s, about 100 m/s, or at any speed between these speeds.

[0029] The excitation laser beam LR2 generated by the excitation laser source **300** is a pulsed beam. The laser pulses of laser beam LR2 are generated by the excitation laser source **300**. The excitation laser source **300** may include a laser generator **310**, laser guide optics **320** and a focusing apparatus **330**. In some embodiments, the laser generator **310** includes a carbon dioxide (CO_2) or a neodymium-doped yttrium aluminum garnet (Nd:YAG) laser source with a wavelength in the infrared region of the electromagnetic spectrum. For example, the laser source **310** has a wavelength of 9.4 μm or 10.6 μm in an embodiment. The laser light beam LR0 generated by the excitation laser source **300** is guided by the laser guide optics **320** and focused, by the focusing apparatus **330**, into the excitation laser beam LR2 that is introduced into the EUV radiation source

100. In some embodiments, in addition to CO.sub.2 and Nd:YAG lasers, the laser beam LR2 is generated by a gas laser including an excimer gas discharge laser, helium-neon laser, nitrogen laser, transversely excited atmospheric (TEA) laser, argon ion laser, copper vapor laser, KrF laser or ArF laser; or a solid state laser including Nd:glass laser, ytterbium-doped glasses or ceramics laser, or ruby laser. In some embodiments, a non-ionizing laser beam LR1 is also generated by the excitation laser source **300** and the laser beam LR1 is also focused by the focusing apparatus **330**.

[0030] In some embodiments, the excitation laser beam LR2 includes a pre-heat laser pulse and a main laser pulse. In such embodiments, the pre-heat laser pulse (interchangeably referred to herein as the “pre-pulse”) is used to heat (or pre-heat) a given target droplet to create a low-density target plume with multiple smaller droplets, which is subsequently heated (or reheated) by a pulse from the main laser (main pulse), generating increased emission of EUV light compared to when the pre-heat laser pulse is not used.

[0031] In various embodiments, the pre-heat laser pulses have a spot size about 100 μm or less, and the main laser pulses have a spot size in a range of about 150 μm to about 300 μm . In some embodiments, the pre-heat laser and the main laser pulses have a pulse-duration in the range from about 10 ns to about 50 ns, and a pulse-frequency in the range from about 1 kHz to about 100 kHz. In various embodiments, the pre-heat laser and the main laser have an average power in the range from about 1 kilowatt (kW) to about 50 kW. The pulse-frequency of the excitation laser beam LR2 is matched with the ejection-frequency of the target droplets DP in an embodiment.

[0032] The laser beam LR2 is directed through windows (or lenses) into the zone of excitation ZE. The windows adopt a suitable material substantially transparent to the laser beams. The generation of the laser pulses is synchronized with the ejection of the target droplets DP through the nozzle **117**. As the target droplets move through the excitation zone, the pre-pulses heat the target droplets and transform them into low-density target plumes. A delay between the pre-pulse and the main pulse is controlled to allow the target plume to form and to expand to an optimal size and geometry. In various embodiments, the pre-pulse and the main pulse have the same pulse-duration and peak power. When the main pulse heats the target plume, a high-temperature plasma is generated. The plasma emits EUV radiation, which is collected by the collector mirror **110**. The collector mirror **110**, an EUV collector mirror, further reflects and focuses the EUV radiation for the lithography exposing processes performed through the exposure device **200**. A droplet DP that does not interact with the laser pulses is captured by the droplet catcher **85**.

[0033] One method of synchronizing the generation of a pulse (either or both of the pre-pulse and the main pulse) from the excitation laser with the arrival of the target droplet in the zone of excitation is to detect the passage of a target droplet at given position and use it as a signal for triggering an excitation pulse (or pre-pulse). In this method, if, for example, the time of passage of the target droplet is denoted by $t_{\text{sub.0}}$, the time at which EUV radiation is generated (and detected) is denoted by $t_{\text{sub.rad}}$, and the distance between the position at which the passage of the target droplet is detected and a center of the zone of excitation is d , the speed of the target droplet, $v_{\text{sub.dp}}$, is calculated as: $v_{\text{sub.dp}} = d / (t_{\text{sub.rad}} - t_{\text{sub.o}})$ equation (1).

[0034] Because the droplet generator **115** is expected to reproducibly supply droplets at a fixed speed, once $v_{\text{sub.dp}}$ is calculated, the excitation pulse is triggered with a time delay of $d / v_{\text{sub.dp}}$ after a target droplet is detected to have passed the given position to ensure that the excitation pulse arrives at the same time as the target droplet reaches the center of the zone of excitation. In some embodiments, because the passage of the target droplet is used to trigger the pre-pulse, the main pulse is triggered following a fixed delay after the pre-pulse. In some embodiments, the value of target droplet speed $v_{\text{sub.dp}}$ is periodically recalculated by periodically measuring $t_{\text{sub.rad}}$, if needed, and the generation of pulses with the arrival of the target droplets is resynchronized.

[0035] FIG. 2 shows a schematic view of an EUV lithography (EUVL) exposure tool in accordance with some embodiments of the present disclosure. The EUVL exposure tool of FIG. 2 includes the exposure device **200** that shows the exposure of photoresist coated substrate, a target

semiconductor substrate **210**, with a patterned beam of EUV light. The exposure device **200** is an integrated circuit lithography tool such as a stepper, scanner, step and scan system, direct write system, device using a contact and/or proximity mask, etc., provided with one or more optics **205a**, **205b**, for example, to illuminate a patterning optic, such as a reticle, e.g., a reflective mask **205c**, with a beam of EUV light, to produce a patterned beam, and one or more reduction projection optics **205d**, **205e**, for projecting the patterned beam onto the target semiconductor substrate **210**. A mechanical assembly (not shown) may be provided for generating a controlled relative movement between the target semiconductor substrate **210** and patterning optic, e.g., a reflective mask **205c**. As further shown, the EUVL exposure tool of FIG. 2, further includes the EUV radiation source **100** including a plasma plume **23** at the zone of excitation ZE emitting EUV light in the chamber **105** that is collected and reflected by a collector mirror **110** into the exposure device **200** to irradiate the target semiconductor substrate **210**. In some embodiments, a pressure inside the exposure device **200** is sensed by a pressure sensor **208** inside the exposure device **200** and is controlled by a vacuum pressure controller **206** that is coupled to the exposure device **200**.

[0036] As noted above, because gas molecules absorb EUV light, the lithography system for the EUV lithography patterning, e.g., the exposure device **200**, is maintained in a vacuum environment to avoid EUV intensity loss. After transferring the reticle with the pellicle into the exposure device **200**, the air pressure in the enclosure between the reticle and the pellicle is equalized with the vacuum environment of the exposure device **200** through the holes in the mounting fixture (the frame) and, thus, vacuum is produced in the enclosure between the reticle and the pellicle. In some embodiments, after the exposure of the mask on the photo resist layer of the substrate, the reticle with the pellicle, the reticle structure, is transferred out of the exposure device **200**. After transferring the reticle with the pellicle out of the exposure device **200**, the vacuum in the enclosure between the reticle and the pellicle is equalized with the atmospheric pressure outside the exposure device **200** through the holes in the mounting fixture and, thus, atmospheric pressure is produced in the enclosure between the reticle and the pellicle.

[0037] FIGS. 3A and 3B show a cross-sectional view of a reflective reticle structure **350**, e.g., a reticle system, and projecting the reflective reticle structure **350** on a semiconductor device in accordance with some embodiments of the present disclosure.

[0038] FIG. 3A shows a cross-sectional view of a reflective reticle structure **350** that includes a reticle **80**, e.g., a reflective mask. As noted above, the terms mask, photomask, and reticle may be used interchangeably. In some embodiments, the reticle **80** is a reflective mask and is used as part of the reflective reticle structure **350**. The reflective reticle structure **350** is consistent with reflective mask **205c** of FIG. 2 and is used in the exposure device **200** of FIG. 2.

[0039] The reticle **80** includes a substrate **30**, reflective multiple layers (ML) **35** that are deposited on the substrate **30**, a conductive backside coating **60**, a capping layer **40**, and an absorption layer **45**. In some embodiments, the reflective reticle structure **350** also includes a pellicle structure **70**, a mounted structure that includes a membrane **65** mounted on a frame **75**.

[0040] In some embodiments, the material of the substrate **30** includes TiO₂ doped SiO₂, or other suitable materials with low thermal expansion. In some embodiments, the substrate **30** includes fused quartz and has a thickness between about 6 mm to about 7 mm.

[0041] In some embodiments, the ML **35** includes a plurality of film pairs, such as molybdenum-silicon (Mo/Si) film pairs (e.g., a layer of molybdenum layer **39** above or below a layer of silicon layer **37** in each film pair). In some embodiments, the ML **35** has 40 to 50 pairs of the molybdenum layer **39** and the silicon layer **37** and each molybdenum layer **39** has a thickness of 3 nm and each silicon layer **37** has a thickness of 4 nm. Thus, in some embodiments, the ML **35** has a thickness between 280 nm to 350 nm. Alternatively, the ML **35** may include molybdenum-beryllium (Mo/Be) film pairs, or other suitable materials that are configured to highly reflect the EUV light.

[0042] The capping layer **40** may include ruthenium (Ru) and may be disposed on the ML **35** for protection and may have a thickness of 2.5 nm. In some embodiments, the capping layer **40** may

include silicon (Si) and may be disposed on the ML **35** for protection and may have a thickness of 4 nm. In some embodiments, the absorption layer **45** that includes a tantalum boron nitride (TaBN) layer is deposited over the ML **35** and the capping layer **40**.

[0043] In some embodiments, the absorption layer **45** is patterned into pattern features **55** to define a layout pattern for layer of an integrated circuit (IC). In some embodiments, the backside coating **60** includes chromium nitride (CrN) or tantalum boride (TaB) and has a thickness of about 20 nm to about 100 nm. In some embodiments, the absorption layer **45** includes one or a combination of TaBO, TaBN, TaNO, and TaN and has a thickness between 50 nm and 70 nm.

[0044] FIG. **3B** shows exposing the photoresist of a semiconductor device to radiation in accordance with some embodiments of the present disclosure. FIG. **3B** shows the semiconductor device **34** includes a photoresist layer **15** that is disposed on a semiconductor substrate **10**. FIG. **3B** also shows a radiation beam **50** that is originated from an EUV light source, e.g., EUV light source **100** of FIG. **1**. The radiation beam **50** is directed to the reticle **80**, e.g., a reflective photomask, where the radiation beam **50'** is reflected from the reflective photomask **80** and is incident onto the photoresist layer **15**. The incident angle of the radiation beam **50'**, which is defined with respect to a line **302** that is perpendicular to a top surface of the semiconductor substrate **10** is angle A. As shown in FIG. **3B**, the incident radiation beam **50** and the reflected radiation beam **50'** pass through the membrane **65** of the pellicle structure **70**. In some embodiments, the semiconductor substrate **10**, consistent with the semiconductor substrate **210** of FIG. **2**, is mounted on a stage **360** that is coupled to and controlled by a stage controller **365** for moving the semiconductor device **34** and exposing different locations of the semiconductor device **34**.

[0045] FIG. **4** shows the membrane **65**, e.g., a transparent membrane, of a pellicle **70** having a border section **402**. In some embodiments, the membrane **65** is an about 25 nm to about 125 nm thick layer of a material that is transparent to the UV radiation source, e.g., transparent to the DUV or EUV radiation source of the lithography process. In some embodiments, a width **410** of the membrane **65** is between about 50 mm to about 100 mm and a length **412** of the membrane **65** is between about 100 mm and about 200 mm. In some embodiments, the membrane **65** is attached on a frame **75** from a back side at the border section **402** of the membrane **65**.

[0046] FIG. **5** shows a pellicle cleaning system **500** to remove particles from a pellicle in accordance with some embodiments of the present disclosure. In some embodiments, the pellicle cleaning system **500** includes an automated optical inspection (AOI) system **600**, a processor controller **520** coupled to the AOI system **600**, a nozzle **502**, a tube (or pipe) **503** in liquid connection with the nozzle **502**, a robot arm **504** to move the nozzle **502**, a cleaning liquid supply **506** in liquid connection with the tube **503**, a vacuum pump **508**, an air blower **509**, and a pellicle stage **90** to support the pellicle **70**.

[0047] In some embodiments, the nozzle **502** dispenses a droplet of a cleaning liquid to cover a particle on a surface of a pellicle **70**. In some embodiments, the nozzle **502** drags the droplet along with the particle along the surface of the pellicle **70** using the surface tension of the droplet. In some embodiments, the robot arm **504** horizontally and/or vertically moves the nozzle **502** under the control of the processor controller **520**. In some embodiments, the cleaning liquid supply **506** supplies a cleaning liquid to the nozzle **502** via the tube **503** under the control of the processor controller **520**. In some embodiments, the vacuum pump **508** is located at an edge of the pellicle **70** and sucks off the droplet along with the particle from the pellicle **70** under the control of the processor controller **520**. In some embodiments, the air blower **509** is located at an edge of the pellicle **70** and blows off the droplet and the particle outside of the pellicle **70** under the control of the processor controller **520**.

[0048] In some embodiments, the processor controller **520** controls the robot arm **504** to horizontally and/or vertically move the nozzle **502**, controls the cleaning liquid supply **506** to supply the cleaning liquid to the nozzle **502** via the tube **503**, and activates the vacuum pump **508** to suck liquid droplets off the pellicle **70**. In other embodiments, the processor controller **520**

activates the air blower **509** to blow liquid droplets off the pellicle **70**.

[0049] In some embodiments, the AOI system **600** includes a particle detector **601**, a distance detector **602**, a droplet monitor **603**, and a pellicle damage detector **604**. FIGS. **6A**, **6B**, **6C** and **6D** respectively show some AOI devices in accordance with some embodiments of the present disclosure.

[0050] As shown in FIG. **6A**, in some embodiments, the particle detector **601** includes a laser source to emit a horizontal laser beam approximately in parallel to a surface of a pellicle of a reticle, and a camera aimed at the surface of the pellicle in a direction perpendicular to the surface of the pellicle to capture images (scattered laser light) of the surface of the pellicle, thereby determining whether there are particles on the surface of the pellicle. The pellicle stage records the X-Y coordinates of the location of the particle, which is stored in a memory device. A particle is located on a surface of the membrane of the pellicle **70** using the particle detector **601**. The processor controller **520** (in FIG. **5**) uses the location obtained from the particle detector **601** to control the robot arm **504** to move the nozzle **502** toward the location of the particle.

[0051] As shown in FIG. **6B**, in some embodiments, the distance detector **602** includes a distance detection laser source to emit a laser beam to the surface of the pellicle in a direction perpendicular to the surface of the pellicle, a backlight source to emit a backlight to an edge of the pellicle in direction opposite to the laser beam from the distance detection laser source, and a camera aimed at the edge of the pellicle and the reticle in a direction perpendicular to the surface of the pellicle, thereby determining a thickness of the pellicle and the distance between a head of the nozzle and the surface of the pellicle. The processor controller **520** (in FIG. **5**) uses the thickness of the pellicle and the distance to determine whether the distance reaches a threshold distance (f) when the robot arm **504** lowers the nozzle **502** toward the pellicle **70**. Once the distance is determined reaching the threshold distance (f), the processor controller **520** controls the robot arm **504** to stop lowering the nozzle **502**.

[0052] As shown in FIG. **6C**, in some embodiments, the droplet monitor **603** includes a backlight source to emit a backlight beam in a direction to the droplet and parallel with the surface of the pellicle; and a camera to receive the backlight beam passing through the droplet to monitor the contact of the droplet with the head of the nozzle, thereby determining whether or not the contact of the droplet with the nozzle is maintained. In some embodiments, the droplet monitor **603** monitors a contact status of the droplet **803** with the nozzle **502**, the process controller **520** controls the cleaning liquid supply **506** to adjust a supply of the cleaning liquid to the nozzle **502** based on the monitored contact status, thereby maintaining the contact of the droplet **803** with the nozzle **502**.

[0053] As shown in FIG. **6D**, in some embodiments, the pellicle damage detector **604** includes a laser line scan device that scans the pellicle, emits an incident laser beam to the surface of the pellicle, and receives a reflective laser beam from the surface of the pellicle, in which the incident laser beam and the reflective laser beam form an angle (α) (such as 30, 45 or 90 degree), thereby detecting one or more holes in the transparent pellicle. The pellicle stage records the X-Y coordinates of the location of the hole, which is stored in a memory device. Once one or more holes are detected by the pellicle damage detector **604**, the process controller **520** determines that the pellicle **70** is damaged.

[0054] FIGS. **7A**, **7B**, **7C**, **7D** and **7E** show some sequential operations of removing a particle from a pellicle in accordance with some embodiments of the present disclosure. In some embodiments, in a pre-inspection, a pellicle **70** attached to a reticle **80** and supported by a mask stage **90** undertakes an optical inspection by an Integrated Reticle Inspection System (IRIS) to find whether there are any particles on the pellicle **70**. In some embodiments, once a particle **801** is found on the pellicle **80**, an Out-Of-Control Action Plan (OCAP) will be triggered, the reticle **80** along with the pellicle **70** is transferred to a pellicle cleaning system **500** as shown in FIG. **5**, and some operations as shown in FIGS. **7A**, **7B**, **7C**, **7D** and **7E** are performed to remove the particle **801** from the pellicle **70**.

[0055] As shown in FIG. 7A, a particle **801** is located on a surface of the pellicle **70**. In some embodiments, the location of the particle **801** is detected by a particle detector **601** as shown in FIG. 6A. In other embodiments, the location of the particle **801** is received from another device or system (not shown).

[0056] As shown in FIG. 7B, a nozzle **502** is moved toward the particle **801** according to the location data obtained from the particle detector **601**. In some embodiments, the nozzle **502** is in fluid connection with a cleaning liquid supply **506** via a tube **503** as shown in FIG. 5. In some embodiments, the nozzle **502** is moved to the particle **801** by a robot arm **504** that is controlled by a process controller **520** as shown in FIG. 5. In some embodiments, the nozzle **502** is horizontally moved to the location of the particle **801**, and then is lowered toward the particle **801** until a distance between a head of the nozzle **502** and a surface of the pellicle **70** reaching a threshold distance. In some embodiments, the distance between the head of the nozzle **502** and the surface of the pellicle **70** is detected by a distance detector **602** as shown in FIG. 6B.

[0057] As shown in FIG. 7C, a droplet **803** of a cleaning liquid material is dispensed from the nozzle **502** to cover the particle **801** on the surface of the pellicle **70**. In some embodiments, the cleaning liquid material is an organic solvent, such as an anhydrous alcohol. In some embodiments, a droplet monitor **603** is used to continuously monitor a contact of the droplet **803** with the head of the nozzle **502**, thereby determining whether or not the contact of the droplet with the nozzle is maintained. In some embodiments, a supply of the cleaning liquid material to the nozzle **502** is controlled by the process controller **520** to maintain the contact of the droplet **803** with the nozzle **502**. In some embodiments, when the droplet monitor **603** finds that the contact of the droplet **803** with the nozzle **502** is lost, the process controller **520** controls the supply of the cleaning liquid material to the nozzle **502** so that the nozzle **502** dispenses additional cleaning liquid material to droplet **803**, thereby maintaining the contact of the droplet **803** with the nozzle **502**. Once the droplet monitor **603** determines that the contact of the droplet **803** with the nozzle **502** is resumed, the process controller **520** controls the supply of the cleaning liquid material to the nozzle **502** to stop dispensing additional cleaning liquid material to droplet **803**. In some embodiments, a volume of the cleaning liquid material is in a range from 0.1 ml to about 10.0 ml. In some embodiments, the volume of the cleaning material is adjusted based on the size of the particles or the number of particles targeted by one supply (droplet) of the cleaning liquid material.

[0058] As shown in FIG. 7D, the droplet **803** along with the particle **801** is dragged by the nozzle **502** using the surface tension of the droplet **803** toward an edge of the pellicle **70**. In some embodiments, the droplet **803** is dragged by the nozzle **502** at a speed in a range from about 1.0 mm/second to about 10.0 mm/second.

[0059] As shown in FIG. 7E, in some embodiments, the droplet **803** along with the particle **801** is suck off from the edge of the pellicle **70** by a vacuum pump **508**. In other embodiments, the droplet **803** along with the particle **801** is blown off from the edge of the pellicle **70** by an air blower **509** (not shown in FIG. 7E) to an outside of the pellicle **70**.

[0060] In addition, in some embodiments, after the removing the particle **801** from the pellicle **70**, the pellicle **70** undertakes another optical inspection performed by the IRIS to find whether there are additional particles on the pellicle **70**. After that, the pellicle **70** is determined clean if no additional particles are found. In some embodiments, the nozzle dragging the droplet with the particle is moved to another location of another particle to capture the another particle with the same droplet.

[0061] FIG. 8 shows a schematic view of a pellicle cleaning apparatus **800** in accordance with some embodiments of the present disclosure. The pellicle cleaning apparatus **800** is used for removing a particle **801** from a pellicle **70**. In some embodiments, the pellicle cleaning apparatus **800** includes a support stage **90** for holding a reticle **80** and the pellicle **70**, a nozzle **502** to dispense a droplet **803** of a cleaning liquid material to cover the particle **801** on a surface of the pellicle **70**, a robot arm **504** to move the nozzle **502** with respect to the surface of the membrane of the pellicle

70, and a vacuum pump **508** located on an edge of the pellicle **70** to suck off the droplet **803** and the particle **801**.

[0062] In some embodiments, the pellicle cleaning apparatus **800** obtains the location of a particle **801** on the surface of the membrane of the pellicle from a particle detector **601** as shown in FIG. **6A**. In some embodiments, the pellicle cleaning apparatus **800** obtains a distance between a head of the nozzle **502** and the surface of the membrane of the pellicle **70** from a distance detector **602** as shown in FIG. **6B**.

[0063] In some embodiments, the pellicle cleaning apparatus **800** obtains information about the contact of the droplet **803** with a head of the nozzle **502** from a droplet monitor **603** as shown in FIG. **6C**. In some embodiments, a cleaning liquid supply **506** to the nozzle **502** is adjusted to maintain the contact of the droplet **803** with the nozzle **502** based on the information about the contact of the droplet **803** with the head of the nozzle **502**.

[0064] In some embodiments, the pellicle cleaning apparatus **800** is coupled to a process controller **520**, which is coupled to the particle detector **601**, the distance detector **602**, and the droplet monitor **603** (as shown in FIG. **5**), and controls the operations of the robot arm **504**, the cleaning liquid supply **506**, and the vacuum pump **508**.

[0065] In some embodiments, the processor controller **520** controls the robot arm **504** to horizontally move the nozzle **502** with respect to the surface of the membrane of the pellicle **70** to the location of the particle **801**. In some embodiments, the processor controller **520** controls the robot arm **504** to lower the nozzle **502** toward the membrane of the pellicle **70** until the distance between the nozzle **502** and the surface of the membrane of the pellicle **70** reaches a threshold distance (f). In some embodiments, the threshold distance (f) is in a range from about 2.5 mm to about 3.5 mm.

[0066] In some embodiments, the process controller **520** controls the robot arm **504** to horizontally drag the droplet **803** along with the particle **801** toward the membrane edge of the pellicle **70** by the nozzle **502** using the surface tension of the droplet **803**.

[0067] In some embodiments, the process controller **520** activates the vacuum pump **508** to suck off the droplet **803** and the particle **801** from the edge of the membrane of the pellicle **70**. In other embodiments, the process controller **520** activates an air blower **509** (in FIG. **5**) to blow off the droplet **803** and the particle **801** from the edge of the membrane of the pellicle **70** to an outside of the pellicle **70** (not shown in FIG. **8**).

[0068] FIGS. **9A** and **9B** show various nozzle structures of a pellicle cleaning apparatus **800** in accordance with some embodiments of the present disclosure. In some embodiments, the nozzle **502** is made of a thermoplastic material. In some embodiments, the nozzle **502** is made of fluorocarbon polymer, such as poly tetra fluoroethylene (PTFE), poly-fluoro-alkoxy (PFA), fluorinated ethylene propylene (FEP), ethylene-tetra-fluoro-ethylene (ETFE), or poly vinylidene fluoride (PVDF). In some embodiments, the nozzle **502** is made of silica gel. In some embodiments, the nozzle **502** is made of glass or fiberglass. In some embodiments, the nozzle **502** and the tube **503** are made of the same material.

[0069] In some embodiments, the nozzle **502** is in a cylindrical shape. The nozzle **502** has a wall **502A** and an opening **502B**. In some embodiments, a thickness (a) of the wall **502A** is in a range from about 1 mm to about 2 mm, and an inner diameter (b) of the opening **502B** is in a range from about 3 mm to about 10 mm. In some embodiments, a ratio of the wall thickness (a) of the wall **502A** of the nozzle **502** to the inner diameter (b) of the opening **502B** of the nozzle **502** is in a range from about 0.30 to about 0.42.

[0070] As shown in FIG. **9B**, in some embodiments, the wall **502A** of the nozzle **502** is in a V-shape at the head of the nozzle **502**, the end line AA of the wall **502A** and the end line BB of the opening **502B** at the head of the nozzle **502** form a first angle θ_1 , which is in a range from about 5 degree to about 70 degree. In some embodiments, the nozzle **502** and the pellicle **70** forms a second angle θ_2 , which is about 90 degree. In some embodiments, the second angle θ_2 is in a range from

about 70 degree to about 110 degree. In some embodiments, the thickness of the pellicle **70** is greater than 500 μm , and the size of the particle **803** is less than 35 μm .

[0071] FIG. **10** shows a flowchart of a method **1000** of removing a particle from a pellicle in accordance with an embodiment of present disclosure. In some embodiments, a pellicle cleaning system as shown in FIG. **5** is used to clean a pellicle **70**. In some embodiments, the pellicle cleaning system **500** includes an AOI system **600**, a processor controller **520** coupled to the AOI system **600**, a nozzle **502**, a tube **503**, a robot arm **504** to move the nozzle **502**, a cleaning liquid supply **506** in liquid connection with the nozzle **502** via the tube **503**, and a vacuum pump **508** or an air blower **509**.

[0072] It is understood that additional operations can be provided before, during, and after the processes shown by FIG. **10**, and some of the operations described below can be replaced or eliminated, for additional embodiments of the method. The order of the operations/processes may be interchangeable. Materials, configurations, methods, processes and/or dimensions as explained with respect to the foregoing embodiments are applicable to the following embodiments, and the detailed description thereof may be omitted.

[0073] At S**1001** of FIG. **10**, the nozzle **502** is moved over a surface of a membrane of a pellicle **70** to a location of a particle **801** (in FIG. **7B**). In some embodiments, the nozzle moves while the reticle stage (reticle) stays. In other embodiments, the stage moves while reticle stage stays or both the nozzle and the reticle stage move.

[0074] At S**1002** of FIG. **10**, a droplet **803** of a cleaning liquid material is dispensed from the nozzle **502** on and covering the particle **801** on the surface of the membrane of the pellicle **70** (in FIG. **7C**). In some embodiments, the cleaning liquid material is an anhydrous alcohol.

[0075] At S**1003** of FIG. **10**, the droplet **803** along with the particle **801** is horizontally dragged toward an edge of the pellicle **70** by the nozzle **502** using the surface tension of the droplet **803** (in FIG. **7D**).

[0076] At S**1004** of FIG. **10**, in some embodiments, the droplet **801** along with the particle **803** is sucked off by a vacuum pump **508** from the edge of the membrane of the pellicle **70** (in FIG. **7E**), thereby automatically and safely removing the particle **803** without damaging the pellicle **70**. In other embodiments, the droplet **801** along with the particle **803** is blown off by an air blower **509** from the edge of the membrane of the pellicle **70** (not shown).

[0077] In some embodiments, before the dispensing the droplet **801**, the nozzle **502** is lowered toward the surface of the membrane of pellicle **70** until a distance between the nozzle and the surface of the membrane reaching a threshold distance (f) as shown in FIG. **9A**. In some embodiments, the threshold distance (f) is in a range from about 2.5 mm to about 3.5 mm.

[0078] In some embodiments, a contact of the droplet **803** with the nozzle **502** is monitored by a droplet monitor **603** (in FIG. **6C**). When the contact is found lost or the droplet is found not well-formed, additional cleaning liquid material is dispensed from the nozzle **502** to maintain the contact of the droplet **803** with the nozzle **502** (in FIG. **6C**).

[0079] FIG. **11** shows a flowchart of a method **1100** of removing a particle **801** from a pellicle **70** in accordance with another embodiment of present disclosure. It is understood that additional operations can be provided before, during, and after the processes shown by FIG. **11**, and some of the operations described below can be replaced or eliminated, for additional embodiments of the method. The order of the operations/processes may be interchangeable. Materials, configurations, methods, processes and/or dimensions as explained with respect to the foregoing embodiments are applicable to the following embodiments, and the detailed description thereof may be omitted.

[0080] At S**1101** of FIG. **11**, a location of the particle **801** on a surface of a membrane of the pellicle **70** is obtained. In some embodiments, the location of the particle **801** on the surface of the membrane of the pellicle **70** is detected by a particle detector **601** (in FIG. **6A**). In other embodiments, the location of the particle **801** on the surface of the membrane of the pellicle **70** is received from another device or system (not shown).

[0081] At S1102 of FIG. 11, a distance between the nozzle 502 and the surface of the membrane of the pellicle 70 is detected. In some embodiments, the distance between the nozzle 502 and the surface of the membrane of the pellicle 70 is detected by the distance detector 602 (in FIG. 6B). [0082] At S1103 of FIG. 11, the nozzle 502 is moved over the surface of the pellicle 70 to a place over the location of the particle 70. In some embodiments, the nozzle 502 is moved by a robot arm 504 with respect to the surface of the pellicle 70. In other embodiments, the nozzle 502 is relatively moved with respect to the surface of the pellicle 70 by moving a pellicle stage 90 that holds the pellicle 70.

[0083] At S1104 of FIG. 11, the nozzle 502 is lowered by the robot arm 504 toward the pellicle 70 until the distance between the nozzle 502 and the surface of the pellicle 70 reaches a threshold distance (f). In some embodiments, the threshold distance (f) is in a range from about 2.5 mm to about 3.5 mm.

[0084] At S1105 of FIG. 11, a droplet 803 of a cleaning liquid material is dispensed through the nozzle 502 to cover the particle 801 on the surface of the pellicle 70.

[0085] At S1106 of FIG. 11, the droplet 803 along with the particle 801 is horizontally dragged toward an edge of the membrane of the pellicle 70 by the nozzle 502 using the surface tension of the droplet 803.

[0086] At S1107 of FIG. 11, the droplet 803 and the particle 801 are removed from the edge of the membrane of the pellicle 70. In some embodiments, the droplet 803 and the particle 801 are sucked off from the edge of the membrane of the pellicle 70 by a vacuum pump 508, thereby automatically and safely removing the particle 803 without damaging the pellicle. In other embodiments, the droplet 803 and the particle 801 are blown off from the edge of the membrane of the pellicle 70 by an air blower 509 to an outside of the pellicle 70.

[0087] In some embodiments, after the droplet 803 and the particle 801 are removed, the surface of the membrane of the pellicle 70 is detected again to find any additional particles. The pellicle 70 is determined clean if no additional particles are found on surface of the pellicle 70.

[0088] In some embodiments, a contact of the droplet 803 with the nozzle 502 is monitored, and a supply of the cleaning liquid material to the nozzle 502 is controlled to maintain the contact (in FIG. 6C). When the contact is found lost or the droplet is not well-formed, additional cleaning liquid material is dispensed from the nozzle 502 to maintain the contact of the droplet 803 with the nozzle 502. Otherwise, when the contact is found remained or the droplet is well-formed, no additional cleaning liquid material is dispensed from the nozzle 502.

[0089] In some embodiments, the membrane of the pellicle 70 is detected using a pellicle damage detector 604 to find any holes therein (in FIG. 6D). The pellicle 70 is determined damaged once at least one hole is found in the pellicle 70.

[0090] FIGS. 12A and 12B illustrate an apparatus for removing particles from a pellicle of a reticle in accordance with some embodiments of the present disclosure.

[0091] FIG. 12A is a schematic view of a computer system that performs the functions of an apparatus for removing particles from the pellicle of the reticle. All of or a part of the processes, method and/or operations of the foregoing embodiments can be realized using computer hardware and computer programs executed thereon. In FIG. 12A, a computer system 1200 is provided with a computer 1201 including an optical disk read only memory (e.g., CD-ROM or DVD-ROM) drive 1205 and a magnetic disk drive 1206, a keyboard 1202, a mouse 1203, and a monitor 1204.

[0092] FIG. 12B is a diagram showing an internal configuration of the computer system 1200. In FIG. 12B, the computer 1201 is provided with, in addition to the optical disk drive 1205 and the magnetic disk drive 1206, one or more processors, such as a micro processing unit (MPU) 1211, a ROM 1212 in which a program such as a boot up program is stored, a random access memory (RAM) 1213 that is connected to the MPU 1211 and in which a command of an application program is temporarily stored and a temporary storage area is provided, a hard disk 1214 in which an application program, a system program, and data are stored, and a bus 1215 that connects the

MPU **1211**, the ROM **1212**, and the like. Note that the computer **1201** may include a network card (not shown) for providing a connection to a LAN.

[0093] The program for causing the computer system **1200** to execute the functions for removing particles from the pellicle of the reticle in the foregoing embodiments may be stored in an optical disk **1221** or a magnetic disk **1222**, which are inserted into the optical disk drive **1205** or the magnetic disk drive **1206**, and transmitted to the hard disk **1214**. Alternatively, the program may be transmitted via a network (not shown) to the computer **1201** and stored in the hard disk **1214**. At the time of execution, the program is loaded into the RAM **1213**. The program may be loaded from the optical disk **1221** or the magnetic disk **1222**, or directly from a network. The program does not necessarily have to include, for example, an operating system (OS) or a third party program to cause the computer **1201** to execute the functions of the control system for cleaning reticles and projecting layout patterns of the cleaned reticles in the foregoing embodiments. The program may only include a command portion to call an appropriate function (module) in a controlled mode and obtain desired results.

[0094] According to some embodiments of the present disclosure, a method of removing a particle from a pellicle includes: moving a nozzle over a surface of a membrane of the pellicle to a location of the particle, wherein the nozzle is in fluid connection with a supply of a liquid material; dispensing a droplet of the liquid material from the nozzle on and covering the particle; horizontally dragging the droplet and the particle toward an edge of the membrane; and sucking off the droplet and the particle by a vacuum pump from the edge of the membrane. In an embodiment, before the dispensing the droplet, the nozzle is lowered toward the surface of the membrane until a distance between the nozzle and the surface of the membrane reaching a threshold distance. In an embodiment, the threshold distance (f) is in a range from about 2.5 mm to about 3.5 mm. In an embodiment, a contact of the droplet with the nozzle is monitored, wherein when the contact is found lost, additional liquid material is dispensed from the nozzle to maintain the contact. In an embodiment, the liquid material includes an anhydrous alcohol. In an embodiment, before moving the nozzle, the location of the particle on the surface of the membrane of the pellicle is obtained. In an embodiment, the nozzle is relatively moved with respect to the surface of the membrane by moving a pellicle stage that holds the pellicle.

[0095] According to some embodiments of the present disclosure, a method of removing a particle from a pellicle includes: obtaining a location of the particle on a surface of a membrane of the pellicle; detecting a distance between a nozzle and the surface of the membrane; moving the nozzle over the surface of the membrane and to the location of the particle; lowering the nozzle toward the membrane until the distance reaching a threshold distance; dispensing a droplet of a liquid material through the nozzle to cover the particle; horizontally dragging the droplet and the particle toward an edge of the membrane by the nozzle; and removing the droplet and the particle from the edge of the membrane. In an embodiment, a contact of the droplet with the nozzle is monitored; and a supply of the liquid material to the nozzle is controlled to maintain the contact. In an embodiment, the membrane is detected to find a hole therein, wherein the pellicle is determined damaged once the hole is found. In an embodiment, the removing includes sucking off the droplet and the particle from the edge of the membrane by a vacuum pump. In an embodiment, the removing includes blowing off the droplet and the particle outside of the membrane from the edge of the membrane by an air blower. In an embodiment, the nozzle is made of a thermoplastic material, the nozzle is in a cylindrical shape, and a ratio of a wall thickness (a) of the nozzle to an inner diameter (b) of the nozzle is in a range from about 0.3 to about 0.42. In an embodiment, after the removing the droplet and the particle, the surface of the membrane is detected to find an additional particle, wherein the pellicle is determined clean if no additional particle is found.

[0096] According to some embodiments of the present disclosure, a system of removing a particle from a pellicle includes: a support stage for holding the pellicle; a nozzle to dispense a droplet of a liquid material to cover the particle on a surface of a membrane of the pellicle; a robot arm to move

the nozzle; a vacuum pump located on an edge of the membrane to suck off the droplet; a distance detector to detect a distance between the nozzle and the surface; and a processor controller coupled to the robot arm, the vacuum pump, and the distance detector, wherein the processor controller is configured to control the robot arm to horizontally move the nozzle to the location of the particle, to lower the nozzle toward the membrane until the distance reaching a threshold distance, and to horizontally drag the droplet and the particle toward the membrane edge using the nozzle; and to activate the vacuum pump to suck off the droplet and the particle from the edge of the membrane. In an embodiment, a pellicle damage detector is configured to detect the membrane to find a hole therein, wherein once the hole in the membrane is found, the pellicle is determined damaged. In an embodiment, the threshold distance is in a range from about 2.5 mm to about 3.5 mm. In an embodiment, a droplet monitor is configured to monitor a contact of the droplet with the nozzle, wherein the processor controller is configured to control a supply of the liquid material to the nozzle to maintain the contact of the droplet with the nozzle. In an embodiment, the droplet monitor includes a backlight source to emit a backlight in a direction to the droplet and parallel with the surface of the membrane; and a backlight camera to receive the backlight passing through the droplet to monitor the contact of the droplet with the nozzle. In an embodiment, the nozzle is made of a thermoplastic material, and the nozzle is a cylindrical nozzle having a wall thickness (a) greater than 1 mm and an inner diameter (b) in a range from about 3 mm to about 10 mm. [0097] The foregoing outlines features of several embodiments or examples so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments or examples introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A system of removing a particle from a pellicle, comprising: a support stage for holding the pellicle; a nozzle to dispense a droplet of a liquid material to cover the particle on a surface of a membrane of the pellicle; a robot arm to move the nozzle; a vacuum pump located on an edge of the membrane to suck off the droplet; a distance detector to detect a distance between the nozzle and the surface; and a processor controller coupled to the robot arm, the vacuum pump, and the distance detector, wherein the processor controller is configured to control the robot arm to horizontally move the nozzle to a location of the particle, to lower the nozzle toward the membrane until the distance reaches a threshold distance, and to horizontally drag the droplet and the particle toward the membrane edge using contact between the nozzle and the droplet, and to activate the vacuum pump to suck off the droplet and the particle from the edge of the membrane.
2. The system of claim 1, wherein the threshold distance is in a range from 2.5 mm to 3.5 mm.
3. The system of claim 1, further comprising a droplet monitor configured to monitor the contact of the droplet with the nozzle, wherein the processor controller is configured to control a supply of the liquid material to the nozzle to maintain the contact of the droplet with the nozzle.
4. The system of claim 3, wherein the droplet monitor comprises a backlight source to emit a backlight in a direction to the droplet and parallel with the surface of the membrane; and a backlight camera to receive the backlight passing through the droplet to monitor the contact of the droplet with the nozzle.
5. The system of claim 1, wherein the nozzle is made of a thermoplastic material, and wherein the nozzle is a cylindrical nozzle having a wall thickness greater than 1 mm and an inner diameter in a range from 3 mm to 10 mm.

6. The system of claim 1, further comprising a pellicle damage detector configured to detect the membrane to find a hole therein, wherein once the hole in the membrane is found, the pellicle is determined to be damaged.
 7. A pellicle cleaning system comprising: a stage configured to support a pellicle; a particle detector configured to detect a particle **801** on the pellicle; a liquid supply connected to a nozzle, wherein the nozzle is configured to dispense a droplet of a liquid on the particle on the pellicle; an air conveyor configured to remove the droplet and the particle from the pellicle; and a process controller programmed to: control the particle detector to detect a location of the particle on the pellicle, control a relative position between the nozzle and the stage to position the nozzle proximal to the particle on the pellicle, control the liquid supply to dispense the droplet from the nozzle onto the particle on the pellicle, control the relative position between the nozzle and the stage to drag the droplet and particle to an edge of the pellicle through contact between the nozzle and the droplet, and control the air conveyor to remove the particle from the edge of the pellicle.
 8. The pellicle cleaning system of claim 7, wherein the air conveyor is configured to blow the droplet and the particle off the pellicle.
 9. The pellicle cleaning system of claim 7, wherein the air conveyor is configured to suck the droplet and the particle off the pellicle.
 10. The pellicle cleaning system of claim 7, further comprising a droplet monitor configured to determine whether the contact between the nozzle and the droplet is maintained.
 11. The pellicle cleaning system of claim 10, wherein the process controller is further configured to adjust a supply of the liquid from the liquid supply to the nozzle to maintain contact between the nozzle and the droplet in response to a monitored contact status measured by the droplet monitor.
 12. The pellicle cleaning system of claim 7, further comprising a distance detector configured to measure a distance between a head of the nozzle and a surface of the pellicle.
 13. The pellicle cleaning system of claim 12, wherein the controller is further configured to control a movement of the head of the nozzle toward the surface of the pellicle until the distance reaches a threshold distance.
 14. The pellicle cleaning system of claim 7, further comprising a robot arm connected to the nozzle and configured to move the nozzle.
 15. The pellicle cleaning system of claim 14, wherein the process controller is further programmed to control the robot arm to adjust the relative position between the nozzle and the particle on the pellicle.
 16. A pellicle cleaning system comprising: a stage configured to support a pellicle; a nozzle configured to dispense a droplet of a liquid onto the pellicle; an air conveyor configured to remove the droplet from the pellicle; and a process controller programmed to: control a relative position between the nozzle and the stage to a location for dispensing the droplet from the nozzle onto a particle on the pellicle, control the dispensing of the droplet on the particle on the pellicle, control the relative position between the nozzle and the stage to move the droplet and particle across the pellicle with the nozzle in contact with the droplet, and control the air conveyor to remove the droplet and the particle from the pellicle.
 17. The pellicle cleaning system of claim 16, further comprising a robot arm connected to and configured to move the nozzle.
 18. The pellicle cleaning system of claim 17, wherein the process controller is further programmed to control the robot arm to adjust the relative position between the nozzle and the stage.
 19. The pellicle cleaning system of claim 16, wherein the stage is configured to move relative to the nozzle.
 20. The pellicle cleaning system of claim 19, wherein the process controller is further programmed to control a position of the stage to adjust the relative position between the nozzle and stage.
-