

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287093

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

LEE; Sihyoung

ELECTRONIC DEVICE PROVIDING FILTER FUNCTION AND OPERATION METHOD THEREOF

Abstract

An electronic device is provided. The electronic device includes a display which provides a preview, a camera including an image sensor, a memory which stores instructions, and at least one processor communicatively coupled to the display, the camera, and the memory. The instructions, when executed by the at least one processor individually or collectively, cause the electronic device to display a shooting setting including at least one first set value and a second set value through the display, change the at least one first set value which determines a shutter speed when the second set value which determines strength of a neural density (ND) filter is changed by a user input, and display the changed shooting setting through the display along with the preview.

Inventors: LEE; Sihyoung (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008629800

Appl. No.: 19/220533

Filed: May 28, 2025

Foreign Application Priority Data

KR 10-2022-0161639

Nov. 28, 2022

KR 10-2023-0001239

Jan. 04, 2023

Related U.S. Application Data

parent WO continuation PCT/KR2023/017712 20231107 PENDING child US 19220533

Publication Classification

Int. Cl.: H04N23/63 (20230101); H04N23/71 (20230101)

U.S. Cl.:

CPC H04N23/632 (20230101); H04N23/633 (20230101); H04N23/71 (20230101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) [0001] This application is a continuation application, claiming priority under 35 U.S.C. § 365 (c), of an International application No. PCT/KR2023/017712, filed on Nov. 7, 2023, which is based on and claims the benefit of a Korean patent application number 10-2022-0161639, filed on Nov. 28, 2022, in the Korean Intellectual Property Office, and of a Korean patent application number 10-2023-0001239, filed on Jan. 4, 2023, in the Korean Intellectual Property Office, the disclosure of each of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

[0002] The disclosure relates to an electronic device providing a filter function, and an operation method thereof.

2. Description of Related Art

[0003] Long exposure photos not only capture a moment but also represent a time flow. A camera may provide the long exposure photo by slowing down a shutter speed to capture a flow of light in the photo. In order to obtain the long exposure photo, a time for light to enter an image sensor shall be increased by setting the shutter speed to be slow.

[0004] When the image sensor is overexposed with the increase in the time for the light to enter the image sensor due to the slowed-down shutter speed, it is difficult to accurately capture motions in the photo. To solve this problem, a neutral density (ND) filter may be attached to a camera lens to reduce an amount of light while maintaining the shutter speed, allowing the motion in the photo to be expressed with a proper exposure.

[0005] Meanwhile, the ND filter is usually implemented as hardware mountable on the camera lens, but may also be implemented as software. If the ND filter is implemented as software, a relationship between a shooting setting (e.g., sensitivity (ISO), shutter speed) in a camera and a set value of the ND filter shall be considered in order to achieve perfection of the long exposure photo.

[0006] The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

SUMMARY

[0007] Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide a long exposure photo with high perfection without a hardware neutral density (ND) filter.

[0008] Another aspect of the disclosure is to provide software providing an ND filter function, and may provide a proper shooting setting based on set values of various ND filters.

[0009] Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

[0010] In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes a display which provides a preview, a camera including an image sensor, a memory which stores instructions, and at least one processor communicatively coupled to the

display, the camera, and the memory. The instructions, when executed by the at least one processor individually or collectively, may cause the electronic device to display a shooting setting including at least one first set value and a second set value through the display, change the at least one first set value which determines a shutter speed when the second set value which determines strength of a ND filter is changed by a user input, and display the changed shooting setting through the display along with the preview.

[0011] In accordance with another aspect of the disclosure, a method performed by an electronic device is provided. The method may include displaying a shooting setting including at least one first set value and a second set value through the display, changing the at least one first set value which determines a shutter speed when the second set value which determines strength of an ND filter is changed by a user input, and displaying the changed shooting setting through the display along with the preview.

[0012] In accordance with another aspect of the disclosure, one or more non-transitory computer-readable storage media storing one or more computer programs including computer-executable instructions that, when executed by one or more processors of an electronic device individually or collectively, cause the electronic device to perform operations are provided. The operations may include displaying a shooting setting including at least one first set value and a second set value through a display, changing the at least one first set value which determines a shutter speed when the second set value which determines strength of an ND filter is changed by a user input, and displaying the changed shooting setting through the display along with the preview.

[0013] Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

[0015] FIG. 1 is a block diagram of an electronic device in a network environment according to an embodiment of the disclosure;

[0016] FIG. 2 is a block diagram illustrating a camera module, according to an embodiment of the disclosure;

[0017] FIG. 3 is a block diagram of an electronic device according to an embodiment of the disclosure;

[0018] FIG. 4 illustrates a user interface displayed for an electronic device to provide a neutral density (ND) filter function according to an embodiment of the disclosure;

[0019] FIG. 5 is a drawing for explaining an operation of creating a long exposure image by using a short exposure image according to an embodiment of the disclosure;

[0020] FIG. 6 is a flowchart of an operation method in which an electronic device creates a long exposure photo according to an embodiment of the disclosure;

[0021] FIG. 7 is a flowchart of an operation method in which an electronic device changes a preview and a shooting setting according to an embodiment of the disclosure;

[0022] FIG. 8 is a drawing for explaining a change in brightness of the preview when strength of an ND filter is adjusted in an electronic device according to an embodiment of the disclosure;

[0023] FIG. 9 is a flowchart of an operation method in which a shooting setting and brightness of a preview change when a first set value is adjusted in an electronic device according to an embodiment of the disclosure;

[0024] FIG. **10** is a drawing to be referred to in the operation method according to FIG. **9** according to an embodiment of the disclosure;

[0025] FIG. **11** is a flowchart of an operation method in which a set value of an ND filter changes when a first set value is adjusted in an electronic device according to an embodiment of the disclosure;

[0026] FIG. **12** is a drawing to be referred to in the operation method according to FIG. **11** according to an embodiment of the disclosure;

[0027] FIG. **13** is a flowchart of an operation method in which a first set value changes when a set value of an ND filter is adjusted in an electronic device according to an embodiment of the disclosure;

[0028] FIG. **14** is a drawing to be referred to in the operation method according to FIG. **13** according to an embodiment of the disclosure;

[0029] FIG. **15** illustrates examples of a shooting setting based on whether an ND filter function is present or absent according to an embodiment of the disclosure;

[0030] FIG. **16** is a flowchart of an operation method in which a setting range of a first set value changes when a set value of an ND filter is adjusted in an electronic device according to an embodiment of the disclosure;

[0031] FIG. **17** is a drawing to be referred to in the operation method according to FIG. **16** according to an embodiment of the disclosure; and

[0032] FIG. **18** illustrates examples in which a shutter speed is restricted based on a set value of an ND filter according to an embodiment of the disclosure.

[0033] Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

DETAILED DESCRIPTION

[0034] The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

[0035] The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

[0036] It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

[0037] It should be appreciated that the blocks in each flowchart and combinations of the flowcharts may be performed by one or more computer programs which include instructions. The entirety of the one or more computer programs may be stored in a single memory device or the one or more computer programs may be divided with different portions stored in different multiple memory devices.

[0038] Any of the functions or operations described herein can be processed by one processor or a combination of processors. The one processor or the combination of processors is circuitry performing processing and includes circuitry like an application processor (AP, e.g. a central processing unit (CPU)), a communication processor (CP, e.g., a modem), a graphics processing unit (GPU), a neural processing unit (NPU) (e.g., an artificial intelligence (AI) chip), a wireless fidelity

(Wi-Fi) chip, a Bluetooth® chip, a global positioning system (GPS) chip, a near field communication (NFC) chip, connectivity chips, a sensor controller, a touch controller, a fingerprint sensor controller, a display driver integrated circuit (IC), an audio CODEC chip, a universal serial bus (USB) controller, a camera controller, an image processing IC, a microprocessor unit (MPU), a system on chip (SoC), an IC, or the like.

[0039] FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to an embodiment of the disclosure.

[0040] Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**). [0041] The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation.

According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

[0042] The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised

learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

[0043] The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

[0044] The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

[0045] The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

[0046] The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

[0047] The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

[0048] The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

[0049] The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

[0050] The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

[0051] A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

[0052] The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

[0053] The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

[0054] The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

[0055] The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

[0056] The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a fifth-generation (5G) network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

[0057] The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

[0058] The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

[0059] According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

[0060] At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

[0061] According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

[0062] The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the

disclosure, the electronic devices are not limited to those described above.

[0063] It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

[0064] As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

[0065] Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

[0066] According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

[0067] According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of

the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

[0068] FIG. 2 is a block diagram **200** illustrating the camera module **180** according to an embodiment of the disclosure. Referring to FIG. 2, the camera module **180** may include a lens assembly **210**, a flash **220**, an image sensor **230**, an image stabilizer **240**, memory **250** (e.g., buffer memory), or an image signal processor **260**. The lens assembly **210** may collect light emitted or reflected from an object whose image is to be taken. The lens assembly **210** may include one or more lenses. According to an embodiment, the camera module **180** may include a plurality of lens assemblies **210**. In such a case, the camera module **180** may form, for example, a dual camera, a 360-degree camera, or a spherical camera. Some of the plurality of lens assemblies **210** may have the same lens attribute (e.g., view angle, focal length, auto-focusing, f number, or optical zoom), or at least one lens assembly may have one or more lens attributes different from those of another lens assembly. The lens assembly **210** may include, for example, a wide-angle lens or a telephoto lens.

[0069] The flash **220** may emit light that is used to reinforce light reflected from an object. According to an embodiment, the flash **220** may include one or more light emitting diodes (LEDs) (e.g., a red-green-blue (RGB) LED, a white LED, an infrared (IR) LED, or an ultraviolet (UV) LED) or a xenon lamp. The image sensor **230** may obtain an image corresponding to an object by converting light emitted or reflected from the object and transmitted via the lens assembly **210** into an electrical signal. According to an embodiment, the image sensor **230** may include one selected from image sensors having different attributes, such as a RGB sensor, a black-and-white (BW) sensor, an IR sensor, or a UV sensor, a plurality of image sensors having the same attribute, or a plurality of image sensors having different attributes. Each image sensor included in the image sensor **230** may be implemented using, for example, a charged coupled device (CCD) sensor or a complementary metal oxide semiconductor (CMOS) sensor.

[0070] The image stabilizer **240** may move the image sensor **230** or at least one lens included in the lens assembly **210** in a particular direction, or control an operational attribute (e.g., adjust the read-out timing) of the image sensor **230** in response to the movement of the camera module **180** or the electronic device **101** including the camera module **180**. This allows compensating for at least part of a negative effect (e.g., image blurring) by the movement on an image being captured. According to an embodiment, the image stabilizer **240** may sense such a movement by the camera module **180** or the electronic device **101** using a gyro sensor (not shown) or an acceleration sensor (not shown) disposed inside or outside the camera module **180**. According to an embodiment, the image stabilizer **240** may be implemented, for example, as an optical image stabilizer.

[0071] The memory **250** may store, at least temporarily, at least part of an image obtained via the image sensor **230** for a subsequent image processing task. For example, if image capturing is delayed due to shutter lag or multiple images are quickly captured, a raw image obtained (e.g., a Bayer-patterned image, a high-resolution image) may be stored in the memory **250**, and its corresponding copy image (e.g., a low-resolution image) may be previewed via the display module **160**. Thereafter, if a specified condition is met (e.g., by a user's input or system command), at least part of the raw image stored in the memory **250** may be obtained and processed, for example, by the image signal processor **260**. According to an embodiment, the memory **250** may be configured as at least part of the memory **130** or as a separate memory that is operated independently from the memory **130**.

[0072] The image signal processor **260** may perform one or more image processing with respect to an image obtained via the image sensor **230** or an image stored in the memory **250**. The one or more image processing may include, for example, depth map generation, three-dimensional (3D) modeling, panorama generation, feature point extraction, image synthesizing, or image

compensation (e.g., noise reduction, resolution adjustment, brightness adjustment, blurring, sharpening, or softening). Additionally or alternatively, the image signal processor **260** may perform control (e.g., exposure time control or read-out timing control) with respect to at least one (e.g., the image sensor **230**) of the components included in the camera module **180**. An image processed by the image signal processor **260** may be stored back in the memory **250** for further processing, or may be provided to an external component (e.g., the memory **130**, the display module **160**, the electronic device **102**, the electronic device **104**, or the server **108**) outside the camera module **180**. According to an embodiment, the image signal processor **260** may be configured as at least part of the processor **120**, or as a separate processor that is operated independently from the processor **120**. If the image signal processor **260** is configured as a separate processor from the processor **120**, at least one image processed by the image signal processor **260** may be displayed, by the processor **120**, via the display module **160** as it is or after being further processed.

[0073] According to an embodiment, the electronic device **101** may include a plurality of camera modules **180** having different attributes or functions. In such a case, at least one of the plurality of camera modules **180** may form, for example, a wide-angle camera and at least another of the plurality of camera modules **180** may form a telephoto camera. Similarly, at least one of the plurality of camera modules **180** may form, for example, a front camera and at least another of the plurality of camera modules **180** may form a rear camera.

[0074] FIG. **3** is a block diagram of an electronic device according to an embodiment of the disclosure.

[0075] An electronic device **101** according to an embodiment may include a display **310** (e.g., the display module **160** of FIG. **1**), a camera module **320** (e.g., the camera module **180** of FIG. **2**), a memory **330** (e.g., the memory **130** of FIG. **1**, the memory **250** of FIG. **2**), and at least one processor **340** (e.g., the processor **120** of FIG. **1**). The camera module **320** according to an embodiment may include an image sensor **230** and an image signal processor (ISP) **260**. FIG. **3** is for explaining an embodiment, and some components of FIG. **3** may be omitted or replaced with other components.

[0076] The electronic device **101** according to an embodiment may execute a camera application for capturing an image. The camera application may support not only a basic mode in which all shooting settings are automatically determined based on a shooting environment but also a pro mode (or a manual mode) in which the shooting setting may be determined by a user setting. The electronic device **101** according to an embodiment may provide an interface capable of selecting strength (or a filter coefficient) of a neutral density (ND) filter in the pro mode along with intensity (ISO) of the image sensor **230**, a shutter speed, and an exposure value (EV).

[0077] The electronic device **101** according to an embodiment may determine brightness of a preview and/or a system shooting time, based on the strength of the ND filter.

[0078] FIG. **4** illustrates a user interface displayed for an electronic device to provide an ND filter function according to an embodiment of the disclosure.

[0079] The electronic device **101** may obtain a plurality of short exposure images in a state where a shutter speed is set to be long (slow) and synthesize the plurality of short exposure images to obtain a long exposure image. The electronic device **101** has difficulty in obtaining the long exposure image in a relatively bright environment due to an excessive amount of light entering the image sensor **230**. In this case, an ND filter may be used to adjust the amount of light in the bright environment. The ND filter mentioned herein is a physical device mountable on the electronic device **101**, and shall be provided by a user separately from the electronic device **101**.

[0080] Since the electronic device **101** is equipped with separate software capable of performing the ND filter function in the disclosure, the user may obtain the long exposure image in the bright environment without having to provide the separate physical device.

[0081] Referring to FIG. **4**, the electronic device **101** according to an embodiment may provide a

second set value **164** capable of selecting strength of the ND filter in a user interface provided when a shooting mode is executed. The shooting mode may be a pro mode (or a manual mode) in which not all shooting modes are determined automatically based on a shooting environment. [0082] The electronic device **101** according to an embodiment may provide a shooting setting **165** including the second set value **164** capable of selecting strength (or a filter coefficient) of the ND filter in the pro mode along with sensitivity (ISO) **161** of the image sensor **230**, a shutter speed **162**, an EV **163**. In addition to the aforementioned functions, the shooting setting **165** may include items such as a focus-auto function and a white balance (WB) function.

[0083] The electronic device **101** according to an embodiment may display a preview **169** on a real-time basis by using the display module **160** (see FIG. 1) along with the shooting setting **165**. The preview may be displayed on the display module **160** with a change on a real-time basis according to the shooting setting **165**. For example, brightness of the preview **169** may be determined based on the EV **163**.

[0084] The electronic device **101** according to an embodiment may display the second set value **164** as a numerical value corresponding to the strength of the ND filter through the display module **160**. For example, the user may select any one of ND2, and ND4 to ND8 as the second set value **164** through the user interface. The greater the numerical value of the second set value **164**, the more the light to be blocked may be. In an embodiment, the second set value **164** is not limited to the aforementioned example, and may include various numerical values (e.g., ND512, ND1000).

[0085] When the shutter speed is 1 second in a bright shooting environment, an image to be output as the preview may be oversaturated due to a high EV. In this case, when the second set value **164** proposed in the disclosure is set to a great value through a user input, the image to be output as the preview may be prevented from the oversaturation. In this case, not only a setting of a preview system which determines brightness of the preview but also a setting of a shooting system may be changed.

[0086] Meanwhile, in order to obtain a long exposure image, the electronic device **101** creates a plurality of short exposure images by varying a user-set shooting time and a system shooting time. In this case, another shooting set value (e.g., ISO) other than the user-set shooting time may be changed and used to obtain the short exposure image.

[0087] FIG. 5 is a drawing for explaining an operation of creating a long exposure image by using a short exposure image according to an embodiment of the disclosure.

[0088] For example, when an ND filter (a physical filter) is not mounted on a camera, a magnitude of an electronic signal converted using the image sensor **230** (see FIG. 3) may correspond to a sum of an area of a first region **51** and an area of a second region **52**. In this case, when the ND filter is mounted to reduce an amount of light irradiated to the image sensor **230** by half, the magnitude of the electric signal converted using the image sensor **230** may correspond to the area of the second region **52**.

[0089] Meanwhile, in an embodiment, the electronic device may use an ND filter algorithm instead of using the physical ND filter, thereby having an effect of substantially increasing an exposure time.

[0090] In an embodiment, the processor **120** may set a user-set shooting time which is a shutter speed, and a system shooting time, which is an exposure time for obtaining a short exposure image so as to be different from each other, and may synthesize the short exposure image obtained based on the system shooting time. A method of synthesizing the short exposure image may be roughly classified into two methods.

[0091] Referring to FIG. 5, in part (5-A), a long exposure image is created based on an average of a plurality of short exposure images. In part (5-B), the long exposure image is created based on a sum for the plurality of short exposure images. In parts (5-A) and (5-B), an area per bar corresponds to the magnitude of the electronic signal converted by the image sensor **230**.

[0092] In part (5-A), the area per bar corresponds to an area of the second region **52**. This is

because, when an image is obtained through a change in another shooting set value (e.g., ISO) other than the user-set shooting time, brightness of an image created in a state where a system shooting time is set to be short may be equal to brightness of an image created through the user-set shooting time.

[0093] In order to obtain the long exposure image according to part (5-A), a synthesis algorithm for motion, brightness, or the like may be added based on a method in which an average on pixel values of respective short exposure images is calculated, and all of the calculated average values are summed up.

[0094] In part (5-B), a sum of areas of three bars corresponds to a width of the second region 52. In order to obtain the long exposure image according to part (5-B), the synthesis algorithm for motion, brightness, or the like may be added based on a method in which pixel values of respective short exposure images are all summed up.

[0095] The processor **120** according to an embodiment may obtain a pixel value of a long exposure image, based on one of an average value, maximum value, minimum value, and mode value of pixels included in the respective short exposure images.

[0096] That is, the electronic device according to an embodiment may obtain a plurality of short exposure images during a user-set time (e.g., a shutter speed) and synthesize the obtained plurality of short exposure images, thereby providing a long exposure effect.

[0097] In order to obtain the long exposure image, the processor **120** according to an embodiment may use shake information of the electronic device **101** (see FIG. **1**) and/or motion information of an object.

[0098] The electronic device **101** according to an embodiment may obtain the shake information of the electronic device **101**. For example, as the shake information, the electronic device **101** may obtain user's heartbeat information, user's breathing information, and/or 3-dimensional acceleration information of the electronic device **101** while the plurality of short exposure images are obtained. The shake information may be used to select at least some of the plurality of short exposure images used to obtain the long exposure image. For example, the electronic device **101** may select a short exposure image obtained in a section in which a change in the user's heartbeat or breathing is less than or equal to a specific value. According to another example, the electronic device **101** may select a short exposure image obtained in a section in which a 3-dimensional acceleration value of the electronic device is less than or equal to a specific value. According to another example, the electronic device **101** may select at least some of the plurality of short exposure images by using an artificial intelligence model, based on the shake information.

[0099] When at least one of a plurality of short exposure images is selected based on the shake information of the electronic device, the processor **120** according to an embodiment may obtain motion information of an object included in the at least one short exposure image. The processor **120** may perform interpolation between the short exposure images, based on the motion information of the object. The processor **120** may synthesize the short exposure image subjected to the interpolation and the other short exposure images to obtain a long exposure image.

[0100] FIG. **6** is a flowchart **600** of an operation method in which the electronic device **101** (see FIG. **1**) creates a long exposure photo according to an embodiment of the disclosure.

[0101] In operation **601**, a pro mode is executed in the electronic device **101** according to an embodiment through user selection. The pro mode is one of shooting modes in which the electronic device **101** captures an image, and may provide a user interface which allows a user to directly select various shooting settings (e.g., sensitivity, shutter speed, etc.).

[0102] In operation **602**, the electronic device **101** according to an embodiment may display the shooting setting through the display module **160**. The shooting setting may provide the shooting setting **165** including the second set value capable of selecting strength (or a filter coefficient) of the ND filter along with the first set value including the ISO **161** of the image sensor, the shutter speed **162**, and the EV **163**. In addition to the aforementioned functions, the shooting setting may

include items such as a focus-auto function and a WB function (see FIG. 4).

[0103] In operation **603**, the electronic device **101** according to an embodiment detects whether the shooting setting is changed by the user input.

[0104] When it is detected that the shooting setting is changed by the user input, in operation **604**, the electronic device **101** according to an embodiment may change the shooting setting and update a range. Herein, the range refers to a selection range of a shooting item selectable by the user among the remaining shooting items when any one of items of the shooting setting is changed by the user input. This will be described below with reference to FIGS. **16** and **17**.

[0105] When there is no change in the shooting setting, the electronic device **101** according to an embodiment may determine a setting of a shooting system, based on the previously displayed shooting setting.

[0106] In operation **605**, the electronic device **101** according to an embodiment determines the setting of the shooting system. The shooting system may determine an exposure time, sensitivity (ISO), or the like of a short exposure image so that the electronic device **101** obtains a long exposure image. In addition, the shooting system may determine a shooting count of the short exposure image to obtain the long exposure image. The shooting system may determine the exposure time and/or the ISO and/or the shooting count, based on a shooting environment and/or strength of an ND filter selected by the user. When the user determines a user-set shooting time (shutter speed), the shooting system may determine an exposure time for obtaining the short exposure image in consideration of the shooting environment. The exposure time is a system shooting time. In order to perform an ND filter function, the system shooting time is set to a shorter time than a user-set shooting time. If the ND filter function is not enabled, the system shooting time may be equal to the user-set shooting time.

[0107] In operation **606**, the electronic device **101** according to an embodiment performs shooting in response to a user input. In operation **607**, the electronic device **101** according to an embodiment applies an ND filter algorithm. The ND filter algorithm includes an operation of determining a shooting count and exposure time of the short exposure image by the shooting system. The shooting count and the exposure time may be determined based on a shooting environment of the electronic device **101**.

[0108] In operation **608**, the electronic device **101** according to an embodiment creates a long exposure photo (a long exposure image). The electronic device **101** may synthesize a plurality of short exposure images created in the operation **607** to create the long exposure image. The long exposure images may be synthesized in reference to parts (5-A) and (5-B) described in FIG. 5.

[0109] Meanwhile, apart from creating and storing the long exposure image, the electronic device may determine brightness of a preview, based on the strength of the ND filter selected by the user. For example, when the user changes the shooting setting irrespective of the exposure time determined by the shooting system, the electronic device **101** may determine the brightness of the preview, based on values for the changed shooting setting. An embodiment for adjusting the brightness of the preview will be described with reference to FIG. 7.

[0110] FIG. 7 is a flowchart **700** of an operation method in which an electronic device changes a preview and a shooting setting according to an embodiment of the disclosure.

[0111] In the embodiment, the preview is a preview image which shows a long exposure image to be created by an ND filter algorithm, and may be displayed along with the shooting setting through the display module **160**. However, the preview may not be the same as the long exposure image or a short exposure image. A user may predict what kind of long exposure image will be output through the preview, or may verify only a brightness difference between a shooting setting currently being output and a changed shooting setting through the preview.

[0112] The shooting setting provided along with the preview may be any one of a shooting setting previously set by the user and a value obtained by analyzing a current shooting environment.

[0113] In operation **701**, the electronic device **101** according to an embodiment may obtain an EV.

For example, the EV is a value specified by a combination of a shutter speed, ISO, or the like (an aperture value), and may represent brightness of a resultant object captured through the camera module **180**. A process of calculating the EV may refer to a standard for additive system of photographic exposure (APEX), and a detailed description thereof will be omitted since it is a previously announced method. The EV may be calculated based on brightness of an image consequently obtained by an actual user through the entire value of the shooting setting.

[0114] In operation **702**, the electronic device **101** according to an embodiment may select the shooting setting to be applied to the preview, and may determine a value thereof. For example, assuming that the shutter speed, the sensitivity, and the strength of the ND filter are the entire shooting setting of the electronic device **101**, the shutter speed and the sensitivity may be selected to obtain the preview, and the shutter speed and the sensitivity value may be determined by considering the calculated EV.

[0115] In addition, in response to changing the shooting setting by the user, the electronic device **101** according to an embodiment may transfer to a preview system a shooting set value changed by the user.

[0116] In operation **703**, the electronic device **101** according to an embodiment may transfer to the preview system the selected (or changed) shooting set value. The preview system determines brightness of the preview which is output on the display module **160** on a real-time basis, and is not involved in an exposure time and shooting count determined by a shooting system.

[0117] In operation **704**, the electronic device **101** according to an embodiment may determine whether there is a need to adjust the brightness of the preview.

[0118] If the EV obtained in operation **701** and an image obtained in the preview system are different in brightness (Yes in the operation **704**), the electronic device **101** according to an embodiment may adjust the brightness of the preview through image processing in operation **705**.

[0119] If there is no brightness difference between the EV obtained in operation **701** and the image obtained in the preview system and thus it is not necessary to adjust the brightness of the preview (No in the operation **704**), the electronic device **101** according to an embodiment may display, without alternation, the existing preview and the existing shooting setting.

[0120] If the strength of the ND filter is adjusted by a user input in a state where a setting option for the shutter speed and sensitivity is the auto mode, it is not necessary to adjust the brightness of the preview since the EV is automatically set to 0. On the contrary, when the strength of the ND filter is adjusted by the user input in a state where the setting option for the shutter speed and sensitivity is the manual mode, the brightness of the preview may be changed. For example, when the user increases the strength of the ND filter, the preview becomes relatively dark. When the strength of the ND filter is increased, the shooting settings of the shooting system may be suitable for obtaining a long exposure image, but may not be suitable for the user to identify an image on a real-time basis through the preview. Therefore, when there is a great difference between the shooting setting of the shooting system and the shooting setting of the preview system, the electronic device **101** according to the embodiment may automatically change the shooting setting (shutter speed and/or sensitivity) of the preview system, or may adjust the brightness of the preview itself through image processing.

[0121] When the shooting mode is the pro mode and the EV is defined in the range of -2.0 to $+2.0$, a most suitable EV may correspond to 0. For example, when the shutter speed is set to $1/100$ and the sensitivity is set to 100, the EV may be $+1.0$. When the EV is $+1.0$, the preview displayed on the display module **160** may have relatively high brightness. In this case, the preview system may automatically change the shooting setting, or may adjust only the brightness of the preview without alternation of the shooting setting.

[0122] When there is a need to adjust the brightness of the preview, the electronic device **101** according to an embodiment may automatically change the shooting setting. For example, the electronic device **101** may change the shutter speed to $1/50$ (the sensitivity is 100 without change),

or may change the sensitivity to 200 (the shutter speed is 1/100 without change), in a state where the EV is +1 (shutter speed: 1/100, sensitivity: 100).

[0123] When there is a need to adjust the brightness of the preview, the electronic device **101** according to an embodiment may change the brightness of the preview itself. The electronic device **101** according to the embodiment may adjust the brightness itself of the image recognized by the user through image processing, without alternation of the shooting setting.

[0124] If shooting set values of the shooting system are equal to shooting set values of the preview system, the electronic device **101** may not adjust the brightness of the preview.

[0125] In operation **706**, the electronic device **101** according to an embodiment displays the preview and the (changed) shooting setting through the display module **160**.

[0126] When at least one first set value including the shutter speed (and/or sensitivity) is changed by the user input, the electronic device **101** according to an embodiment may obtain the EV, and may adjust the brightness of the preview, based on the EV and a second set value which is the strength of the ND filter.

[0127] FIG. **8** is a drawing for explaining a change in brightness of the preview **169** when strength of an ND filter is adjusted in an electronic device according to an embodiment of the disclosure.

[0128] Part (8-A) of FIG. **8** shows a state where a user adjusts a shutter speed, sensitivity, and strength of the ND filter, and thus an Exposure value (EV) becomes 0. In an embodiment, a maximum value of the strength (the second set value **164**) which may be selected by the user through the electronic device **101** (see FIG. **1**) may be restricted to 1000. The electronic device **101** may automatically change the EV and/or brightness of the preview **169** whenever there is a change in the strength of the ND filter.

[0129] Part (8-B) of FIG. **8** shows a state where the user increases the strength of the ND filter by double through the electronic device **101**. Since only the strength of the ND filter increases from 256 to 512 in a state where a value (a shutter speed and sensitivity) for another shooting setting is fixed, the EV is calculated to be -1.0, and it is shown that the brightness of the preview **169** is darker compared to (8-A).

[0130] FIG. **9** is a flowchart **900** of an operation method in which a shooting setting and brightness of a preview change when a first set value is adjusted in an electronic device according to an embodiment of the disclosure. FIG. **10** is a drawing to be referred to in the operation method according to FIG. **9** according to an embodiment of the disclosure.

[0131] In operation **901**, the electronic device **101** according to an embodiment displays a shooting setting through the display module **160**. Referring to part (10-A) of FIG. **10** together, it is a state where the shutter speed **162** is set to 1 in the shooting setting of the electronic device **101**. In this case, the electronic device **101** may calculate an EV to be 0, based on at least one of a shutter speed value of 1, a sensitivity value of 100, and an ND filter strength of 128, and may display the EV through the display module **160** (see FIG. **1**).

[0132] In operation **902**, the shutter speed (or sensitivity) of the electronic device **101** according to an embodiment may be changed by a user input. Referring to parts (10-A) and (10-B) of FIG. **10**, it is a state where the shutter speed has been changed from 1 to 4 by the user input.

[0133] In operation **903**, the electronic device **101** according to an embodiment adjusts brightness of a preview. Due to an increase in the shutter speed by 4 times, the EV **163** is determined to be +2. The electronic device **101** may adjust the brightness of the preview according to the EV, based on a shooting set value and/or image processing.

[0134] In operation **904**, the electronic device **101** according to an embodiment displays the adjusted preview and the changed shooting setting. Referring to part (10-B) of FIG. **10**, the brightness of the preview **169** is adjusted to be brighter than that in part (10-A) of FIG. **10** since the EV **163** is determined to be +2. The brightness of the preview **169** according to FIG. **10** may be rendered with reference to the process of FIG. **7**.

[0135] FIG. **11** is a flowchart **1100** of an operation method in which a set value of an ND filter

changes when a first set value is adjusted in an electronic device according to an embodiment of the disclosure. FIG. 12 is a drawing to be referred to in the operation method according to FIG. 11 according to an embodiment of the disclosure.

[0136] In operation **1101**, the electronic device **101** according to an embodiment displays a shooting setting through the display module **160**. Referring to part (12-A) of FIG. 12 together, it is a state where the shutter speed **162** is set to 1 in the shooting setting of the electronic device **101**. In this case, the electronic device **101** may calculate an EV to be 0, based on a shutter speed value of 1 and a sensitivity value of 100, and may display the EV through the display module **160** (see FIG. 1).

[0137] In operation **1102**, the shutter speed (or sensitivity) of the electronic device **101** according to an embodiment may be changed by a user input. Referring to parts (12-A) and (12-B) of FIG. 12, it is a state where the shutter speed has been changed from 1 to 4 by the user input. Considering only an increase in the shutter speed **162**, the preview **169** will become relatively bright.

[0138] In an embodiment according to FIG. 12, there is no change in the brightness of the preview **169** even if the shutter speed is increased by the user input unlike in FIG. 10 described above. The brightness of the preview **169** does not change because the electronic device **101** according to an embodiment automatically changes the set value **164** of the ND filter in accordance with the change in the shutter speed in operation **1103**. Referring to parts (12-A) and (12-B) of FIG. 12, the electronic device **101** may change the set value **164** of the ND filter from 128 to 512 in compensation for maintaining a proper EV even if the shutter speed increases.

[0139] In operation **1104**, the electronic device **101** according to an embodiment displays the changed set value of the ND filter through the display module **160**.

[0140] To summarize an embodiment according to FIG. 11, in order to properly maintain the brightness and/or EV of the preview, the electronic device **101** automatically changes the set value of the ND filter in accordance with a change in the shutter speed (or sensitivity) by a user input.

[0141] The electronic device **101** according to an embodiment may automatically change the second set value which determines the strength of the ND filter, when at least one first set value which determines the shutter speed (and/or sensitivity) is changed by the user input. The electronic device **101** may display the shooting setting including the changed first and second set values through the display module **160** along with the preview.

[0142] As described above, the brightness of the preview may vary based on the set value of the ND filter in addition to the shutter speed or the sensitivity. This will be described with reference to FIGS. 13 and 14.

[0143] FIG. 13 is a flowchart **1300** of an operation method in which a first set value changes when a set value of an ND filter is adjusted in an electronic device according to an embodiment of the disclosure. FIG. 14 is a drawing to be referred to in the operation method according to FIG. 13 according to an embodiment of the disclosure.

[0144] In operation **1301**, the electronic device **101** according to an embodiment displays a shooting setting through the display module **160**. Referring to part (14-A) of FIG. 14 together, it is a state where the shutter speed **162** is set to $\frac{1}{8}$ in the shooting setting of the electronic device **101**. In this case, the electronic device **101** may calculate an EV to be 0, based on a shutter speed value of $\frac{1}{8}$ and a sensitivity value of 50, and may display the EV through the display module **160** (see FIG. 1).

[0145] In operation **1302**, the set value **164** of the ND filter of the electronic device **101** according to an embodiment may be changed by a user input. Referring to parts (14-A) and (14-B) of FIG. 14, it is a state where the set value of the ND filter has been changed from 512 to 256. Considering only a decrease in the set value **164**, the preview **169** will become relatively bright.

[0146] In operation **1303**, in an embodiment according to FIG. 14, there is no change in the brightness of the preview **169** even if the set value **164** of the ND filter is changed by the user input similarly to FIG. 12 described above. The brightness of the preview **169** does not change because

the electronic device **101** according to an embodiment automatically changes the set value of the shutter speed (or sensitivity) in accordance with the change in the set value **164** of the ND filter in the operation **1303**. Referring to parts **(14-A)** and **(14-B)** of FIG. **14**, the electronic device **101** may change the set value of the shutter speed **162** from $\frac{1}{8}$ to $\frac{1}{16}$ in compensation for maintaining a proper EV even if the set value **164** of the ND filter decreases.

[0147] In operation **1304**, the electronic device **101** according to an embodiment displays the changed shooting setting through the display module **160**. For example, the electronic device **101** changes the set value of the shutter speed (or sensitivity) when the set value of the ND filter is changed by the user input, and displays the changed set value through the display module **160** so as to be recognizable by the user.

[0148] When a setting option for a first set value which determines the shutter speed and/or the sensitivity is set to an auto mode, the electronic device **101** according to an embodiment may automatically change the first set value in response to changing the set value of the ND filter by the user input. The electronic device **101** may automatically adjust the shutter speed and/or the sensitivity in order to compensate for the change in the set value of the ND filter to maintain the EV at a proper level of 0. Since the electronic device **101** always maintains the EV at **0**, the brightness of the preview **169** remains to be the same.

[0149] The electronic device **101** according to an embodiment may automatically change at least one first set value which determines the shutter speed (and/or sensitivity), when a second set value which determines the strength of the ND filter is changed by the user input. The electronic device **101** may display the shooting setting including the changed first and second set values through the display module **160** along with the preview.

[0150] The electronic device **101** according to an embodiment may increase the set value of the shutter speed in response to changing the second set value which determines the strength of the ND filter by the user input, and may decrease the set value of the shutter speed in response to decreasing the second set value by the user input.

[0151] FIG. **15** illustrates examples of a shooting setting based on whether an ND filter function is present or absent according to an embodiment of the disclosure.

[0152] It is shown in FIG. **15** that a long exposure time (a shutter speed) may be secured in the shooting environment (the same brightness) as the existing environment, by adjusting strength of an ND filter.

[0153] Part **(15-A)** of FIG. **15** shows a case where an EV is 0, when a shutter speed is $\frac{1}{500}$ and ISO is 50, as a default initial value of a shooting setting. However, each of numerical values of FIG. **15** is only one example for facilitating understanding, and it is obvious that more various numerical values may be used based on various specifications of the electronic device **101**.

[0154] Part **(15-B)** of FIG. **15** shows that the EV decreases to -1, -2, or -3, when the strength of the ND filter increases to 2, 4, or 8 in a state where the shutter speed and the ISO are fixed. That is, the EV decreases in proportion to an increase in the strength of the ND filter in the state where the shutter speed and the ISO are fixed.

[0155] Referring to part **(15-C)** of FIG. **15**, it is shown that the EV is 0 when the electronic device **101** increases the shutter speed by double for a proper exposure in part **(15-B)** of FIG. **15**. The disclosure allows a user to obtain an optimal long exposure image through such interaction. For example, the EV may be maintained at **0** to induce an increase in the shutter speed, and an exposure time of a shooting system may be secured to be longer than the existing one.

[0156] Meanwhile, various embodiments described with reference to FIGS. **11** to **15** may automatically adjust the set value of the ND filter in response to changing the shutter speed (and/or sensitivity) by the user input, or may automatically adjust the set value of the shutter speed (and/or sensitivity) in response to changing the set value of the ND filter by the user input. The electronic device **101** may automatically change each set value in an auto mode or a manual mode.

[0157] When the setting option for the set value is the manual mode, the electronic device **101** may

provide a selection range so that the user selects a specific set value. For example, the electronic device **101** may provide a selection range of a shutter speed having an interval of 1/12000 to 30 in the manual mode. In addition, the electronic device **101** may provide a selection range of a shutter speed having an interval of 50 to 3200 in the manual mode. In addition, the electronic device **101** may provide a selection range for strength of an ND filter having an interval of 1 to 1000 in the manual mode.

[0158] When the selection range for the set value is provided in the manual mode, the electronic device **101** may provide a selection range for another set value variably by considering any one set value selected in advance so that the user obtains a long exposure photo, based on a proper exposure time. A specific process is described with reference to FIGS. **16** and **17**.

[0159] FIG. **16** is a flowchart **1600** of an operation method in which a setting range of a first set value changes when a set value of an ND filter is adjusted in an electronic device according to an embodiment of the disclosure. FIG. **17** is a drawing to be referred to in the operation method according to FIG. **16** according to an embodiment of the disclosure.

[0160] In operation **1601**, the electronic device **101** according to an embodiment displays a shooting setting through the display module **160**. In the embodiment, the electronic device **101** displays a selection range for the shutter speed through the display module **160** along with the shooting setting. Referring to part (17-A) of FIG. **17**, a first selection range **1620-1** of the shutter speed **162** is displayed on the display module **160** along with the shooting setting. The first selection range **1602-1** includes a plurality of selection values.

[0161] For example, $\frac{1}{8}$, $\frac{1}{4}$, $\frac{1}{2}$, 1, and 2 are provided in the first selection range **1620-1** of the shutter speed of part (17-A) of FIG. **17** as the plurality of selection values. The first selection range **1620-1** may include the plurality of selection values for the shutter speed so that a proper exposure time is determined when the set value **164** of the ND filter is 1000.

[0162] In operation **1602**, the set value **164** of the ND filter of the electronic device **101** according to an embodiment may be changed by a user input. Referring to parts (17-A) and (17-B) of FIG. **17**, it is a state where the set value of the ND filter has been changed from 1000 to 512. The change in the set value of the ND filter results in a change in an EV from 0 to +1.0. Brightness of the preview **169** may be adjusted in response to determining the EV **163** to be +1.0. In operation **1603**, the electronic device **101** according to an embodiment may change a selection range of a shutter speed (and/or sensitivity) (see operation **1603**). The change in the selection range is based on the change in the set value of the ND filter in the operation **1602**. Referring to parts (17-A) and (17-B) of FIG. **17**, it is shown that the selection range of the shutter speed changes from a first selection range **1620-1** to a second selection range **1620-2** with a change in the set value of the ND filter from 1000 to 512. When the set value of the ND filter is 1000, a minimum selection value of the shutter speed selectable by the user is $\frac{1}{8}$, whereas with the change in the set value of the ND filter to 512, the minimum selection value of the shutter speed selectable by the user is $\frac{1}{16}$, which shows that the selection range is further widened.

[0163] In operation **1604**, the electronic device **101** according to an embodiment displays the changed selection range through the display. For example, in response to changing the set value of the ND filter, the electronic device **101** according to an embodiment may change the selection range of the shutter speed from the first selection range **1620-1** to the second selection range **1620-2**. The electronic device **101** according to an embodiment may be configured to, when a second set value which is the strength of the ND filter is first strength, display a first selection range corresponding to the first set value on the display module **160** in response to detecting a user input for selecting at least one first set value including the shutter speed (and/or sensitivity), detect a change in the second set value from the first strength to second strength by the user input, and when the second set value is the second strength, display a second selection range corresponding to the first set value on the display module **160** in response to detecting the user input for selecting the first set value.

[0164] An embodiment described with reference to FIGS. **16** and **17** refers to an operation in which the selection range of the shutter speed (and/or shutter) changes based on a change in the set value of the ND filter. However, according to the same principle, the selection range of the ND filter may change based on a change in the set value of the shutter speed (and/or sensitivity).

[0165] The electronic device **101** according to an embodiment may be configured to, when the at least one first set value including the shutter speed (and/or sensitivity) is a first value, display the first strength selection range corresponding to the second set value on the display module **160** in response to detecting a user input for selecting the second set value which is the strength of the ND filter, detect a change in the first set value from the first value to a second value by the user input, and when the first set value is the second value, display a second strength selection range corresponding to the second set value on the display module **160** in response to detecting the user input for selecting the second set value.

[0166] FIG. **18** illustrates examples in which a shutter speed is restricted based on a set value of an ND filter according to an embodiment of the disclosure.

[0167] FIG. **18** shows a level of restricting an exposure time (the shutter speed) which is one of shooting settings selectable by a user according to the set value (strength) of the ND filter. When an ND filter function is not enabled, a minimum value of an exposure time provided by a shooting system of the electronic device **101** is 1/8000. That is, a minimum value of a shutter speed selectable by the user in a state where the ND filter function is not enabled is 1/8000. In this case, when the user sets the shutter speed to 1/8000, the shooting system also sets the exposure time to 1/8000 to obtain an image.

[0168] Unlike this, in the state where the ND filter function is enabled, the shutter speed set by the user and the exposure time determined by the shooting system are different from each other. For example, when the user sets the strength of the ND filter to 2, the minimum value of the shutter speed selectable by the user changes from 1/8000 to 1/4000, thereby decreasing a range of the shutter speed selectable by the user.

[0169] The electronic device **101** according to an embodiment decreases the range of the shutter speed selectable by the user in proportion to an increase in the strength of the ND filter. When the strength of the ND filter has a value other than 0, the electronic device **101** sets the exposure time (the shutter speed) set by the user and the exposure time determined by the shooting system to be different from each other since a plurality of images with a shorter time than the exposure time (the shutter speed) set by the user shall be obtained and synthesized.

[0170] For example, when the user is allowed to set the strength of the ND filter to 2 and to select the shutter speed to 1/8000, the shooting system has to use an exposure time shorter than 1/8000 to obtain at least two images, which is beyond a limit of the shooting system (a minimum exposure time of the shooting system: 1/8000). Therefore, the electronic device **101** according to the embodiment may induce the user to obtain an optimal long exposure image by restricting the range of the shutter speed provided to the user.

[0171] When the user sets the strength of the ND filter to a great value, it is predictable that a selection range of the shutter speed selectable by the user is decreased. If the user intends to change a set value of the ND filter to further increase the shutter speed, the electronic device **101** may automatically disable the ND filter function.

[0172] The electronic device **101** according to an embodiment determines the exposure time of the shooting system, based on the shutter speed and the strength of the ND filter. When a difference between the minimum value of the exposure time and the minimum value of the shutter speed is greater than or equal to a predetermined numerical value, the electronic device **101** may restrict a change in the second set value which is the strength of the ND filter.

[0173] Additionally, the electronic device **101** may further include an illumination detection module (e.g., the sensor module **176** of FIG. **1**) to automatically enable the function of the ND filter in consideration of an ambient environment of the electronic device **101**. According to an

embodiment, the electronic device **101** may further include the illumination detection module which outputs a signal for measuring ambient brightness. In addition, the aforementioned illumination detection module may be implemented by analyzing an image obtained from the image sensor through the first set value. The electronic device **101** may adaptively display the second set value which is the strength of the ND filter on the display module **160**, based on the signal obtained from the illumination sensor. For example, the electronic device **101** may display the second set value through the display module **160** only when the illumination is greater than or equal to a pre-set value.

[0174] An electronic device (e.g., the electronic device **101** of FIGS. **1** and **3**) according to an embodiment may include a display (e.g., the display module **160** of FIG. **1**, the display **310** of FIG. **3**) which provides a preview, a camera (e.g., the camera module **180** of FIGS. **1** and **2**) including an image sensor (e.g., the image sensor **230** of FIGS. **2** and **3**), a memory (e.g., the memory **130** of FIG. **1**, the memory **250** of FIG. **2**, the memory **330** of FIG. **3**) which stores instructions, and at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**).

[0175] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may execute instructions stored in the memory (e.g., the memory **130** of FIG. **1**, the memory **250** of FIG. **2**, the memory **330** of FIG. **3**).

[0176] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may display a shooting setting including at least one first set value and a second set value through the display (e.g., the display module **160** of FIG. **1**, the display **310** of FIG. **3**).

[0177] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may change the at least one first set value which determines a shutter speed when the second set value which determines strength of a ND filter is changed by a user input.

[0178] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may display the changed shooting setting through the display (e.g., the display module **160** of FIG. **1**, the display **310** of FIG. **3**) along with the preview.

[0179] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may change the second set value when the at least one first set value is changed by the user input.

[0180] The at least one first set value of the electronic device (e.g., the electronic device **101** of FIGS. **1** and **3**) according to an embodiment may include the shutter speed and sensitivity (ISO) of the image sensor.

[0181] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may determine an exposure value, based on the shutter speed and the sensitivity, and may display the exposure value through the display (e.g., the display module **160** of FIG. **1**, the display **310** of FIG. **3**).

[0182] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may obtain the exposure value when the at least one first set value is changed by the user input, and may adjust brightness of the preview, based on the exposure value and the second set value.

[0183] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may increase a set value of the shutter speed when the second set value increases based on the user input, and may decrease the set value of the shutter speed when the second set value decreases based on the user input.

[0184] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may be configured to, when the second set value is first strength, display a first selection range corresponding to the first set value on the display in response to detecting a user input for selecting the first set value, detect that the second set value is changed

from the first strength to second strength by the user input, and when the second set value is the second strength, display a second selection range corresponding to the first set value on the display (e.g., the display module **160** of FIG. **1**, the display **310** of FIG. **3**) in response to detecting the user input for selecting the first set value.

[0185] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may be configured to, when the first set value is a first value, display a first strength selection range corresponding to the second set value on the display in response to detecting a user input for selecting the second set value, detect that the first set value is changed from the first value to a second value by the user input, and when the first set value is the second value, display a second strength selection range corresponding to the second set value on the display (e.g., the display module **160** of FIG. **1**, the display **310** of FIG. **3**) in response to detecting the user input for selecting the second set value.

[0186] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may determine an exposure time of a shooting system, based on the shutter speed and the strength of the ND filter.

[0187] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may restrict a change in the second set value, when a difference between a minimum value of the exposure time and a minimum value of the shutter speed is greater than or equal to a predetermined numerical value.

[0188] The electronic device (e.g., the electronic device **101** of FIGS. **1** and **3**) according to an embodiment may further include an illumination sensor which outputs a signal for measuring illumination around the electronic device.

[0189] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may display the second set value adaptively on the display (e.g., the display module **160** of FIG. **1**, the display **310** of FIG. **3**), based on a signal obtained from the illumination sensor.

[0190] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may determine an exposure time of a shooting system, based on the strength of the ND filter selected based on the user input, and may obtain a plurality of short exposure images, based on the exposure time and the shutter speed selected based on the user input.

[0191] The at least one processor (e.g., the processor **120** of FIG. **1**, the processor **340** of FIG. **3**) according to an embodiment may align the plurality of short exposure images, based on shake information of the electronic device (e.g., the electronic device **101** of FIGS. **1** and **3**) and/or motion information of an object included in the short exposure image, and may obtain a long exposure image by synthesizing the aligned plurality of short exposure images.

[0192] Advantages acquired in the disclosure are not limited to the aforementioned advantages, and other advantages not mentioned herein may be clearly understood by those skilled in the art to which the disclosure pertains from the following descriptions.

[0193] Methods based on the embodiments disclosed in the claims and/or specification of the disclosure may be implemented in hardware, software, or a combination of both.

[0194] When implemented in software, a computer readable recording medium for storing one or more programs (i.e., software modules) may be provided. The one or more programs stored in the computer readable recording medium are configured for execution performed by one or more processors in the electronic device. The one or more programs include instructions for allowing the electronic device to execute the methods based on the embodiments disclosed in the claims and/or specification of the disclosure.

[0195] In the disclosure, programs (e.g., software modules or software) may be stored in a random access memory and/or a non-volatile memory including a flash memory, a read only memory (ROM), an electrically erasable programmable read only memory (EEPROM), a magnetic disc storage device, a compact disc-ROM (CD-ROM), digital versatile discs (DVDs), other forms of

optical storage devices, or a magnetic cassette. Alternatively, the programs may be stored in a memory configured in combination of all or some of these storage media. The memory may be constructed of a single storage medium or a combination of a plurality of storage media. The at least one instruction may be stored in the single storage medium, or may be stored in the plurality of storage media in a distributed manner.

[0196] Further, the program may be stored in an attachable storage device capable of accessing the electronic device through a communication network such as the Internet, an Intranet, a local area network (LAN), a wide LAN (WLAN), or a storage area network (SAN) or a communication network configured by combining the networks. The storage device may have access to a device for performing an embodiment of the disclosure via an external port. In addition, an additional storage device on a communication network may have access to the device for performing the embodiment of the disclosure.

[0197] In the aforementioned specific embodiments of the disclosure, a component included in the disclosure is expressed in a singular or plural form according to the specific embodiment proposed herein. However, the singular or plural expression is selected properly for a situation proposed for the convenience of explanation, and thus the various embodiments of the disclosure are not limited to a single or a plurality of components. Therefore, a component expressed in a plural form may also be expressed in a singular form, or vice versa.

[0198] In addition, in the disclosure, the term “unit”, “module”, or the like may be a hardware component such as a processor or a circuit, and/or a software component executed by the hardware component such as the processor.

[0199] The “unit” and the “module” may be implemented by a program stored in an addressable storage medium and executable by the processor. For example, the “unit” and “module” may be implemented by software components, object-oriented software components, class components, and task components, processes, functions, attributes, procedures, subroutines, segments of program code, drivers, firmware, microcode, circuitry, data, databases, data structures, tables, arrays, and variables.

[0200] Specific implementations described in the disclosure are only one embodiment, and do not limit the scope of the disclosure in any way. For brevity of the specification, descriptions on the conventional electronic components, control systems, software, and other functional aspects of the systems may be omitted.

[0201] In addition, in the disclosure, “including at least one of a, b, or c” may mean “including only a”, “including only b”, “including only c”, “including a and b”, “including b and c”, “including a and c”, or “including a, b, and c”.

[0202] While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. An electronic device comprising: a display which provides a preview; a camera including an image sensor; a memory which stores instructions; and at least one processor communicatively coupled to the display, the camera, and the memory, wherein the instructions, when executed by the at least one processor individually or collectively, cause the electronic device to: display a shooting setting including at least one first set value and a second set value through the display, change the at least one first set value which determines a shutter speed when the second set value which determines strength of a neural density (ND) filter is changed by a user input, and display the changed shooting setting through the display along with the preview.
2. The electronic device of claim 1, wherein the instructions, when executed by the at least one

processor individually or collectively, further cause the electronic device to: change the second set value when the at least one first set value is changed by the user input.

3. The electronic device of claim 1, wherein the at least one first set value includes the shutter speed and sensitivity (ISO) of the image sensor, and wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: determine an exposure value, based on the shutter speed and the sensitivity, and display the exposure value through the display.

4. The electronic device of claim 3, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: obtain the exposure value when the at least one first set value is changed by the user input, and adjust brightness of the preview, based on the exposure value and the second set value.

5. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: increase a set value of the shutter speed when the second set value increases based on the user input, and decrease the set value of the shutter speed when the second set value decreases based on the user input.

6. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: when the second set value is first strength, display a first selection range corresponding to the first set value on the display in response to detecting a user input for selecting the first set value, detect that the second set value is changed from the first strength to second strength by the user input, and when the second set value is the second strength, display a second selection range corresponding to the first set value on the display in response to detecting the user input for selecting the first set value.

7. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: when the first set value is a first value, display a first strength selection range corresponding to the second set value on the display in response to detecting a user input for selecting the second set value, detect that the first set value is changed from the first value to a second value by the user input, and when the first set value is the second value, display a second strength selection range corresponding to the second set value on the display in response to detecting the user input for selecting the second set value.

8. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: determine an exposure time of a shooting system, based on the shutter speed and the strength of the ND filter, and restrict a change in the second set value, when a difference between a minimum value of the exposure time and a minimum value of the shutter speed is greater than or equal to a predetermined numerical value.

9. The electronic device of claim 1, further comprising: an illumination sensor which outputs a signal for measuring illumination around the electronic device, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: display the second set value adaptively on the display, based on a signal obtained from the illumination sensor.

10. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: determine an exposure time of a shooting system, based on the strength of the ND filter selected based on the user input, and obtain a plurality of short exposure images, based on the exposure time and the shutter speed selected based on the user input.

11. The electronic device of claim 10, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: align the plurality of short exposure images, based on at least one of shake information of the electronic device or motion information of an object included in the short exposure images, and obtain a long exposure image by synthesizing the aligned plurality of short exposure images.

- 12.** A method performed by an electronic device, the method comprising: displaying a shooting setting including at least one first set value and a second set value through a display of the electronic device; changing the at least one first set value which determines a shutter speed when the second set value which determines strength of a neural density (ND) filter is changed by a user input; and displaying the changed shooting setting through the display along with a preview.
- 13.** The method of claim 12, further comprising: changing the second set value when the at least one first set value is changed by the user input.
- 14.** The method of claim 12, wherein the at least one first set value includes the shutter speed and sensitivity (ISO) of an image sensor of the electronic device, and wherein the method further comprises: determining an exposure value, based on the shutter speed and the sensitivity; and displaying the exposure value through the display.
- 15.** The method of claim 14, further comprising: obtaining the exposure value when the at least one first set value is changed by the user input; and adjusting brightness of the preview, based on the exposure value and the second set value.
- 16.** The method of claim 12, further comprising: increasing a set value of the shutter speed when the second set value increases based on the user input; and decreasing the set value of the shutter speed when the second set value decreases based on the user input.
- 17.** The method of claim 12, further comprising: when the second set value is first strength, displaying a first selection range corresponding to the first set value on the display in response to detecting a user input for selecting the first set value; detecting that the second set value is changed from the first strength to second strength by the user input; and when the second set value is the second strength, displaying a second selection range corresponding to the first set value on the display in response to detecting the user input for selecting the first set value.
- 18.** The method of claim 12, further comprising: when the first set value is a first value, displaying a first strength selection range corresponding to the second set value on the display in response to detecting a user input for selecting the second set value; detecting that the first set value is changed from the first value to a second value by the user input; and when the first set value is the second value, displaying a second strength selection range corresponding to the second set value on the display in response to detecting the user input for selecting the second set value.
- 19.** The method of claim 12, further comprising: determining an exposure time of a shooting system, based on the shutter speed and the strength of the ND filter; and restricting a change in the second set value, when a difference between a minimum value of the exposure time and a minimum value of the shutter speed is greater than or equal to a predetermined numerical value.
- 20.** The method of claim 12, wherein the electronic device further includes an illumination sensor which outputs a signal for measuring illumination around the electronic device, and wherein the method further comprises: displaying the second set value adaptively on the display, based on a signal obtained from the illumination sensor.
-