

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276740

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

INOUE; Shigeyuki et al.

VEHICLE LOWER STRUCTURE

Abstract

A vehicle lower structure includes a pair of vehicle body frame members, an intermediate member at least a portion of which is disposed between the pair of vehicle body frame members, a power storage device disposed below the intermediate member, a seat disposed above the intermediate member, and a reinforcing member disposed inside the intermediate member or on an upper surface of the intermediate member, wherein the vehicle lower structure has a region in which the reinforcing member is not provided below the seat in a vehicle up/down direction.

Inventors: INOUE; Shigeyuki (Toyota-shi, JP), KAWAMOTO; Naoya (Nisshin-shi, JP), SAKURABA; Takahito (Seto-shi, JP), KAKISHITA; Kenichi (Nagoya-shi, JP), TAKASE; Kohei (Susono-shi, JP), MIYAMURA; Kai (Toyota-shi, JP), KUMAZAWA; Kazuya (Nagoya-shi, JP)

Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota-shi, JP)

Family ID: 96738328

Assignee: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota-shi, JP)

Appl. No.: 19/052629

Filed: February 13, 2025

Foreign Application Priority Data

JP	2024-031449	Mar. 01, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: B62D25/20 (20060101); B60K1/04 (20190101)

U.S. Cl.:

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This nonprovisional application is based on Japanese Patent Application No. 2024-031449 filed on Mar. 1, 2024 with the Japan Patent Office, the entire contents of which are hereby incorporated by reference.

BACKGROUND

Field

[0002] The present disclosure relates to a vehicle lower structure.

Description of the Background Art

[0003] As disclosed in Japanese Patent Laying-Open No. 2020-142589, it is required to ensure rigidity of a vehicle lower structure, and to suppress an increase in weight of the vehicle lower structure as much as possible.

SUMMARY

[0004] An object of the present disclosure is to provide a vehicle lower structure that can ensure rigidity of the vehicle lower structure and suppress an increase in weight of the vehicle lower structure.

[0005] A vehicle lower structure in the present disclosure includes a pair of vehicle body frame members, a first intermediate member at least a portion of which is disposed between the pair of vehicle body frame members, a power storage device disposed below the first intermediate member, a first seat disposed above the first intermediate member, and a first reinforcing member disposed inside the first intermediate member or on an upper surface of the first intermediate member, wherein the vehicle lower structure has a region in which the first reinforcing member is not provided below the first seat in a vehicle up/down direction.

[0006] According to the above configuration, even if rigidity of only the first intermediate member is insufficient to receive a load, the presence of the first reinforcing member allows the first intermediate member and the first reinforcing member to cooperate to receive the load of an occupant, and it is possible to ensure rigidity by the presence of the first reinforcing member, and to suppress an increase in weight of the vehicle lower structure by the presence of the region in which the first reinforcing member is not provided below the first seat in the vehicle up/down direction.

[0007] In the above disclosure, the vehicle lower structure may include a lower frame including a pair of side members, a front member connecting front portions of the pair of side members, a rear member connecting rear portions of the pair of side members, and a cross member connecting intermediate portions of the pair of side members in a vehicle front/rear direction, wherein the pair of vehicle body frame members may be any two members selected from the pair of side members, the front member, and the cross member; the first intermediate member may be disposed to fill a space formed by the pair of side members, the front member, and the cross member, inside these members; the first reinforcing member may have a first support region; and when a first right reference line and a first left reference line extending in the vehicle front/rear direction along a right end portion and a left end portion of the first seat in a vehicle width direction are defined respectively, and the first support region is projected upward in a vertical direction, a first projection image formed by projection thereof may be located on a front side relative to a front end portion of the first seat, and may be located between the first right reference line and the first left reference line.

[0008] According to the above configuration, the first intermediate member can be disposed without any gap in a space formed by a plurality of members among the pair of side members, the

front member, the cross member, and the rear member, inside the plurality of members.

[0009] In the above disclosure, the first reinforcing member may be provided to extend from the front member toward a rear side in the vehicle front/rear direction.

[0010] According to the above configuration, since the first reinforcing member is bonded to the front member, the first reinforcing member can resist a greater load.

[0011] In the above disclosure, the lower frame may include a plurality of the cross members; the vehicle lower structure may further include a second intermediate member disposed to fill a space formed by the pair of side members and the plurality of the cross members, inside these members; the power storage device may be disposed below both the first intermediate member and the second intermediate member; the vehicle lower structure may further include a second seat, and a second reinforcing member disposed inside the second intermediate member or on an upper surface of the second intermediate member; the second reinforcing member may have a second support region; and when a second right reference line and a second left reference line extending in the vehicle front/rear direction along a right end portion and a left end portion of the second seat in the vehicle width direction are defined respectively, and the second support region is projected upward in the vertical direction, a second projection image formed by projection thereof may be located on a front side relative to a front end portion of the second seat, and may be located between the second right reference line and the second left reference line.

[0012] According to the above configuration, even if rigidity of only the second intermediate member is insufficient to receive a load, the presence of the second reinforcing member allows the second intermediate member and the second reinforcing member to cooperate to receive the load of an occupant, and it is possible to ensure rigidity by the presence of the second reinforcing member, and to suppress an increase in the weight of the vehicle lower structure.

[0013] In the above configuration, the second reinforcing member may be provided to extend from any of the plurality of the cross members toward a front side or a rear side in the vehicle front/rear direction.

[0014] According to the above configuration, since the second reinforcing member is bonded to the cross member, the second reinforcing member can resist a greater load.

[0015] In the above configuration, the power storage device may include a power storage module including a plurality of power storage cells arranged in a horizontal direction, a case having a top plate and a bottom plate and accommodating the power storage module, and a rigid board disposed between the top plate and the power storage module, and when the first reinforcing member is projected downward in the vertical direction, at least a portion of a third projection image formed by projection thereof may be located not to overlap the rigid board.

[0016] According to the above configuration, the fact that the third projection image of the first reinforcing member is located not to overlap the rigid board means that the rigid board is not present at that location. Even if there is a portion where the rigid board is not present as described above, rigidity can be ensured by the presence of the first reinforcing member. Since the presence of the rigid board is omitted, the vehicle lower structure can be manufactured at a lower cost correspondingly.

[0017] In the above configuration, the power storage device may further include a cushion member disposed between the top plate and the power storage module, and at least a portion of the third projection image may be located to overlap the cushion member.

[0018] According to the above configuration, even if there is a portion where the rigid board is not present as described above, the cushion member is present to fill such a portion. The cushion member can be constituted by a member which is less expensive than the rigid board and an adhesive, and in that case, the vehicle lower structure can be manufactured at a lower cost.

[0019] In the above configuration, the rigid board may have an underlying portion underlying the third projection image, the underlying portion of the rigid board may not be bonded to the top plate, and at least a portion of the rigid board other than the underlying portion may be bonded to the top

plate.

[0020] According to the above configuration, since the adhesive is not present between the underlying portion of the rigid board and the top plate, the vehicle lower structure can be manufactured at a lower cost correspondingly. Further, in a non-bonded range of the underlying portion, a space is formed, because the adhesive is not present. When a load is inputted from an upper surface side of a floor, the floor is deformed, the intermediate member and the like are also deformed, and thereafter the top plate is also deformed. By absorbing (stroking) displacement associated with such deformation in the space, input of the load to the rigid board can be reduced.

[0021] In the above disclosure, the rigid board may have an underlying portion underlying the third projection image, the underlying portion of the rigid board may be bonded to the top plate, and at least a portion of the rigid board other than the underlying portion may not be bonded to the top plate.

[0022] Also according to the above configuration, since the adhesive is not present, the vehicle lower structure can be manufactured at a lower cost correspondingly. Further, since the underlying portion is likely to be located under the occupant's feet, the rigid board can be reinforced by bonding the underlying portion of the rigid board to the top plate. On the other hand, a portion of the rigid board not underlying the third projection image (a non-underlying portion) below the seat is less likely to directly receive a load generated when the occupant taps his or her foot. Therefore, by not bonding the non-underlying portion of the rigid board to the top plate, a space is formed at this position, and this space can absorb variation in vertical position between the cross member and the like and the power storage device and displacement due to relative vibration.

[0023] The foregoing and other objects, features, aspects and advantages of the present disclosure will become more apparent from the following detailed description of the present disclosure when taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] FIG. 1 is a side view showing a vehicle 1 including a vehicle lower structure 10 in a first embodiment.

[0025] FIG. 2 is a plan view showing a vehicle compartment 13 and vehicle lower structure 10 of vehicle 1 in the first embodiment.

[0026] FIG. 3 is a cross sectional view of vehicle lower structure 10 in the first embodiment as viewed from a front side of vehicle 1, which corresponds to a cross sectional view taken along a line III-III in FIG. 4 and viewed in a direction indicated by arrows.

[0027] FIG. 4 is a cross sectional view of vehicle lower structure 10 in the first embodiment as viewed from a left side of vehicle 1, which corresponds to a cross sectional view taken along a line IV-IV in FIG. 3 and viewed in a direction indicated by arrows.

[0028] FIG. 5 is an enlarged view of a portion in FIG. 4.

[0029] FIG. 6 is an exploded cross sectional view of vehicle lower structure 10 in the first embodiment, which corresponds to FIG. 4.

[0030] FIG. 7 is an exploded perspective view of vehicle lower structure 10 in the first embodiment.

[0031] FIG. 8 is a cross sectional view showing a vehicle lower structure 10A in a second embodiment, which corresponds to FIG. 5 in the first embodiment.

[0032] FIG. 9 is a cross sectional view showing a vehicle lower structure 10B in a third embodiment, which corresponds to FIG. 5 in the first embodiment.

[0033] FIG. 10 is a cross sectional view showing a vehicle lower structure 10C in a fourth embodiment, which corresponds to FIG. 5 in the first embodiment.

[0034] FIG. **11** is a cross sectional view showing a vehicle lower structure **10D** in a fifth embodiment, which corresponds to FIG. **5** in the first embodiment.

[0035] FIG. **12** is a cross sectional view showing a vehicle lower structure **10E** in a sixth embodiment, which corresponds to FIG. **5** in the first embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0036] Hereinafter, embodiments of the present disclosure will be described. When the number, amount, or the like is mentioned in the embodiments described below, the scope of the present disclosure is not necessarily limited to that number, amount, or the like unless otherwise specified. Each component is not necessarily essential to the present disclosure unless otherwise specified. The same parts and corresponding parts will be designated by the same reference numerals, and the same description may not be repeated.

[0037] Arrows F, B, U, D, L, and R in the drawings used in the following description indicate directions with respect to a vehicle, and arrow F indicates a “forward direction”, arrow B indicates a “backward direction”, arrow U indicates an “upward direction”, arrow D indicates a “downward direction”, arrow L indicates a “left direction”, and arrow R indicates a “right direction”.

First Embodiment

(Vehicle **1**)

[0038] Referring to FIGS. **1** to **7**, a vehicle **1** including a vehicle lower structure **10** in a first embodiment will be described. FIG. **1** is a side view showing vehicle **1**, and FIG. **2** is a plan view showing a vehicle compartment **13** and vehicle lower structure **10** of vehicle **1**.

[0039] Vehicle **1** is, for example, an electrically powered vehicle such as an electric vehicle or a hybrid vehicle that can be driven by a motor. Vehicle **1** includes vehicle compartment **13** and vehicle lower structure **10**.

(Vehicle Lower Structure **10**)

[0040] FIG. **3** is a cross sectional view of vehicle lower structure **10** as viewed from a front side of vehicle **1**, which corresponds to a cross sectional view taken along a line III-III in FIG. **4** and viewed in a direction indicated by arrows. FIG. **4** is a cross sectional view of vehicle lower structure **10** as viewed from a left side of vehicle **1**, which corresponds to a cross sectional view taken along a line IV-IV in FIG. **3** and viewed in a direction indicated by arrows. FIG. **5** is an enlarged view of a portion in FIG. **4**. FIG. **6** is an exploded cross sectional view of vehicle lower structure **10**, which corresponds to FIG. **4**. FIG. **7** is an exploded perspective view of vehicle lower structure **10**.

[0041] As shown in FIGS. **3** to **7** (in particular, FIGS. **6** and **7**), vehicle lower structure **10** includes seats **11** and **12** in which occupants can sit, a floor carpet **14**, intermediate members **21** to **23**, reinforcing members **31** and **32**, a lower frame **15**, and a power storage device **40**.

(Lower Frame **15**)

[0042] Lower frame **15** (FIG. **7**) includes a pair of side members **16L** and **16R**, a front member **16F**, a rear member **16B**, and cross members **17** and **18**. Front member **16F** extends in a vehicle width direction and connects front portions of the pair of side members **16L** and **16R**. Rear member **16B** extends in the vehicle width direction and connects rear portions of the pair of side members **16L** and **16R**. Each of cross members **17** and **18** also extends in the vehicle width direction and connects intermediate portions of the pair of side members **16L** and **16R** in a vehicle front/rear direction.

[0043] In the present embodiment, vehicle lower structure **10** includes a pair of vehicle body frame members, and at least a portion of intermediate member **21** (a first intermediate member) described later is disposed between the pair of vehicle body frame members. For example, the pair of vehicle body frame members may be any two members selected from the pair of side members **16L** and **16R**, front member **16F**, and cross member **17**. In the present embodiment, the pair of side members **16L** and **16R**, front member **16F**, and cross member **17** are disposed in a rectangular frame shape, and a space SP1 (FIGS. **6** and **7**) is formed inside these members. Similarly, the pair of side members **16L** and **16R** and cross members **17** and **18** are disposed in a rectangular frame

shape, and a space SP2 is formed inside these members.

[0044] The pair of side members **16L** and **16R**, cross member **18**, and rear member **16B** are disposed in a rectangular frame shape, and a space SP3 is formed inside these members. Vehicle lower structure **10** is not provided with a member generally called a floor panel or the like, which is constituted by a metal steel plate or the like. Vehicle lower structure **10** penetrates through spaces SP1, SP2, and SP3 in an up/down direction at portions where spaces SP1, SP2, and SP3 are provided.

(Intermediate Members **21** to **23**)

[0045] Intermediate member **21** (the first intermediate member), intermediate member **22** (a second intermediate member), and intermediate member **23** are constituted by members including a foamed resin, for example, and each have a block-like shape. Seats **11** described later are disposed above intermediate member **21**. Intermediate members **21** to **23** can be constituted by members that are lighter than metal and softer than metal. Intermediate members **21** to **23** have substantially the same sizes and shapes as those of spaces SP1, SP2, and SP3, respectively. Intermediate members **21** to **23** are disposed to fill spaces SP1, SP2, and SP3, respectively (FIGS. 6 and 7).

(Floor Carpet **14**)

[0046] Floor carpet **14** is a member forming a portion of vehicle compartment **13** above floor carpet **14**. As shown in FIGS. 1 and 2, a pair of seats **11** (first seats) are disposed to be arranged in a right/left direction at positions above floor carpet **14** (positions above intermediate member **21**) inside vehicle compartment **13**, and seat **12** (a second seat) is disposed behind the seats.

[0047] As shown in FIG. 6, floor carpet **14** is disposed above intermediate members **21** to **23**. Floor carpet **14** may be disposed to directly contact upper surfaces **21U**, **22U**, and **23U** of intermediate members **21**, **22**, and **23**. Between floor carpet **14** and intermediate members **21** to **23**, a fixture for preventing movement of floor carpet **14**, a structure for preventing slippage (a hook-and-loop fastener), or the like may be provided as appropriate. Although floor carpet **14** is constituted by one member in vehicle **1** in the present embodiment, floor carpet **14** may be constituted by a plurality of members.

(Power Storage Device **40**)

[0048] As shown in FIGS. 3 to 6, power storage device **40** is disposed below intermediate members **21** to **23**. Power storage device **40** (FIG. 3) includes a power storage module **41** and a case **42**. Power storage module **41** includes a plurality of power storage cells **41C** accommodated by case **42** and arranged in a horizontal direction. Power storage cell **41C** is configured to include a battery that stores electric power to be supplied to the motor. The plurality of power storage cells **41C** may be stacked in the vehicle width direction, or may be stacked in the vehicle front/rear direction.

[0049] Case **42** (FIG. 3) has a top plate **43**, an adhesive **44**, side walls **45**, inner walls **46**, a support member **47**, and a bottom plate **48**. Top plate **43**, a pair of side walls **45**, and bottom plate **48** are made of FRP, for example, these members constitute an outer structure of case **42**, and adhesive **44**, inner walls **46** and support member **47**, and power storage module **41** are disposed in this structure.

[0050] Power storage module **41** (each of the plurality of power storage cells **41C**) is bonded to top plate **43** with adhesive **44**. Inner walls **46** are disposed on both outer sides of power storage module **41** (the plurality of power storage cells **41C**) in a stacking direction. Support member **47** has a plate-like shape, and is disposed between power storage module **41** and bottom plate **48**. Each inner wall **46** is integrated with top plate **43** by a fixture **61**, and is integrated with bottom plate **48** by a fixture **62**.

[0051] Power storage device **40** configured as described above is fastened to, for example, side members **16L** and **16R** of lower frame **15**, by a plurality of fasteners **63** (FIG. 3). Thereby, power storage device **40** is supported by lower frame **15**. Seals **51** and **52** (FIGS. 4 and 6) may be disposed between power storage device **40** (top plate **43**) and lower frame **15** (front member **16F**, side member **16R**).

[0052] As shown in FIG. 6, power storage device **40** is disposed below intermediate members **21** to

23. Power storage device **40** (top plate **43**) may be disposed to directly contact lower surfaces **21D**, **22D**, and **23D** of intermediate members **21**, **22**, and **23** (see also FIG. 3).

(Reinforcing Members **31** and **32**)

[0053] Reinforcing members **31** and **32** are constituted by members having rigidity higher than that of intermediate members **21** to **23**, for example, such as GFRP or metal. In vehicle lower structure **10**, reinforcing members **31** (first reinforcing members) and reinforcing member **32** (a second reinforcing member) each having a plate shape are used. Here, reinforcing members **31** are disposed on upper surface **21U** of intermediate member **21**, and reinforcing member **32** is disposed on upper surface **22U** of intermediate member **22**.

[0054] Reinforcing member **31** is provided to extend from front member **16F** toward a rear side in the vehicle front/rear direction. Reinforcing member **31** may be detachably or non-detachably bonded to front member **16F**. Here, reinforcing members **31** and **32** are disposed to extend in a plane direction including the vehicle width direction and a vehicle right/left direction.

[0055] Vehicle lower structure **10** in the present embodiment is characterized by having a region in which reinforcing member **31** is not provided below seat **11** in a vehicle up/down direction. For example, even when seat **11** is projected downward in a vertical direction, a projection image thereof does not overlap reinforcing member **31**. Further, for example, even when seat **12** is projected downward in the vertical direction, a projection image thereof does not overlap reinforcing member **32**.

(Support Region **31A**)

[0056] For example, reinforcing member **31** has a support region **31A** (a first support region). Support region **31A** is defined as follows. That is, as shown in FIG. 2, a right reference line **11RC** (a first right reference line) and a left reference line **11LC** (a first left reference line) extending in the vehicle front/rear direction along a right end portion **11R** and a left end portion **11L** of seat **11** in the vehicle width direction are defined respectively. Further, as shown in FIGS. 2 and 5, when support region **31A** of reinforcing member **31** is projected upward in the vertical direction, a first projection image **31M** is formed by projection thereof. First projection image **31M** is located on a front side relative to a front end portion **11T** of seat **11**, and is located between right reference line **11RC** and left reference line **11LC**. Reinforcing member **31** has support region **31A** defined as described above.

Functions and Effects

[0057] As described above, vehicle lower structure **10** is not provided with a member generally called a floor panel or the like, which is constituted by a metal steel plate or the like. Support region **31A** of reinforcing member **31** is a region that is likely to receive a load of an occupant sitting in seat **11**. Even if the rigidity of only intermediate member **21** is insufficient to receive the load, the presence of reinforcing member **31** allows intermediate member **21** and reinforcing member **31** to cooperate to receive the load of the occupant. That is, according to vehicle lower structure **10** in the first embodiment, it is possible to ensure rigidity by the presence of reinforcing member **31**, and to suppress an increase in weight of vehicle lower structure **10** by the presence of the region in which reinforcing member **31** is not provided below seat **11** in the vehicle up/down direction.

[0058] Further, reinforcing member **31** may have at least support region **31A** defined as described above. With such a configuration, it is possible to ensure rigidity and to suppress an increase in the weight of vehicle lower structure **10**.

[0059] In the first embodiment described above, reinforcing member **31** is provided to extend from front member **16F** toward the rear side in the vehicle front/rear direction. Reinforcing member **31** is not limited to being disposed on upper surface **21U** of intermediate member **21**, and may be disposed to be embedded in intermediate member **21**. Further, reinforcing member **31** may be provided at a position spaced apart from front member **16F**. Reinforcing member **31** may be provided to straddle side members **16L** and **16R**, for example. At least a portion of intermediate

member **21** may be disposed between the pair of vehicle body frame members, and the pair of vehicle body frame members may be any two members selected from the pair of side members **16L** and **16R**, front member **16F**, and cross member **17**. When reinforcing member **31** is bonded to front member **16F** and side members **16L** and **16R**, reinforcing member **31** can resist a greater load.

(Reinforcing Member **32**)

[0060] Referring to FIGS. **2** and **5**, here, reinforcing member **32** is provided to extend from cross member **17** toward the rear side in the vehicle front/rear direction. Reinforcing member **32** may be detachably or non-detachably bonded to cross member **17**.

[0061] Reinforcing member **32** has a support region **32A** (a second support region). Support region **32A** is defined as follows. That is, as shown in FIG. **2**, a right reference line **12RC** (a second right reference line) and a left reference line **12LC** (a second left reference line) extending in the vehicle front/rear direction along a right end portion **12R** and a left end portion **12L** of seat **12** in the vehicle width direction are defined respectively. Further, as shown in FIGS. **2** and **5**, when support region **32A** of reinforcing member **32** is projected upward in the vertical direction, a second projection image **32M** is formed by projection thereof. Second projection image **32M** is located on a front side relative to a front end portion **12T** of seat **12**, and is located between right reference line **12RC** and left reference line **12LC**. Reinforcing member **32** has support region **32A** defined as described above.

[0062] Support region **32A** of reinforcing member **32** is a region that is likely to receive a load of an occupant sitting in seat **12**. Even if the rigidity of only intermediate member **22** is insufficient to receive the load, the presence of reinforcing member **32** allows intermediate member **22** and reinforcing member **32** to cooperate to receive the load of the occupant. That is, according to vehicle lower structure **10** in the first embodiment, it is possible to ensure rigidity by the presence of reinforcing member **32**, and to suppress an increase in the weight of vehicle lower structure **10**.

[0063] Reinforcing member **32** is satisfactory as long as it has at least support region **32A** defined as described above. With such a configuration, it is possible to ensure rigidity and to suppress an increase in the weight of vehicle lower structure **10**.

[0064] In the first embodiment described above, reinforcing member **32** is provided to extend from cross member **17** toward the rear side in the vehicle front/rear direction. Reinforcing member **32** is not limited to being disposed on upper surface **22U** of intermediate member **22**, and may be disposed to be embedded in intermediate member **22**. Further, reinforcing member **32** may be provided at a position spaced apart from cross member **17**. Reinforcing member **32** may be provided to straddle side members **16L** and **16R**, for example. Reinforcing member **32** may be provided to extend from cross member **18** toward the front side in the vehicle front/rear direction, and when cross member **18** is not provided, reinforcing member **32** may be provided to extend from rear member **16B** toward the front side in the vehicle front/rear direction. When reinforcing member **32** is bonded to these members, reinforcing member **32** can resist a greater load.

Second Embodiment

[0065] FIG. **8** is a cross sectional view showing a vehicle lower structure **10A** in a second embodiment, which corresponds to FIG. **5** in the first embodiment.

[0066] In the first embodiment described above, the entire upper surface of reinforcing member **31** constitutes support region **31A**, and first projection image **31M** formed by projection of support region **31A** is located on the front side relative to front end portion **11T** of seat **11**, and is located between right reference line **11RC** and left reference line **11LC**.

[0067] In the second embodiment, a portion of the upper surface of reinforcing member **31** constitutes support region **31A**. In other words, support region **31A** corresponds to a region corresponding to a portion located on the front side relative to front end portion **11T** of seat **11** and located between right reference line **11RC** and left reference line **11LC** when the upper surface of reinforcing member **31** is projected in the same manner as that described above. Also with such a configuration, the same functions and effects as those in the first embodiment can be obtained.

[0068] Similarly, in the second embodiment, a portion of an upper surface of reinforcing member **32** constitutes support region **32A**. In other words, support region **32A** corresponds to a region corresponding to a portion located on the front side relative to front end portion **12T** of seat **12** and located between right reference line **12RC** and left reference line **12LC** when the upper surface of reinforcing member **32** is projected in the same manner as that described above. Also with such a configuration, the same functions and effects as those in the first embodiment can be obtained.

Third Embodiment

[0069] FIG. **9** is a cross sectional view showing a vehicle lower structure **10B** in a third embodiment, which corresponds to FIG. **5** in the first embodiment.

[0070] In vehicle lower structure **10B**, power storage device **40** further includes a rigid board **70**. Rigid board **70** can function as a reinforcing member for top plate **43** constituting case **42** of power storage device **40**. Rigid board **70** is satisfactory when it is configured to have a material or a structure having strength higher than that of top plate **43**, for example. In the present embodiment, rigid board **70** has a plurality of board pieces **71** to **73**, and each of the plurality of board pieces **71** to **73** is disposed between top plate **43** and power storage module **41**.

[0071] Here, when reinforcing member **31** is projected downward in the vertical direction, at least a portion of a third projection image **31N** formed by projection thereof is located not to overlap rigid board **70** (that is, the plurality of board pieces **71** to **73**). Similarly, when reinforcing member **32** is projected downward in the vertical direction, at least a portion of a third projection image **32N** formed by projection thereof is located not to overlap rigid board **70** (that is, the plurality of board pieces **71** to **73**).

[0072] The fact that third projection images **31N** and **32N** of reinforcing members **31** and **32** are located not to overlap rigid board **70** means that rigid board **70** is not present at those locations. Even if there is a portion where rigid board **70** is not present as described above, rigidity can be ensured by the presence of reinforcing members **31** and **32**. Since the presence of rigid board **70** is omitted, the vehicle lower structure can be manufactured at a lower cost correspondingly.

Fourth Embodiment

[0073] FIG. **10** is a cross sectional view showing a vehicle lower structure **10C** in a fourth embodiment, which corresponds to FIG. **5** in the first embodiment. The fourth embodiment can be implemented as a modification of the third embodiment described above.

[0074] In vehicle lower structure **10C**, power storage device **40** further includes cushion members **81** and **82**. Cushion members **81** and **82** are disposed between top plate **43** and power storage module **41**. When reinforcing members **31** and **32** are projected downward in the vertical direction, at least portions of third projection images **31N** and **32N** formed by projection thereof are located to overlap cushion members **81** and **82**.

[0075] Even if there is a portion where rigid board **70** is not present as described above in the third embodiment described above, cushion members **81** and **82** are present to fill such a portion. Cushion members **81** and **82** are satisfactory when they are constituted by members which are less expensive than rigid board **70** and adhesive **44**, for example. According to such a configuration, the vehicle lower structure can be manufactured at a lower cost.

Fifth Embodiment

[0076] FIG. **11** is a cross sectional view showing a vehicle lower structure **10D** in a fifth embodiment, which corresponds to FIG. **5** in the first embodiment. The fifth embodiment can be implemented as a modification of the third embodiment described above.

[0077] In vehicle lower structure **10D**, rigid board **70** has underlying portions **70P** underlying third projection images **31N** and **32N**, and non-underlying portions **70W** not underlying third projection images **31N** and **32N**. That is, when reinforcing members **31** and **32** are projected downward in the vertical direction, third projection images **31N** and **32N** formed by projection thereof are located to overlap underlying portions **70P** of rigid board **70**.

[0078] Here, underlying portion **70P** of rigid board **70** is not bonded to top plate **43**, and as shown

in FIG. 11, adhesive 44 is not present between underlying portion 70P of rigid board 70 and top plate 43. On the other hand, at least a portion of rigid board 70 other than underlying portion 70P (non-underlying portion 70W) is bonded to top plate 43. In the present embodiment, substantially entire rigid board 70 other than underlying portions 70P is bonded to top plate 43. Since adhesive 44 is not present between underlying portion 70P of rigid board 70 and top plate 43, the vehicle lower structure can be manufactured at a lower cost correspondingly.

[0079] Further, in a non-bonded range of underlying portion 70P, a space is formed, because adhesive 44 is not present. When a load is inputted from an upper surface side of a floor, the floor is deformed, intermediate member 21 and the like are also deformed, and thereafter top plate 43 is also deformed. By absorbing (stroking) displacement associated with such deformation in the space, input of the load to rigid board 70 can be reduced.

Sixth Embodiment

[0080] FIG. 12 is a cross sectional view showing a vehicle lower structure 10E in a sixth embodiment, which corresponds to FIG. 5 in the first embodiment. The sixth embodiment can be implemented as a modification of the third embodiment described above.

[0081] In vehicle lower structure 10E, underlying portion 70P of rigid board 70 is bonded to top plate 43, and as shown in FIG. 12, adhesive 44 is present between underlying portion 70P of rigid board 70 and top plate 43. On the other hand, at least a portion of rigid board 70 other than underlying portion 70P (non-underlying portion 70W) is not bonded to top plate 43. In the present embodiment, substantially entire rigid board 70 other than underlying portions 70P is not bonded to top plate 43. Since adhesive 44 is not present between non-underlying portion 70W of rigid board 70 and top plate 43, the vehicle lower structure can be manufactured at a lower cost correspondingly.

[0082] Further, since underlying portion 70P is likely to be located under the occupant's feet, rigid board 70 can be reinforced by bonding underlying portion 70P of rigid board 70 to top plate 43. On the other hand, the portion of rigid board 70 not underlying third projection image 31N (non-underlying portion 70W) below seat 11 is less likely to directly receive a load generated when the occupant taps his or her foot. Therefore, by not bonding non-underlying portion 70W of rigid board 70 to top plate 43, a space is formed at this position, and this space can absorb variation in vertical position between cross member 17 and the like and power storage device 40 and displacement due to relative vibration.

[0083] Although the embodiments of the present disclosure have been described, it should be understood that the embodiments disclosed herein are illustrative and non-restrictive in every respect. The scope of the present disclosure is defined by the scope of the claims, and is intended to include any modifications within the scope and meaning equivalent to the scope of the claims.

Claims

1. A vehicle lower structure comprising: a pair of vehicle body frame members; a first intermediate member at least a portion of which is disposed between the pair of vehicle body frame members; a power storage device disposed below the first intermediate member; a first seat disposed above the first intermediate member; and a first reinforcing member disposed inside the first intermediate member or on an upper surface of the first intermediate member, wherein the vehicle lower structure has a region in which the first reinforcing member is not provided below the first seat in a vehicle up/down direction.

2. The vehicle lower structure according to claim 1, comprising a lower frame including a pair of side members, a front member connecting front portions of the pair of side members, a rear member connecting rear portions of the pair of side members, and a cross member connecting intermediate portions of the pair of side members in a vehicle front/rear direction, wherein the pair of vehicle body frame members are any two members selected from the pair of side members, the

front member, and the cross member, the first intermediate member is disposed to fill a space formed by the pair of side members, the front member, and the cross member, inside these members, the first reinforcing member has a first support region, and when a first right reference line and a first left reference line extending in the vehicle front/rear direction along a right end portion and a left end portion of the first seat in a vehicle width direction are defined respectively, and the first support region is projected upward in a vertical direction, a first projection image formed by projection thereof is located on a front side relative to a front end portion of the first seat, and is located between the first right reference line and the first left reference line.

3. The vehicle lower structure according to claim 2, wherein the first reinforcing member is provided to extend from the front member toward a rear side in the vehicle front/rear direction.

4. The vehicle lower structure according to claim 2, wherein the lower frame includes a plurality of the cross members, the vehicle lower structure further comprises a second intermediate member disposed to fill a space formed by the pair of side members and the plurality of the cross members, inside these members, the power storage device is disposed below both the first intermediate member and the second intermediate member, the vehicle lower structure further comprises a second seat, and a second reinforcing member disposed inside the second intermediate member or on an upper surface of the second intermediate member, the second reinforcing member has a second support region, and when a second right reference line and a second left reference line extending in the vehicle front/rear direction along a right end portion and a left end portion of the second seat in the vehicle width direction are defined respectively, and the second support region is projected upward in the vertical direction, a second projection image formed by projection thereof is located on a front side relative to a front end portion of the second seat, and is located between the second right reference line and the second left reference line.

5. The vehicle lower structure according to claim 4, wherein the second reinforcing member is provided to extend from any of the plurality of the cross members toward a front side or a rear side in the vehicle front/rear direction.

6. The vehicle lower structure according to claim 2, wherein the power storage device includes a power storage module including a plurality of power storage cells arranged in a horizontal direction, a case having a top plate and a bottom plate and accommodating the power storage module, and a rigid board disposed between the top plate and the power storage module, and when the first reinforcing member is projected downward in the vertical direction, at least a portion of a third projection image formed by projection thereof is located not to overlap the rigid board.

7. The vehicle lower structure according to claim 6, wherein the power storage device further includes a cushion member disposed between the top plate and the power storage module, and at least a portion of the third projection image is located to overlap the cushion member.

8. The vehicle lower structure according to claim 6, wherein the rigid board has an underlying portion underlying the third projection image, the underlying portion of the rigid board is not bonded to the top plate, and at least a portion of the rigid board other than the underlying portion is bonded to the top plate.

9. The vehicle lower structure according to claim 6, wherein the rigid board has an underlying portion underlying the third projection image, the underlying portion of the rigid board is bonded to the top plate, and at least a portion of the rigid board other than the underlying portion is not bonded to the top plate.
