

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278080

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

KODAMA; Sohei et al.

QUALITY PREDICTION MODEL CREATION SYSTEM, QUALITY PREDICTION SYSTEM, QUALITY PREDICTION MODEL CREATION METHOD, AND QUALITY PREDICTION METHOD

Abstract

A quality prediction model for predicting quality of an elongated product is created. A quality prediction model creation system includes: a first logging data acquisition unit acquiring already-known first logging data respectively detected at every predetermined interval by a plurality of detectors and stored at time of manufacture of an elongated product; an average value calculation unit calculating each average value of the logging data from the logging data acquired by the first logging data acquisition unit; and a model creation unit creating a quality prediction model corresponded to quality property of the elongated product, based on the average value of the logging data.

Inventors: KODAMA; Sohei (Tokyo, JP), TOYA; Masaharu (Tokyo, JP), KUDO; Ryosuke (Tokyo, JP)

Applicant: Proterial, Ltd. (Tokyo, JP)

Family ID: 96827093

Appl. No.: 19/040076

Filed: January 29, 2025

Foreign Application Priority Data

JP 2024-030763

Feb. 29, 2024

Publication Classification

Int. Cl.: G05B19/418 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims foreign priority benefits under 35 U.S.C. § 119 to Japanese Patent Application No. 2024-30763 filed on Feb. 29, 2024, the content of which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD OF THE INVENTION

[0002] The present invention relates to a quality prediction model creation system, a quality prediction system, a quality prediction model creation method, and a quality prediction method.

BACKGROUND OF THE INVENTION

[0003] Japanese Patent Application Laid-Open Publication No. 2022-87429 (Patent Document 1) describes a technique for accurately estimating a physical property value of a composite material by using artificial intelligence.

SUMMARY OF THE INVENTION

[0004] In an elongated product, even if it is possible to evaluate a quality property of its end portion by a destructive test or the like, it is impossible to evaluate its quality property of its entire length. Accordingly, it is impossible to determine whether or not a quality property of an intermediate portion of the elongated product or the like actually satisfies a quality property to be required. And, the quality properties of the elongated product include quality properties, an actually-measured value of which is difficult to be logged during manufacture by a detector or the like, as different from physical property values such as an outer diameter, an eccentricity ratio, and an electrostatic capacitance.

[0005] A quality prediction model creation system according to an embodiment includes: a first logging data acquisition unit acquiring already-known first logging data respectively detected at every predetermined interval by a plurality of detectors and stored at time of manufacture of an elongated product; an average value calculation unit calculating each average value of the first logging data from the first logging data acquired by the first logging data acquisition unit; and a model creation unit creating a quality prediction model corresponded to quality property of the elongated product, based on the average value of the first logging data.

[0006] A quality prediction system according to an embodiment includes: a quality prediction model storage unit storing a quality prediction model created based on an average value of already-known first logging data of an elongated product and corresponded to quality property of the elongated product; a second logging data acquisition unit acquiring second logging data during manufacture of the elongated product at time of manufacture of an elongated product as a prediction target; and a prediction unit predicting quality property of the elongated product as the prediction target by substituting the second logging data acquired by the second logging data acquisition unit into the quality prediction model.

[0007] A quality prediction model creation method according to an embodiment includes: a step of acquiring already-known first logging data; a step of calculating each average value of the first logging data from the acquired first logging data; and a step of creating a quality prediction model corresponded to quality property of the elongated product, based on the average value of the first logging data.

[0008] A quality predicting method according to an embodiment includes: a step of acquiring already-known first logging data respectively detected at every predetermined interval by a plurality of detectors and stored at time of manufacture of an elongated product; a step of calculating each average value of the first logging data from the acquired first logging data; a step

of creating a quality prediction model corresponded to quality property of the elongated product, based on the average value of the first logging data; a step of acquiring second logging data during manufacture of an elongated product as a prediction target; and a step of predicting quality property of the elongated product as the prediction target by substituting the second logging data into the quality prediction model.

[0009] According to an embodiment, a quality prediction model for predicting a quality of an elongated product can be created. According to an embodiment, quality property of an elongated product can be predicted over its entire length by using the quality prediction model.

Description

BRIEF DESCRIPTIONS OF THE DRAWINGS

[0010] FIG. 1 is a schematic diagram illustrating an example of a configuration of a manufacturing system including a quality prediction system;

[0011] FIG. 2 is a schematic diagram illustrating an example of a configuration of the manufacturing system including the quality prediction system;

[0012] FIG. 3 is a diagram illustrating an example of a hardware configuration of the quality prediction system;

[0013] FIG. 4 is a diagram illustrating an example of a functional block of the quality prediction system;

[0014] FIG. 5 is a flowchart illustrating an example of quality prediction model creation processing;

[0015] FIG. 6 is a diagram illustrating an example of first logging data;

[0016] FIG. 7 is a diagram illustrating an example of calculation result data representing a calculation result of an average value of logging data;

[0017] FIG. 8 is a flowchart illustrating an example of processing for achieving an entire length quality prediction technique;

[0018] FIG. 9 is a diagram for describing the entire length quality prediction technique;

[0019] FIG. 10 is a diagram illustrating an example of second logging data;

[0020] FIG. 11 is a diagram for describing an outline of a simulation;

[0021] FIG. 12 is a diagram illustrating a relationship between a measured value (measured strength) and a predicted value (predicted strength) of a tensile strength;

[0022] FIG. 13 is a diagram illustrating a relationship between a measured value (measured elongation) and a predicted value (predicted elongation) of a tensile elongation;

[0023] FIG. 14 is a diagram illustrating a number of screw revolutions and a cylinder temperature as second logging data;

[0024] FIG. 15 is a diagram illustrating a current value of a cylinder and a resin pressure value detected by a resin pressure sensor as second logging data;

[0025] FIG. 16 is a diagram illustrating a winding speed of a winder and an ambient air temperature as second logging data;

[0026] FIG. 17 is a diagram illustrating a maximum resin pressure and a driving force as second simulation data;

[0027] FIG. 18 is a diagram illustrating a retention time period and an average temperature as second simulation data;

[0028] FIG. 19 is a diagram illustrating a strain and a torque as second simulation data;

[0029] FIG. 20 is a diagram illustrating a prediction result of a tensile strength of a heat-resistant insulated electric wire; and

[0030] FIG. 21 is a diagram illustrating a prediction result of a tensile elongation of the heat-resistant insulated electric wire.

DESCRIPTIONS OF THE PREFERRED EMBODIMENTS

[0031] The same components are denoted by the same reference symbols throughout all the drawings for describing the embodiments, and the repetitive description thereof will be omitted. Note that hatching is used even in a plan view so as to make the drawings easy to see.

[0032] The technical idea of the present embodiment is an idea of creating a quality prediction model and predicting quality property over an entire length of an elongated product by using the quality prediction model. If the elongated product is, for example, an electric wire covered with a heat-resistant insulating member, quality properties such as a tensile strength and a tensile elongation at each position of the electric wire are predicted by using CAE and AI/machine learning.

[0033] A technique according to the present embodiment creates a quality prediction model corresponded to quality property by machine learning, by using data (such as a number of screw revolutions of an extruder, a cylinder temperature, a resin pressure value, and an outer diameter size) that can be measured and logged at the time of manufacture of an elongated product in past and data (such as an average resin temperature in a cylinder, a maximum resin pressure value, a torque value, a strain magnitude) that can be calculated by a numerical simulation. The technique according to the present embodiment achieves prediction of quality property of the entire length of the elongated product by using a created quality prediction model and real-time data at the time of manufacture.

Description of Related Art

[0034] A case of an elongated product such as a heat-resistant insulated electric wire will be described. Standards have been determined for quality properties of the heat-resistant insulated electric wire, such as an insulation resistance, a withstand voltage, tension of an insulator and a sheath, heating, an oil resistance, and the like, and a testing method for them has also been specifically determined by a rubber/plastic insulated electric wire testing method defined in JIS C3005.

[0035] Measurement for mechanical properties (a tensile strength and a tensile elongation) of an insulator and a sheath of an elongated cable such as a rubber electric wire is determined so that three or more dumbbell-shaped or tubular-shaped test pieces are sampled from a finished product and are measured at a predetermined tensile speed (25 to 500 mm/min), as described in 4.16 in JIS C3005. Accordingly, three or more test pieces are cut off from an end portion of the finished elongated cable, and a value of the tensile strength and a value of the tensile elongation are calculated by using a tensile tester, and are set as the quality properties of the elongated cable.

[0036] The related art is possible to evaluate the quality properties only by the destructive test for an end portion of the elongated product, and is impossible to determine whether or not an intermediate portion of the elongated product really satisfies the standards. There are also quality properties, the measured value of which in the elongated product during manufacture is difficult to be always logged by a detector or the like, as different from an outer diameter, an eccentricity ratio, an electrostatic capacitance, and the like.

Configuration of Manufacturing System

[0037] FIGS. 1 and 2 are schematic diagrams each illustrating an example of a configuration of a manufacturing system 1 including a quality prediction system 100. FIG. 1 is a schematic diagram illustrating an example of a configuration of an extruder 10 in the manufacturing system 1 viewed in a Y-direction. FIG. 2 is a schematic diagram illustrating an example of the configuration of the extruder 10 in the manufacturing system 1 viewed in an X-direction in a head 31 illustrated in FIG. 1. In the present embodiment, a case where the quality prediction system 100 includes a quality prediction model creation system will be described. However, the quality prediction system 100 and the quality prediction model creation system may be different systems from each other.

[0038] As illustrated in FIGS. 1 and 2, the X-direction, the Y-direction, and a Z-direction are defined. The X-direction, the Y-direction, and the Z-direction are perpendicular to one another, but

may intersect one another at an angle other than the perpendicular angle.

[0039] The manufacturing system **1** includes the extruder **10** and the quality prediction system **100**. The extruder **10** has a single screw not illustrated. In the present embodiment, a case where the quality property of a heat-resistant insulated electric wire EW manufactured as an example of the elongated product in the extruder **10** is predicted will be described. Note that the elongated product is not limited to an electric wire such as the heat-resistant insulated electric wire EW. The elongated product may be, for example, a pipe, a sheet, or a film. The quality prediction system **100** is, for example, a computer system. Details of the quality prediction system **100** will be described later.

[0040] As illustrated in FIG. **1**, the extruder **10** manufacture the heat-resistant insulated electric wire EW by covering a core wire CW with resin such as a heat-resistant insulating member. As illustrated in FIG. **1**, the extruder **10** includes a feeder **20**, the head **31**, a die **32**, a water reservoir **40**, and a winder **50**. An extrusion line is made of the feeder **20**, the head **31**, the die **32**, the water reservoir **40**, and the winder **50**. As illustrated in FIG. **2**, the extruder **10** includes a cylinder **33** connected to the head **31** and a material input unit **34**.

[0041] The feeder **20** is housed in a state with the wound core wire CW thereon. When the feeder **20** rotates as illustrated with an arrow AR1, the core wire CW is drawn from the feeder **20**. The core wire CW drawn in a direction illustrated with an arrow AR2 passes through the head **31** and the die **32**. The heat-resistant insulated electric wire EW that has passed through the head **31** and the die **32** passes through the water reservoir **40**, and then, is wound up by the winder **50**. In the winder **50**, the heat-resistant insulated electric wire EW is wound thereon, and is housed therein. An illustrated arrow AR3 indicates a direction in which the heat-resistant insulated electric wire EW is wound.

[0042] The head **31** is connected to the cylinder **33**. The heat-resistant insulating member is supplied from the cylinder **33** to the head **31**. The heat-resistant insulating member supplied to the head **31** adheres to the core wire CW drawn from the feeder **20**. The die **32** is provided with a hole of a predetermined size although not illustrated. The core wire CW to which the heat-resistant insulating member has adhered passes through the hole of the die **32**. As a result, the heat-resistant insulating member having a thickness corresponding to the size of the hole is formed on the core wire CW, to manufacture the heat-resistant insulated electric wire EW.

[0043] The heat-resistant insulated electric wire EW that has passed through the die **32** passes through the water reservoir **40**. In the water reservoir **40**, the heat-resistant insulated electric wire EW is cooled to a predetermined temperature. The heat-resistant insulated electric wire EW cooled as described above is wound by the winder **50**. In the winder **50**, the heat-resistant insulated electric wire EW is wound at a winding speed (hereinafter, also referred to as a “linear speed”), and is housed in the winder **50**. Information representing the winding speed and a winding current value representing a current value to be supplied to the winder **50** is transmitted to the quality prediction system **100** at every predetermined interval such as one second.

[0044] As illustrated in FIG. **2**, the head **31** is connected to one end of the cylinder **33**, and the material input unit **34** is connected to the top of the other end thereof. The heat-resistant insulating member is inputted into the material input unit **34**. As illustrated with a dashed arrow AR4, the heat-resistant insulating member is supplied from the material input unit **34** into the cylinder **33**. The cylinder **33** has a single screw. The cylinder **33** is configured to rotate the screw at a predetermined number of revolutions, depending on a current amount to be supplied. By the rotation of the screw, the heat-resistant insulating member inputted from the material input unit **34** is gradually extruded toward the head **31** side as illustrated with a dashed arrow AR5. The extruded heat-resistant insulating member is adhered to the core wire CW in the head **31**, and is extruded outward as part of the heat-resistant insulated electric wire EW from the die **32**. The number-of-revolutions information representing the number of revolutions of the screw, an acceleration, a current value, and the like are transmitted to the quality prediction system **100** at every predetermined interval such as one second.

[0045] Here, the screw has, for example, three playing roles. The first role is a role of extruding the heat-resistant insulating member supplied from the material input unit **34** toward the head **31** side to reach the head **31**. At this time, residual heat is given to the heat-resistant insulating member. The second role is a role of bringing the heat-resistant insulating member from a solid state to a molten state. The third role is a role of stably extruding a certain amount of the heat-resistant insulating member from the die **32**.

[0046] A core wire temperature sensor **S11** as one of detectors is provided between the feeder **20** and the head **31**. The core wire temperature sensor **S11** detects a temperature of the core wire CW between the feeder **20** and the head **31**. The temperature detected by the core wire temperature sensor **S11** is transmitted to the quality prediction system **100** at every predetermined interval such as one second.

[0047] As illustrated in FIG. **1**, the head **31** is provided with a head temperature sensor **S12** and a die temperature sensor **S13**. The head temperature sensor **S12** and the die temperature sensor **S13** are respectively detectors. The head temperature sensor **S12** is a sensor that detects a head temperature of the head **31**. The die temperature sensor **S13** is a sensor that detects a die temperature of the die **32**. A neck temperature sensor **S14** as one of detectors is provided in the vicinity of a junction between the cylinder **33** and the head **31** (see FIG. **2**). The neck temperature sensor **S14** is a sensor that detects a neck temperature in the vicinity of the junction between the cylinder **33** and the head **31**. The head temperature, the die temperature, and the neck temperature respectively detected by the head temperature sensor **S12**, the die temperature sensor **S13**, and the neck temperature sensor **S14** are each transmitted to the quality prediction system **100** at every predetermined interval such as one second.

[0048] The water reservoir **40** is provided with a water reservoir temperature sensor **S15** as one of detectors. The water reservoir temperature sensor **S15** is a sensor that detects a water temperature of the water reservoir **40**. The temperature detected by the water reservoir temperature sensor **S15** is transmitted to the quality prediction system **100** at every predetermined interval such as one second.

[0049] An outer diameter measurement sensor **S16** as one of detectors is provided between the water reservoir **40** and the feeder **50**. The outer diameter measurement sensor **S16** is a sensor that detects an outer diameter size of the heat-resistant insulated electric wire EW that has been cooled by the water reservoir **40**. The outer diameter size detected by the outer diameter measurement sensor **S16** is transmitted to the quality prediction system **100** at every predetermined interval such as one second.

[0050] As illustrated in FIG. **2**, a resin temperature sensor **S17** and a resin pressure sensor **S18** are provided in the vicinity of a connection of the cylinder **33** with the head **31**. The resin temperature sensor **S17** and the resin pressure sensor **S18** are respectively detectors. The resin temperature sensor **S17** is a sensor that detects a resin temperature of the heat-resistant insulating member to be supplied to the head **31**. The resin pressure sensor **S18** is a sensor that detects a resin pressure value (also referred to as a distal-end resin pressure value) of the heat-resistant insulating member to be supplied to the head **31**. The resin temperature and the resin pressure value respectively detected by the resin temperature sensor **S17** and the resin pressure sensor **S18** are each transmitted to the quality prediction system **100** at every predetermined interval such as one second.

[0051] The cylinder **33** is provided with five temperature sensors **S21** to **S25** in a longitudinal direction from the material input unit **34** side. The five temperature sensors **S21** to **S25** are respectively detectors. As a result, a temperature of the cylinder **33** is detected at a plurality of positions in the longitudinal direction of the cylinder **33**. Note that the number of temperature sensors is not limited to five, but may be, for example, three, four, six or more. Temperatures respectively detected by the five temperature sensors **S21** to **S25** are each transmitted to the quality prediction system **100** at every predetermined interval such as one second. Although the cylinder **33** has three playing roles as described above, since the plurality of temperature sensors **S21** to **S25**

are provided, the quality prediction system **100** can detect a change in the temperature of the cylinder **33** in each of the playing roles.

[0052] An air temperature sensor **S31** and a humidity sensor **S32** are arranged around the extruder **10**, e.g., around the cylinder **33**. The air temperature sensor **S31** and the humidity sensor **S32** are respectively detectors. A temperature detected by the air temperature sensor **S31** and a humidity detected by the humidity sensor **S32** are each transmitted to the quality prediction system **100** at every predetermined interval such as one second.

Hardware Configuration

[0053] Next, a hardware configuration of the quality prediction system **100** according to the present embodiment will be described. FIG. **3** is a diagram illustrating an example of the hardware configuration of the quality prediction system **100** according to the present embodiment. The configuration illustrated in FIG. **3** is merely the example of the hardware configuration of the quality prediction system **100**. The hardware configuration of the quality prediction system **100** is not limited to the configuration illustrated in FIG. **1**, but may be another configuration.

[0054] In FIG. **1**, the quality prediction system **100** includes a CPU (central Processing Unit) **101** that executes programs. The CPU **101** is electrically connected to, for example, a ROM (Read Only Memory) **102**, a RAM (Random Access Memory) **103**, and a hard disk device **112** via a bus **113**, and is configured to control these hardware devices.

[0055] The CPU **101** is also connected to an input device and an output device via the bus **113**. Examples of the input device can include a keyboard **105**, a mouse **106**, a communication port **107**, and a scanner **111**. On the other hand, examples of the output devices can include a display **104**, the communication port **107**, and a printer **110**. Further, the CPU **101** may be connected to, for example, a removable disk device **108** or a CD/DVD-ROM device **109**. And, for example, the cylinder **33**, the feeder **20**, the winder **50**, the core wire temperature sensor **S11**, the head temperature sensor **S12**, the die temperature sensor **S13**, the neck temperature sensor **S14**, the water reservoir temperature sensor **S15**, the outer diameter measurement sensor **S16**, the resin temperature sensor **S17**, the resin pressure sensor **S18**, the temperature sensors **S21** to **S25**, the air temperature sensor **S31**, and the humidity sensor **S32** are connected to the communication port **107**.

[0056] The quality prediction system **100** may be connected to, for example, a network. If, for example, the quality prediction system **100** is connected to another external device via the network, the communication port **107** constituting part of the quality prediction system **100** is connected to a LAN (local area network), a wide area network (WAN), or the Internet.

[0057] The RAM **103** is an example of a volatile memory while storage media such as the ROM **102**, the removable disk device **108**, the CD/DVD-ROM device **109**, and the hard disk device **112** are each an example of a non-volatile memory. The volatile memory and the non-volatile memory configure a storage device of the quality prediction system **100**.

[0058] The hard disk device **112** stores, for example, an operating system (OS) **201**, a program group **202**, and a file group **203**. Programs included in the program group **202** are executed while the CPU **101** uses the operating system **201**. The RAM **103** temporarily stores at least some of programs in the operating system **201** and application programs executed by the CPU **101**, and stores various types of data required for processing executed by the CPU **101**.

[0059] The ROM **102** stores a BIOS (Basic Input Output System) program, and the hard disk device **112** stores a boot program. When the quality prediction system **100** is activated, the BIOS program stored in the ROM **102** and the boot program stored in the hard disk device **112** are executed, and the operating system **201** is activated by the BIOS program and the boot program.

[0060] The program group **202** stores a program for achieving a function of the quality prediction system **100**, and the program is loaded and executed by the CPU **101**. The file group **203** stores information, data, a signal value, a variable value, and a parameter, which represent a result of the processing executed by the CPU **101**, respectively, as factors of a file. The program group **202** includes, for example, a quality prediction model creation program **202A** and a quality prediction

program **202B** described later.

[0061] The file group **203** includes logging data **203A**, simulation data **203B**, and a quality prediction model **203C**. The logging data **203A** is manufacturing data acquired when the heat-resistant insulated electric wire EW has been manufactured. The simulation data **203B** is simulation data representing a result of a simulation using the logging data. The quality prediction model **203C** is a model for predicting the quality property of the heat-resistant insulated electric wire EW. Details of the logging data **203A**, the simulation data **203B**, and the quality prediction model **203C** will be described later.

[0062] The file is stored in a storage medium such as the hard disk device **112** or a memory. The information, data, signal value, variable value, and parameter stored in the storage medium such as the hard disk device **112** or the memory are loaded into a main memory or a cache memory by the CPU **101**, and are used for an operation of the CPU **101**, typified by extraction, search, reference, comparison, calculation, processing, editing, output, printing, and display. For example, during the above-described operation of the CPU **101**, the information, data, signal value, variable value, and parameter are temporarily stored in a main memory, a register, a cache memory, a buffer memory, or the like.

[0063] The function of the quality prediction system **100** may be achieved by firmware stored in the ROM **102**, or by only software, only hardware typified by an element, a device, a substrate, and a wiring, a combination of the software and the hardware, or further a combination with the firmware. The firmware and the software are stored as a program in a storage medium typified by the hard disk device **112**, the removable disk drive **108**, the CD/DVD-ROM drive **109**, and the like. The program is loaded and executed by the CPU **101**. For example, by the program, the computer is functioned as the quality prediction system **100**.

[0064] Thus, the quality prediction system **100** is the computer including the CPU **101** as a processing device, the hard disk device **112** or the memory as a storage device, the keyboard **105**, the mouse **106**, or the communication port **107** as an input device, and the display **104**, the printer **110**, or the communication port **107** as an output device. The function of the quality prediction system **100** is achieved by using the processing device, the storage device, the input device, and the output device.

Functional Block

[0065] FIG. **4** is a diagram illustrating an example of a functional block of the quality prediction system **100**. As illustrated in FIG. **4**, the quality prediction system **100** includes a first logging data acquisition unit **301**, an average value calculation unit **302**, a first simulation unit **303**, a model creation unit **304**, a data merging unit **305**, a quality prediction model storage unit **306**, a second logging data acquisition unit **307**, a second simulation unit **308**, and a prediction unit **309**. Details of functions respectively achieved by the first logging data acquisition unit **301**, the average value calculation unit **302**, the first simulation unit **303**, the model creation unit **304**, the data merging unit **305**, the quality prediction model storage unit **306**, the second logging data acquisition unit **307**, the second simulation unit **308**, and the prediction unit **309** will be described later.

Creation of Quality Prediction Model

[0066] Next, a quality prediction model creation processing for creating the quality prediction model **203C** for predicting the quality property of the heat-resistant insulated electric wire EW manufactured by the extruder **10** will be described. FIG. **5** is a flowchart illustrating an example of the quality prediction model creation processing. This processing is achieved when the quality prediction model creation program **202A** stored in the hard disk device **112** is loaded and executed by the CPU **101**.

[0067] First, the CPU **101** acquires the first logging data in step ST**101**. A function of the first logging data acquisition unit **301** in the quality prediction system **100** is achieved by processing in step ST**101**. From the hard disk device **112**, the first logging data acquisition unit **301** acquires the already-known first logging data respectively detected and stored at every predetermined interval

by a plurality of devices and sensors at the time of manufacture of the heat-resistant insulated electric wire EW. The acquired first logging data is, in other words, already-known manufacturing data for each production number of the same product at the time of manufacture of the heat-resistant insulated electric wire EW. Here, examples of the plurality of devices and sensors include the cylinder **33**, the feeder **20**, the winder **50**, the core wire temperature sensor **S11**, the head temperature sensor **S12**, the die temperature sensor **S13**, the neck temperature sensor **S14**, the water reservoir temperature sensor **S15**, the outer diameter measurement sensor **S16**, the resin temperature sensor **S17**, the resin pressure sensor **S18**, the temperature sensors **S21** to **S25**, the air temperature sensor **S31**, and the humidity sensor **S32**.

[0068] FIG. **6** is a diagram illustrating an example of first logging data **203A1**. The first logging data **203A1** is data included in the logging data **203A**. FIG. **6** illustrates the first logging data **203A1** for the heat-resistant insulated electric wire EW with a production number “AAA”. Factors such as a number of screw revolutions (rpm), a cylinder temperature (° C.), a linear speed (m/s), etc., are corresponded to a time. Although not illustrated, temperatures respectively acquired by the temperature sensors **S21** to **S25** are included as the factors in the cylinder temperature. In the present embodiment, the first logging data **203A1** is included and stored in the logging data **203A** of the file group **203** at every one second as the predetermined interval. Accordingly, the first logging data **203A1** is acquired from the file group **203**. The illustration shows an example in which the three factors are included as the first logging data **203A1**. However, as the first logging data **203A1**, the logging data as a predetermined factor among all logging data as the factors that can be acquired by the quality prediction system **100** is corresponded to the time.

[0069] In order to create the quality prediction model **203C**, for example, the CPU **101** desirably acquires several tens or more of pieces of the already-known first logging data **203A1** for the same product. The more factors as the first logging data **203A1** to be acquired are desirable. The CPU **101** desirably acquires the logging data as the measurable factors such as the number of screw revolutions, the cylinder temperature, the linear speed, etc., illustrated in FIG. **6** among the factors acquired from the logging data **203A**, as many as possible as the first logging data **203A1**. The CPU **101** can set any of all the factors included in the logging data **203A** to a creation target for the quality prediction model **203C**, based on setting. The created quality prediction model **203C** is stored in the hard disk device **112**.

[0070] Next, the CPU **101** calculates an average value in step **ST102**. A function of the average value calculation unit **302** in the quality prediction system **100** is achieved by processing in step **ST102**. The average value calculation unit **302** calculates, for each of the factors, an average value of the first logging data **203A1** from the first logging data **203A1** acquired by the first logging data acquisition unit **301** in step **ST101**. In the present embodiment, if the logging data **203A** includes data of a setup time period and an adjustment time period before manufacture of the heat-resistant insulated electric wire EW, the CPU **101** performs processing for excluding respective parts for the setup time period and the adjustment time period from the first logging data **203A1**. As a result, the CPU **101** can acquire, for each of the factors, the average value of the first logging data **203A1** from the start to the end of manufacture of the heat-resistant insulated electric wire EW.

[0071] FIG. **7** is a diagram illustrating an example of calculation result data **D10** representing a calculation result of the average value of the first logging data **203A1**. As illustrated in FIG. **7**, an average number of screw revolutions, an average cylinder temperature, an average linear speed, etc., for each production number are calculated.

[0072] Next, the CPU **101** performs a simulation in step **ST103**. A function of the first simulation unit **303** in the quality prediction system **100** is achieved by processing in step **ST103**. The first simulation unit **303** simulates the quality property of the heat-resistant insulated electric wire EW by using the average value of the first logging data **203A1**. The CPU **101** calculates a feature amount described later by using the average value of the first logging data **203A1** calculated in step **ST102** as a condition for a CAE (Computer Aided Engineering) analysis. The feature amount can

also be said as the quality property of the heat-resistant insulated electric wire EW acquired by simulation data. The number of production numbers used in the CAE analysis is desirably larger in order to increase an accuracy of the correspondence to the quality property of the heat-resistant insulated electric wire EW. On the other hand, the larger number of production numbers possibly causes an enormous time period required for the CAE analysis. Accordingly, the number of production numbers is desirably set such that a computational load used for the CAE analysis does not exceed a limit of the CPU **101** along with the large number of production numbers. A simulation result in step **ST103** is set as first simulation data. The first simulation data is stored as simulation data **203B** in the hard disk device **112**.

[0073] The above-described feature amount is, for example, the unmeasurable data such as the strain and the retention time period of the heat-resistant insulating member in the extruder **10**, or data that requires a large amount of labor for the measurement. A cylinder temperature related to the cylinder **33**, a temperature and a resin pressure value of the heat-resistant insulating member in the cylinder **33**, and the like may be added to the feature amounts. These items can be actually measured, but are measured as only their values in the vicinity of the arranged detector. In other words, this is because positions and values of an “average” temperature, a “maximum” resin pressure, and the like of the heat-resistant insulating member in the extruder **10** can be derived by a simulation. Therefore, the CPU **101** also desirably sets, as the feature amount, the factor that can be detected as the value only in the vicinity of the detector, and adds the factor to the simulation target.

[0074] Next, the CPU **101** merges result data measured by a quality inspection with the first simulation data in step **ST104**. A function of the data merging unit **305** in the quality prediction system **100** is achieved by processing in step **ST104**. The data merging unit **305** acquires quality result data of a quality test performed for an end portion of the heat-resistant insulated electric wire EW, and merges the quality result data with the first simulation data. The quality inspection is, for example, a destructive inspection. The quality inspection targets are the factors that can be evaluated only by the destructive inspection, such as a tensile strength, a tensile elongation, a flame retardancy, and an oil resistance. If these factors include a factor that allows the validity of the first simulation data to be determined, the CPU **101** desirably simulates this factor, and merges the factor with the quality result data.

[0075] Next, the CPU **101** creates a quality prediction model **203C** in step **ST105**. A function of the model creation unit **304** in the quality prediction system **100** is achieved by processing in step **ST105**. The model creation unit **304** creates the quality prediction model **203C** corresponded to the quality property of the heat-resistant insulated electric wire EW, based on the average value of first logging data **203A1** and the first simulation data representing the simulation result. The model creation unit **304** creates the quality prediction model **203C** by machine learning while setting the quality property data representing the quality property of the heat-resistant insulated electric wire EW, respectively, as objective variables, and setting the first logging data of the heat-resistant insulated electric wire EW and the first simulation data, respectively, as explanatory variables.

[0076] A multivariate analysis is used to create the quality prediction model **203C**. There are many methods for performing the multivariate analysis. The CPU **101** can calculate a regression coefficient of each data relatively easily by performing the multiple regression analysis using a class “sklearn. Linear model. Linear Regression” of a python machine learning library “scikit-learn” given as an example. The CPU **101** may interpret the quality prediction model **203C** by using libraries such as “SHAP”, acquire a degree of contribution or the like, and exactly examine whether or not the quality prediction model **203C** is valid. The machine learning is used as described above to create the quality prediction model **203C**. The quality prediction model **203C** created as described above is stored in the hard disk device **112** by a function of the quality prediction model storage unit **306**.

Prediction of Entire Length Quality

[0077] Next, an entire length quality prediction technique using the created quality prediction

model **203C** for predicting quality property of the heat-resistant insulated electric wire EW over its entire length will be described. FIG. **8** is a flowchart illustrating an example of a processing for achieving the entire length quality prediction technique. This processing is achieved when a quality prediction program **202B** stored in the hard disk device **112** is loaded and executed by the CPU **101**. FIG. **9** is a diagram for describing the entire length quality prediction technique.

[0078] As illustrated in FIG. **8**, the CPU **101** acquires second logging data in step ST**201**. A function of the second logging data acquisition unit **307** in the quality prediction system **100** is achieved by processing in step ST**201**. And, for example, at the time of manufacture of the heat-resistant resistant insulated electric wire EW, the second logging data acquisition unit **307** acquires second logging data **203A2** (see FIG. **10**) during manufacture of the heat-resistant insulated electric wire EW as a prediction target.

[0079] FIG. **10** is a diagram illustrating an example of the second logging data **203A2**. FIG. **10** illustrates the second logging data **203A2** for a heat-resistant insulated electric wire EW with a production number “FFF”. Factors such as a number of screw revolutions (rpm), a cylinder temperature (° C.), a linear speed (m/s), etc., are corresponded to a time. Although not illustrated, temperatures respectively acquired by the temperature sensors S**21** to S**25** are included as the factors in the cylinder temperature. In the present embodiment, during the manufacture of the heat-resistant insulated electric wire EW with the production number FFF, the second logging data **203A2** is included and stored in the logging data **203A** of the file group **203** at every one second as the predetermined interval. Accordingly, the second logging data **203A2** is acquired from the file group **203**. The illustration shows an example in which the three factors are included as the second logging data **203A2**. However, the second logging data **203A2** is the logging data as a predetermined factor among all logging data as the factors that can be acquired by the quality prediction system **100**, and is, for example, logging data as the same factor with that of the first logging data **203A1** used for the creation of the quality prediction model **203C**.

[0080] Next, the CPU **101** performs a continuous simulation at every predetermined time period in step ST**202**. A function of the second simulation unit **308** in the quality prediction system **100** is achieved by processing in step ST**202**. The second simulation unit **308** creates the second simulation data by performing a simulation based on the second logging data **203A2** acquired by the second logging data acquisition unit **307**.

[0081] For the second logging data **203A2** based on which the simulation is performed, the explanation will be made in a case where the CPU **101** acquires a cylinder temperature “C”, a number “N” of revolutions as a number of revolutions of a screw, a distal-end resin pressure “P” detected by the resin pressure sensor S**18**, and an air temperature “Ta” detected by the air temperature sensor S**31**, respectively, as the second logging data **203A** as measured values as illustrated in items (a) and (b) of FIG. **9**, although different from those in the example illustrated in FIG. **10**. The CPU **101** extracts the second logging data **203A2** acquired at every predetermined time period, and performs the continuous simulation by using the extracted second logging data **203A2**. Feature amounts as the simulation targets are a strain magnitude “ γ ”, an average material temperature “ t ” of the heat-resistant insulating member as a material, and a retention time period “ t ” of the heat-resistant insulating member in the cylinder **33**.

[0082] The second logging data **203A2** may be collected at time interval that is, for example, every one second in the present embodiment, or that is generally every one or shorter second.

Accordingly, the second logging data **203A2** has an enormous data amount. Therefore, if the simulation is performed by using all the second logging data **203A2** as the analysis condition, the computational load of the CPU **101** becomes enormous. In consideration of the computational load of the CPU **101**, the CPU **101** desirably extracts the second logging data **203A2** as the simulation target from among all the second logging data **203A2** while thinning out the second logging data **203A2** at every predetermined time period such as every 10 seconds or every 60 seconds. Since the second simulation data is calculated at every predetermined time period, the second simulation data

as the simulation result is not single data but is treated as continuous data.

[0083] Next, the CPU **101** substitutes the second logging data **203A2** and the second simulation data into the quality prediction model **203C** in step **ST203**. A function of the prediction unit **309** in the quality prediction system **100** is achieved by processing in step **ST203**. The prediction unit **309** predicts the quality property of the heat-resistant insulated electric wire EW as the prediction target by substituting the second logging data **203A2** and the second simulation data created by the second simulation unit **308** into the quality prediction model **203C**.

[0084] For example, as illustrated in an item (c) of FIG. **9**, the CPU **101** performs the machine learning by substituting the second logging data **203A2** acquired at every predetermined time period and the second simulation data acquired at every predetermined time period into the quality prediction model **203C**. Here, the sophisticated AI can also be used for the machine learning. However, if the above-described python library “scikit-learn” or the like is used, the CPU **101** can perform a multiple regression analysis relatively easily. By the multiple regression analysis, each regression coefficient “a1”, “a2”, . . . for variable and an intercept “b” are acquired. The item (c) of FIG. **9** illustrates an example in which a relationship between the tensile strength (predicted value) and the tensile strength (measured value) is acquired. In this example, the predicted value and the measured value are gathered in the vicinity of a straight line **L1**. Accordingly, the CPU **101** determines that the quality prediction model **203C** is valid.

[0085] Next, in step **ST204**, the CPU **101** substitutes the data acquired in step **ST203** into the logging data **203A** stored in the file group **203**. That is, if the quality prediction model **203C** is valid, the CPU **101** substitutes the acquired data such as the tensile strength (predicted value) illustrated in the item (c) of FIG. **9** into the original logging data **203A**. As a result, as illustrated in an item (d) of FIG. **9**, into the file group **203**, the CPU **101** can store the magnitude of the tensile strength that has been acquired only around the end of the manufacturing time period, i.e., at several points of the end portion of the heat-resistant insulated electric wire EW as the measured values as the logging data **203A**, instead of the magnitude of the tensile strength from the start to the end of the manufacture. As a result, the quality prediction system **100** can predict a variation in value of the quality property for the set objective variable such as the tensile strength over the entire length of the heat-resistant insulated electric wire EW.

[0086] Further, the CPU **101** may acquire the objective variable, i.e., the predicted value of the quality property nearly in real time during the manufacture of the heat-resistant insulated electric wire EW. When this result is displayed on a display device such as the display **104**, an operator can always monitor the variation in the predicted value of the quality property of the heat-resistant insulated electric wire EW. In further application of this system, for example, if the predicted value of the quality property tends to exceed a proper range during the manufacture of the heat-resistant insulated electric wire EW, the CPU **101** can change manufacturing parameters such that the predicted value of the quality property tends to be the proper range. That is, the CPU **101** can properly control the manufacturing parameters.

EXAMPLE

[0087] Next, as an example, a processing in the case of the entire length quality prediction of the heat-resistant insulated electric wire EW manufactured by the manufacturing system **1** will be described in more detail. In this example, the quality properties to be predicted are assumed to be the tensile strength and the tensile elongation defined in JIS C3005.

[0088] First, logging data used in this example will be described. The quality prediction system **100** always stores 13 values of the number of screw revolutions in the cylinder **33**, the current value rotating the screw, the acceleration of the screw, the respective cylinder temperatures at five different positions, the neck temperature, the head temperature, the die temperature, the resin temperature, and the distal-end resin pressure value at every interval of one second. The 13 data values are stored as the logging data **203A** in the file group **203** of the hard disk device **112**.

[0089] Also, the quality prediction system **100** stores seven values in total, i.e., the air temperature

of the extruder **10**, the humidity of the extruder **10**, the core wire temperature of the core wire CW, the water temperature of the water reservoir **40**, the outer diameter size of the heat-resistant insulated electric wire EW, and the winding speed and the winding current value of the winder **50** at every interval of one second. These seven data values are stored as the logging data **203A** in the file group **203** of the hard disk device **112**.

[0090] In this example, in order to consider that the heat-resistant insulating member (resin) changes in its properties when being rapidly or slowly cooled, the quality prediction system **100** also stores two values, i.e., a value [“resin temperature”–“air temperature”] acquired by subtracting the air temperature from the resin temperature detected by the resin temperature sensor **S17** and a value [“resin temperature”–“water temperature”] acquired by subtracting the water temperature from the resin temperature at every interval of one second. These two data values are stored as the logging data **203A** in the file group **203** of the hard disk device **112**. As described above, in this example, the CPU **101** uses the data of the 22 factors as the first logging data **203A1**.

[0091] Next, the CPU **101** performs a simulation as illustrated in FIG. **11**. FIG. **11** is a diagram for describing the outline of the simulation. As illustrated in FIG. **11**, the CPU **101** performs the simulation by using screw structure information **D1** representing a structure of the screw included in the cylinder **33**, a number of screw revolutions **D2**, a resin pressure value **D3**, respective cylinder temperatures **D4** of the temperature sensors **S21** to **S25**, and an air temperature **D5** as the analysis conditions. Simulation software used in this example is “Single Screw Simulator” manufactured by a HASL company. In this example, the seven factors, i.e., the “discharge volume”, the “maximum resin pressure”, the “driving force”, the “retention time period”, the “average temperature”, the “strain”, and the “torque” are simulated. The “maximum resin pressure”, the “driving force”, the “retention time period”, the “average temperature”, the “strain”, and the “torque” are respectively feature amounts for the heat-resistant insulating member and the screw in the cylinder **33**. By the CPU **101**, the seven first simulation data **D11**, i.e., the “discharge volume”, the “maximum resin pressure”, the “driving force”, the “retention time period”, the “average temperature”, the “strain”, and the “torque”, which are respectively simulation results, are stored as the simulation data **203B** in the file group **203** of the hard disk device **112**.

[0092] As described above, the CPU **101** creates the quality prediction model **203C** for calculating the value of the tensile strength and the value of the tensile elongation, respectively, as the objective variables by using 29 variables including the 22 first logging data **203A1** and the seven first simulation data **D11**, respectively, as the explanatory variables.

[0093] In this example, **58** production numbers are prepared as a learning model, and are analyzed by performing a “multiple regression analysis” using a class “sklearn.linear_model.LinearRegression” of the python machine learning library “scikit-learn” to calculate respective regression coefficients “a1” to “a29” of the explanatory variables and the intercept “b” (see the item (c) of FIG. **9**).

[0094] FIG. **12** is a diagram illustrating a relationship between a measured value (measured strength) and a predicted value (predicted strength) of the created tensile strength. FIG. **13** is a diagram illustrating a relationship between a measured value (measured elongation) and a predicted value (predicted elongation) of the created tensile elongation. In FIG. **12**, an average value of the tensile strength is set to zero, and a tensile strength higher than the average value is illustrated with “+”, and a tensile strength lower than the average value is illustrated with “-”. The same applies to the tensile elongation illustrated in FIG. **13**. As illustrated in FIG. **12**, there is a substantially constant relationship between the measured strength and the predicted value. As a result, the CPU **101** created the quality prediction model **203C** for the tensile strength as illustrated with a dashed line **L2**. A determination coefficient as a gradient of the dashed line **L2** is 0.79, and an intercept is 0. As illustrated in FIG. **13**, there is a substantially constant relationship between the measured elongation and the predicted elongation. As a result, the CPU **101** created the quality prediction model **203C** for the tensile elongation as illustrated with a dashed line **L3**. A determination

coefficient as a gradient of the dashed line L2 is 0.89, and an intercept is 0.

[0095] Next, the CPU **101** performs the entire length prediction of the heat-resistant insulated electric wire EW as the prediction target manufactured by the manufacturing system **1** by using the quality prediction models **203C** for the tensile strength and the tensile elongation respectively illustrated in FIGS. **12** and **13**.

[0096] FIGS. **14** to **16** are diagrams each illustrating an example of the second logging data **203A2** acquired at every interval of one second. FIG. **14** is a diagram illustrating the number of screw revolutions and the cylinder temperature as the second logging data **203A2**. As the cylinder temperature, all temperatures to be respectively detected by the temperature sensors **S21** to **S25** may be acquired, or any temperature may be acquired. For example, the CPU **101** acquires three temperatures to be respectively detected by the temperature sensors **S23**, **S24**, and **S25** close to the head **31**. FIG. **15** is a diagram illustrating the current value of the cylinder **33** and the resin pressure value detected by the resin pressure sensor **S18** as the second logging data **203A2**. FIG. **16** is a diagram illustrating the winding speed of the winder **50** and the ambient air temperature as the second logging data **203A2**. The CPU **101** extracts the second logging data **203A2** among the second logging data **203A2** respectively illustrated in FIGS. **14** to **16**, at every 60 seconds.

[0097] Next, the CPU **101** performs a simulation by using the extracted second logging data **203A2**. The CPU **101** performs a simulation from the setup time period to be normally excluded, in order to evaluate the validity of the simulation result. Here, the setup time period described here is a time period before the actual start of the manufacture of the heat-resistant insulated electric wire EW.

[0098] FIGS. **17** to **19** are diagrams each illustrating one example of the second simulation data representing the simulation result. FIG. **17** is a diagram illustrating the maximum resin pressure and the driving force as the second simulation data. FIG. **18** is a diagram illustrating the retention time period and the average temperature as the second simulation data. FIG. **19** is a diagram illustrating the strain and the torque as the second simulation data. As illustrated in FIGS. **17** to **19**, it is found that a tendency of continuity of data greatly changes between the setup time period and the data acquisition time period. Accordingly, the CPU **101** can determine that the simulation result is valid.

[0099] Next, the CPU **101** substitutes the second logging data **203A2** extracted at every 60 seconds from among the second logging data illustrated in FIGS. **14** to **16** and the second simulation data at every 60 seconds illustrated in FIGS. **17** to **19** into the quality prediction models **203C** for the tensile strength and the tensile elongation respectively illustrated in FIGS. **12** and **13**. As a result, the CPU **101** can calculate respective predicted values of the tensile strength and the tensile elongation at every 60 seconds over the entire length of the heat-resistant insulated electric wire EW. Therefore, the CPU **101** can predict the tensile strength and the tensile elongation of the manufactured heat-resistant insulated electric wire EW, in other words, the quality property over the entire length of the heat-resistant insulated electric wire EW. The predicted values of the tensile strength and the tensile elongation are stored as part of the logging data **203A** in the file group **203** of the hard disk device **112** so as to be included in the logging data **203A** acquired in step **ST201**.

[0100] FIG. **20** is a diagram illustrating the prediction result of the tensile strength of the heat-resistant insulated electric wire EW. FIG. **21** is a diagram illustrating the prediction result of the tensile elongation of the heat-resistant insulated electric wire EW. As illustrated in FIGS. **20** and **21**, a state of the changes in the respective predicted values of the tensile strength and the tensile elongation is acquired from the start to the end of the manufacture of the heat-resistant insulated electric wire EW, that is, over the entire length of the heat-resistant insulated electric wire EW. On the other hand, in a comparative example not using the technique of this example, the respective values of the tensile strength and the tensile elongation can be acquired only at several points of the end portion of the heat-resistant insulated electric wire EW. Therefore, the quality prediction system **100** in this example can predict the tensile strength and the tensile elongation over the entire

length of the heat-resistant insulated electric wire EW. Accordingly, the quality prediction system **100** can acquire a state of variations in the quality properties over the entire length of the heat-resistant insulated electric wire EW.

[0101] The quality prediction system **100** needs to create the quality prediction model **203C** from the logging data of the elongated product manufactured in past, that is, the already-known first logging data **203A1**. Accordingly, if the elongated product has been manufactured in past, the technique of the quality prediction system **100** can be applied to this elongated product.

Particularly, for the elongated product having a sufficient manufacturing track record, the accuracy of the predicted value can be enhanced. Accordingly, the quality prediction system **100** can greatly improve the effectiveness of the prediction of the quality property.

[0102] Further, the quality prediction system **100** can predict the quality properties of the elongated product, which are not only the tensile strength and the tensile elongation of the elongated product but also those such as the flame retardancy and the oil resistance allowed to be evaluated only by the destructive test for the end portion.

[0103] As described above, the quality prediction system **100** creates the quality prediction model **203C** by using not only the already-known first logging data **203A1** but also the first simulation data based on the already-known first logging data **203A1**. The quality prediction system **100** predicts the quality property of the elongated product by using not only the second logging data **203A2** during manufacture but also the second simulation data based on the second logging data **203A2** during manufacture and the quality prediction model **203C**. However, the processing for the quality prediction model creation and the quality prediction performed by the quality prediction system **100** are not limited to them. For example, the quality prediction system **100** may create a quality prediction model based on only the already-known first logging data **203A1**. The quality prediction system **100** may predict the quality property of the elongated product by using a quality prediction model created based on only the second logging data **203A2** during manufacture and the already-known first logging data **203A1**. This results in a reduced processing load of the quality prediction system **100**.

[0104] In the foregoing, the invention made by the present inventors of the present application has been concretely described on the basis of the embodiments. However, it is needless to say that the present invention is not limited to the foregoing embodiments, and various modifications can be made within the scope of the present invention.

Claims

1. A quality prediction model creation system comprising: a first logging data acquisition unit acquiring already-known first logging data respectively detected at every predetermined interval by a plurality of detectors and stored at time of manufacture of an elongated product; an average value calculation unit calculating each average value of the first logging data from the first logging data acquired by the first logging data acquisition unit; and a model creation unit creating a quality prediction model corresponded to quality property of the elongated product, based on the average value of the first logging data.
2. The quality prediction model creation system according to claim 1, further comprising a first simulation unit simulating the quality property of the elongated product by using the average value of the first logging data, wherein the model creation unit creates the quality prediction model, based on the average value of the first logging data and first simulation data representing a result of the simulation.
3. The quality prediction model creation system according to claim 2, further comprising a data merging unit acquiring quality result data of a quality test performed for an end portion of the elongated product, and merging the quality result data with the first simulation data, wherein, when the quality prediction model is created, the model creation unit uses a result of the merging made

by the data merging unit.

4. The quality prediction model creation system according to claim 2, wherein the model creation unit creates the quality prediction model by using machine learning while setting quality property data representing the quality property of the elongated product as an objective variable, and setting the first logging data of the elongated product and the first simulation data as an explanatory variable.

5. The quality prediction model creation system according to claim 4, wherein the elongated product is an electric wire covered with a heat-resistant insulating member, the electric wire is manufactured by an extruder including a cylinder including a screw and a winder winding the electric wire, and the explanatory variable includes at least one or more of a number of screw revolutions of the screw, a cylinder temperature of the cylinder, a linear speed of the winding of the electric wire by the winder, a retention time period of the heat-resistant insulating member in the cylinder, a pressure value of the heat-resistant insulating member, and a value of a strain of the heat-resistant insulating member.

6. The quality prediction model creation system according to claim 4, wherein the elongated product is an electric wire covered with a heat-resistant insulating member, and the objective variable includes a value of a tensile strength or a value of a tensile elongation of the electric wire.

7. A quality prediction system comprising: a quality prediction model storage unit storing a quality prediction model, created based on an average value of already-known first logging data of an elongated product and corresponded to quality property of the elongated product; a second logging data acquisition unit acquiring second logging data during manufacture of an elongated product as a prediction target; and a prediction unit predicting quality property of the elongated product as the prediction target by substituting the second logging data acquired by the second logging data acquisition unit into the quality prediction model.

8. The quality prediction system according to claim 7, further comprising a second simulation unit creating second simulation data by performing a simulation based on the second logging data acquired by the second logging data acquisition unit, wherein the prediction unit predicts the quality property of the elongated product as the prediction target by substituting the second logging data acquired by the second logging data acquisition unit and the second simulation data created by the second simulation unit into the quality prediction model.

9. The quality prediction system according to claim 8, wherein the second simulation unit performs the simulation based on logging data extracted at every predetermined interval from the second logging data acquired by the second logging data acquisition unit.

10. The quality prediction system according to claim 7, wherein the prediction unit stores quality property data representing the quality property together with the second logging data acquired by the second logging data acquisition unit.

11. A quality prediction model creation method comprising steps of: acquiring already-known first logging data respectively detected at every predetermined interval by a plurality of detectors and stored at time of manufacture of an elongated product; calculating each average value of the first logging data from the acquired first logging data; and creating a quality prediction model corresponded to quality property of the elongated product, based on the average value of the first logging data.

12. The quality prediction model creation method according to claim 11, further comprising steps of: calculating each average value of the first logging data, and then, simulating the quality property of the elongated product by using the average value of the first logging data; and creating the quality prediction model, based on the average value of the first logging data and first simulation data representing a result of the simulation.

13. A quality prediction method comprising steps of: acquiring already-known first logging data respectively detected at every predetermined interval by a plurality of detectors and stored at time of manufacture of an elongated product; calculating each average value of the first logging data

from the acquired first logging data; creating a quality prediction model corresponded to quality property of the elongated product, based on the average value of the first logging data; acquiring second logging data during manufacture of an elongated product as a prediction target; and predicting quality property of the elongated product as the prediction target by substituting the second logging data into the quality prediction model.

14. The quality prediction method according to claim 13, wherein the quality prediction model is created by the first logging data and first simulation data acquired based on the first logging data, the method further comprising steps of: acquiring the second logging data, and then, creating second simulation data by performing a simulation based on the second logging data; and substituting the second logging data and the second simulation data into the quality prediction model.
