

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279115

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

TAKAYAMA; Seiichi et al.

LIGHT SOURCE UNIT, THERMALLY ASSISTED MAGNETIC HEAD, HEAD GIMBAL ASSEMBLY, AND HARD DISK DRIVE

Abstract

The disclosure disclose a light source unit applied to the thermally assisted magnetic head. A welding layer and a stopping structure are disposed between the slider of the thermally assisted magnetic head and the light source unit. When the light source unit is joined with the slider, the light source unit moves as the welding layer melts and can be precisely limited at the preset position by the stopping structure. In this way, the emission opening of the light source unit and the waveguide can be aligned precisely, thereby increasing the optical coupling efficiency between the light source unit and the waveguide. Meanwhile, the embodiment of the disclosure further accordingly provides a thermally assisted magnetic head, a head gimbal assembly, and a hard disk drive.

Inventors: TAKAYAMA; Seiichi (Hong Kong, CN), FUJII; Ryuji (Hong Kong, CN), LEE; Tai Boon (Hong Kong, CN), WONG; Ka Yip (Hong Kong, CN)

Applicant: SAE Magnetics (H.K.) Ltd. (Hong Kong, CN)

Family ID: 96822937

Appl. No.: 18/807684

Filed: August 16, 2024

Foreign Application Priority Data

CN

202410228557.4

Feb. 29, 2024

Publication Classification

Int. Cl.: G11B5/31 (20060101); G11B5/00 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to CN 202410228557.4 filed Feb. 29, 2024, the entire contents of which are hereby incorporated by reference.

TECHNICAL FIELD

[0002] The present disclosure relates to the technical field of hard disk drives, more particularly to a light source unit, a thermally assisted magnetic head, a head gimbal assembly, and a hard disk drive.

BACKGROUND

[0003] The hard disk drive (HDD) is used for writing/reading data to/from a disk. As shown in FIG. 1, a hard disk drive **300** generally comprises a plurality of rotatable disks **301** connected to a spindle motor **302**, a drive arm **304**, and a head gimbal assembly (HGA) **200** mounted at an end of the drive arm **304**. Typically, the hard disk drive **300** may further include a voice-coil motor (VCM) to control the movement of the driving arm **304**. The head gimbal assembly **200** comprises a magnetic head **230** and a suspension **290** for supporting the magnetic head **230**. When the hard disk drive **300** works, the disk **301** is rotated at a high speed by the spindle motor **302**, and the magnetic head **230** flies above the disk due to the air pressure generated by the rotation of the disk **301**. Under the control of the voice-coil motor, the magnetic head **230** moves in a radial direction on the surface of the disk **301**. Concerning different tracks, the magnetic head **230** can read/write data from/to the disk **301**.

[0004] According to the technology of heat assisted magnetic recording (HAMR), the magnetic head comprises a slider and a light source unit (such as a laser diode) arranged on the slider. The light source unit provides energy to a part of the magnetic recording medium so as to reduce the coercive force the part. Furthermore, a write magnetic field can be applied to the part that is heated, to facilitate the write operation. Please referring to FIG. 2, for example, the light source unit **10** may be a laser diode, and in the LIT (LD In Trailing surface) structure, the trailing surface of the slider **50** may be provided with a cavity, in which the laser diode is placed. The laser emitted from the laser diode can be transmitted by the waveguide **20** and transduced into the near-field light by the surface plasmon antenna **30**, so as to heat the magnetic recording medium and reduce the coercive force of the magnetic recording medium to facilitate data writing on the magnetic recording medium by the magnetic head.

[0005] Please referring to FIG. 3, concerning the above LIT structure, in order to ensure the optical alignment between the emission opening **101** of the light source unit and the waveguide **20**, the following mechanical dimensions may be adjusted: (1) the distance d_1 between the emission opening **101** of the light source unit and the electrical connecting layer **102** of the light source unit; (2) the distance d_2 between the bottom surface of the cavity **60** of the slider **50** and the waveguide **20**; (3) the thickness d_3 of the welding layer **40** between the light source unit **10** and the slider **50**. In practical application, the abovementioned dimensions (1) and (2) can be precisely controlled. However, during use, as the thickness d_3 of the welding layer in the dimension (3) changes due to the melting, it is difficult to control the thickness of the welding layer between the light source unit and the slider which are joined. Hence, it is difficult to achieve precise optical alignment between the light source unit and the waveguide, and thus it is difficult to ensure the optical coupling efficiency between the light source unit and the waveguide.

SUMMARY

[0006] Aiming at the shortcomings of existing technologies, the embodiment of the disclosure

provides a light source unit, which is applied to a thermally assisted magnetic head. The thermally assisted magnetic head comprises a slider, and the slider is provided with a waveguide and with a first cavity for accommodating the light source unit; A welding layer and a stopping structure are provided between the light source unit and the slider; The light source unit is configured to move as the welding layer melts and can be limited at a preset position by the stopping structure, when joined with the slider. At the preset position, an emission opening of the light source unit aligns with the waveguide.

[0007] Preferably, the slider may comprise a slider body and a conductive layer, wherein the conductive layer may be connected to the slider body and the conductive layer may be provided for connecting with the welding layer; The light source unit may comprise a light source body and a first electrical connecting layer, the first electrical connecting layer may be connected with the light source body, and the welding layer may be configured to be provided on the first electrical connecting layer or the conductive layer.

[0008] Preferably, the stopping structure may comprise at least one stop. The stop may be configured to be provided on the light source unit, and the stop may move to abut against the slider as the welding layer melts when the light source unit is joined with the slider, alternatively,

[0009] The stop may be configured to be provided on the slider, and the stop may move to abut against the light source unit as the welding layer melts when the light source unit is joined with the slider.

[0010] Preferably, a first surface of the stop may be connected to the light source body, a second surface of the stop may abut against the slider body or the conductive layer when the light source unit is joined with the slider, and the first surface of the stop may be arranged opposite to the second surface of the stop.

[0011] Preferably, a number of the stops may be at least two. The at least two stops may define an interval space therebetween, and the first electrical connecting layer may be at least partially accommodated in the interval space;

[0012] In the case that the welding layer is provided on the first electrical connecting layer, the welding layer may protrude further than the second surface of the stop. When the light source unit is joined with the slider, the second surface of the stop may move to abut against the conductive layer as the welding layer melts, thereby limiting the light source unit at the preset position; alternatively,

[0013] In the case that the welding layer is provided on the first electrical connecting layer, the welding layer may protrude further than the second surface of the stop, or, the second surface of the stop may protrude further than the welding layer. When the light source unit is joined with the slider, the second surface of the stop may move to abut against the slider body as the welding layer melts, thereby limiting the light source unit at the preset position; alternatively,

[0014] In the case that the welding layer is provided on the conductive layer, the second surface of the stop may move to abut against the conductive layer or the slider body as the welding layer melts when the light source unit is joined with the slider, thereby limiting the light source unit at the preset position.

[0015] Preferably, the at least two stops may be arranged to define an interval space, and the at least two stops may extend along a length direction or a width direction of the light source body.

[0016] Preferably, the stop may extend along a length direction of the light source body, and a length of the stop is less than a length of the light source unit.

[0017] Preferably, the light source unit may be a laser diode, and the light source body may comprise a substrate, the light source body may be formed by a deposition on the substrate, the stop may be formed in a deposition process of the light source body, and a material of the stop may be the same as a material of the light source body.

[0018] Preferably, both the stop and the light source body may be made of GaAs.

[0019] Preferably, the light source unit may be a laser diode, and the light source body may

comprise a substrate, the light source body may be formed by a deposition on the substrate, the stop may be formed after a deposition process of the light source body, and a material of the stop may be different from a material of the light source body.

[0020] Preferably, the stop may be made of a dielectric material.

[0021] Preferably, the stop may be formed in a wafer process of the slider.

[0022] Preferably, the stop may have a length less than a length of the light source unit.

[0023] Preferably, the stopping structure may comprise a second cavity and the first cavity, the second cavity may be provided in the slider body, and the second cavity may be in communication with the first cavity, to form a double-cavity structure with a step; the conductive layer may be connected to the slider body and accommodated in the second cavity; when the light source unit is joined with the slider, the light source body or the first electrical connecting layer move to abut against the step as the welding layer melts, thereby limiting the light source unit at the preset position.

[0024] In order to solve same technical problems, an embodiment of the disclosure further provides a thermally assisted magnetic head, which comprises the slider and the light source unit, and the light source unit is joined with the slider.

[0025] In order to solve same technical problems, an embodiment of the disclosure further provides a head gimbal assembly, which comprises the thermally assisted magnetic head.

[0026] In order to solve same technical problems, an embodiment of the disclosure further provides a hard disk drive, which comprises the head gimbal assembly.

[0027] Compared with existing technologies, the embodiment of the disclosure has advantages as follows. The embodiment of the disclosure provides the light source unit which can be applied to the thermally assisted magnetic head, and the welding layer and the stopping structure are disposed between the slider of the thermally assisted magnetic head and the light source unit. The light source unit moves as the welding layer melts and can be precisely limited at the preset position by the stopping structure, when joined with the slider. Consequently, the emission opening of the light source unit and the waveguide can be aligned precisely, thereby increasing the optical coupling efficiency between the light source unit and the waveguide. Meanwhile, the embodiments of the disclosure further provide the thermally assisted magnetic head, the head gimbal assembly, and the hard disk drive, accordingly.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] FIG. 1 is a structural schematic view of a hard disk drive in related art;

[0029] FIG. 2 is a structural schematic view of an LIT structure in related art;

[0030] FIG. 3 is a view illustrating a position relationship between a light source unit and a waveguide in related art;

[0031] FIG. 4 is a structural schematic view of a light source unit according to an embodiment of the disclosure;

[0032] FIG. 5 is a top view of a light source unit according to an embodiment of the disclosure;

[0033] FIG. 6 is a side view of a light source unit according to an embodiment of the disclosure;

[0034] FIG. 7 is a bottom view of a light source unit according to an embodiment of the disclosure;

[0035] FIG. 8 is a schematic view illustrating a light source unit and a slider which are joined according to an embodiment of the disclosure;

[0036] FIG. 9 is a schematic view illustrating a first way to assemble a light source unit and a slider according to an embodiment of the disclosure;

[0037] FIG. 10 is a schematic view illustrating a second way to assemble a light source unit and a slider according to an embodiment of the disclosure;

[0038] FIG. **11** is a schematic view illustrating a third way to assemble a light source unit and a slider according to an embodiment of the disclosure;

[0039] FIG. **12** is a schematic view illustrating a fourth way to assemble a light source unit and a slider according to an embodiment of the disclosure;

[0040] FIG. **13** is a schematic view illustrating a fifth way to assemble a light source unit and a slider according to an embodiment of the disclosure;

[0041] FIG. **14** is a schematic view illustrating a light source unit and a slider which are joined according to an embodiment of the disclosure;

[0042] FIG. **15** is a flow chart illustrating a preparation method for a light source unit according to an embodiment of the disclosure;

[0043] FIG. **16** is a top view of a light source unit with an end coating according to an embodiment of the disclosure;

[0044] FIG. **17** is a side view of a light source unit with an end coating according to an embodiment of the disclosure;

[0045] FIG. **18** is a bottom view of a light source unit with an end coating according to an embodiment of the disclosure;

[0046] FIG. **19** is a schematic view illustrating a light source unit and a slider with a second cavity are assembled according to an embodiment of the disclosure

[0047] Herein: **300.** hard disk drive; **302.** spindle motor; **301.** disk; **304.** drive arm; **200.** head gimbal assembly; **230.** magnetic head; **290.** suspension; **10.** light source unit; **101.** emission opening of light source unit; **102.** electrical connecting layer of light source unit; **20.** waveguide; **30.** surface plasmon antenna; **40.** welding layer; **50.** slider; **60.** cavity; **1.** light source unit; **11.** emission opening of light source unit; **12.** light source body; **13.** first electrical connecting layer; **14.** second electrical connecting layer; **2.** slider; **21.** slider body; **22.** conductive layer; **3.** waveguide; **4.** first cavity; **5.** welding layer; **6.** stopping structure; **61.** stop; **62.** second cavity; **7.** substrate; **8.** end coating.

DETAILED DESCRIPTION OF ILLUSTRATED EMBODIMENTS

[0048] The technical solutions according to the embodiments of the present disclosure will be clearly and completely explained below in conjunction with the drawings for the embodiments. Apparently, the described embodiments are merely a part rather than all of the embodiments of the present disclosure. All embodiments obtained by those skilled in the art based on the embodiments of the present disclosure without creative work shall fall within the scope of the present disclosure.

[0049] Please refer to FIG. **4**, which is a structural schematic view of a light source unit according to an embodiment of the disclosure.

[0050] In the embodiment of the disclosure, the light source unit **1** is applied to a thermally assisted magnetic head. The thermally assisted magnetic head comprises a slider **2**, and the slider **2** is provided with a waveguide **3** and with a first cavity **4** for accommodating the light source unit **1**. A welding layer **5** and a stopping structure **6** are provided between the light source unit **1** and the slider **2**. The light source unit **1** is configured to move as the welding layer **5** melts and can be limited at a preset position by the stopping structure **6**, when joined with the slider **2**. At the preset position, an emission opening **11** of the light source unit **1** aligns with the waveguide **3**.

[0051] In the embodiment of the disclosure, the welding layer **5** and the stopping structure **6** are disposed between the slider **2** of the thermally assisted magnetic head and the light source unit **1**. Thus, when the light source unit **1** is joined with the slider **2**, the light source unit **1** moves as the welding layer **5** melts and can be precisely limited at the preset position by the stopping structure **6**. In such a case, the emission opening **11** of the light source unit **1** and the waveguide **3** can be aligned precisely, thereby increasing the optical coupling efficiency between the light source unit **1** and the waveguide **3**.

[0052] Please referring to FIGS. **4-7**, in a particular implementation, the light source unit **1** comprises a light source body **12** and a first electrical connecting layer **13**, and the first electrical

connecting layer **13** is connected with a first surface of the light source body **12**. In a particular implementation, the light source unit **1** may further comprise a second electrical connecting layer **14**, the second electrical connecting layer **14** may be connected with a second surface of the light source body **12**, and the first surface of the light source body **12** may be arranged opposite to the second surface of the light source body **12**. Illustratively, the light source unit **1** may be a laser diode (LD). The first electrical connecting layer **13** of the light source unit **1** may serve as the N connecting electrode of the laser diode, and the second electrical connecting layer **14** of the light source unit **1** may serve as the P connecting electrode of the laser diode. Alternatively, the first electrical connecting layer **13** of the light source unit **1** may serve as the P connecting electrode of the laser diode, and the second electrical connecting layer **14** of the light source unit **1** may serve as the N connecting electrode of the laser diode. In practical application, the light source unit **1** may be controlled to operate depending on the power supply to the first electrical connecting layer **13** and the second electrical connecting layer **14** of the light source unit **1**. The HAMR structure in the present embodiment is LIT structure, i.e., a structure in which the laser diode is placed in the trailing surface of the slider **2**.

[0053] Please referring to FIG. **8**, in a particular implementation, the slider **2** may comprise a slider body **21** and a conductive layer **22**, wherein the conductive layer **22** may be connected to the slider body **21** and the conductive layer **22** may be provided for connecting with the welding layer **5**. In practical application, when the light source unit **1** is joined with the slider **2**, the conductive layer **22** and the first electrical connecting layer **13** respectively come into contact with the welding layer **5**, and melt the welding layer **5** by heating (for example, heating the slider **2** such that the welding layer **5** can be melt due to the heat energy transferred to the welding layer **5**), thereby enabling the light source unit **1** to join with the slider **2**. In particular, the first electrical connecting layer **13** of the light source unit **1** may be connected to an external control circuit through the welding layer **5** and the conductive layer **22**, and the second electrical connecting layer **14** of the light source unit **1** may be connected to an external control circuit, such that the light source unit **1** can be controlled by the external control circuit. Illustratively, the conductive layer **22** for example may be a gold layer. Apparently, the conductive layer **22** may use other conductive materials according to actual use requirements and details will not be repeated here.

[0054] Please referring to FIGS. **9-13**, in an optional example, the stopping structure **6** may comprise at least one stop **61**. The stop **61** may be configured to be provided on the light source unit **1**, and the stop **61** may move to abut against the slider **2** as the welding layer **5** melts when the light source unit **1** is joined with the slider **2**. Alternatively, the stop **61** may be configured to be provided on the slider **2**, and the stop **61** may move to abut against the light source unit **1** as the welding layer **5** melts when the light source unit **1** is joined with the slider **2**.

[0055] In a particular implementation, the stop **61** may be positioned in two ways. In the first way, before the light source unit **1** is joined with the slider **2**, the stop **61** may be provided on the light source unit **1**. When the light source unit **1** is joined with the slider **2**, the welding layer **5** is heated and melts. At that time, as the welding layer **5** melts, the stop **61** moves along with the light source unit **1** and stops when the stop **61** comes into contact with the slider **2**. By this time, the light source unit **1** arrives at the preset position. In the second way, before the light source unit **1** is joined with the slider **2**, the stop **61** is provided on the slider **2**. When the light source unit **1** is joined with the slider **2**, the welding layer **5** is heated and melts. At that time, the stop **61** and the light source unit **1** simultaneously move as the welding layer **5** melts and stop when the stop **61** comes into contact with the light source unit **1**. By this time, the light source unit **1** arrives at the preset position. Consequently, in the present embodiment, the emission opening **11** of the light source unit **1** and the waveguide **3** can be aligned precisely, thereby increasing the optical coupling efficiency between the light source unit **1** and the waveguide **3**.

[0056] In an optional example, the first surface of the stop **61** may be connected to the light source body **12**, the second surface of the stop **61** may abut against the slider body **21** or the conductive

layer 22 when the light source unit 1 is joined with the slider 2, and the first surface of the stop 61 may be arranged opposite to the second surface of the stop 61.

[0057] In the present embodiment, the stopping structure 6 comprises at least one stop 61 provided on the light source body 12. When the light source unit 1 is joined with the slider 2, the welding layer 5 is heated and melts, and both the stop 61 and the light source unit 1 simultaneously move towards the slider 2. Once the stop 61 comes into contact with the slider body 21 or the conductive layer 22, the stop 61 and the light source unit 1 stop moving, thereby ensuring that the light source unit 1 is stopped at the preset position.

[0058] In a particular implementation, the first surface of the stop 61 may be connected to the light source body 12, and the welding layer 5 may be provided on the first electrical connecting layer 13 or the conductive layer 22. Illustratively, a number of the stops 61 may be at least two. The at least two stops 61 may define an interval space therebetween, and the first electrical connecting layer 13 may be at least partially accommodated in the interval space. It should be explained that, in order to facilitate the accommodation of the solder of the melted welding layer 5, the welding layer 5 may be designed with a length less than that of the stop 61; alternatively, a certain gap may be provided between the first electrical connecting layer 13 and the stop 61; alternatively, a certain gap may be provided between the welding layer 5 and the stop 61; alternatively, a certain gap may be provided between the conductive layer 22 and the stop 61. Illustratively, referring to FIGS. 9-13, 5 ways of assembling the light source unit 1 and the slider 2 are listed below.

[0059] Please refer to FIG. 9, which is a schematic view illustrating a first way to assemble the light source unit 1 and the slider 2 according to the embodiment of the disclosure. In the case that the welding layer 5 is provided on the first electrical connecting layer 13, the welding layer 5 may protrude further than the second surface of the stop 61. When the light source unit 1 is joined with the slider 2, the second surface of the stop 61 may move to abut against the conductive layer 22 as the welding layer 5 melts, whereby the light source unit 1 can be limited at the preset position.

[0060] In the present embodiment, before the light source unit 1 is joined with the slider 2, the welding layer 5 is provided on the first electrical connecting layer 13, and the welding layer 5 protrudes further than the second surface of the stop 61. Thus, when the light source unit 1 is joined with the slider 2, the welding layer 5 may be brought into contact with the conductive layer 22, and the welding layer 5 may be heated to melt. As the welding layer 5 melts, the stop 61 and the light source unit 1 move simultaneously. At last, the stop 61 may abut against the conductive layer 22. At this moment, the light source unit 1 is stopped at the preset position, and the welding layer 5 is accommodated in the interval space.

[0061] Please refer to FIG. 10, which is a schematic view illustrating a second way to assemble the light source unit 1 and the slider 2 according to the embodiment of the disclosure. In the case that the welding layer 5 is provided on the first electrical connecting layer 13, the welding layer 5 may protrude further than the second surface of the stop 61. When the light source unit 1 is joined with the slider 2, the second surface of the stop 61 may move to abut against the slider body 21 as the welding layer 5 melts, whereby the light source unit 1 can be limited at the preset position.

[0062] In the present embodiment, before the light source unit 1 is joined with the slider 2, the welding layer 5 is provided on the first electrical connecting layer 13, and the welding layer 5 protrudes further than the second surface of the stop 61. When the light source unit 1 is joined with the slider 2, the welding layer 5 may be brought into contact with the conductive layer 22, and the welding layer 5 may be heated to melt. As the welding layer 5 melts, the stop 61 and the light source unit 1 move simultaneously. At last, the stop 61 may abut against the slider body 21. At this moment, the light source unit 1 is stopped at the preset position, and the welding layer 5 and the conductive layer 22 are accommodated in the interval space.

[0063] Please refer to FIG. 11, which is a schematic view illustrating a third way to assemble the light source unit 1 and the slider 2 according to the embodiment of the disclosure. In the case that the welding layer 5 is provided on the first electrical connecting layer 13, the second surface of the

stop **61** may protrude further than the welding layer **5**. When the light source unit **1** is joined with the slider **2**, the second surface of the stop **61** may move to abut against the slider body **21** as the welding layer **5** melts, whereby the light source unit **1** can be limited at the preset position.

[0064] In the present embodiment, before the light source unit **1** is joined with the slider **2**, the welding layer **5** is provided on the first electrical connecting layer **13**, and the second surface of the stop **61** protrudes further than the welding layer **5**. When the light source unit **1** is joined with the slider **2**, the welding layer **5** may be brought into contact with the conductive layer **22**, and the welding layer **5** may be heated to melt. As the welding layer **5** melts, the stop **61** and the light source unit **1** move simultaneously. At last, the stop **61** may abut against the slider body **21**. At this moment, the light source unit **1** is stopped at the preset position, and the welding layer **5** and the conductive layer **22** are accommodated in the interval space.

[0065] Please refer to FIG. **12**, which is a schematic view illustrating a fourth way to assemble the light source unit **1** and the slider **2** according to the embodiment of the disclosure. In the case that the welding layer **5** is provided on the conductive layer **22**, the second surface of the stop **61** may move to abut against the conductive layer **22** as the welding layer **5** melts when the light source unit **1** is joined with the slider **2**, whereby the light source unit **1** can be limited at the preset position.

[0066] In the present embodiment, before the light source unit **1** is joined with the slider **2**, the welding layer **5** is provided on the conductive layer **22**. When the light source unit **1** is joined with the slider **2**, the welding layer **5** may be brought into contact with the first electrical connecting layer **13**, and the welding layer **5** may be heated to melt. As the welding layer **5** melts, the stop **61** and the light source unit **1** move simultaneously. At last, the stop **61** may abut against the conductive layer **22**. At this moment, the light source unit **1** is stopped at the preset position, and the welding layer **5** is accommodated in the interval space.

[0067] Please refer to FIG. **13**, which is a schematic view illustrating a fifth way to assemble the light source unit **1** and the slider **2** according to the embodiment of the disclosure. In the case that the welding layer **5** is provided on the conductive layer **22**, the second surface of the stop **61** may move to abut against the slider body **21** as the welding layer **5** melts when the light source unit **1** is joined with the slider **2**, whereby the light source unit **1** can be limited at the preset position.

[0068] In the present embodiment, before the light source unit **1** is joined with the slider **2**, the welding layer **5** is provided on the conductive layer **22**. When the light source unit **1** is joined with the slider **2**, the welding layer **5** may be brought into contact with the first electrical connecting layer **13**, and the welding layer **5** may be heated to melt. As the welding layer **5** melts, the stop **61** and the light source unit **1** move simultaneously. At last, the stop **61** may abut against the conductive layer **22**. At this moment, the light source unit **1** is stopped at the preset position, and the welding layer **5** and the conductive layer **22** are accommodated in the interval space.

[0069] Please referring to FIGS. **4-8** and **14**, in an optional example, the at least two stops **61** are arranged to define an interval space, and the at least two stops **61** extend along the length direction or width direction of the light source body **12**.

[0070] Illustratively, please referring to FIGS. **4-8**, a number of the stops **61** in the present embodiment may be two. The two stops **61** may have a cuboid structure. The two stops **61** may be arranged to define an interval space and extend along the length direction of the light source body **12** in such a manner that the stops **61** can be reliably stopped at the slider **2**.

[0071] Illustratively, please referring to FIG. **14**, a number of the stops **61** in the present embodiment may be two. The two stops **61** may be arranged to define an interval space and extend along the width direction of the light source body **12**, thereby allowing the stops **61** to be reliably stopped at the slider **2**.

[0072] In a particular implementation, the at least two stops **61** may be arranged substantially in parallel, thereby further allowing the stops **61** to be reliably stopped at the slider **2**. In addition, the two stops **61** may have a cuboid structure, or U-shaped structure, or L-shaped structure, or other

structures. Apparently, the stops **61** may be designed to have other shapes according to actual use requirements and details will not be repeated here. Preferably, the second surface of the stop **61** may be a flat surface, to further ensure that the stops **61** can be reliably stopped at the slider **2**. [0073] Please referring to FIGS. **16-18**, in an optional example, the stop **61** may extend along the length direction of the light source unit **1**, and the length **L1** of the stop **61** is less than the length **L2** of the light source unit **1**. In a particular implementation, the light source unit **1** may be further provided with an end coating **8**. In order to avoid the overlapping of the end coating **8** and the stop **61** which may result in falling off of the end coating **8**, the stop **61** in the present embodiment may have a length less than the length of the light source unit **1**.

[0074] In an optional example, the light source unit **1** may be a laser diode, and the light source body **12** may comprise a substrate **7**. The light source body **12** may be formed by a deposition process on the substrate **7**, the stop **61** may be formed in the deposition process of the light source body **12**, and the material of the stop **61** may be the same as the material of the light source body **12**. Illustratively, both the stop **61** and the light source body **12** may be made of GaAs.

[0075] Please referring to FIG. **15**, in a particular implementation, in order to form the stop **61**, firstly conducting PN-layer deposition on the GaAs substrate **7**. Then, using GaAs material to deposit the stop **61** (for example, forming a step structure). Then, preparing the first electrical connecting layer **13** and the welding layer **5**. Finally, conducting backside grind for the laser diode, and preparing the second electrical connecting layer **14**. For example, the first electrical connecting layer **13** and the second electrical connecting layer **14** may be gold layers.

[0076] In practical application, the PN-layer deposition process of the laser diode usually uses the Metal-organic Chemical Vapor Deposition (MO-CVD) method or the Molecular beam epitaxy (MBE) method. These methods can achieve a precise control of the deposition thickness. Hence, as the stop **61** in the present embodiment is formed in the deposition process of the light source body **12**, the thickness of the stop **61** can be precisely controlled, thereby ensuring that the light source unit **1** can be precisely limited at the preset position by the stop **61** when the light source unit **1** is joined with the slider **2**. Thus, a precise alignment between the emission opening **11** of the light source unit **1** and the waveguide **3** can be ensured, thereby increasing the optical coupling efficiency between the light source unit **1** and the waveguide **3**.

[0077] In an optional example, the light source unit **1** may be a laser diode, the light source body **12** may comprise a substrate **7**, the light source body **12** may be formed by a deposition process on the substrate **7**, the stop **61** may be formed after the deposition process of the light source body **12**, the material of the stop **61** may be different from the material of the light source body **12**. The stop **61** may be made of a dielectric material. Illustratively, the stop **61** may be made of at least one of SiO.sub.2, SiN, and AlO.

[0078] It should be noted that the stop **61** may be provided on the slider **2**, and the stop **61** may be formed in the wafer process of the slider **2**. The stop **61** may be made of a dielectric material. Illustratively, the stop **61** may be made of at least one of SiO.sub.2, SiN, and AlO.

[0079] In a particular implementation, it is generally required that the accuracy of the optical alignment of the light source unit **1** and the waveguide **3** in the Y direction is at a level less than $\pm 0.45\text{ }\mu\text{m}$. Please referring to FIG. **8**, the structure of the light source unit **1** in the embodiment of the disclosure uses the deposition process, ensuring that the accuracy **30** of the distance **D1** between the second surface (i.e., the joint surface of the light source unit **1**) of the stop **61** and the emission opening **11** of the light source unit **1** is $0.3\text{ }\mu\text{m}$. In the structure of the slider **2**, the accuracy **30** of the distance **D2** between the bottom surface (i.e., the joint surface of the slider **2**) of the first cavity **4** and the waveguide **3** is $0.3\text{ }\mu\text{m}$. After the welding layer **5** is melted, the stop **61** comes into contact with the slider **2**, and the thickness of the welding layer **5** that is welded can be accurately maintained at a same size. In overall, $3\sigma = \sqrt{(0.3.\text{sup.}2 + 0.3.\text{sup.}2)}$, approximately 0.42 , and thus meets the required accuracy $\pm 0.45\text{ }\mu\text{m}$.

[0080] Please referring to FIG. **19**, in a further optional example, the stopping structure **6** may

comprise a second cavity **62** and the first cavity **4**, the second cavity **62** is provided in the slider body **21**, and the second cavity **62** is in communication with the first cavity **4**, to form a double-cavity structure with a step. The conductive layer **22** is connected to the slider body **21** and is accommodated in the second cavity **62**. When the light source unit **1** is joined with the slider **2**, the light source body **12** or the first electrical connecting layer **13** move to abut against the step as the welding layer **5** melts, thereby limiting the light source unit **1** at the preset position.

[0081] In the present embodiment, as the second cavity **62** in communication with the first cavity **4** is provided in the slider **2**, the double-cavity structure can be formed. The double-cavity structure has a step, and the conductive layer **22** is accommodated in the second cavity **62**. Consequently, when the light source unit **1** is joined with the slider **2**, the welding layer **5** which sandwiched between the first electrical connecting layer **13** and the conductive layer **22** can be heated to melt. The light source unit **1** may move as the welding layer **5** melts and finally stop when it comes into contact with the slider body **21**, in particular stop at the step of the double-cavity structure. At this moment, the light source unit **1** is stepped at the preset position, and the welding layer **5** and the conductive layer **22** are accommodated in the second cavity **62**. It should be explained that, in order to facilitate the accommodation of the solder of the melted welding layer **5**, a certain gap may be provided between the welding layer **5** and the second cavity **62**; alternatively, a certain gap may be provided between the conductive layer **22** and the second cavity **62**.

[0082] In the present embodiment, before the light source unit **1** is joined with the slider **2**, the welding layer **5** may be provided on the first electrical connecting layer **13** or the conductive layer **22**. In particular, in the case that the welding layer **5** is provided on the first electrical connecting layer **13** before the light source unit **1** is joined with the slider **2**, the welding layer **5** may be brought into contact with the conductive layer **22** and heated to melt when the light source unit **1** is joined with the slider **2**. The light source unit **1** may move as the welding layer **5** melts, and finally stop when the first electrical connecting layer **13** or the light source body **12** comes into contact with the slider body **21**. At this moment, the light source unit **1** is stopped at the preset position, and the welding layer **5** and the conductive layer **22** are accommodated in the second cavity **62**. Herein, in the case that the size of the first electrical connecting layer **13** is less than the second cavity **62**, the light source body **12** can come into contact with the slider body **21** and be stopped (not shown in the drawings). In the case that the size of the first electrical connecting layer **13** is greater than the second cavity **62**, the first electrical connecting layer **13** can come into contact with the slider body **21** and be stopped (as shown in FIG. 19).

[0083] Accordingly, an embodiment of the disclosure further provides a thermally assisted magnetic head **230**, which comprises the slider **2** and the light source unit **1**, and the light source unit **1** is joined with the slider **2**.

[0084] Accordingly, an embodiment of the disclosure further provides a head gimbal assembly **200**, which comprises the thermally assisted magnetic head **230**.

[0085] Accordingly, an embodiment of the disclosure further provides a head gimbal assembly **200**. Please referring to FIG. 1, the head gimbal assembly **200** comprises the thermally assisted magnetic head.

[0086] Accordingly, referring to FIG. 1, a hard disk drive **300** is further provided in an embodiment of the disclosure, which comprises the head gimbal assembly **200**. In a particular implementation, the hard disk drive **300** may further comprise a plurality of rotatable disks **301** connected with the spindle motor **302** and a drive arm **304**, and the head gimbal assembly **200** is mounted at an end of the drive arm **304**. Generally, the hard disk drive **300** may further comprise a voice-coil motor for control the movement of the drive arm **304**. When the hard disk drive **300** works, the disks **301** are rotated at a high speed by the spindle motor **302**, and the magnetic head flies above the disks due to the air pressure generated by the rotation of the disks **301**. Under the control of the voice-coil motor, the magnetic head moves in a radial direction on the surface of the disks **301**. Concerning different tracks, the magnetic head can read/write data from/to the disks **301**.

[0087] Compared with existing technologies, the embodiment of the disclosure has advantages as follows. The embodiment of the disclosure provides the light source unit **1** which can be applied to the thermally assisted magnetic head, and the welding layer **5** and the stopping structure **6** are disposed between the slider **2** of the thermally assisted magnetic head and the light source unit **1**. The light source unit **1** moves as the welding layer **5** melts and can be precisely limited at the preset position by the stopping structure **6**, when joined with the slider **2**. Consequently, the emission opening **11** of the light source unit **1** and the waveguide **3** can be aligned precisely, thereby increasing the optical coupling efficiency between the light source unit **1** and the waveguide **3**. Meanwhile, the embodiments of the disclosure further provide the thermally assisted magnetic head, the head gimbal assembly, and the hard disk drive.

[0088] All the above are merely preferred embodiments of the present disclosure. It should be noted that those skilled in the art may obtain modifications and equivalents without departing from the technical principle of the present disclosure. The invention is intended to cover all modifications and equivalents included within the scope of the present disclosure.

Claims

1. A light source unit, wherein the light source unit is applicable for a thermally assisted magnetic head, the thermally assisted magnetic head comprises a slider, and the slider is provided with a waveguide and with a first cavity for accommodating the light source unit; a welding layer and a stopping structure are provided between the light source unit and the slider; the light source unit is configured to move as the welding layer melts and be limited at a preset position by the stopping structure, when joined with the slider, and at the preset position, an emission opening of the light source unit aligns with the waveguide.
2. The light source unit according to claim 1, wherein the slider comprises a slider body and a conductive layer, wherein the conductive layer is connected to the slider body and the conductive layer is provided for connecting with the welding layer; the light source unit comprises a light source body and a first electrical connecting layer, the first electrical connecting layer is connected with the light source body, and the welding layer is configured to be provided on the first electrical connecting layer or the conductive layer.
3. The light source unit according to claim 2, wherein the stopping structure comprise at least one stop; the stop is configured to be provided on the light source unit, and the stop is allowed to move to abut against the slider as the welding layer melts when the light source unit is joined with the slider, or, the stop is configured to be provided on the slider, and the stop is allowed to move to abut against the light source unit as the welding layer melts when the light source unit is joined with the slider.
4. The light source unit according to claim 3, wherein a first surface of the stop is connected to the light source body, a second surface of the stop abuts against the slider body or the conductive layer when the light source unit is joined with the slider, and the first surface of the stop is arranged opposite to the second surface of the stop.
5. The light source unit according to claim 4, wherein a number of the stops is at least two, the at least two stops define an interval space therebetween, and the first electrical connecting layer is at least partially accommodated in the interval space; if the welding layer is configured to be provided on the first electrical connecting layer, the welding layer protrudes further than the second surface of the stop, the second surface of the stop is allowed to move to abut against the conductive layer as the welding layer melts when the light source unit is joined with the slider, such that the light source unit is stopped at the preset position; or, if the welding layer is configured to be provided on the first electrical connecting layer, the welding layer protrudes further than the second surface of the stop, or, the second surface of the stop protrudes further than the welding layer, to allow the second surface of the stop to move to abut against the slider body as the welding layer melts when

the light source unit is joined with the slider, such that the light source unit is stopped at the preset position; or, if the welding layer is configured to be provided on the conductive layer, the second surface of the stop is allowed to move to abut against the conductive layer or the slider body as the welding layer melts when the light source unit is joined with the slider, such that the light source unit is stopped at the preset position.

6. The light source unit according to claim 3, wherein the at least two stops are arranged to define an interval space, and the at least two stops extend along a length direction or a width direction of the light source body.

7. The light source unit according to claim 3, wherein the stop extends along a length direction of the light source body, and a length of the stop is less than a length of the light source unit.

8. The light source unit according to claim 3, wherein the light source unit is a laser diode, and the light source body comprises a substrate, the light source body is formed by a deposition on the substrate, the stop is formed in a deposition process of the light source body, and a material of the stop is the same as that of the light source body.

9. The light source unit according to claim 8, wherein both the stop and the light source body are made of GaAs.

10. The light source unit according to claim 3, wherein the light source unit is a laser diode, and the light source body comprises a substrate, the light source body is formed by a deposition on the substrate, the stop is formed after a deposition process of the light source body, and a material of the stop is different from that of the light source body.

11. The light source unit according to claim 10, wherein the stop is made of a dielectric material.

12. The light source unit according to claim 3, wherein the stop is formed in a wafer process of the slider.

13. The light source unit according to claim 2, wherein the stopping structure comprise a second cavity and the first cavity, the second cavity is provided in the slider body, and the second cavity is in communication with the first cavity, to form a double-cavity structure having a step, the conductive layer is connected to the slider body and accommodated in the second cavity; when the light source unit is joined with the slider, the light source body or the first electrical connecting layer is allowed to move to abut against the step as the welding layer melts, such that the light source unit is stopped at the preset position.

14. A thermally assisted magnetic head, comprising the slider and the light source unit according to claim 1, and the light source unit is joined with the slider.

15. A head gimbal assembly, comprising the thermally assisted magnetic head according to claim 14.

16. A hard disk drive, comprising the head gimbal assembly according to claim 15.
