

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280662

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

LOU; Junhui et al.

DISPLAY PANEL AND DISPLAY DEVICE

Abstract

Embodiments of the present disclosure provide a display panel and a display device. The display panel includes: a substrate; a pixel defining layer; an isolation structure disposed on the substrate, an orthographic projection of the isolation structure on the substrate being located outside an orthographic projection of the pixel opening on the substrate, and the isolation structure including a first isolation structure and a second isolation structure which are spaced apart and insulated from each other; and a functional layer including a first electrode, a touch electrode and a second electrode. The touch electrode is configured to implement a touch function of the display panel, and the functional layer includes both the touch electrode and the first electrode. The functional layer also includes the second electrode, and by rationally positioning the touch electrode and the second electrode.

Inventors: LOU; Junhui (Langfang, CN), WANG; Lihua (Hefei, CN)

Applicant: Yungu (Gu'an) Technology Co., Ltd. (Langfang, CN); Hefei Visionox Technology Co., Ltd. (Hefei, CN)

Family ID: 96816159

Assignee: Yungu (Gu'an) Technology Co., Ltd. (Langfang, CN); Hefei Visionox Technology Co., Ltd. (Hefei, CN)

Appl. No.: 19/010210

Filed: January 06, 2025

Foreign Application Priority Data

CN

202410232781.0

Feb. 29, 2024

Publication Classification

Int. Cl.: H10K59/122 (20230101); H10K59/40 (20230101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

[0001] The present application claims priority to Chinese Patent Application No. 202410232781.0 filed on Feb. 29, 2024, and titled “DISPLAY PANEL AND DISPLAY DEVICE”, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0002] The present disclosure relates to the technical field of display equipment, and particularly to a display panel and a display device.

BACKGROUND ART

[0003] An organic light-emitting diode (OLED) is an active light-emitting device. Compared with a conventional liquid crystal display (LCD) method, OLED display technology does not require a backlight and has self-luminous properties. OLED display panels can significantly save energy and be made lighter and thinner, tolerate a wider range of temperature changes than LCD display panels, and have a larger viewing angle.

SUMMARY OF THE INVENTION

[0004] Embodiments of the present disclosure provide a display panel and a display device, with a view to simplifying the structure of the display panel.

[0005] An embodiment in a first aspect of the present disclosure provides a display panel. The display panel includes: a substrate; a pixel defining layer disposed on the substrate and including a pixel defining portion and a pixel opening within which a light-emitting unit is disposed; an isolation structure disposed on the substrate, an orthographic projection of the isolation structure on the substrate being located outside an orthographic projection of the pixel opening on the substrate, and the isolation structure including a first isolation structure and a second isolation structure which are spaced apart and insulated from each other; and a functional layer including a first electrode, a touch electrode and a second electrode which are insulated and spaced apart from each other, the first electrode being located on a side of the light-emitting unit away from the substrate, the touch electrode being located on a side of the first isolation structure away from the substrate, and the second electrode being located on a side of the second isolation structure away from the substrate.

[0006] According to an implementation of the first aspect of the present disclosure, the display panel includes a plurality of touch areas, each of the touch areas is provided with the touch electrode, a non-touch area is formed between two adjacent ones of the touch areas, and the non-touch area is provided with the second electrode.

[0007] According to any one of the foregoing implementations of the first aspect of the present disclosure, the plurality of touch areas are distributed in an array in a first direction and a second direction.

[0008] According to any one of the foregoing implementations of the first aspect of the present disclosure, the touch electrode includes: [0009] a first touch portion arranged to extend in the first direction, a plurality of first touch portions being distributed at intervals in the second direction; and [0010] a second touch portion connecting two adjacent ones of the first touch portions; [0011] where a plurality of pixel openings are distributed in an array in the first direction and the second direction, two or more rows of pixel openings are arranged between two adjacent ones of the first touch portions, and the second electrode is correspondingly arranged between the two adjacent

ones of the first touch portions and between two adjacent rows of pixel openings.

[0012] According to any one of the foregoing implementations of the first aspect of the present disclosure, the width of the second electrode in the second direction is the same as the width of the first touch portion in the second direction.

[0013] According to any one of the foregoing implementations of the first aspect of the present disclosure, the first electrode includes a first sub-electrode portion and a second sub-electrode portion, the first sub-electrode portion being located between two adjacent ones of the first touch portions, a plurality of first sub-electrode portions being arranged at intervals in the second direction, and the second sub-electrode portion connecting two adjacent ones of the first sub-electrode portions.

[0014] According to any one of the foregoing implementations of the first aspect of the present disclosure, at least a part of the second sub-electrode portion and the second touch portion are respectively arranged on two sides of the same first touch portion in the first direction.

[0015] According to any one of the foregoing implementations of the first aspect of the present disclosure, the second electrode is arranged between two adjacent ones of the first touch portions and between two adjacent ones of the first sub-electrode portions.

[0016] According to any one of the foregoing implementations of the first aspect of the present disclosure, the second electrode includes a first virtual electrode arranged to extend in the first direction.

[0017] According to any one of the foregoing implementations of the first aspect of the present disclosure, the first virtual electrode is located between two adjacent ones of the first touch portions in the first direction.

[0018] According to any one of the foregoing implementations of the first aspect of the present disclosure, the first virtual electrode extends by the same width as the first touch portion in the second direction.

[0019] According to any one of the foregoing implementations of the first aspect of the present disclosure, a plurality of first virtual electrodes are arranged side by side in the second direction, and the second electrode further includes a second virtual electrode connecting two adjacent ones of the first virtual electrodes in the second direction.

[0020] According to any one of the foregoing implementations of the first aspect of the present disclosure, the shape of an extension path of the second virtual electrode is the same as the shape of an extension path of the second touch portion.

[0021] According to any one of the foregoing implementations of the first aspect of the present disclosure, the second virtual electrode extends by the same width in the first direction as the second touch portion in the first direction.

[0022] According to any one of the foregoing implementations of the first aspect of the present disclosure, two adjacent ones of the touch areas are spaced apart by the same distance in the first direction and/or the second direction; and [0023] the width of the second electrode between two adjacent ones of the touch areas in the first direction is the same, and/or the length of the second electrode between two adjacent ones of the touch areas in the second direction is the same.

[0024] According to any one of the foregoing implementations of the first aspect of the present disclosure, the number of touch electrodes provided in each of the touch areas is the same.

[0025] According to any one of the foregoing implementations of the first aspect of the present disclosure, a plurality of pixel openings are distributed in an array in a first direction and a second direction, the first direction being a row direction, and the second electrode being correspondingly located between two adjacent rows of pixel openings.

[0026] According to any one of the foregoing implementations of the first aspect of the present disclosure, a plurality of second electrodes are arranged side by side at intervals in the first direction.

[0027] According to any one of the foregoing implementations of the first aspect of the present

disclosure, the second electrode and one or more of the pixel openings are arranged side by side in the second direction, or the plurality of second electrodes and the same pixel opening are arranged side by side in the second direction.

[0028] According to any one of the foregoing implementations of the first aspect of the present disclosure, the isolation structure is disposed on a side of the pixel defining portion away from the substrate; [0029] or the pixel defining portion also encloses a clearance opening, and the isolation structure is located in the clearance opening and is spaced apart from an inner wall surface of the pixel defining portion facing the clearance opening.

[0030] According to any one of the foregoing implementations of the first aspect of the present disclosure, the first isolation structure includes a conductive portion and an insulating portion on a side of the conductive portion away from the substrate, the touch electrode being located on a side of the insulating portion away from the substrate, [0031] and/or, the second isolation structure includes a conductive portion and an insulating portion on a side of the conductive portion away from the substrate, the second electrode being located on a side of the insulating portion away from the substrate, [0032] where the first electrode and the conductive portion are electrically connected to each other.

[0033] According to any one of the foregoing implementations of the first aspect of the present disclosure, the insulating portion includes an inorganic insulation layer and/or an organic insulation layer.

[0034] According to any one of the foregoing implementations of the first aspect of the present disclosure, an orthographic projection of the conductive portion on the substrate is located within an orthographic projection of the insulating portion on the substrate.

[0035] According to any one of the foregoing implementations of the first aspect of the present disclosure, the conductive portion includes a first sub-layer and a second sub-layer on a side of the first sub-layer away from the substrate, the first sub-layer and the first electrode being electrically connected to each other, an orthographic projection of the first sub-layer on the substrate being located within an orthographic projection of the second sub-layer on the substrate, and the orthographic projection of the second sub-layer on the substrate being located within an orthographic projection of the insulating portion on the substrate.

[0036] According to any one of the foregoing implementations of the first aspect of the present disclosure, the conductive portion further includes a third sub-layer on a side of the first sub-layer facing the substrate, the orthographic projection of the first sub-layer on the substrate being located within an orthographic projection of the third sub-layer on the substrate.

[0037] According to any one of the foregoing implementations of the first aspect of the present disclosure, the second sub-layer and the third sub-layer are made of the same material.

[0038] An embodiment of a first aspect of the present disclosure further provides a display panel, including: a substrate; a pixel defining layer disposed on the substrate and including a pixel defining portion and a pixel opening; a light-emitting layer including a light-emitting unit located in the pixel opening; and a functional layer disposed on a side of the light-emitting layer and the pixel defining layer away from the substrate, the functional layer including a first electrode, a touch electrode and a second electrode which are insulated and spaced apart from each other, the first electrode being located on a side of the light-emitting unit away from the substrate.

[0039] According to an implementation of the first aspect of the present disclosure, the display panel further includes an isolation structure disposed on one side of the substrate, an orthographic projection of the isolation structure on the substrate being located outside an orthographic projection of the pixel opening on the substrate, the isolation structure including a first isolation structure and a second isolation structure which are spaced apart and insulated from each other, the touch electrode being located on a side of the first isolation structure away from the substrate, and the second electrode being located on a side of the second isolation structure away from the substrate.

[0040] According to any one of the foregoing implementations of the first aspect of the present disclosure, the first electrode is electrically connected to the isolation structure.

[0041] An embodiment of a first aspect of the present disclosure further provides a display panel, including: a substrate; an isolation structure disposed on the substrate, the isolation structure enclosing an isolation opening, and the isolation structure including a first isolation structure and a second isolation structure which are spaced apart and insulated from each other; a light-emitting layer including a light-emitting unit located at the isolation opening; and a functional layer including a first electrode, a touch electrode and a second electrode which are insulated and spaced apart from each other, the first electrode being located on a side of the light-emitting unit away from the substrate, the touch electrode being located on a side of the first isolation structure away from the substrate, and the second electrode being located on a side of the second isolation structure away from the substrate.

[0042] According to any one of the foregoing implementations of the first aspect of the present disclosure, the first isolation structure and the second isolation structure each include a conductive portion and an insulating portion on a side of the conductive portion away from the substrate, the touch electrode and the second electrode being located on a side of the insulating portion away from the substrate, and the first electrode and the conductive portion being connected to each other.

[0043] According to any one of the foregoing implementations of the first aspect of the present disclosure, the first isolation structure and the second isolation structure are spaced apart to create a gap, an orthographic projection of the light-emitting unit on the substrate is outside the gap, and at least a part of the first electrode is located in the gap to connect the conductive portions of the first isolation structure and the second isolation structure.

[0044] An embodiment in a second aspect of the present disclosure further provides a display device, including a display panel according to any one of the above-described embodiments in the first aspect.

[0045] In the display panel provided in the embodiment of the present disclosure, the display panel includes the substrate, the pixel defining layer, the isolation structure, and the functional layer, the pixel defining layer including the pixel defining portion and the pixel opening within which the light-emitting unit is disposed to achieve luminous display of the display panel. The orthographic projection of the isolation structure on the substrate is located outside the orthographic projection of the pixel opening on the substrate to improve the effect of the isolation structure on a luminous effect of the light-emitting unit. The functional layer includes the first electrode, the touch electrode and the second electrode, the first electrode being located on the side of the light-emitting unit away from the substrate to drive the light-emitting unit, and the isolation structure including the first isolation structure and the second isolation structure which are insulated from each other, to improve a short-circuit connection between the touch electrode on the first isolation structure and the second electrode on the second isolation structure. The touch electrode is configured to implement a touch function of the display panel, and the functional layer includes both the touch electrode and the first electrode, simplifying the structure of the display panel without separately providing a touch structure layer. The functional layer also includes the second electrode, and by rationally positioning the touch electrode and the second electrode, it is possible to improve the display effect of the display panel that is affected by the addition of the touch electrode in the functional layer.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0046] By reading the following detailed description made with reference to the drawings for non-limiting embodiments, the other features, objectives and advantages of the present disclosure will

become more apparent, in which the same or similar features are denoted by the same or similar reference numerals.

[0047] FIG. 1 is a top view of a display panel according to an embodiment of the present disclosure;

[0048] FIG. 2 is a partial top view of a display panel according to another embodiment of the present disclosure;

[0049] FIG. 3 is a sectional view along line A-A in FIG. 2;

[0050] FIG. 4 is a partial sectional view of a display panel according to another embodiment;

[0051] FIG. 5 is a partial top view of a display panel according to a further embodiment of the present disclosure;

[0052] FIG. 6 is a partial top view of a display panel according to a still further embodiment of the present disclosure;

[0053] FIG. 7 is a partial top view of a display panel according to yet another embodiment of the present disclosure;

[0054] FIG. 8 is a partial top view of a display panel according to yet another embodiment of the present disclosure;

[0055] FIG. 9 is a partial top view of a display panel according to yet another embodiment of the present disclosure;

[0056] FIG. 10 is a partial top view of a display panel according to an example;

[0057] FIG. 11 is a partial top view of a display panel according to another example; and

[0058] FIG. 12 is a partial sectional view of a display panel according to a further embodiment.

LIST OF REFERENCE SIGNS

[0059] **100**. Substrate; [0060] **200**. Pixel defining layer; **210**. Pixel defining portion; **220**. Pixel opening; **230**. Light-emitting unit; **240**. Clearance opening; [0061] **300**. Isolation structure; **301**. First isolation structure; **302**. Second isolation structure; **310**. Conductive portion; **311**. First sub-layer; **312**. Second sub-layer; **313**. Third sub-layer; **320**. Insulating portion; [0062] **400**. Functional layer; **410**. First electrode; **411**. First sub-electrode portion; **412**. Second sub-electrode portion; **420**. Touch electrode; **421**. First touch portion; **422**. Second touch portion; **430**. Second electrode; **431**. First virtual electrode; **432**. Second virtual electrode; **440**. Signal line; [0063] **500**. Pixel electrode layer; **510**. Pixel electrode; [0064] TA. Touch area; NTA. Non-touch area; AA. Display area; X. First direction; Y. Second direction.

DETAILED DESCRIPTION OF EMBODIMENTS

[0065] The features and exemplary embodiments of the present disclosure in various aspects will be described in detail below. In the following detailed description, many specific details are set forth to comprehensively understand the present disclosure. However, it will be very apparent to those skilled in the art that the present disclosure may be implemented without some of these specific details. The following description of the embodiments is merely to provide a better understanding for the present disclosure by illustrating examples of the present disclosure. In the drawings and the following description, at least some of known structures and techniques are not shown to avoid unnecessary ambiguousness of the present disclosure; and for the case of clarity, the dimensions of part of the structure may be enlarged. In addition, the features, structures or characteristics described below may be combined, in any suitable manner, in one or more embodiments.

[0066] In the description of the present disclosure, it should be noted that “a plurality of” means two or more, unless otherwise specified. The orientation or position relationship indicated by the terms “upper”, “lower”, “left”, “right”, “inner”, “outer”, etc. is merely for the convenience of describing the present disclosure and simplifying the description, rather than indicating or implying that a device or element referred to must have a particular orientation or be constructed and operated in a particular orientation, and therefore should not be construed as limiting the present disclosure. Moreover, the terms such as “first” and “second” are merely used for the illustrative

purpose, and should not be construed as indicating or implying the relative importance.

[0067] The orientation terms used in the following description all indicate directions shown in the accompanying drawings, and do not limit the specific structure of the embodiment of the present disclosure. In the description of the present disclosure, it should also be noted that unless otherwise explicitly specified and defined, the terms “mounting” and “connection” should be understood in a broad sense, for example, they may be a fixed connection, a detachable connection, or an integrated connection, and may be a direct connection, or an indirect connection. For those of ordinary skill in the art, the specific meanings of the terms mentioned above in the present disclosure may be construed according to specific circumstances.

[0068] In order to better understand the present disclosure, a display panel and a display device according to the embodiments of the present disclosure will be described in detail below with reference to FIGS. 1 to 12.

[0069] Referring to FIGS. 1 to 3 together, FIG. 1 is a top view of a display panel according to an embodiment of the present disclosure. FIG. 2 is a schematic diagram of a local enlarged structure of a display panel according to another embodiment of the present disclosure. FIG. 3 is a sectional view along line A-A in FIG. 2.

[0070] As shown in FIGS. 1 to 3, the display panel according to the embodiment of the present disclosure includes a substrate **100**, a pixel defining layer **200**, an isolation structure **300**, and a functional layer **400**. The pixel defining layer **200** is disposed on the substrate **100** and includes a pixel defining portion **210** and a pixel opening **220** within which a light-emitting unit **230** is disposed; the isolation structure **300** is disposed on the substrate **100**, an orthographic projection of the isolation structure **300** on the substrate **100** is located outside an orthographic projection of the pixel opening **220** on the substrate **100**, and the isolation structure **300** includes a first isolation structure **301** and a second isolation structure **302** which are spaced apart and insulated from each other; and the functional layer **400** includes a first electrode **410**, a touch electrode **420** and a second electrode **430** which are insulated and spaced apart from each other, the first electrode **410** being located on a side of the light-emitting unit **230** away from the substrate **100**, the touch electrode **420** being located on a side of the first isolation structure **301** away from the substrate **100**, and the second electrode **430** being located on a side of the second isolation structure **302** away from the substrate **100**.

[0071] In the display panel provided in the embodiment of the present disclosure, the display panel includes the substrate **100**, the pixel defining layer **200**, the isolation structure **300**, and the functional layer **400**, the pixel defining layer **200** including the pixel defining portion **210** and the pixel opening **220** within which the light-emitting unit **230** is disposed to achieve luminous display of the display panel. The orthographic projection of the isolation structure **300** on the substrate **100** is located outside the orthographic projection of the pixel opening **220** on the substrate **100** to improve the effect of the isolation structure **300** on a luminous effect of the light-emitting unit **230**. The functional layer **400** includes the first electrode **410**, the touch electrode **420** and the second electrode **430**, the first electrode **410** being located on the side of the light-emitting unit **230** away from the substrate **100** to drive the light-emitting unit **230**, and the isolation structure **300** including the first isolation structure **301** and the second isolation structure **302** which are insulated from each other, to improve a short-circuit connection between the touch electrode **420** on the first isolation structure **301** and the second electrode **430** on the second isolation structure **302**. The touch electrode **420** is configured to implement a touch function of the display panel, and the functional layer **400** includes both the touch electrode **420** and the first electrode **410**, simplifying the structure of the display panel without separately providing a touch structure layer. The functional layer **400** also includes the second electrode **430**, and by rationally positioning the touch electrode **420** and the second electrode **430**, it is possible to improve the display effect of the display panel that is affected by the addition of the touch electrode **420** in the functional layer **400**.

[0072] The substrate **100** is arranged in a variety of ways, optionally, the substrate **100** may include

a substrate and an array substrate, and the array substrate may include a drive circuit. For example, the array substrate may include a first signal line layer, a second signal line layer and a third signal line layer which are disposed on one side of the substrate in a stacked manner. An insulation layer is provided between adjacent signal line layers. For example, a pixel drive circuit disposed on the array substrate includes a transistor and a storage capacitor. The transistor includes a semiconductor, a gate, a source and a drain. The storage capacitor includes a first plate and a second plate. As an example, the gate and the first plate may be located in the first signal line layer, the second plate may be located in the second signal line layer, and the source and the drain may be located in the third signal line layer.

[0073] Optionally, the substrate **100** is further provided with a pixel electrode layer **500**, the pixel electrode layer **500** including a plurality of pixel electrodes **510** distributed at intervals, each pixel electrode **510** being located on a side of each light-emitting unit **230** facing the substrate **100**, and the pixel electrode **510** and the first electrode **410** interacting to drive the light-emitting unit **230** to emit light. One of the pixel electrode **510** and the first electrode **410** is an anode, and the other is a cathode. An embodiment of the present disclosure is exemplified by using the pixel electrode **510** as the anode.

[0074] Optionally, the isolation structure **300** may be disposed on a side of the pixel defining portion **210** away from the substrate **100**. Alternatively, as shown in FIG. 4, the pixel defining portion **210** is also provided with a clearance opening **240**, and the isolation structure **300** may be located in the clearance opening **240** to be in direct contact connection with the substrate **100**.

[0075] Optionally, the shape of the first isolation structure **301** is adapted to the shape of the touch electrode **420**, the first isolation structure **301** is present to support the touch electrode **420**, and an orthographic projection of the touch electrode **420** on the substrate **100** is located within an orthographic projection of the first isolation structure **301** on the substrate **100**, so that the first isolation structure **301** can separate the touch electrode **420** from the first electrode **410**. Similarly, the shape of the second isolation structure **302** is adapted to the shape of the second electrode **430**, the second isolation structure **302** is present to support the second electrode **430**, and an orthographic projection of the second electrode **430** on the substrate **100** is located within an orthographic projection of the second isolation structure **302** on the substrate **100**, so that the second isolation structure **302** can separate the second electrode **430** from the first electrode **410**.

[0076] Optionally, in preparing the functional layer **400**, a layer of conductive material may be deposited directly on a side of the pixel defining layer **200** and the isolation structure **300** away from the substrate **100**, the conductive material falling within the pixel opening **220** forms the first electrode **410**, the conductive material falling on the first isolation structure **301** forms the touch electrode **420**, and the conductive material falling on the second isolation structure **302** forms the second electrode **430**.

[0077] Optionally, the shapes of the first electrode **410**, the touch electrode **420** and the second electrode **430** in the functional layer **400** are adapted to each other, and the first electrode **410**, the touch electrode **420** and the second electrode **430** form a complete layer of conductive material. Optionally, the functional layer **400** further includes a signal line **440**, where the signal line **440** is configured to connect the touch electrode **420**, and the signal line **440** is configured to connect the touch electrode **420** to components such as a processor.

[0078] In some optional embodiments, as shown in FIG. 1, the display panel includes a plurality of touch areas TA, each of which is provided with the touch electrode **420**, a non-touch area NTA is formed between two adjacent touch areas TA, and the non-touch area NTA is provided with the second electrode **430**.

[0079] In these optional embodiments, the display panel includes a plurality of touch areas TA within which touch electrodes **420** are disposed to implement the touch function of the display panel.

[0080] Optionally, the plurality of touch areas TA are distributed in an array in a first direction X

and a second direction Y, so that the display panel is provided with the touch areas TA at different positions, which can increase the area of distribution of the touch function on the display panel. [0081] A non-touch area NTA is formed between two adjacent touch areas TA, resulting in a display disparity between the touch area TA and the non-touch area NTA due to the absence of touch electrode **420** within the non-touch area NTA. In the state where the display panel is in a standby mode, due to the different distribution area of a conductive metal material in the touch area TA and the non-touch area NTA, the display disparity between the touch area TA and the non-touch area NTA is large. In an embodiment of the present disclosure, by providing the second electrode **430** within the non-touch area NTA, the distribution density of the conductive material in the touch area TA and the non-touch area NTA tends to be uniform, thereby improving the display disparity between the touch area TA and the non-touch area NTA.

[0082] The touch electrode **420** may be shaped in a variety of ways, for example, the touch electrode **420** may be strip-shaped and located between two adjacent rows or columns of pixel openings **220**. Alternatively, the touch electrode **420** may be dot-shaped or block-shaped.

[0083] In some other optional embodiments, as shown in FIG. 5, the touch electrode **420** includes a first touch portion **421** and a second touch portion **422**, the first touch portion **421** being arranged to extend in the first direction X, a plurality of first touch portions **421** being distributed at intervals in the second direction Y, and the second touch portion **422** connecting two adjacent first touch portions **421**; where a plurality of pixel openings **220** are distributed in an array in the first direction X and the second direction Y, two or more rows of pixel openings **220** are arranged between two adjacent first touch portions **421**, and the second electrode **430** is correspondingly arranged between the two adjacent first touch portions **421** and between two adjacent rows of pixel openings **220**.

[0084] In these optional embodiments, the touch electrode **420** includes a first touch portion **421** and a second touch portion **422**, the first touch portion **421** extending in the first direction X and being located between two adjacent rows of pixel openings **220**, and the second touch portion **422** being configured to connect two adjacent first touch portions **421**, so that the first touch portion **421** and the second touch portion **422** can be electrically connected to each other to form the electrode block described above.

[0085] The provision of two or more rows of pixel openings **220** between two adjacent first touch portions **421** results in the provision of a first touch portion **421** between two adjacent rows of pixel openings **220** on the one hand, and the provision of no first touch portion **421** between two adjacent rows of pixel openings **220** on the other hand. The uneven distribution of the conductive material may cause the display disparity. In an embodiment of the present disclosure, the display disparity caused by the above-mentioned non-uniform conductive material can be improved by providing the second electrode **430** between two adjacent first touch portions **421** and between two adjacent rows of pixel openings **220**, thereby further improving the display effect of the display panel.

[0086] Optionally, the first touch portion **421** and the second touch portion **422** are connected to each other to form the touch electrode **420**, and one or more electrode blocks may be provided in the same touch area TA. Optionally, the touch electrode **420** may be a self-capacitive touch electrode **420** or a mutual-capacitive touch electrode **420**.

[0087] Optionally, in other embodiments, as shown in FIG. 6, a row of pixel openings **220** may also be correspondingly arranged between two adjacent first touch portions **421**, and at this time, no second electrode **430** may be arranged between the two adjacent first touch portions **421**.

[0088] Optionally, the shape of the first isolation structure **301** is adapted to the shape of the touch electrode **420**, the first isolation structure **301** may include a first isolation portion and a second isolation portion, the first touch portion **421** is located on a side of the first isolation portion away from the substrate **100**, and the second touch portion **422** is located on a side of the second isolation portion away from the substrate **100**.

[0089] Optionally, the second touch portion **422** may be strip-shaped or serrated, etc. For example,

as shown in FIGS. 1 to 6, when a plurality of pixel openings **220** are arranged in the first direction X and the second direction Y, and two adjacent rows of pixel openings **220** are aligned, the second touch portion **422** may be strip-shaped and extend between two adjacent columns of pixel openings **220**. As shown in FIG. 7, when two adjacent rows of pixel openings **220** are misaligned, the second touch portion **422** may extend along a bend path to misalign with the pixel openings **220**. The touch electrode **420** in one of the touch areas TA and the second electrode **430** are merely schematically shown in FIG. 7, and the first touch portion **421** and the second touch portion **422** of the touch electrode **420** are schematically shown in a line structure. The second electrode **430** is schematically shown in a line structure. The first touch portion **421** and the second touch portion **422** of the touch electrode **420**, and the second electrode **430** may be a metal trace structure having a certain width as shown in FIGS. 1 and 2.

[0090] For example, as shown in FIGS. 5 and 6, when the plurality of pixel openings **220** are arranged in rows and columns along the first direction X and the second direction Y, the first direction X is a row direction, the second direction Y is a column direction, two adjacent rows of pixel openings **220** are aligned in the second direction Y, and two adjacent columns of pixel openings **220** are aligned in the first direction X. Then the first touch portion **421** may extend in the first direction X in the shape of a strip, and the second touch portion **422** may be strip-shaped in the second direction Y.

[0091] In some other optional embodiments, as shown in FIG. 7, when two adjacent rows of pixel openings **220** are misaligned, and two or more rows of pixel openings **220** are arranged between the two first touch portions **421**, in order to avoid positional interference between the second touch portion **422** and the pixel opening **220**, the second touch portion **422** may be bent or tilted such that the second touch portion **422** may avoid the position of the pixel opening **220**.

[0092] Optionally, when the second electrode **430** is correspondingly arranged between the two adjacent first touch portions **421** and between two adjacent rows of pixel openings **220**, the width of the second electrode **430** in the second direction Y is the same as the width of the first touch portion **421** in the second direction Y. The distribution of the conductive material is more balanced, and the display effect of the display panel may be better improved.

[0093] In some optional embodiments, the first electrode **410** includes a first sub-electrode portion **411** and a second sub-electrode portion **412**, the first sub-electrode portion **411** being located between two adjacent first touch portions **421**, a plurality of first sub-electrode portions **411** being arranged at intervals in the second direction Y, and the second sub-electrode portion **412** connecting two adjacent first sub-electrode portions **411**.

[0094] In these optional embodiments, the first sub-electrode portion **411** is located between two adjacent first touch portions **421**, and the first sub-electrode portion **411** is configured to drive light emission from the light-emitting unit **230** located within the pixel opening **220** between the two adjacent first touch portions **421**. The second sub-electrode portion **412** is configured to connect the plurality of first sub-electrode portions **411** into a continuous electrode.

[0095] Optionally, as shown in FIGS. 1 and 2, the display panel includes a display area AA, and the second sub-electrode portion **412** is configured to connect the plurality of first sub-electrode portions **411** into a continuous electrode, the continuous electrode does not necessarily have to be an electrode that is physically laid out over the entire surface, meaning it does not have to be laid out over the entire display area AA, but may interconnect the first sub-electrode portions **411** and the second sub-electrode portion **412** in the display area AA, and the first sub-electrode portions **411** and the second sub-electrode portion **412** in the display area AA have the same potential. Optionally, the display panel may also include a non-display area AA arranged around the display area AA.

[0096] In an embodiment of the present disclosure, when the touch electrode **420** is comb-shaped and includes a first touch electrode **420** portion and a second touch electrode **420** portion, the first electrode **410** is also comb-shaped and includes the first sub-electrode portion **411** and the second

sub-electrode portion **412**, and the touch electrode **420** and the first electrode **410** are substantially interconnected, which can increase the distribution area of the touch electrode **420** and the first electrode **410**, and improves the sensitivity of the touch function without affecting a luminous effect of the display panel. In addition, by adding the second electrode **430** in the non-touch area NTA or the touch area TA, it is possible to improve the display effect of the display panel that is affected by the uneven distribution of the conductive material caused by the provision of the touch electrode **420**.

[0097] Optionally, at least a part of the second sub-electrode portion **412** and the second touch portion **422** are respectively arranged on two sides of the same first touch portion **421** in the first direction X. For example, the second touch portion **422** connected to a certain first touch portion **421**, and the second sub-electrode portion **412** for connecting the first sub-electrode portions **411** located on two sides of the first touch portion **421** are respectively arranged on two sides of the first touch portion **421** in the first direction X, so that the arrangement of the second sub-electrode portion **412** and the second touch portion **422** does not affect each other. The shape of the touch electrode **420** and the shape of the first electrode **410** are adapted to each other to increase the distribution area of the touch electrode **420** and the first electrode **410**.

[0098] Optionally, the second electrode **430** is arranged between the first touch portion **421** and the first sub-electrode portion **411** which are adjacent to each other. For example, when two or more rows of pixel openings **220** are arranged between two adjacent first touch portions **421**, two or more first sub-electrode portions **411** may be arranged between the two adjacent first touch portions **421**, each first sub-electrode portion **411** corresponding to each row of pixel openings **220**, and the first sub-electrode portion **411** being configured to drive the light-emitting units **230** in the same row of pixel openings **220** to emit light. At this time, the second electrode **430** may be arranged between two adjacent first sub-electrode portions **411** to increase the distribution area of the second electrode **430** and to make the distribution of the touch electrode **420** and the second electrode **430** more balanced, thereby improving the display effect of the display panel.

[0099] In some optional embodiments, the second electrode **430** includes a first virtual electrode **431**, the first virtual electrode **431** being located between two adjacent first touch portions **421** in the first direction X, and the first virtual electrode **431** being arranged to extend in the first direction X.

[0100] In these optional embodiments, the second electrode **430** includes a first virtual electrode **431**, and the first virtual electrode **431** extends in the first direction X such that the shapes of the first virtual electrode **431** and the first touch portion **421** are more similar, which can improve the display disparity due to a gap between two adjacent first touch portions **421** in the first direction X.

[0101] Optionally, as shown in FIG. 1, the first virtual electrode **431** is located between the adjacent first touch portions **421** in the first direction X. For example, the first virtual electrode **431** is located between the first touch portions **421** of the adjacent touch areas TA in the first direction X, so as to improve the display disparity between the touch area TA and the non-touch area NTA of the display panel.

[0102] Optionally, the first virtual electrode **431** extends by the same width as the first touch portion **421** in the second direction Y. The shape of the first virtual electrode **431** and the shape of the first touch portion **421** are more similar, which better improves the display disparity due to the gap between the two adjacent first touch portions **421** in the first direction X.

[0103] In some optional embodiments, as shown in FIGS. 7 and 8, a plurality of first virtual electrodes **431** are arranged side by side in the second direction Y, the second electrode **430** includes a second virtual electrode **432**, and the second virtual electrode **432** connects two adjacent first virtual electrodes **431** in the second direction Y.

[0104] In these optional embodiments, by adding the second virtual electrode **432**, the second electrode **430** includes the first virtual electrode **431** and the second virtual electrode **432**, and the second electrode **430** has a more similar shape than the touch electrode **420** including the first

touch portion **421** and the second touch portion **422**, to better improve the display effect of the display panel.

[0105] Optionally, the shape of the second isolation structure **302** is adapted to the shape of the second electrode **430**. When the second electrode **430** includes the first virtual electrode **431** and the second virtual electrode **432**, the second isolation structure **302** may include a third isolation portion and a fourth isolation portion, the first virtual electrode **431** being located on a side of the third isolation portion away from the substrate **100**, and the second virtual electrode **432** being located on a side of the fourth isolation portion away from the substrate **100**. Optionally, an orthographic projection of the first virtual electrode **431** on the substrate **100** is located within an orthographic projection of the third isolation portion on the substrate **100**, and an orthographic projection of the second virtual electrode **432** on the substrate **100** is located within an orthographic projection of the fourth isolation portion on the substrate **100**.

[0106] Optionally, the first virtual electrode **431** may be provided in the touch area TA, and the second virtual electrode **432** may be connected to the first virtual electrode **431** in the non-touch area NTA. Alternatively, as shown in FIG. 9, the second virtual electrode **432** may be connected to the first virtual electrodes **431** in the touch area TA and the non-touch area NTA. The length of the first virtual electrode **431** in the touch area TA may be the same as or different from the length of the first virtual electrode **431** in the non-touch area NTA in the first direction X.

[0107] Optionally, the shape of an extension path of the second virtual electrode **432** is the same as the shape of an extension path of the second touch portion **422**. For example, as shown in FIG. 7, when the second touch portion **422** extends along the bend path, the second virtual electrode **432** extends along the bend path. Alternatively, as shown in FIGS. 8 and 9, when the second touch portion **422** extends in the second direction Y in the shape of a strip, the second virtual electrode **432** extends in the second direction Y in the shape of a strip, so that the shape of the second electrode **430** is more adapted to the shape of the touch electrode **420**, thereby better improving the display effect of the display panel.

[0108] Optionally, the second virtual electrode **432** extends by the same width in the first direction X as the second touch portion **422** in the first direction X, so that the shape of the second electrode **430** is more adapted to the shape of the touch electrode **420**, thereby better improving the display effect of the display panel.

[0109] In some optional embodiments, as shown in FIG. 1, the display panel includes a plurality of touch areas TA, the plurality of touch areas TA being distributed in an array in the first direction X and the second direction Y, and two adjacent touch areas TA are equidistant in the first direction X and/or the second direction Y. The distribution of the plurality of touch areas TA is made more even, so that the display effect of the display panel is more even.

[0110] Optionally, the width of the second electrode **430** between two adjacent touch areas TA in the first direction X is the same, and/or the length of the second electrode **430** between two adjacent touch areas TA in the second direction Y is the same. The distribution of a plurality of second electrodes **430** is made more even, so that the display effect of the display panel is more even.

[0111] Optionally, the number of touch electrodes **420** provided in each touch area TA is the same, so that the touch electrodes **420** are more evenly distributed in the plurality of touch areas TA, achieving a more even display effect of the display panel.

[0112] In some optional embodiments, as shown in FIG. 10, the plurality of pixel openings **220** are distributed in an array in the first direction X and the second direction Y, the first direction X is the row direction, and the second electrode **430** is correspondingly located between two adjacent rows of pixel openings **220**, so as to improve the effect of the second electrode **430** on the display effect.

[0113] Optionally, as shown in FIG. 11, the plurality of second electrodes **430** are arranged side by side at intervals in the first direction X, i.e., the same pixel opening **220** may correspond to the plurality of second electrodes **430**, to make the shaping of the second electrodes **430** more

extensive.

[0114] Optionally, as shown in FIG. 10, the second electrode 430 and one or more pixel openings 220 are arranged side by side in the second direction Y. When the second electrode 430 and the plurality of pixel openings 220 are arranged side by side in the second direction Y, the shape of the second electrode 430 is more adapted to the shape of the touch electrode 420 to better improve the display effect of the display panel. When the second electrode 430 and the single pixel opening 220 are arranged side by side in the second direction Y, it is possible to reduce the distribution area of the second electrode 430, increase the distribution area of the first electrode 410, and decrease the resistance of the first electrode 410.

[0115] Alternatively, the plurality of second electrodes 430 and the same pixel opening 220 are arranged side by side in the second direction Y, to diversify the shaping of the second electrodes 430, so that the second electrodes 430 are arranged in various shapes in different positions to improve the display effect of the display panel.

[0116] In some optional embodiments, as shown in FIG. 3, the first isolation structure 301 includes a conductive portion 310 and an insulating portion 320 located on a side of the conductive portion 310 away from the substrate 100, and the touch electrode 420 is located on a side of the insulating portion 320 away from the substrate 100; and/or, the second isolation structure 302 includes a conductive portion 310 and an insulating portion 320 located on a side of the conductive portion 310 away from the substrate 100, and the touch electrode 420 is located on a side of the insulating portion 320 away from the substrate 100, where the first electrode 410 and the conductive portion 310 are electrically connected to each other.

[0117] In these optional embodiments, the first electrode 410 and the conductive portion 310 are electrically connected to each other, such that the first electrodes 410 can be interconnected by the conductive portion 310 into a continuous electrode, and the impedance of the first electrode 410 can be reduced.

[0118] The insulating portion 320 is provided in a variety of materials, for example, the insulating portion 320 may include an organic insulation layer and/or an inorganic insulation layer, i.e., the material of the insulating portion 320 may include an organic insulating material and/or an inorganic insulating material.

[0119] Optionally, an orthographic projection of the conductive portion 310 on the substrate 100 is located within an orthographic projection of the insulating portion 320 on the substrate 100, i.e., the size of the conductive portion 310 is less than or equal to the size of the insulating portion 320, so that a segment difference can be formed between the conductive portion 310 and the insulating portion 320, or one side of the conductive portion 310 can form a recess, and the functional layer 400 can break at the edge of the isolation structure 300 to form the first electrode 410 and the touch electrode 420.

[0120] Optionally, as shown in FIGS. 1 to 4, the conductive portion 310 includes a first sub-layer 311 and a second sub-layer 312 located on a side of the first sub-layer 311 away from the substrate 100, the first sub-layer 311 and the first electrode 410 being electrically connected to each other, an orthographic projection of the first sub-layer 311 on the substrate 100 being located within an orthographic projection of the second sub-layer 312 on the substrate 100, and the orthographic projection of the second sub-layer 312 on the substrate 100 being located within an orthographic projection of the insulating portion 320 on the substrate 100. That is, the cross-sectional dimension of the first sub-layer 311 is less than or equal to that of the second sub-layer 312, making it easier for the functional layer 400 to break at the edge of the isolation structure 300 to form the first electrode 410 and the touch electrode 420.

[0121] Optionally, as shown in FIG. 4, the conductive portion 310 further includes a third sub-layer 313 on a side of the first sub-layer 311 facing the substrate 100, the orthographic projection of the first sub-layer 311 on the substrate 100 being located within an orthographic projection of the third sub-layer 313 on the substrate 100, that is, the cross-sectional dimension of the first sub-layer 311

is less than or equal to that of the third sub-layer **313**, enabling the first electrode **410** to more easily climb over the third sub-layer **313** to the first sub-layer **311** and to be electrically connected to the first sub-layer **311**.

[0122] Optionally, the material of the second sub-layer **312** is the same as the material of the third sub-layer **313** so as to simplify a preparation process for the display panel.

[0123] Optionally, as shown in FIG. **12**, the conductive portion **310** is a single-layer structural body, the cross-sectional area of the conductive portion **310** is gradually reduced in a direction from the conductive portion **310** to the substrate **100**, so that one side of the conductive portion **310** can form a recess, and the first electrode **410** and the touch electrode **420** can break at the edge of the conductive portion **310**.

[0124] As mentioned above, the material of the insulating portion **320** includes an organic material and/or an inorganic material. Optionally, as shown in FIG. **12**, the light-emitting unit **230** includes a carrier layer, and the material of the insulating portion **320** may be the same as the material of the carrier layer, so that the insulating portion **320** and the carrier layer may be formed in the same process step. The carrier layer may include at least one of a hole injection layer, a hole transport layer, an electron blocking layer, a hole blocking layer, an electron transport layer and an electron injection layer.

[0125] Alternatively, the material of the insulating portion **320** includes an inorganic material such that the thickness of the insulating portion **320** is thin, or the material of the insulating portion **320** includes an organic material such that the thickness of the insulating portion **320** is thick.

Alternatively, the material of the insulating portion **320** includes an organic material and an inorganic material, i.e., the insulating portion **320** includes two sub-layers to further increase the thickness of the insulating portion **320**, enabling the first electrode **410** and the touch electrode **420** to break at the edge of the isolation structure **300**.

[0126] As shown in FIGS. **1** to **11**, yet another embodiment in the first aspect of the present disclosure further provides a display panel, including: a substrate **100**; a pixel defining layer **200** disposed on the substrate **100** and including a pixel defining portion **210** and a pixel opening **220**; a light-emitting layer including a light-emitting unit **230** located in the pixel opening **220**; and a functional layer **400** disposed on a side of the light-emitting layer and the pixel defining layer **200** away from the substrate **100**, the functional layer **400** including a first electrode **410**, a touch electrode **420** and a second electrode **430** which are insulated and spaced apart from each other, the first electrode **410** being located on a side of the light-emitting unit **230** away from the substrate **100**.

[0127] The display panel according to the embodiment of the present disclosure includes a substrate **100**, a pixel defining layer **200**, a light-emitting layer, and a functional layer **400**. The pixel defining layer **200** includes a pixel defining portion **210** and a pixel opening **220**, and a light-emitting unit **230** of the light-emitting layer is located within the pixel opening **220** to achieve luminous display of the display panel. The functional layer **400** includes a first electrode **410**, a touch electrode **420** and a second electrode **430**, the first electrode **410** being located on a side of the light-emitting unit **230** away from the substrate **100** to drive the light-emitting unit **230** to emit light. The touch electrode **420** is configured to implement the touch function and simplify the structure of the display panel, and the second electrode **430** is configured to equalize the distribution pattern and the distribution area of the functional layer **400**, so as to improve the display effect of the display panel.

[0128] In some optional embodiments, the display panel further includes an isolation structure **300**, the isolation structure **300** being disposed on one side of the substrate **100**, an orthographic projection of the isolation structure **300** on the substrate **100** being located outside an orthographic projection of the pixel opening **220** on the substrate **100**, the isolation structure **300** including a first isolation structure **301** and a second isolation structure **302** which are spaced apart and insulated from each other, the touch electrode **420** being located on a side of the first isolation structure **301**

away from the substrate **100**, and the second electrode **430** being located on a side of the second isolation structure **302** away from the substrate **100**. By adding the first isolation structure **301** and the second isolation structure **302**, the first electrode **410**, the touch electrode **420** and the second electrode **430** can be insulated and separated from each other.

[0129] Optionally, the first electrode **410** and the isolation structure **300** are electrically connected to allow for a complete interconnection of the plurality of first electrodes **410** in the display panel.

[0130] In the embodiment of the present disclosure, the substrate **100**, the pixel defining layer **200**, the isolation structure **300** and the functional layer **400** are arranged in such a manner as described above, which will not be repeated herein.

[0131] As shown in FIGS. **1** to **11**, an embodiment in the first aspect of the present disclosure further provides a display panel, including: a substrate **100**; an isolation structure **300** disposed on the substrate **100**, the isolation structure **300** enclosing an isolation opening, and the isolation structure **300** including a first isolation structure **301** and a second isolation structure **302** which are spaced apart and insulated from each other; a light-emitting layer including a light-emitting unit **230** located at the isolation opening; and a functional layer **400** including a first electrode **410**, a touch electrode **420** and a second electrode **430** which are insulated and spaced apart from each other, the first electrode **410** being located on a side of the light-emitting unit **230** away from the substrate **100**, the touch electrode **420** being located on a side of the first isolation structure **301** away from the substrate **100**, and the second electrode **430** being located on a side of the second isolation structure **302** away from the substrate **100**.

[0132] The display panel according to the embodiment of the present disclosure includes a substrate **100**, a pixel defining layer **200**, a light-emitting layer, and a functional layer **400**. The isolation structure **300** includes an isolation opening within which a light-emitting unit **230** of the light-emitting layer is disposed to achieve luminous display of the display panel. The functional layer **400** includes a first electrode **410**, a touch electrode **420** and a second electrode **430**, the first electrode **410** being located on a side of the light-emitting unit **230** away from the substrate **100** to drive the light-emitting unit **230** to emit light. The touch electrode **420** is configured to implement the touch function and simplify the structure of the display panel, and the second electrode **430** is configured to equalize the distribution pattern and the distribution area of the functional layer **400**, so as to improve the display effect of the display panel.

[0133] In some optional embodiments, the first isolation structure **301** and the second isolation structure **302** each include a conductive portion **310** and an insulating portion **320** located on a side of the conductive portion **310** away from the substrate **100**, the touch electrode **420** and the second electrode **430** are located on a side of the insulating portion **320** away from the substrate **100**, and the first electrode **410** and the conductive portion **310** are connected to each other.

[0134] In these optional embodiments, the first isolation structure **301** and the second isolation structure **302** each include a conductive portion **310** and an insulating portion **320**, the conductive portion **310** and the first electrode **410** being connected such that the first electrodes **410** are interconnected into a continuous electrode. The insulating portion **320** on the conductive portion **310** can mitigate the problem of a short-circuit connection between the first electrode **410** and the touch electrode **420** and between the first electrode **410** and the second electrode **430**.

[0135] Optionally, the first isolation structure **301** and the second isolation structure **302** are spaced apart to create a gap, an orthographic projection of the light-emitting unit **230** on the substrate **100** is outside the gap, and at least a part of the first electrode **410** is located in the gap to connect the conductive portions **310** of the first isolation structure **301** and the second isolation structure **302**.

[0136] In these embodiments, the first isolation structure **301** and the second isolation structure **302** are spaced apart from each other to mitigate the problem of a short-circuit connection between the touch electrode **420** on the first isolation structure **301** and the second electrode **430** on the second isolation structure **302**, and the first electrode **410** is provided in the gap between the first isolation structure **301** and the second isolation structure **302** to connect the conductive portions **310** of the

first isolation structure **301** and the second isolation structure **302**, so that the first electrodes **410** may be interconnected into a continuous electrode to reduce the resistance of the first electrode **410**.

[0137] In the embodiment of the present disclosure, the substrate **100**, the pixel defining layer **200**, the isolation structure **300** and the functional layer **400** are arranged in such a manner as described above, which will not be repeated herein.

[0138] An embodiment in a second aspect of the present disclosure further provides a display device, including a display panel according to any one of the above-described embodiments in the first aspect. Since the display device according to the embodiment in the second aspect of the present disclosure includes the display panel according to any one of the above-described embodiments in the first aspect, the display device according to the embodiment in the second aspect of the present disclosure has the beneficial effects of the display panel according to any one of the above-described embodiments in the first aspect, which will not be repeated herein.

[0139] The display device in the embodiment of the present disclosure includes, but is not limited to devices having a display function, such as a cell phone, a personal digital assistant (PDA), a tablet computer, an e-book, a television, an access control, a smart fixed-line telephone, or a control console.

[0140] Although the present disclosure is described with reference to the preferred embodiments, various modifications can be made, and equivalents can be provided to substitute for the components thereof without departing from the scope of the present disclosure. In particular, the technical features mentioned in the embodiments can be combined in any manner, provided that there is no structural conflict. The present disclosure is not limited to the specific embodiments disclosed herein but includes all the technical solutions that fall within the scope of the claims.

Claims

1. A display panel, comprising: a substrate; a pixel defining layer disposed on the substrate and comprising a pixel defining portion and a pixel opening within which a light-emitting unit is disposed; an isolation structure disposed on the substrate, an orthographic projection of the isolation structure on the substrate being located outside an orthographic projection of the pixel opening on the substrate, and the isolation structure including a first isolation structure and a second isolation structure which are spaced apart and insulated from each other; and a functional layer comprising a first electrode, a touch electrode and a second electrode which are insulated and spaced apart from each other, the first electrode being located on a side of the light-emitting unit away from the substrate, the touch electrode being located on a side of the first isolation structure away from the substrate, and the second electrode being located on a side of the second isolation structure away from the substrate.
2. The display panel according to claim 1, wherein the display panel comprises a plurality of touch areas, each of the touch areas is provided with the touch electrode, a non-touch area is formed between two adjacent ones of the touch areas, and the non-touch area is provided with the second electrode; and the plurality of touch areas are distributed in an array in a first direction and a second direction.
3. The display panel according to claim 2, wherein the touch electrode comprises: a first touch portion arranged to extend in the first direction, a plurality of first touch portions being distributed at intervals in the second direction; and a second touch portion connecting two adjacent ones of the first touch portions; wherein a plurality of pixel openings are distributed in an array in the first direction and the second direction, at least two rows of pixel openings are arranged between two adjacent ones of the first touch portions, and the second electrode is correspondingly arranged between the two adjacent ones of the first touch portions and between two adjacent rows of pixel openings; and the width of the second electrode in the second direction is the same as the width of

the first touch portion in the second direction.

4. The display panel according to claim 3, wherein the first electrode comprises a first sub-electrode portion and a second sub-electrode portion, the first sub-electrode portion being located between two adjacent ones of the first touch portions, a plurality of first sub-electrode portions being arranged at intervals in the second direction, and the second sub-electrode portion connecting two adjacent ones of the first sub-electrode portions; and the second electrode is arranged between two adjacent ones of the first touch portions and between two adjacent ones of the first sub-electrode portions.

5. The display panel according to claim 4, wherein at least a part of the second sub-electrode portion and the second touch portion are respectively arranged on two sides of the same first touch portion in the first direction.

6. The display panel according to claim 3, wherein the second electrode comprises a first virtual electrode arranged to extend in the first direction; and the first virtual electrode is located between two adjacent ones of the first touch portions in the first direction; and the first virtual electrode extends by the same width as the first touch portion in the second direction.

7. The display panel according to claim 6, wherein a plurality of first virtual electrodes are arranged side by side in the second direction, and the second electrode further comprises a second virtual electrode connecting two adjacent ones of the first virtual electrodes in the second direction; and the shape of an extension path of the second virtual electrode is the same as the shape of an extension path of the second touch portion; and the second virtual electrode extends by the same width in the first direction as the second touch portion in the first direction.

8. The display panel according to claim 2, wherein two adjacent ones of the touch areas are spaced apart by the same distance at least one of in the first direction and the second direction; the width of the second electrode between two adjacent ones of the touch areas in the first direction is the same, and the length of the second electrode between two adjacent ones of the touch areas in the second direction is the same; or the width of the second electrode between two adjacent ones of the touch areas in the first direction is the same, or the length of the second electrode between two adjacent ones of the touch areas in the second direction is the same; and the number of touch electrodes provided in each of the touch areas is the same.

9. The display panel according to claim 1, wherein a plurality of pixel openings are distributed in an array in a first direction and a second direction, the first direction being a row direction, and the second electrode being correspondingly located between two adjacent rows of pixel openings; and a plurality of second electrodes are arranged side by side at intervals in the first direction; and the second electrode and one or more of the pixel openings are arranged side by side in the second direction, or the plurality of second electrodes and the same pixel opening are arranged side by side in the second direction.

10. The display panel according to claim 1, wherein the isolation structure is disposed on a side of the pixel defining portion away from the substrate; or the pixel defining portion also encloses a clearance opening, and the isolation structure is located in the clearance opening and is spaced apart from an inner wall surface of the pixel defining portion facing the clearance opening.

11. The display panel according to claim 1, wherein the first isolation structure comprises a conductive portion and an insulating portion on a side of the conductive portion away from the substrate, the touch electrode being located on a side of the insulating portion away from the substrate, and the second isolation structure comprises a conductive portion and an insulating portion on a side of the conductive portion away from the substrate, the second electrode being located on a side of the insulating portion away from the substrate, wherein the first electrode and the conductive portion are electrically connected to each other; and the insulating portion comprises at least one of an inorganic insulation layer and an organic insulation layer.

12. The display panel according to claim 11, wherein an orthographic projection of the conductive portion on the substrate is located within an orthographic projection of the insulating portion on the

substrate.

13. The display panel according to claim 11, wherein the conductive portion comprises a first sub-layer and a second sub-layer on a side of the first sub-layer away from the substrate, the first sub-layer and the first electrode being electrically connected to each other, an orthographic projection of the first sub-layer on the substrate being located within an orthographic projection of the second sub-layer on the substrate, and the orthographic projection of the second sub-layer on the substrate being located within an orthographic projection of the insulating portion on the substrate.

14. The display panel according to claim 13, wherein the conductive portion further comprises a third sub-layer on a side of the first sub-layer facing the substrate, the orthographic projection of the first sub-layer on the substrate being located within an orthographic projection of the third sub-layer on the substrate; and the second sub-layer and the third sub-layer are made of the same material.

15. A display panel, comprising: a substrate; a pixel defining layer disposed on the substrate and comprising a pixel defining portion and a pixel opening; a light-emitting layer comprising a light-emitting unit located in the pixel opening; and a functional layer disposed on a side of the light-emitting layer and the pixel defining layer away from the substrate, the functional layer comprising a first electrode, a touch electrode and a second electrode which are insulated and spaced apart from each other, the first electrode being located on a side of the light-emitting unit away from the substrate.

16. The display panel according to claim 15, wherein the display panel further comprises an isolation structure disposed on one side of the substrate, an orthographic projection of the isolation structure on the substrate being located outside an orthographic projection of the pixel opening on the substrate, the isolation structure comprising a first isolation structure and a second isolation structure which are spaced apart and insulated from each other, the touch electrode being located on a side of the first isolation structure away from the substrate, and the second electrode being located on a side of the second isolation structure away from the substrate; and the first electrode is electrically connected to the isolation structure.

17. A display panel, comprising: a substrate; an isolation structure disposed on the substrate, the isolation structure enclosing an isolation opening, and the isolation structure comprising a first isolation structure and a second isolation structure which are spaced apart and insulated from each other; a light-emitting layer comprising a light-emitting unit located in the isolation opening; and a functional layer comprising a first electrode, a touch electrode and a second electrode which are insulated and spaced apart from each other, the first electrode being located on a side of the light-emitting unit away from the substrate, the touch electrode being located on a side of the first isolation structure away from the substrate, and the second electrode being located on a side of the second isolation structure away from the substrate.

18. The display panel according to claim 17, wherein the first isolation structure and the second isolation structure each comprises a conductive portion and an insulating portion on a side of the conductive portion away from the substrate, the touch electrode and the second electrode being located on a side of the insulating portion away from the substrate, and the first electrode and the conductive portion being connected to each other.

19. The display panel according to claim 18, wherein the first isolation structure and the second isolation structure are spaced apart to create a gap, an orthographic projection of the light-emitting unit on the substrate is outside the gap, and at least a part of the first electrode is located in the gap to connect the conductive portions of the first isolation structure and the second isolation structure.

20. A display device, comprising a display panel according to claim 1.
