

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280686

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

AHN; Ji Young et al.

DISPLAY DEVICE

Abstract

The present disclosure relates to a display device. A display device is provided. The display device includes a first sub-pixel emitting a light of a first color different from a light emitted by the second sub-pixel, and a second sub-pixel emitting white light. A structure of a first electrode of the first sub-pixel and a structure of a first electrode of the second sub-pixel are different. In addition, the display device includes a second electrode including a first conductive layer and a second conductive layer. A transmittance of the second conductive layer is different from a transmittance of the first conductive layer.

Inventors: AHN; Ji Young (Paju-si, KR), NAM; Jun ho (Paju-si, KR), KIM; Ahn Ki (Paju-si, KR)

Applicant: LG Display Co., Ltd. (Seoul, KR)

Family ID: 96828678

Appl. No.: 18/774622

Filed: July 16, 2024

Foreign Application Priority Data

KR 10-2024-0030215

Feb. 29, 2024

Publication Classification

Int. Cl.: H10K59/35 (20230101); H10K59/38 (20230101); H10K59/80 (20230101);
H10K102/10 (20230101)

U.S. Cl.:

CPC H10K59/351 (20230201); H10K59/38 (20230201); H10K59/80517 (20230201);
H10K2102/101 (20230201)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the priority and benefit of the Korean Patent Application No. 10-2024-0030215 filed on Feb. 29, 2024, which is hereby incorporated by reference as if fully set forth herein.

BACKGROUND

Technical Field

[0002] The present disclosure relates to a display device, and more particularly, for example, without limitation, to a display device including high efficiency and low reflection electrode structure.

Description of the Related Art

[0003] The display device is widely used as a display screen of a notebook computer, a tablet computer, a smart phone, a portable display device, and a portable information device in addition to a display screen of a television or a monitor. With the advancement of technology, a display device may provide photographing or various sensing functions in addition to an image display function. Accordingly, the display device may include an electronic device such as a camera or a sensor.

[0004] Among the display devices, an organic light emitting display device is a self-emission type, and has advantages such as superior viewing angle and contrast ratio compared to a liquid crystal display (LCD), light weight and thinness are possible because no separate backlight is required, and power consumption is advantageous. In addition, the organic light emitting display device has an advantage of being able to drive DC low voltage, fast response speed, and especially low manufacturing cost.

BRIEF SUMMARY

[0005] Recently, in order to improve the light efficiency of the display device, an electrode including a highly reflective material is used. For example, in a top emission type display device, an anode of the light emitting device may be formed of the highly reflective material. In this case, when the light generated by the light emitting layer of the light emitting device proceeds toward a lower portion of the display device, the light is reflected by the anode, and a path of the light may be changed from a direction of the lower portion of the display device to a direction of the upper portion of the display device. Accordingly, a light efficiency of the display device may be improved. However, the inventors of the present disclosure have appreciated that the electrode including the highly reflective material reflects external light, and a reflectance of the display device with respect to the external light may increase. Accordingly, the inventors identified that there is a technical problem that the visibility of the display device is reduced.

[0006] The description provided in the discussion of the related art section should not be assumed to be prior art merely because it is mentioned in or associated with that section. The discussion of the related art section may include information that describes one or more aspects of the subject technology, and the description in this section does not limit the invention.

[0007] Therefore, the inventors of the present disclosure recognized the limitations or problems mentioned above and other limitations associated with the related art, and conducted various experiments to implement a display device that includes high efficiency and low reflection electrode structure.

[0008] The present disclosure has been made in view of one or more technical problems in the related art also including the above-identified problems and various embodiments of the present disclosure provide a display device including high efficiency and low reflection electrode structure.

[0009] In accordance with an aspect of the present disclosure, the above and other objects can be accomplished by the provision of a display device comprising a substrate on which a first sub-pixel

and a second sub-pixel are disposed, each of the first sub-pixel and the second sub-pixel including an emitting area and a non-emitting area surrounding the emitting area, wherein each of the first and second sub-pixels includes a first electrode disposed in the emitting area, a light emitting layer disposed on the first electrode, and a second electrode disposed on the light emitting layer, the first sub-pixel emits a light of a first color different from a light emitted by the second sub-pixel, the second sub-pixel emits white light, a structure of the first electrode of the first sub-pixel and a structure of the first electrode of the second sub-pixel are different.

[0010] In addition, in accordance with an aspect of the present disclosure, the above and other objects can be accomplished by the provision of a display device comprising a substrate on which a plurality of sub-pixels are disposed, the plurality of sub-pixels including an emitting area and a non-emitting area surrounding the emitting area, wherein each of the plurality of sub-pixels includes a first electrode disposed in the emitting area, a light emitting layer disposed on the first electrode, and a second electrode disposed on the light emitting layer, the second electrode includes a first conductive layer and a second conductive layer disposed on the first conductive layer, and a transmittance of the second conductive layer is different from a transmittance of the first conductive layer.

[0011] The effects according to the present disclosure are not limited to the contents exemplified above, and more various effects are included in the present disclosure.

[0012] It is to be understood that both the foregoing general description and the following detailed description of the present disclosure are exemplary and explanatory and are intended to provide further explanation of the inventive concepts as claimed.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0013] The above and other aspects, features and other advantages of the present disclosure will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

[0014] FIG. 1 is a plan view of a display device according to an exemplary embodiment of the present disclosure.

[0015] FIG. 2 is a plan view of one pixel according to an exemplary embodiment of the present disclosure.

[0016] FIG. 3 is a cross-sectional view of a sub-pixel according to an exemplary embodiment of the present disclosure.

[0017] FIG. 4 is a cross-sectional view of a pixel according to a first exemplary embodiment of the present disclosure.

[0018] FIG. 5 is a cross-sectional view of a pixel according to a second exemplary embodiment of the present disclosure.

[0019] FIG. 6 is a cross-sectional view of a pixel according to a third exemplary embodiment of the present disclosure.

[0020] FIG. 7 is a cross-sectional view of a pixel according to a fourth exemplary embodiment of the present disclosure.

[0021] FIGS. 8A to 8D are plan views of a sub-pixel according to various exemplary embodiments.

[0022] FIG. 9 is a cross-sectional view of a sub-pixel according to another exemplary embodiment of the present disclosure.

[0023] FIG. 10 is a cross-sectional view of a pixel according to a fifth exemplary embodiment of the present disclosure.

[0024] FIG. 11 is a cross-sectional view of a pixel according to a sixth exemplary embodiment of the present disclosure.

[0025] FIG. 12 is a cross-sectional view of a pixel according to a seventh exemplary embodiment of the present disclosure.

[0026] Throughout the drawings and the detailed description, unless otherwise described, the same drawing reference numerals should be understood to refer to the same elements, features, and structures. The sizes, lengths, and thicknesses of layers, regions and elements, and depiction thereof may be exaggerated for clarity, illustration, and convenience.

DETAILED DESCRIPTION

[0027] Advantages and features of the present disclosure and implementation methods thereof will be clarified through following exemplary embodiments described with reference to the accompanying drawings. The present disclosure may, however, be embodied in different forms and should not be construed as limited to the exemplary embodiments set forth herein. Rather, these exemplary embodiments are provided so that this disclosure will be sufficiently thorough and complete and will fully convey the scope of the present disclosure to those skilled in the art. Further, the present disclosure is only defined by scopes of claims.

[0028] A shape, a size, a dimension (e.g., length, width, height, thickness, radius, diameter, area, etc.), a ratio, an angle, a number, and the like disclosed in the drawings for describing exemplary embodiments of the present disclosure are merely an example and thus, the present disclosure is not limited to the illustrated details.

[0029] A dimension including size and a thickness of each component illustrated in the drawing are illustrated for convenience of description, and the present disclosure is not limited to the size and the thickness of the component illustrated, but it is to be noted that the relative dimensions including the relative size, location, and thickness of the components illustrated in various drawings submitted herewith are part of the present disclosure.

[0030] Like reference numerals refer to like elements throughout the specification. In the following description, when the detailed description of the relevant known function or configuration is determined to unnecessarily obscure the aspects of the present disclosure, the detailed description will be omitted. In a case where ‘comprise,’ ‘have’ and ‘include’ described in the present disclosure are used, another portion may be added unless ‘only’ is used. The terms of a singular form may include plural forms unless referred to the contrary.

[0031] In construing an element, the element is construed as including an error band although there is no explicit description. Any implementation described herein as an “example” is not necessarily to be construed as preferred or advantageous over other implementations.

[0032] In describing a position relationship, for example, when the position relationship is described as ‘upon~,’ ‘above~,’ ‘below~,’ ‘beside~,’ ‘next to~,’ or the like one or more portions may be disposed between two other portions unless ‘just’ or ‘direct’ is used, that is, one or more other parts may be disposed located between the two parts. For example, where an element or layer is disposed “on” another element or layer, a third layer or element may be interposed therebetween. The terms, such as “below,” “lower,” “above,” “upper” and the like, may be used herein to describe a relationship between element(s) as illustrated in the drawings. It will be understood that the terms are spatially relative and based on the orientation depicted in the drawings.

[0033] It will be understood that, although the terms “first,” “second,” “A,” “B,” “(a),” and “(b),” etc., may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of the present disclosure.

[0034] Features of various exemplary embodiments of the present disclosure may be partially or overall coupled to or combined with each other and may be variously inter-operated with each other and driven technically as those skilled in the art can sufficiently understand. The exemplary embodiments of the present disclosure may be carried out independently from each other or may be carried out together in a co-dependent relationship.

[0035] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which exemplary example embodiments belong. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning for example consistent with their meaning in the context of the relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. For example, the term “part” or “unit” may apply, for example, to a separate circuit or structure, an integrated circuit, a computational block of a circuit device, or any structure configured to perform a described function as should be understood to one of ordinary skill in the art.

[0036] In addition, when any dimensions, relative sizes etc. are mentioned, it should be considered that numerical values for an elements or features, or corresponding information (e.g., level, range, etc.) include a tolerance or error range that may be caused by various factors (e.g., process factors, internal or external impact, noise, etc.) even when a relevant description is not specified. Further, the term “may” fully encompasses all the meanings of the term “can”.

[0037] Hereinafter, example embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. For convenience of description, a scale of each of elements illustrated in the accompanying drawings differs from a real scale, and thus, is not limited to a scale illustrated in the drawings

[0038] Hereinafter, the preferred exemplary embodiment of the present disclosure will be described in detail with reference to the accompanying drawings.

[0039] FIG. 1 is a plan view of a display device according to an exemplary embodiment of the present disclosure.

[0040] Referring to FIG. 1, a display device according to an exemplary embodiment of the present disclosure may include a display area DA and a non-display area NDA surrounding the display area DA. The display area DA is an area in which an image may be displayed, and the non-display area NDA is an area in which an image is not displayed.

[0041] The display area DA may include a plurality of pixels P. The plurality of pixels P may be arranged in a matrix form consisting of a plurality of rows and columns. Also, the non-display area NDA may include a plurality of wirings, pads, driving circuits, and the like for driving the plurality of pixels P. However, the configurations of the display area DA and the non-display area NDA are not limited thereto.

[0042] FIG. 2 is a plan view of one-pixel P according to an exemplary embodiment of the present disclosure.

[0043] Referring to FIG. 2, one-pixel P may include a plurality of sub-pixels, such as a first sub-pixel, a second sub-pixel, a third sub-pixel and a fourth sub-pixel SP1, SP2, SP3 and SP4, but is not limited thereto. The plurality of sub-pixels, such as first to fourth sub-pixels SP1 to SP4 may emit light different from each other such as red, green, or blue (e.g., white, red, green, or blue, or cyan, magenta, or yellow, etc.). For example, the first sub-pixel SP1 may emit a light of a first color, such as red light, the second sub-pixel SP2 may emit a light of a second color, such as white light, the third sub-pixel SP3 may emit a light of a third color, such as blue light, and the fourth sub-pixel SP4 may emit a light of a fourth color, such as green light, but is not limited thereto. Also, although FIG. 2 shows that one-pixel P includes four sub-pixels SP1 to SP4, the one-pixel P is not limited thereto, and one-pixel P may include fewer or more sub-pixels.

[0044] Each of the first to fourth sub-pixels SP1 to SP4 is disposed on the substrate 100 and may include an emitting area EA and a non-emitting area NEA surrounding the emitting area EA. The emitting area EA is an area capable of emitting light, and the non-emitting area NEA is an area that does not emit light. Also, a light emitting element may be disposed in the emitting area EA, and a bank may be disposed in the non-emitting area NEA.

[0045] FIG. 3 is a cross-sectional view of a sub-pixel SP according to an exemplary embodiment of the present disclosure. In detail, FIG. 3 is a cross-sectional view of the first sub-pixel SP1 taken

along line A-A' of FIG. 2.

[0046] Referring to FIG. 3, one sub-pixel SP according to an exemplary embodiment of the present disclosure may include a substrate **100**, a buffer layer **110**, a light blocking layer **115**, a thin film transistor **120**, a passivation layer **130**, a first planarization layer **140**, a second planarization layer **150**, a light emitting device **160**, a bank **170**, and a first color filter **181** and the like, but the present disclosure is not limited thereto.

[0047] The substrate **100** may be made of glass, plastic, or a flexible polymer film, but is not limited thereto. For example, the flexible polymer film may be made of any one of polyethylene terephthalate(PET), polycarbonate(PC), acrylonitrile-butadiene-styrene copolymer(ABS), polymethyl methacrylate(PMMA), polyethylene naphthalate(PEN), polyether sulfone(PES), cyclic olefin copolymer(COC), triacetylcellulose(TAC) film, polyvinyl alcohol(PVA) film, polyimide(PI) film, and polystyrene(PS), which is only an example and is not necessarily limited thereto. The display device according to an exemplary embodiment of the present disclosure may be made of a bottom emission type in which the emitted light is emitted downward. Therefore, a transparent material may be used as the material of the substrate **100**.

[0048] The light blocking layer **115** may be disposed on the substrate **100**. The light blocking layer **115** may be disposed in an area overlapping the thin film transistor **120** and the bank **170**. The light blocking layer **115** may prevent or reduce external light from penetrating into a channel area of the thin film transistor **120**. Also, the light blocking layer **115** may prevent or reduce light from penetrating into the non-emitting area NEA. The light blocking layer **115** may include an opaque metal material such as molybdenum (Mo), but is not limited thereto.

[0049] The buffer layer **110** may be disposed on the substrate **100** and the light blocking layer **115**. The buffer layer **110** may cover the light blocking layer **115** and compensate for a step difference caused by the light blocking layer **115**. Also, adhesion between the thin film transistor **120** and the substrate **100** may be improved. The buffer layer **110** may be formed of an inorganic insulating material, such as silicon oxide (SiOx), silicon nitride (SiNx), silicon oxynitride (SiOxNy), or the like, but is not limited thereto.

[0050] The thin film transistor **120** may be disposed on the buffer layer **110** and may be disposed in the non-emission area NEA. Also, the thin film transistor **120** may be disposed in an area overlapping the light blocking layer **115**. The thin film transistor **120** may include a gate electrode **121**, a semiconductor layer **122**, a gate insulating layer **123**, a first electrode such as a source electrode **124**, a second electrode such as a drain electrode **125**, and the like, but the present disclosure is not limited thereto.

[0051] The semiconductor layer **122** of the thin film transistor **120** may be disposed on the buffer layer **110**. Also, the gate electrode **121** may be disposed on the semiconductor layer **122**. The semiconductor layer **122** may include a poly-silicon semiconductor or an oxide semiconductor. In addition, when the semiconductor layer **122** includes an oxide semiconductor, at least one oxide of indium-gallium-zinc-oxide (IGZO), indium-zinc-oxide (IZO), indium-gallium-tin-oxide (IGTO), and indium-gallium-oxide (IGO) may be included. Also, the gate electrode **121** may be formed of a conductive material, for example, copper Cu, aluminum Al, molybdenum Mo, nickel Ni, titanium Ti, chromium Cr, or an alloy thereof, but is not limited thereto.

[0052] To insulate the gate electrode **121** from the semiconductor layer **122**, a gate insulating layer **123** may be disposed between the gate electrode **121** and the semiconductor layer **122**. The gate insulating layer **123** may include a single layer of silicon nitride (SiNx) or silicon oxide (SiOx), or multiple layers thereof. Also, although FIG. 3 shows a top gate structure in which the gate electrode **121** is disposed on the semiconductor layer **122**, it is not limited thereto. For example, a bottom gate structure in which the semiconductor layer **122** is disposed on the gate electrode **121** may be disclosed.

[0053] The passivation layer **130** may be disposed on the gate electrode **121**. The passivation layer **130** may be formed of an inorganic insulating material such as silicon oxide (SiOx), silicon nitride

(SiNx), silicon oxynitride (SiOxNy), or the like. Depending on circumstances, the passivation layer **130** may be omitted when the first planarization layer **140** has a function of protecting the thin film transistor **120**. The source electrode **124** and the drain electrode **125** may be disposed on the passivation layer **130** while facing each other. The source electrode **124** and the drain electrode **125** may be connected with the semiconductor layer **122** through contact holes formed in the gate insulating layer **123** and the passivation layer **130**.

[0054] The first and second planarization layers **140** and **150** may be disposed on the thin film transistor **120**. The first planarization layer **140** may be disposed on the thin film transistor **120**, and the second planarization layer **150** may be disposed on the first planarization layer **140**. The first and second planarization layers **140** and **150** may protect the thin film transistor **120**. The first and second planarization layers **140** and **150** may compensate for a step difference caused by the thin film transistor **120** to planarize an upper region of the thin film transistor **120**. Furthermore, the first and second planarization layers **140** and **150** may be formed of an organic insulating material such as an acrylic resin, an epoxy resin, a phenolic resin, a polyimide resin, or a polyimide resin, but embodiments are not limited thereto.

[0055] The light emitting device **160** may be disposed on the second planarization layer **150**. The light emitting device **160** may include a first electrode **161**, a light emitting layer **162**, and a second electrode **163**, but is not limited thereto.

[0056] The first electrode **161** may be disposed on the second planarization layer **150** and may function as an anode of the display device. The first electrode **161** may be electrically connected with the drain electrode **125** of the thin film transistor **120** through a contact hole formed in the first and second planarization layers **140** and **150**, but is not limited thereto.

[0057] Since the display device according to an exemplary embodiment of the present disclosure is configured in a bottom emission type, the first electrode **161** may include a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO) to transmit the light emitted from the light emitting layer **162** to a lower side of the display device. Also, the display device according to an exemplary embodiment of the present disclosure may be configured in a top emission type.

[0058] The bank **170** may be disposed on the second planarization layer **150** and the first electrode **161**. The bank **170** serves to define a sub-pixel. The bank **170** may define an emitting area EA and a non-emitting area NEA. That is, the area in which the bank **170** is not disposed may become the emitting area EA, and the area in which the bank **170** is disposed may become the non-emitting area NEA.

[0059] The bank **170** may include an organic insulating material such as an acrylic resin, an epoxy resin, a phenolic resin, a polyamide resin, a polyimide resin, or the like. Alternatively, the bank **170** may include an inorganic insulating material such as silicon oxide (SiOx), silicon nitride (SiNx), silicon oxynitride (SiOxNy). Also, the bank **170** may include a black dye in order to absorb light incident from the outside. Further, the bank **170** may also be made of a transparent insulating material.

[0060] The light emitting layer **162** may be disposed on the first electrode **161**. The light emitting layer **162** may also be disposed on an upper surface of the bank **170**. The light emitting layer **162** may include one or more of a hole transporting layer, an organic light emission layer, an electron transporting layer, but the present disclosure is not limited thereto. In this case, when a voltage is applied to the first electrode **161** and the second electrode **163**, holes and electrons move to the organic light emission layer through the hole transport layer and the electron transport layer, respectively, and may be combined with each other in the organic light emission layer to emit light.

[0061] The second electrode **163** may be disposed on the light emitting layer **162**. The second electrode **163** may function as a cathode of the display device, but is not limited thereto. Like the light emitting layer **162**, the second electrode **163** may also be disposed on the upper surface of the bank **170**.

[0062] The second electrode **163** may be made of a highly reflective metal material. For example, the second electrode **163** may include a metal material such as aluminum (Al), silver (Ag), copper (Cu), molybdenum (Mo), titanium (Ti), tungsten (W), or chromium (Cr), or an alloy thereof. Also, the second electrode **163** may include a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO).

[0063] The first color filter **181** may be disposed on the first planarization layer **140** and may be disposed in the emitting area EA. That is, the first color filter **181** may be disposed below the light emitting device **160**. The first color filter **181** may transmit light in a particular color wavelength band, such as a red wavelength band. Accordingly, when the light generated by the light emitting device **160** is incident on the first color filter **181**, red light may be emitted from the first color filter **181**. That is, the first sub-pixel SP1 may emit red light, but is not limited thereto.

[0064] FIG. 4 is a cross-sectional view of a pixel P according to a first embodiment of the present disclosure. In detail, FIG. 4 is a cross-sectional view of the first to fourth sub-pixels SP1 to SP4 taken along line B-B' of FIG. 2.

[0065] As described in FIG. 4, each of the sub-pixels SP may include a substrate **100**, a buffer layer **110**, a light blocking layer **115**, a thin film transistor **120**, a passivation layer **130**, a first planarization layer **140**, a second planarization layer **150**, a light emitting device **160**, and a bank **170**, and the like. FIG. 4 is a cross-sectional view taken along line B-B' of FIG. 2, and thus a structure of the thin film transistor **120** is not shown.

[0066] Referring to FIG. 4, the buffer layer **110**, the light blocking layer **115**, a gate insulating layer **123** of the thin film transistor **120**, a passivation layer **130**, a first planarization layer **140**, and a second planarization layer **150** may be sequentially disposed on the substrate **100**, but is not limited thereto.

[0067] The light blocking layer **115** may be disposed at a position overlapping the bank **170**. Also, the light blocking layer **115** may be patterned. For example, the plurality of light blocking layers **115** spaced apart from each other may be disposed between the first and second sub-pixels SP1 and SP2, but are not limited thereto. Also, one light blocking layer **115** may be disposed between the second and third sub-pixels SP2 and SP3, but is not limited thereto. Also, the plurality of light blocking layers **115** spaced apart from each other may be disposed between the third and fourth sub-pixels SP3 and SP4, without being limited thereto.

[0068] A plurality of color filters such as a first color filter, a second color filter and a third color filter **181**, **182** and **183** may be disposed on the first planarization layer **140**. The first color filter **181** may be disposed in the first sub-pixel SP1 and may transmit a light of a first color such as red light, without being limited thereto. The second color filter **182** may be disposed in the third sub-pixel SP3 and may transmit a light of a second color such as blue light, without being limited thereto. The third color filter **183** may be disposed in the fourth sub-pixel SP4 and may transmit a light of a third color such as green light, without being limited thereto. Also, since the second sub-pixel SP2 emits white light, the second sub-pixel SP2 may not include a color filter.

[0069] Each of the first to fourth sub-pixels SP1 to SP4 may include the light emitting device **160**. As described above, the light emitting device **160** may include a first electrode **161**, a light emitting layer **162**, and a second electrode **163**, without being limited thereto.

[0070] The first electrode **161** of the first sub-pixel SP1 may include a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO), without being limited thereto. Likewise, the first electrodes **161** of the third and fourth sub-pixels SP3 and SP4 may include the transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO), without being limited thereto. Also, the first electrodes **161** of the first to fourth sub-pixels SP1 to SP4 may be separated by the bank **170**.

[0071] Meanwhile, the first electrode **161** of the second sub-pixel SP2 emitting white light may include a first conductive layer **161a** and a second conductive layer **161b**, without being limited thereto.

[0072] The first conductive layer **161a** may be disposed on the second planarization layer **150**. The first conductive layer **161a** may be disposed on an entire area of the emitting area EA of the second sub-pixel SP2. Also, the first conductive layer **161a** may be formed of a conductive material having high transmittance, without being limited thereto. For example, the first conductive layer **161a** may be formed of a metal oxide. Also, the first conductive layer **161a** may be formed of a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO), without being limited thereto. Also, the first conductive layer **161a** may be a metal thin film having a thickness of 500 Å or less.

[0073] The second conductive layer **161b** may be disposed on the first conductive layer **161a**. Also, the second conductive layer **161b** may be disposed on the entire area of the emitting area EA of the second sub-pixel SP2, and may cover an entire upper surface US of the first conductive layer **161a**. The second conductive layer **161b** may be made of a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO). That is, a transmittance of the second conductive layer **161b** may be greater than or equal to that of the first conductive layer **161a**, without being limited thereto.

[0074] The light emitting layer **162** of the first to fourth sub-pixels SP1 to SP4 may be formed of the same material, but is not limited thereto. All of the light emitting layers **162** of the first to fourth sub-pixels SP1 to SP4 may generate white light. Alternatively, the light emitting layer **162** of the first sub-pixel SP1 may generate red light, the light emitting layer **162** of the second sub-pixel SP2 may emit white light, the light emitting layer **162** of the third sub-pixel SP3 may emit blue light, and the light emitting layer **162** of the fourth sub-pixel SP4 may emit green light, but is not limited thereto. Also, the light emitting layer **162** of the first to fourth sub-pixels SP1 to SP4 may be continuously formed on the bank **170**, but is not limited thereto.

[0075] Likewise, the second electrodes **163** of the first to fourth sub-pixels SP1 to SP4 may be formed of the same material, but is not limited thereto. That is, the second electrodes **163** of the first to fourth sub-pixels SP1 to SP4 may be formed of a highly reflective metal material. Also, the second electrodes **163** of the first to fourth sub-pixels SP1 to SP4 may be continuously formed on the bank **170**, but the present disclosure is not limited thereto. Specifically, the second electrodes **163** of the first to fourth sub-pixels SP1 to SP4 may be continuously formed on the light emitting layer **162**, but the present disclosure is not limited thereto.

[0076] That is, the first exemplary embodiment of the present disclosure discloses that the first electrode **161** of the second sub-pixel SP2 emitting white light has a double layer structure in a bottom emission type, but the present disclosure is not limited thereto. Specifically, the first electrode **161** may include the first conductive layer **161a** made of a conductive material having high transmittance and the second conductive layer **161b** made of a transparent conductive material, but the present disclosure is not limited thereto.

[0077] The first exemplary embodiment of the present disclosure is the bottom emission type, and in order to improve the light efficiency of the display device, the second electrode **163** of the light emitting device **160** may be formed of a highly reflective metal material., but the present disclosure is not limited thereto. Specifically, when the light generated by the light emitting layer **162** of the light emitting device proceeds toward the upper portion of the display device, the light may be reflected by the second electrode **163**. Accordingly, the path of the light may be changed from a direction of the upper portion of the display device to a direction of the lower portion of the display device. Accordingly, the light directed toward the lower portion of the display device may increase, and thus the light efficiency of the display device may be improved.

[0078] In this case, external light may penetrate from the lower portion of the substrate **100** into the display device. When external light penetrates into the first sub-pixel, the third sub-pixel and the fourth sub-pixel SP1, SP3 and SP4, external light may be absorbed through the first to third color filters **181** to **183**. Specifically, when external light penetrates into red, green, and blue sub-pixels, external light may be absorbed through the color filter. However, since the second sub-pixel SP2

such as white sub-pixel does not include the color filter, external light may be reflected by the second electrode **163**. Accordingly, the reflectance of the display device with respect to external light may increase.

[0079] However, the first exemplary embodiment of the present disclosure has the effect of reducing or minimizing the reflectance of the display device with respect to external light by forming the first electrode **161** of the second sub-pixel SP2 emitting white light in a double layer structure.

[0080] In detail, after passing through the first electrode **161** in the second sub-pixel SP2, an external light L1 may be reflected by the second electrode **163**. Then, the external light L1 may pass through the first electrode **161** again. In this process, destructive interference occurs due to the first conductive layer **161a** having high transmittance, and an amount of the light L1' finally passing through the first electrode **161** may decrease compared to an amount of the first incident light L1. Thus, the reflectance of the display device with respect to the external light may be reduced.

[0081] Also, in order for the sub-pixel SP to emit light, a light L2 generated in the light emitting layer **162** may pass through the first conductive layer **161a** toward the lower portion of the substrate **100**. In this case, since the first conductive layer **161a** has a high transmittance, an amount of light L2 generated in the light emitting layer **162** may be maintained to some extent even if the light L2 passes through the first conductive layer **161a**. Accordingly, it is possible to minimize the reduction of the light generated in the light emitting layer **162** by the first conductive layer **161a**.

[0082] FIG. 5 is a cross-sectional view of a pixel P according to a second exemplary embodiment of the present disclosure.

[0083] Compared with FIG. 4, FIG. 5 illustrates substantially the same structure except for the structure of the first electrode **161** of the second sub-pixel SP2. Accordingly, the same reference numerals are used for components or substantially the same that are the same as those of the pixel P illustrated in FIG. 4, and repeated descriptions are omitted or briefly provided.

[0084] Referring to FIG. 5, the first electrode **161** of the second sub-pixel SP2 may further include a third conductive layer **161c** in addition to the first conductive layer and second conductive layer **161a** and **161b**. The third conductive layer **161c** may be disposed between the first conductive layer **161a** and the second planarization layer **150**. Specifically, the third conductive layer **161c** may be disposed on the second planarization layer **150** and may be disposed on the entire area of the emitting area EA of the second sub-pixel SP2. The first conductive layer **161a** may be disposed on the third conductive layer **161c** and may be disposed on the entire area of the emitting area EA of the second sub-pixel SP2. The second conductive layer **161b** may be disposed on the first conductive layer **161a** and may be disposed on the entire area of the emitting area EA of the second sub-pixel SP2. Also, the third conductive layer **161c** may be made of a transparent conductive material, such as an indium tin oxide (ITO) or an indium zinc oxide (IZO). Accordingly, while an adhesion between the first electrode **161** and the second planarization layer **150** is increased, an influence of the destructive interference may be increased when external light is penetrated.

[0085] FIG. 6 is a cross-sectional view of a pixel P according to a third exemplary embodiment of the present disclosure.

[0086] Compared with FIG. 4, FIG. 6 illustrates substantially the same structure except for the structure of the first electrode **161** of the second sub-pixel SP2. Accordingly, the same reference numerals are used for components that are the same or substantially the same as those of the pixel P illustrated in FIG. 4, and repeated descriptions are omitted or briefly provided.

[0087] Referring to FIG. 6, the first electrode **161** of the second sub-pixel SP2 may include a first conductive layer and a second conductive layer **161a** and **161b**. In this case, the first conductive layer **161a** may not be disposed on the entire area of the emitting area EA of the second sub-pixel SP2. The first conductive layer **161a** may be formed in a ring shape surrounding an edge of the

emitting area EA of the second sub-pixel SP2. That is, the first conductive layer **161a** may not be disposed in a center of the emitting area EA of the second sub-pixel SP2.

[0088] As one example, the second conductive layer **161b** may be disposed on the first conductive layer **161a** and may be disposed on the entire area of the emitting area EA of the second sub-pixel SP2, but is not limited thereto. That is, the second conductive layer **161b** may cover an upper surface US and an inner side surface ISS of the first conductive layer **161a**. Also, the second conductive layer **161b** may cover an upper surface USS of the second planarization layer **150** exposed by the first conductive layer **161a**.

[0089] Accordingly, the third exemplary embodiment of the present disclosure discloses that only a partial area of the first electrode **161** of the second sub-pixel SP2 is formed as a double layer. That is, an edge area of the first electrode **161** may include first and second conductive layers **161a** and **161b**, and a central area of the first electrode **161** may include only the second conductive layer **161b**. Accordingly, the light generated by the light emitting layer **162** may not pass through the first conductive layer **161a**, but may pass through the second conductive layer **161b** only. Accordingly, compared with the first embodiment, a possibility that an amount of light generated by the light emitting layer **162** is reduced is further reduced, thereby further preventing the light efficiency of the display device from being reduced.

[0090] FIG. 7 is a cross-sectional view of a pixel P according to a fourth exemplary embodiment of the present disclosure.

[0091] Compared with FIG. 6, FIG. 7 illustrates substantially the same structure except for the structure of the first electrode **161** of the second sub-pixel SP2. Accordingly, the same reference numerals are used for components that are the same or substantially the same as those of the pixel P illustrated in FIG. 6, and repeated descriptions are omitted or briefly provided.

[0092] Referring to FIG. 7, the first electrode **161** of the second sub-pixel SP2 may further include a fourth conductive layer **161d** in addition to the first conductive layer and second conductive layer **161a** and **161b**.

[0093] The fourth conductive layer **161d** may be disposed between the first and second conductive layers **161a** and **161b**. Also, the fourth conductive layer **161d** may have a shape corresponding to that of the first conductive layer **161a**, but is not limited thereto. That is, as described above in FIG. 6, since the first conductive layer **161a** is formed in a ring shape surrounding the edge of the emitting area EA of the second sub-pixel SP2, the fourth conductive layer **161d** may also be formed in a ring shape surrounding the edge of the emitting area EA of the second sub-pixel SP2, but is not limited thereto.

[0094] The fourth conductive layer **161d** may be formed of a highly reflective metal material. The fourth conductive layer **161d** may include a metal material such as aluminum (Al), silver (Ag), copper (Cu), molybdenum (Mo), titanium (Ti), tungsten (W), or chromium (Cr), or an alloy thereof, but is not limited thereto.

[0095] Accordingly, when external light is penetrated, the light may be reflected by the fourth conductive layer **161d**. The light reflected by the fourth conductive layer **161d** may be directed to the first and third sub-pixels SP1 and SP3 adjacent to the second sub-pixel SP2. Since the first color filter **181** is disposed in the first sub-pixels SP1 and the second color filter **182** is disposed in the third sub-pixels SP3, the light reflected by the fourth conductive layer **161d** may be directed to the first and second color filters **181** and **182**. Accordingly, the external light may be absorbed by the first and second color filters **181** and **182**. Therefore, the external light may be further reduced. Also, since the fourth conductive layer **161d** is disposed in the edge of the emitting area EA of the second sub-pixel SP2, an influence on the path of light generated by the light emitting layer **162** may be reduced or minimized.

[0096] FIGS. 8A to 8D are plan views of a sub-pixel according to various exemplary embodiments. Specifically, FIGS. 8A to 8D are plan views of the first electrode **161** of the second sub-pixel SP2.

[0097] FIG. 8A is a plan view of the third embodiment described above in FIG. 6. That is, the first

conductive layer **161a** may be formed in a ring shape surrounding the edge of the emitting area EA and may not be disposed on the entire area of the emitting area EA of the second sub-pixel SP2. Also, the second conductive layer **161b** may be disposed on the first conductive layer **161a** and may be disposed on the entire area of the emitting area EA of the second sub-pixel SP2. That is, the second conductive layer **161b** may cover the upper surface and the inner side surface of the first conductive layer **161a** and the upper surface of the second planarization layer **150** exposed by the first conductive layer **161a**.

[0098] Also, the first conductive layer **161a** may include not a single layer but a plurality of regions spaced apart from each other. Referring to FIG. **8B**, the first conductive layer **161a** may include a plurality of regions spaced apart from each other in a first direction. Alternatively, referring to FIG. **8C**, the first conductive layer **161a** may include a plurality of regions spaced apart from a second direction crossing the first direction. The first conductive layer **161a** may be spaced apart from the edge of the emitting area EA. Also, the second conductive layer **161b** may be disposed on the first conductive layer **161a** and may be disposed on the entire area of the emitting area EA of the second sub-pixel SP2. That is, the second conductive layer **161b** may cover the upper surface of the first conductive layer **161a**.

[0099] Referring to FIG. **8D**, the first conductive layer **161a** may be formed along the first and second directions and may have a shape crossing each other. For example, the first conductive layer **161a** may have a shape in which two regions spaced apart from each other in the first direction and two regions spaced apart from each other in the second direction overlap. Also, the first electrode **161** of the second sub-pixel SP2 is not limited to the shape disclosed in FIGS. **8A** to **8D**, and may have various shapes.

[0100] FIG. **9** is a cross-sectional view of one sub-pixel SP according to another exemplary embodiment of the present disclosure. In detail, FIG. **9** is a cross-sectional view of the first sub-pixel SP1 taken along line A-A' of FIG. **2**.

[0101] Since FIG. **9** discloses substantially the same structure as FIG. **4**, the same reference numerals are used for the components that are the same or substantially the same as those of the sub-pixel SP shown in FIG. **3**, and repeated descriptions are omitted or briefly provided.

[0102] The exemplary embodiment of FIG. **3** discloses the bottom emission type in which the emitted light is emitted downward, whereas the embodiment of FIG. **9** discloses a top emission type in which the emitted light is emitted upward. Therefore, a transparent material or an opaque material may be used as a material of a lower substrate **100**.

[0103] The light blocking layer **115** may be disposed on the lower substrate **100**. The light blocking layer **115** may be disposed in an area overlapping the thin film transistor **120**. Also, it may be disposed in both the emitting area EA and the non-emitting area NEA.

[0104] The thin film transistor **120** may be disposed on the buffer layer **110**. The thin film transistor **120** may include a gate electrode **121**, a semiconductor layer **122**, a gate insulation layer **123**, a first electrode such as a source electrode **124**, a second electrode such as a drain electrode **125**, and the like, but the present disclosure is not limited thereto. Although a bottom gate structure in which a semiconductor layer **122** is disposed on a gate electrode **121** is disclosed in FIG. **9**, it is not limited thereto. For example, a top gate structure in which the gate electrode **121** is disposed on the semiconductor layer **122** may be disclosed.

[0105] A auxiliary electrode **135** may be disposed on the gate insulating layer **123**. The auxiliary electrode **135** may be formed of the same material through the same process as the semiconductor layer **112**, but is not limited thereto. The passivation layer **130** may be disposed on the semiconductor layer **112** and the auxiliary electrode **135**.

[0106] The first and second planarization layers **140** and **150** may be disposed on the thin film transistor **120**. The first planarization layer **140** may be disposed on the thin film transistor **120**, and the second planarization layer **150** may be disposed on the first planarization layer **140**. The first and second planarization layers **140** and **150** may protect the thin film transistor **120**.

[0107] The light emitting device **160** may be disposed on the second planarization layer **150**. The light emitting device **160** may include a first electrode **161**, a light emitting layer **162**, and a second electrode **163**, but is not limited thereto.

[0108] The first electrode **161** may be disposed on the second planarization layer **150** and may function as an anode of the display device. The first electrode **161** may be electrically connected with the drain electrode **125** of the thin film transistor **120** through a connection electrode **155** disposed on the first planarization layer **140**.

[0109] The first electrode **161** may include a first transparent conductive layer **161a**, a reflective layer **161b**, and a second transparent conductive layer **161c**, without being limited thereto.

[0110] The first transparent conductive layer **161a** may be disposed on the second planarization layer **150**. The first transparent conductive layer **161a** may include a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO), without being limited thereto.

[0111] The reflective layer **161b** may be disposed on the first transparent conductive layer **161a**. The reflective layer **161b** may be formed of a metal material. For example, the reflective layer **161b** may include a metal material such as aluminum (Al), silver (Ag), copper (Cu), molybdenum (Mo), titanium (Ti), tungsten (W), or chromium (Cr), or an alloy thereof, without being limited thereto.

[0112] The second transparent conductive layer **161c** may be disposed on the reflective layer **161b**. The second transparent conductive layer **161c** may include a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO), without being limited thereto.

[0113] The light emitting layer **162** may be disposed on the first electrode **161**. The light emitting layer **162** may also be disposed on an upper surface of the bank **170**. The light emitting layer **162** may be disposed on the entire area of the emitting area EA and the non-emitting area NEA.

[0114] The second electrode **163** may be disposed on the light emitting layer **162**. The second electrode **163** may include a first conductive layer **163a** and a second conductive layer **163b**, and the like.

[0115] The first conductive layer **163a** may be disposed on the light emitting layer **162**. The first conductive layer **163a** may be disposed on the entire area of the emitting area EA and the non-emitting area NEA. Also, the first conductive layer **163a** may be formed of a material having high transmittance, without being limited thereto. For example, the first conductive layer **163a** may be formed of a metal oxide, without being limited thereto. Also, the first conductive layer **163a** may be formed of a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO), without being limited thereto. Also, the first conductive layer **163a** may be a metal thin film having a thickness of 500 Å or less. For example, the first conductive layer **163a** may be a thin film including a metal such as aluminum (Al), silver (Ag), copper (Cu), molybdenum (Mo), titanium (Ti), tungsten (W), or chromium (Cr), without being limited thereto.

[0116] The second conductive layer **163b** may be disposed on the first conductive layer **163a**. Also, the second conductive layer **163b** may be disposed on the entire emitting area EA and the non-emitting area NEA, and may cover an entire upper surface of the first conductive layer **163a**. The second conductive layer **163b** may be formed of a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO), without being limited thereto. That is, a transmittance of the second conductive layer **163b** may be greater than or equal to that of the first conductive layer **163a**, without being limited thereto.

[0117] The first color filter **181** and the black matrix BM may be disposed on a lower surface of an upper substrate **200**. The first color filter **181** may be disposed in the emitting area EA, and the black matrix BM may be disposed in the non-emitting area NEA. The black matrix BM may absorb light.

[0118] The lower substrate **100** and the upper substrate **200** may be bonded by an encapsulation layer **190**. That is, the encapsulation layer **190** may be disposed between the light emitting device **160** and the color filter **181**. The encapsulation layer **190** may include an organic insulating

material such as an acrylic resin, an epoxy resin, a phenolic resin, a polyamide resin, a polyimide resin, or the like but is not limited thereto. Also, the encapsulation layer **190** may include an inorganic insulating material such as silicon nitride (SiN), silicon oxide (SiO), silicon oxynitride (SiON) and aluminum oxide (AlO).

[0119] Referring to FIG. **9**, a structure in which an insulating layer is disposed between the light blocking layer **115** and the auxiliary electrode **135** may be disclosed. Accordingly, a first storage capacitor Cst1 may be formed. Also, a structure in which an insulating layer is disposed between the auxiliary electrode **135** and the first electrode **161** may be disclosed. Accordingly, a second storage capacitor Cst2 may be formed.

[0120] FIG. **10** is a cross-sectional view of a pixel according to a fifth exemplary embodiment of the present disclosure. In detail, FIG. **10** is a cross-sectional view of the first to fourth sub-pixels SP1 to SP4 taken along line B-B' of FIG. **2**.

[0121] As described above in FIG. **9**, each of the sub-pixels SP may include a lower substrate **100**, a buffer layer **110**, a light blocking layer **115**, a thin film transistor **120**, a passivation layer **130**, a first planarization layer **140**, a second planarization layer **150**, a light emitting device **160**, a bank **170**, and the like.

[0122] Referring to FIG. **10**, the buffer layer **110**, the light blocking layer **115**, a gate insulating layer **123** of the thin film transistor **120**, an auxiliary electrode **135**, the passivation layer **130**, the first planarization layer **140**, and the second planarization layer **150** may be sequentially disposed on the lower substrate **100**, but is not limited thereto.

[0123] The light blocking layer **115** may be disposed at a position overlapping the bank **170**. Also, the light blocking layer **115** may be disposed at a position overlapping the light emitting device **160**.

[0124] A plurality of color filters such as first to third color filters **181** to **183** may be disposed on a lower surface of an upper substrate **200**. The first color filter **181** may be disposed in the first sub-pixel SP1 and may transmit a light of a first color such as red light, without being limited thereto. The second color filter **182** may be disposed in the third sub-pixel SP3 and may transmit a light of a second color such as blue light, without being limited thereto. The third color filter **183** may be disposed in the fourth sub-pixel SP4 and may transmit a light of a third color such as green light, without being limited thereto. Also, since the second sub-pixel SP2 emits white light, the second sub-pixel SP2 may not include a color filter.

[0125] The black matrix BM may be disposed on the lower surface of the upper substrate **200**. Also, the black matrix BM may be disposed in a boundary area of the sub-pixels SP adjacent to each other.

[0126] Each of the first to fourth sub-pixels SP1 to SP4 may include a light emitting device **160**. As described above, the light emitting device **160** may include a first electrode **161**, a light emitting layer **162**, and a second electrode **163**, but is not limited thereto.

[0127] The first electrode **161** of the first sub-pixel SP1 may include a first transparent conductive layer **161a**, a reflective layer **161b**, and a second transparent conductive layer **163c**, but is not limited thereto. Likewise, the first electrode **161** of each of the second to fourth sub-pixels SP2 to SP4 may include the first transparent conductive layer **161a**, the reflective layer **161b**, and the second transparent conductive layer **163c**. The first electrode **161** of each of the first to fourth sub-pixels SP1 to SP4 may be separated by the bank **170**.

[0128] The light emitting layer **162** of the first to fourth sub-pixels SP1 to SP4 may be formed of the same material, but is not limited thereto. All of the light emitting layers **162** of the first to fourth sub-pixels SP1 to SP4 may generate white light. Alternatively, the light emitting layer **162** of the first sub-pixel SP1 may generate red light, the light emitting layer **162** of the second sub-pixel SP2 may emit white light, the light emitting layer **162** of the third sub-pixel SP3 may emit blue light, and the light emitting layer **162** of the fourth sub-pixel SP4 may emit green light, but is not limited thereto. Also, the light emitting layer **162** of the first to fourth sub-pixels SP1 to SP4 may be

continuously formed on the bank **170**, but is not limited thereto.

[0129] The second electrode **163** of the first sub-pixel SP**1** may include a first conductive layer **163a** and a second conductive layer **163b**. Likewise, the second electrode **163** of each of the second to fourth sub-pixels SP**2** to SP**4** may include the first conductive layer **163a** and the second conductive layer **163b**. The second electrodes **163** of the first to fourth sub-pixels SP**1** to SP**4** may be continuously formed on the bank **170**, but the present disclosure is not limited thereto.

[0130] That is, the fifth exemplary embodiment of the present disclosure discloses that the second electrodes **163** of the first to fourth sub-pixels SP**1** to SP**4** have a double layer structure in the top emission type, but is not limited thereto. Specifically, the second electrode **163** may include the first conductive layer **162a** made of a conductive material having high transmittance and the second conductive layer **162b** made of a transparent conductive material.

[0131] The fifth exemplary embodiment of the present disclosure is the top emission type, and in order to improve the light efficiency of the display device, the first electrode **161** of the light emitting device **160** is formed to include the reflective layer **161b**. Specifically, when the light generated by the light emitting layer **162** of the light emitting device proceeds toward a lower portion of the display device, the light is reflected by the reflective layer **161b** of the first electrode **161**. Accordingly, a path of the light may be changed from a direction of the lower portion of the display device to a direction of an upper portion of the display device. Therefore, light directed toward the upper portion of the display device may increase, and thus the light efficiency of the display device may be improved.

[0132] In this case, external light may be penetrated from an upper portion of the upper substrate **200** to the inside of the display device. When external light is penetrated into the first sub-pixel, the third sub-pixel and the fourth sub-pixel SP**1**, SP**3** and SP**4**, external light may be absorbed through the first to third color filters **181** to **183**. Specifically, when the external light is penetrated into the red, green, and blue sub-pixels, the external light may be absorbed through the color filter.

However, since the second sub-pixel SP**2** such as white sub-pixel does not include a color filter, the external light may be reflected by the reflective layer **161b** of the first electrode **161**. Accordingly, the reflectance of the display device with respect to the external light may increase.

[0133] However, the fifth exemplary embodiment of the present disclosure has the effect of reducing or minimizing the reflectance of the display device to external light by forming the second electrode **163** of the first to fourth sub-pixels SP**1** to SP**4** in a double layer structure.

[0134] In detail, after passing through the second electrode **163** in the second sub-pixel SP**2**, an external light L**1** may be reflected by the reflective layer **161b** of the first electrode **161**. Then, the external light L**1** may pass through the second electrode **163** again. In this process, destructive interference occurs due to the first conductive layer **163a** having high transmittance, and an amount of light L**1'** finally passing through the second electrode **163** may decrease compared to an amount of the first incident light L**1**. Thus, the reflectance of the display device with respect to the external light may be reduced.

[0135] Also, in order for the sub-pixel SP to emit light, a light L**2** generated in the light emitting layer **162** may pass through the first conductive layer **163a** toward the upper substrate **200**. In this case, since the first conductive layer **163a** has a high transmittance, an amount of light L**2** generated in the light emitting layer **162** may be maintained to some extent even if the light L**2** passes through the first conductive layer **163a**. Accordingly, it is possible to minimize the reduction of the light generated in the light emitting layer **162** by the first conductive layer **163a**.

[0136] FIG. **11** is a cross-sectional view of a pixel P according to a sixth exemplary embodiment of the present disclosure.

[0137] Compared with FIG. **10**, FIG. **11** discloses substantially the same structure except for the structures of the second electrodes **163** of the first to fourth sub-pixels SP**1** to SP**4**. Accordingly, the same reference numerals are used for components that are the same or substantially the same as those of the pixel P shown in FIG. **10**, and repeated descriptions are omitted.

[0138] Referring to FIG. 11, the second electrodes **163** of the first to fourth sub-pixels SP1 to SP4 may further include a third conductive layer **163c** in addition to the first conductive layer **163a** and the second conductive layer **163b**. The third conductive layer **163c** may be disposed between the first conductive layer **163a** and the light emitting layer **162**. The third conductive layer **163c** may be disposed on the entire area of the emitting area EA and the non-emitting area NEA. Also, the third conductive layer **163c** may be formed of a material having high transmittance. For example, the third conductive layer **163c** may be formed of a metal oxide. Also, the third conductive layer **163c** may be formed of a transparent conductive material such as an indium tin oxide (ITO) or an indium zinc oxide (IZO), without being limited thereto. Also, the third conductive layer **163c** may be a metal thin film having a thickness of 500 Å or less. Accordingly, when external light is penetrated, the influence of the destructive interference may be increased.

[0139] FIG. 12 is a cross-sectional view of a pixel according to a seventh exemplary embodiment of the present disclosure.

[0140] FIG. 12 discloses a structure in which the second conductive layer **163b** is omitted in the sixth embodiment of FIG. 11. That is, the second electrodes **163** of the first to fourth sub-pixels SP1 to SP4 may include the first and third conductive layers **163a** and **163c**. The third conductive layer **163c** may be disposed between the first conductive layer **163a** and the light emitting layer **162**. Also, the first conductive layer **163a** may be in contact with the encapsulation layer **190**. Accordingly, while the adhesion between the second electrode **163** and the encapsulation layer **190** is increased, the destructive interference function may be performed when external light is penetrated.

[0141] According to the present disclosure, the following advantageous effects may be obtained.

[0142] According to the present disclosure, the plurality of light conversion layers may be formed so that light efficiency may be improved, and reflectance due to external light may be reduced.

[0143] A display device according to one or more exemplary embodiments of the present disclosure may be applied to mobile apparatuses, video phones, smart watches, watch phones, wearable apparatuses, foldable apparatuses, rollable apparatuses, bendable apparatuses, flexible apparatuses, curved apparatuses, variable apparatuses, sliding apparatuses, electronic organizers, electronic books, portable multimedia players (PMPs), personal digital assistants (PDAs), MP3 players, mobile medical devices, desktop personal computers (PCs), laptop PCs, netbook computers, workstations, navigation apparatuses, automotive navigation apparatuses, automotive display apparatuses, automotive apparatuses, theater apparatuses, theater display apparatuses, TVs, wall paper display apparatuses, signage apparatuses, game machines, notebook computers, monitors, cameras, camcorders, home appliances, etc, but embodiments of the present disclosure are not limited thereto.

[0144] Although the exemplary embodiments of the present disclosure have been described in detail with reference to the accompanying drawings, the present disclosure is not limited thereto and may be embodied in many different forms without departing from the technical concept of the present disclosure. Therefore, the exemplary embodiments of the present disclosure are provided for illustrative purposes only but not intended to limit the technical concept of the present disclosure. The scope of the technical concept of the present disclosure is not limited thereto. Therefore, it should be understood that the above-described exemplary embodiments are illustrative in all aspects and do not limit the present disclosure. The protective scope of the present disclosure should be construed based on the following claims, and all the technical concepts in the equivalent scope thereof should be construed as falling within the scope of the present disclosure.

[0145] The various embodiments described above can be combined to provide further embodiments. All of the U.S. patents, U.S. patent application publications, U.S. patent applications, foreign patents, foreign patent applications and non-patent publications referred to in this specification and/or listed in the Application Data Sheet are incorporated herein by reference, in their entirety. Aspects of the embodiments can be modified, if necessary to employ concepts of the

various patents, applications and publications to provide yet further embodiments.
[0146] These and other changes can be made to the embodiments in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the claims to the specific embodiments disclosed in the specification and the claims, but should be construed to include all possible embodiments along with the full scope of equivalents to which such claims are entitled. Accordingly, the claims are not limited by the disclosure.

Claims

1. A display device comprising: a substrate on which a first sub-pixel and a second sub-pixel are disposed, each of the first sub-pixel and the second sub-pixel including an emitting area and a non-emitting area adjacent to the emitting area, wherein each of the first and second sub-pixels includes: a first electrode disposed in the emitting area; a light emitting layer disposed on the first electrode; and a second electrode disposed on the light emitting layer, wherein, in operation, the first sub-pixel emits a light of a first color different from a light emitted by the second sub-pixel, and the second sub-pixel emits white light, and wherein a structure of the first electrode of the first sub-pixel and a structure of the first electrode of the second sub-pixel are different from each other.
2. The display device of claim 1, wherein the light of the first color comprises any one of red, green, and blue light.
3. The display device of claim 2, wherein the first electrode of the first sub-pixel includes a transparent conductive layer, wherein the first electrode of the second sub-pixel includes a first conductive layer and a second conductive layer disposed on the first conductive layer, and wherein a transmittance of the second conductive layer is greater than or equal to a transmittance of the first conductive layer.
4. The display device of claim 3, wherein the first conductive layer includes metal oxide, and the second conductive layer includes a transparent conductive material.
5. The display device of claim 3, wherein the first electrode of the second sub-pixel further includes a third conductive layer disposed on a lower surface of the first conductive layer, and the third conductive layer includes a transparent conductive material.
6. The display device of claim 4, wherein the first conductive layer is disposed on an entire surface of the emitting area of the second sub-pixel, and the second conductive layer is disposed on the entire surface of the emitting area of the second sub-pixel and covers an upper surface of the first conductive layer.
7. The display device of claim 3, wherein the first conductive layer has a ring shape surrounding an edge of the emitting area of the second sub-pixel, and wherein the second conductive layer is disposed on an entire surface of the emitting area of the second sub-pixel and covers an upper surface and an inner side surface of the first conductive layer.
8. The display device of claim 7, wherein the second conductive layer covers the upper surface and the inner side surface of the first conductive layer and an upper surface of a planarization layer exposed by the first conductive layer.
9. The display device of claim 7, wherein the first electrode of the second sub-pixel further includes a fourth conductive layer disposed between the first and second conductive layers, and the fourth conductive layer has a shape corresponding to a shape of the first conductive layer.
10. The display device of claim 9, wherein the fourth conductive layer has a higher reflectance than the first and second conductive layers.
11. The display device of claim 3, wherein the first conductive layer includes a plurality of regions spaced apart from each other in the emitting area of the second sub-pixel, and wherein the second conductive layer is disposed on an entire area of the light emitting area of the second sub-pixel and covers an upper surface of the plurality of regions of the first conductive layer.
12. The display device of claim 1, wherein the first sub-pixel includes any one of a red color filter,

a green color filter, and a blue color filter disposed below the first electrode.

13. The display device of claim 1, further comprising a third sub-pixel disposed on the substrate and emitting light different from a light emitted by the first sub-pixel, wherein the third sub-pixel emits any one of red, green, and blue light, wherein a structure of a first electrode of the third sub-pixel and a structure of the first electrode of the first sub-pixel are the same as each other, and wherein a structure of the first electrode of the third sub-pixel and a structure of the first electrode of the second sub-pixel are different from each other.

14. The display device of claim 13, further comprising a fourth sub-pixel disposed on the substrate and emitting light different from a light emitted by the first sub-pixel and the third sub-pixel, wherein the fourth sub-pixel emits any one of red, green, and blue light, a structure of a first electrode of the fourth sub-pixel and a structure of the first electrode of the first sub-pixel are the same, and a structure of the first electrode of the fourth sub-pixel and a structure of the first electrode of the second sub-pixel are different.

15. A display device comprising: a substrate on which a plurality of sub-pixels is disposed, the plurality of sub-pixels including an emitting area and a non-emitting area adjacent to the emitting area, wherein each of the plurality of sub-pixels includes: a first electrode disposed in the emitting area; a light emitting layer disposed on the first electrode; and a second electrode disposed on the light emitting layer, wherein the second electrode includes a first conductive layer and a second conductive layer disposed on the first conductive layer, and wherein a transmittance of the second conductive layer is different from a transmittance of the first conductive layer.

16. The display device of claim 15, wherein the transmittance of the second conductive layer is greater than or equal to the transmittance of the first conductive layer.

17. The display device of claim 16, wherein the first conductive layer includes metal oxide, and the second conductive layer includes a transparent conductive material.

18. The display device of claim 17, wherein the second electrode further includes a third conductive layer disposed below the first conductive layer, and the third conductive layer includes a metal oxide.

19. The display device of claim 18, wherein the second electrode includes the first conductive layer and the third conductive layer disposed below the first conductive layer without the second conductive layer.

20. The display device of claim 15, wherein the transmittance of the first conductive layer is greater than or equal to the transmittance of the second conductive layer.

21. The display device of claim 20, wherein the first conductive layer includes a transparent conductive material, and the second conductive layer includes metal oxide.

22. The display device of claim 15, wherein the plurality of sub-pixels includes a first sub-pixel and a second sub-pixel, and wherein the first sub-pixel emits any one of red, green, and blue light, and the second sub-pixel emits white light.

23. The display device of claim 22, wherein the first sub-pixel includes any one of a red color filter, a green color filter, and a blue color filter disposed on the second electrode.

24. The display device of claim 15, wherein the first electrode includes a first transparent conductive layer, a reflective layer disposed on the first transparent conductive layer, and a second transparent conductive layer disposed on the reflective layer.
