

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396836
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	MacDonald; Sumaira et al.

Fenestrated sheath for embolic protection during transcarotid carotid artery revascularization

Abstract

Methods, devices, and systems establish and facilitate retrograde or reverse flow blood circulation in the region of the carotid artery bifurcation in order to limit or prevent the release of emboli into the cerebral vasculature such as into the internal carotid artery. The methods are particularly useful for interventional procedures, such as stenting and angioplasty, atherectomy performed through a transcarotid approach or transfemoral into the common carotid artery, either using an open surgical technique or using a percutaneous technique, such as a modified Seldinger technique or a micropuncture technique.

Inventors: MacDonald; Sumaira (Sunnyvale, CA), Kume; Stewart M. (Sunnyvale, CA)

Applicant: Boston Scientific Scimed, Inc. (Maple Grove, MN)

Family ID: 1000008778747

Assignee: BOSTON SCIENTIFIC SCIMED, INC. (Maple Grove, MN)

Appl. No.: 18/535698

Filed: December 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240341941 A1	Oct. 17, 2024

Related U.S. Application Data

continuation parent-doc US 17470213 20210909 US 11864988 child-doc US 18535698
continuation parent-doc US 16171784 20181026 US 11141259 20211012 child-doc US 17470213
us-provisional-application US 62580869 20171102

Publication Classification

Int. Cl.: **A61F2/01** (20060101); **A61B17/12** (20060101); **A61F2/954** (20130101); **A61M25/00** (20060101); **A61M25/09** (20060101); A61M25/06 (20060101); A61M25/10 (20130101)

U.S. Cl.:

CPC **A61F2/014** (20200501); **A61B17/12** (20130101); **A61F2/954** (20130101); **A61M25/0032** (20130101); **A61M25/09** (20130101); A61M2025/0008 (20130101); A61M2025/0681 (20130101); A61M2025/1052 (20130101)

Field of Classification Search

CPC: A61B (17/12022); A61B (17/12045); A61B (17/1204); A61B (17/12036); A61B (17/12031); A61B (17/12027); A61B (17/12109); A61B (17/12136); A61B (17/12168); A61B (17/12172); A61M (1/3613)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4493707	12/1984	Ishihara	N/A	N/A
4865581	12/1988	Lundquist et al.	N/A	N/A
5584803	12/1995	Stevens et al.	N/A	N/A
5727594	12/1997	Choksi	N/A	N/A
5769830	12/1997	Parker	N/A	N/A
5916193	12/1998	Stevens et al.	N/A	N/A
6033413	12/1999	Mikus et al.	N/A	N/A
6152912	12/1999	Jansen et al.	N/A	N/A
6161547	12/1999	Barbut	N/A	N/A
6165199	12/1999	Barbut	N/A	N/A
6197014	12/2000	Samson et al.	N/A	N/A
6206868	12/2000	Parodi	N/A	N/A
6312444	12/2000	Barbut	N/A	N/A
6383172	12/2001	Barbut	N/A	N/A
6413235	12/2001	Parodi	N/A	N/A
6423032	12/2001	Parodi	N/A	N/A
6527746	12/2002	Oslund et al.	N/A	N/A
6540712	12/2002	Parodi et al.	N/A	N/A
6558356	12/2002	Barbut	N/A	N/A
6595953	12/2002	Coppi et al.	N/A	N/A
6626886	12/2002	Barbut	N/A	N/A
6673040	12/2003	Samson et al.	N/A	N/A
6682505	12/2003	Bates et al.	N/A	N/A
6824553	12/2003	Samson et al.	N/A	N/A
6837881	12/2004	Barbut	N/A	N/A
6855136	12/2004	Dorros et al.	N/A	N/A
6878140	12/2004	Barbut	N/A	N/A
6887227	12/2004	Barbut	N/A	N/A

6929634	12/2004	Dorros et al.	N/A	N/A
6936060	12/2004	Hogendijk et al.	N/A	N/A
7004931	12/2005	Hogendijk	N/A	N/A
7083594	12/2005	Coppi	N/A	N/A
7108677	12/2005	Courtney et al.	N/A	N/A
7223253	12/2006	Hogendijk	N/A	N/A
7422579	12/2007	Wahr et al.	N/A	N/A
7604612	12/2008	Ressemann et al.	N/A	N/A
7833259	12/2009	Boatman	N/A	N/A
8083788	12/2010	Acosta et al.	N/A	N/A
8157760	12/2011	Criado et al.	N/A	N/A
8545432	12/2012	Renati et al.	N/A	N/A
9126018	12/2014	Garrison	N/A	N/A
9241699	12/2015	Kume et al.	N/A	N/A
9789242	12/2016	Criado et al.	N/A	N/A
9833555	12/2016	Criado et al.	N/A	N/A
10039906	12/2017	Kume et al.	N/A	N/A
10085864	12/2017	Chou et al.	N/A	N/A
10159479	12/2017	Hentges et al.	N/A	N/A
10286139	12/2018	Criado et al.	N/A	N/A
10426885	12/2018	Criado et al.	N/A	N/A
2001/0044598	12/2000	Parodi	N/A	N/A
2002/0052620	12/2001	Barbut	N/A	N/A
2002/0087119	12/2001	Parodi	N/A	N/A
2002/0165598	12/2001	Wahr et al.	N/A	N/A
2002/0173815	12/2001	Hogendijk et al.	N/A	N/A
2003/0040762	12/2002	Dorros et al.	N/A	N/A
2003/0050600	12/2002	Ressemann et al.	N/A	N/A
2003/0069468	12/2002	Bolling et al.	N/A	N/A
2003/0212304	12/2002	Lattouf	N/A	N/A
2004/0064179	12/2003	Linder et al.	N/A	N/A
2005/0124973	12/2004	Dorros et al.	N/A	N/A
2005/0131453	12/2004	Parodi	N/A	N/A
2005/0154344	12/2004	Chang	N/A	N/A
2005/0154349	12/2004	Renz et al.	N/A	N/A
2005/0222532	12/2004	Bertolero et al.	N/A	N/A
2005/0228432	12/2004	Hogendijk et al.	N/A	N/A
2005/0267323	12/2004	Dorros et al.	N/A	N/A
2006/0106338	12/2005	Chang	N/A	N/A
2006/0149350	12/2005	Patel et al.	N/A	N/A
2009/0024072	12/2008	Criado et al.	N/A	N/A
2009/0048654	12/2008	Chmura et al.	N/A	N/A
2009/0198172	12/2008	Garrison et al.	N/A	N/A
2009/0228020	12/2008	Wallace et al.	N/A	N/A
2009/0254166	12/2008	Chou et al.	N/A	N/A
2010/0042118	12/2009	Garrison et al.	N/A	N/A
2010/0191169	12/2009	Chang	N/A	N/A
2010/0191170	12/2009	Chang	N/A	N/A
2010/0204684	12/2009	Garrison et al.	N/A	N/A
2010/0217276	12/2009	Garrison et al.	N/A	N/A

2010/0228269	12/2009	Garrison et al.	N/A	N/A
2010/0280431	12/2009	Criado et al.	N/A	N/A
2011/0004147	12/2010	Renati et al.	N/A	N/A
2011/0034986	12/2010	Chou et al.	N/A	N/A
2011/0166496	12/2010	Criado et al.	N/A	N/A
2011/0166497	12/2010	Criado et al.	N/A	N/A
2011/0213410	12/2010	Ginn et al.	N/A	N/A
2012/0136350	12/2011	Goshgarian et al.	N/A	N/A
2012/0197383	12/2011	Ivancev et al.	N/A	N/A
2013/0172852	12/2012	Chang	N/A	N/A
2014/0031925	12/2013	Garrison et al.	N/A	N/A
2014/0058414	12/2013	Garrison et al.	N/A	N/A
2014/0135661	12/2013	Garrison et al.	N/A	N/A
2014/0296769	12/2013	Hyde et al.	N/A	N/A
2014/0296868	12/2013	Garrison et al.	N/A	N/A
2015/0025616	12/2014	Chang	N/A	N/A
2015/0080942	12/2014	Garrison et al.	N/A	N/A
2015/0141760	12/2014	Chou et al.	N/A	N/A
2015/0150562	12/2014	Chang	N/A	N/A
2015/0174368	12/2014	Garrison et al.	N/A	N/A
2015/0327843	12/2014	Garrison	N/A	N/A
2016/0128688	12/2015	Garrison et al.	N/A	N/A
2016/0158044	12/2015	Chou et al.	N/A	N/A
2016/0158502	12/2015	Kume et al.	N/A	N/A
2016/0242764	12/2015	Garrison et al.	N/A	N/A
2016/0271315	12/2015	Chang	N/A	N/A
2016/0271316	12/2015	Criado et al.	N/A	N/A
2016/0279379	12/2015	Chang	N/A	N/A
2016/0296690	12/2015	Kume et al.	N/A	N/A
2016/0317288	12/2015	Rogers et al.	N/A	N/A
2017/0021127	12/2016	Manouchehr et al.	N/A	N/A
2017/0043141	12/2016	Kume et al.	N/A	N/A
2017/0136212	12/2016	Garrison et al.	N/A	N/A
2017/0209260	12/2016	Garrison et al.	N/A	N/A
2017/0296798	12/2016	Kume et al.	N/A	N/A
2017/0312491	12/2016	Ryan et al.	N/A	N/A
2017/0354523	12/2016	Chou et al.	N/A	N/A
2017/0354803	12/2016	Kume et al.	N/A	N/A
2017/0361072	12/2016	Chou et al.	N/A	N/A
2017/0368296	12/2016	Chang	N/A	N/A
2018/0008294	12/2017	Garrison et al.	N/A	N/A
2018/0154063	12/2017	Criado et al.	N/A	N/A
2018/0185614	12/2017	Garrison et al.	N/A	N/A
2018/0289884	12/2017	Criado et al.	N/A	N/A
2019/0105439	12/2018	Criado et al.	N/A	N/A
2019/0125512	12/2018	MacDonald et al.	N/A	N/A
2019/0150916	12/2018	Hentges et al.	N/A	N/A
2019/0175885	12/2018	Kume et al.	N/A	N/A
2019/0231962	12/2018	Criado et al.	N/A	N/A
2019/0254680	12/2018	Chang	N/A	N/A

2019/0262530	12/2018	Criado et al.	N/A	N/A
2019/0269538	12/2018	Chou et al.	N/A	N/A
2019/0350568	12/2018	Garrison	N/A	N/A
2019/0366070	12/2018	Kume et al.	N/A	N/A
2019/0388654	12/2018	Chou et al.	N/A	N/A
2020/0009406	12/2019	Garrison et al.	N/A	N/A
2020/0015826	12/2019	Chang	N/A	N/A
2020/0016321	12/2019	Criado et al.	N/A	N/A
2020/0038576	12/2019	Garrison et al.	N/A	N/A
2020/0054871	12/2019	Ryan et al.	N/A	N/A
2020/0108221	12/2019	Chang	N/A	N/A
2020/0113587	12/2019	Garrison et al.	N/A	N/A
2020/0170637	12/2019	Garrison et al.	N/A	N/A
2020/0171277	12/2019	Garrison et al.	N/A	N/A
2020/0282127	12/2019	Garrison et al.	N/A	N/A
2020/0297912	12/2019	Criado et al.	N/A	N/A
2021/0212679	12/2020	Hentges et al.	N/A	N/A
2021/0228847	12/2020	Kume et al.	N/A	N/A
2021/0236790	12/2020	Kume et al.	N/A	N/A
2021/0251634	12/2020	Chang	N/A	N/A
2021/0290213	12/2020	Garrison	N/A	N/A
2021/0290257	12/2020	Garrison et al.	N/A	N/A
2021/0298929	12/2020	Wallace et al.	N/A	N/A
2021/0299343	12/2020	Criado et al.	N/A	N/A
2021/0299425	12/2020	Kume et al.	N/A	N/A
2021/0307945	12/2020	Chou et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2525742	12/2014	EP	N/A
H07-265412	12/1994	JP	N/A
H08-071161	12/1995	JP	N/A
10-052490	12/1997	JP	N/A
H10-033666	12/1997	JP	N/A
2001-523492	12/2000	JP	N/A
2002-522149	12/2001	JP	N/A
2002-543914	12/2001	JP	N/A
2003-521286	12/2002	JP	N/A
2003-521299	12/2002	JP	N/A
2005-523123	12/2004	JP	N/A
2007-301326	12/2006	JP	N/A
WO-99/25419	12/1998	WO	N/A
WO-99/040945	12/1998	WO	N/A
WO-00/76390	12/1999	WO	N/A
WO-03/090831	12/2002	WO	N/A

OTHER PUBLICATIONS

Alexandrescu et al. (2006) “Filter-protected carotid stenting via a minimal cervical access with transitory aspirated reversed flow during initial passage of the target lesion” J. Endovasc. Ther. 13(2):196-204. cited by applicant

Alvarez et al. (2008). "Transcervical carotid stenting with flow reversal is safe in octogenarians: A preliminary safety study" J. Vasc. Surg. 47:96-100. cited by applicant

Bates M.D., et al. (2003). "Reversal of the Direction of Internal Carotid Artery Blood Flow by Occlusion of the Common and External Carotid Arteries in a Swine Model" Catherization and Cardiovascular Intervention 60:270-275. cited by applicant

Bates, M.D., et al. (2004). "Internal Carotid Artery Flow Arrest/Reversal Cerebral Protection Techniques" The West Virginal Medical Journal, vol. 99:60-63. cited by applicant

Bergeron et al. (1999). "Percutaneous stenting of the internal carotid artery: the European CAST I Study" J. Endovasc. Surg. 6:155-159. cited by applicant

Bergeron P. et al. (1996). "Recurrent Carotid Disease: Will Stents be an alternative to surgery?" J Endovasc Surg; 3: 76-79. cited by applicant

Chang, D.W., et al., "A new approach to carotid angioplasty and stenting with transcervical occlusion and protective shunting: Why it may be a better carotid artery intervention" (J Vasc Surg 2004; 39:994-1002). cited by applicant

Chang, M.D., "Carotid Angioplasty And Stenting Using Transcervical Occlusion And Protective Shunting Via A Mini Incision In The Neck: A New Technique For Difficult Femoral Access Or Filter Placement May Be The Better Carotid Artery Intervention" 30th Global: Vascular and Endovascular Issues, Techniques and Horizons Symposium, New York, NY, Nov. 20-23, 2003; XXVII 6.1-XXVII 6.2. cited by applicant

Coppi et al. (2005). "PRIAMUS Proximal flow blockage cerebral protection during carotid stenting: Results from a multicenter Italian regiStry" J. Cardiovasc. Surg. 46:219-227. cited by applicant

Criado et al. (1997). "Evolving indications for and early results of carotid artery stenting" Am. J. Surg.; 174:111-114. cited by applicant

Criado et al. (2004). "Transcervical carotid artery angioplasty and stenting with carotid flow reversal: Surgical technique" J. Vasc. Surg. 18:257-261. cited by applicant

Criado et al. (2004). "Transcervical carotid stenting with internal carotid artery flow reversal: Feasibility and preliminary results" J. Vasc. Surg. 40:476-483. cited by applicant

Criado, et al. (2007). "Transcervical carotid stenting with carotid artery flow reversal: 3-year follow-up of 103 stents." J Vasc Surg 46(5): 864-9. cited by applicant

Criado, F.J., et al., Access strategies for carotid artery intervention. J Invasive Cardiol, 2000. 12(1): p. 61-8. cited by applicant

Criado, M.D., et al. (2004). "Carotid angioplasty with internal carotid artery flow reversal is well tolerated in the awake patient" Journal of Vascular Surgery, 40(1):92-7. cited by applicant

Diethrich et al., (1996). "Percutaneous techniques for endoluminal carotid interventions" J. Endovasc. Surg. 3:182-202. cited by applicant

Henry, et al. (1999). "Carotid Stenting With Cerebral Protection: First Clinical Experience Using the PercuSurge GuardWire System" J. Endovasc. Surg. 6:321-331. cited by applicant

Lin et al. (2005). "Protected carotid artery stenting and angioplasty via transfemoral versus transcervical approaches" Vasc. Endovasc. Surg. 39(6):499-503. cited by applicant

Lo et al. (2005). "Advantages and indications of transcervical carotid artery stenting with carotid flow reversal" J. Cardiovasc. Surg (Torino). 46(3):229-239. cited by applicant

MacDonald, S. (2006). "Is there any evidence that cerebral protection is beneficial?" J. Cardiovasc. Surg. 47:127-36. cited by applicant

Matas et al. (2007). "Transcervical carotid stenting with flow reversal protection: Experience in high-risk patients" J. Vasc. Surg. 46:49-54. cited by applicant

Ohki, M.D., et al., "Efficacy of a proximal occlusion catheter with reversal of flow in the prevention of embolic events during carotid artery stenting: An experimental analysis" (J Vasc Surg 2001; 33:504-9). cited by applicant

Parodi (2005). "Is flow reversal the best method of protection during carotid stenting?" J Endovasc.

Ther. 12:166-170. cited by applicant

Pipinos et al. (2005). "Transcervical approach with protective flow reversal for carotid angioplasty and stenting" J. Endovasc. Ther. 12:446-453. cited by applicant

Pipinos et al. (2006). "Transcervical carotid stenting with flow reversal for neuroprotection: Technique, results, advantages, and limitations" 14(5):245-255. cited by applicant

Ribo et al. (2006). "Transcranial doppler monitoring of transcervical carotid stenting with flow reversal protection: a novel carotid revascularization technique" 27:2846-2849. (originally published online Sep. 28, 2006). cited by applicant

Stecker et al., (2002). "Stent placement in common carotid and internal carotid artery stenoses with use of an open transcervical approach in a patient with previous endarterectomy" J. Vasc. Interv. Radiol. 13:413-417. cited by applicant

Stejskal et al., "Experience of 500 Cases of Neurophysiological Monitoring in Carotid Endarterectomy", Acta Neurochir, 2007, 149:681-689. cited by applicant

U.S. Appl. No. 14/227,585, filed Mar. 27, 2014, US 2014-0296769. cited by applicant

U.S. Appl. No. 15/049,637, filed Feb. 22, 2016, US 2016-0242764. cited by applicant

U.S. Appl. No. 15/399,638, filed Jan. 5, 2017, US 2017-0209260. cited by applicant

U.S. Appl. No. 16/530,783, filed Aug. 2, 2019, US 2020-0054871. cited by applicant

U.S. Appl. No. 16/894,474, filed Jun. 5, 2020, US 2020-0297912. cited by applicant

U.S. Appl. No. 16/906,457, filed Jun. 19, 2020, US 2020-0397472. cited by applicant

U.S. Appl. No. 16/951,767, filed Nov. 18, 2020, US 2021-0145453. cited by applicant

U.S. Appl. No. 16/999,634, filed Aug. 21, 2020, US 2020-0375728. cited by applicant

U.S. Appl. No. 16/999,640, filed Aug. 21, 2020, US 2020-0375729. cited by applicant

U.S. Appl. No. 17/000,004, filed Aug. 21, 2020, US 2020-0390438. cited by applicant

U.S. Appl. No. 17/074,299, filed Oct. 19, 2020, US 2021-0205571. cited by applicant

U.S. Appl. No. 17/149,450, filed Jan. 14, 2021, US 2021-0298929. cited by applicant

U.S. Appl. No. 17/179,746, filed Feb. 19, 2021, US 2021-0244522. cited by applicant

U.S. Appl. No. 17/206,665, filed Mar. 19, 2021, US 2021-0307945. cited by applicant

U.S. Appl. No. 17/220,718, filed Apr. 1, 2021, US 2021-0290213. cited by applicant

U.S. Appl. No. 17/237,911, filed Apr. 22, 2021, US 2021-0236790. cited by applicant

U.S. Appl. No. 17/307,359, filed May 4, 2021, US 2021-0322738. cited by applicant

U.S. Appl. No. 17/345,502, filed Jun. 11, 2021, US 2021-0299343. cited by applicant

U.S. Appl. No. 17/345,544, filed Jun. 11, 2021, US 2021-0299425. cited by applicant

U.S. Appl. No. 17/398,969, filed Aug. 10, 2021, US 2022-0047267. cited by applicant

U.S. Appl. No. 17/406,822, filed Aug. 19, 2021, US 2022-0040502. cited by applicant

U.S. Appl. No. 17/555,127, filed Dec. 17, 2021, US 2022-0193321. cited by applicant

U.S. Appl. No. 17/684,745, filed Mar. 2, 2022, US 2023-0045964. cited by applicant

U.S. Appl. No. 17/749,423, filed May 20, 2022, US 2023-0001161. cited by applicant

U.S. Appl. No. 17/749,454, filed May 20, 2022, US 2023-0097442. cited by applicant

U.S. Appl. No. 17/773,200, filed Apr. 29, 2022, US 2022-0401111. cited by applicant

U.S. Appl. No. 17/773,206, filed Apr. 29, 2022, US 2022-0378565. cited by applicant

U.S. Appl. No. 17/899,279, filed Aug. 30, 2022, US 2023-0067426. cited by applicant

U.S. Appl. No. 17/951,727, filed Sep. 23, 2022, US 2023-0101242. cited by applicant

U.S. Appl. No. 18/071,323, filed Nov. 29, 2022, US 2023-0165696. cited by applicant

U.S. Appl. No. 18/301,838, filed Apr. 17, 2023, US 2024-0091424. cited by applicant

PCT/US2022/050714, Nov. 22, 2022, WO 2023/096898. cited by applicant

PCT/US2022/051275, Nov. 29, 2022, WO 2023/101982. cited by applicant

PCT/US2022/080992, Dec. 6, 2022, WO 2023/107926. cited by applicant

PCT/US2023/064772, Mar. 21, 2023, WO 2023/183808. cited by applicant

PCT/US2023/016058, Mar. 23, 2023, WO 2023/183476. cited by applicant

PCT/US2023/023603, May 25, 2023, WO 2023/230277. cited by applicant

PCT/US2023/025266, Jun. 14, 2023, WO 2023/244643. cited by applicant
PCT/US2023/027339, Jul. 11, 2023, WO 2024/015336. cited by applicant
PCT/US2023/028248, Jul. 21, 2023, WO 2024/020142. cited by applicant
PCT/US2023/033165, Sep. 19, 2023, WO 2024/064153. cited by applicant
PCT/US2023/033949, Sep. 28, 2023, WO 2024/072944. cited by applicant

Primary Examiner: Mcevoy; Thomas

Attorney, Agent or Firm: Seager, Tufte & Wickhem, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 17/470,213 filed on Sep. 9, 2021, which is a continuation of U.S. patent application Ser. No. 16/171,784 filed on Oct. 26, 2018, now U.S. Pat. No. 11,141,259, and claims priority to U.S. Provisional Patent Application Ser. No. 62/580,869 filed on Nov. 2, 2017 and entitled “FENESTRATED SHEATH FOR EMBOLIC PROTECTION DURING TRANSCAROTID CAROTID ARTERY REVASCULARIZATION” the disclosure of these are incorporated herein by reference in their entirety.

BACKGROUND

(1) The present disclosure relates generally to medical methods and devices. More particularly, the present disclosure relates to devices for use during carotid arterial vasculature and establishing retrograde blood flow during performance of carotid artery stenting and other procedures.

(2) Carotid artery disease usually consists of deposits of plaque P which narrow the junction between the common carotid artery CCA and the internal carotid artery ICA, an artery which provides blood flow to the brain (FIG. 5). These deposits increase the risk of embolic particles being generated and entering the cerebral vasculature, leading to neurologic consequences such as transient ischemic attacks TIA, ischemic stroke, or death. In addition, should such narrowings become severe, blood flow to the brain is inhibited with serious and sometimes fatal consequences.

(3) Two principal therapies are employed for treating carotid artery disease. The first is carotid endarterectomy CEA, an open surgical procedure which relies on occluding the common, internal and external carotid arteries, opening the carotid artery at the site of the disease (usually the carotid bifurcation where the common carotid artery CCA divides into the internal carotid artery ICA and external carotid artery ECA), dissecting away and removing the plaque P, and then closing the carotid artery. The second procedure relies on stenting of the carotid arteries, referred to as carotid artery stenting CAS, typically at or across the branch from the common carotid artery CAA into the internal carotid artery ICA, or entirely in the internal carotid artery. Usually, a self-expanding stent is introduced through percutaneous puncture into the femoral artery in the groin and up the aortic arch into the target common carotid artery CCA.

(4) In both these approaches, the patient is at risk of emboli being released into the cerebral vasculature via the internal carotid artery ICA. The clinical consequence of emboli release into the external carotid artery ECA, an artery which provides blood to facial structures, is less significant. During CEA, the risk of emboli release into the internal carotid artery ICA is minimized by debriding and vigorously flushing the arteries before closing the vessels and restoring blood flow. During the procedure while the artery is opened, all the carotid arteries are occluded so particles are unable to enter the vasculature.

(5) In carotid stenting CAS procedures, adjunct embolic protection devices are usually used to at least partially alleviate the risk of emboli. An example of these devices are distal filters, which are

deployed in the internal carotid artery distal to the region of stenting. The filter is intended to capture the embolic particles to prevent passage into the cerebral vasculature. Such filtering devices, however, carry certain limitations. They must be advanced to the target vessel and cross the stenosis prior to deployment, which exposes the cerebral vasculature to embolic showers; they are not always easy to advance, deploy, and remove through a tight stenosis and/or a severely angulated vasculature; and finally, they only filter particles larger than the filter pore size, typically 100 to 120 μm . Also, these devices do not filter 100% of the flow due to incomplete wall opposition of the filter, and furthermore there is a risk of debris escape during filter retrieval.

(6) Of particular interest to the present disclosure, an alternative method for reducing the risk of emboli release into the internal carotid artery ICA has been proposed for use during carotid stenting CAS procedures utilizing the concept of reversing the flow in the internal carotid artery ICA to prevent embolic debris entering the cerebral vasculature. Although a number of specific protocols have been described, they generally rely on placing a sheath via the femoral artery (transfemoral access) into the common carotid artery. Flow in the common carotid artery is occluded, typically by inflating a balloon on the distal tip of the sheath. Flow into the external carotid artery ECA may also be occluded, typically using a balloon catheter or balloon guidewire introduced through the sheath. The sheath is then connected to a venous location or to a low pressure external receptacle in order to establish a reverse or retrograde flow from the internal carotid artery through the sheath and away from the cerebral vasculature. After such reverse or retrograde flow is established, the stenting procedure may be performed with a greatly reduced risk of emboli entering the cerebral vasculature.

(7) An alternate system which simply halts forward flow in the ICA consists of a carotid access sheath with two integral balloons: an ECA occlusion balloon at the distal tip, and a CCA occlusion balloon placed some fixed distance proximal to the ECA balloon. Between the two balloons is an opening for delivery of the interventional carotid stenting devices. This system does not reverse flow from the ICA to the venous system, but instead relies on blocking flow and performing aspiration to remove embolic debris prior to establishing forward flow in the ICA.

(8) While such reverse or static flow protocols for performing stenting and other interventional procedures in the carotid vasculature hold great promise, such methods have generally required the manipulation of multiple separate access and occlusion components. Moreover, the protocols have been rather complicated, requiring many separate steps, limiting their performance to only the most skilled vascular surgeons, interventional radiologists and cardiologists. In addition, due to the size limitations of the femoral access, the access devices themselves provide a very high resistance to flow, limiting the amount of reverse flow and/or aspiration possible. Furthermore, the requirement to occlude the external carotid artery adds risk and complexity to the procedure. The balloon catheter for occluding the external carotid artery can become trapped in the arterial wall in cases where the stent is placed across the bifurcation from the common carotid artery to the internal carotid artery, and may cause damage to the deployed stent when it is removed.

(9) None of the cerebral protection devices and methods described offer protection after the procedure. However, generation of embolic particles has been measured up to 48 hours or later, after the stent procedure. During CEA, flushing at the end of the procedure while blocking flow to the internal carotid artery ICA may help reduce post-procedure emboli generation. A similar flushing step during CAS may also reduce emboli risk. Additionally, a stent which is designed to improve entrapment of embolic particles may also reduce post-procedure emboli.

(10) In addition, all currently available carotid stenting and cerebral protection systems are designed for access from the femoral artery. Unfortunately, the pathway from the femoral artery to the common carotid artery is relatively long, has several turns which in some patients can be quite angulated, and often contains plaque and other diseases. The portion of the procedure involving access to the common carotid artery from the femoral artery can be difficult and time consuming as well as risk generating showers of embolic debris up both the target and the opposite common

carotid artery and thence to the cerebral vasculature. Some studies suggest that up to half, or more, of embolic complications during CAS procedures occur during access to the CCA. None of the protocols or systems offer protection during this portion of the procedure.

(11) Recently, a reverse flow protocol having an alternative access route to the carotid arteries has been proposed by Criado. This alternative route consists of direct surgical access to the common carotid artery CCA, called transcervical or transcarotid access. Transcarotid access greatly shortens the length and tortuosity of the pathway from the vascular access point to the target treatment site thereby easing the time and difficulty of the procedure. Additionally, this access route reduces the risk of emboli generation from navigation of diseased, angulated, or tortuous aortic arch or common carotid artery anatomy.

(12) The Criado protocol is described in several publications in the medical literature cited below. As shown in FIG. 3, the Criado protocol uses a flow shunt which includes an arterial sheath **210** and a venous sheath **212**. Each sheath has a side arm **214**, terminating in a stopcock **216**. The two sheaths stopcocks are connected by a connector tubing **218**, thus completing a reverse flow shunt from the arterial sheath **210** to the venous sheath **212**. The arterial sheath is placed in the common carotid artery CCA through an open surgical incision in the neck below the carotid bifurcation. Occlusion of the common carotid artery CCA is accomplished using a temporary vessel ligation, for example using a Rummel tourniquet and umbilical tape or vessel loop. The venous return sheath **212** is placed in the internal jugular vein IJV (FIG. 3), also via an open surgical incision. Retrograde flow from the internal carotid artery ICA and the external carotid artery ECA may then be established by opening the stopcock **216**. The Criado protocol is an improvement over the earlier retrograde flow protocols since it eliminates the need for femoral access. Thus, the potential complications associated with the femoral access are completely avoided. Furthermore, the lower flow restrictions presented by the shorter access route offer the opportunity for more vigorous reverse flow rate, increasing the efficiency of embolic debris removal. Because of these reduced flow restrictions, the desired retrograde flow of the internal carotid artery ICA may be established without occluding the external carotid artery ECA, as required by the earlier protocols.

(13) While a significant improvement over the femoral access-based retrograde flow protocols, the Criado protocol and flow shunt could still benefit from improvement. In particular, the existing arterial and venous sheaths used in the procedure still have significant flow restrictions in the side arms **214** and stopcocks **216**. When an interventional catheter is inserted into the arterial access sheath, the reverse flow circuit resistance is at a maximum. In some percentage of patients, the external carotid artery ECA perfusion pressure is greater than the internal carotid artery ICA perfusion pressure. In these patients, this differential pressure might drive antegrade flow into the ICA from the ECA. A reverse flow shunt with lower flow resistance could guarantee reversal of flow in both the ECA and ICA despite a pressure gradient from the ECA to the ICA.

(14) In addition, there is no means to monitor or regulate the reverse flow rate. The ability to increase and/or modulate the flow rate would give the user the ability to set the reverse flow rate optimally to the tolerance and physiology of the patient and the stage of the procedure, and thus offer improved protection from embolic debris. Further, the system as described by Criado relies on manually turning one or more stopcocks to open and close the reverse flow shunt, for example during injection of contrast medium to facilitate placement of the CAS systems. Finally, the Criado protocol relies on open surgical occlusion of the common carotid artery, via a vessel loop or Rummel tourniquet. A system with means to occlude the common carotid artery intravascularly, for example with an occlusion element on the arterial access sheath, would allow the entire procedure to be performed using percutaneous techniques. A percutaneous approach would limit the size and associated complications of a surgical incision, as well as enable non-surgical physicians to perform the procedure.

(15) For these reasons, it would be desirable to provide improved methods, apparatus, and systems for performing transcarotid access, retrograde flow and flushing procedures and implantation of a

carotid stent in the carotid arterial vasculature to reduce the risk of procedural and post-procedural emboli, to improve the level of hemostasis throughout the procedure, and to improve the ease and speed of carotid artery stenting. The methods, apparatus, and system should simplify the procedure to be performed by the physician as well as reduce the risk of improperly performing the procedures and/or achieving insufficient retrograde flow and flushing to protect against emboli release. The systems should provide individual devices and components which are readily used with each other and which protect against emboli-related complications. The methods and systems should also provide for convenient and preferably automatic closure of any and all arterial penetrations at the end of the procedure to prevent unintended blood loss. Additionally, the systems, apparatus, and methods should be suitable for performance by either open surgical or percutaneous access routes into the vasculature. Additionally, the methods, apparatus, and systems should enable implantation of an intravascular prosthetic implant which lowers post procedural complications. At least some of these objectives will be met by the inventions described herein below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a schematic illustration of a retrograde blood flow system including a flow control assembly wherein an arterial access device accesses the common carotid artery via a transcarotid approach and a venous return device communicates with the internal jugular vein.
- (2) FIG. 1B is a schematic illustration of a retrograde blood flow system wherein an arterial access device accesses the common carotid artery via a transcarotid approach and a venous return device communicates with the femoral vein.
- (3) FIG. 1C is a schematic illustration of a retrograde blood flow system wherein an arterial access device accesses the common carotid artery via a transfemoral approach and a venous return device communicates with the femoral vein.
- (4) FIG. 1D is a schematic illustration of a retrograde blood flow system wherein retrograde flow is collected in an external receptacle.
- (5) FIG. 2A is an enlarged view of the carotid artery wherein the carotid artery is occluded with an occlusion element on the sheath and connected to a reverse flow shunt, and an interventional device, such as a stent delivery system or other working catheter, is introduced into the carotid artery via an arterial access device.
- (6) FIG. 2B is an alternate system wherein the carotid artery is occluded with a separate external occlusion device and connected to a reverse flow shunt, and an interventional device, such as a stent delivery system or other working catheter, is introduced into the carotid artery via an arterial access device.
- (7) FIG. 2C is an alternate system wherein the carotid artery is connected to a reverse flow shunt and an interventional device, such as a stent delivery system or other working catheter, is introduced into the carotid artery via an arterial access device, and the carotid artery is occluded with a separate occlusion device.
- (8) FIG. 2D is an alternate system wherein the carotid artery is occluded and the artery is connected to a reverse flow shunt via an arterial access device and the interventional device, such as a stent delivery system, is introduced into the carotid artery via a separate arterial introducer device.
- (9) FIG. 3 illustrates a prior art Criado flow shunt system.
- (10) FIG. 4 illustrates a normal cerebral circulation diagram including the Circle of Willis.
- (11) FIG. 5 illustrates the vasculature in a patient's neck, including the common carotid artery CCA, the internal carotid artery ICA, the external carotid artery ECA, and the internal jugular vein IJV.

- (12) FIG. 6A illustrates an arterial access device useful in the methods and systems of the present disclosure.
- (13) FIG. 6B illustrates an additional arterial access device construction with a reduced diameter distal end.
- (14) FIGS. 7A and 7B illustrate a tube useful with the sheath of FIG. 6A.
- (15) FIG. 7C show an embodiment of a sheath stopper.
- (16) FIG. 7D shows the sheath stopper of FIG. 7C positioned on a sheath.
- (17) FIGS. 7E and 7F show the malleable sheath stopper in use.
- (18) FIG. 7G shows an embodiment of a sheath with a flexible distal segment and a sheath stopper in use.
- (19) FIG. 8A illustrates an additional arterial access device construction with an expandable occlusion element.
- (20) FIG. 8B illustrates an additional arterial access device construction with an expandable occlusion element and a reduced diameter distal end.
- (21) FIGS. 9A and 9B illustrate an additional embodiment of an arterial access device.
- (22) FIGS. 9C and 9D illustrate an embodiment of a valve on the arterial access device.
- (23) FIGS. 10A through 10D illustrate embodiments of a venous return device useful in the methods and systems of the present disclosure.
- (24) FIG. 11 illustrates the system of FIG. 1 including a flow control assembly.
- (25) FIGS. 12A-12B illustrate an embodiment of a variable flow resistance component useful in the methods and systems of the present disclosure.
- (26) FIGS. 13A-13D illustrate an embodiment of a fenestrated sheath.
- (27) FIGS. 14A-14E illustrate the exemplary blood flow paths during a procedure for implanting a stent at the carotid bifurcation in accordance with the principles of the present disclosure.

DETAILED DESCRIPTION

- (28) The disclosed methods, apparatus, and systems establish and facilitate retrograde or reverse flow blood circulation in the region of the carotid artery bifurcation in order to limit or prevent the release of emboli into the cerebral vasculature, particularly into the internal carotid artery. The methods are particularly useful for interventional procedures, such as stenting and angioplasty, atherectomy, performed through a transcarotid approach or transfemoral into the common carotid artery, either using an open surgical technique or using a percutaneous technique, such as a modified Seldinger technique or a micropuncture technique.
- (29) Access into the common carotid artery (FIG. 5) is established by placing a sheath or other tubular access cannula into a lumen of the artery, typically having a distal end of the sheath positioned proximal to the junction or bifurcation B from the common carotid artery to the internal and external carotid arteries. The sheath may have an occlusion member at the distal end, for example a compliant occlusion balloon. A catheter or guidewire with an occlusion member, such as a balloon, may be placed through the access sheath and positioned in the proximal external carotid artery ECA to inhibit the entry of emboli, but occlusion of the external carotid artery is usually not necessary. A second return sheath is placed in the venous system, for example the internal jugular vein IJV or femoral vein FV. The arterial access and venous return sheaths are connected to create an external arterial-venous shunt.
- (30) Retrograde flow is established and modulated to meet the patient's requirements. Flow through the common carotid artery is occluded, either with an external vessel loop or tape, a vascular clamp, an internal occlusion member such as a balloon, or other type of occlusion means. When flow through the common carotid artery is blocked, the natural pressure gradient between the internal carotid artery and the venous system will cause blood to flow in a retrograde or reverse direction from the cerebral vasculature through the internal carotid artery and through the shunt into the venous system.
- (31) Alternately, the venous sheath could be eliminated and the arterial sheath could be connected

to an external collection reservoir or receptacle. The reverse flow could be collected in this receptacle. If desired, the collected blood could be filtered and subsequently returned to the patient during or at the end of the procedure. The pressure of the receptacle could be open to atmospheric pressure, causing the pressure gradient to create blood to flow in a reverse direction from the cerebral vasculature to the receptacle or the pressure of the receptacle could be a negative pressure.

(32) Optionally, to achieve or enhance reverse flow from the internal carotid artery, flow from the external carotid artery may be blocked, typically by deploying a balloon or other occlusion element in the external carotid just above (i.e., distal) the bifurcation within the internal carotid artery.

(33) Although the procedures and protocols described hereinafter will be particularly directed at carotid stenting, it will be appreciated that the methods for accessing the carotid artery described herein would also be useful for angioplasty, artherectomy, and any other interventional procedures which might be carried out in the carotid arterial system, particularly at a location near the bifurcation between the internal and external carotid arteries. In addition, it will be appreciated that some of these access, vascular closure, and embolic protection methods will be applicable in other vascular interventional procedures, for example the treatment of acute stroke.

(34) The present disclosure includes a number of specific aspects for improving the performance of carotid artery access protocols. At least most of these individual aspects and improvements can be performed individually or in combination with one or more other of the improvements in order to facilitate and enhance the performance of the particular interventions in the carotid arterial system.

(35) In one aspect, there is disclosed a system for use in accessing and treating a carotid artery. The system comprises an arterial access device adapted to be introduced into a common carotid artery and receive blood flow from the common carotid artery; a shunt fluidly connected to the arterial access device, wherein the shunt provides a pathway for blood to flow from the arterial access device to a return site; and a flow control assembly coupled to the shunt and adapted to regulate blood flow through the shunt between at least a first blood flow state and at least a second blood flow state, wherein the flow control assembly includes one or more components that interact with the blood flow through the shunt.

(36) In another aspect, there is disclosed a system for use in accessing and treating a carotid artery. The system comprises an arterial access device adapted to be introduced into a common carotid artery and receive blood flow from the common carotid artery; a shunt fluidly connected to the arterial access device, wherein the shunt provides a pathway for blood to flow from the arterial access device to a return site; a flow mechanism coupled to the shunt and adapted to vary the blood flow through the shunt between a first blood flow rate and a second blood flow rate; and a controller that automatically interacts with the flow mechanism to regulate blood flow through the shunt between the first blood flow rate and the second blood flow rate without requiring input from a user.

(37) In another aspect, there is disclosed a device for use in accessing and treating a carotid artery. The device comprises a distal sheath having a distal end adapted to be introduced into the common carotid artery, a proximal end, and a lumen extending between the distal and proximal ends; a proximal extension having a distal end, a proximal end, and a lumen therebetween, wherein the distal end of the proximal extension is connected to the proximal end of the sheath at a junction so that the lumens of each are contiguous; a flow line having a lumen, said flow line connected near the junction so that blood flowing into the distal end of the sheath can flow into the lumen of the flow line; and a hemostasis valve at the proximal end of the proximal extension, said hemostasis valve being adapted to inhibit blood flow from the proximal extension while allowing catheter introduction through the proximal extension and into the distal sheath.

(38) In another aspect, there is disclosed a method for accessing and treating a carotid artery. The method comprises forming a penetration in a wall of a common carotid artery; positioning an access sheath through the penetration; blocking blood flow from the common carotid artery past the sheath; allowing retrograde blood flow from the carotid artery into the sheath and from the sheath

via a flow path to a return site; and modifying blood flow through the flow path based on feedback data.

(39) In another aspect, there is disclosed a method for accessing and treating a carotid artery. The method comprises forming a penetration in a wall of a common carotid artery; positioning an access sheath through the penetration; blocking blood flow from the common carotid artery past the sheath; allowing retrograde blood flow from the carotid artery into the sheath and from the sheath via a flow path to a return site; and monitoring flow through the flow path.

(40) In another aspect, there is disclosed a method for accessing and treating a carotid artery. The method comprises: forming a penetration in a wall of a common carotid artery; positioning an arterial access sheath through the penetration; blocking blood flow from the common carotid artery past the sheath; allowing retrograde blood flow from the internal carotid artery into the sheath while the common carotid artery remains blocked; and adjusting the state of retrograde blood flow through the sheath.

(41) In another aspect, there is disclosed a method for accessing and treating a carotid artery. The method comprises forming a penetration in a wall of a common carotid artery; positioning an arterial access sheath through the penetration; blocking blood flow from the common carotid artery past the sheath; allowing retrograde blood flow from the internal carotid artery into the sheath while the common carotid artery remains blocked; and adjusting a rate of retrograde blood flow from the sheath to as high a level as the patient will tolerate, wherein said adjusted rate is a baseline.

(42) This application is related to U.S. Pat. No. 8,157,760 entitled “Methods and Systems for Establishing Retrograde Carotid Arterial Flow” and U.S. patent application Ser. No. 14/227,585 entitled “Methods and Systems For Establishing Retrograde Carotid Arterial Blood Flow”, both of which are incorporated herein by reference.

(43) FIG. 1A shows a first embodiment of a retrograde flow system **100** that is adapted to establish and facilitate retrograde or reverse flow blood circulation in the region of the carotid artery bifurcation in order to limit or prevent the release of emboli into the cerebral vasculature, particularly into the internal carotid artery. The system **100** interacts with the carotid artery to provide retrograde flow from the carotid artery to a venous return site, such as the internal jugular vein (or to another return site such as another large vein or an external receptacle in alternate embodiments.) The retrograde flow system **100** includes an arterial access device **110**, a venous return device **115**, and a shunt **120** that provides a passageway for retrograde flow from the arterial access device **110** to the venous return device **115**. A flow control assembly **125** interacts with the shunt **120**. The flow control assembly **125** is adapted to regulate and/or monitor the retrograde flow from the common carotid artery to the internal jugular vein, as described in more detail below. The flow control assembly **125** interacts with the flow pathway through the shunt **120**, either external to the flow path, inside the flow path, or both. The arterial access device **110** at least partially inserts into the common carotid artery CCA and the venous return device **115** at least partially inserts into a venous return site such as the internal jugular vein IJV, as described in more detail below. The arterial access device **110** and the venous return device **115** couple to the shunt **120** at connection locations **127a** and **127b**. When flow through the common carotid artery is blocked, the natural pressure gradient between the internal carotid artery and the venous system causes blood to flow in a retrograde or reverse direction RG (FIG. 2A) from the cerebral vasculature through the internal carotid artery and through the shunt **120** into the venous system. The flow control assembly **125** modulates, augments, assists, monitors, and/or otherwise regulates the retrograde blood flow.

(44) In the embodiment of FIG. 1A, the arterial access device **110** accesses the common carotid artery CCA via a transcarotid approach. Transcarotid access provides a short length and non-tortuous pathway from the vascular access point to the target treatment site thereby easing the time and difficulty of the procedure, compared for example to a transfemoral approach. In an embodiment, the arterial distance from the arteriotomy to the target treatment site (as measured

traveling through the artery) is 15 cm or less. In an embodiment, the distance is between 5 and 10 cm. Additionally, this access route reduces the risk of emboli generation from navigation of diseased, angulated, or tortuous aortic arch or common carotid artery anatomy. At least a portion of the venous return device **115** is placed in the internal jugular vein IJV. In an embodiment, transcarotid access to the common carotid artery is achieved percutaneously via an incision or puncture in the skin through which the arterial access device **110** is inserted. If an incision is used, then the incision can be about 0.5 cm in length. An occlusion element **129**, such as an expandable balloon, can be used to occlude the common carotid artery CCA at a location proximal of the distal end of the arterial access device **110**. The occlusion element **129** can be located on the arterial access device **110** or it can be located on a separate device. In an alternate embodiment, the arterial access device **110** accesses the common carotid artery CCA via a direct surgical transcarotid approach. In the surgical approach, the common carotid artery can be occluded using a tourniquet **2105**. The tourniquet **2105** is shown in phantom to indicate that it is a device that is used in the optional surgical approach.

(45) In another embodiment, shown in FIG. **1B**, the arterial access device **110** accesses the common carotid artery CCA via a transcarotid approach while the venous return device **115** access a venous return site other than the jugular vein, such as a venous return site comprised of the femoral vein FV. The venous return device **115** can be inserted into a central vein such as the femoral vein FV via a percutaneous puncture in the groin.

(46) In another embodiment, shown in FIG. **1C**, the arterial access device **110** accesses the common carotid artery via a femoral approach. According to the femoral approach, the arterial access device **110** approaches the CCA via a percutaneous puncture into the femoral artery FA, such as in the groin, and up the aortic arch AA into the target common carotid artery CCA. The venous return device **115** can communicate with the jugular vein JV or the femoral vein FV.

(47) FIG. **1D** shows yet another embodiment, wherein the system provides retrograde flow from the carotid artery to an external receptacle **130** rather than to a venous return site. The arterial access device **110** connects to the receptacle **130** via the shunt **120**, which communicates with the flow control assembly **125**. The retrograde flow of blood is collected in the receptacle **130**. If desired, the blood could be filtered and subsequently returned to the patient. The pressure of the receptacle **130** could be set at zero pressure (atmospheric pressure) or even lower, causing the blood to flow in a reverse direction from the cerebral vasculature to the receptacle **130**. Optionally, to achieve or enhance reverse flow from the internal carotid artery, flow from the external carotid artery can be blocked, typically by deploying a balloon or other occlusion element in the external carotid artery just above the bifurcation with the internal carotid artery. FIG. **1D** shows the arterial access device **110** arranged in a transcarotid approach with the CCA although it should be appreciated that the use of the external receptacle **130** can also be used with the arterial access device **110** in a transfemoral approach.

(48) With reference to the enlarged view of the carotid artery in FIG. **2A**, an interventional device, such as a stent delivery system **135** or other working catheter, can be introduced into the carotid artery via the arterial access device **110**, as described in detail below. The stent delivery system **135** can be used to treat the plaque P such as to deploy a stent into the carotid artery. The arrow RG in FIG. **2A** represents the direction of retrograde flow.

(49) FIG. **2B** shows another embodiment, wherein the arterial access device **110** is used for the purpose of creating an arterial-to-venous shunt as well as introduction of at least one interventional device into the carotid artery. A separate arterial occlusion device **112** with an occlusion element **129** can be used to occlude the common carotid artery CCA at a location proximal to the distal end of the arterial access device **110**.

(50) FIG. **2C** shows yet another embodiment wherein the arterial access device **110** is used for the purpose of creating an arterial-to-venous shunt as well as arterial occlusion using an occlusion element **129**. A separate arterial introducer device can be used for the introduction of at least one

interventional device into the carotid artery at a location distal to the arterial access device **110**.

Description of Anatomy

(51) Collateral Brain Circulation

(52) The Circle of Willis CW is the main arterial anastomatic trunk of the brain where all major arteries which supply the brain, namely the two internal carotid arteries (ICAs) and the vertebral basilar system, connect. The blood is carried from the Circle of Willis by the anterior, middle and posterior cerebral arteries to the brain. This communication between arteries makes collateral circulation through the brain possible. Blood flow through alternate routes is made possible thereby providing a safety mechanism in case of blockage to one or more vessels providing blood to the brain. The brain can continue receiving adequate blood supply in most instances even when there is a blockage somewhere in the arterial system (e.g., when the ICA is ligated as described herein). Flow through the Circle of Willis ensures adequate cerebral blood flow by numerous pathways that redistribute blood to the deprived side.

(53) The collateral potential of the Circle of Willis is believed to be dependent on the presence and size of its component vessels. It should be appreciated that considerable anatomic variation between individuals can exist in these vessels and that many of the involved vessels may be diseased. For example, some people lack one of the communicating arteries. If a blockage develops in such people, collateral circulation is compromised resulting in an ischemic event and potentially brain damage. In addition, an autoregulatory response to decreased perfusion pressure can include enlargement of the collateral arteries, such as the communicating arteries, in the Circle of Willis. An adjustment time is occasionally required for this compensation mechanism before collateral circulation can reach a level that supports normal function. This autoregulatory response can occur over the space of 15 to 30 seconds and can only compensate within a certain range of pressure and flow drop. Thus, it is possible for a transient ischemic attack to occur during the adjustment period. Very high retrograde flow rate for an extended period of time can lead to conditions where the patient's brain is not getting enough blood flow, leading to patient intolerance as exhibited by neurologic symptoms or in some cases a transient ischemic attack.

(54) FIG. 4 depicts a normal cerebral circulation and formation of Circle of Willis CW. The aorta AO gives rise to the brachiocephalic artery BCA, which branches into the left common carotid artery LCCA and left subclavian artery LSCA. The aorta AO further gives rise to the right common carotid artery RCCA and right subclavian artery RSCA. The left and right common carotid arteries CCA gives rise to internal carotid arteries ICA which branch into the middle cerebral arteries MCA, posterior communicating artery PcoA, and anterior cerebral artery ACA. The anterior cerebral arteries ACA deliver blood to some parts of the frontal lobe and the corpus striatum. The middle cerebral arteries MCA are large arteries that have tree-like branches that bring blood to the entire lateral aspect of each hemisphere of the brain. The left and right posterior cerebral arteries PCA arise from the basilar artery BA and deliver blood to the posterior portion of the brain (the occipital lobe).

(55) Anteriorly, the Circle of Willis is formed by the anterior cerebral arteries ACA and the anterior communicating artery ACoA which connects the two ACAs. The two posterior communicating arteries PCoA connect the Circle of Willis to the two posterior cerebral arteries PCA, which branch from the basilar artery BA and complete the Circle posteriorly.

(56) The common carotid artery CCA also gives rise to external carotid artery ECA, which branches extensively to supply most of the structures of the head except the brain and the contents of the orbit. The ECA also helps supply structures in the neck and face.

(57) Carotid Artery Bifurcation

(58) FIG. 5 shows an enlarged view of the relevant vasculature in the patient's neck. The common carotid artery CCA branches at bifurcation B into the internal carotid artery ICA and the external carotid artery ECA. The bifurcation is located at approximately the level of the fourth cervical vertebra. FIG. 5 shows plaque P formed at the bifurcation B.

(59) As discussed above, the arterial access device **110** can access the common carotid artery CCA via a transcarotid approach. Pursuant to the transcarotid approach, the arterial access device **110** is inserted into the common carotid artery CCA at an arterial access location L, which can be, for example, a surgical incision or puncture in the wall of the common carotid artery CCA. There is typically a distance D of around 5 to 7 cm between the arterial access location L and the bifurcation B. When the arterial access device **110** is inserted into the common carotid artery CCA, it is undesirable for the distal tip of the arterial access device **110** to contact the bifurcation B as this could disrupt the plaque P and cause generation of embolic particles. In order to minimize the likelihood of the arterial access device **110** contacting the bifurcation B, in an embodiment only about 2-4 cm of the distal region of the arterial access device is inserted into the common carotid artery CCA during a procedure.

(60) The common carotid arteries are encased on each side in a layer of fascia called the carotid sheath. This sheath also envelops the internal jugular vein and the vagus nerve. Anterior to the sheath is the sternocleidomastoideole. Transcarotid access to the common carotid artery and internal jugular vein, either percutaneous or surgical, can be made immediately superior to the clavicle, between the two heads of the sternocleidomastoid muscle and through the carotid sheath, with care taken to avoid the vagus nerve.

(61) At the upper end of this sheath, the common carotid artery bifurcates into the internal and external carotid arteries. The internal carotid artery continues upward without branching until it enters the skull to supply blood to the retina and brain. The external carotid artery branches to supply blood to the scalp, facial, ocular, and other superficial structures. Intertwined both anterior and posterior to the arteries are several facial and cranial nerves. Additional neck muscles may also overlay the bifurcation. These nerve and muscle structures can be dissected and pushed aside to access the carotid bifurcation during a carotid endarterectomy procedure. In some cases the carotid bifurcation is closer to the level of the mandible, where access is more challenging and with less room available to separate it from the various nerves which should be spared. In these instances, the risk of inadvertent nerve injury can increase and an open endarterectomy procedure may not be a good option.

(62) Detailed Description of Retrograde Blood Flow System

(63) As discussed, the retrograde flow system **100** includes the arterial access device **110**, venous return device **115**, and shunt **120** which provides a passageway for retrograde flow from the arterial access device **110** to the venous return device **115**. The system also includes the flow control assembly **125**, which interacts with the shunt **120** to regulate and/or monitor retrograde blood flow through the shunt **120**. Exemplary embodiments of the components of the retrograde flow system **100** are now described.

(64) Arterial Access Device

(65) FIG. 6A shows an exemplary embodiment of the arterial access device **110**, which comprises a distal sheath **605**, a proximal extension **610**, a flow line **615**, an adaptor or Y-connector **620**, and a hemostasis valve **625**. The arterial access device may also comprise a dilator **645** with a tapered tip **650** and an introducer guide wire **611**. The arterial access device together with the dilator and introducer guidewire are used together to gain access to a vessel. Features of the arterial access device may be optimized for transcarotid access. For example, the design of the access device components may be optimized to limit the potential injury on the vessel due to a sharp angle of insertion, allow atraumatic and secure sheath insertion, and limiting the length of sheath, sheath dilator, and introducer guide wire inserted into the vessel.

(66) The distal sheath **605** is adapted to be introduced through an incision or puncture in a wall of a common carotid artery, either an open surgical incision or a percutaneous puncture established, for example, using the Seldinger technique. The length of the sheath can be in the range from 5 to 15 cm, usually being from 10 cm to 12 cm. The inner diameter is typically in the range from 7 Fr (1 Fr=0.33 mm), to 10 Fr, usually being 8 Fr. Particularly when the sheath is being introduced through

the transcarotid approach, above the clavicle but below the carotid bifurcation, it is desirable that the sheath **605** be highly flexible while retaining hoop strength to resist kinking and buckling. Thus, the distal sheath **605** can be circumferentially reinforced, such as by braid, helical ribbon, helical wire, cut tubing, or the like and have an inner liner so that the reinforcement structure is sandwiched between an outer jacket layer and the inner liner. The inner liner may be a low friction material such as PTFE. The outer jacket may be one or more of a group of materials including Pebax, thermoplastic polyurethane, or nylon. In an embodiment, the reinforcement structure or material and/or outer jacket material or thickness may change over the length of the sheath **605** to vary the flexibility along the length. In an alternate embodiment, the distal sheath is adapted to be introduced through a percutaneous puncture into the femoral artery, such as in the groin, and up the aortic arch AA into the target common carotid artery CCA.

(67) The distal sheath **605** can have a stepped or other configuration having a reduced diameter distal region **630**, as shown in FIG. **6B**, which shows an enlarged view of the distal region **630** of the sheath **605**. The distal region **630** of the sheath can be sized for insertion into the carotid artery, typically having an inner diameter in the range from 2.16 mm (0.085 inch) to 2.92 mm (0.115 inch) with the remaining proximal region of the sheath having larger outside and luminal diameters, with the inner diameter typically being in the range from 2.794 mm (0.110 inch) to 3.43 mm (0.135 inch). The larger luminal diameter of the proximal region minimizes the overall flow resistance of the sheath. In an embodiment, the reduced-diameter distal section **630** has a length of approximately 2 cm to 4 cm. The relatively short length of the reduced-diameter distal section **630** permits this section to be positioned in the common carotid artery CCA via the transcarotid approach with reduced risk that the distal end of the sheath **605** will contact the bifurcation B. Moreover, the reduced diameter section **630** also permits a reduction in size of the arteriotomy for introducing the sheath **605** into the artery while having a minimal impact in the level of flow resistance. Further, the reduced distal diameter section may be more flexible and thus more conformal to the lumen of the vessel.

(68) With reference again to FIG. **6A**, the proximal extension **610**, which is an elongated body, has an inner lumen which is contiguous with an inner lumen of the sheath **605**. The lumens can be joined by the Y-connector **620** which also connects a lumen of the flow line **615** to the sheath. In the assembled system, the flow line **615** connects to and forms a first leg of the retrograde shunt **120** (FIG. **1**). The proximal extension **610** can have a length sufficient to space the hemostasis valve **625** well away from the Y-connector **620**, which is adjacent to the percutaneous or surgical insertion site. By spacing the hemostasis valve **625** away from a percutaneous insertion site, the physician can introduce a stent delivery system or other working catheter into the proximal extension **610** and sheath **605** while staying out of the fluoroscopic field when fluoroscopy is being performed. In an embodiment, the proximal extension is about 16.9 cm from a distal most junction (such as at the hemostasis valve) with the sheath **605** to the proximal end of the proximal extension. In an embodiment, the proximal extension has an inner diameter of 0.125 inch and an outer diameter of 0.175 inch. In an embodiment, the proximal extension has a wall thickness of 0.025 inch. The inner diameter may range, for example, from 0.60 inch to 0.150 inch with a wall thickness of 0.010 inch to 0.050 inch. In another embodiment, the inner diameter may range, for example, from 0.150 inch to 0.250 inch with a wall thickness of 0.025 inch to 0.100 inch. The dimensions of the proximal extension may vary. In an embodiment, the proximal extension has a length within the range of about 12-20 cm. In another embodiment, the proximal extension has a length within the range of about 20-30 cm.

(69) In an embodiment, the distance along the sheath from the hemostasis valve **625** to the distal tip of the sheath **605** is in the range of about 25 and 40 cm. In an embodiment, the distance is in the range of about 30 and 35 cm. With a system configuration that allows 2.5 cm of sheath introduction into the artery, and an arterial distance of between 5 and 10 cm from the arteriotomy site to the target site, this system enables a distance in the range of about 32.5 cm to 42.5 cm from the

hemostasis valve **625** (the location of interventional device introduction into the access sheath) to the target site of between 32 and 43 cm. This distance is about a third the distance required in prior art technology.

(70) A flush line **635** can be connected to the side of the hemostasis valve **625** and can have a stopcock **640** at its proximal or remote end. The flush-line **635** allows for the introduction of saline, contrast fluid, or the like, during the procedures. The flush line **635** can also allow pressure monitoring during the procedure. A dilator **645** having a tapered distal end **650** can be provided to facilitate introduction of the distal sheath **605** into the common carotid artery. The dilator **645** can be introduced through the hemostasis valve **625** so that the tapered distal end **650** extends through the distal end of the sheath **605**, as best seen in FIG. 7A. The dilator **645** can have a central lumen to accommodate a guide wire. Typically, the guide wire is placed first into the vessel, and the dilator/sheath combination travels over the guide wire as it is being introduced into the vessel.

(71) Optionally, a sheath stopper **705** such as in the form of a tube may be provided which is coaxially received over the exterior of the distal sheath **605**, also as seen in FIG. 7A. The sheath stopper **705** is configured to act as a sheath stopper to prevent the sheath from being inserted too far into the vessel. The sheath stopper **705** is sized and shaped to be positioned over the sheath body **605** such that it covers a portion of the sheath body **605** and leaves a distal portion of the sheath body **605** exposed. The sheath stopper **705** may have a flared proximal end **710** that engages the adapter **620**, and a distal end **715**. Optionally, the distal end **715** may be beveled, as shown in FIG. 7B. The sheath stopper **705** may serve at least two purposes. First, the length of the sheath stopper **705** limits the introduction of the sheath **605** to the exposed distal portion of the sheath **605**, as seen in FIG. 7A, such that the sheath insertion length is limited to the exposed distal portion of the sheath. In an embodiment, the sheath stopper limits the exposed distal portion to a range between 2 and 3 cm. In an embodiment, the sheath stopper limited the exposed distal portion to 2.5 cm. In other words, the sheath stopper may limit insertion of the sheath into the artery to a range between about 2 and 3 cm or to 2.5 cm. Second, the sheath stopper **705** can engage a pre-deployed puncture closure device disposed in the carotid artery wall, if present, to permit the sheath **605** to be withdrawn without dislodging the closure device. The sheath stopper **705** may be manufactured from clear material so that the sheath body may be clearly visible underneath the sheath stopper **705**. The sheath stopper **705** may also be made from flexible material, or the sheath stopper **705** include articulating or sections of increased flexibility so that it allows the sheath to bend as needed in a proper position once inserted into the artery. The sheath stopper may be plastically bendable such that it can be bent into a desired shape such that it retains the shape when released by a user. The distal portion of the sheath stopper may be made from stiffer material, and the proximal portion may be made from more flexible material. In an embodiment, the stiffer material is 85A durometer and the more flexible section is 50A durometer. In an embodiment, the stiffer distal portion is 1 to 4 cm of the sheath stopper **705**. The sheath stopper **705** may be removable from the sheath so that if the user desired a greater length of sheath insertion, the user could remove the sheath stopper **705**, cut the length (of the sheath stopper) shorter, and re-assemble the sheath stopper **705** onto the sheath such that a greater length of insertable sheath length protrudes from the sheath stopper **705**.

(72) FIG. 7C shows another embodiment of a sheath stopper **705** positioned adjacent a sheath **605** with a dilator **645** positioned therein. The sheath stopper **705** of FIG. 7C may be deformed from a first shaped, such as a straight shape, into a second different from the first shape wherein the sheath stopper retains the second shape until a sufficient external force acts on the sheath stopper to change its shape. The second shape may be for example non-straight, curved, or an otherwise contoured or irregular shape. For example, FIG. 7C shows the sheath stopper **705** having multiple bends as well as straight sections. FIG. 7C shows just an example and it should be appreciated that the sheath stopper **705** may be shaped to have any quantity of bends along its longitudinal axis. FIG. 7D shows the sheath stopper **705** positioned on the sheath **605**. The sheath stopper **705** has a

greater stiffness than the sheath **605** such that the sheath **605** takes on a shape or contour that conforms to the shape of contour of the sheath stopper **705**.

(73) The sheath stopper **705** may be shaped according to an angle of the sheath insertion into the artery and the depth of the artery or body habitus of the patient. This feature reduces the force of the sheath tip in the blood vessel wall, especially in cases where the sheath is inserted at a steep angle into the vessel. The sheath stopper may be bent or otherwise deformed into a shape that assists in orienting the sheath coaxially with the artery being entered even if the angle of the entry into the arterial incision is relatively steep. The sheath stopper may be shaped by an operator prior to sheath insertion into the patient. Or, the sheath stopper may be shaped and/or re-shaped in situ after the sheath has been inserted into the artery. FIGS. 7E and 7F show an example of the malleable sheath stopper **705** in use. FIG. 7E shows the sheath stopper **705** positioned on the sheath **605** with the sheath stopper **705** in a straight shape. The sheath **605** takes on the straight shape of the sheath stopper **705** and is entering the artery A at a relatively steep angle such that the distal tip of the sheath **605** abuts or faces the wall of the artery. In FIG. 7F, a user has bent the sheath stopper **705** so as to adjust the angle of entry of the sheath **605** so that the longitudinal axis of the sheath **605** is more aligned with the axis of the artery A. In this manner, the sheath stopper **705** has been formed by a user into a shape that assists in directing the sheath **605** away from the opposing wall of the artery A and into a direction that is more coaxial with the axis of the artery A relative to the shape in FIG. 7E.

(74) In an embodiment, the sheath stopper **705** is made from malleable material, or with an integral malleable component positioned on or in the sheath stopper. In another embodiment, the sheath stopper is constructed to be articulated using an actuator such as concentric tubes, pull wires, or the like. The wall of the sheath stopper may be reinforced with a ductile wire or ribbon to assist it in holding its shape against external forces such as when the sheath stopper encounters an arterial or entryway bend. Or the sheath stopper may be constructed of a homogeneous malleable tube material, including metal and polymer. The sheath stopper body may also be at least partially constructed of a reinforced braid or coil capable of retaining its shape after deformation.

(75) Another sheath stopper embodiment is configured to facilitate adjustment of the sheath stopper position (relative to the sheath) even after the sheath is positioned in the vessel. One embodiment of the sheath stopper includes a tube with a slit along most or all of the length, so that the sheath stopper can be peeled away from the sheath body, moved forward or backwards as desired, and then re-positioned along the length of the sheath body. The tube may have a tab or feature on the proximal end so it may be grasped and more easily to peel away.

(76) In another embodiment, the sheath stopper is a very short tube (such as a band), or ring that resides on the distal section of the sheath body. The sheath stopper may include a feature that could be grasped easily by forceps, for example, and pulled back or forwards into a new position as desired to set the sheath insertion length to be appropriate for the procedure. The sheath stopper may be fixed to the sheath body through either friction from the tube material, or a clamp that can be opened or closed against the sheath body. The clamp may be a spring-loaded clamp that is normally clamped onto the sheath body. To move the sheath stopper, the user may open the clamp with his or her fingers or an instrument, adjust the position of the clamp, and then release the clamp. The clamp is designed not to interfere with the body of the sheath.

(77) In another embodiment, the sheath stopper includes a feature that allows suturing the sheath stopper and sheath to the tissue of the patient, to improve securement of the sheath and reduce risk of sheath dislodgement. The feature may be suture eyelets that are attached or molded into the sheath stopper tube.

(78) In another embodiment, as shown in FIG. 9A, the sheath stopper **705** includes a distal flange **710** sized and shaped to distribute the force of the sheath stopper over a larger area on the vessel wall and thereby reduce the risk of vessel injury or accidental insertion of the sheath stopper through the arteriotomy and into the vessel. The flange **710** may have a rounded shape or other

atraumatic shape that is sufficiently large to distribute the force of the sheath stopper over a large area on the vessel wall. In an embodiment, the flange is inflatable or mechanically expandable. For example, the arterial sheath and sheath stopper may be inserted through a small puncture in the skin into the surgical area, and then expanded prior to insertion of the sheath into the artery.

(79) The sheath stopper may include one or more cutouts or indents **720** along the length of the sheath stopper which are patterned in a staggered configuration such that the indents increase the bendability of the sheath stopper while maintaining axial strength to allow forward force of the sheath stopper against the arterial wall. The indents may also be used to facilitate securement of the sheath to the patient via sutures, to mitigate against sheath dislodgement. The sheath stopper may also include a connector element **730** on the proximal end which corresponds to features on the arterial sheath such that the sheath stopper can be locked or unlocked from the arterial sheath. For example, the connector element is a hub with generally L-shaped slots **740** that correspond to pins **750** on the hub to create a bayonet mount-style connection. In this manner, the sheath stopper can be securely attached to the hub to reduce the likelihood that the sheath stopper will be inadvertently removed from the hub unless it is unlocked from the hub.

(80) The distal sheath **605** can be configured to establish a curved transition from a generally anterior-posterior approach over the common carotid artery to a generally axial luminal direction within the common carotid artery. Arterial access through the common carotid arterial wall either from a direct surgical cut down or a percutaneous access may require an angle of access that is typically larger than other sites of arterial access. This is due to the fact that the common carotid insertion site is much closer to the treatment site (i.e., carotid bifurcation) than from other access points. A larger access angle is needed to increase the distance from the insertion site to the treatment site to allow the sheath to be inserted at an adequate distance without the sheath distal tip reaching the carotid bifurcation. For example, the sheath insertion angle is typically 30-45 degrees or even larger via a transcarotid access, whereas the sheath insertion angle may be 15-20 degrees for access into a femoral artery. Thus the sheath must take a greater bend than is typical with introducer sheaths, without kinking and without causing undue force on the opposing arterial wall. In addition, the sheath tip desirably does not be abut or contact the arterial wall after insertion in a manner that would restrict flow into the sheath. The sheath insertion angle is defined as the angle between the luminal axis of the artery and the longitudinal axis of the sheath.

(81) The sheath body **605** can be formed in a variety of ways to allow for this greater bend required by the angle of access. For example, the sheath and/or the dilator may have a combined flexible bending stiffness less than typical introducer sheaths. In an embodiment, the sheath/dilator combination (i.e., the sheath with the dilator positioned inside the sheath) has a combined flexible stiffness ($E \cdot I$) in the range of about 80 and 100 N-m.^{sup.2}×10.^{sup.-6}, where E is the clastic modulus and I is the area moment of inertia of the device. The sheath alone may have a bending stiffness in the range of about 30 to 40 N-m.^{sup.2}×10.^{sup.-6} and the dilator alone has a bending stiffness in the range of about 40 to 60 N-m.^{sup.2}×10.^{sup.-6}. Typical sheath/dilator bending stiffnesses are in the range of 150 to 250 N-m.^{sup.2}×10.^{sup.-6}. The greater flexibility may be achieved through choice of materials or design of the reinforcement. For example, the sheath may have a ribbon coil reinforcement of stainless steel with dimensions. 0.002" to 0.003" thick and 0.005" to 0.015" width, and with outer jacket durometer of between 40 and 55D. In an embodiment, the coil ribbon is 0.003"×0.010", and the outer jacket durometer is 45D. In an embodiment, the sheath **605** can be pre-shaped to have a curve or an angle some set distance from the tip, typically 0.5 to 1 cm. The pre-shaped curve or angle can typically provide for a turn in the range from 5° to 90°, preferably from 10° to 30°. For initial introduction, the sheath **605** can be straightened with an obturator or other straight or shaped instrument such as the dilator **645** placed into its lumen. After the sheath **605** has been at least partially introduced through the percutaneous or other arterial wall penetration, the obturator can be withdrawn to allow the sheath **605** to reassume its pre-shaped configuration into the arterial lumen. To retain the curved or angled shape

of the sheath body after having been straightened during insertion, the sheath may be heat set in the angled or curved shape during manufacture. Alternately, the reinforcement structure may be constructed out of nitinol and heat shaped into the curved or angled shape during manufacture. Alternately, an additional spring element may be added to the sheath body, for example a strip of spring steel or nitinol, with the correct shape, added to the reinforcement layer of the sheath. (82) Other sheath configurations include having a deflection mechanism such that the sheath can be placed and the catheter can be deflected in situ to the desired deployment angle. In still other configurations, the catheter has a non-rigid configuration when placed into the lumen of the common carotid artery. Once in place, a pull wire or other stiffening mechanism can be deployed in order to shape and stiffen the sheath into its desired configuration. One particular example of such a mechanism is commonly known as “shape-lock” mechanisms as well described in medical and patent literature.

(83) Another sheath configuration comprises a curved dilator inserted into a straight but flexible sheath, so that the dilator and sheath are curved during insertion. The sheath is flexible enough to conform to the anatomy after dilator removal.

(84) Another sheath embodiment is a sheath that includes one or more flexible distal sections, such that once inserted and in the angled configuration, the sheath is able to bend at a large angle without kinking and without causing undue force on the opposing arterial wall. In one embodiment, there is a distalmost section of sheath body **605** which is more flexible than the remainder of the sheath body. For example, the flexural stiffness of the distalmost section is one half to one tenth the flexural stiffness of the remainder of the sheath body **605**. In an embodiment, the distalmost section has a flexural stiffness in the range 30 to 300 N-mm.^{sup.2} and the remaining portion of the sheath body **605** has a flexural stiffness in the range 500 to 1500 N-mm.^{sup.2}, For a sheath configured for a CCA access site, the flexible, distal most section comprises a significant portion of the sheath body **222** which may be expressed as a ratio. In an embodiment, the ratio of length of the flexible, distalmost section to the overall length of the sheath body **222** is at least one tenth and at most one half the length of the entire sheath body **222**. This change in flexibility may be achieved by various methods. For example, the outer jacket may change in durometer and/or material at various sections. Alternately, the reinforcement structure or the materials may change over the length of the sheath body. In an embodiment, the distal-most flexible section ranges from 1 cm to 3 cm. In an embodiment with more than one flexible section, a less flexible section (with respect to the distal-most section) may be 1 cm to 2 cm from the distal-most proximal section. In an embodiment, the distal flexible section has a bending stiffness in the range of about 30 to 50 N-m.^{sup.2}×10.^{sup.-6} and the less flexible section has a bending stiffness in the range of about 50 and 100 N-m.^{sup.2}×10.^{sup.-6}. In another embodiment, a more flexible section is located between 0.5 and 1.5 cm for a length of between 1 and 2 cm, to create an articulating section that allows the distal section of the sheath to align more easily with the vessel axis though the sheath enters the artery at an angle. These configurations with variable flexibility sections may be manufactured in several manners. For example the reinforced, less flexible section may vary such that there is stiffer reinforcement in the proximal section and more flexible reinforcement in the distal section or in the articulating section. In an embodiment, an outer-most jacket material of the sheath is 45D to 70D durometer in the proximal section and 80A to 25D in the distalmost section. In an embodiment, the flexibility of the sheath varies continuously along the length of the sheath body. FIG. 7G shows such a sheath inserted in the artery, with the flexible distal section allowing the sheath body to bend and the distal tip to be in general alignment with the vessel lumen. In an embodiment, the distal section is made with a more flexible reinforcement structure, either by varying the pitch of a coil or braid or by incorporating a cut hypotube with differing cut patterns. Alternately the distal section has a different reinforcement structure than the proximal section.

(85) In an embodiment, the distal sheath tapered tip is manufactured from harder material than the distal sheath body. A purpose of this is to facilitate ease of sheath insertion by allowing for a very

smooth taper on the sheath and reduce the change of sheath tip distortion or ovalizing during and after sheath insertion into the vessel. In one example the distal tapered tip material is manufactured from a higher durometer material, for example a 60-72D shore material. In another example, distal tip is manufactured from a separate material, for example HDPE, stainless steel, or other suitable polymers or metals. In an additional embodiment, the distal tip is manufactured from radiopaque material, either as an additive to the polymer material, for example tungsten or barium sulfate, or as an inherent property of the material (as is the case with most metal materials).

(86) In another embodiment, the dilator **645** may also have variable stiffness. For example the tapered tip **650** of the dilator may be made from more flexible material than the proximal portion of the dilator, to minimize the risk of vessel injury when the sheath and dilator are inserted into the artery. In an embodiment, the distal flexible section has a bending stiffness in the range of about 45 to 55 N-m.^{sup.2}×10.^{sup.-6} and a less flexible proximal section has a bending stiffness in the range of about 60 and 90 N-m.^{sup.2}×10.^{sup.-6}. The taper shape of the dilator may also be optimized for transcarotid access. For example, to limit the amount of sheath and dilator tip that enter the artery, the taper length and the amount of the dilator that extends past the sheath should be shorter than typical introducer sheaths. For example, the taper length may be 1 to 1.5 cm, and extend 1.5 to 2 cm from the end of the sheath body. In an embodiment, the dilator contains a radiopaque marker at the distal tip so that the tip position is easily visible under fluoroscopy.

(87) In another embodiment, the introducer guide wire is optimally configured for transcarotid access. Typically, when inserting an introducer sheath into a vessel, an introducer guide wire is first inserted into the vessel. This may be done either with a micropuncture technique or a modified Seldinger technique. Usually there is a long length of vessel in the direction that the sheath is to be inserted into which an introducer guidewire may be inserted, for example into the femoral artery. In this instance, a user may introduce a guide wire between 10 and 15 cm or more into the vessel before inserting the sheath. The guide wire is designed to have a flexible distal section so as not to injure the vessel when being introduced into the artery. The flexible section of an introducer sheath guide wire is typically 5 to 6 cm in length, with a gradual transition to the stiffer section. Inserting the guide wire 10 to 15 cm means the stiffer section of the guide wire is positioned in the area of the puncture and allows a stable support for subsequent insertion of the sheath and dilator into the vessel. However, in the case of transcarotid sheath insertion into the common carotid artery, there is a limit on how much guide wire may be inserted into the carotid artery. In cases with carotid artery disease at the bifurcation or in the internal carotid artery, it is desirable to minimize the risk of emboli by inserting the wire into the external carotid artery (ECA), which would mean only about 5 to 7 cm of guide wire insertion, or to stop it before it reaches the bifurcation, which would be only 3 to 5 cm of guide wire insertion. Thus, a transcarotid sheath guidewire may have a distal flexible section of between 3 and 4 cm, and/or a shorter transition to a stiffer section. Alternately, a transcarotid sheath guidewire has an atraumatic tip section but have a very distal and short transition to a stiffer section. For example, the soft tip section is 1.5 to 2.5 cm, followed by a transition section with length from 3 to 5 cm, followed by a stiffer proximal segment, with the stiffer proximal section comprising the remainder of the wire.

(88) In addition to the configurations described above, features may be included in the introducer guide wire, or the micropuncture catheter, or the micropuncture catheter guide wire, to prevent inadvertent advancement of these devices into the diseased portion of the carotid artery. For example, a stopper feature may be positioned over the introducer guide wire, micropuncture catheter and/or the micropuncture guide wire to limit the length these devices can be inserted. The stopper feature may be, for example, a short section of tubing which can be slideably positioned on the device, and once positioned remains in place on the device via friction. For example, the stopper feature may be manufactured from soft polymer material such as silicone rubber, polyurethane, or other thermoplastic elastomer. The stopper feature may have an inner diameter the same size or even slightly smaller than the device diameter. Alternately the stopper feature may be

configured to clamp on to the device, such that the user must squeeze or otherwise unlock the stopper feature to unclamp and reposition the device, and then release or otherwise relock the stopper feature onto the device. The stopper feature may be positioned for optimal entry into the vessel based on location of the puncture site, distance of the bifurcation with respect to the puncture site, and amount of disease in the carotid bifurcation.

(89) The sheath guide wire may have guide wire markings to help the user determine where the tip of the wire is with respect to the dilator. For example, there may be a marking on the proximal end of the wire corresponding to when the tip of the wire is about to exit the micro access cannula tip. This marking would provide rapid wire position feedback to help the user limit the amount of wire insertion. In another embodiment, the wire may include an additional mark to let the user know the wire has exited the cannula by a set distance, for example 5 cm. Alternately, the introducer guide wire, micropuncture catheter and/or the micropuncture guide wire may be constructed or have sections constructed out of material which is markable with a marking pen, wherein the mark is easily visible in a cath lab or operating room (OR) setting. In this embodiment, the user pre-marks the components based on the anatomic information as described above, and uses these marks to determine the amount of maximal insertion for each component. For example, the guide wires may have a white coating around the section to be marked.

(90) In an embodiment, the sheath has built-in puncturing capability and atraumatic tip analogous to a guide wire tip. This eliminates the need for needle and wire exchange currently used for arterial access according to the micropuncture technique, and can thus save time, reduce blood loss, and require less surgeon skill.

(91) In another embodiment, the sheath dilator is configured to be inserted over an 0.018" guide wire for transcarotid access. Standard sheath insertion using a micropuncture kit requires first insertion of an 0.018" guide wire through a 22 Ga needle, then exchange of the guide wire to an 0.035" or 0.038" guide wire using a micropuncture catheter, and finally insertion of the sheath and dilator over the 0.035" or 0.038" guide wire. There exist sheaths which are insertable over a 0.018" guidewire, thus eliminating the need for the wire exchange. These sheaths, usually labeled "transradial" as they are designed for insertion into the radial artery, typically have a longer dilator taper, to allow an adequate diameter increase from the 0.018" wire to the body of the sheath. Unfortunately for transcarotid access, the length for sheath and dilator insertion is limited and therefore these existing sheaths are not appropriate. Another disadvantage is that the 0.018" guide wire may not have the support needed to insert a sheath with a sharper angle into the carotid artery. In the embodiment disclosed here, a transcarotid sheath system includes a sheath body, a sheath dilator, and an inner tube with a tapered distal edge that slidably fits inside the sheath dilator and can accommodate an 0.018" guide wire.

(92) To use this sheath system embodiment, the 0.018" guide wire is first inserted into the vessel through a 22 Ga needle. The sheath system which is coaxially assembled is inserted over the 0.018" wire. The inner tube is first advanced over the 0.018" wire which essentially transforms it into the equivalent of an 0.035" or 0.038" guide wire in both outer diameter and mechanical support. It is locked down to the 0.018" wire on the proximal end. The sheath and dilator are then advanced over the 0.018" wire and inner tube into the vessel. This configuration eliminates the wire exchange step without the need for a longer dilator taper as with current transradial sheaths and with the same guide wire support as standard introducer sheaths. As described above, this configuration of sheath system may include stopper features which prevent inadvertent advancement too far of the 0.018" guide wire and/or inner tube during sheath insertion. Once the sheath is inserted, the dilator, inner tube, and 0.018" guide wire are removed.

(93) FIG. 8A shows another embodiment of the arterial access device **110**. This embodiment is substantially the same as the embodiment shown in FIG. 6A, except that the distal sheath **605** includes an occlusion element **129** for occluding flow through, for example the common carotid artery. If the occluding element **129** is an inflatable structure such as a balloon or the like, the

sheath **605** can include an inflation lumen that communicates with the occlusion element **129**. The occlusion element **129** can be an inflatable balloon, but it could also be an inflatable cuff, a conical or other circumferential element which flares outwardly to engage the interior wall of the common carotid artery to block flow therepast, a membrane-covered braid, a slotted tube that radially enlarges when axially compressed, or similar structure which can be deployed by mechanical means, or the like. In the case of balloon occlusion, the balloon can be compliant, non-compliant, elastomeric, reinforced, or have a variety of other characteristics. In an embodiment, the balloon is an elastomeric balloon which is closely received over the exterior of the distal end of the sheath prior to inflation. When inflated, the elastomeric balloon can expand and conform to the inner wall of the common carotid artery. In an embodiment, the elastomeric balloon is able to expand to a diameter at least twice that of the non-deployed configuration, frequently being able to be deployed to a diameter at least three times that of the undeployed configuration, more preferably being at least four times that of the undeployed configuration, or larger.

(94) As shown in FIG. **8B**, the distal sheath **605** with the occlusion element **129** can have a stepped or other configuration having a reduced diameter distal region **630**. The distal region **630** can be sized for insertion into the carotid artery with the remaining proximal region of the sheath **605** having larger outside and luminal diameters, with the inner diameter typically being in the range from 2.794 mm (0.110 inch) to 3.43 mm (0.135 inch). The larger luminal diameter of the proximal region minimizes the overall flow resistance of the sheath. In an embodiment, the reduced-diameter distal section **630** has a length of approximately 2 cm to 4 cm. The relatively short length of the reduced-diameter distal section **630** permits this section to be positioned in the common carotid artery CCA via the transcarotid approach with reduced risk that the distal end of the sheath **605** will contact the bifurcation B.

(95) FIG. **2B** shows an alternative embodiment, wherein the occlusion element **129** can be introduced into the carotid artery on a second sheath **112** separate from the distal sheath **605** of the arterial access device **110**. The second or “proximal” sheath **112** can be adapted for insertion into the common carotid artery in a proximal or “downward” direction away from the cerebral vasculature. The second, proximal sheath can include an inflatable balloon **129** or other occlusion element, generally as described above. The distal sheath **605** of the arterial access device **110** can be then placed into the common carotid artery distal of the second, proximal sheath and generally oriented in a distal direction toward the cerebral vasculature. By using separate occlusion and access sheaths, the size of the arteriotomy needed for introducing the access sheath can be reduced.

(96) FIG. **2C** shows yet another embodiment of a two arterial sheath system, wherein the interventional devices are introduced via an introducer sheath **114** separate from the distal sheath **605** of the arterial device **110**. A second or “distal” sheath **114** can be adapted for insertion into the common carotid artery distal to the arterial access device **110**. As with the previous embodiment, the use of two separate access sheaths allows the size of each arteriotomy to be reduced.

(97) In a situation with a sharp sheath insertion angle and/or a short length of sheath inserted in the artery, such as one might see in a transcarotid access procedure, the distal tip of the sheath has a higher likelihood of being partially or totally positioned against the vessel wall, thereby restricting flow into the sheath. In an embodiment, the sheath is configured to center the tip in the lumen of the vessel. One such embodiment includes a balloon such as the occlusion element **129** described above. In another embodiment, a balloon may not be occlusive to flow but still center the tip of the sheath away from a vessel wall, like an inflatable bumper. In another embodiment, expandable features are situated at the tip of the sheath and mechanically expanded once the sheath is in place. Examples of mechanically expandable features include braided structures or helical structures or longitudinal struts which expand radially when shortened.

(98) In an embodiment, occlusion of the vessel proximal to the distal tip of the sheath may be done from the outside of the vessel, as in a Rummel tourniquet or vessel loop proximal to sheath insertion site. In an alternate embodiment, an occlusion device may fit externally to the vessel

around the sheath tip, for example an elastic loop, inflatable cuff, or a mechanical clamp that could be tightened around the vessel and distal sheath tip. In a system of flow reversal, this method of vessel occlusion minimizes the area of static blood flow, thereby reducing risk of thrombus formation, and also ensure that the sheath tip is axially aligned with vessel and not partially or fully blocked by the vessel wall.

(99) Another arterial access device is shown in FIGS. **9A-9D**. This configuration has a different style of connection to the flow shunt than the versions described previously. FIG. **9A** shows the components of the arterial access device **110** including arterial access sheath **605**, sheath dilator **645**, sheath stopper **705**, and sheath guidewire **611**. FIG. **9B** shows the arterial access device **110** as it would be assembled for insertion over the sheath guide wire **611** into the carotid artery. After the sheath is inserted into the artery and during the procedure, the sheath guide wire **611** and sheath dilator **705** are removed. In this configuration, the sheath has a sheath body **605**, proximal extension **610**, and proximal hemostasis valve **625** with flush line **635** and stopcock **640**. The proximal extension **610** extends from a Y-adaptor **660** to the hemostasis valve **625** where the flush line **635** is connected. The sheath body **605** is the portion that is sized to be inserted into the carotid artery and is actually inserted into the artery during use.

(100) Instead of a Y-connector with a flow line connection terminating in a valve, the sheath has a Y-adaptor **660** that connects the distal portion of the sheath to the proximal extension **610**. The Y-adaptor can also include a valve **670** that can be operated to open and close fluid connection to a connector or hub **680** that can be removably connected to a flow line such as a shunt. The valve **670** is positioned immediately adjacent to an internal lumen of the adaptor **660**, which communicates with the internal lumen of the sheath body **605**. FIGS. **9C** and **9D** show details in cross section of the Y-adaptor **660** with the valve **670** and the hub **680**. FIG. **9C** shows the valve closed to the connector. This is the position that the valve would be in during prep of the arterial sheath. The valve is configured so that there is no potential for trapped air during prep of the sheath. FIG. **9D** shows the valve open to the connector. This position would be used once the flow shunt **120** is connected to hub **680**, and would allow blood flow from the arterial sheath into the shunt. This configuration eliminates the need to prep both a flush line and flow line, instead allowing prep from the single flush line **635** and stopcock **640**. This single-point prep is identical to prep of conventional introducer sheaths which do not have connections to shunt lines, and is therefore more familiar and convenient to the user. In addition, the lack of flow line on the sheath makes handling of the arterial sheath easier during prep and insertion into the artery.

(101) With reference again to FIG. **9A**, the sheath may also contain a second more distal connector **690**, which is separated from the Y-adaptor **660** by a segment of tubing **665**. A purpose of this second connector and the tubing **665** is to allow the valve **670** to be positioned further proximal from the distal tip of the sheath, while still limiting the length of the insertable portion of the sheath **605**, and therefore allow a reduced level of exposure of the user to the radiation source as the flow shunt is connected to the arterial sheath during the procedure. In an embodiment, the distal connector **690** contains suture eyelets to aid in securement of the sheath to the patient once positioned.

(102) During a transcarotid artery revascularization (TCAR) procedure, the arterial sheath **605** can be inserted into the common carotid artery (CCA) of the patient. As described elsewhere herein, to achieve reverse flow of blood, the CCA may be occluded to stop antegrade blood flow from the aorta through the CCA. Flow through the CCA can be occluded with an external vessel loop or tape, a vascular clamp, an internal occlusion member such as a balloon, or other type of occlusion means. When flow through CCA is blocked, the natural pressure gradient between the internal carotid artery (ICA) and the venous system will cause blood to flow in a retrograde or reverse direction from the cerebral vasculature. Blood from the ICA and the external carotid artery (ECA) flows in a retrograde direction and the systems described herein allow the retrograde blood to flow into the sheath **605**, through the flow controller **1130**, the venous sheath **910**, and then returned into

the patient's femoral vein as described elsewhere herein. Loose embolic material can be carried with the retrograde blood flow into the arterial sheath **605**.

(103) FIGS. **13A-13B** illustrate an arterial sheath **605** inserted within a vessel V, such as the carotid artery, exposed through an incision I. A sheath guidewire **611** and an arterial access sheath dilator **645** protrude out from a distal opening **641** near the distal region **630** of the sheath **605**. A sheath stopper **705** can be used with the sheath **605**, as described elsewhere herein. Manual occlusion of the vessel V by a clinician at an occlusion location proximal to the distal tip of the sheath **605** may be provided from the outside of the vessel V using a vascular clamp **800**, such as a Rummel tourniquet or vessel loop positioned proximal to the sheath insertion site. An occlusion device may fit externally to the vessel V around the sheath tip, for example, an elastic loop, inflatable cuff, or a mechanical clamp that can be tightened around the vessel and the distal sheath tip. In a flow reversal system, this type of vessel occlusion can minimize creation of a zone of static blood flow, thereby reducing the risk of thrombus formation. This also ensures that the sheath tip is axially aligned with the vessel V and avoids partially or fully blocking the distal opening **641** by the vessel wall.

(104) Despite these clamp techniques, the zone of static blood flow can still be created. FIG. **13B** illustrates a system for retrograde blood flow into the distal opening **641** of the arterial sheath **605** after removal of the access sheath dilator **645**. The location of the vascular clamp **800** in FIG. **13B** is partially obscured by the presence of the sheath stopper **705**. Embolic material within the retrograde blood flow may drift and be trapped within a zone **905** of static blood flow within the vessel V between the distal opening **641** of the arterial sheath **605** and the location of the vascular clamp **800** proximal to the sheath insertion location. Embolic material may remain within this zone **905** rather than flow into the distal opening **641** of the arterial sheath **605**. Once the target vessel has been treated by the operator, the vascular clamp **800** is released permitting resumption of antegrade blood flow. Embolic material from this zone **905** may be carried into the neurovasculature when the vascular clamp **800** is released and antegrade blood flow resumes. The trapped embolic material within the zone **905** may cause an ischemic event despite the use of reverse flow embolic protection during the procedure because it fails to ever enter the lumen of the arterial sheath **605** during the period of retrograde flow.

(105) FIG. **13C** illustrates a distal end region of an implementation of an arterial sheath **605** having a fenestrated distal portion **643**. The fenestrated distal portion **643** of the sheath **605** includes one or more side holes or fenestrations **646** in the side wall of the sheath **605**. As described above, blood from zone **905** may potentially contain embolic material that would otherwise flow into the neurovasculature upon release of the vascular clamp **800**. Material from this zone **905** can enter the sheath **605** through the fenestrations **646** in the sidewall of the sheath **605**. The fenestrations **646** can also maintain flow into the sheath **605** even if the distal opening **641** at the distal tip of sheath **605** is partially or fully blocked by arterial wall. Blood and any embolic material can flow into the lumen of the sheath **604** through the one or more fenestrations **646** and transported proximally through the embolic protection system with the retrograde blood flow.

(106) The location, distribution, shape, and size of the fenestrations **646** can vary. The fenestrations **646** can be distributed longitudinally and/or circumferentially along the distal portion **643** of the arterial sheath **605**. The location and distribution of the fenestrations **646** can be selected based on whether a sheath stopper **705** is to be used with the sheath **605**. For example, a sheath stopper **705** can be positioned on the arterial sheath **605** to limit an insertion depth of the sheath **605** into the vessel. In some implementations, the sheath stopper **705** limits the insertion depth to 2.5 cm. Thus, the one or more fenestrations **646** can be distributed along the distal-most 2.5 cm of the sheath **605**. Fenestrations **646** may also be distributed along the sheath **605** over a greater distance. The proximal sheath fenestrations **646** sitting external to the vessel can be blocked by a sleeve or other feature of the system thereby preventing leakage.

(107) As described elsewhere herein, the sheath **605** can be reinforced to provide improved

flexibility and kink-resistance. The reinforcement can be a spiral-wound stainless steel ribbon, braid, or mesh as is known in the art. The one or more fenestrations **646** can be positioned such that they extend through and/or align with the side wall in the space(s) between the reinforcement material such that the fenestrations **646** and the space(s) collectively form passageways through which fluid can flow into the internal lumen of the sheath **605**. The spaces within the reinforcement layer can include gaps between individual coils, circular or diamond-shaped holes through the braid or mesh, etc. The fenestrations **646** through the sidewall of the sheath **605** align with these spaces or gaps in the reinforcement layer thereby providing additional entrance points for blood and embolic material while maintaining the structural benefits of the reinforcement layer. The orientation of the fenestrations **646** can be such that they align with these spaces between the reinforcement material (see FIG. 13D). The fenestrations **646** can vary in their number, size, and shape, including circular, oval, rectangular, or other elongate shape. The elongate fenestrations **646** can extend along an axis perpendicular or at an angle to the longitudinal axis of the sheath overall such that they fit within or align with the spaces between the reinforcement layer.

(108) For example, as described elsewhere herein the arterial sheath **605** may have a ribbon coil reinforcement of stainless steel with dimensions 0.002" to 0.003" thick and 0.005" to 0.015" width. In an embodiment, the coil ribbon is 0.003"×0.010". The nominal spacing between the reinforcement coils of the sheath **605** can vary, but generally is about 0.020". The elongated fenestrations **646** can thus have a width of about this size such that they extend through the wall between the reinforcement coils. In some implementations, the fenestrations **646** can be between about 0.010" to about 0.080", with a nominal range of about 0.015"-0.020". Depending on the spacing between the reinforcement, the elongated fenestrations **646** can have a size between 0.015"×0.030" to about 0.040"×0.080". Elongated fenestrations **646** that fit between or within the gaps in the reinforcement material can be up to about 0.020", with a maximum envisioned dimension of about 0.020"×0.080". It may be possible to vary the pitch of the coils as well as the width of the coil ribbon to adjust and optimize the flexibility and performance of the sheath **605** and the size of the fenestrations **646**. For example, the reinforcement material can be a coil ribbon.

(109) The width between the individual coils can be increased near where one or more fenestrations **646** would extend through the wall of the sheath **605**. The width near this location can be increased from 0.020" to 0.050". The fenestrations **646** need not be limited to the location of the gaps in the reinforcement. For example, the reinforcement material can be a wire or polymer mesh. One or more regions of the mesh can be cut to create a larger sized space (while taking into consideration maintaining the overall functionality of the sheath) and the one or more fenestrations **646** co-located to that larger space.

(110) The embolic protection system can include a passive method of driving retrograde blood flow into the distal opening **641** at the sheath tip and the fenestrations **646** in the distal end region **643**, for example, by relying upon arterial-venous pressure differential. The embolic protection system can also incorporate active aspiration of blood through the arterial sheath **605** to enhance the withdrawal of embolic material into the distal opening **641** as well as through the fenestrations **646**. The fenestrations **646** can also be useful in delivering materials into the vessel through the fenestrations **646**. In some implementations, a gentle injection of saline through the lumen of the sheath **605** into the vessel through the fenestrations **646** can cause turbulence/agitation within the zone **905** of static blood. The flush of fluid can induce any particulates trapped within the zone **905** to be drawn into the fluid flow path and to enter the sheath **605**, either through the fenestrations **646** upon resumption of aspiration forces or through the distal opening **641**.

(111) The arterial sheath **605** having one or more fenestrations **646** on the distal end portion **643** can be delivered in combination with a delivery tool (not shown) configured to facilitate a smooth delivery into the vessel and prevent the edges of the fenestrations **646** from catching on tissue as the sheath **605** is inserted through the vessel wall. The fenestrations **646** may also impact delivery of guidewires, balloon catheters, or other devices through the lumen of the arterial sheath **605**. As

such, the arterial sheath **605** can incorporate a secondary sleeve on the inside or outside of the arterial sheath **605**. The secondary sleeve can be initially positioned such that the sheath fenestrations **646** are covered or closed, thereby permitting smooth passage of guidewires and other devices through the lumen of the arterial sheath **605**. Once the devices have been passed through the sheath, the secondary sleeve can be rotated, advanced and/or retracted to uncover or open the fenestrations. A lubricious coating of material on the inner and/or outer surfaces of the sheath **605** can be provided to improve advancement of materials. In addition, a coating of heparin can be provided to decrease the likelihood of thrombus formation on the sheath **605**.

(112) Venous Return Device

(113) Referring now to FIG. **10**, the venous return device **115** can comprise a distal sheath **910** and a flow line **915**, which connects to and forms a leg of the shunt **120** when the system is in use. The distal sheath **910** is adapted to be introduced through an incision or puncture into a venous return location, such as the jugular vein or femoral vein. The distal sheath **910** and flow line **915** can be permanently affixed, or can be attached using a conventional luer fitting, as shown in FIG. **10A**. Optionally, as shown in FIG. **10B**, the sheath **910** can be joined to the flow line **915** by a Y-connector **1005**. The Y-connector **1005** can include a hemostasis valve **1010**. The venous return device also comprises a venous sheath dilator **1015** and an introducer guide wire **611** to facilitate introduction of the venous return device into the internal jugular vein or other vein. As with the arterial access dilator **645**, the venous dilator **1015** includes a central guide wire lumen so the venous sheath and dilator combination can be placed over the guide wire **611**. Optionally, the venous sheath **910** can include a flush line **1020** with a stopcock **1025** at its proximal or remote end.

(114) An alternate configuration is shown in FIGS. **10C** and **10D**. FIG. **10C** shows the components of the venous return device **115** including venous return sheath **910**, sheath dilator **1015**, and sheath guidewire **611**. FIG. **10D** shows the venous return device **115** as it would be assembled for insertion over the sheath guide wire **611** into a central vein. Once the sheath is inserted into the vein, the dilator and guidewire are removed. The venous sheath can include a hemostasis valve **1010** and flow line **915**. A stopcock **1025** on the end of the flow line allows the venous sheath to be flushed via the flow line prior to use. This configuration allows the sheath to be prepped from a single point, as is done with conventional introducer sheaths. Connection to the flow shunt **120** is made with a connector **1030** on the stopcock **1025**.

(115) In order to reduce the overall system flow resistance, the arterial access flow line **615** (FIG. **6A**) and the venous return flow line **915**, and Y-connectors **620** (FIG. **6A**) and **1005**, can each have a relatively large flow lumen inner diameter, typically being in the range from 2.54 mm (0.100 inch) to 5.08 mm (0.200 inch), and a relatively short length, typically being in the range from 10 cm to 20 cm. The low system flow resistance is desirable since it permits the flow to be maximized during portions of a procedure when the risk of emboli is at its greatest. The low system flow resistance also allows the use of a variable flow resistance for controlling flow in the system, as described in more detail below. The dimensions of the venous return sheath **910** can be generally the same as those described for the arterial access sheath **605** above. In the venous return sheath, an extension for the hemostasis valve **1010** is not required.

(116) Retrograde Shunt

(117) The shunt **120** can be formed of a single tube or multiple, connected tubes that provide fluid communication between the arterial access catheter **110** and the venous return catheter **115** to provide a pathway for retrograde blood flow therebetween. As shown in FIG. **1A**, the shunt **120** connects at one end (via connector **127a**) to the flow line **615** of the arterial access device **110**, and at an opposite end (via connector **127b**) to the flow line **915** of the venous return catheter **115**.

(118) In an embodiment, the shunt **120** can be formed of at least one tube that communicates with the flow control assembly **125**. The shunt **120** can be any structure that provides a fluid pathway for blood flow. The shunt **120** can have a single lumen or it can have multiple lumens. The shunt **120**

can be removably attached to the flow control assembly **125**, arterial access device **110**, and/or venous return device **115**. Prior to use, the user can select a shunt **120** with a length that is most appropriate for use with the arterial access location and venous return location. In an embodiment, the shunt **120** can include one or more extension tubes that can be used to vary the length of the shunt **120**. The extension tubes can be modularly attached to the shunt **120** to achieve a desired length. The modular aspect of the shunt **120** permits the user to lengthen the shunt **120** as needed depending on the site of venous return. For example, in some patients, the internal jugular vein IJV is small and/or tortuous. The risk of complications at this site may be higher than at some other locations, due to proximity to other anatomic structures. In addition, hematoma in the neck may lead to airway obstruction and/or cerebral vascular complications. Consequently, for such patients it may be desirable to locate the venous return site at a location other than the internal jugular vein IJV, such as the femoral vein. A femoral vein return site may be accomplished percutaneously, with lower risk of serious complication, and also offers an alternative venous access to the central vein if the internal jugular vein IJV is not available. Furthermore, the femoral venous return changes the layout of the reverse flow shunt such that the shunt controls may be located closer to the “working area” of the intervention, where the devices are being introduced and the contrast injection port is located.

(119) In an embodiment, the shunt **120** has an internal diameter of 4.76 mm (3/16 inch) and has a length of 40-70 cm. As mentioned, the length of the shunt can be adjusted. In an embodiment, connectors between the shunt and the arterial and/or venous access devices are configured to minimize flow resistance. In an embodiment, the arterial access sheath **110**, the retrograde shunt **120**, and the venous return sheath **115** are combined to create a low flow resistance arterio-venous AV shunt, as shown in FIGS. **1A-1D**. As described above, the connections and flow lines of all these devices are optimized to minimize or reduce the resistance to flow. In an embodiment, the AV shunt has a flow resistance which enables a flow of up to 300 mL/minute when no device is in the arterial sheath **110** and when the AV shunt is connected to a fluid source with the viscosity of blood and a static pressure head of 60 mmHg. The actual shunt resistance may vary depending on the presence or absence of a check valve **1115** or a filter **1145** (as shown in FIG. **11**), or the length of the shunt, and may enable a flow of between 150 and 300 mL/min.

(120) When there is a device such as a stent delivery catheter in the arterial sheath, there is a section of the arterial sheath that has increased flow resistance, which in turn increases the flow resistance of the overall AV shunt. This increase in flow resistance has a corresponding reduction in flow. In an embodiment, the Y-arm **620** as shown in FIG. **6A** connects the arterial sheath body **605** to the flow line **615** some distance away from the hemostasis valve **625** where the catheter is introduced into the sheath. This distance is set by the length of the proximal extension **610**. Thus the section of the arterial sheath that is restricted by the catheter is limited to the length of the sheath body **605**. The actual flow restriction will depend on the length and inner diameter of the sheath body **605**, and the outer diameter of the catheter. As described above, the sheath length may range from 5 to 15 cm, usually being from 10 cm to 12 cm, and the inner diameter is typically in the range from 7 Fr (1 Fr=0.33 mm), to 10 Fr, usually being 8 Fr. Stent delivery catheters may range from 3.7 Fr. to 5.0 or 6.0 Fr, depending on the size of the stent and the manufacturer. This restriction may further be reduced if the sheath body is designed to increase in inner diameter for the portion not in the vessel (a stepped sheath body), as shown in FIG. **6B**. Since flow restriction is proportional to luminal distances to the fourth power, small increases in luminal or annular areas result in large reductions in flow resistance.

(121) Actual flow through the AV shunt when in use will further depend on the cerebral blood pressures and flow resistances of the patient.

(122) Flow Control Assembly-Regulation and Monitoring of Retrograde Flow

(123) The flow control assembly **125** interacts with the retrograde shunt **120** to regulate and/or monitor the retrograde flow rate from the common carotid artery to the venous return site, such as

the femoral vein, internal jugular vein, or to the external receptacle **130**. In this regard, the flow control assembly **125** enables the user to achieve higher maximum flow rates than existing systems and to also selectively adjust, set, or otherwise modulate the retrograde flow rate. Various mechanisms can be used to regulate the retrograde flow rate, as described more fully below. The flow control assembly **125** enables the user to configure retrograde blood flow in a manner that is suited for various treatment regimens, as described below.

(124) In general, the ability to control the continuous retrograde flow rate allows the physician to adjust the protocol for individual patients and stages of the procedure. The retrograde blood flow rate will typically be controlled over a range from a low rate to a high rate. The high rate can be at least two fold higher than the low rate, typically being at least three fold higher than the low rate, and often being at least five fold higher than the low rate, or even higher. In an embodiment, the high rate is at least three fold higher than the low rate and in another embodiment the high rate is at least six fold higher than the low rate. While it is generally desirable to have a high retrograde blood flow rate to maximize the extraction of emboli from the carotid arteries, the ability of patients to tolerate retrograde blood flow will vary. Thus, by having a system and protocol which allows the retrograde blood flow rate to be easily modulated, the treating physician can determine when the flow rate exceeds the tolerable level for that patient and set the reverse flow rate accordingly. For patients who cannot tolerate continuous high reverse flow rates, the physician can chose to turn on high flow only for brief, critical portions of the procedure when the risk of embolic debris is highest. At short intervals, for example between 15 seconds and 1 minute, patient tolerance limitations are usually not a factor.

(125) In specific embodiments, the continuous retrograde blood flow rate can be controlled at a base line flow rate in the range from 10 ml/min to 200 ml/min, typically from 20 ml/min to 100 ml/min. These flow rates will be tolerable to the majority of patients. Although flow rate is maintained at the base line flow rate during most of the procedure, at times when the risk of emboli release is increased, the flow rate can be increased above the base line for a short duration in order to improve the ability to capture such emboli. For example, the retrograde blood flow rate can be increased above the base line when the stent catheter is being introduced, when the stent is being deployed, pre- and post-dilatation of the stent, removal of the common carotid artery occlusion, and the like.

(126) The flow rate control system can be cycled between a relatively low flow rate and a relatively high flow rate in order to “flush” the carotid arteries in the region of the carotid bifurcation prior to reestablishing antegrade flow. Such cycling can be established with a high flow rate which can be approximately two to six fold greater than the low flow rate, typically being about three fold greater. The cycles can typically have a length in the range from 0.5 seconds to 10 seconds, usually from 2 seconds to 5 seconds, with the total duration of the cycling being in the range from 5 seconds to 60 seconds, usually from 10 seconds to 30 seconds.

(127) FIG. **11** shows an example of the system **100** with a schematic representation of the flow control assembly **125**, which is positioned along the shunt **120** such that retrograde blood flow passes through or otherwise communicates with at least a portion of the flow control assembly **125**. The flow control assembly **125** can include various controllable mechanisms for regulating and/or monitoring retrograde flow. The mechanisms can include various means of controlling the retrograde flow, including one or more pumps **1110**, valves **1115**, syringes **1120** and/or a variable resistance component **1125**. The flow control assembly **125** can be manually controlled by a user and/or automatically controlled via a controller **1130** to vary the flow through the shunt **120**. For example, by varying the flow resistance, the rate of retrograde blood flow through the shunt **120** can be controlled. The controller **1130**, which is described in more detail below, can be integrated into the flow control assembly **125** or it can be a separate component that communicates with the components of the flow control assembly **125**.

(128) In addition, the flow control assembly **125** can include one or more flow sensors **1135** and/or

anatomical data sensors **1140** (described in detail below) for sensing one or more aspects of the retrograde flow. A filter **1145** can be positioned along the shunt **120** for removing emboli before the blood is returned to the venous return site. When the filter **1145** is positioned upstream of the controller **1130**, the filter **1145** can prevent emboli from entering the controller **1145** and potentially clogging the variable flow resistance component **1125**. It should be appreciated that the various components of the flow control assembly **125** (including the pump **1110**, valves **1115**, syringes **1120**, variable resistance component **1125**, sensors **1135/1140**, and filter **1145**) can be positioned at various locations along the shunt **120** and at various upstream or downstream locations relative to one another. The components of the flow control assembly **125** are not limited to the locations shown in FIG. **11**. Moreover, the flow control assembly **125** does not necessarily include all of the components but can rather include various sub-combinations of the components. For example, a syringe could optionally be used within the flow control assembly **125** for purposes of regulating flow or it could be used outside of the assembly for purposes other than flow regulation, such as to introduce fluid such as radiopaque contrast into the artery in an antegrade direction via the shunt **120**.

(129) Both the variable resistance component **1125** and the pump **1110** can be coupled to the shunt **120** to control the retrograde flow rate. The variable resistance component **1125** controls the flow resistance, while the pump **1110** provides for positive displacement of the blood through the shunt **120**. Thus, the pump can be activated to drive the retrograde flow rather than relying on the perfusion stump pressures of the ECA and ICA and the venous back pressure to drive the retrograde flow. The pump **1110** can be a peristaltic tube pump or any type of pump including a positive displacement pump. The pump **1110** can be activated and deactivated (either manually or automatically via the controller **1130**) to selectively achieve blood displacement through the shunt **120** and to control the flow rate through the shunt **120**. Displacement of the blood through the shunt **120** can also be achieved in other manners including using the aspiration syringe **1120**, or a suction source such as a vacutainer, vaculock syringe, or wall suction may be used. The pump **1110** can communicate with the controller **1130**.

(130) One or more flow control valves **1115** can be positioned along the pathway of the shunt. The valve(s) can be manually actuated or automatically actuated (via the controller **1130**). The flow control valves **1115** can be, for example one-way valves to prevent flow in the antegrade direction in the shunt **120**, check valves, or high pressure valves which would close off the shunt **120**, for example during high-pressure contrast injections (which are intended to enter the arterial vasculature in an antegrade direction). In an embodiment, the one-way valves are low flow-resistance valves for example that described in U.S. Pat. No. 5,727,594, or other low resistance valves.

(131) In an embodiment of a shunt with both a filter **1145** and a one-way check valve **1115**, the check valve is located down stream of the filter. In this manner, if there is debris traveling in the shunt, it is trapped in the filter before it reaches the check valve. Many check valve configurations include a sealing member that seals against a housing that contains a flow lumen. Debris may have the potential to be trapped between the sealing member and the housing, thus compromising the ability of the valve to seal against backwards pressure.

(132) The controller **1130** communicates with components of the system **100** including the flow control assembly **125** to enable manual and/or automatic regulation and/or monitoring of the retrograde flow through the components of the system **100** (including, for example, the shunt **120**, the arterial access device **110**, the venous return device **115** and the flow control assembly **125**). For example, a user can actuate one or more actuators on the controller **1130** to manually control the components of the flow control assembly **125**. Manual controls can include switches or dials or similar components located directly on the controller **1130** or components located remote from the controller **1130** such as a foot pedal or similar device. The controller **1130** can also automatically control the components of the system **100** without requiring input from the user. In an embodiment,

the user can program software in the controller **1130** to enable such automatic control. The controller **1130** can control actuation of the mechanical portions of the flow control assembly **125**. The controller **1130** can include circuitry or programming that interprets signals generated by sensors **1135/1140** such that the controller **1130** can control actuation of the flow control assembly **125** in response to such signals generated by the sensors.

(133) The representation of the controller **1130** in FIG. **11** is merely exemplary. It should be appreciated that the controller **1130** can vary in appearance and structure. The controller **1130** is shown in FIG. **11** as being integrated in a single housing. This permits the user to control the flow control assembly **125** from a single location. It should be appreciated that any of the components of the controller **1130** can be separated into separate housings. Further, FIG. **11** shows the controller **1130** and flow control assembly **125** as separate housings. It should be appreciated that the controller **1130** and flow control regulator **125** can be integrated into a single housing or can be divided into multiple housings or components.

(134) Flow State Indicator(s)

(135) The controller **1130** can include one or more indicators that provides a visual and/or audio signal to the user regarding the state of the retrograde flow. An audio indication advantageously reminds the user of a flow state without requiring the user to visually check the flow controller **1130**. The indicator(s) can include a speaker **1150** and/or a light **1155** or any other means for communicating the state of retrograde flow to the user. The controller **1130** can communicate with one or more sensors of the system to control activation of the indicator. Or, activation of the indicator can be tied directly to the user actuating one of the flow control actuators **1165**. The indicator need not be a speaker or a light. The indicator could simply be a button or switch that visually indicates the state of the retrograde flow. For example, the button being in a certain state (such as a pressed or down state) may be a visual indication that the retrograde flow is in a high state. Or, a switch or dial pointing toward a particular labeled flow state may be a visual indication that the retrograde flow is in the labeled state.

(136) The indicator can provide a signal indicative of one or more states of the retrograde flow. In an embodiment, the indicator identifies only two discrete states: a state of “high” flow rate and a state of “low” flow rate. In another embodiment, the indicator identifies more than two flow rates, including a “high” flow rate, a “medium” flow rate, and a “low” rate. The indicator can be configured to identify any quantity of discrete states of the retrograde flow or it can identify a graduated signal that corresponds to the state of the retrograde flow. In this regard, the indicator can be a digital or analog meter **1160** that indicates a value of the retrograde flow rate, such as in ml/min or any other units.

(137) In an embodiment, the indicator is configured to indicate to the user whether the retrograde flow rate is in a state of “high” flow rate or a “low” flow rate. For example, the indicator may illuminate in a first manner (e.g., level of brightness) and/or emit a first audio signal when the flow rate is high and then change to a second manner of illumination and/or emit a second audio signal when the flow rate is low. Or, the indicator may illuminate and/or emit an audio signal only when the flow rate is high, or only when the flow rate is low. Given that some patients may be intolerant of a high flow rate or intolerant of a high flow rate beyond an extended period of time, it can be desirable that the indicator provide notification to the user when the flow rate is in the high state. This would serve as a fail safe feature.

(138) In another embodiment, the indicator provides a signal (audio and/or visual) when the flow rate changes state, such as when the flow rate changes from high to low and/or vice-versa. In another embodiment, the indicator provides a signal when no retrograde flow is present, such as when the shunt **120** is blocked or one of the stopcocks in the shunt **120** is closed.

(139) Flow Rate Actuators

(140) The controller **1130** can include one or more actuators that the user can press, switch, manipulate, or otherwise actuate to regulate the retrograde flow rate and/or to monitor the flow

rate. For example, the controller **1130** can include a flow control actuator **1165** (such as one or more buttons, knobs, dials, switches, etc.) that the user can actuate to cause the controller to selectively vary an aspect of the reverse flow. For example, in the illustrated embodiment, the flow control actuator **1165** is a knob that can be turned to various discrete positions each of which corresponds to the controller **1130** causing the system **100** to achieve a particular retrograde flow state. The states include, for example, (a) OFF; (b) LO-FLOW; (c) HI-FLOW; and (d) ASPIRATE. It should be appreciated that the foregoing states are merely exemplary and that different states or combinations of states can be used. The controller **1130** achieves the various retrograde flow states by interacting with one or more components of the system, including the sensor(s), valve(s), variable resistance component, and/or pump(s). It should be appreciated that the controller **1130** can also include circuitry and software that regulates the retrograde flow rate and/or monitors the flow rate such that the user wouldn't need to actively actuate the controller **1130**.

(141) The OFF state corresponds to a state where there is no retrograde blood flow through the shunt **120**. When the user sets the flow control actuator **1165** to OFF, the controller **1130** causes the retrograde flow to cease, such as by shutting off valves or closing a stop cock in the shunt **120**. The LO-FLOW and HI-FLOW states correspond to a low retrograde flow rate and a high retrograde flow rate, respectively. When the user sets the flow control actuator **1165** to LO-FLOW or HI-FLOW, the controller **1130** interacts with components of the flow control regulator **125** including pump(s) **1110**, valve(s) **1115** and/or variable resistance component **1125** to increase or decrease the flow rate accordingly. Finally, the ASPIRATE state corresponds to opening the circuit to a suction source, for example a vacutainer or suction unit, if active retrograde flow is desired.

(142) The system can be used to vary the blood flow between various states including an active state, a passive state, an aspiration state, and an off state. The active state corresponds to the system using a means that actively drives retrograde blood flow. Such active means can include, for example, a pump, syringe, vacuum source, etc. The passive state corresponds to when retrograde blood flow is driven by the perfusion stump pressures of the ECA and ICA and possibly the venous pressure. The aspiration state corresponds to the system using a suction source, for example a vacutainer or suction unit, to drive retrograde blood flow. The off state corresponds to the system having zero retrograde blood flow such as the result of closing a stopcock or valve. The low and high flow rates can be either passive or active flow states. In an embodiment, the particular value (such as in ml/min) of either the low flow rate and/or the high flow rate can be predetermined and/or pre-programmed into the controller such that the user does not actually set or input the value. Rather, the user simply selects "high flow" and/or "low flow" (such as by pressing an actuator such as a button on the controller **1130**) and the controller **1130** interacts with one or more of the components of the flow control assembly **125** to cause the flow rate to achieve the predetermined high or low flow rate value. In another embodiment, the user sets or inputs a value for low flow rate and/or high flow rate such as into the controller. In another embodiment, the low flow rate and/or high flow rate is not actually set. Rather, external data (such as data from the anatomical data sensor **1140**) is used as the basis for affects the flow rate.

(143) The flow control actuator **1165** can be multiple actuators, for example one actuator, such as a button or switch, to switch state from LO-FLOW to HI-FLOW and another to close the flow loop to OFF, for example during a contrast injection where the contrast is directed antegrade into the carotid artery. In an embodiment, the flow control actuator **1165** can include multiple actuators. For example, one actuator can be operated to switch flow rate from low to high, another actuator can be operated to temporarily stop flow, and a third actuator (such as a stopcock) can be operated for aspiration using a syringe. In another example, one actuator is operated to switch to LO-FLOW and another actuator is operated to switch to HI-FLOW. Or, the flow control actuator **1165** can include multiple actuators to switch states from LO-FLOW to HI-FLOW and additional actuators for fine-tuning flow rate within the high flow state and low flow state. Upon switching between LO-FLOW and HI-FLOW, these additional actuators can be used to fine-tune the flow rates within those states.

Thus, it should be appreciated that within each state (i.e. high flow state and low flow states) a variety of flow rates can be dialed in and fine-tuned. A wide variety of actuators can be used to achieve control over the state of flow.

(144) The controller **1130** or individual components of the controller **1130** can be located at various positions relative to the patient and/or relative to the other components of the system **100**. For example, the flow control actuator **1165** can be located near the hemostasis valve where any interventional tools are introduced into the patient in order to facilitate access to the flow control actuator **1165** during introduction of the tools. The location may vary, for example, based on whether a transfemoral or a transcarotid approach is used, as shown in FIGS. **1A-C**. The controller **1130** can have a wireless connection to the remainder of the system **100** and/or a wired connection of adjustable length to permit remote control of the system **100**. The controller **1130** can have a wireless connection with the flow control regulator **125** and/or a wired connection of adjustable length to permit remote control of the flow control regulator **125**. The controller **1130** can also be integrated in the flow control regulator **125**. Where the controller **1130** is mechanically connected to the components of the flow control assembly **125**, a tether with mechanical actuation capabilities can connect the controller **1130** to one or more of the components. In an embodiment, the controller **1130** can be positioned a sufficient distance from the system **100** to permit positioning the controller **1130** outside of a radiation field when fluoroscopy is in use.

(145) The controller **1130** and any of its components can interact with other components of the system (such as the pump(s), sensor(s), shunt, etc) in various manners. For example, any of a variety of mechanical connections can be used to enable communication between the controller **1130** and the system components. Alternately, the controller **1130** can communicate electronically or magnetically with the system components. Electro-mechanical connections can also be used. The controller **1130** can be equipped with control software that enables the controller to implement control functions with the system components. The controller itself can be a mechanical, electrical or electro-mechanical device. The controller can be mechanically, pneumatically, or hydraulically actuated or electromechanically actuated (for example in the case of solenoid actuation of flow control state). The controller **1130** can include a computer, computer processor, and memory, as well as data storage capabilities.

(146) FIG. **11** shows an exemplary embodiment of a variable flow control element **1125**. In this embodiment, the flow resistance through shunt **120** may be changed by providing two or more alternative flow paths to create a low and high resistance flow path. As shown in FIG. **12A**, the flow through shunt **120** passes through a main lumen **1700** as well as secondary lumen **1705**. The secondary lumen **1705** is longer and/or has a smaller diameter than the main lumen **1700**. Thus, the secondary lumen **1705** has higher flow resistance than the main lumen **1700**. By passing the blood through both these lumens, the flow resistance will be at a minimum. Blood is able to flow through both lumens **1700** and **1705** due to the pressure drop created in the main lumen **1700** across the inlet and outlet of the secondary lumen **1705**. This has the benefit of preventing stagnant blood. As shown in FIG. **12B**, by blocking flow through the main lumen **1700** of shunt **120**, the flow is diverted entirely to the secondary lumen **1705**, thus increasing the flow resistance and reducing the blood flow rate. It will be appreciated that additional flow lumens could also be provided in parallel to allow for a three, four, or more discrete flow resistances. The shunt **120** may be equipped with a valve **1710** that controls flow to the main lumen **1700** and the secondary lumen **1705**. The valve position may be controlled by an actuator such as a button or switch on the housing of flow controller **125**. The embodiment of FIGS. **12A** and **12B** has an advantage in that this embodiment in that it maintains precise flow lumen sizes even for the lowest flow setting. The secondary flow lumen size can be configured to prevent thrombus from forming under even the lowest flow or prolonged flow conditions. In an embodiment, the inner diameter of the secondary lumen **1705** lumen is 0.063 inches or larger.

(147) In a preferred embodiment, the connectors which connect the elements of the reverse flow

system are large bore, quick-connect style connectors. For example, a male large-bore hub **680** on the Y-adaptor **660** of arterial sheath **110**, as seen in FIG. **9B**, connects to a female counterpart **1320** on the arterial side of flow shunt **120**. Similarly, a male large bore connector **1310** on the venous side of flow shunt **120** connects to a female counterpart connector **1310** on the flow line of venous sheath **115**, as seen in FIG. **10C**. The connections can be standard female and male Luer connectors or other style of tubing connectors.

(148) Sensor(s)

(149) As mentioned, the flow control assembly **125** can include or interact with one or more sensors, which communicate with the system **100** and/or communicate with the patient's anatomy. Each of the sensors can be adapted to respond to a physical stimulus (including, for example, heat, light, sound, pressure, magnetism, motion, etc.) and to transmit a resulting signal for measurement or display or for operating the controller **1130**. In an embodiment, the flow sensor **1135** interacts with the shunt **120** to sense an aspect of the flow through the shunt **120**, such as flow velocity or volumetric rate of blood flow. The flow sensor **1135** could be directly coupled to a display that directly displays the value of the volumetric flow rate or the flow velocity. Or the flow sensor **1135** could feed data to the controller **1130** for display of the volumetric flow rate or the flow velocity.

(150) The type of flow sensor **1135** can vary. The flow sensor **1135** can be a mechanical device, such as a paddle wheel, flapper valve, rolling ball, or any mechanical component that responds to the flow through the shunt **120**. Movement of the mechanical device in response to flow through the shunt **120** can serve as a visual indication of fluid flow and can also be calibrated to a scale as a visual indication of fluid flow rate. The mechanical device can be coupled to an electrical component. For example, a paddle wheel can be positioned in the shunt **120** such that fluid flow causes the paddle wheel to rotate, with greater rate of fluid flow causing a greater speed of rotation of the paddle wheel. The paddle wheel can be coupled magnetically to a Hall-effect sensor to detect the speed of rotation, which is indicative of the fluid flow rate through the shunt **120**.

(151) In an embodiment, the flow sensor **1135** is an ultrasonic or electromagnetic, or electro-optic flow meter, which allows for blood flow measurement without contacting the blood through the wall of the shunt **120**. An ultrasonic or electromagnetic flow meter can be configured such that it does not have to contact the internal lumen of the shunt **120**. In an embodiment, the flow sensor **1135** at least partially includes a Doppler flow meter, such as a Transonic flow meter, that measures fluid flow through the shunt **120**. In another embodiment, the flow sensor **1135** measures pressure differential along the flow line to determine flow. It should be appreciated that any of a wide variety of sensor types can be used including an ultrasound flow meter and transducer. Moreover, the system can include multiple sensors.

(152) The system **100** is not limited to using a flow sensor **1135** that is positioned in the shunt **120** or a sensor that interacts with the venous return device **115** or the arterial access device **110**. For example, an anatomical data sensor **1140** can communicate with or otherwise interact with the patient's anatomy such as the patient's neurological anatomy. In this manner, the anatomical data sensor **1140** can sense a measurable anatomical aspect that is directly or indirectly related to the rate of retrograde flow from the carotid artery. For example, the anatomical data sensor **1140** can measure blood flow conditions in the brain, for example the flow velocity in the middle cerebral artery, and communicate such conditions to a display and/or to the controller **1130** for adjustment of the retrograde flow rate based on predetermined criteria. In an embodiment, the anatomical data sensor **1140** comprises a transcranial Doppler ultrasonography (TCD), which is an ultrasound test that uses reflected sound waves to evaluate blood as it flows through the brain. Use of TCD results in a TCD signal that can be communicated to the controller **1130** for controlling the retrograde flow rate to achieve or maintain a desired TCD profile. The anatomical data sensor **1140** can be based on any physiological measurement, including reverse flow rate, blood flow through the middle cerebral artery, TCD signals of embolic particles, or other neuromonitoring signals.

(153) In an embodiment, the system **100** comprises a closed-loop control system. In the closed-

loop control system, one or more of the sensors (such as the flow sensor **1135** or the anatomical data sensor **1140**) senses or monitors a predetermined aspect of the system **100** or the anatomy (such as, for example, reverse flow rate and/or neuromonitoring signal). The sensor(s) feed relevant data to the controller **1130**, which continuously adjusts an aspect of the system as necessary to maintain a desired retrograde flow rate. The sensors communicate feedback on how the system **100** is operating to the controller **1130** so that the controller **1130** can translate that data and actuate the components of the flow control regulator **125** to dynamically compensate for disturbances to the retrograde flow rate. For example, the controller **1130** may include software that causes the controller **1130** to signal the components of the flow control assembly **125** to adjust the flow rate such that the flow rate is maintained at a constant state despite differing blood pressures from the patient. In this embodiment, the system **100** need not rely on the user to determine when, how long, and/or what value to set the reverse flow rate in either a high or low state. Rather, software in the controller **1130** can govern such factors. In the closed loop system, the controller **1130** can control the components of the flow control assembly **125** to establish the level or state of retrograde flow (either analog level or discreet state such as high, low, baseline, medium, etc.) based on the retrograde flow rate sensed by the sensor **1135**.

(154) In an embodiment, the anatomical data sensor **1140** (which measures a physiologic measurement in the patient) communicates a signal to the controller **1130**, which adjusts the flow rate based on the signal. For example, the physiological measurement may be based on flow velocity through the MCA, TCD signal, or some other cerebral vascular signal. In the case of the TCD signal, TCD may be used to monitor cerebral flow changes and to detect microemboli. The controller **1130** may adjust the flow rate to maintain the TCD signal within a desired profile. For example, the TCD signal may indicate the presence of microemboli ("TCD hits") and the controller **1130** can adjust the retrograde flow rate to maintain the TCD hits below a threshold value of hits. (See, Ribo, et al., "Transcranial Doppler Monitoring of Transcervical Carotid Stenting with Flow Reversal Protection: A Novel Carotid Revascularization Technique", *Stroke* 2006, 37, 2846-2849; Shekel, et al., "Experience of 500 Cases of Neurophysiological Monitoring in Carotid Endarterectomy", *Acta Neurochir*, 2007, 149:681-689, which are incorporated by reference in their entirety.

(155) In the case of the MCA flow, the controller **1130** can set the retrograde flow rate at the "maximum" flow rate that is tolerated by the patient, as assessed by perfusion to the brain. The controller **1130** can thus control the reverse flow rate to optimize the level of protection for the patient without relying on the user to intercede. In another embodiment, the feedback is based on a state of the devices in the system **100** or the interventional tools being used. For example, a sensor may notify the controller **1130** when the system **100** is in a high risk state, such as when an interventional catheter is positioned in the sheath **605**. The controller **1130** then adjusts the flow rate to compensate for such a state.

(156) The controller **1130** can be used to selectively augment the retrograde flow in a variety of manners. For example, it has been observed that greater reverse flow rates may cause a resultant greater drop in blood flow to the brain, most importantly the ipsilateral MCA, which may not be compensated enough with collateral flow from the Circle of Willis. Thus a higher reverse flow rate for an extended period of time may lead to conditions where the patient's brain is not getting enough blood flow, leading to patient intolerance as exhibited by neurologic symptoms. Studies show that MCA blood velocity less than 10 cm/sec is a threshold value below which patient is at risk for neurological blood deficit. There are other markers for monitoring adequate perfusion to the brains, such as EEG signals. However, a high flow rate may be tolerated even up to a complete stoppage of MCA flow for a short period, up to about 15 seconds to 1 minute.

(157) Thus, the controller **1130** can optimize embolic debris capture by automatically increasing the reverse flow only during limited time periods which correspond to periods of heightened risk of emboli generation during a procedure. These periods of heightened risk include the period of time

while an interventional device (such as a dilatation balloon for pre or post stenting dilatation or a stent delivery device) crosses the plaque P. Another period is during an interventional maneuver such as deployment of the stent or inflation and deflation of the balloon pre- or post-dilatation. A third period is during injection of contrast for angiographic imaging of treatment area. During lower risk periods, the controller can cause the reverse flow rate to revert to a lower, baseline level. This lower level may correspond to a low reverse flow rate in the ICA, or even slight antegrade flow in those patients with a high ECA to ICA perfusion pressure ratio.

(158) In a flow regulation system where the user manually sets the state of flow, there is risk that the user may not pay attention to the state of retrograde flow (high or low) and accidentally keep the circuit on high flow. This may then lead to adverse patient reactions. In an embodiment, as a safety mechanism, the default flow rate is the low flow rate. This serves as a fail safe measure for patient's that are intolerant of a high flow rate. In this regard, the controller **1130** can be biased toward the default rate such that the controller causes the system to revert to the low flow rate after passage of a predetermined period of time of high flow rate. The bias toward low flow rate can be achieved via electronics or software, or it can be achieved using mechanical components, or a combination thereof. In an embodiment, the flow control actuator **1165** of the controller **1130** and/or valve(s) **1115** and/or pump(s) **1110** of the flow control regulator **125** are spring loaded toward a state that achieves a low flow rate. The controller **1130** is configured such that the user may over-ride the controller **1130** such as to manually cause the system to revert to a state of low flow rate if desired.

(159) In another safety mechanism, the controller **1130** includes a timer **1170** (FIG. **11**) that keeps time with respect to how long the flow rate has been at a high flow rate. The controller **1130** can be programmed to automatically cause the system **100** to revert to a low flow rate after a predetermined time period of high flow rate, for example after 15, 30, or 60 seconds or more of high flow rate. After the controller reverts to the low flow rate, the user can initiate another predetermined period of high flow rate as desired. Moreover, the user can override the controller **1130** to cause the system **100** to move to the low flow rate (or high flow rate) as desired.

(160) In an exemplary procedure, embolic debris capture is optimized while not causing patient tolerance issues by initially setting the level of retrograde flow at a low rate, and then switching to a high rate for discreet periods of time during critical stages in the procedure. Alternately, the flow rate is initially set at a high rate, and then verifying patient tolerance to that level before proceeding with the rest of the procedure. If the patient shows signs of intolerance, the retrograde flow rate is lowered. Patient tolerance may be determined automatically by the controller based on feedback from the anatomical data sensor **1140** or it may be determined by a user based on patient observation. The adjustments to the retrograde flow rate may be performed automatically by the controller or manually by the user. Alternately, the user may monitor the flow velocity through the middle cerebral artery (MCA), for example using TCD, and then to set the maximum level of reverse flow which keeps the MCA flow velocity above the threshold level. In this situation, the entire procedure may be done without modifying the state of flow. Adjustments may be made as needed if the MCA flow velocity changes during the course of the procedure, or the patient exhibits neurologic symptoms.

Exemplary Methods of Use

(161) Referring now to FIGS. **14A-14E**, flow through the carotid artery bifurcation at different stages of the methods of the present disclosure will be described. Initially, as shown in FIG. **14A**, the distal sheath **605** of the arterial access device **110** is introduced into the common carotid artery CCA. As mentioned, entry into the common carotid artery CCA can be via a transcarotid or transfemoral approach, and can be either a direct surgical cut-down or percutaneous access. After the sheath **605** of the arterial access device **110** has been introduced into the common carotid artery CCA, the blood flow will continue in antegrade direction AG with flow from the common carotid artery entering both the internal carotid artery ICA and the external carotid artery ECA, as shown in

FIG. 14A.

(162) The venous return device **115** is then inserted into a venous return site, such as the internal jugular vein IJV (not shown in FIGS. **14A-14E**) or femoral vein. The shunt **120** is used to connect the flow lines **615** and **915** of the arterial access device **110** and the venous return device **115**, respectively (as shown in FIG. **1A**). In this manner, the shunt **120** provides a passageway for retrograde flow from the arterial access device **110** to the venous return device **115**. In another embodiment, the shunt **120** connects to an external receptacle **130** rather than to the venous return device **115**, as shown in FIG. **1C**.

(163) Once all components of the system are in place and connected, flow through the common carotid artery CCA is stopped, typically by use of a tourniquet **2105** or other external vessel occlusion device to occlude the common carotid artery CCA. In an alternative embodiment, an occlusion element **129** is located on the distal end of arterial access device **110**. Alternately, the occlusion element **129** is introduced on second occlusion device **112** separate from the distal sheath **605** of the arterial access device **110**, as shown in FIG. **2B**. The ECA may also be occluded with a separate occlusion element, either on the same device **110** or on a separate occlusion device.

(164) At that point retrograde flow RG from the external carotid artery ECA and internal carotid artery ICA will begin and will flow through the sheath **605**, the flow line **615**, the shunt **120**, and into the venous return device **115** via the flow line **915**. The flow control assembly **125** regulates the retrograde flow as described above. FIG. **14B** shows the occurrence of retrograde flow RG. While the retrograde flow is maintained, a stent delivery catheter **2110** is introduced into the sheath **605**, as shown in FIG. **14C**. The stent delivery catheter **2110** is introduced into the sheath **605** through the hemostasis valve **615** and the proximal extension **610** (not shown in FIGS. **14A-14E**) of the arterial access device **110**. The stent delivery catheter **2110** is advanced into the internal carotid artery ICA and a stent **2115** deployed at the bifurcation B, as shown in FIG. **14D**.

(165) The rate of retrograde flow can be increased during periods of higher risk for emboli generation for example while the stent delivery catheter **2110** is being introduced and optionally while the stent **2115** is being deployed. The rate of retrograde flow can be increased also during placement and expansion of balloons for dilatation prior to or after stent deployment. An atherectomy can also be performed before stenting under retrograde flow.

(166) Still further optionally, after the stent **2115** has been expanded, the bifurcation B can be flushed by cycling the retrograde flow between a low flow rate and high flow rate. The region within the carotid arteries where the stent has been deployed or other procedure performed may be flushed with blood prior to reestablishing normal blood flow. In particular, while the common carotid artery remains occluded, a balloon catheter or other occlusion element may be advanced into the internal carotid artery and deployed to fully occlude that artery. The same maneuver may also be used to perform a post-deployment stent dilatation, which is typically done currently in self-expanding stent procedures. Flow from the common carotid artery and into the external carotid artery may then be reestablished by temporarily opening the occluding means present in the artery. The resulting flow will thus be able to flush the common carotid artery which saw slow, turbulent, or stagnant flow during carotid artery occlusion into the external carotid artery. In addition, the same balloon may be positioned distally of the stent during reverse flow and forward flow then established by temporarily relieving occlusion of the common carotid artery and flushing. Thus, the flushing action occurs in the stented area to help remove loose or loosely adhering embolic debris in that region.

(167) Optionally, while flow from the common carotid artery continues and the internal carotid artery remains blocked, measures can be taken to further loosen emboli from the treated region. For example, mechanical elements may be used to clean or remove loose or loosely attached plaque or other potentially embolic debris within the stent, thrombolytic or other fluid delivery catheters may be used to clean the area, or other procedures may be performed. For example, treatment of in-stent restenosis using balloons, atherectomy, or more stents can be performed under retrograde flow. In

another example, the occlusion balloon catheter may include flow or aspiration lumens or channels which open proximal to the balloon. Saline, thrombolytics, or other fluids may be infused and/or blood and debris aspirated to or from the treated area without the need for an additional device. While the emboli thus released will flow into the external carotid artery, the external carotid artery is generally less sensitive to emboli release than the internal carotid artery. By prophylactically removing potential emboli which remain, when flow to the internal carotid artery is reestablished, the risk of emboli release is even further reduced. The emboli can also be released under retrograde flow so that the emboli flows through the shunt **120** to the venous system, a filter in the shunt **120**, or the receptacle **130**.

(168) After the bifurcation has been cleared of emboli, the occlusion element **129** or alternately the tourniquet **2105** can be released, reestablishing antegrade flow, as shown in FIG. **14E**. The sheath **605** can then be removed.

(169) A self-closing element may be deployed about the penetration in the wall of the common carotid artery prior to withdrawing the sheath **605** at the end of the procedure. Usually, the self-closing element will be deployed at or near the beginning of the procedure, but optionally, the self-closing element could be deployed as the sheath is being withdrawn, often being released from a distal end of the sheath onto the wall of the common carotid artery. Use of the self-closing element is advantageous since it affects substantially the rapid closure of the penetration in the common carotid artery as the sheath is being withdrawn. Such rapid closure can reduce or eliminate unintended blood loss either at the end of the procedure or during accidental dislodgement of the sheath. In addition, such a self-closing element may reduce the risk of arterial wall dissection during access. Further, the self-closing element may be configured to exert a frictional or other retention force on the sheath during the procedure. Such a retention force is advantageous and can reduce the chance of accidentally dislodging the sheath during the procedure. A self-closing element eliminates the need for vascular surgical closure of the artery with suture after sheath removal, reducing the need for a large surgical field and greatly reducing the surgical skill required for the procedure.

(170) The disclosed systems and methods may employ a wide variety of self-closing elements, typically being mechanical elements which include an anchor portion and a self-closing portion. The anchor portion may comprise hooks, pins, staples, clips, tine, suture, or the like, which are engaged in the exterior surface of the common carotid artery about the penetration to immobilize the self-closing element when the penetration is fully open. The self-closing element may also include a spring-like or other self-closing portion which, upon removal of the sheath, will close the anchor portion in order to draw the tissue in the arterial wall together to provide closure. Usually, the closure will be sufficient so that no further measures need be taken to close or seal the penetration. Optionally, however, it may be desirable to provide for supplemental sealing of the self-closing element after the sheath is withdrawn. For example, the self-closing element and/or the tissue tract in the region of the element can be treated with hemostatic materials, such as bioabsorbable polymers, collagen plugs, glues, sealants, clotting factors, or other clot-promoting agents. Alternatively, the tissue or self-closing element could be sealed using other sealing protocols, such as electrocautery, suturing, clipping, stapling, or the like. In another method, the self-closing element will be a self-sealing membrane or gasket material which is attached to the outer wall of the vessel with clips, glue, bands, or other means. The self-sealing membrane may have an inner opening such as a slit or cross cut, which would be normally closed against blood pressure. Any of these self-closing elements could be designed to be placed in an open surgical procedure, or deployed percutaneously.

(171) In another embodiment, carotid artery stenting may be performed after the sheath is placed and an occlusion balloon catheter deployed in the external carotid artery. The stent having a side hole or other element intended to not block the ostium of the external carotid artery may be delivered through the sheath with a guidewire or a shaft of an external carotid artery occlusion

balloon received through the side hole. Thus, as the stent is advanced, typically by a catheter being introduced over a guidewire which extends into the internal carotid artery, the presence of the catheter shaft in the side hole will ensure that the side hole becomes aligned with the ostium to the external carotid artery as the stent is being advanced. When an occlusion balloon is deployed in the external carotid artery, the side hole prevents trapping the external carotid artery occlusion balloon shaft with the stent which is a disadvantage of the other flow reversal systems. This approach also avoids “jailing” the external carotid artery, and if the stent is covered with a graft material, avoids blocking flow to the external carotid artery.

(172) In another embodiment, stents are placed which have a shape which substantially conforms to any preexisting angle between the common carotid artery and the internal carotid artery. Due to significant variation in the anatomy among patients, the bifurcation between the internal carotid artery and the external carotid artery may have a wide variety of angles and shapes. By providing a family of stents having differing geometries, or by providing individual stents which may be shaped by the physician prior to deployment, the physician may choose a stent which matches the patient's particular anatomy prior to deployment. The patient's anatomy may be determined using angiography or by other conventional means. As a still further alternative, the stent may have sections of articulation. These stents may be placed first and then articulated in situ in order to match the angle of bifurcation between a common carotid artery and internal carotid artery. Stents may be placed in the carotid arteries, where the stents have a sidewall with different density zones.

(173) In another embodiment, a stent may be placed where the stent is at least partly covered with a graft material at either or both ends. Generally, the stent will be free from graft material and the middle section of the stent which will be deployed adjacent to the ostium to the external carotid artery to allow blood flow from the common carotid artery into the external carotid artery.

(174) In another embodiment, a stent delivery system can be optimized for transcervical/transcarotid access by making them shorter and/or more rigid than systems designed for transfemoral access. These changes will improve the ability to torque and position the stent accurately during deployment. In addition, the stent delivery system can be designed to align the stent with the ostium of the external carotid artery, either by using the external carotid occlusion balloon or a separate guide wire in the external carotid artery, which is especially useful with stents with sideholes or for stents with curves, bends, or angulation where orientation is critical.

(175) In certain embodiments, the shunt is fixedly connected to the arterial access sheath and the venous return sheath so that the entire assembly of the replaceable flow assembly and sheaths may be disposable and replaceable as a unit. In other instances, the flow control assembly may be removably attached to either or both of the sheaths.

(176) In an embodiment, the user first determines whether any periods of heightened risk of emboli generation may exist during the procedure. As mentioned, some exemplary periods of heightened risk include (1) during periods when the plaque P is being crossed by a device; (2) during an interventional procedure, such as during delivery of a stent or during inflation or deflation of a balloon catheter or guidewire; (3) during injection of contrast. The foregoing are merely examples of periods of heightened risk. During such periods, the user sets the retrograde flow at a high rate for a discreet period of time. At the end of the high risk period, or if the patient exhibits any intolerance to the high flow rate, then the user reverts the flow state to baseline flow. If the system has a timer, the flow state automatically reverts to baseline flow after a set period of time. In this case, the user may re-set the flow state to high flow if the procedure is still in a period of heightened embolic risk.

(177) In another embodiment, if the patient exhibits an intolerance to the presence of retrograde flow, then retrograde flow is established only during placement of a filter in the ICA distal to the plaque P. Retrograde flow is then ceased while an interventional procedure is performed on the plaque P. Retrograde flow is then re-established while the filter is removed. In another embodiment, a filter is placed in the ICA distal of the plaque P and retrograde flow is established

while the filter is in place. This embodiment combines the use of a distal filter with retrograde flow. (178) Although embodiments of various methods and devices are described herein in detail with reference to certain versions, it should be appreciated that other versions, embodiments, methods of use, and combinations thereof are also possible. Therefore the spirit and scope of the appended claims should not be limited to the description of the embodiments contained herein.

Claims

1. A method for treating a carotid artery, comprising: positioning an arterial access device into a common carotid artery through an access location in a neck of a patient, the arterial access device comprising: a distal sheath having a lumen extending between a distal opening and a proximal opening; wherein the distal sheath defines a plurality of spaces evenly distributed and uninterrupted along at least a portion of a length of the distal sheath; and wherein the distal sheath includes at one least fenestration aligned with at least one of the spaces; occluding blood flow at an occlusion location of the common carotid artery to establish retrograde blood flow through the common carotid artery such that blood flows into the lumen of the arterial access device, wherein the occlusion location is located proximal of the distal opening; wherein the blood flows into the distal sheath via at least one of the distal opening and the at least one fenestration.
 2. The method of claim 1, wherein the distal sheath includes a removable stopper member that covers a portion of a distal section of the distal sheath such that a portion of the distal section of the distal sheath is covered by the stopper member and a portion of the distal section of the distal sheath is exposed, wherein the stopper member, when coupled to the distal sheath, limits insertion of the distal sheath into the carotid artery to the exposed portion, and further comprising: inserting no more than the exposed portion of the distal sheath into the common carotid artery.
 3. The method of claim 2, wherein the at least one fenestration is located entirely within the exposed portion of the distal sheath.
 4. The method of claim 1, wherein a zone is defined adjacent to the occlusion location and wherein the zone is a static zone.
 5. The method of claim 1, wherein a zone is defined adjacent to the occlusion location and further comprising positioning the distal sheath so that at least one fenestration is positioned in the zone.
 6. The method of claim 1, wherein occluding blood flow at an occlusion location comprises applying a vascular clamp at the occlusion location.
 7. The method of claim 1, wherein occluding blood flow at an occlusion location comprises expanding a balloon at the occlusion location.
 8. The method of claim 1, further comprising making a transcervical incision to expose a region of the common carotid artery at the access location.
 9. The method of claim 1, wherein the at least one fenestration is positioned external to the common carotid artery, and further comprising blocking the at least one fenestration positioned external to the common carotid artery to prevent leakage.
 10. The method of claim 1, further comprising placing a stent in an artery via the arterial access device.
-