

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397206
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Sugimae; Ryuichi et al.

Golf club head with improved inertia performance

Abstract

A golf club head that is capable improving on the inertia properties of a golf club head all while also improving the Center of Gravity (CG) location is disclosed herein. More specifically, the golf club head in accordance with the present invention achieves a relative low Moment of Inertia (MOI) about the Z-axis (MOI-Z) as well as a relatively low MOI about the Shaft-axis (MOI-SA), all combined with a high MOI about the X and Y-axis (MOI-X and MOI-Y).

Inventors: Sugimae; Ryuichi (San Diego, CA), Larsen; Peter (San Marcos, CA), Murphy; Stephen S. (Carlsbad, CA), Knutson; Scott A. (Escondido, CA), Golden; Charles E. (Encinitas, CA), Ashcroft; Joey (Oceanside, CA), Cleghorn; Richard L. (Oceanside, CA), Johnson; Gregory D. (Tucson, AZ), Ferguson; Gentry (San Marcos, CA), Soracco; Peter L. (Carlsbad, CA), de la Cruz; Noah (San Diego, CA), Kawaguchi; Hiroshi (Aliso Viejo, CA)

Applicant: Acushnet Company (Fairhaven, MA)

Family ID: 1000008778736

Assignee: Acushnet Company (Fairhaven, MA)

Appl. No.: 18/365048

Filed: August 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230381606 A1	Nov. 30, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 16539622 20190813 US 11027178 20210608 child-doc US 16780040

continuation-in-part parent-doc US 16219651 20181213 ABANDONED child-doc US 16539622

Publication Classification

Int. Cl.: **A63B53/08** (20150101); **A63B53/04** (20150101); **A63B53/06** (20150101); **F16B21/02** (20060101); **F16B33/00** (20060101)

U.S. Cl.:

CPC **A63B53/08** (20130101); **A63B53/06** (20130101); A63B53/0437 (20200801); A63B53/0466 (20130101); A63B2053/0491 (20130101); A63B2209/00 (20130101); F16B21/02 (20130101); F16B33/004 (20130101)

Field of Classification Search

CPC: A63B (53/08); A63B (53/06); A63B (53/0466); A63B (2053/0491); A63B (2209/00); A63B (53/0437); F16B (33/004); F16B (21/02)

USPC: 473/334-339

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6162132	12/1999	Yoneyama	N/A	N/A
6491592	12/2001	Cackett et al.	N/A	N/A
7166038	12/2006	Williams et al.	N/A	N/A
7318782	12/2007	Imamoto et al.	N/A	N/A
7344452	12/2007	Imamoto et al.	N/A	N/A
7438649	12/2007	Ezaki et al.	N/A	N/A
7497789	12/2008	Burnett et al.	N/A	N/A
7530903	12/2008	Imamoto et al.	N/A	N/A
7691008	12/2009	Oyama	N/A	N/A
7806781	12/2009	Imamoto	N/A	N/A
7850542	12/2009	Cackett et al.	N/A	N/A
8025591	12/2010	De La Cruz et al.	N/A	N/A
8100781	12/2011	Burnett et al.	N/A	N/A
8197357	12/2011	Rice et al.	N/A	N/A
8308582	12/2011	Tanimoto	N/A	N/A
8444506	12/2012	Watson et al.	N/A	N/A
8540588	12/2012	Rice	N/A	N/A
8622847	12/2013	Beach et al.	N/A	N/A
8636608	12/2013	De la Cruz et al.	N/A	N/A
8636610	12/2013	Golden et al.	N/A	N/A
8753226	12/2013	Rice et al.	N/A	N/A
8858362	12/2013	Leposky et al.	N/A	N/A
8979671	12/2014	DeMille et al.	N/A	N/A
9174096	12/2014	Sargent et al.	N/A	N/A

9192831	12/2014	Stites et al.	N/A	N/A
9205312	12/2014	Zimmerman et al.	N/A	N/A
9259627	12/2015	Myers et al.	N/A	N/A
9381410	12/2015	Golden et al.	N/A	N/A
9387373	12/2015	DeMille et al.	N/A	N/A
9427637	12/2015	Beach et al.	N/A	N/A
9440126	12/2015	Boyd	N/A	N/A
9498688	12/2015	Galvan et al.	N/A	N/A
9687700	12/2016	Honea et al.	N/A	N/A
9814954	12/2016	Westrum et al.	N/A	N/A
9868036	12/2017	Kleinert et al.	N/A	N/A
9908014	12/2017	Wester et al.	N/A	N/A
9950222	12/2017	Albertsen et al.	N/A	N/A
9968834	12/2017	Seluga et al.	N/A	N/A
9987533	12/2017	Oldknow et al.	N/A	N/A
10065094	12/2017	Wallin	N/A	N/A
10207160	12/2018	Johnson et al.	N/A	N/A
10293225	12/2018	Sargent et al.	N/A	N/A
10434380	12/2018	Kawaguchi	N/A	N/A
10603555	12/2019	Beach et al.	N/A	N/A
10617916	12/2019	Milleman et al.	N/A	N/A
10675514	12/2019	Spackman et al.	N/A	N/A
10751585	12/2019	Johnson et al.	N/A	N/A
10864413	12/2019	Stokke et al.	N/A	N/A
11027178	12/2020	Sugimae et al.	N/A	N/A
11040256	12/2020	Milleman et al.	N/A	N/A
11117026	12/2020	Stokke	N/A	N/A
11192005	12/2020	Bennett	N/A	A63B 60/02
11213730	12/2021	Sugimae et al.	N/A	N/A
11331546	12/2021	Golden	N/A	A63B 60/02
11701559	12/2022	Bennett	473/335	A63B 53/06
11752405	12/2022	Sugimae	473/334	A63B 53/0408
12115419	12/2023	Golden	N/A	A63B 60/02
2004/0092332	12/2003	Willett	N/A	N/A
2010/0075774	12/2009	Ban	N/A	N/A
2011/0224017	12/2010	Thomas et al.	N/A	N/A
2014/0004972	12/2013	Thomas et al.	N/A	N/A
2014/0038737	12/2013	Roach et al.	N/A	N/A
2015/0273293	12/2014	Akiyama et al.	N/A	N/A
2015/0297961	12/2014	Voshall et al.	N/A	N/A
2015/0360094	12/2014	Deshmukh	N/A	N/A
2017/0050091	12/2016	Shimahara et al.	N/A	N/A
2017/0136321	12/2016	Gibbs	N/A	A63B 60/02
2017/0259128	12/2016	Greensmith et al.	N/A	N/A
2020/0121999	12/2019	Sargent et al.	N/A	N/A
2020/0206589	12/2019	Parsons et al.	N/A	N/A
2021/0138323	12/2020	Harbert et al.	N/A	N/A
2021/0220709	12/2020	Johnson et al.	N/A	N/A
2021/0283473	12/2020	Stokke et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101060892	12/2006	CN	N/A
102886130	12/2012	CN	N/A
2006288882	12/2005	JP	N/A
2016-19731	12/2015	JP	N/A
10-2020-0039768	12/2019	KR	N/A

Primary Examiner: Passaniti; Sebastiano

Background/Summary

RELATED APPLICATIONS (1) The present application is a divisional of co-pending U.S. application Ser. No. 17/521,089, filed on Nov. 8, 2021, which is a divisional of U.S. application Ser. No. 16/780,040, filed on Feb. 3, 2020, which issued as U.S. Pat. No. 11,213,730 on Jan. 4, 2022, which is a continuation-in-part of U.S. application Ser. No. 16/539,622, filed on Aug. 13, 2019, which issued as U.S. Pat. No. 11,027,178 on Jun. 8, 2021, which is a continuation-in-part of U.S. application Ser. No. 16/219,651, filed on Dec. 13, 2018, the entirety of which are incorporated by reference herein.

FIELD OF THE INVENTION

(1) The present invention relates generally to a new and improved golf club having improved Moment of Inertia (MOI) characteristics, combined with an improved Center of Gravity (CG) location. More specifically, the golf club head in accordance with the present invention achieves a relative low Moment of Inertia (MOI) about the Z-axis (MOI-Z), a low MOI about the Shaft Axis (MOI-SA), all combined with a high MOI about the X and Y-axis (MOI-X and MOI-Y) and maintaining a consistently and relatively low CG location measured along a direction normal to the hosel axis along the X-Y plane (CG-B).

BACKGROUND OF THE INVENTION

(2) With the development of the modern day oversized metalwoods, the performance capabilities of these types of golf clubs have increased dramatically over their predecessor, “the persimmon wood”. One of the ways these metalwood type golf clubs have been performing better than their predecessors is in the increase in overall distance, generally attributed to the inherent elastic deformation of thin metallic metal materials used by these metalwoods. Another way the metalwood type golf clubs have been outperforming their predecessors is in the increase in overall forgiveness of the golf club head, generally attributed to the increase in the MOI of the golf club head itself.

(3) The MOI of a golf club head generally is a term used to describe the ability of an object to resist rotational movement upon impact with a secondary object. In the case of a golf club head, MOI refers to the ability of the golf club head to resist undesirable twisting upon impact with a golf ball, as such a twisting movement will generally change the face angle of the golf club head away from the intended target line, sending the golf ball away from the intended target.

(4) U.S. Pat. No. 5,354,055 to MacKeil shows one of the earliest attempts to increase the MOI of a golf club head by placing the Center of Gravity (CG) location rearward. U.S. Pat. No. 6,364,788 to Helmstetter et al. shows the utilization of weighting members to help control the MOI of the golf club head. Both of these patents refer to the MOI-y of the golf club head, as it relates to the ability of the golf club head to stay stable when encountering an off-center impact in the heel and toe direction.

(5) U.S. Pat. No. 7,850,542 to Cackett et al. illustrates a further development in the MOI research wherein a recognition of the different axis of rotation of the different MOI's. (Alternatively known as Ixx, Iyy, and Izz instead of MOI-X, MOI-Y, and MOI-Z) Despite the recognition and identification of the difference in MOI values, U.S. Pat. No. 7,850,542 only focuses its attention on Ixx and Iyy (adapted and changes to the current reference nomenclature), without any recognition of the importance of the last MOI number, Izz, nor MOI-SA and how they can affect the performance of the golf club.

(6) Despite the above, none of the references recognizes the importance of the MOI of the golf club head horizontally forward and aft of the face (MOI-Z), and ways to design a golf club that takes advantage of the performance characteristics of golf club with more optimal MOI-Z values along with the minimized MOI-SA values. Moreover, a closer investigation of the MOI-Z values will yield CG locations that will work in conjunction with the above MOI-Z values to create more performance. Hence, it can be seen from the above there is a need for more research and a design of a golf club capable of achieving better performance by investigating the importance of MOI-Z and MOI-SA as well as the CG location and designing a golf club head.

BRIEF SUMMARY OF THE INVENTION

(7) One aspect of the present invention is a golf club comprised of a golf club head, a shaft coupled to the golf club head at a first end of the shaft and a grip coupled to the shaft at a second end of the shaft, where the golf club head comprises of a frontal portion further comprising a striking face that defines a face center, located at a forward portion of the golf club head; a rear portion located aft of the striking face; and at least one weighting member located near a central portion of the golf club head in a heel to toe orientation, substantially in line with and behind the face center; wherein an x-axis is defined as a horizontal axis tangent to a geometric center of said striking face with the positive direction towards a heel of said golf club head, a y-axis is a vertical axis orthogonal to said x-axis with a positive direction towards a crown of said golf club head, and a z-axis being orthogonal to both said x-axis and said y-axis with a positive direction towards a frontal portion of said golf club head, and wherein said golf club head has a MOI-Y to MOI-Z ratio of greater than about 1.50.

(8) In another aspect of the present invention is a golf club head comprising of a golf club head comprising of a frontal portion further comprising a striking face that defines a face center, located at a forward portion of the golf club head, a rear portion located aft of the striking face, and at least one weighting member located near a central portion of the golf club head in a heel to toe orientation, substantially in line with and behind the face center; wherein an x-axis is defined as a horizontal axis tangent to a geometric center of said striking face with the positive direction towards a heel of said golf club head, a y-axis is a vertical axis orthogonal to said x-axis with a positive direction towards a crown of said golf club head, and a z-axis being orthogonal to both said x-axis and said y-axis with a positive direction towards a frontal portion of said golf club head, and wherein said golf club head has a MOI-X, MOI-Z, and CG-Z numbers that satisfies the equation

$$MOI-X/MOI-Z \geq (6.7501 * CG-Z) - 99.30.$$

(9) Another aspect of the present invention is a golf club head comprising a striking face, a crown return, a sole return and a central body member that are formed of metal. The central body member is located near the central portion of said golf club head in a heel to toe orientation, substantially in line along the z-axis, and extends from the crown return and the sole return to a back edge of said golf club.

(10) Preferably, the golf club head is further comprised of a heel body member made of a non-metallic material and coupled to a heel side of the central body member and a toe body member made of a non-metallic material and coupled to a toe side of the central body member. The golf club head can further include two weight members, one forward near the striking face and one aft near the back edge. In one embodiment, a wall member is coupled to a crown portion of the central

body member and a sole portion of the central body member and extends between the first and second weight members.

(11) In another embodiment, the golf club head is further comprised of a central support member that is comprised of a plurality of angled strut members extending from the crown to the sole between the two weight members. Preferably, a first angled strut member extends from a crown portion of the central body member to the sole and a second angled strut member extends from a sole portion of the central body member to the crown, and the first and second angled strut members cross each other. More preferably, the first and second angled strut members extend at an angle of between 15 degrees and 75 degrees from both the y-axis and the z-axis. The golf club head can further comprise a third angled strut member that extends from a crown portion of the central body member to the sole and a fourth angled strut member that extends from a sole portion of the central body member to the crown, and the third and fourth angled strut members cross each other. The third and fourth angled strut members also extend at an angle of between 15 degrees and 75 degrees from both the y-axis and the z-axis, and preferably, the third angled strut member is coupled to the first angled strut member and the fourth angled strut member is coupled to the second angled strut member. The golf club can further comprise a vertical strut member extending vertically, substantially parallel to the y-axis, between the fourth angled strut member and the third angled strut member.

(12) These and other features, aspects and advantages of the present invention will become better understood with reference to the following drawings, description and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The foregoing and other features and advantages of the invention will be apparent from the following description of the invention as illustrated in the accompanying drawings. The accompanying drawings, which are incorporated herein and form a part of the specification, further serve to explain the principles of the invention and to enable a person skilled in the pertinent art to make and use the invention.

(2) FIG. 1 of the accompanying drawings shows a perspective view of a golf club head in accordance with an exemplary embodiment of the present invention;

(3) FIG. 2 of the accompanying drawings shows a top view of a golf club head in accordance with an exemplary embodiment of the present invention;

(4) FIG. 3 of the accompanying drawings shows a frontal view of a golf club head in accordance with an exemplary embodiment of the present invention;

(5) FIG. 4 of the accompanying drawings shows a plot of MOI-Z vs MOI-Y numbers for the current invention, compared to prior art golf club heads;

(6) FIG. 5 of the accompanying drawings shows a plot of MOI-Z vs MOI-Shaft Axis numbers for the current invention, compared to prior art golf club heads;

(7) FIG. 6 of the accompanying drawings shows a plot of MOI-Y vs MOI-Shaft Axis numbers for the current invention, compared to prior art golf club heads;

(8) FIG. 7 of the accompanying drawings shows a plot of MOI-X vs MOI-Shaft Axis numbers for the current invention, compared to prior art golf club heads;

(9) FIG. 8 of the accompanying drawings shows a plot of MOI-Z vs CG-B/Face Width numbers for the current invention, compared to prior art golf club heads;

(10) FIG. 9 of the accompanying drawings shows a plot of MOI-Z vs CG-B/Head Width numbers for the current invention, compared to prior art golf club heads;

(11) FIG. 10 of the accompanying drawings shows a plot of MOI-X/MOI-Z vs CG-Z numbers for the current invention, compared to prior art golf club heads;

(12) FIG. 11 of the accompanying drawings shows a plot of $\text{MOI-Y}/\text{MOI-Z}$ vs CG-Z numbers for the current invention, compared to prior art golf club heads;

(13) FIG. 12 of the accompanying drawings shows a plot of $(\text{MOI-X}+\text{MOI-Y})/\text{MOI-Z}$ vs CG-Z numbers for the current invention, compared to prior art golf club heads;

(14) FIG. 13 of the accompanying drawings shows an exploded sole perspective view of a golf club head in accordance with an exemplary embodiment of the present invention;

(15) FIG. 14 of the accompanying drawings shows a horizontal cross-sectional view of a golf club head in accordance with an exemplary embodiment of the present invention;

(16) FIG. 15 of the accompanying drawings shows a vertical cross-sectional view of a golf club head in accordance with an exemplary embodiment of the present invention;

(17) FIG. 16 of the accompany drawings shows a perspective view of a golf club head in accordance with an alternative embodiment of the present invention;

(18) FIG. 17 of the accompanying drawings shows a top view of a golf club head in accordance with an alternative embodiment of the present invention;

(19) FIG. 18 of the accompanying drawings shows a frontal view of a golf club head in accordance with an alternative embodiment of the present invention;

(20) FIG. 19 of the accompanying drawings shows a horizontal cross-sectional view of a golf club head in accordance with an alternative embodiment of the present invention;

(21) FIG. 20 of the accompanying drawings shows a vertical cross-sectional view of a golf club head in accordance with an alternative embodiment of the present invention;

(22) FIG. 21 of the accompanying drawings shows a top view of a golf club head in accordance with an alternative embodiment of the present invention;

(23) FIG. 22 of the accompanying drawings shows a frontal view of a golf club head in accordance with an alternative embodiment of the present invention;

(24) FIG. 23 of the accompanying drawings shows a top view of a body portion of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. 21;

(25) FIG. 24 of the accompanying drawings shows a bottom view of a body portion of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. 21;

(26) FIG. 25 of the accompanying drawings shows a vertical side view of a body portion of a golf club head in accordance with an alternative embodiment of the present invention;

(27) FIG. 26 of the accompanying drawings shows a vertical side view of a body portion of a golf club head in accordance with an alternative embodiment of the present invention;

(28) FIG. 27 of the accompanying drawings shows a top view of a golf club head in accordance with an alternative embodiment of the present invention;

(29) FIG. 28 of the accompanying drawings shows a top view of a body portion of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. 27;

(30) FIG. 29 of the accompanying drawings shows a bottom view of a body portion of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. 27;

(31) FIG. 30 of the accompanying drawings shows a top view of a body portion of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. 27;

(32) FIG. 31 of the accompanying drawings shows a bottom view of a body portion of the golf club head in accordance with an alternative embodiment of the present invention;

(33) FIG. 32 of the accompanying drawings shows a cross-sectional view of a first weight member shown in FIG. 31;

(34) FIG. 33 of the accompanying drawings shows a cross-sectional view of a second weight member shown in FIG. 31;

(35) FIG. 34 of the accompanying drawings shows a bottom perspective view of another embodiment of a golf club head in accordance with the present invention;

(36) FIG. 35 of the accompanying drawings shows a cross-sectional view of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. 34;

(37) FIG. **36** of the accompanying drawings shows a close-up, cross-sectional view of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. **34**;
(38) FIG. **37** of the accompanying drawings shows a close-up, cross-sectional view of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. **34**;
(39) FIG. **38** of the accompanying drawings shows a bottom perspective view of another embodiment of a golf club head rear portion in accordance with the present invention;
(40) FIG. **39** of the accompanying drawings shows a frontal view of the golf club head rear portion in accordance with an alternative embodiment of the present invention shown in FIG. **38**;
(41) FIG. **40** of the accompanying drawings shows a close-up, cross-sectional view of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. **38**;
(42) FIG. **41** of the accompanying drawings shows a close-up, cross-sectional view of the golf club head in accordance with an alternative embodiment of the present invention shown in FIG. **38**; and
(43) FIG. **42** of the accompanying drawings shows a golf club head, a shaft and a grip.

DETAILED DESCRIPTION OF THE INVENTION

(44) The following detailed description describes the best currently contemplated modes of carrying out the invention. The description is not to be taken in a limiting sense, but is made merely for the purpose of illustrating the general principles of the invention, since the scope of the invention is best defined by the appended claims.

(45) Various inventive features are described below and each can be used independently of one another or in combination with other features. However, any single inventive feature may not address any or all of the problems discussed above or may only address one of the problems discussed above. Further, one or more of the problems discussed above may not be fully addressed by any of the features described below.

(46) Before beginning the discussion on the current inventive golf club head and its performance criteria, it is worthwhile to note here that the discussion below will be based on a coordinate system **101** and axis of measurement that is critical to the proper valuation of the performance numbers. Hence, it is important to recognize here that although the specific names given for the measurements below are important to the understanding of the current invention, the naming nomenclature should not be viewed in vacuum. Rather, the importance is the numbers presented below needs to be taken in context with how the coordinate system relates to the golf club head itself. In order to provide sufficient information to avoid any ambiguity, each of the figures provided below referencing a golf club head will all be accompanied by a coordinate system that is all consistent with one another.

(47) Pursuant to the above, and to establish the reference coordinate system for the subsequent discussion, FIG. **1** of the accompanying drawings shows the coordinate system **101** that will be used to define the various measurement and performance figures for the current invention. The x-axis used by the current discussion refers to the axis that is horizontal to the striking face from a heel to toe direction. The y-axis used by the current discussion refers to the vertical axis through the club in a crown to sole direction. The t-axis used by the current discussion refers to the horizontal axis that is horizontal front to back in a forward and rear direction. Alternatively speaking, it can be the x-axis is defined as a horizontal axis tangent to a geometric center of the striking face with the positive direction towards a heel of the golf club head, a y-axis is a vertical axis orthogonal to the x-axis with a positive direction towards a top of the golf club head, and a z-axis being orthogonal to both the x-axis and the y-axis with a positive direction towards a front of the golf club head. The x-y-z coordinate system described above shall be the same for all subsequent discussions.

(48) FIG. **1** of the accompanying drawings shows a perspective view of a golf club head **100** in accordance with an embodiment of the present invention. In this perspective view shown in FIG. **1**, the golf club head **100** may not look very different than other golf club heads, but the subsequent figures and discussion will show that the internal components and the material properties of this

golf club head **100** allows it to achieve unique performance properties consistent with the present invention. What FIG. **1** does show is a location of a face center **102** of the frontal portion **104** of the golf club head **100** that contains a striking face insert. The face center, as shown here and referred to by the current invention, relates to the geometric center of the striking face portion of said golf club head **100** measured by the USGA provided face center template as it would be commonly known to a person of ordinary skill in the golf club art. Attached to the rear of the frontal portion **104** is a rear portion **106**, which makes up the back end of the golf club head **100**.

(49) In this embodiment of the present invention, the frontal portion **104** may generally be made out of a steel type material having a density of between about 7.75 g/cc and about 8.00 g/cc, allowing a significant portion of the mass of the golf club head **100** to be concentrated at a frontal bottom region of the golf club head **100**. The rear portion **106** of the golf club head **100** in this embodiment of the present invention may generally be made out of the standard titanium material having a density of between about 4.00 g/cc and about 5.00 g/cc, allowing the rear portion **106** of the golf club head **100** to be relatively lightweight. However, it should be noted that in alternative embodiments of the present invention, the frontal portion **104** may also be made out of a standard titanium material such as Ti-6-4, Ti-8-1-1, beta-titanium, or any other type of titanium material without departing from the scope and content of the present invention.

(50) In order to illustrate more specific features of the golf club head **100**, FIGS. **2** and **3** of the accompanying drawings is provided to give more insight into some of the specific inherent characteristics of the golf club head **200** that will be important to determine its improved performance. First off, FIG. **2** of the accompanying drawings, in addition to illustrating a golf club head **200** with a frontal portion **204** and a rear portion **206**, also shows a Center of Gravity (CG) **210** location along the x-z plane on the coordinate system **201**. Although the details of the CG location will be discussed in more detail with respect to the inertia properties of the golf club head **200**, the general direction of the current inventive golf club head **200** is to have a CG location that is strategically located at a distance back from the frontal portion of the golf club head **200** to yield the most advantageous results.

(51) More specifically, in the current invention, the CG location rearward from the striking face, identified here as CG-Z is generally between about 25 mm to about 40 mm, more preferably between about 26 mm and about 38 mm, and most preferably between about 27 mm and about 36 mm, all measured rearward from the face center **202** along the Z axis shown by the coordinate system **201**. In addition to illustrating the CG-Z **212** numbers, an alternative measurement method is provided to measure how far back the CG **210** is located within the club head **200**. In this alternative method, the CG **210** is measured from the shaft axis **215**, and this measurement is illustrated as CG-C **214** is generally measured to be between about 10 mm to about 25 mm, more preferably between about 12 mm to about 23 mm, and most preferably between about 14 mm to about 21 mm, all measured rearward from the shaft axis **215** along the Z axis shown by the coordinate system **201**.

(52) It should be noted that the strategic location of the CG **210** location rearward along the Z axis, irrespective of whether it is measured from the face center **202** or the shaft axis **215**, is critical to the proper functionality of the current inventive golf club head **200**. If the CG **210** location is too far forward, the golf club head **200** can result in a low MOI-X and MOI-Y as well as too low of a backspin when contacting a golf ball to yield desirable results. However, in the alternative, if the CG **210** location is too far rearward, the golf club head **200** can produce too much spin to yield desirable results. Hence, it can be seen that the criticality of the CG location rearward of along the Z axis is a fine balance of a very specific range of numbers that can severely hinder the performance of the golf club head **200** if it deviates from the ranges articulated above.

(53) FIG. **3** of the accompanying drawings shows another important CG **210** measurement that is important to the proper functionality of the current invention. More specifically, FIG. **3**, in addition to illustrating all of the basic components of the golf club head **200** as previously shown, now

introduces another measurement of the CG **210** location from the shaft axis **215** along an x-y plane shown by coordinate system **301**. More specifically, FIG. **3** shows a CG **210** measurement that is perpendicular to the shaft axis **215** along this x-y plane away from the actual shaft axis **215** itself, called CG-B for the purpose of this application. The CG-B of the golf club head **210** may generally be between about 32 mm and about 39 mm, more preferably between about 33 mm and about 38 mm, and most preferably about 35 mm.

(54) In addition to illustrating the very important CG-B measurement of the golf club head, FIG. **3** of the accompanying drawings also shows measurements W1 and W2, indicative of the width of the golf club head **200** itself and the width of the face of the golf club head **200** respectively. In this embodiment of the present invention, the width of the golf club head W1 may generally be between about 130 mm to and about 140 mm, more preferably between about 132 mm to about 138 mm, and most preferably about 136 mm. The width of the face W2 may generally be between about 95 mm and about 105 mm, more preferably between about 97 mm and about 103 mm, and most preferably about 100 mm.

(55) Now that the CG location of the golf club head **200** has been defined, the other important features associated with the present invention relates to the Moment of Inertia (MOI) of the golf club head **200**. The MOI of a golf club head generally depicts the ability of the golf club head to resist twisting when it impacts an object at a location that is not aligned with the CG location previously discussed. More specifically, the MOI of a golf club head relates to the ability of the golf club head to resist twisting relative to the CG location. As is well known in the art, the MOI of the golf club head **200** may generally be broken down to three unique components, relating to the ability of the golf club head **200** to resist rotation along three different axes with the origin of the three axes being coincident with the CG location of the golf club head. The three axes of rotation for which the MOI is generally referred coincides with the coordinate system **101**, **201**, and **301** (shown in FIG. **1**, FIG. **2**, and FIG. **3** respectively), where MOI-X is measured about the X axis passing through the CG location, MOI-Y is measured about the Y axis passing through the CG location, and MOI-Z is measured about the Z axis passing through the CG location.

(56) As the previously discussion already hinted, the current inventive golf club head **200** may generally have a high value for the MOI about the X and Y axis, while maintaining a low MOI about the Z axis. More specifically, the current inventive golf club head **200** may generally have a MOI about the X axis (MOI-X) that is greater than about 300 kg-mm.sup.2, more preferably greater than about 310 kg-mm.sup.2, and most preferably greater than about 320 kg-mm.sup.2 without departing from the scope and content of the present invention. As for MOI about the Y axis (MOI-Y), the present inventive golf club head **200** may generally have a MOI about the Y axis that is greater than about 400 kg-mm.sup.2, more preferably greater than about 410 kg-mm.sup.2, and most preferably greater than about 420 kg-mm.sup.2 all without departing from the scope and content of the present invention.

(57) While the large MOI number about the X and Y axis discussed previously are not necessarily new in the world of golf club head **200** designs, the ability to maintain those number while decreasing the MOI about the Z axis (MOI-Z) and holding the MOI about the Shaft axis (MOI-SA) to a minimum is what makes the present invention. While the majority of the golf industry are focusing their attention so intently on the ability of the golf club head **200** to offer forgiveness on off center hits by trying to increase the MOI-Y to astronomical numbers, they have failed to recognize the ability of the golf club head **200** to offer more club head speed and more ball speed by decreasing the MOI about the Z axis (MOI-Z) in concert with the minimization of MOI about the Shaft axis (MOI-SA). The present invention focuses its attention on that very specific unrecognized characteristic, and has developed a golf club head **200** design to take advantage and maximize the performance of the golf club head **200** by focusing on the MOI about the Z axis. More specifically, a golf club head **200** in accordance with the present invention may generally have a MOI about a Z axis that is less than about 268 kg-mm.sup.2, more preferably less than about

260 kg-mm.sup.2, and most preferably less than about 250 kg-mm.sup.2. Additionally, the golf club head **200** may generally have a MOI about a Shaft axis that is less than about 850 kg-mm.sup.2.

(58) It should be noted here that the low MOI-Z numbers mentioned above cannot by itself accurately depict and describe the current invention; as old school golf club heads with much smaller footprint may inherently have a low MOI-Z number, combined with a low MOI-X and MOI-Y number. Hence, it is important to recognize here that the present invention is predicated on the interrelationship between the different numbers achieved by the MOI-X and MOI-Y numbers as it relates to MOI-Z and MOI-SA, in combination with the CG location articulated above.

(59) In order to capture the essence of the present invention, a ratio can be created between the MOI-X, MOI-Y, and MOI-Z to help provide one way to quantify this relationship. In one first example, a MOI-X to MOI-Z Ratio can be created to help quantify the current golf club head **200** as illustrated by Eq. (1) below. In one exemplary embodiment of the present invention, the MOI-X to MOI-Z Ratio is greater than about 1.10, more preferably greater than about 1.20, and most preferably greater than about 1.28.

(60)
$$\text{MOI-X to MOI-Z Ratio} = \frac{\text{MOI-X}}{\text{MOI-Z}} \quad \text{Eq. (1)}$$

(61) Similarly, a comparable ratio can be established called a MOI-Y to MOI-Z Ratio to quantify the current golf club head **200** as illustrate by Eq. (2) below. In one exemplary embodiment of the present invention, the MOI-Y to MOI-Z ratio is greater than about 1.50, more preferably greater than about 1.57, and most preferably greater than about 1.68.

(62)
$$\text{MOI-Y to MOI-Z Ratio} = \frac{\text{MOI-Y}}{\text{MOI-Z}} \quad \text{Eq. (2)}$$

(63) As it can be seen from the relationship established by the Eqs (1) and (2) above, the present invention relates to a specific relationship between the MOI of the golf club head **200** with an extra focus on minimizing the MOI-Z about the Z axis while maintaining a high MOI-Y. In order to further illustrate this, a graphical representation of the relationship is provided as FIG. 4.

(64) FIG. 4 of the accompanying drawings shows a plot of various data points of various golf club head and their respective MOI-Z numbers as well as their MOI-Y number. In FIG. 4 the X-axis represents the MOI-Y while the Y-axis represents the MOI-Z. The data points shown in FIG. 4 have been separated into circular dots and asterisks. The circular dots are representative of the data of “prior art” golf club heads, whereas the asterisk data points represent the current invention.

(65) A closer examination of the prior art data points will show that none of the golf club heads in the prior art are capable of achieving a MOI-Z number of lower than 268 kg-mm.sup.2, for all modern-day golf club heads that have a MOI-Y of greater than 420 kg-mm.sup.2. However, an even closer examination of the graph of FIG. 4 will show that as the MOI-Y numbers of the golf club heads exceeds 500 kg-mm.sup.2, an additional relationship can be established to quantify the ability of the present invention to achieve the optimal MOI-Z to MOI-Y relationship. In fact, that relationship is shown in FIG. 4 as $Y \leq 0.47x + 33$. Combining the two conditions articulated above can result in another unique way to quantify the present invention whereas, for golf club heads having a MOI-Y of between 420 kg-mm² and 500 kg-mm.sup.2, the golf club head generally has a MOI-Z of less than about 268 kg-mm.sup.2; however, for golf club heads having a MOI-Y of greater than 500 kg-mm.sup.2, the golf club head may have a MOI-Z that satisfies Eq. (3) below:

$$\text{MOI-Z} \leq (0.47 * \text{MOI-Y}) + 33 \quad \text{Eq. (3)}$$

(66) Alternatively speaking, it can be said that in one embodiment of the present invention, the golf club head **200** may have a MOI-Z that satisfies the relationship $\text{MOI-Z} \leq (0.47 * \text{MOI-Y}) + 33$ if the MOI-Y number is greater than 500 kg-mm.sup.2, and a MOI-Z that is less than 268 kg-mm.sup.2 if the MOI-Y number is between 420 kg-mm² and 500 kg-mm.sup.2.

(67) FIG. 5 of the accompanying drawing introduces another MOI value relating to a golf club head not previously discussed named MOI-Shaft Axis (MOI-SA). The MOI of a golf club head as it relates to the shaft axis is defined as the ability of the golf club head to resist twisting upon

impact with a golf ball at a location that is not aligned with the shaft axis. A golf club head in accordance with the present invention may generally have a MOI-SA of less than about 850 kg-mm.sup.2, more preferably less than about 800 kg-mm.sup.2, and most preferably less than about 750 kg-mm.sup.2. The relationship between the MOI-SA and MOI-Z is highlighted in FIG. 5 and is important to the present invention. FIG. 5 of the accompanying drawings shows that irrespective of the MOI-SA numbers, all of the prior art golf club heads have a MOI-Z of greater than about 268 kg-mm.sup.2, while all of the current inventive golf club heads have a MOI-Z of less than about 268 kg-mm.sup.2.

(68) FIG. 6 of the accompanying drawings establishes a graphical relationship between the MOI-Y of the golf club head with the newly introduced MOI-SA. As a closer examination of the graph shown in FIG. 6 will show, the current invention is capable of achieving a higher than average MOI-Y, all while keeping a relatively small MOI-SA. Similar to previous plots, the circular points on the plot will refer to prior art golf club heads, while the asterisks will refer to the current invention. Hence, it can be seen that the present invention occupies a previously unachieved space delineated by an equation $Y \geq 0.52x + 147$, which when put into context with the variables used in this plot, yields Eq. (4) below:

$$MOI-Y \geq (0.52 * MOI-SA) + 147 \quad \text{Eq. (4)}$$

(69) FIG. 7 of the accompanying drawings establishes a graphical relationship between the MOI-X of the golf club head with now a familiar MOI-SA. As a closer examination of the graph shown in FIG. 7 will show, the current invention is capable of achieving a higher than average MOI-X, all while keeping a relatively small MOI-SA. Hence, it can be seen that the present invention occupies a previously unachieved space delineated by an equation $Y \geq 0.40x + 50$, which when put into context with the variables used in this plot, yields Eq. (5) below:

$$MOI-X \geq (0.40 * MOI-SA) + 50 \quad \text{Eq. (5)}$$

(70) FIG. 8 of the accompanying drawings establishes a graphical relationship between the MOI-Z of the golf club head with a ratio of CG-B/Face Width. Both the measurement for CG-B and Face Width can be found in FIG. 3 of the accompanying drawings as well as the accompanying discussion as set forth above. The CG-B measurement is explicitly shown in FIG. 3, while the Face Width referred to by the chart in FIG. 8 is shown as W2. A closer examination of the graph shown in FIG. 8 will show that the current invention is capable of achieving a lower MOI-Z, while keeping the CG-B/Face Width number fairly consistent above 0.4. CG-B/Face Width is indicative of the location of the center of gravity while keeping a moderately sized face golf club head.

(71) In the chart shown in FIG. 8, it can be seen that the present invention occupies a previously unachieved space delineated by an equation $Y \leq 1000x - 150$, which when put into context with the variable used in this plot, yields Eq. (6) below:

$$MOI-Z \leq (1000 * \frac{CG-B}{FaceWidth}) - 150 \quad \text{Eq. (6)}$$

(73) FIG. 9 of the accompanying drawings establishes a graphical relationship between the MOI-Z of the golf club head with a ratio of CG-B/Head Width. Both the measurement for CG-B and Head Width can be found in FIG. 3 of the accompanying drawings as well as the accompanying discussion above. The CG-B measurement is explicitly shown in FIG. 3, while the Head Width referred to by the chart in FIG. 9 is shown as W1. A closer examination of the graph shown in FIG. 9 will show that the current invention is capable of achieving a lower MOI-Z, while keeping the CG-B/Head Width number fairly consistent above 0.34. CG-B/Head Width is indicative of the location of the center of gravity while keeping a moderately sized head width of the golf club head.

(74) In the chart shown in FIG. 9, it can be seen that the present invention occupies a previously unachieved space delineated by a MOI-Z number that is lower than 320 kg-mm.sup.2 combined with a CG-B/Head Width number that is greater than about 0.34.

(75) FIG. 10 of the accompanying drawings establishes another graphical relationship of the performance of a golf club in accordance with an embodiment of the present invention. More

specifically, FIG. 10 of the accompanying drawings shows a relationship between MOI-X/MOI-Z and CG-Z. (MOI-X is used interchangeably with Ixx, MOI-Y is used interchangeably with Iyy, and finally MOI-Z is used interchangeably with Izz) The definition and measurement for CG-Z of a golf club head can be found in the earlier discussion relating to FIG. 2 of the accompanying drawings, while the background information establishing MOI-X and MOI-Z have already been discussed previously. Although the selection of the plot for the X and Y axis may appear random initially to a person not versed in golf club design, but a closer examination will reveal that the relationship created here is absolutely critical to the proper performance of the present invention. On the Y axis of the plot shown in FIG. 10, a ratio between MOI-X and MOI-Z is created here. This ratio created illustrates the ability of the current inventive golf club head to maximize the value of one variable (MOI-X) while minimizing the value of another variable (MOI-Z); which resonates with the theme of the present invention. The CG-Z used in the X axis of the plot shown in FIG. 10 is indicative of the CG location of the golf club head rearward from the front of the golf club head, and it is desirable to maintain that in the range described above.

(76) A further examination of the plot shown in FIG. 10 will show that the present invention occupies a portion of the graph that was previously unachieved. This portion of the graph is delineated from other prior art data points by an equation $Y \geq 6.7501x - 99.30$, which when put into context with the variable used in this plot, yields Eq. (7) below:

$$(77) \frac{MOI-X}{MOI-Z} \geq (6.7501 * CG - Z) - 99.30 \quad \text{Eq. (7)}$$

(78) FIG. 11 of the accompanying drawings establishes another graphical relationship of a golf club in accordance with an embodiment of the present invention by creating a relationship between the MOI-Y/MOI-Z and CG-Z. The definition and measurement for CG-Z of a golf club head can be found in the earlier discussion relating to FIG. 2 of the accompanying drawings, while the background information establishing MOI-Y and MOI-Z have already been discussed previously. Similar to the previous discussion, the relationship between MOI-Y and MOI-Z is indicative of the ability of a golf club to achieve great forgiveness along the MOI-Y axis, while minimizing the MOI-Z of a golf club head to achieve a higher ball speed, as previously discussed. Similar to previous discussion, FIG. 11 of the accompanying drawings shows that the present invention is capable of achieving performance characteristics that was previously unachieved. This portion of the graph is delineated from other prior art data points by an equation $Y \geq 11.349x - 175.76$, which when put into context with the variable used in this plot, yields Eq. (8) below:

$$(79) \frac{MOI-Y}{MOI-Z} \geq (11.349 * CG - Z) - 175.76 \quad \text{Eq. (8)}$$

(80) FIG. 12 of the accompanying drawings establishes another graphical relationship of a golf club in accordance with an embodiment of the present invention by creating a relationship between the (MOI-X+MOI-Y)/MOI-Z and CG-Z. The definition and measurement for CG-Z of a golf club head can be found in the earlier discussion relating to FIG. 2 of the accompanying drawings, while the background information establishing MOI-X, MOI-Y, and MOI-Z have already been discussed previously. Similar to the previous discussion, the relationship between MOI-X, MOI-Y, and MOI-Z is indicative of the ability of a golf club to achieve great forgiveness along both the MOI-X and MOI-Y axes, while minimizing the MOI-Z of a golf club head to achieve a higher ball speed, as previously discussed. Similar to previous discussion, FIG. 12 of the accompanying drawings shows that the present invention is capable of achieving performance characteristics that was previously unachieved. This portion of the graph is delineated from other prior art data points by an equation $Y \geq 18.67x - 296.63$, which when put into context with the variable used in this plot, yields Eq. (9) below:

$$(81) \frac{(MOI-X + MOI-Y)}{MOI-Z} \geq (18.67 * CG - Z) - 296.63 \quad \text{Eq. (9)}$$

(82) FIGS. 13 through 15 show different exploded and cross-sectional view of golf club heads and their internal components that are used to achieve the performance characteristics described above. FIG. 13 shows an exploded perspective view of an exemplary design of a golf club head 1300 in

capable of achieving the performance characteristics previously discussed. The golf club head **1300** is made out of the essential components previously discussed in FIG. **1** in terms of a frontal portion **1304** and a rear portion **1306**. However, this exploded view of golf club head **1300** allows additional components to be shown in more detail. More specifically, FIG. **13** illustrates that, as often the case in a golf club head construction, the frontal portion **1304** may further be comprised out of a separate component called the striking face insert **1320** to form the striking portion of the golf club head **1300**. The rear portion **1306** of the golf club head **1300** is where it gets more interesting. In order to achieve the performance numbers above of a higher MOI-Y, a higher MOI-X, and a lower MOI-Z, a significant amount of mass is re-allocated towards the center of the golf club head away from the perimeter. In order to achieve this, the present invention utilizes four weighting members that are all comprised out of a high density material that have a higher density than the frontal portion **1304** or the rear portion **1306**. The four weighting members can be separated into a frontal sole weight **1322**, frontal internal weight **1324**, rear internal weight **1326**, and rear sole weight **1328**, and these weighting members may all generally have a material density of greater than 13 g/cc, more preferably greater than about 15 g/cc, and most preferably greater than or about 17 g/cc.

(83) It should be noted that in this exemplary embodiment of the present invention, all of the weighting members **1322**, **1324**, **1326**, and **1328** are all made out of the same material having the same heavy density discussed previously. However, in alternative embodiments of the present invention, different densities of tungsten may be used for different weighting members depending on the design criteria and desired CG location all without departing from the scope and content of the present invention.

(84) FIG. **14** of the accompanying drawings shows a cross-sectional view of a golf club head **1400** in accordance with an exemplary embodiment of the present invention. The cross-sectional view of the golf club head taken across a horizontal plane across the face of the golf club head **1400** to allow some of the relationship between the golf club head **1400** and the various weighting member **1422**, **1424**, **1426**, and **1428** to be shown more clearly. In addition to the weighting members, the cross-sectional view of the golf club head **1400** shown in FIG. **14** also allows the face center **1402** and the CG location **1410** to be re-introduced as it relates to the weighting members. It can be seen from this view that at least one weighting member is located near a central portion of the golf club head in a heel to toe direction, and substantially in line with and behind said face center.

(85) FIG. **15** of the accompanying drawings shows a cross-sectional view of a golf club head **1500** in accordance with an exemplary embodiment of the present invention taken along a vertical plane that passes through the center of the face. This cross-sectional view of the golf club head **1500** shown in FIG. **15** provides a little more information on the interworking relationship between the components. More specifically, FIG. **15** shows a striking face insert **1520** being located in the frontal portion **1504** of the golf club head **1500**. In addition to the above, FIG. **15** also shows that the frontal sole weight **1522** is located in a receptacle that is created within the frontal portion **1504**. Although not shown in this cross-sectional view in FIG. **15**, the frontal internal weight is also located in the frontal portion **1504**. Attached to the rear of the frontal portion **1504** is the rear portion **1506**. The rear portion **1506** forms the aft body portion of the golf club head **1500**, and contains the rear internal weight **1526** and the rear sole weight **1528**. These weighting members, combined with the unique materials used to form the frontal portion **1504** and the rear portion **1506**, allow the golf club head **1500** to achieve the unique performance characteristics outlined previously.

(86) FIGS. **16** through **20** show various perspective and cross-sectional views of a golf club head **1600** in accordance with an alternative embodiment of the present invention that is capable of achieving the performance goals previously mentioned. Similar to the previous embodiment illustrated by FIGS. **1-3** and **13-15**, a lot of weighting member is located near the center of the golf club head **1600** in a heel to toe orientation along the x-axis behind the face center **1602** to help

minimize the MOI-Z of the golf club head **1600**.

(87) More specifically, FIG. **16** of the accompanying drawings shows a perspective view of a golf club head **1600** in accordance with this alternative embodiment of the present invention. Although not much can be gleaned from this perspective view of the golf club head **1600**, it does lay the ground work for the subsequent discussion relating to this particular embodiment of the present invention. Finally, FIG. **16**, similar to previous figures that illustrate a golf club head, provides a coordinate system **1601** to guide the subsequent discussions.

(88) FIG. **17** of the accompanying drawings shows a top view of a golf club head **1600** in accordance with this alternative embodiment of the present invention. In this top view, a couple of familiar dimensions are reintroduced here. First and foremost, the top view of the golf club head **1600** shown in FIG. **17** allows the relationship between the face center **1602** and the CG **1610** to be shown in more detail. When measured along the Z-axis, the measurement CG-Z is shown as **1612**. The location of the CG, when referenced against the shaft axis **1615** yields another way to measure the CG location along the Z-axis called CG-C **1614**. The number ranges for the CG-Z **1612** and CG-C **1614** measurements are not much different from previous discussions, but this embodiment of the present invention provides an alternative way to achieve those targets with a slightly different construction without the need for a multi-material chassis.

(89) FIG. **18** of the accompanying drawings shows a frontal view of a golf club head **1600** in accordance with this alternative embodiment of the present invention. In this frontal view, we can see another feature utilized by the present embodiment to help achieve the performance criteria of the current invention. More specifically, FIG. **18** shows that in this embodiment of the present invention, in order to minimize the MOI-Z of the golf club head **1600**, weight is removed from the extremities of the golf club head **1600** via a reshaping of the contour at the toe portion of the golf club head **1600**. This reshaping of the contour at the toe portion of the golf club head **1600** not only removes weight from the extremities, but also tightens up the face profile of the golf club head **1600** to create a unique performing golf club head **1600**.

(90) In addition to illustrating this toe contour profiling, FIG. **18** also shows a CG-B **1616** measurement relating to the shaft axis **1615** similar to the previous discussion. Once again, the CG-B **1616** measurement range is in line as the previous discussion have mentioned, and does not deviate much from the design intent of the present invention.

(91) FIG. **19** of the accompanying drawings shows a cut open cross-sectional view of a golf club head **1600** in accordance with this alternative embodiment of the present invention taken along a horizontal plane. In this embodiment of the present invention, the overarching theme of placing the weights along the central portion of the golf club head **1600** reemerges again. More specifically, the golf club head **1600** further comprises of a frontal internal weight **1624** and a rear internal weight **1626**. These weights, however, different from prior embodiments of the present invention in that they can be made out of the same material as the body portion of the golf club head **1600** such as titanium and be directly cast into the body without departing from the scope and content of the present invention. These weighting members **1624** and **1626** may also be made out of a tungsten type material having a total weight of 20-23 grams to further improve the performance of the golf club head **1600** without departing from the scope and content of the present invention.

(92) FIG. **20** of the accompanying drawings provides another cross-sectional cut open view of the golf club head **1600** in accordance with an alternative embodiment of the present invention taken along a vertical plane. Once again, the measurements here are very similar to the discussion previously relating to prior embodiments and the CG-Z **1612** number remain within the same range as the prior discussion. This cross-sectional cut open view of the golf club head **1600** taken along this line allows the profile and geometry of the frontal internal weight **1624** and the rear internal weight **1626** to be shown more clearly and their relationship together with the body portion of the golf club head **1600**.

(93) Referring to FIGS. **21-25** the golf club head **2000** has all of the mass and inertial properties

discussed above. Further, the golf club head **2000** comprises frontal portion comprising a striking face **2001** having a face center FC, a crown on the upper portion of the golf club head **2000** and a sole on the bottom portion of the golf club head **2000**. The golf club head **2000** further comprises a crown return **2002** and a sole return **2003** as part of the frontal portion and a central body member **2004** that are all formed of metal. The central body member **2004** is located near the central portion of the golf club head **2000** in a heel-to-toe orientation, substantially in line along the z-axis as set forth above, and extends from the crown return **2002** and the sole return **2003** to a back edge **2005** of the golf club head. The golf club head **2000** is further comprised of a heel body member **2006** made of a non-metallic material and coupled to a heel side of the central body member **2004** and the crown return **2002** and the sole return **2003**. The golf club head **2000** also includes a toe body member **2007** made of a non-metallic material and coupled to a toe side of the central body member **2004** and the crown return **2002** and the sole return **2003**. The heel body member **2006** and the toe body member **2007** are essentially taco shell shaped, taco-shaped, in that they form a portion of the crown and a portion of the sole such that they have a c-shaped cross section. Preferably, as set forth above, the metal portions can be formed of a standard titanium materials such as Ti-6-4, Ti-8-1-1, beta-titanium, and others that have a specific gravity of about 4 g/cc to 5 g/cc. Alternatively, the metal portions can be formed of a standard steel materials that have a specific gravity of about 7 g/cc to 9 g/cc. The heel body member **2006** and the toe body member **2007** are preferably formed of a standard composite fiber composite laminate, chopped fiber composite generally referred to as fiber-reinforced plastic (FRP), or a composite material such as those disclosed in U.S. Publication No. 2015-0360094, which is incorporated by reference in its entirety herein. Alternatively, the heel body member **2006** and the toe body member **2007** are preferably formed of structural material having a density of less than 3.0 g/cc such as a thermoplastic material such as those disclosed in U.S. application Ser. No. 16/528,210, filed on Jul. 31, 2019, which is incorporated by reference in its entirety herein, polyetherimide (PEI), polyether ether ketone (PEEK), polyphenylene sulfide (PPS), polysulfone (PSU), polyacryletherketone (PEAK), polyetherketoneketone (PEKK) and polyvinyl chloride (PVC). The heel body member **2006** and the toe body member **2007** are preferably formed by compression molding, injection molding or 3D printing.

(94) The golf club head **2000** further has a center of gravity CG that is located a distance back from the face center, CG-z, a vertical distance up from the ground plane, CG-y, a perpendicular distance from the shaft axis, GC-SA, a horizontal distance from the face center toward the heel side, CG-x and a distance back, parallel to the z-axis, from the shaft axis, CG-C. As stated above, in the current invention, the CG-z is generally between about mm to about 40 mm, more preferably between about 26 mm and about 38 mm, and most preferably between about 27 mm and about 36 mm, all measured rearward from the face center FC along the z-axis shown by the coordinate system above. In addition to the CG-z numbers, an alternative measurement method is provided to measure how far back the CG is located within the club head **2000**. In this alternative method, the CG is measured from the shaft axis SA, and this measurement is illustrated as CG-C is generally measured to be between about 10 mm to about 30 mm, preferably 10 mm to 25 mm, more preferably between about 12 mm to about 28 mm, and more preferably 12 mm to 23 mm and most preferably between about 14 mm to about 21 mm, all measured rearward from the shaft axis SA along the z-axis direction shown by the coordinate system above.

(95) As stated above, it is important that the strategic location of the CG rearward along the z-axis be correct, irrespective of whether it is measured from the face center FC or the shaft axis SA, for the proper functionality of the current inventive golf club head **2000**. If the CG location is too far forward, the golf club head **2000** can have a low MOI-X and MOI-Y and low backspin when contacting a golf ball. However, in the alternative, if the CG location is too far rearward, the golf club head **2000** can produce too much spin to yield desirable results. Hence, the CG location rearward along the z-axis is important for the performance of the golf club head **2000**.

(96) FIG. 22 of the accompanying drawings shows another important CG measurement that is important to the proper functionality of the current invention. More specifically, FIG. 22, in addition to illustrating all of the components of the golf club head **2000** as previously discussed, shows another measurement of the CG location from the shaft axis SA along an x-y plane. More specifically, FIG. 22 shows a CG measurement that is perpendicular to the shaft axis SA along this x-y plane, called CG-B for the purpose of this application. The CG-B of the golf club head **2000** may generally be between about 32 mm and about 39 mm, more preferably between about 33 mm and about 38 mm, and most preferably about 35 mm.

(97) As shown in FIG. 22, the golf club head **2000** can further include a central support member **2010** such as wall member **2010** that is coupled to a crown portion of the central body member **2004** and a sole portion of the central body member **2004**. The wall member **2010** preferably has a thickness t that is between 0.2 mm and 5 mm, and more preferably, between about 0.4 mm and 2 mm.

(98) As shown in FIG. 23, the central body member **2004** preferably has a heel side circumferential attachment edge **2011** and a toe side circumferential attachment edge **2012** for coupling the heel body member **2006** and the toe body member **2007**, respectively, to the central body member **2004** and the crown return **2002** and the sole return **2003**. The heel side circumferential attachment edge **2011** and the toe side circumferential attachment edge **2012** preferably extend from approximate the crown return **2002** and the sole return **2003** to a back edge **2005** of the golf club head **2000**.

(99) As shown in FIG. 24, the golf club head **2000** can further include at least one weight member **2008** or **2009**, and more preferably, includes two weight members **2008** and **2009**. The first weight member **2008** is located on the sole portion of the club head, forward near the striking face **2001** and the second weight member **2009** is located on the sole portion of the club head, aft near the back edge **2005**. At least one of the weight members **2008** and **2009** may generally have a material density of greater than 13 g/cc, and more preferably greater than about 15 g/cc. The weight members **2008** and **2009** preferably have a mass of between about 0 grams and 50 grams, more preferably between about 3 grams and 35 grams and most preferably between 5 grams and 25 grams. In one embodiment of the invention, the first weight member **2008** has a mass of at least two times the mass of the second weight member **2009**. In another embodiment of the invention, the first weight member **2008** has a mass of less than half the mass of the second weight member **2009**. More preferably, the weight members **2008** and **2009** are interchangeable so that the CG can be adjusted forward and rearward to control the club head's launch and spin characteristics. Furthermore, the center of the first weight member **2008** is preferably located less than 30 mm from the striking face **2001** along the z-axis and the center of the second weight member **2009** is preferably located less than 20 mm from the back edge **2005** along the z-axis such that the interchangeable weights can have a maximum effect on the spin and launch characteristics of the club head.

(100) In one embodiment of the present invention and as shown in FIG. 25, the central support member or wall member **2010** is coupled to a crown portion of the central body member **2004** and a sole portion of the central body member **2004** and extends between the first and second weight members **2008** and **2009**. The central support member **2010** preferably has a maximum height H parallel to the y-axis and a maximum depth D parallel to the z-axis. The depth D is preferably greater than the maximum height H . Also shown in FIG. 25, the heel side circumferential attachment edge **2011** and the toe side circumferential attachment edge **2012** for coupling the heel body member **2006** and the toe body member **2007** to the central body member **2004** can include a plurality of recesses or apertures **2013** that adhesive can enter into and better lock the components together. Alternatively, the heel side circumferential attachment edge **2011** and the toe side circumferential attachment edge **2012** may have a plurality of protrusions on the outer surface to create a gap between the heel body member **2006** and the toe body member **2007** to the central body member **2004** such that an adhesive can fill the gap and create a stronger bond therebetween.

(101) In another embodiment of the present invention, the golf club head's central support member **2010** can be comprised of a plurality of strut members **2014**, **2015**, **2016**, **2017**, **2018** and **2019** that extend from the crown to the sole of the central body member **2004** between the two weight members **2008** and **2009**. Again, the central support member **2010** preferably has a maximum height H parallel to the y-axis and a maximum depth D parallel to the z-axis. The depth D is preferably greater than the maximum height H . Preferably, a first angled strut member **2014** extends from a crown portion of the central body member **2004** to the sole and a second angled strut member **2015** extends from a sole portion of the central body member **2004** to the crown, and the first and second angled strut members **2014** and **2015** preferably cross each other. Preferably, the first and second angled strut members **2014** and **2015** extend at an angle α of between 15 degrees and 75 degrees from the y-axis and an angle β of between 15 degrees and 75 degrees from the z-axis. More preferably, the first and second angled strut members **2014** and **2015** extend at an angle α of between 15 degrees and 45 degrees from the y-axis and an angle β of between 45 degrees and 75 degrees from the z-axis. The golf club head **2000** can further comprise a third angled strut member **2016** that extends from a crown portion of the central body member **2004** to the sole and a fourth angled strut member **2017** that extends from a sole portion of the central body member **2004** to the crown, and the third and fourth angled strut members cross each other. The third and fourth angled strut members also extend at angles α and β of between 15 degrees and 75 degrees from both the y-axis and the z-axis respectively. Preferably, the third angled strut member **2016** is coupled to the first angled strut member **2014** at the crown and the fourth angled strut member **2017** is coupled to the second angled strut member **2015** at the sole. Furthermore, preferably, the third angled strut member **2016** is substantially parallel to the second angled strut member **2015** and the fourth angled strut member **2017** is substantially parallel to the first angled strut member **2014**. The golf club head **2000** can further comprise a vertical strut member **2018** extending vertically, substantially parallel to the y-axis, between the first angled strut member **2014** and the second angled strut member **2015** approximate the first weight member **2008**. Even more preferably, the golf club head **2000** can further comprise a second vertical strut member **2019** extending vertically, substantially parallel to the y-axis, between the fourth angled strut member **2017** and the third angled strut member **2016** adjacent to the second weight member **2009**.

(102) The advantage of the central support member **2010**, either in the form of the wall member **2010** or the angled strut members **2014**, **2015**, **2016** and **2017** is that it prevents the crown portion of the central body member **2004** from deflecting relative to the sole portion of the central body member **2004** in the y-axis and also prevents the portions from shearing with respect to each other in the z-axis.

(103) The advantage of multiple weight members **2008** and **2009** is that the weight members can have equal mass, for example between 10 and 15 grams each, such that the CG of the club head **2000** is in a neutral position. However, the weight members **2008** and **2009** can also be comprised of a heavy weight, for example greater than 15 grams, and a light weight, for example less than 10 grams, such that the CG can be moved forward or back depending on the placement of the weights. With the heavy weight located in the aft weight member **2009**, the MOI-Y is increased and is preferably greater than about 450 kg-mm^{sup.2}. Thus, in a preferred golf club head **2000**, the MOI-Y is greater than or equal to approximately 2 times the MOI-Z. Conversely, when the heavy weight is in the forward weight member **2008**, the CG-C can be significantly decreased. For example, a preferred golf club head **2000** can have a GC-C of between 14 mm to 21 mm.

(104) The advantages of the club head **2000** discussed above can also apply to fairway woods and hybrids. In those embodiments, it is understood that the numerical values for the club properties will be lower and the metal will be generally steels and high strength steels known in the art. However, the construction of the golf club head **2000** can be easily applied to these smaller heads.

(105) Referring to FIGS. 27-29 the golf club head **2000** has all of the mass and inertial properties discussed above. Further, the golf club head **2000** comprises frontal portion comprising a variable

thickness striking face **2001** having a maximum thickness at the face center FC, a crown on the upper portion of the golf club head **2000** and a sole on the bottom portion of the golf club head **2000**. The golf club head **2000** further comprises a crown return **2002** and a sole return **2003** adjacent the striking face **2001** as discussed above and a central body member **2004** that are all formed of metal. The central body member **2004** is located near the central portion of the golf club head **2000** in a heel-to-toe orientation, substantially in line along the z-axis as set forth above, and extends from the crown return **2002** and the sole return **2003** to a back edge **2005** of the golf club head **2000**. As discussed above, the golf club head **2000** is further comprised of a heel body member **2006** made of a non-metallic material and coupled to a heel side of the central body member **2004** along the heel edge **2011** and a toe body member **2007** made of a non-metallic material is coupled to a toe side of the central body member **2004** along the toe edge **2012**. The central body member **2004** can include a plurality of protrusions **2013a** that create an adhesive filled gap and better lock the components together. The heel body member **2006** and the toe body member **2007** are essentially taco shell shaped, taco-shaped, in that they form a portion of the crown and a portion of the sole such that they have a c-shaped cross section. Preferably, as set forth above, the metal portions can be formed of a standard titanium materials such as Ti-6-4, Ti-8-1-1, beta-titanium, and others that have a specific gravity of about 4 g/cc to 5 g/cc. The heel body member **2006** and the toe body member **2007** are preferably formed of a standard composite fiber composite laminate, chopped fiber composite generally referred to as fiber-reinforced plastic (FRP), or a composite material such as those disclosed in U.S. Publication No. 2015-0360094, which is incorporated by reference in its entirety herein. Alternatively, the heel body member **2006** and the toe body member **2007** are preferably formed of a thermoplastic material such as those disclosed in U.S. application Ser. No. 16/528,210, filed on Jul. 31, 2019, which is incorporated by reference in its entirety herein, polyetherimide (PEI), polyether ether ketone (PEEK), polyphenylene sulfide (PPS), polysulfone (PSU), polyacryletherketone (PEAK), polyetherketoneketone (PEKK) and polyvinyl chloride (PVC). The heel body member **2006** and the toe body member **2007** are preferably formed by compression molding, injection molding or 3D printing.

(106) In a most preferred embodiment, the heel body member **2006** and the toe body member **2007** are preferably formed from a high crystallinity PPS, that is a PPS in which the crystallinity is greater than 40%, and more preferably, greater than about 50% as measured using differential scanning calorimetry (DSC) at a heating rate of 20° C./min. The crystallinity percentage can be calculated using the following equation:

$$\% \text{ crystallinity} = \Delta H_{\text{sub.sample}} / \Delta H_{\text{sub.reference}} \times 100$$

where: $\Delta H_{\text{sub.sample}}$ is the sample melting enthalpy with unknown crystallinity percentage and $\Delta H_{\text{sub.reference}}$ is the sample melting enthalpy with the known crystallinity. For PPS, 76.5 J/g may be utilized as the $\Delta H_{\text{sub.reference}}$.

(107) In order to increase the crystallinity level in PPS, it is recommended that the material be injection molded into molds that are at a temperature of greater than 115° C. and more particularly in a mold that is between about 125° C. and 135° C. In the most preferred embodiment, the PPS crystallinity is between about 50% and 70%. The material preferably has a uniform thickness of about 0.5 mm to about 2 mm. However, in one embodiment, the toe body member **2007** has a thickness that is less than the thickness of the heel body member **2006**. In another embodiment, the toe body member **2007** and the heel body member **2006** vary such that they are thinnest on the crown portion and thicker on the sole portion. In this embodiment, the crown portions of the toe body member **2007** and the heel body member **2006** have a thickness that is preferably between about 0.5 mm and 1 mm and the sole portions of the toe body member **2007** and the heel body member **2006** are between about 1 mm and 2 mm thick.

(108) The golf club head **2000** further has a center of gravity CG that is located a distance back from the face center, CG-z, a vertical distance up from the ground plane, CG-y, a perpendicular

distance from the shaft axis, GC-SA, a horizontal distance from the face center toward the heel side, CG-x and a distance back, parallel to the z-axis, from the shaft axis, CG-C. As stated above, in the current invention, the CG-z is generally between about 25 mm to about 40 mm, more preferably between about 26 mm and about 38 mm, and most preferably between about 27 mm and about 36 mm, all measured rearward from the face center FC along the z-axis shown by the coordinate system above. In addition to the CG-z numbers, an alternative measurement method is provided to measure how far back the CG is located within the club head **2000**. In this alternative method, the CG is measured from the shaft axis SA, and this measurement is illustrated as CG-C is generally measured to be between about 10 mm to about 25 mm, more preferably between about 12 mm to about 23 mm, and most preferably between about 14 mm to about 21 mm, all measured rearward from the shaft axis SA along the z-axis shown by the coordinate system above.

(109) As stated above, it is important that the strategic location of the CG location rearward along the z-axis be correct, irrespective of whether it is measured from the face center FC or the shaft axis SA, for the proper functionality of the current inventive golf club head **2000**. If the CG location is too far forward, the golf club head **2000** can have a low MOI-X and MOI-Y and low backspin when contacting a golf ball. However, in the alternative, if the CG location is too far rearward, the golf club head **2000** can produce too much spin to yield desirable results. Hence, the CG location rearward along the z-axis is important for the performance of the golf club head **2000**.

(110) As shown in FIGS. **29** and **31**, the weight member **2008** has less mass than weight member **2009** and is preferably made from steel (or at least a material that has a lower density than the density of weight member **2009**). The first weight member **2008** can be located on the forward portion of the sole return **2003**, near the striking face **2001** and the second weight member **2009** located on the sole portion of the golf club head **2000**, aft near the back edge **2005**. At least one of the weight members **2008** and **2009** may generally have a material density of greater than 13 g/cc, more preferably greater than about 15 g/cc, and most preferably about 17 g/cc. Preferably, at least one of the weight members **2008** and **2009** may generally have a material density of greater than 2 g/cc and less than about 9 g/cc, and most preferably between about 4 g/cc and about 8 g/cc. The weight members **2008** and **2009** preferably have a mass of between about 0 grams and 50 grams, and more preferably between about 5 grams and 25 grams. In one embodiment of the invention, the first weight member **2008** has a mass of at least two times the mass of the second weight member **2009**. In another embodiment of the invention, the first weight member **2008** has a mass of less than half the mass of the second weight member **2009**. More preferably, the weight members **2008** and **2009** are the same shape and volume such that they are interchangeable so that the CG of the golf club head **2000** can be adjusted forward and rearward to control the club head's launch and spin characteristics. Furthermore, the center of the first weight member **2008** is preferably located less than 30 mm from the striking face **2001** along the z-axis direction and the center of the second weight member **2009** is preferably located less than 20 mm from the back edge **2005** along the z-axis direction such that the interchangeable weights can have a maximum effect on the spin and launch characteristics of the club head. More preferably, the center of the first weight member **2008** is preferably located less than 25 mm from the striking face **2001** along the z-axis direction and the center of the second weight member **2009** is preferably located less than mm from the back edge **2005** along the z-axis direction.

(111) As shown in FIG. **32**, the first weight member **2008** is preferably releasably coupled to the sole return **2003** portion of the golf club head **2000** by a fastener **2020**. The first weight member **2008** may generally have a material density of greater than 4 g/cc, more preferably greater than about 7 g/cc, and most preferably between about 7 g/cc and 8 g/cc. The first weight member preferably has a light side **2021** and a heavy side **2022**. The heavy side **2022** is preferably substantially solid and as shown in FIGS. **29** and **31** is the side identified with indicia such as with a dot. In a preferred embodiment, the first weight member **2008** has a hollow portion **2023** that forms the light side **2021** of the weight member **2008**.

(112) As shown in FIGS. 33, the second weight member **2009** is also preferably releasably coupled to the sole portion of the central body member **2004** portion of the golf club head **2000** by a fastener **2025**. The second weight member **2009** may generally have a material density of greater than 13 g/cc, more preferably greater than about 15 g/cc, and most preferably greater than or equal to about 17 g/cc. The second weight member **2009** preferably has a light side **2026** and a heavy side **2027**. The heavy side **2027** is preferably substantially solid and as shown in FIGS. 29 and 31 is the side identified with indicia such as with a dot. In a preferred embodiment, the weight member **2009** has a hollow portion **2028** that forms the light side **2026** of the second weight member **2009**.

(113) More preferably, at least one or both of the weight members **2008** or **2009** are comprised of a light side **2021** and **2026** that includes a hollow portion **2023** and **2028** and a heavy side **2022** and **2027** that is substantially solid or is solid enough that the mass on the heavy side is greater than the mass on the light side. Alternatively, at least one or both of the weight members **2008** or **2009** are comprised of a light side **2021** and **2026** that includes a hollow portion **2023** and **2028** that can be filled with a material having a density of less than 4 g/cc and a heavy side **2022** and **2027** that is a hollow portion that is filled with a material having a density of greater than about 7 g/cc and more preferably greater than or equal to about 15 g/cc. As shown in FIGS. 29 and 31, the weight member **2008** has less mass than weight member **2009** and is preferably made from steel (or at least a material that has a lower density than the density of weight member **2009**). More preferably, the first weight member **2008** has a mass of about 7 g and 14 g and the second weight member has a mass of between about 15 g and 22 g. Most preferably, the first weight member **2008** and the second weight member **2009** can be interchanged in the front and aft locations as shown in FIGS. 29 and 31 to move the CG-C by approximately 1 mm to 5 mm and most preferably by about 2.5 mm to 3.5 mm. In the most preferred embodiment, the CG-C can be between about 14 mm and 21 mm when the first weight member **2008** is in the aft location adjacent the back edge **2005** and the CG-C can be between about 22 mm and 30 mm when the first weight member **2008** is in the forward position adjacent the striking face **2001**. Further, the first weight member **2008** and the second weight member **2009** preferably have approximately the same difference in mass between the light sides **2021** and **2026** and the heavy sides **2022** and **2027**. Preferably, the difference in mass between the light sides **2021** and **2026** and the heavy sides **2022** and **2027** is between about 4 g and 8 g. Thus, if one of the weight members has the heavy side toward the heel in the x-axis direction and the other has the heavy side toward the toe in the x-axis direction, the CG of the golf club head **2000** can be neutral in the x-axis direction as shown in FIG. 29. However, if the weight members have both of their heavy sides **2022** and **2027** toward the toe or the heel in the x-axis direction, the CG can be moved away from the neutral position along the x-axis direction toward the toe or heel, respectively. Preferably, the golf club head CG can be moved at least 0.5 mm toward the toe or the heel from the neutral location and more preferably, between about 0.7 mm and 1.5 mm. As shown in FIG. 31, both the first weight member **2008** and the second weight member **2009** have the heavy sides **2022** and **2027** toward the toe in the x-axis direction such that the golf club head CG is moved toward the toe by about 1 mm from the neutral position GC-n. These weight members can both be rotated about the fastener such that the CG is moved toward the heel by about 1 mm from the neutral position CG-n and 2 mm from the far toe CG position as shown in FIG. 31.

(114) FIGS. 34 through 37 show different perspective and cross-sectional views of golf club heads and their internal components that are used to achieve the performance characteristics described above. FIG. 34 shows a perspective view of an exemplary design of a golf club head **3000** that capable of achieving the performance characteristics previously discussed with respect to the embodiments in FIGS. 1-3 and 13-15 in particular. The golf club head **3000** is comprised of the essential components previously discussed in FIGS. 1 and 13 in terms of a frontal portion having a striking face **3001**, a crown return **3002** and a sole return **3003** and a rear portion **3004** comprised of an aft body. In order to achieve the performance numbers above of a higher MOI-Y, a higher MOI-X, and a lower MOI-Z, a significant amount of mass is allocated towards the center of the

golf club head away from the perimeter. In order to achieve this, the present invention utilizes two weighting members that are preferably comprised of high density materials that have a higher density than the frontal portion **3001**, **3002** and **3003** and the rear portion **3004**. Preferably, as set forth above, the frontal portion **3001**, **3002** and **3003** can be formed of a standard titanium material such as TI-6-4, Ti-8-1-1, beta-titanium, and others that have a density of about 4 g/cc to 5 g/cc. The rear portion **3004** is preferably formed of a standard composite fiber composite laminate, chopped fiber composite generally referred to as fiber-reinforced plastic (FRP), or a composite material such as those disclosed in U.S. Publication No. 2015-0360094, which is incorporated by reference in its entirety herein. Alternatively, the rear portion **3004** is preferably formed of structural material having a density of less than 3.0 g/cc such as a thermoplastic materials such as those disclosed in U.S. application Ser. No. 16/528,210, filed on Jul. 31, 2019, which is incorporated by reference in its entirety herein, polyetherimide (PEI), polyether ether ketone (PEEK), polyphenylene sulfide (PPS), poly sulfone (PSU), polyacryletherketone (PEAK), polyetherketoneketone (PEKK) and polyvinyl chloride (PVC). The rear portion **3004** is preferably formed by compression molding, injection molding or 3D printing. Additionally, the golf club head **3000** includes a sole plate member **3006** secured to an outer surface of the rear portion **3004**. In a preferred embodiment, the sole plate member **3006** is also formed from standard titanium materials such as TI-6-4, Ti-8-1-1, beta-titanium, and others that have a density of about 4 g/cc to 5 g/cc. In another preferred embodiment, the sole plate member **3006** is formed from stainless steel or similar material having a density of about 7 g/cc to 8 g/cc.

(115) The golf club head **3000** also includes weight members **3008** and **3009**. In a first embodiment, the weight members **3008** and **3009** can have equal mass, for example between 10 and 15 grams each, such that the CG of the club head **3000** is in a neutral position along the z-axis direction. However, the weight members **3008** and **3009** can also be comprised of a heavy weight, for example greater than 15 grams, and a light weight, for example less than 10 grams, such that the CG can be moved forward or back along the z-axis direction depending on the placement of the weights. With the heavy weight located in the aft weight member **3009**, the MOI-Y is increased and is preferably greater than about 450 kg-mm.sup.2. Thus, in a preferred golf club head **3000**, the MOI-Y is greater than or equal to approximately 2 times the MOI-Z. Conversely, when the heavy weight is in the forward weight member **3008**, the CG-C can be significantly decreased. For example, a preferred golf club head **3000** can have a GC-C of between 14 mm to 21 mm.

(116) Referring to FIG. 35, the golf club head **3000** further includes an internal rib member **3010** that is located in the frontal portion. The rib member **3010** is preferably located near or at the overlapping juncture of the frontal portion and the rear portion **3004**. Preferably, the depth DD of the golf club head from the leading edge LE to the back edge **3005** is between 105 mm and 125 mm, and more preferably between about 118 mm and 122 mm. The distance of the crown return DCR from the leading edge to where the crown return **3002** abuts the rear portion **3004** is preferably about 20 mm and 35 mm and more preferably between about 30 mm and 34 mm. The distance of the sole return DSR from the leading edge to where the back end of the sole return **3003** is preferably about 24 mm and 44 mm and more preferably between about 35 mm and 42 mm. The rib member **3010** is therefore preferably located a distance from the leading edge that is between the DCR and the DSR or between 20 mm and 44 mm. Most preferably, the rib member **3010** is angled such that the distance from the leading edge to the crown portion of the rib member **3010** (at the center of the crown in the heel-to-toe direction, back from the face center) DRC is less than the distance from the leading edge to the sole portion of the rib member **3010** (at the center of the sole in the heel-to-toe direction, back from the face center) DRS. More preferably, DRC is preferably between 22 mm and 33 mm and DRS is between 26 mm and 42 mm and is at least 10% greater than DRC. Thus, the rib member **3010** forms an angle α .sub.R that is between about 2° and 10° from the vertical plane at the DRC to a point on the sole at the DRS. The rib member **3010** has a rib height RH (the height of the rib member from the inner surface of the frontal portion) that also

preferably varies from the crown center to the sole center and at the heel and toe. Most preferably, the rib height RH is between about 2 mm and 8 mm and is greatest at the sole center and shortest at the heel and toe. Most preferably, the rib member **3010** has a rib height RH of about 5 mm at the sole center, 4 mm at the crown center and is 3 mm to 3.5 mm at the heel and toe.

(117) The center of the first weight member **3008** is preferably located a distance DW1 from the leading edge LE of about 15 mm to 25 mm. The center of the second weight member **3009** is preferably located a distance DW2 from the leading edge LE of about 80 mm to 115 mm.

(118) Referring to FIGS. **36** and **37**, the second weight member **3009** is shown in a close-up cross-sectional view. The second weight member **3009** is comprised of an internal weight member **3021** and an external weight member **3022** with a fastener **3020** coupling the members together to the rear portion **3004**. The first weight member **3008** preferably has a similar construction but would secure about the frontal portion on the sole return **3003**. Most preferably, the first weight member **3008** and the second weight member **3009** have similar shaped external weight members **3022** that can be interchanged. In this embodiment, the internal weight member **3021** and the external weight member also secure the sole plate member **3006** to the rear portion **3004** by having the rear portion **3004** and the sole plate member **3006** compressed between the internal weight member **3021** and the external weight member **3022**. In the weight embodiment shown in FIG. **37**, the sole plate member **3006** and the internal weight member **3021** are also threaded so that they can be coupled to the rear portion **3004** before the external weight member **3022** is couple by the fastener **3020**.

(119) Referring to FIGS. **38-41**, another embodiment of a rear portion **4004** is shown with a pinch weight member **4009** secured near the back edge **4005** that is used to achieve the performance characteristics described above. The pinch weight member **4009** is similar to the second weight member **3009** discussed above. The pinch weight member **4009** is comprised of an internal weight member **4021** and an external weight member **4022** with a fastener **4020** coupling the members together to compress the rear portion **4004**. A first weight member, not shown, preferably has a similar construction, but would secure about a frontal portion, also not shown. In the weight embodiment shown in FIG. **41**, the sole portion **4012** is compressed between the internal weight member **4021** and a weight retaining pocket **4023** which are also threaded so that they can be coupled to the rear portion **4004** before the external weight member **4022** is coupled to the weight retaining pocket **4023** by the fastener **4020**. The exterior surface of the weight retaining pocket **4023** is cylindrical with treads and the interior surface is preferably hexagonal or other polygon and matches the shape of the exterior weight member **4022** such that the exterior weight member **4022** cannot rotate in the weight retaining pocket **4023**.

(120) In a preferred embodiment, the rear portion **4004** is formed from a crown portion **4011** and a sole portion **4012** that can be coupled by a joint connector **4013**. The crown portion **4011** and the sole portion **4012** are preferably injection molded separately and then coupled by the joint connector **4013**. The materials for the crown portion **4011** and the sole portion **4012** are preferably the same and the material for the joint connector is preferably the same or is at least compatible such that it easily joins to the crown portion **4011** and the sole portion **4012**.

(121) In a most preferred embodiment, the rear portion **4004** is preferably formed from a high crystallinity PPS, that is a PPS in which the crystallinity is greater than 40%, and more preferably, greater than about 50% as measured using differential scanning calorimetry (DSC) at a heating rate of 20° C./min. In order to increase the crystallinity level in PPS, it is recommended that the material be injection molded into molds that are at a temperature of greater than 115° C. and more particularly in a mold that is between about 125° C. and 135° C. In the most preferred embodiment, the PPS crystallinity is between about 50% and 70%. Preferably, the PPS can be formed without any filler or can contain a filler such as glass filler. In the glass filler PPS embodiment, the PPS preferably has greater than about 20% glass filler, more preferably between about 20% and 50% and most preferably between about 30% and 50%. The material preferably has a uniform thickness of about 0.5 mm to about 2 mm. However, in one embodiment, the heel side **4007** has a thickness

that is less than the thickness of the toe side **4006**. In another embodiment, the thickness varies such that it is thinnest on the crown portion **4011** and thicker on the sole portion **4012**. In this embodiment, the crown portion **4011** has a thickness that is preferably between about 0.5 mm and 1 mm and the sole portion **4012** thickness is between about 1 mm and 2 mm.

(122) FIG. **42** shows a golf club head **12** attached to a first end of a shaft **14** and a grip **16** attached to a second end of the shaft **14**.

(123) Other than in the operating example, or unless otherwise expressly specified, all of the numerical ranges, amounts, values and percentages such as those for amounts of materials, moment of inertias, center of gravity locations, loft, draft angles, various performance ratios, and others in the aforementioned portions of the specification may be read as if prefaced by the word “about” even though the term “about” may not expressly appear in the value, amount, or range.

Accordingly, unless indicated to the contrary, the numerical parameters set forth in the above specification and attached claims are approximations that may vary depending upon the desired properties sought to be obtained by the present invention. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques.

(124) Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the invention are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains certain errors necessarily resulting from the standard deviation found in their respective testing measurements. Furthermore, when numerical ranges of varying scope are set forth herein, it is contemplated that any combination of these values inclusive of the recited values may be used.

(125) It should be understood, of course, that the foregoing relates to exemplary embodiments of the present invention and that modifications may be made without departing from the spirit and scope of the invention as set forth in the following claims.

Claims

1. A golf club comprised of a golf club head, a shaft having a shaft axis coupled to the golf club head at a first end of the shaft and a grip coupled to the shaft at a second end of the shaft, wherein the golf club head comprises: a frontal portion comprised of metal and comprising a striking face having a face center located at a forward portion of said golf club head, a crown return extending from a striking face top portion and a sole return extending from a striking face bottom portion; a thermoplastic rear portion located aft of said striking face comprising a crown at an upper portion of said golf club that is coupled to the crown return and a sole on a bottom portion of said golf club that is coupled to the sole return; and wherein an x-axis is defined as a horizontal axis tangent to said face center with a positive x direction towards a heel of said golf club head, a y-axis is a vertical axis orthogonal to said x-axis with a positive y direction towards said crown of said golf club head, and a z-axis being orthogonal to both said x-axis and said y-axis with a positive z direction extending forward, a first weighting member located near a central portion of said golf club head in a heel-to-toe orientation, substantially in line with a vertical plane containing the z-axis with said face center, wherein the first weighting member is secured to the sole and comprises an internal weight member and a weight retaining pocket threaded to the internal weight member such that the internal weight member and the weight retaining pocket compresses the sole therebetween and a fastener couples an exterior weight member to the weight retaining pocket; and a second weighting member located near the central portion of said golf club head in the heel-to-toe orientation, substantially in line with the vertical plane containing the z-axis with said face center coupled to the sole return via a second fastener; wherein said golf club head has a moment of inertia about said y-axis (MOI-Y) passing through a center of gravity (CG) of said golf club head,

said golf club head has a moment of inertia about said z-axis (MOI-Z) passing through said CG, and said golf club head has a moment of inertia about said x-axis (MOI-X) passing through said CG; and wherein said golf club head has a MOI-Y to MOI-Z ratio of greater than about 1.5.

2. The golf club of claim 1, wherein said golf club head has a MOI-Y to MOI-Z ratio of greater than about 1.57.

3. The golf club of claim 2, wherein said golf club head has a MOI-Y to MOI-Z ratio of equal to or greater than about 2.

4. The golf club of claim 1, wherein the golf club head has a CG-C, being a distance the CG is back, parallel to the z-axis, from the shaft axis, of between 14 mm to 21 mm.

5. The golf club of claim 1, wherein said golf club head has a MOI-X to MOI-Z ratio of greater than about 1.10.

6. The golf club of claim 5, wherein said golf club head has a MOI-X to MOI-Z ratio of greater than about 1.20.

7. The golf club of claim 6, wherein said golf club head has a MOI-X to MOI-Z ratio of greater than about 1.28.

8. The golf club of claim 1, wherein said first weighting member and said second weighting member are interchangeable to move the CG of the golf club head between a forward position and an aft position along a direction parallel to the z-axis.

9. The golf club of claim 8, wherein the first weighting member is greater than 15 grams and the second weighting member is less than 10 grams.

10. The golf club of claim 8, wherein the second weighting member is greater than 15 grams and the first weighting member is less than 10 grams.

11. A golf club comprised of a golf club head, a shaft having a shaft axis coupled to the golf club head at a first end of the shaft and a grip coupled to the shaft at a second end of the shaft, wherein the golf club head comprises: a frontal portion comprised of metal and comprising a striking face having a face center located at a forward portion of said golf club head, a crown return extending from a striking face top portion and a sole return extending from a striking face bottom portion; a rear portion comprising a thermoplastic material selected from the group consisting of polyetherimide, polyether ether ketone, polyphenylene sulfide, polysulfone, polyacryletherketone, polyetherketoneketone and polyvinyl chloride, located aft of said striking face comprising a crown at an upper portion of said golf club that is coupled to the crown return and a sole on a bottom portion of said golf club that is coupled to the sole return; and wherein an x-axis is defined as a horizontal axis tangent to said face center with a positive x direction towards a heel of said golf club head, a y-axis is a vertical axis orthogonal to said x-axis with a positive y direction towards said crown of said golf club head, and a z-axis being orthogonal to both said x-axis and said y-axis with a positive z direction extending forward, a first weighting member located near a central portion of said golf club head in a heel-to-toe orientation, substantially in line with a vertical plane containing the z-axis with said face center, wherein the first weighting member is secured to the sole and comprises an internal weight member and a weight retaining pocket threaded to the internal weight member such that the internal weight member and the weight retaining pocket compresses the sole therebetween and a fastener couples an exterior weight member to the weight retaining pocket; and a second weighting member located near the central portion of said golf club head in the heel-to-toe orientation, substantially in line with the vertical plane containing the z-axis with said face center coupled to the sole return via a second fastener; wherein said golf club head has a moment of inertia about said y-axis (MOI-Y) passing through a center of gravity (CG) of said golf club head, said golf club head has a moment of inertia about said z-axis (MOI-Z) passing through said CG, and said golf club head has a moment of inertia about said x-axis (MOI-X) passing through said CG; and wherein said golf club head has a MOI-Y to MOI-Z ratio of greater than about 1.5.
