

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397825
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Lee; Myung Su et al.

Autonomous driving safety system for sharing risk-based operation design domain and method thereof

Abstract

An autonomous driving safety system for sharing a risk-based operation design domain includes an autonomous driving system configured to control a vehicle driving unit according to information detected by a sensor unit to perform autonomous driving, in which the autonomous driving system includes an operation design domain update unit configured to evaluate a risk of at least one of a static operation design domain and a dynamic operation design domain recognized by the sensor unit while driving to update the operation design domain.

Inventors: Lee; Myung Su (Daegu, KR), Kim; Tae Hyeong (Daegu, KR), Kim; Bong Seob (Daegu, KR), Lim; Tae Ho (Daegu, KR), Yun; Kyung Su (Daegu, KR)

Applicant: KIAPI (Korea Intelligent Automotive Parts Promotion Institute) (Daegu, KR)

Family ID: 1000008778812

Assignee: KIAPI (KOREA INTELLIGENT AUTOMOTIVE PARTS PROMOTION INSTITUTE) (Daegu, KR)

Appl. No.: 18/203176

Filed: May 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240157971 A1	May. 16, 2024

Foreign Application Priority Data

KR	10-2022-0148668	Nov. 09, 2022
----	-----------------	---------------

Publication Classification

Int. Cl.: B60W60/00 (20200101)

U.S. Cl.:

CPC **B60W60/0015** (20200201); B60W2552/05 (20200201); B60W2552/10 (20200201); B60W2552/30 (20200201); B60W2552/40 (20200201); B60W2554/20 (20200201); B60W2554/40 (20200201); B60W2554/4029 (20200201); B60W2554/804 (20200201); B60W2555/20 (20200201); B60W2555/60 (20200201); B60W2556/10 (20200201); B60W2556/45 (20200201)

Field of Classification Search

CPC: B60W (60/0015); B60W (2552/05); B60W (2552/10); B60W (2552/30); B60W (2552/40); B60W (2554/20); B60W (2554/40); B60W (2554/4029); B60W (2554/804); B60W (2555/20); B60W (2555/60); B60W (2556/10); B60W (2556/45); G08G (1/096716); G08G (1/096783); G08G (1/0116); G08G (1/0129); G08G (1/0133); G08G (1/0141); G08G (1/096725); G08G (1/096741); G08G (1/096775); G08G (1/0112)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0223788	12/2020	Garcia et al.	N/A	N/A
2022/0161816	12/2021	Gyllenhammar	N/A	G06V 20/56
2022/0289252	12/2021	Liu et al.	N/A	N/A
2023/0140569	12/2022	Foster	701/400	B60W 60/0017
2023/0264719	12/2022	Yang	701/23	B60W 60/0015

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
114407915	12/2021	CN	N/A
4 050 583	12/2021	EP	N/A
2018-207154	12/2017	JP	N/A
2021-068132	12/2020	JP	N/A
2022-164696	12/2021	JP	N/A
0201900124120	12/2017	KR	N/A
20200010654	12/2017	KR	N/A
10-2019-0124120	12/2018	KR	N/A
10-2020-0010654	12/2019	KR	N/A
10-2020-0101517	12/2019	KR	N/A
20220067874	12/2019	KR	N/A
20220100128	12/2020	KR	N/A
10-2022-0067874	12/2021	KR	N/A
10-2022-0100128	12/2021	KR	N/A
WO 2020/257642	12/2019	WO	N/A
WO 2021/252174	12/2020	WO	N/A
WO 2022/054712	12/2021	WO	N/A

OTHER PUBLICATIONS

Yoo Su Jung, Apr. 11, 2018, English Machine Translation_KR 2019-0124120 provided by Patent Translate by EPO and Google (Year: 2018). cited by examiner

Mok Yeonkweon, Jan. 7, 2021, English Machine Translation_KR 2022-0100128 provided by Patent Translate by EPO and Google (Year: 2021). cited by examiner

Yun Ilsoo, Nov. 18, 2020, English Machine Translation_KR 2022-0067874 provided by Patent Translate by EPO and Google (Year: 2020). cited by examiner

Chung Sung Mun, Jun. 29, 2018, English Machine Translation_KR 2020-0010654 provided by Patent Translate by EPO and Google (Year: 2018). cited by examiner

European Search Report For EP23179382.9 issued on Apr. 11, 2024 from European patent office in a counterpart European patent application. cited by applicant

Office action issued on Feb. 7, 2023 from Korean Patent Office in a counterpart Korean Patent Application No. 10-2022-0148668 (English translation is also submitted herewith.). cited by applicant

Office action issued on Jul. 30, 2024 from Japan Intellectual Property Office in a counterpart Japanese Patent Application No. 2023-096321 (English translation is also submitted herewith.). cited by applicant

Office action issued on Jan. 21, 2025 from Japan Intellectual Property Office in a counterpart Japanese Patent Application No. 2023-096321 (English translation is also submitted herewith.). cited by applicant

Office action issued on Jun. 20, 2025 from Japan Intellectual Property Office in a counterpart Japanese Patent Application No. 2023-096321 (English translation is also submitted herewith.). cited by applicant

Primary Examiner: Redhead, Jr.; Ashley L

Attorney, Agent or Firm: The PL Law Group, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION AND CLAIM OF PRIORITY

(1) This application claims the benefit under 35 USC § 119 of Korean Patent Application No. 10-2022-0148668, filed on Nov. 9, 2022, in the Korean Intellectual Property Office, the entire disclosure of which is incorporated herein by reference for all purposes.

BACKGROUND

1. Field

(2) The present disclosure relates to an autonomous driving safety system for sharing a risk-based operation design domain and a method thereof capable of designing a risk-based operation design domain and sharing the designed operation design domain through an edge infrastructure.

2. Description of Related Art

(3) According to Ministry of Land, Infrastructure and Transport “Level 4 autonomous vehicle production safety guidelines” defines an operation design domain (ODD) as an operation domain (road, weather, traffic, etc.) in which a function of an autonomous driving system may be performed normally and safely, and recommends to clearly present the operation design domain related to a safe operation of autonomous driving system.

(4) In addition, the above safety guideline clearly presents the operation design domain and at the same time, presents status information of the system when it is out of the operation design domain,

and includes a road type, a geographical range, a weather environment, a speed range, and other constraints in the operation design domain.

(5) In addition, according to NHTSA's Automated driving systems: A Vision for Safety 2.0 in the United States, each autonomous driving system (ADS) recommends to define and document an ODD for testing or deployment to be used on public roads.

(6) In addition, the operation design domain (ODD) should describe specific conditions under which the given ADS or function is intended to operate, and the ADS should be able to operate safely within the designed ODD.

(7) However, the operation design domain (ODD) recommends designing the operation design domain (ODD) to secure autonomous driving operation and functional safety based on real roads, but is a part requiring complementary settings such as classification for each layer and definition of detailed attribute values for the operation design domain (ODD).

(8) In addition, an autonomous driving operation on a real road may be divided into a static operation design domain (static ODD) and a dynamic operation design domain (dynamic ODD). For example, width and lanes of roads, signs, and structures may be regarded as characteristics of static (static ODD) characteristics, and objects (people, vehicles, etc.) and a weather environment may be regarded as dynamic (dynamic ODD) characteristics.

(9) The dynamic and static characteristics of the operation design domain (ODD) require updating and complementing initially designed ODD design according to a passage of time (changes in ODD characteristics according to day and night, structural deformation over time, etc.) and changes in traffic (traffic volume, unexpected objects, etc.).

(10) However, in the related art, the lack of update of the operation design domain (ODD) or subsequent complementation after the update has become a factor that reduces safety.

(11) In addition, since the operation design domain (ODD) has different design conditions and response strategies for each vehicle, there is a cumbersome problem of having to changing characteristics of different operation design domains (ODDs).

SUMMARY

(12) The present disclosure has been derived to solve the above conventional problems, and an aspect of the present disclosure provides an autonomous driving safety system for sharing a risk-based operation design domain and a method thereof capable of securing autonomous driving safety by complementing different operation design domains (ODDs) for each autonomous vehicle using a method of calculating a risk of an operation design domain (ODD) and vehicle-to-vehicle communication technology.

(13) The present disclosure may include the following embodiments in order to achieve one or more of the above aspects.

(14) According to an embodiment of the present disclosure, there may be provided an autonomous driving safety system for sharing a risk-based operation design domain including: an autonomous driving system **110** configured to control a vehicle driving unit **140** according to information detected by a sensor unit **120** to perform autonomous driving, in which the autonomous driving system **110** includes an operation design domain (ODD) update unit **111** configured to evaluate a risk of at least one of a static operation design domain and a dynamic operation design domain recognized by the sensor unit **120** while driving to update the operation design domain (ODD).

(15) The autonomous driving system may transmit the updated operation design domain (ODD) to at least one of a roadside unit, other autonomous vehicles, and a control server, and share the updated operation design domain (ODD).

(16) The autonomous driving system may include: a layer-specific attribute information DB configured to layer the operation design domains into a plurality of layers and stores attributes for each layer and weights set for each attribute; a risk calculation module configured to calculate risks for each layer by applying the weight of the attributes stored in the layer-specific attribute information DB according to the recognized operation design domain, and calculates a final risk by

summing the risks for each layer; and an update module configured to update the risk calculated by the risk calculation module to the operation design domain.

(17) The autonomous driving system may be classified into: a road geometry layer that is classified into an operation design domain (ODD) of a road structure, a road type, a road shape and form, and a shape, type, and condition of a road surface; a social infrastructure layer that is classified into the operation design domain of a traffic signal and structure; a temporary restricted area layer that is classified into an unexpected situation caused by a traffic accident, a construction section, and an emergency stop vehicle, and an operation design domain of a protected zone; an object layer that is classified into an operation design domain of a static object, a dynamic object, and an unexpected object on and around a road; an environmental condition layer that is classified into an operation design domain of season, weather (climate), and a light source; and a connectivity (communication) layer that is classified into an operation design domain of communication and control.

(18) The temporary restricted area layer may have an attribute set as at least one of a distance between start and end points of the protected zone and the autonomous vehicle, a type of protected zone, a distance between the autonomous vehicle and an unexpected section, left and right lane positions between the unexpected sections from the autonomous vehicle, a relative position of the unexpected section from autonomous vehicle, and a type of the unexpected section.

(19) In addition, the operation design domain of a type of the road structure may have an attribute set as an accident rate and fatality, and the accident rate and fatality may be weighted differently depending on a degree of death and injury.

(20) In addition, the operation design domain of the road shape may have an attribute set as at least one of a lane width, the total number of lanes on a road, a lane number on which the autonomous vehicle **100** is driving, a radius of curvature of a road, and a road design speed.

(21) In addition, the operation design domain of the road surface may have an attribute set as at least one of a road surface material type, a road surface friction coefficient (μ), a damage type, road surface damage severity (high, medium, low), and a distance between the autonomous vehicle and a road surface damage section.

(22) In the above embodiment, a risk of the operation design domain of the type of the road structure may be calculated according to Equation below.

$$(23) \text{ Risk} = \frac{\text{fatalaccident} \times 1 + \text{seriousaccident} \times 0.7 + \text{minoraccident} \times 0.3}{\text{numberoftrafficaccidents}}$$

(24) In Equation above, a weight of 1 may be set for a fatal accident, a weight of 0.7 may be set for a serious accident, and a weight of 0.3 may be set for a minor accident.

(25) The operation design domain of the weather may set a cloud ratio, a wind speed, precipitation, snowfall, a visibility range as an attribute, the cloud ratio may be set as a ratio occupied by clouds in sunny and cloudy conditions, and wind, rain, and snow may be classified and set into multiple categories based on the amount, and fog may be classified into multiple types based on the visibility range.

(26) The object layer may be classified into an operation design domain of a vehicle, a pedestrian, and an animal, the operation design domain of the vehicle may have an attribute set as at least one of left/right lane positions of a target vehicle from the autonomous vehicle, a surrounding position of the target vehicle from the autonomous vehicle, an absolute speed (X and Y axes), a relative speed (X and Y axes) from the autonomous vehicle, a distance (X and Y axes), a travel angle (direction), detection coordinates, and a type of a vehicle, and the operation design domain of the pedestrian and animal may have an attribute set as at least one of the relative speed, absolute speed, distance, travel angle, detection coordinates, and type from the autonomous vehicle.

(27) In the above embodiment, a risk of the operation design domain of the road shape may be calculated by Equation below.

$$\text{Risk of road shape} = \text{AMF.sub.curve radius} \times \text{AMF.sub.longitudinal slope}$$

(28) The curve radius may be a curve radius of a road, and the longitudinal slope is a longitudinal

slope of a road.

(29) According to another embodiment of the present disclosure, there may be provided an autonomous driving safety system for sharing a risk-based operation design domain including: a control server configured to collect an operation design domain (ODD) from a plurality of autonomous vehicles and roadside units in real time, in which the control server may transmit an operation design domain (ODD) including risk to the plurality of autonomous vehicles and roadside units to update the operation design domain.

(30) The control server may receive the risk-based operation design domain from the autonomous vehicle, and compare and evaluate the collected operation design domain to transmit the updated operation design domain to the autonomous vehicle in which the risk is missing or erroneous.

(31) The control server may include: an information collection unit configured to collect an operation design domain (ODD) and road and surrounding situation information from the plurality of roadside units and autonomous vehicles; an operation design domain design unit configured to model an operation design domain including at least one of a static operation design domain and a dynamic operation design domain collected from the autonomous vehicle; and a server communication unit configured to transmit the operation design domain (ODD) modeled by the operation design domain design unit to the plurality of autonomous vehicles and roadside units.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a block diagram schematically illustrating an autonomous driving safety system for sharing a risk-based operation design domain and a method thereof according to the present disclosure.

(2) FIG. 2 is a block diagram of an autonomous vehicle in the present disclosure.

(3) FIG. 3 is a block diagram illustrating an operation design domain update unit.

(4) FIG. 4 is a block diagram illustrating a control server.

(5) FIG. 5 is a block diagram illustrating an operation design domain design unit.

(6) FIG. 6 is a flowchart illustrating an autonomous driving method of sharing a risk-based operation design domain according to the present disclosure.

(7) FIG. 7 is a flowchart illustrating step S100.

(8) FIG. 8 is a flowchart illustrating step S200.

(9) FIG. 9 is a diagram illustrating a response scenario according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

(10) The present disclosure may be variously modified and have several exemplary embodiments. Therefore, specific exemplary embodiments of the present disclosure will be illustrated in the accompanying drawings and be described in detail. This is not intended to limit the present disclosure to specific embodiments, and it should be understood that this corresponds to any one of all modifications, equivalents or substitutes included in the spirit and scope of the present disclosure for connecting and/or fixing structures extending in different directions.

(11) Terms used in the present specification are used only in order to describe specific exemplary embodiments rather than limiting the present disclosure. Singular forms are intended to include plural forms unless the context clearly indicates otherwise.

(12) It should be further understood that terms “include” or “have” used in the present specification specify the presence of features, numerals, steps, operations, components, parts mentioned in the present specification, or combinations thereof, but do not preclude the presence or addition of one or more other features, numerals, steps, operations, components, parts, or combinations thereof.

(13) An operation design domain (ODD) in this specification refers to an automated domain (e.g.,

road, weather, traffic, etc.) where functions of an autonomous driving system may be performed normally and safely, as suggested by the Ministry of Land, Infrastructure and Transport's "Level 4 Autonomous Vehicle Manufacturing, Safety Guidelines."

(14) Hereinafter, preferred embodiments of an autonomous driving safety system for sharing a risk-based operation design domain and a method thereof according to the present disclosure will be described with reference to the accompanying drawings.

(15) FIG. 1 is a block diagram schematically illustrating an autonomous driving safety system for sharing a risk-based operation design domain and a method thereof according to the present disclosure.

(16) Referring to FIG. 1, the present disclosure may include a control server **200**, a plurality of autonomous vehicles **100**, and a roadside unit **300**.

(17) The plurality of autonomous vehicles **100** may autonomously drive on a road while detecting situations of a roadside, recognize elements of an operation design domain (ODD) while driving to evaluate risk, update the operation design domain with the risk, share the updated operation design domain through infrastructure (e.g., edge infrastructure). A detailed configuration description thereof will be described later.

(18) A roadside unit (RSU) is composed of a plurality of devices capable of communicating and generating and transmitting/receiving traffic information so as to configure, for example, a V2X infrastructure, and is well known.

(19) Here, the roadside unit **300** may share information through an autonomous vehicle and infrastructure, and may relay the shared information to an autonomous vehicle capable of communication, other roadside units **300**, and a control server **200** of a control center.

(20) The control server **200** collects information of operation design domains (ODDs) from an autonomous vehicle and a roadside unit in real time, and compares and evaluates the information of the collected operation design domains (ODD). In addition, the control server **200** transmits the updated operation design domain to an autonomous vehicle in which an error or omission of risk for the operation design domain (ODD) is found among the autonomous vehicles to update the operation design domain of the corresponding autonomous vehicle.

(21) Here, the control server **200** may model a risk-based operation design domain, and compare and evaluate operation design domains of autonomous vehicles collected based on the result.

(22) For example, autonomous vehicles have operation design domains (static operation design domain and dynamic operation design domain) set according to different formats and standards depending on manufacturers or vehicle models, and some or all of the autonomous vehicles should update their own initially designed operation design domains (ODDs) according to a passage of time (change in characteristics of the operation design domain according to day and night, deformation of structures over time, etc.) and a change in traffic (traffic volume, unexpected objects, etc.).

(23) However, the operation design domain may not be updated due to various factors, such as individual circumstances of vehicle owners, a difference in autonomous driving systems, a difference in vehicle models, and circumstances of manufacturers.

(24) Therefore, the control server **200** transmits an operation design domain (ODD) designed according to the up-to-date information to the autonomous vehicle **100** in which an operation design domain (ODD) that does not match the current situation is set. In this case, the updated operation design domain (ODD) may be received through autonomous vehicle **100** and/or infrastructure, or may be designed by the control server itself.

(25) Preferably, the control server **200** may compare and evaluate the operation design domain (ODD) designed by itself and the operation design domain (ODD) of the received autonomous vehicle **100** to calculate the up-to-date information, and transmit the calculated up-to-date information to the autonomous vehicle, the roadside unit **300**, etc., that are not updated to the corresponding operation design domain (ODD).

(26) FIG. 2 is a block diagram of an autonomous vehicle in the present disclosure.

(27) Referring to FIG. 2, the autonomous vehicle **100** includes an autonomous driving system **110**, a sensor unit **120**, a communication unit **130**, and a vehicle driving unit **140**.

(28) The sensor unit **120** is composed of a plurality of sensors capable of detecting objects or surrounding conditions in front and rear and/or left and right sides of the autonomous vehicle **100**, such as a Lidar sensor, a radar sensor, temperature, humidity, and a rain sensor.

(29) The communication unit **130** performs communication with the control server **200**, the roadside unit **300**, and other autonomous vehicles **100**.

(30) The vehicle driving unit **140** is composed of devices that perform unique functions of a vehicle, such as steering, driving, deceleration, and braking. Here, the vehicle driving unit **140** is operated under the control of the autonomous driving system **110**.

(31) The autonomous driving system **110** includes a driving control unit **112** that performs autonomous driving by controlling the vehicle driving unit **140** through scenarios set according to various situations and information detected by the sensor unit **120**, and an operation design domain update unit **111** that evaluates and updates the risk of the recognized operation design domain (ODD).

(32) The driving control unit **112** corresponds to the known autonomous driving system **110** and sets a route to the input destination and controls the vehicle driving unit **140** to perform autonomous driving. Here, the driving control unit **112** controls a vehicle driving unit **140** through a scenario that is set according to various surrounding environments, such as weather (snow, rain, and fog) detected while driving, road surface conditions (wetting, drying, freezing, and damage), unexpected objects (vehicle, pedestrian, animal, rock fall on a road), and road structures (tunnel, second lane, third lane, overpass, back road, pavement, non-pavement), and static or dynamic operation design domains D1, D2, and D3 (see FIG. 9) detected in real time.

(33) The operation design domain update unit **111** models the static or dynamic operation design domain detected by the sensor unit **120** based on risk to update the operation design domain. In addition, the operation design domain update unit **111** updates the shared operation design domain (ODD) from other autonomous vehicles **100** and/or the control server **200** through the communication unit **130** to the up-to-date operation design domain according to the passage of time and the change in traffic.

(34) The operation design domain update unit **111** will be described with reference to FIG. 3.

(35) FIG. 3 is a block diagram illustrating an operation design domain update unit.

(36) Referring to FIG. 3, the operation design domain update unit **111** may include a layer-specific attribute information DB **111a** storing attribute information of the operation design domain, a risk calculation module **111b**, and an update module **111c**.

(37) The layer-specific attribute information DB **111a** layers the operation design domains (ODDs) and stores attribute and weight information set for each layer.

(38) In the present disclosure, the operation design domain (ODD) is layered into 6-layers, and each layer is divided into a single layer. The risk was defined as the total risk of each single layer.

(39) As shown in Table 1 below, the classification of the operation design domains for each layer classifies each layer into road geometry, social infrastructure, a temporary restricted area, an object, an environmental condition, and connectivity (communication), and classifies operation design domain for each layer.

(40) TABLE-US-00001 TABLE 1 6-Layer Operation design domain classification

Layer	Classification
Layer 1: Road geometry	Road structure (type) Road shape (form) Road surface (condition)
Layer 2: Infrastructure	Traffic signal Structure
Layer 3: Temporary restricted	General area Unexpected situation
Layer 4: Object	Object (static, dynamic, unexpected)
Layer 5: Environmental	Season condition Weather (Climate) Light source
Layer 6: Connectivity	V2X (Edge Infra) Control Others

(41) In addition, the present disclosure classifies operation design domains for each layer into large, medium, and small categories by applying criteria such as type, shape, state, and kind, and sets

attributes for judgment of risk evaluation for each small category. Tables 2 to 7 below are classification tables in which attributes for each layer in Table 1 are set. Specifically, Table 2 describes the road geometry layer, Table 3 describes the infrastructure layer, Table 4 describes the temporary restricted area layer, Table 5 describes the object layer, Table 6 describes the environment, and Table 7 describes the detailed classification and properties of the connectivity (communication) layer.

(42) TABLE-US-00002 TABLE 2 Large Medium category category Small category Attribute Road Road Single road, Accident rate geometry structure.sup.{ } Intersection, Fatality (L1) (type) Auxiliary, Others (L1-1) (ex, back road) Road Lane Single Lane width shape lane Total number of lanes on (form) Multi- road (L1-2) lane Lane number on which Ego vehicle is driving Characteristic Curvature Radius of curvature of road Road design speed Slope Road type (flatland, mountainous district, etc.) Longitudinal slope Road design speed Road Pavement Road surface material surface Road surface type (condition) condition Road surface friction (L1-3) coefficient (μ) Damage type (potholes, cracks, etc.) Road surface damage severity (good, average, bad) Distance between Ego vehicle and damaged road surface Lane Lane condition Lane type Land parameter (offset, heading angle, etc.) Left/right position of lane from Ego vehicle Lane condition abnormal (unclear)

(43) Among the contents of Table 2, the attributes of the operation design domain for the road structure are set as accident rate and fatality, so the risk is calculated according to the accident rates and fatalities for each road section. The risks according to the risk factors of the road structure are shown in Table 2-1 below. Table 2-1 classifies the fatality rates for each road section, Ministry of Land, Infrastructure and Transport standards, and risk sections for each EPDO.

(44) TABLE-US-00003 TABLE 2-1 Ministry of Land, Infrastructure Fatality and Transport Score Risk level rate standard EPDO 1 Common 0 to less 6.05 to less 0 to less than 0.8 than 6.82 than 1.42 2 Caution 0.8 to less 6.82 to less 1.42 to than 1.6 than 7.59 less than 2.85 3 Somewhat risk 1.6 to less 7.59 to less 2.85 to than 2. 4 than 8.37 less than 4.27 4 Risk 2.4 to less 8.37 to less 4.27 to than 3.2 than 9.14 less than 5.70 5 Very risk 3.2 to 4.0 9.14 to 9.91 5.70 to or more or more 7.12 or more

(45) In addition, the operation design domain of the type (single road, intersection, back road, etc.) of road structure is classified by type of single roads such as in tunnel, on bridge, over overpass, underpass, and back road, and intersections such as 3-way, 4-way, multiple, and rotation intersections. The risk may be calculated by combining the fatality rates, the EPDO, and the Ministry of Land, Infrastructure and Transport standards for each type.

(46) In addition, the operation design domain of the road shape (form) sets a lane width according to a curvature or slope of a lane and each road, the total number of lanes on a road, a radius of curvature of a road, a road design speed, a road type (flatland or mountainous district) longitudinal slope, and a road design speed as attributes.

(47) With these attributes, risk may take into account the radius of curvature, the longitudinal slope, and the driving speed. For example, risk may be calculated according to the radius of curvature and longitudinal slope of the current road on which the autonomous vehicle **100** is driving, and the current driving speed of the autonomous vehicle **100**. An example thereof is introduced in Table 2-2 below.

(48) TABLE-US-00004 TABLE 2-2 Highway (100 km, longitudinal slope 5%) risk grade by driving speed Risk Curve grade AMF radius Driving speed 1 1~1.1876 460 m Less than 68 km/h 2 1.1877~1.3752 68 to less than 83 km/h 3 1.3753~1.5628 80 to less than 90 km/h 4 1.5629~1.7504 90 to less than 95 km/h 5 1.7505 or more 95 km/h or more

(49) Table 2-2 above sets risk grades for each driving speed on a highway with a longitudinal slope of 5%, and the risk is set high when the driving speed and the longitudinal slope AMF values are low.

(50) In addition, the operation design domain of the road surface and condition is classified into a

pavement, a road surface condition, and a lane. Among those, the road surface friction coefficient according to the type (e.g., asphalt, concrete, block, non-pavement) of pavement is set as an attribute.

(51) Among those, the road surface conditions are subdivided into drying, wetting, snowfall, freezing, and damage. Among those, the drying, wetting, snowfall, and freezing sets the road surface friction coefficient as an attribute. The friction coefficients of the drying, wetting, snowfall, and freezing may have different values depending on the type of pavement.

(52) For example, for the road surface friction coefficients, an asphalt paved road may be assigned attributes of drying (0.8), wetting (0.6 to 0.7), snowfall (0.3 to 0.6), and freezing (0.05 to 0.3), a concrete paved road may be assigned attributes of drying (0.8), wetting (0.4 to 0.6), snowfall (0.3 to 0.6), and freezing (0.05 to 0.3), a block paved road may be assigned attributes of drying (0.7), wetting (0.3 to 0.4), snowfall (0.3 to 0.6), and freezing (0.05 to 0.2), and unpaved road may be assigned may be assigned attributes of drying (0.5), wetting (0.3 to 0.4), snowfall (0.3 to 0.6), and freezing (0.05 to 0.2).

(53) The above friction coefficient is applied to a calculation of a stoppable distance for each driving speed while driving on the road under the corresponding road surface condition of the autonomous vehicle **100**. The calculated stoppable distance is applied as an evaluation criterion for the risk calculation.

(54) Attributes of a lane type (e.g., solid line, dotted line, double solid line, solid line, dotted line, zigzag lane, bus only lane), left/right positions of a lane in the autonomous vehicle **100**, a lane condition (normal or abnormal) are set for a lane. Here, the abnormality of the lane condition means a situation in which the lane is not clearly visually confirmed, such as disappearance or obscurity of a lane.

(55) Table 3 below subdivides the social infrastructure layer and sets the attributes according to each classification.

(56) TABLE-US-00005 TABLE 3 Large Medium category category Small category Attribute
Infrastructure Traffic Caution sign Sign type (L2) signal Regulatory Directional Sign details (L2-1)
sign regulation, No entry, Distance [m] Speed limit Sign Indication Exclusive road coordinates sign
Directional [X, Y] indication Parking, Stop Protection indication Road Prohibited, Center Road
surface surface line, U-turn zone marking type sign line, Lane, Bus-only Road surface lane, Road
edge zone marking line, Restricted details lane, Road barrier, Distance [m] Speed limit, Slow Sign
speed, Temporary coordinates stop, Concession, [X, Y] Guide line, Stop line, Safety zone,
Crosswalk, Protected zone, Heading direction, Lane change, Slope, Auxiliary sign, Signal Structure
Traffic signal sign Road (L2-2) facility type Distance and size [m] Structure coordinates [X, Y]
Guardrail Median strip Streetlight Bump Electric pole Cones Curb Manhole

(57) Among the above contents, the medium category of the traffic signal may be classified into a caution sign, an indication sign, and a road surface sign. Here, the caution sign includes caution signs such as a protected zone (e.g., crosswalks, children protection, wildlife protection), a slope (e.g., uphill, downhill), an accident risk zone, a habitual congestion section, left and right merge roads, left and right diverging roads, an intersection, a median strip start/end road width limit, disappearance of a lane, two way traffic, a speed bump, a priority road, a rock fall road, a construction section, a railway crossing, a tunnel, a bridge, and cross wind.

(58) For the above caution sign, a regulatory sign and an indication sign each have attributes set as the type or details of the sign and the sign coordinates, respectively.

(59) For the road marking, a road surface marking type, a road surface marking details, a distance, and sign coordinates were set as attributes.

(60) In addition, as described in the above Table, the small category of the structure is subdivided into structures on and around a road, such as a traffic signal sign, a guardrail, a median strip, a streetlight, a bump, an electric pole, cones, a curb, and a manhole, and the attributes of each subclass were set as the type, distance, and size of the road facility, and structure coordinates.

(61) The temporary restricted area layer is classified into a protected zone and an operation design domain related to an unexpected situation as shown in Table 4 below, and each attribute is set. Among those, the protected zones (e.g., silver zone, school zone, and school zone protected zone) have start and end points of each protected zone, a distance between the autonomous vehicle **100** and the corresponding protected zone, and the type (e.g., speed reduction, attention) of protected zone set as attributes.

(62) TABLE-US-00006 TABLE 4 Large Medium category category Small category Attribute
Temporary General Protected zone Distance between restricted (L3-1) (ex, silver start/end point of area zone, school protected zone and the (L3) zone, school Ego vehicle zone protection Protected zone type area) Unexpected Distance between Ego situation (ex, vehicle and unexpected traffic section accident, Position of left/right construction lanes in unexpected section, section from Ego vehicle emergency stop Relative position: vehicle) Surrounding position of unexpected section from Ego vehicle Type of unexpected section

(63) The unexpected situation means a traffic accident, a construction section, and an emergency stop vehicle, and attributes are set as a distance between an autonomous vehicle **100** and an unexpected section, a position of the unexpected section, a relative position, and a type of unexpected section.

(64) The object layer includes an object that may appear while driving on the road, as shown in Table 5 below, and is classified into a vehicle, a pedestrian, an animal, etc.

(65) TABLE-US-00007 TABLE 5 Large Medium category category Small category Attribute
Object(L4) Object(L4- Vehicle Relative lane position 1) (left/right lane position of target vehicle from the Ego vehicle), Relative position (surrounding position of target vehicle from Ego vehicle), Absolute speed (X and Y axes), Relative speed from Ego vehicle (X, Y axis), Distance (X, Y axis), Travel angle (direction), Detection coordinate (detection coordinate of object), Type (commercial, passenger, etc.) pedestrian General Adult Relative speed from Ego Elder vehicle (X, Y axis), Children Absolute speed (X, Y Others axis), Distance (X, Y (police axis), Travel angle officer, (direction), Detection etc.) coordinate (detection Animal Mammalia coordinate of object), Birds Type (pedestrian, Others animal, etc.)

(66) Among those, the vehicle includes, for example, a commercial vehicle, a passenger vehicle, agricultural machinery, a two-wheeled vehicle, a motor vehicle, a bicycle, a special vehicle, a truck, a police cars, and special vehicles such as a fire truck, and sets a relative lane position, a lane position, an absolute speed, a relative speed, a travel angle, detection coordinates, etc.

(67) In addition, the pedestrian may also be classified as an adult, a senior, a child, and others, such as officials performing public duties such as police officers or workers during construction.

(68) For the pedestrian and animal, the relative speed from the autonomous vehicle **100**, the absolute speed, the distance, the travel angle, the detection coordinates, the type, etc., are set as attributes.

(69) The environment layer is a layer for the road driving environment of the autonomous vehicle **100** and may be classified as season, weather, and a light source as shown in Table 6 below.

(70) TABLE-US-00008 TABLE 6 Large Medium category category Small category Attribute
Environ- Season(L5- Spring, summer, — ment(L5) 1) fall, winter Weather Sunny cloud ratio (climate) Cloudy (L5-2) Wind Wind speed Rain Precipitation Snow Snowfall Fog Visibility range Light Natural Dawn Standard time: 00 to source(L5- 06 hours 3) Morning Standard time: 06 to 09 hours Daytime Standard time: 09 to 18 hours Evening Standard time: 18 to 21 hours Night Standard time: 21 to 24 hours Artificial Vehicle — lamp (high beam, etc.) Traffic light Streetlight Others

(71) Among the above contents, a cloud ratio, a wind speed, precipitation, snowfall, and visibility range were set as attributes for weather. Here, the cloud ratio is a value for determining sunny and cloudy conditions as a cloud ratio. For example, for the sunny condition, an attribute is assigned as having clouds in the entire sky at a rate of 0 to 50%, and for the cloudy state, an attribute is

assigned as having clouds at a rate of 9 to 10%.

(72) In addition, among the weather attributes, wind is a wind speed (for example, strong: 25 m/s or more, middle: 20-25 m/s, low: 15 m/s) set as an attribute, rain is precipitation (for example, strong: 30 mm or more, middle: 15 to 30 mm, low 1 to 15 mm) set as an attribute, snow is snowfall (e.g., strong: 30 mm or more, medium: 15 to 30 mm, low: 1 to 15 mm) set as an attribute, and fog is a visibility range (e.g., strong: 40 m or less, medium 40 to 200 m, low: 200 to 1000 m) set as an attribute.

(73) The connectivity (communication) layer is a layer for communication with the control server **200** and/or surrounding infrastructure for the operation of the autonomous driving system **110**, and the classification and attributes are set as shown in Table 7 below.

(74) TABLE-US-00009 TABLE 7 ODD classification Variable Attribute Connectivity/ V2V
Communication rangeAverage communication(L6) throughput Packet error rate Average latency
V2I Edge Infra Control — Communication Distance from shadow area shadow area Shadow area
length

(75) The risk calculation module **111b** models the operation design domain (ODD) based on risk depending on whether the static operation design domain or the dynamic operation design domain is recognized while driving, updates the operation design domain to suit the field, and reflects the updated operation design domain on the existing installed operation design domain. Such a risk calculation module will be described through an embodiment of calculating risk in a road geometry layer as an example.

(76) The risk calculation module **111b** may apply weights in risk calculation according to the attributes for each layer described above. Here, risk may be calculated through formula such as Equation 1 below.

$$(77) \text{ SingleLayerRiskValue} = \sum_{k=1}^n (a_k w_k) \quad [\text{Equation1}]$$

$$\text{TotalLayerRiskValue} = L_1 w'_1 + L_2 w'_2 + \dots + \text{Math. } L_6 w'_6$$
$$a_k = \text{ODD}_{\text{element}}$$
$$w_k = \text{weight}$$
$$L_k = \text{SingleLayerRiskValue}$$

(78) In the present disclosure, the risk (total layer risk value) of the operation design domain situation recognized while driving the autonomous vehicle **100** corresponds to the sum of risks (single layer risk values) for each layer.

(79) In addition, the risks (single layer risk values) for each layer are classified according to variables for each layer, and a weight is applied to the calculated attribute value (ODDelement).

(80) The update module **111c** updates the risk evaluation result by the risk calculation module **111b** to the current operation design domain. The autonomous driving unit **112** drives the autonomous vehicle as the best scenario based on the risk included in the updated operation design domain (ODD).

(81) Hereinafter, an embodiment of the above risk calculation and/or evaluation process will be described. However, the final risk is determined by the sum of risks for each layer, but the embodiment describes only some of layers selected from the entire 6-layers as an example.

Example 1

(82) The risk according to a road structure (type) of road geometry layer can be calculated by applying different weights for each traffic accident, for example, a fatal accident, a serious accident, and a minor accident. In this case, the risk may be calculated by Equation 2 as follows.

$$(83) \text{ Risk} = \frac{\text{fatalaccident} \times 1 + \text{seriousaccident} \times 0.7 + \text{minoraccident} \times 0.3}{\text{numberoftrafficaccidents}} \quad [\text{Equation2}]$$

(84) In Equation 2 above, a weight of 1 was set for a fatal accident, a weight of 0.7 was set for a serious accident, and a weight of 0.3 was set for a minor accident.

(85) In addition, the risk according to the accident severity according to the road type is calculated by applying the equivalent property damage only (EPDO) methodology for each average number

of accidents. This is calculated by Equation 3 below.

$$(86) \text{ EPDO}(\text{by number of accidents}) = \frac{\text{death accident} \times 12 + \text{injury accident} \times 3}{\text{number of traffic accidents}} \quad [\text{Equation 3}]$$

(87) Here, a weight of 12 was applied to a fatal accident and a weight of 3 was applied to an injury accident.

(88) The weights in Equation 2 and Equation 3 above are weights applied when the Road Traffic Authority selects accident-prone points. This is not limiting as applied to one example. In other words, the weight may be modified according to the designer's or operator's intention, traffic regulations, and characteristics of roads or regions.

(89) Risk reflecting the result values of Equation 2 and Equation 3 above may be calculated as shown in Table 8 below.

(90) Table 8 summarizes an example of calculating the fatality rate on a single road and intersection among road types, the risk according to traffic risk, and the risk according to EPDO (number of accidents).

(91) TABLE-US-00010 TABLE 8 Classification Traffic risk EPDO Single In tunnel 9.91 7.12 road On bridge 8.13 5.75 On overpass 7.51 5.38 Underpass 7.33 4.93 Others 6.72 4.60 (general) Crossroad 3-way 6.80 4.51 4-way 6.96 4.72 Multiple 6.75 4.69 Roundabout 6.37 4.64 Others•Auxiliary 6.05 0.19

(92) The risk calculation module **111b** evaluates the risk in consideration of both the above traffic risk and the result value of the EPDO, and reflects the evaluated risk when there is a difference from the existing operation design domain (ODD). Such an update of the operation design domain may change the set scenario according to the recognized risk.

(93) For example, the scenario according to the existing operation design domain was set to reduce a driving speed of 100 km to 70% or less when a vehicle-to-vehicle distance is 50 M, but when the risk is evaluated as high in the updated operation design domain (ODD), the scenario may be changed to reduce the driving speed to 30% or less or to stop.

(94) That is, the present disclosure may improve safety of autonomous driving by evaluating risk according to an operation design domain (ODD) situation of a road site and updating the operation design domain (ODD).

Example 2

(95) In road shape elements, elements (attributes) that may affect vehicle driving safety are a curve radius and a longitudinal slope. Therefore, a risk calculation module calculates risk according to a curve radius through an accident modification factor according to the curve radius, which is calculated through the accident modification factor formula in Table 9.

(96) TABLE-US-00011 TABLE 9 Accident modification factor (risk) formula according to curve radius Variable $AMF_{\text{curveradius}} = 1.0 + 0.97(0.147V)^4 \frac{(1.47V)^2}{32.2R^2} [\frac{L_c}{L}]$ V: Speed limit [mph] Lc: Curve length [mile] L: Section length [mile] R: Curve radius [ft]

(97) In addition, the risk calculation module may calculate the risk through the accident modification factor according to the longitudinal slope. The accident modification factor according to the longitudinal slope is calculated through the formula in Table 10 below.

(98) TABLE-US-00012 TABLE 10 Formula Variable $AMF_{\text{sub.longitudinal slope}} = c.\text{sup}.0.016 \text{ g or } c.\text{sup}.0.019 \text{ g}$ g: Longitudinal slope(%)

(99) Table 11 shows examples of values calculated according to curve radius and longitudinal slope.

(100) TABLE-US-00013 TABLE 11 Rule on Road Structure Longitudinal and Facility Standard Radius (m) slope(%) Highway 120 km/h 710 5 110 km/h 600 100 km/h 460 Arterial road 80 km/h 280 7 Local road 50 km/h 90 14

(101) In addition, in order to calculate the risk grade by the curve radius on a highway with many vehicles driving at 100 km/h or more, the curve radius AMF scores obtained by calculating the accident modification factors for speeds of 110 km/h and 100 km/h are shown in Table 12 below.

(102) TABLE-US-00014 TABLE 12 AMF(Accident Highway Radius (m) Modification Factors)
 110 km/h 600 1.7937 693 1.5953 849 1.3968 1200 1.1984 — 1.0000 100 km/h 460 1.7622 531
 1.5716 651 1.3811 920 1.1905 — 1.0000

(103) In addition, the risk calculation module calculates the road type risk using the above curve radius and the longitudinal slope AMF score. The road type risk is calculated by Equation 4 below.
 Risk of road shape=AMF.sub.curve radius×AMF.sub.longitudinal slope [Equation 4]

(104) Therefore, the road type risk may be finally calculated as shown in Table 9 below. The table below evaluates a risk for each driving speed of 110 km/h and 100 km/h on the highway in the second lane. The higher the score, the higher the risk.

(105) TABLE-US-00015 TABLE 13 Risk of road form in highway in second lane Highway No.
 Score No. Score No. Score No. Score No. Score 110 km/h 1 1.000 6 1.198 11 1.397 16 1.595 21
 1.794 2 1.024 7 1.227 12 1.430 17 1.634 22 1.837 3 1.049 8 1.257 13 1.465 18 1.673 23 1.881 4
 1.074 9 1.287 14 1.500 19 1.713 24 1.926 5 1.100 10 1.318 15 1.536 20 1.754 25 1.973 100 km/h 1
 1.000 6 1.191 11 1.381 16 1.572 21 1.762 2 1.024 7 1.219 12 1.414 17 1.609 22 1.804 3 1.049 8
 1.248 13 1.448 18 1.648 23 1.848 4 1.074 9 1.278 14 1.483 19 1.688 24 1.892 5 1.100 10 1.309 15
 1.519 20 1.728 25 1.938

Example 3

(106) Risk that may be issued due to a road surface pavement material and road surface conditions occurs due to an increase in a stopping distance due to a change in frictional force of a road surface.

(107) Therefore, the risk calculation module **111b** calculates the risk through a stopping distance by applying friction coefficients for each road surface condition (drying, wetting, freezing). First, the stopping distance according to the road surface conditions for each driving speed is shown in Table 10 below.

(108) TABLE-US-00016 TABLE 14 Driving speed Stopping distance [m] [km/h] Drying Wetting
 Freezing 20 16.3 17.5 24.4 30 26.4 28.9 44.5 40 37.8 43.5 69.8 50 50.9 62.1 100.3 60 65.3 84.6
 136.2 70 81.3 108.9 177.2 80 100.0 136.8 223.5 90 118.4 168.8 275.1 100 139.7 200.7 331.9 110
 163.0 240.7 394.0 120 188.3 278.8 461.3

(109) The driving speed [km/h] risk calculation module may set the risk higher as the stopping distance increases according to the driving speed and road surface condition.

(110) In addition, the risk calculation module sums up the results of Examples 1 to 3 to finally calculate the risk for the currently detected state of the operation design domain (ODD). However, the above description is based on Examples 1 to 3 for convenience, and the final value for the actual risk is determined by the sum of the risks of all related layers according to the recognized ODD.

(111) In addition, an update module **111c** updates the operation design domain (ODD) according to the above risk. Therefore, a driving control unit **120** may control autonomous driving as a scenario suitable for the site according to the operation design domain (ODD) in which the risk is reflected by the update module **111c**.

(112) The control server **200** will be described in more detail with reference to FIGS. 4 and 5.

(113) FIG. 4 is a block diagram illustrating a control server, and FIG. 5 is a block diagram illustrating an operation design domain design unit.

(114) Referring to FIGS. 4 and 5, the control server **200** may include an information collection unit **210**, an operation design domain design unit **220**, and a server communication unit **130**.

(115) The information collection unit **210** collects information from a roadside unit **300** and an autonomous vehicle **100**. The collected information may be information on operation design domain situations recognized while the autonomous vehicle **100** is driving on the road.

(116) In addition, the information collection unit **210** is capable of collecting various information including the shared operation design domain and roadside and traffic conditions from the autonomous vehicle and the roadside unit.

(117) The operation design domain design unit **220** models an operation design domain (ODD)

including situations of ODDs (e.g., static ODD, dynamic ODD, or a combination of static and dynamic ODD) collected from autonomous vehicles.

(118) To this end, the operation design domain design unit **220** may include an operation design domain design module **221**, an evaluation module **222**, and an information providing module **223**.

(119) The operation design domain design module **221** models a risk-based operation design domain (ODD). The process or method may be performed in the same way as the modeling process of the operation design domain (ODD) of the autonomous vehicle **100** described above (e.g., the sum of risks for each 6-layer).

(120) The evaluation module **222** compares and evaluates the result values modeled by the operation design domain design module **221** and the operation design domains of the autonomous vehicles and the roadside units **300**. Here, the evaluation module **222** compares the collected operation design domain (ODD) and the operation design domain (ODD) modeled by the operation design domain design module **221** to extract the operation design domain (ODD) in which the up-to-date update information such as risk evaluation is missing.

(121) Alternatively, the evaluation module **222** compares the operation design domain design module **221** and the operation design domain (ODD) of the autonomous vehicle **100**, and when the operation design domain (ODD) of the autonomous vehicle is more up-to-date information, updates the operation design domain designed by itself to the operation design domain (ODD) of the corresponding autonomous vehicle.

(122) The information providing module **223** provides information to the autonomous vehicle **100** and the roadside unit **300**. In this case, the provided information may include information including real-time accidents, traffic volume, weather, and the like, and up-to-date update information designed in the operation design domain design module.

(123) In particular, the information providing module **223** may transmit the up-to-date update information of the operation design domain (ODD) to the autonomous vehicle **100** from which the up-to-date update information is missing in the previously collected operation design domain (ODD).

(124) The present disclosure includes an autonomous driving method capable of updating an operation design domain (ODD) achieved through the above configuration. The autonomous driving method capable of updating an operation design domain will be described below.

(125) FIG. **6** is a flowchart illustrating an autonomous driving method capable of updating an operation design domain according to the present disclosure, and FIG. **7** is a flowchart illustrating step **S100**.

(126) Referring to FIGS. **6** and **7**, the present disclosure includes a step **S100** of sharing ODD modeling and information in the autonomous vehicle **100** and a step **S200** of transmitting ODD modeling and updated ODD modeling information of the control server **200**.

(127) Among those, step **S100** is a step of evaluating the risk according to the operation design domain (ODD) recognized in the field by the autonomous vehicle **100**, and thus, updating the operation design domain (ODD) to perform autonomous driving through a scenario according to the risk of the field situation.

(128) Describing in more detail, step **S100** includes step **S110** of autonomous driving in the autonomous vehicle, step **S120** of detecting surrounding situations and objects, step **S130** of calculating risks for each layer set according to the situations recognized while driving, a step **S140** of updating the risk-based operation design domain, and a step **S150** of sharing update information.

(129) Step **S110** is a step of starting autonomous driving in the autonomous vehicle **100**. The autonomous driving system sets a route according to the input destination and starts driving to a destination by controlling the vehicle driving unit **140**.

(130) Step **S120** is a step of detecting an event defined in the operation design domain (ODD) while the autonomous vehicle **100** is driving. For example, as illustrated in FIG. **9**, the autonomous vehicle **100** has a construction section **D1** in which a worker is present in a front lane on which the

autonomous vehicle **100** is driving, and an emergency stop vehicle **D3** is present in front of the construction section, and detects a bump **D2** on the front of the emergency stop vehicle.

(131) Here, the construction section **D1** corresponds to a dynamic ODD classified into a temporary restricted area, the emergency stop vehicle **D3** corresponds to a dynamic ODD/event as an unexpected object, and the bump **D2** corresponds to a static ODD as social infrastructure.

(132) Step **S130** is a step of calculating the risks for the static and dynamic ODDs in which the driving of the autonomous vehicle **100** is detected. For example, the construction section **D1** is classified as the temporary restricted section, the emergency stop vehicle **D3** is classified as an unexpected object, and the bump **D2** is classified as a social infrastructure facility.

(133) Therefore, the autonomous vehicle **100** searches for attributes for each layer classified into 6-layers, such as road surface condition of a road, structure, type, and weather of a road, and wind, and applies the set weight. The autonomous vehicle **100** calculates a final result value by summing the risks for each layer.

(134) Step **S140** is a step of updating the operation design domain based on risk in the autonomous vehicle **100**. The autonomous vehicle **100** updates the previously installed operation design domain by applying the calculated risk.

(135) For example, the updated operation design domain (ODD) included a higher grade risk than the front construction section **D1** as the emergency stopped unexpected object **D3** and the bump **D2** continuously existed.

(136) Therefore, when the autonomous driving system **110** is set to move and drive to the next car by decelerating to 80% when reaching set distance **a** of the corresponding point when there is a construction section in the front lane in the existing scenario, the autonomous driving system decelerates from a longer distance according to the risk grade and controls the driving in a scenario in which the vehicle passes the corresponding section while driving slowly at a speed of 10 km/h or less.

(137) Step **S150** is a step in which the autonomous vehicle **100** shares the updated operation design domain (ODD). The autonomous vehicle **100** transmits the updated operation design domain ODD to other surrounding autonomous vehicles **100**, the roadside unit **300**, and the control server **200**. The transmitted information may be evaluated by the control server **200** and retransmitted to other autonomous vehicles **100** to be shared. Alternatively, the information is directly shared through one-to-one communication with other autonomous vehicles **100**.

(138) Step **S200** will be described with reference to the flowchart of FIG. 8.

(139) FIG. 8 is a flowchart illustrating step **S200**.

(140) Referring to FIG. 8, step **S200** includes step **S210** of collecting, by the control server **200**, information from the autonomous vehicle **100** and the roadside unit **300**, step **S220** of modeling the operation design domain, step **S230** of evaluating the operation design domain of the autonomous vehicles **100**, and step **S240** of updating the operation design domain.

(141) Step **S210** is a step of collecting information from the control server **200**. The control server **200** collects information such as traffic accidents, traffic volumes, and weather or events around roads, including the operation design domain (ODD), through infrastructure such as the autonomous vehicle **100** and the roadside unit **300**.

(142) Step **S220** is a step of modeling, by the control server **200**, the operation design domain. Here, the control server **200** designs and/or shares the operation design domain in various ways.

(143) For example, before step **S210**, the control server **200** may model the operation design domain according to information of a specific road section and store the modeled operation design domain by itself.

(144) Alternatively, the control server **200** may collect the information of the operation design domain (ODD) collected in step **S210** to check whether there is an event on the road and the surrounding situation, and model the operation design domain according to the information of the section in which the event occurred.

(145) Alternatively, the control server **200** may collect the road section and surrounding information (information classified into 6-layer layers and corresponding to attributes) collected through the infrastructure such as the plurality of autonomous vehicles **100** and roadside units **300** in step **S210**, model the operation design domain (ODD), and model the corresponding operation design domain whenever information different from the existing information is collected.

(146) Step **S230** is a step of evaluating, by the control server **200**, whether the collected operation design domain of the autonomous vehicles **100** has been updated to the up-to-date information. As the autonomous vehicles **100** may have different operation design domains (ODD) installed depending on manufacturers and product specifications, the update to the static or dynamic operation design domain may be delayed due to the event, weather, or road type or structure.

(147) Accordingly, the control server **200** may evaluate whether the operation design domain has been updated with the up-to-date information after collecting the operation design domain from the plurality of autonomous vehicles **100** in this way. In this case, the comparison target is either the operation design domain (ODD) modeled by itself through the information collected in real time from the control server **200** or the operation design domain according to the up-to-date road information collected from the autonomous vehicle **100**, or compares and evaluates the collected operation design domains (ODDs) to derive the operation design domain (ODD) updated to the most up-to-date information.

(148) Step **S240** is a step of comparing and evaluating, by the control server **200**, the collected operation design domains (ODDs) and transmitting the updated operation design domains to the autonomous vehicles **100** that have not been updated to the up-to-date information.

(149) That is, the control server **200** may transmit the up-to-date operation design domain received through the operation design domain (ODD) modeled by itself or the infrastructure to other autonomous vehicles **100** to provide the up-to-date operation design domain (ODD) capable of responding to the static and dynamic operation design domains, such as an unexpected situation in a road or an unexpected object due to a surrounding situation.

(150) Therefore, the present disclosure may solve the conventional problems of the autonomous vehicles **100**, which are difficult to update due to various reasons such as systems or manufacturers, and create the safer autonomous driving environment.

(151) According to the present disclosure, it is easy to update an operation design domain by evaluating risk according to road conditions recognized in real time in an autonomous vehicle, and to update the operation design domain regardless of a vehicle model, system specifications, and model year since the updated operation design domain may be shared with other autonomous vehicles and roadside units.

(152) In addition, according to the present disclosure, it is easy to design an operation design domain that includes risk through information collected in real time from a control server communication-connected through infrastructure, and to update the operation design domain since the designed operation design domain may be shared with the autonomous vehicles and roadside units through the infrastructure.

(153) The exemplary embodiments of the present disclosure have been described hereinabove, but those skilled in the art may variously modify and alter the present disclosure by adding, changing or deleting components without departing from the spirit and scope of the present disclosure defined in the claims, and it is to be considered that these modifications and alterations fall in the scope of the present disclosure.

Claims

1. An autonomous driving safety system for sharing a risk-based operation design domain, comprising: an autonomous driving system configured to control a vehicle driving unit according to information detected by a sensor unit to perform autonomous driving, wherein the autonomous

driving system includes an operation design domain (ODD) update unit configured to evaluate a risk of at least one of a static operation design domain and a dynamic operation design domain recognized by the sensor unit while driving to update the operation design domain (ODD), wherein the autonomous driving system shares the updated operation design domain (ODD) with at least one of a roadside unit, other autonomous vehicles, and a control server, wherein the autonomous driving system includes: a layer-specific attribute information DB configured to layer the operation design domains (ODD) into a plurality of layers and stores attributes for each layer and weights set for each attribute; a risk calculation module configured to calculate risks for each layer by applying the weight of the attributes stored in the layer-specific attribute information DB according to the recognized operation design domain (ODD), and calculates a final risk by summing the risks for each layer; and an update module configured to update the risk calculated by the risk calculation module to the operation design domain (ODD), wherein the autonomous driving system is classified into: a road geometry layer that is classified into an operation design domain (ODD) of a road structure, a road type, a road shape and form, and a shape, type, and condition of a road surface; a social infrastructure layer that is classified into the operation design domain (ODD) of a traffic signal and structure; a temporary restricted area layer that is classified into an unexpected situation caused by a traffic accident, a construction section, and an emergency stop vehicle, and an operation design domain (ODD) of a protected zone; an object layer that is classified into an operation design domain (ODD) of a static object, a dynamic object, and an unexpected object on and around a road; an environmental condition layer that is classified into an operation design domain (ODD) of season, weather (climate), and a light source; and a connectivity (communication) layer that is classified into an operation design domain (ODD) of communication and control.

2. The autonomous driving safety system of claim 1, wherein the autonomous driving system shares the updated operation design domain (ODD) with at least one of a roadside unit, other autonomous vehicles, and a control server.

3. The autonomous driving safety system of claim 1, wherein the temporary restricted area layer has an attribute set as at least one of a distance between start and end points of the protected zone and the autonomous vehicle, a type of protected zone, a distance between an autonomous vehicle and an unexpected section, left and right lane positions between the unexpected sections from the autonomous vehicle, a relative position of the unexpected section from autonomous vehicle, and a type of the unexpected section.

4. The autonomous driving safety system of claim 1, wherein the operation design domain (ODD) of a type of the road structure has an attribute set as an accident rate and fatality, and the accident rate and fatality are weighted differently depending on a degree of death and injury.

5. The autonomous driving safety system of claim 1, wherein the operation design domain (ODD) of the road shape has an attribute set as at least one of a lane width, the total number of lanes on a road, a lane number on which the autonomous vehicle is driving, a radius of curvature of a road, and a road design speed.

6. The autonomous driving safety system of claim 1, wherein the operation design domain (ODD) of the road surface has an attribute set as at least one of a road surface material type, a road surface friction coefficient (μ), a damage type, road surface damage severity (high, medium, low), and a distance between the autonomous vehicle and a road surface damage section.

7. The autonomous driving safety system of claim 1, wherein a risk of the operation design domain (ODD) of the type of the road structure is calculated according to Equation below:

$$\text{Risk} = \frac{\text{fatalaccident} \times 1 + \text{seriousaccident} \times 0.7 + \text{minoraccident} \times 0.3}{\text{numberoftrafficaccidents}}$$
 wherein a weight of 1 is set for a fatal accident, a weight of 0.7 is set for a serious accident, and a weight of 0.3 is set for a minor accident.

8. The autonomous driving safety system of claim 1, wherein the operation design domain (ODD) of the weather sets a cloud ratio, a wind speed, precipitation, snowfall, a visibility range as an attribute, the cloud ratio is set as a ratio occupied by clouds in sunny and cloudy conditions, wind,

rain, and snow are classified and set into multiple categories based on the amount, and fog is classified into multiple types based on the visibility range.

9. The autonomous driving safety system of claim 1, wherein the object layer is classified into an operation design domain (ODD) of a vehicle, a pedestrian, and an animal, the operation design domain of the vehicle has an attribute set as at least one of left/right lane positions of a target vehicle from the autonomous vehicle, a surrounding position of the target vehicle from the autonomous vehicle, an absolute speed (X and Y axes), a relative speed (X and Y axes) from the autonomous vehicle, a distance (X and Y axes), a travel angle (direction), detection coordinates, and a type of a vehicle, and the operation design domain (ODD) of the pedestrian and animal has an attribute set as at least one of the relative speed, absolute speed, distance, travel angle, detection coordinates, and type from the autonomous vehicle.

10. The autonomous driving safety system of claim 1, wherein a risk of the operation design domain (ODD) of the road shape is calculated by Equation below: Risk of road shape=AMF.sub.curve radius×AMF.sub.longitudinal slope wherein the curve radius is a curve radius of a road, and the longitudinal slope is a longitudinal slope of a road.

11. An autonomous driving safety system of sharing a risk-based design domain, comprising: a control server configured to collect an operation design domain (ODD) from a plurality of autonomous vehicles **100** and roadside units in real time, wherein the control server transmits an operation design domain (ODD) including risk to the plurality of autonomous vehicles and roadside units to update the operation design domain-, wherein the control server receives the risk-based operation design domain from the autonomous vehicle, and compares and evaluates the collected operation design domain to transmit the updated operation design domain to the autonomous vehicle in which the risk is missing or erroneous.

12. The autonomous driving safety system of claim 11, wherein the control server includes: an information collection unit configured to collect an operation design domain (ODD) and road and surrounding situation information from the plurality of roadside units and autonomous vehicles; an operation design domain design unit configured to model an operation design domain including at least one of a static operation design domain and a dynamic operation design domain collected from the autonomous vehicle; and a server communication unit configured to transmit the operation design domain (ODD) modeled by the operation design domain design unit to the plurality of autonomous vehicles and roadside units.

13. The autonomous driving safety system of claim 12, wherein the operation design domain design unit includes: an operation design domain design module configured to model the risk-based operation design domain (ODD); an evaluation module configured to compare and evaluate the operation design domain (ODD) modeled by the operation design domain design module and the operation design domain (ODD) collected from the autonomous vehicles and the roadside units to extract an operation design domain not including risk; and an information providing module configured to transmit the updated operation design domain (ODD) to the autonomous vehicle and the roadside unit through the server communication unit.

14. An autonomous driving control method of sharing a risk-based design domain, comprising: recognizing an operation design domain (ODD) in real time while an autonomous vehicle is driving, evaluating risk, and updating the operation design domain; transmitting the operation design domain (ODD) updated by the autonomous vehicle to at least one of a control server, and other autonomous vehicles and roadside units **300** and sharing the operation design domain (ODD); and collecting, by the control sever, the operation design domain (ODD) from the plurality of autonomous vehicles and roadside units in real time, evaluating and updating the risk of the collected operation design domain (ODD), and comparing and evaluating the collected operation design domain (ODD) to transmit the updated operation design domain to the autonomous vehicle and the roadside unit transmitting the operation design domain (ODD) in which the risk is missing or erroneous.

15. The autonomous driving control method of claim 14, wherein the recognizing comprises: autonomous driving in the autonomous vehicle; detecting an event defined in the operation design domain (ODD) while the autonomous vehicle is autonomously driving; calculating a risk of an event including at least one of a static operation design domain and a dynamic operation design domain detected while the autonomous vehicle is driving; and calculating a risk of the operation design domain recognized by the autonomous vehicle to update the operation design domain, and performing autonomous driving through a scenario set as the updated operation design domain.
16. The autonomous driving control method of claim 14, further comprising: receiving, by the control server, the updated operation design domain (ODD) and transmitting the updated operation design domain (ODD) to the other autonomous vehicles and roadside units.
-