

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                            |
|----------------------|----------------------------|
| United States Patent | 12398875                   |
| Kind Code            | B2                         |
| Date of Patent       | August 26, 2025            |
| Inventor(s)          | Ahire; Mohan Suklal et al. |

---

### Lightweight and compact elevated approach light

---

#### Abstract

A lighting system includes an enclosure that has a back section, side sections, a front section with a front mounting frame, and an interfacing step extending from or coupled to the side sections and located between the front section and the back section. The enclosure includes an outer surface facilitating heat transfer into the environment. The lighting system also includes a conduction frame attached to the interfacing step, and one or more light emitting assemblies attached to the conduction frame. Each of the light emitting assemblies includes a conduction member and a light source attached to the conduction member, and where each conduction member facilitates heat transfer from the light source to the conduction frame. Additionally, a front housing assembly is attached to the front mounting frame of the front section to seal the enclosure from the environment.

---

**Inventors:** Ahire; Mohan Suklal (Nashik, IN), Gundavarapu; Parameswari V L (Pune, IN), Birje; Ramesh Nagendra (Pune, IN), Makandar; Zahidali Mohammadgous (Pune, IN)

**Applicant:** Eaton Intelligent Power Limited (Dublin, IE)

**Family ID:** 1000008778790

**Assignee:** Eaton Intelligent Power Limited (Dublin, IE)

**Appl. No.:** 18/541562

**Filed:** December 15, 2023

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20240200769 A1          | Jun. 20, 2024           |

#### Foreign Application Priority Data

|    |              |               |
|----|--------------|---------------|
| IN | 202211073289 | Dec. 17, 2022 |
|----|--------------|---------------|

## Publication Classification

**Int. Cl.:** F21V31/00 (20060101); B64D47/02 (20060101); F21V7/00 (20060101); F21V7/28 (20180101); F21V29/70 (20150101); F21Y107/50 (20160101); F21Y107/60 (20160101)

**U.S. Cl.:**

**CPC** F21V31/005 (20130101); F21V29/70 (20150115); B64D47/02 (20130101); B64D2203/00 (20130101); F21V7/0066 (20130101); F21V7/0083 (20130101); F21V7/28 (20180201); F21Y2107/50 (20160801); F21Y2107/60 (20160801)

## Field of Classification Search

**CPC:** F21V (31/005); F21V (29/70); F21V (7/0066); F21V (7/0083); F21V (7/28); F21V (15/01); B64D (47/02); B64D (2203/00); F21Y (2107/50); F21Y (2107/60); F21Y (2115/10); B64F (1/20); F21W (2111/06)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl.   | CPC          |
|--------------|-------------|---------------|------------|--------------|
| 4521836      | 12/1984     | Puttemanns    | N/A        | N/A          |
| 9206961      | 12/2014     | Bastiani      | N/A        | N/A          |
| 9470407      | 12/2015     | Abel          | N/A        | F21V 29/70   |
| 9829191      | 12/2016     | Gongola       | N/A        | N/A          |
| 10647448     | 12/2019     | Hunter        | N/A        | N/A          |
| 2006/0007013 | 12/2005     | Singer        | 340/815.45 | H05B 45/58   |
| 2009/0296379 | 12/2008     | Tartock       | N/A        | N/A          |
| 2013/0094192 | 12/2012     | De            | N/A        | N/A          |
| 2015/0009678 | 12/2014     | Hunter        | 362/346    | F21V 7/09    |
| 2015/0362155 | 12/2014     | Thomsen       | 362/268    | F21V 5/008   |
| 2019/0086061 | 12/2018     | Hunter        | N/A        | F21V 19/0015 |
| 2019/0242547 | 12/2018     | Zhang         | N/A        | F21K 9/66    |
| 2020/0231301 | 12/2019     | Hampel        | N/A        | F21V 5/02    |
| 2020/0240616 | 12/2019     | Sieczkowski   | N/A        | F21V 15/01   |

### FOREIGN PATENT DOCUMENTS

| Patent No. | Application Date | Country | CPC |
|------------|------------------|---------|-----|
| 102454914  | 12/2013          | CN      | N/A |
| 104930418  | 12/2014          | CN      | N/A |
| 106016065  | 12/2015          | CN      | N/A |
| 213207440  | 12/2020          | CN      | N/A |
| 100945420  | 12/2009          | KR      | N/A |
| 200450192  | 12/2009          | KR      | N/A |
| 101269080  | 12/2012          | KR      | N/A |

---

Primary Examiner: Tumebo; Tsion

## Background/Summary

### CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit under 35 U.S.C. § 119(a) of Indian Patent Application No. 202211073289, filed Dec. 17, 2022, which are incorporated herein by reference.

### TECHNICAL FIELD

(2) This disclosure relates to lighting systems, and in particular the disclosure relates to commercial approach lighting systems designed to illuminate the approach end of an airport runway.

### BACKGROUND

(3) Approach lighting systems play a critical role in aviation safety by providing visual guidance to pilots during the landing phase. However, existing systems face challenges. Common issues include susceptibility to environmental conditions such as heavy rain, snow, or fog, which can diminish visibility and compromise the effectiveness of traditional lighting technologies. Additionally, maintenance and durability are key concerns, as frequent exposure to adverse weather conditions can lead to wear and tear, necessitating regular upkeep. Robust approach lighting systems must address these challenges by incorporating advanced technologies resilient to environmental factors, ensuring consistent visibility in various weather conditions. Furthermore, a focus on durability and reduced maintenance requirements is crucial for sustaining optimal performance over time, ultimately contributing to the safety and reliability of aviation operations. Furthermore, the approach lighting systems required to be lightweight, compact, and have an excellent thermal management to facilitate effective removal of heat from light emitting sources into an environment of the approach lighting system.

(4) Consequently, there is a need for an improved design of the approach lighting system, which addresses considerations such as weight, and thermal management, without sacrificing illumination characteristics. The improved design should be well-suited for effectively illuminating the approach end of an airport runway while ensuring resilience to varying environmental conditions.

### SUMMARY OF PARTICULAR EMBODIMENTS

(5) Embodiments described herein relate to a lighting system.

(6) In particular non-limiting embodiments, the lighting system includes an enclosure having a back section, side sections, a front section having a front mounting frame, an interfacing step extending from or coupled to the side sections and disposed between the front section and the back section, and an outer surface configured to facilitate a heat transfer from the enclosure into an environment of the lighting system. Further, the lighting system includes a conduction frame fastened to the interfacing step to facilitate a heat transfer from the conduction frame to the enclosure through the interfacing step, and one or more light emitting assemblies fastened to the conduction frame, wherein each of the one or more light emitting assemblies has a conduction member and a light source fastened to the conduction member, and wherein the conduction member is configured to facilitate a heat transfer from the light source to the conduction frame. Further, the lighting system includes a front housing assembly fastened to the front mounting frame of the front section to seal the enclosure from the environment of the lighting system.

(7) In particular non-limiting embodiments, the lighting system further includes a universal power supply and electromagnetic interference filter circuit. The universal power supply and/or the electromagnetic interference filter circuit are mounted onto a back wall of the back section inside the enclosure, thereby facilitating a heat transfer from the universal power supply and/or the electromagnetic interference filter circuit to the enclosure.

(8) In particular non-limiting embodiments, the front housing assembly includes a front housing

member having a front housing groove at a back side of the front housing member, the back side of the front housing member facing the one or more light emitting assemblies, and a flexible gasket configured to be inserted into the front housing groove. Further, the front housing assembly includes a flat bezel lens configured to allow a light emitted from the one or more light sources of the one or more light emitting assemblies to exit the enclosure, a nichrome wire heater positioned between the flexible gasket and the flat bezel lens, and a retainer plate being configured to be fastened to the back side of the front housing member causing securing the flat bezel lens, the nichrome wire heater and the flexible gasket to the back side of the front housing member.

(9) In particular non-limiting embodiments, the outer surface of the enclosure includes fins, wherein the fins promote the heat transfer from the enclosure into the environment of the lighting system.

(10) In particular non-limiting embodiments, the enclosure is rotationally coupled to a support member via a hinge member enabling the enclosure to assume an inclined or declined position with respect to a ground level.

(11) In particular non-limiting embodiments, the enclosure is configured to be secured in the inclined or declined position via both a locking mechanism of the hinge member and a secondary locking mechanism, the secondary locking mechanism providing another coupling of the enclosure and the support member.

(12) In particular non-limiting embodiments, the one or more light emitting assemblies are positioned at a plurality of corresponding levels.

(13) In particular non-limiting embodiments, the sealing of the enclosure causes the enclosure to be impervious to dust and capable of resisting water penetration when submerged at a depth of up to one meter.

(14) In particular non-limiting embodiments, a lighting system includes an enclosure, a universal power supply, an electromagnetic interference filter circuit, and a light engine. The light engine includes a plurality of light emitting assemblies. Each light emitting assembly includes a conduction member, a printed circuit board configured to be mounted onto the conduction member at a corresponding inclination angle, one or more light sources configured to be mounted onto the printed circuit board, and a reflector configured to be fastened to the conduction member; and a conduction frame fastened to the plurality of light emitting assemblies and to the enclosure, thereby facilitating a heat transfer from the plurality of light emitting assemblies to the enclosure. Furthermore, any one of the inclination angles corresponding to the printed circuit boards of the plurality of light emitting assemblies is at least one degree different than any other one of the inclination angles.

(15) In particular non-limiting embodiments, the plurality of light emitting assemblies includes at least three light emitting assemblies.

(16) In particular non-limiting embodiments, for each one of the plurality of light emitting assemblies any one of the reflectors has an identical reflector shape as any other one of the reflectors.

(17) In particular non-limiting embodiments, the reflector shape comprises a set of sections, each section from the set of sections configured to reflect a light emitted by a light source adjacent to that section.

(18) In particular non-limiting embodiments, each section from the set of sections includes a curved profile.

(19) In particular non-limiting embodiments, the reflector shape includes a reflective coating formed from a polycarbonate resin.

(20) In particular non-limiting embodiments, the plurality of light emitting assemblies includes first, second, and third light emitting assemblies having corresponding first, second, and third printed circuit boards, mounted at corresponding first, second, and third inclination angles, and wherein the first inclination angle is in a range of 15-20 degrees, the second inclination angle is in a

range of 20-22 degrees, and the third inclination angle is in a range of 22-25 degrees.

(21) In particular non-limiting embodiments, the plurality of light emitting assemblies is mounted between the conduction frame and a back side of the enclosure inside of the enclosure.

(22) In particular non-limiting embodiments, the enclosure includes a front housing assembly configured to seal the enclosure when being fastened to a front mounting frame of a front side of the enclosure.

(23) In particular non-limiting embodiments, the plurality of light emitting assemblies is mounted between the conduction frame and the front housing assembly.

(24) In particular non-limiting embodiments, a lighting system includes an enclosure having a back side, and a front side, the front side including a front mounting frame, a universal power supply, an electromagnetic interference filter circuit, and a conduction frame fastened to the enclosure.

Further, the lighting system includes one or more light emitting assemblies fastened to the conduction frame, wherein each of the one or more light emitting assemblies has a conduction member and a light source fastened to the conduction member, and a front housing assembly configured to seal the enclosure when being fastened to the front mounting frame of the front side. The front housing assembly includes a front housing member having a front housing groove at a back side of the front housing member, the back side of the front housing member facing the one or more light emitting assemblies, a flexible gasket configured to be inserted into the front housing groove, and a flat bezel lens configured to allow a light emitted from the one or more light sources of the one or more light emitting assemblies to exit the enclosure. Further, the front housing assembly includes a nichrome wire heater positioned between the flexible gasket and the flat bezel lens, and a retainer plate being configured to be fastened to the back side of the front housing member causing securing the flat bezel lens, the nichrome wire heater and the flexible gasket to the back side of the front housing member.

(25) In particular non-limiting embodiments, the nichrome wire heater is configured to regulate a temperature of the flat bezel lens, ensuring required transparency of the flat bezel lens.

(26) In particular non-limiting embodiments, the front mounting frame of the front side includes a front side groove having a selected profile, the lighting system further comprising a flexible O-ring having a circular profile and configured to be inserted into the front side groove, such that at least a portion of the flexible O-ring is extending beyond the front side groove, and wherein the fastening of the front housing assembly to the front mounting frame of the front side includes at least partially compressing the flexible O-ring.

(27) The embodiments disclosed herein are only examples, and the scope of this disclosure is not limited to them. Particular embodiments may include all, some, or none of the components, elements, features, functions, operations, or steps of the embodiments disclosed herein. The dependencies or references back in the attached claims are chosen for formal reasons only.

However, any subject matter resulting from a deliberate reference back to any previous claims (in particular multiple dependencies) can be claimed as well, so that any combination of claims and the features thereof are disclosed and can be claimed regardless of the dependencies chosen in the attached claims. The subject-matter which can be claimed comprises not only the combinations of features as set out in the attached claims but also any other combination of features in the claims, wherein each feature mentioned in the claims can be combined with any other feature or combination of other features in the claims. Furthermore, any of the embodiments and features described or depicted herein can be claimed in a separate claim and/or in any combination with any embodiment or feature described or depicted herein or with any of the features of the attached claims.

---

## Description

## BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an illustrative exploded view of a lighting system, in accordance with disclosed embodiments.
- (2) FIGS. 2A-2C are illustrative views of an enclosure, in accordance with disclosed embodiments.
- (3) FIGS. 3A and 3B are illustrative implementations of an interface between a front housing assembly and an enclosure, in accordance with disclosed embodiments.
- (4) FIG. 4A-4B are illustrative views of a lighting system, in accordance with disclosed embodiments.
- (5) FIG. 5A-5C are other illustrative views of an enclosure of a lighting system containing electrical components, in accordance with disclosed embodiments.
- (6) FIG. 6 is an illustrative exploded view of a lighting system, in accordance with disclosed embodiments.
- (7) FIGS. 7A-7B are illustrative view of a light engine of a lighting system, in accordance with disclosed embodiments.
- (8) FIGS. 8A-8B are other illustrative view of a light engine of a lighting system, in accordance with disclosed embodiments.
- (9) FIGS. 9A-9C are illustrative view of components of a light emitting assembly of a light engine, in accordance with disclosed embodiments.
- (10) FIGS. 10A-10B are illustrative view of components of a front housing assembly of a lighting system, in accordance with disclosed embodiments.

## DESCRIPTION OF EXAMPLE EMBODIMENTS

- (11) In the following description, for the purposes of explanation, numerous specific details are set forth to provide a thorough understanding of the present disclosure. It will be apparent, however, that embodiments of the present disclosure may be practiced without these specific details.
- (12) Various embodiments may be described in this disclosure to illustrate various aspects. Other embodiments may be utilized and structural, electrical, and other changes may be made without departing from the scope of the embodiments that are specifically described. Various modifications and alterations are possible and expected. Some features may be described with reference to one or more embodiments or drawing figures, but such features are not limited to usage in the one or more embodiments or figures with reference to which they are described. Thus, the present disclosure is neither a literal description of all embodiments nor a listing of features that must be present in all embodiments.
- (13) Spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element's or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.
- (14) Terms such as “same,” “equal,” “planar,” or “coplanar,” as used herein when referring to orientation, layout, location, position, shapes, sizes, amounts, or other measures do not necessarily mean an exactly identical orientation, layout, location, position, shape, size, amount, or other measure, but are intended to encompass nearly identical orientation, layout, location, position, shapes, sizes, amounts, or other measures within acceptable variations that may occur, for example, due to manufacturing processes. The term “substantially” may be used herein to emphasize this meaning, unless the context or other statements indicate otherwise. For example, items described as “substantially the same,” “substantially equal,” or “substantially planar,” may be exactly the same,

equal, or planar, or may be the same, equal, or planar within acceptable variations that may occur, for example, due to manufacturing processes.

(15) Terms such as “about” or “approximately” may reflect sizes, orientations, or layouts that vary only in a small relative manner, and/or in a way that does not significantly alter the operation, functionality, or structure of certain elements. For example, a range from “about 0.1 to about 1” may encompass a range such as a 0%-10% deviation around 0.1 and a 0% to 10% deviation around 1, especially if such deviation maintains the same effect as the listed range. Moreover, as an example, the expression “about 20 degrees” encompasses all degree values within the range of 18 to 22 degrees.

(16) Embodiments described herein relate to a lighting system that can be used for approach lighting. Such lighting system can be designed to illuminate an approach end of an airport runway. The design of approach lighting systems necessitates a careful consideration of key engineering principles to ensure optimal performance and longevity in various environmental conditions. One critical aspect is the need for lightweight construction, which is essential to minimize structural load and facilitate easy installation. Additionally, hermetic sealing is a fundamental requirement to safeguard the internal components from moisture, dust, and other potentially damaging elements. This protective measure not only ensures the longevity of the system but also contributes to its reliability by preventing corrosion and electrical malfunctions. Robustness in the face of diverse environmental challenges, including extreme temperatures, precipitation, and exposure to UV radiation, is equally crucial. The design must account for materials and coatings that withstand these conditions, promoting durability and sustained functionality. In essence, a well-crafted approach lighting system demands a harmonious integration of lightweight design, hermetic scaling, and robust engineering to meet the demanding standards of aviation safety and operational excellence.

(17) An example exploded view of a lighting system **100** is shown in FIG. 1. The system includes an enclosure **110** having a back section **111**, side sections **112**, a front section **113** having a front mounting frame **114**, an interfacing step **115** extending from or coupled to side sections **112** and disposed between front section **113** and back section **111**, and an outer surface **116** of enclosure **110** configured to facilitate a heat transfer from enclosure **110** into an environment of the lighting system **100**.

(18) Further, lighting system **100** includes a conduction frame **120** fastened to interfacing step **115** to facilitate heat transfer from conduction frame **120** to enclosure **110** through interfacing step **115**. Additionally, lighting system **100** includes one or more light emitting assemblies **130** fastened to conduction frame **120**, wherein one or more light emitting assemblies **130** has corresponding conduction members **131** and light sources **132** fastened to conduction members **131**. Each one of conduction members **131** is configured to facilitate a heat transfer from light sources **132** to conduction frame **120**. In various embodiments, conduction frame **120** and one or more light emitting assemblies **130** fastened to it form a light engine **135** for lighting system **100**.

(19) Furthermore, lighting system **100** includes a front housing assembly **140** fastened to front mounting frame **114** of front section **113** to seal enclosure **110** from the environment of lighting system **100**. Additionally, lighting system **100** may include a power supply **150**, which may be, for example, a universal power supply, and can be adaptable to provide power to different configurations of light engines **135**. Furthermore, lighting system **100** may include an electromagnetic interference filter circuit **160** configured to prevent various electrical components of lighting system **100** to be influenced by electromagnetic radiation from the environment of lighting system **100**.

(20) In various embodiments, enclosure **110** is configured to house most of the components of lighting system **100**, such as light engine **135**, power supply **150**, and electromagnetic interference filter circuit **160**. Enclosure **110** can be formed from any suitable structurally stable and thermally conductive material, such as aluminum, plastic, steel, stainless steel, aluminum alloy, die-cast

aluminum, titanium, fiberglass, acrylic, polycarbonate, thermoplastic, or any suitable metallic, plastic, or composite material. In some cases, enclosure **110** may be partially or entirely made of flexible materials such as rubber, flexible plastic, or fabric (e.g., fiberglass fabric).

(21) As shown in FIG. **1**, enclosure **110** is selected to have generally rectangular cross-section. FIGS. **2A-2C** show different views of enclosure **110**. For example, FIG. **2A** shows a three-dimensional view of enclosure **110** as viewed from the back side, FIG. **2B** shows a side view of enclosure **110** (as viewed from the right side of enclosure **110**), and FIG. **2C** shows the top view of enclosure **110**. As seen from FIGS. **2A-2C**, enclosure **110** includes fins **117A** located at the top side of enclosure **110**, fins **117B** located at sides of enclosure **110**, and fins **117C** located at the back side of enclosure **110**. Fins **117A-117C** primarily facilitate convective heat transfer from enclosure **110** to the environment surrounding lighting system **100**, although some conductive heat transfer may also occur.

(22) In several embodiments, fins **117A-117C** serve dual functions by not only offering surfaces for a convective heat transfer but also enhancing the structural dexterity of enclosure **110**. Illustrated in an exemplary embodiment, as depicted in FIGS. **1-2C**, fins **117A-117C** are seamlessly integrated into enclosure **110**. In this scenario, enclosure **110** could be manufactured, for instance, by shaping a single metallic or plastic sheet, thereby creating fins **117A-117C** as an integral part of the same metal or plastic sheet. This integration not only streamlines the manufacturing process but also reinforces the structural integrity of both the fins and the overall enclosure.

(23) Further, as shown in FIGS. **2A-2C**, enclosure **110** includes front mounting frame **114** to which front housing assembly **140** is attached as further described below. Similarly, to fins **117A-117C**, front mounting frame **114** may be seamlessly integrated into enclosure **110**, for example, by shaping a single metallic or plastic sheet, thereby creating front mounting frame **114** as an integral part of enclosure **110**.

(24) Furthermore, enclosure **110** may incorporate regions containing threaded openings, such as regions **118A** and **118B** which are configured to receive suitable fasteners, such as bolts or screws for fastening different components of lighting system **100** to enclosure **110**.

(25) Returning to FIG. **1**, various sides/sections of enclosure **110** (e.g., back section **111**, side sections **112**, and front section **113**) are configured to transfer heat to an environment of lighting system **100**, and at the same time, serve as surfaces or regions for fastening different components of lighting system **100**. For example, a back side **111A** of back section **111** may be used for mounting at least some of the electrical components of lighting system **100**, such as for example, power supply **150**, and/or electromagnetic interference filter circuit **160**.

(26) In one implementation, power supply **150** may be first mounted to back side **111A** of back section **111** of enclosure **110**, while electromagnetic interference filter circuit **160**, may then be mounted over power supply **150**. Alternatively, electromagnetic interference filter circuit **160**, may be mounted onto back side **111A**, while power supply **150** may then be mounted over electromagnetic interference filter circuit **160**. In some configurations, both power supply **150** and electromagnetic interference filter circuit **160** may be mounted onto back side **111A** of back section **111** of enclosure **110**. In some cases, when mounting electrical components (e.g., power supply **150** or electromagnetic interference filter circuit **160**) over any of the internal surfaces of enclosure **110**, these components may include large surface areas in which they are in contact with internal surfaces of enclosure **110**, thereby ensuring an adequate heat transfer from these components to sides of enclosure **110**. In some cases, the heat transfer may be further facilitated by using a thermal grease between heat conductive surfaces of electronic components of lighting system **100** and internal surfaces of enclosure **110**. In some cases, the surfaces of electronic components may include protrusions or cavities configured to be inserted into corresponding cavities or protrusion within internal surfaces of enclosure **110**, thereby facilitating heat transfer between the electronic components and enclosure **110**.

(27) In various embodiments, enclosure **110** features an interfacing step **115** extending from the



side sections **112** of enclosure **110**, as depicted in FIG. 1. This interfacing step **115** serves as an element to which conduction frame **120** may be affixed. Specifically, conduction frame **120** can be securely attached to threaded openings **115A** of interfacing step **115** using appropriate fasteners such as bolts or screws. Notably, certain regions of the surfaces of conduction frame **120** are designed to be in close contact with and flushed adjacent to the surfaces of interfacing step **115**. Such design facilitates the efficient heat transfer from conduction frame **120** to interfacing step **115**. In certain instances, a thermal grease may be applied to an interface between the conduction frame **120** and interfacing step **115** to enhance heat conductivity, promoting optimal heat transfer between the two components.

(28) Conduction frame **120** can be constructed from a variety of materials chosen for their excellent heat conductivity properties. Suitable materials include, but are not limited to, aluminum, aluminum alloys, copper, copper alloys, stainless steel, and thermoplastics. These materials are selected based on their ability to efficiently transfer heat, contributing to the overall thermal management of the system. Additionally, the choice of material depends on factors such as the specific requirements of the application, durability, heat expansion, weight considerations, and cost-effectiveness. The flexibility to use diverse materials underscores the adaptability of conduction frame **120** to different thermal challenges in various contexts.

(29) As described above, conduction frame **120** and one or more light emitting assemblies **130** fastened to conduction frame **120** form light engine **135**. An example light emitting assembly **130** may include an assembly of conduction members **131**, one or more reflectors **133** and one or more light sources **132**. In various embodiments, conduction members **131** are configured to support one or more light sources **132** and one or more reflectors **133**. In various embodiments, one or more light sources **132** may be mounted onto conduction members **131**. In some configuration, one or more light sources **132** may be mounted onto one or more printed circuit boards, and the printed circuit boards may be attached to conduction members **131**. Further, reflectors **133** may also be fastened or otherwise attached to conduction members **131**.

(30) Conduction members **131** may be any suitable elements configured to support one or more light sources **132**, one or more reflectors **133**, and/or a printed circuit board. Further, conduction members **131** are configured to be attached to conduction frame **120**, such that the heat generated by one or more light sources **132** is conducted from the one or more light sources **132** towards and into conduction frame **120**. In various example embodiments, conduction members **131** may be formed from a material capable of conducting heat, such as metal. In some cases, conduction members **131** may be formed from any suitable heat conducting material such as aluminum, aluminum alloys, copper, copper alloys, stainless steel, and thermoplastics, among others. These materials are selected based on their ability to efficiently transfer heat, contributing to the overall thermal management of the system. Additionally, the choice of material depends on factors such as the specific requirements of the application, durability, heat expansion, weight considerations, and cost-effectiveness.

(31) In some embodiments, conduction members **131** may be fastened to conduction frame **120** using any suitable fasteners, such as bolts or screws. In some cases, a thermal grease may be used when fastening conduction members **131** and conduction frame **120** to improve heat conductivity at the interface of conduction members **131** and conduction frame **120**. In some cases, conduction members **131** and conduction frame **120** may be formed from the same sheet of metal, thereby improving heat conductivity from one or more light sources **132** to conduction frame **120**. In some cases, conduction members **131** may be welded to conduction frame **120**.

(32) In various embodiments, when conduction frame **120** is fastened to interfacing step **115**, light engine **135** is secured within enclosure **110**. To protect the electronic components (e.g., power supply **150**, electromagnetic interference filter circuit **160**, and light engine **135**), enclosure **110** may be sealed by fastening front housing assembly **140** to front mounting frame **114** of front section **113**. Front housing assembly **140** may be fastened to front mounting frame **114** via suitable

fasteners **141** (e.g., bolts or screws) configured to be fastened to threaded openings within front mounting frame **114**. When fastening front mounting frame **114**, a flexible O-ring **142** may be placed in a front side groove **119** of front mounting frame **114**, such that flexible O-ring **142** is positioned partially within and between front mounting frame **114** and front housing assembly **140**. (33) FIG. 3A presents a cross-sectional view illustrating an exemplary configuration of the lighting system **100**, where front housing assembly **140** is securely fastened to front mounting frame **114** utilizing a fastener **141**. In this specific implementation, front side groove **119** accommodates flexible O-ring **142**, which can be compressed by front housing assembly **140** during the attachment process to front mounting frame **114**. Alternatively, as depicted in FIG. 3B, an alternative arrangement involves the inclusion of a groove **119A** within front housing assembly **140**. This design allows flexible O-ring **142** to maintain its more or less uncompressed form within grooves **119** and **119A** while front housing assembly **140** being affixed to the front mounting frame **114** using fastener **141**.

(34) Flexible O-ring **142** can adopt various cross-sectional profiles, including circular, rectangular, square, elliptical, and others. In certain instances, as illustrated in FIG. 3A, when inserted into the front side groove **119**, a portion of flexible O-ring **142** may extend beyond front side groove **119**. Consequently, during the fastening of front housing assembly **140** to front mounting frame **114**, there is a partial compression of flexible O-ring **142**.

(35) Flexible O-ring **142** can be composed of suitable materials such as rubber, flexible plastics, or equivalent materials. Notably, in one implementation, the chosen material for flexible O-ring **142** is engineered to withstand environmental factors, including humidity and exposure to chemicals such as fuel gases, while maintaining its flexibility over time. In some cases, flexible O-ring **142** may include one or more cavities, and/or can be formed from a composite material. For example, flexible O-ring **142** may include structural flexible threads forming from any suitable flexible material, such as plastic, metal, fiberglass, and the like.

(36) As shown in FIG. 1, front housing assembly **140** includes a window **143** configured to transmit light emitted by one or more light sources **132** into the environment of lighting system **100**. Window **143** may be formed from any suitable material transparent to light emitted from light sources **132**. For example, window **143** may be made from transparent plastic, transparent glass, or any other suitable transparent material (e.g., quartz, sapphire, and the like). In some cases, window **143** may include suitable light guiding elements (e.g., optical elements) integrated into window **143** and configured to direct or otherwise distribute light from one or more light sources **132**. For instance, such light guiding elements may include curved or flat lenses, such as bezel lenses, prisms, reflectors, diffraction gratings, combination thereof, and the like. In some cases, the light guiding elements may be located adjacent to window **143**. For instance, such light guiding elements may be positioned between light engine **135** and window **143**.

(37) In various embodiments, enclosure **110** of lighting system **100** may be rotationally coupled to a support member **170** via a hinge member **171** enabling enclosure **110** to assume an inclined or declined position with respect to a ground level. Enclosure **110** may be configured to be secured in the inclined or declined position via both a locking mechanism of hinge member **171** and a secondary locking mechanism **173**. In various cases, secondary locking mechanism **173** may provide another coupling of enclosure **110** and support member **170**, thereby providing an additional structural joint between enclosure and support member **170**. For example, second locking mechanism **173** may be attached to support member **170** using a fastener **172A** and attached to enclosure **110** using a fastener **172B**. In some cases, secondary locking mechanism **173** can secure enclosure **110** in a specific orientation relative to the ground level. This includes adjusting its inclination or decline, and even swiveling it left, right, or both.

(38) While FIG. 1 provides the exploded view of lighting system **100**, FIG. 4A provides a three-dimensional view of lighting system **100** when it is completely assembled. As shown in FIG. 4A, the lighting system **100** includes enclosure **110**, support member **170** for supporting enclosure **110**,

secondary locking mechanism **173**, front housing assembly **140** being fastened to front mounting frame **114** via fasteners **141**, and elements of light engine **135** seen through window **143** of front housing assembly **140**. Further, FIG. **4B** shows a cross-sectional view of lighting system **100**. As shown in FIG. **4B**, lighting system **100** includes enclosure **110**, front housing assembly **140** having transparent window **143** and attached to enclosure **110** via fasteners **141**, support member **170**, and secondary locking mechanism **173**. Further, within enclosure **110**, FIG. **4B** shows a portion of conduction frame **120**, a portion of light engine **135**, a power supply **150**, and electromagnetic interference filter circuit **160** fastened to back side **111A** of back section **111**.

(39) FIGS. **5A-5C** offer perspective views of the electrical components housed within the enclosure **110**. In particular, FIG. **5A** presents a three-dimensional exploded view, showing the internal arrangement of enclosure **110** along with the presence of power supply **150** and electromagnetic interference filter circuit **160**. Notably, a pole **175** is featured, strategically positioned for attaching the enclosure **110** to the support member **170** (although support member **170** is not depicted in FIG. **5A**).

(40) FIG. **5B** shows an alternative view of enclosure **110** depicting internal components including power supply **150** and electromagnetic interference filter circuit **160**. This internal perspective is presented without the front housing assembly **140**, allowing for a detailed examination of the electrical elements. Further, FIG. **5C** offers a frontal view of enclosure **110**, providing insight into its internal structure while omitting the front housing assembly **140**. These various views collectively contribute to a comprehensive understanding of the electrical configurations and structural nuances within the enclosure **110** of lighting system **100**.

(41) Another exploded view of lighting system **100** is shown in FIG. **6**. Lighting system **100** includes enclosure **110**, support member **170**, secondary locking mechanism **173**, electronic components such as power supply **150**, front housing assembly **140** configured to be fastened to front mounting frame **114**, and light engine **135**.

(42) Light engine **135** includes conduction frame **120** configured to be fastened to interface step **115**, and several conduction members **131A-131C** configured to support light sources **132A-132C** and reflectors **133A-133C**, as well as to facilitate heat transfer from light sources **132A-132C** and various electronic components of light engine **135** to conduction frame **120**. While three conduction members **131A-131C** are shown, in some cases, light engine **135** may have fewer than three conduction members, and in other cases, light engine **135** can have more than three conduction members.

(43) The thickness and material selection for conduction members **131A-131C** play an important role in achieving the necessary heat management for the optimal functioning of light engine **135**. Specifically, in certain instances, these parameters are chosen to regulate the temperature of light sources **132A-132C** within the prescribed acceptable range.

(44) As previously outlined, the combination of a conduction member, one or more light sources, and a reflector constitutes a light emitting assembly. Illustrated in FIG. **6**, light engine **135** exemplifies this configuration, featuring three distinct light emitting assemblies.

(45) In various embodiments, the design of light engine **135** can be adaptable, and in certain scenarios, it may include more than three light emitting assemblies. Such configuration may allow for redundancy within the system, mitigating potential issues arising from the failure or overheating of individual light emitting assemblies. For instance, in cases where redundancy is incorporated, if one operational light emitting assembly experiences overheating, a redundant light emitting assembly can seamlessly take over, while the overheated unit is temporarily deactivated, enabling it to cool down before reengagement. This approach ensures the continued functionality and reliability of light engine **135** under varying operational conditions.

(46) In illustrative embodiment of the light engine **135** is shown in FIGS. **7A-7B**, **8A-8B**, and **9A-9C**. FIG. **7A** presents an exploded three-dimensional perspective, depicting various components of the light engine **135**. These components include conduction members **131A-131C**, reflectors of the

light emitting assemblies (e.g., reflector **133A** in FIG. 7A), and the conduction frame **120**, to which conduction members **131A-131C** are affixed. In a specific implementation, conduction members **131A-131C** incorporate threaded openings, such as opening **138A**, aligned with an opening **128** of the conduction frame **120**. This alignment facilitates the insertion of a fastener **128A** into opening **128**, securely attaching it to threaded opening **138A**, thereby effecting the robust fastening of the conduction frame **120** to conduction member **131A**. It is noteworthy that, in certain instances, opening **128** may also feature threading, enhancing the stability of the attachment.

(47) In various embodiments, reflectors of light engine **135**, such as reflector **133A**, as shown in FIG. 7A, may be mounted onto respective conduction members (e.g., reflector **133A** is mounted onto conduction member **131A**) using suitable fasteners such as fasteners **134A** and **136A**, which may include bolts or screws. In some cases, fasteners **134A** and **136A** include washers, or any other suitable elements for facilitating accurate positioning of reflector **133A** relative to conduction member **131A**. For example, suitable washers may be used for selecting a vertical positioning of reflector **133A** relative to conduction member **131A**.

(48) FIG. 7B shows a side view of light engine **135** including conduction frame **120**, conduction members **131A-131C**, light sources **132A-132C**, and reflectors **133A-133C**. As described above, light sources **132A-132C** and reflectors **133A-133C** are configured to be mounted onto respective conduction members **131A-131C**.

(49) FIG. 8A shows a three-dimensional view of the light engine **135**, featuring three distinct light emitting assemblies, denoted as **130A-130C**. The complementary FIG. 8B provides a front-facing perspective of the light engine **135**, highlighting the arrangement of the three light emitting assemblies.

(50) Examining FIG. 8A, the conduction frame **120** exhibits a first side (referred to as side 1). This side is positioned within the enclosure **110**, facing the back side **111A** of the back section **111**. Additionally, conduction frame **120** includes a second side (side 2), oriented to face the window **143** of the front housing assembly **140**. It is important to note that in FIG. 8B, the light sources **132A-132C** and reflectors **133A-133C** are situated on side 2 of the conduction frame **120**. This configuration ensures that the light emitted by the light sources **132A-132C** is directed towards the window **143**, contributing to the effective illumination and functionality of the lighting system.

(51) FIG. 9A shows an example light emitting assembly **130A** which includes conduction member **131A**, light sources **132A**, reflector **133A** coupled to conduction member **131A** via bolts **134A** and **136A**. Further, as shown in FIG. 9A, conduction member **131A** includes a threaded opening **138A** which can be used for fastening conduction member **131A** to conduction frame **120**.

(52) Note that in the implementation of light emitting assembly **130A**, as shown in FIG. 9A, three light sources are used as light sources **132A**. In various embodiments, light sources **132A** may include any suitable number of individual light sources. For example, light sources **132A** may include one, two, three, four, five, or more light sources. Furthermore, light sources **132A** may be any suitable light sources of any suitable light. For example, when light sources **132A** are configured to emit visible light, such light sources may be light emitting diodes, incandescent bulbs, fluorescent bulbs, or any other suitable light sources activated by an electrical current and/or voltage. Light sources **132A** (or any other light sources of light engine **135**) may emit at any suitable visible wavelength. For example, such light sources may be configured to emit at wavelengths ranging between purple (e.g., wavelength of about 380-450 nanometers (nm)) to red wavelengths of about 700 nm).

(53) Furthermore, in some cases, light sources **132A** may be configured to emit at a wavelength that is not visible to a human eye (e.g., infrared wavelength, ultraviolet wavelength, microwave wavelength, radio-frequency wavelength, and the like).

(54) Reflectors, such as reflector **133A** may be made from any suitable material, such as metal, plastic, or any other suitable material capable of reflecting light emitted by light sources **132A**. In some cases, reflectors may include coatings configured to facilitate reflection of light from reflector

**133A**. For instance, a coating can be a thin metal coating, a thin plastic coating (e.g., polycarbonate resin), or any other coating, which in some cases can include multiple coating layers forming a reflective mirror. Such coating layers may have a thickness on the order of a wavelength of emitted light from light sources **132A**, or a fraction of the wavelength. Specific design of the coating may be selected based on the wavelength of light for light sources **132A**. For example, the coating layers may be selected to form a Bragg reflector.

(55) In various cases, reflector **133A** (or any other reflector of light engine **135**) may include several sections such as sections **R1**, **R2**, and **R3**, as shown in FIG. **9C**. Each section may be dedicated for reflecting light from a particular light source **L1**, **L2**, and **L3**, as shown in FIG. **9B**. Each section may include a curved reflective surface which can have a selected profile. For example, reflector **133A** includes surfaces **S1**, **S2**, and **S3**, as shown in FIG. **9A**. In an example implementation, profiles for surfaces may be parabolic, spherical, or any other suitable shape. In some cases, sections of reflector **133A** may be positioned relative to light sources **L1**, **L2**, and **L3**, such that these light sources are placed close to corresponding focal points of these reflector sections. Alternatively, light sources **L1**, **L2**, and **L3**, may be placed in regions that are not necessarily close to those focal points.

(56) As shown in FIGS. **9B** and **9C**, light sources **L1**, **L2**, and **L3** may be mounted on a printed circuit board **139A**. In turn, printed circuit board **139A** is configured to be mounted onto conduction member **131A** such that there is an inclination angle **137A**, as shown in FIG. **9B** formed between a plane of circuit board **139A** and a ground level. Angle **137A** may be defined as  $\arccos(N_{sub.1} \cdot N_{sub.2})$ , where  $N_{sub.1}$  is a unit normal vector to a plane of circuit board **139A**,  $N_{sub.2}$  is a unit normal vector to a plane corresponding to a ground level, and  $N_{sub.1} \cdot N_{sub.2}$  is a dot product between vectors  $N_{sub.1}$  and  $N_{sub.2}$ .

(57) FIG. **9B** shows that reflector **133A** may further include pin legs **P1** and **P2** configured to penetrate openings within printed circuit board **139A**, and optionally, openings within conduction member **131A**. Use of pin legs **P1** and **P2** can help secure reflector **133A** to conduction member **131A** and ensure secure attachment of circuit board **139A** to conduction member **131A** when reflector **133A** is fastened using fasteners **134A** and **136A**, as shown in FIGS. **9A-9C**.

(58) While FIGS. **9A-9C**, shows a particular light emitting assembly **130A**, various assemblies of light engine **135** include similar elements, such as conduction members **131A-131C**, reflectors **133A-133C** having sections, multiple light sources for each light emitting assembly **130A-130C**, and circuit boards mounted at inclination angles corresponding to respective light emitting assemblies,

(59) In an example implementation, light engine **135** includes several light emitting assemblies, such as three light emitting assemblies **130A-130C** as indicated in FIG. **8A**. In various implementations of light engine **135**, any one of the inclination angles for any one of light emitting assemblies **130A-130C** is configured to be at least one degree different than any other one of the inclination angles for any other one of light emitting assemblies **130A-130C**. For example, a first inclination angle for light emitting assembly **130A** (e.g., inclination angle **137A**) may be in a range of 15-20 degrees, a second inclination angle for light emitting assembly **130B** may be in a range of 20-22 degrees, and a third inclination angle for light emitting assembly **130C** may be in a range of 22-25 degrees. In some cases, the first inclination angle may be about 18 degrees, the second inclination angle may be about 20 degrees, and the third inclination angle may be about 23 degrees. Alternatively, in some cases, the first inclination angle may be about 18 degrees, the second inclination angle may be about 21 degrees, and the third inclination angle may be about 24 degrees. Furthermore, in some cases, the first inclination angle may be about 13 degrees, the second inclination angle may be about 18 degrees, and the third inclination angle may be about 20 degrees.

(60) In one example implementation, the first inclination angle may be 18 degrees, the second inclination angle may be 20.5 degrees, and the third inclination angle may be 23 degrees. In another example implementation, the first inclination angle may be 13 degrees, the second

inclination angle may be 20 degrees, and the third inclination angle may be 24.25 degrees. In yet another example implementation, the first inclination angle may be 18 degrees, the second inclination angle may be 21.75 degrees, and the third inclination angle may be 24.25 degrees.

(61) As shown, for example, in FIG. 8A, light emitting assemblies **130A-130C** may be positioned at different levels. For example, light emitting assembly **130A** may be at a top level above light emitting assembly **130B**, while light emitting assembly **130C** may be at a bottom level below light emitting assembly **130B**. In some cases, vertical spacing between different levels may be configured to be the same.

(62) In some implementations the inclination angle selected for the lowest positioned light emitting assembly (e.g., light emitting assembly **130C**) may be the highest, and the inclination angle selected for the highest positioned light emitting assembly **130A** may be the lowest. In some implementations the difference between the highest inclination angle and the lowest inclination angle can be in a range of one to five degrees.

(63) In some implementations, reflectors **133A-133C** may have the same shape. For example, reflectors **133A-133C** may include three sections **R1-R3**, as shown in FIGS. 9B and 9C, each section having the same shape as any other section. In an example embodiment, a section, such as section **R1**, may have a substantially parabolic shape, and a corresponding light source, such as light source **L1**, may be placed at about a focal point corresponding to reflective section **R1**. In various embodiments, the number of sections for reflectors of the light emitting assembly may correspond to the number of light sources for that light emitting assembly.

(64) In various implementations, light emitting assemblies **130A-130C** may be mounted, such that conduction members **131A-131C** are attached to the conduction frame **120** from the first side (side 1) as shown, for example, in FIG. 8A. Such mounting results in light emitting assemblies being mounted between conduction frame **120** and back side **111A** of back section **111** of enclosure **110**, and inside enclosure **110**. Alternatively, light emitting assemblies may be mounted such that conduction members **131A-131C** are attached to the conduction frame **120** from the second side (side 2). Using such mounting, the light emitting assemblies are positioned between conduction frame **120** and front housing assembly **140**.

(65) In various embodiments, lighting system **100** includes front housing assembly **140** configured to seal enclosure **110** when being fastened to front mounting frame **114** of front section **113** of enclosure **110**. An illustrative exploded view of front housing assembly **140** is shown in FIGS. 10A and 10B. FIG. 10A shows a three-dimensional exploded view of front housing assembly **140** as seen from the direction of a first side (side 1) that faces back side **111A** of back section **111** of enclosure **110**, while FIG. 10B shows a three-dimensional exploded view of front housing assembly **140** as seen from the direction of a second side (side 2) that faces outwards from enclosure **110**.

(66) Front housing assembly **140** includes a front housing member **144** having a front housing groove **145** at a back side (side 1) of front housing member **144**, where the back side of front housing member **144** is configured to face back side **111A** of back section **111** of enclosure **110**, as well as light engine **135** having one or more light emitting assemblies, such as light emitting assemblies **130A-130C**.

(67) In various implementations, a flexible gasket **147** is configured to be inserted into the front housing groove **145**, thus, providing a flexible interface between front housing member **144** and a transparent member **143A** forming a transparent window **143**. The front housing groove **145** may have any suitable cross-sectional profile such as circular profile, rectangular profile, elliptical profile and the like. Flexible gasket **147** may include similar profile, such that it can be inserted into housing groove **145**. Flexible gasket **147** may be made from any suitable flexible material such as flexible plastic or rubber. In one illustrative implementation, flexible gasket **147** may be made from the same material as O-ring **142**.

(68) Transparent member **143A** may be any suitable light transmissive element, such as a flat

transparent plate, a flat bezel lens, a curved lens, and the like. In various implementations, transparent member **143A** is configured to allow a light emitted from the one or more light sources of the one or more light emitting assemblies to exit enclosure **110** via transparent window **143**.

(69) Further, front housing assembly **140** may include a heating wire **146**, which in some cases may be a nichrome wire heater positioned between flexible gasket **147** and transparent member **143A**. Heating wire **146** may be configured to regulate a temperature of transparent member **143A** ensuring required transparency of transparent member **143A**. Heating wire **146** may provide heating to front housing assembly **140** to ensure that front housing assembly **140** does not accumulate moisture that can reduce transparent properties of transparent member **143A**.

(70) Additionally, front housing assembly **140** includes a retainer plate **148** being configured to be fastened to the back side (side 1) of front housing member **144** via fasteners **149** causing securing transparent member **143A**, such as flat bezel lens, heating wire **146** and flexible gasket **147** to the back side of front housing member **144**.

(71) In various embodiments, front housing assembly **140** configured to seal enclosure **110** such that enclosure **110** is impervious to dust and capable of resisting water penetration when submerged at a depth of up to one meter. The design of front housing assembly **140** strategically positions flexible gasket **147** and heating wire **146** on the inside of enclosure **110**, where they are sealed from the environment by transparent member **143A**. Transparent member **143A** is securely attached to the front housing member **144** using retainer plate **148**.

(72) The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements, feature, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative. Additionally, although this disclosure describes or illustrates particular embodiments as providing particular advantages, particular embodiments may provide none, some, or all of these advantages.

(73) Herein, “or” is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A or B” means “A, B, or both,” unless expressly indicated otherwise or indicated otherwise by context. Moreover, “and” is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A and B” means “A and B, jointly or severally,” unless expressly indicated otherwise or indicated otherwise by context.

## Claims

1. A lighting system comprising: an enclosure having a back section, side sections, a front section having a front mounting frame, an interfacing step extending from or coupled to the side sections and disposed between the front section and the back section, and an outer surface configured to facilitate a heat transfer from the enclosure into an environment of the lighting system; a conduction frame fastened to the interfacing step to facilitate a heat transfer from the conduction frame to the enclosure through the interfacing step, wherein the conduction frame has a first side

facing the back section, a second side facing the front section of the enclosure, and a central opening; one or more light emitting assemblies fastened to the conduction frame, wherein each of the one or more light emitting assemblies has a conduction member and a light source fastened to the conduction member, wherein the conduction member is fastened to the first side of the conduction frame, and the light source attached to the conduction member is situated on the second side of the conduction frame to direct light toward the front section of the enclosure, wherein the conduction member is configured to facilitate a heat transfer from the light source to the conduction frame; and a front housing assembly fastened to the front mounting frame of the front section to seal the enclosure from the environment of the lighting system.

2. The lighting system of claim 1, further comprising: a universal power supply; and electromagnetic interference filter circuit; and wherein at least one of the universal power supply or the electromagnetic interference filter circuit is mounted onto a back wall of the back section inside the enclosure, thereby facilitating a heat transfer from the at least one of the universal power supply or the electromagnetic interference filter circuit to the enclosure.

3. The lighting system of claim 1, wherein the front housing assembly includes: a front housing member having a front housing groove at a back side of the front housing member, the back side of the front housing member facing the one or more light emitting assemblies; a flexible gasket configured to be inserted into the front housing groove; a flat bezel lens configured to allow a light emitted from the one or more light sources of the one or more light emitting assemblies to exit the enclosure; a nichrome wire heater positioned between the flexible gasket and the flat bezel lens; and a retainer plate being configured to be fastened to the back side of the front housing member causing securing the flat bezel lens, the nichrome wire heater and the flexible gasket to the back side of the front housing member.

4. The lighting system of claim 1, wherein the outer surface of the enclosure includes fins, wherein the fins promote the heat transfer from the enclosure into the environment of the lighting system.

5. The lighting system of claim 1, wherein the enclosure is rotationally coupled to a support member via a hinge member enabling the enclosure to assume an inclined or declined position with respect to a ground level.

6. The lighting system of claim 5, wherein the enclosure is configured to be secured in the inclined or declined position via both a locking mechanism of the hinge member and a secondary locking mechanism, the secondary locking mechanism providing another coupling of the enclosure and the support member.

7. The lighting system of claim 1, wherein the one or more light emitting assemblies are positioned at a plurality of corresponding levels.

8. The lighting system of claim 1, wherein the sealing of the enclosure causes the enclosure to be impervious to dust and capable of resisting water penetration when submerged at a depth of up to one meter.

9. A lighting system comprising: an enclosure having a back section, side sections, and a front section; a universal power supply; an electromagnetic interference filter circuit; a light engine including: a plurality of light emitting assemblies, each one comprising: a conduction member; a printed circuit board configured to be mounted onto the conduction member at a corresponding inclination angle; one or more light sources configured to be mounted onto the printed circuit board; and a reflector configured to be fastened to the conduction member; and a conduction frame having a first side facing the back section, a second side facing the front section of the enclosure, and a central opening, wherein the conduction frame is fastened to the plurality of light emitting assemblies and to the enclosure, thereby facilitating a heat transfer from the plurality of light emitting assemblies to the enclosure, wherein the conduction member of each of the plurality of light emitting assemblies is fastened to the first side of the conduction frame and passes through the central opening such that the light source attached to the conduction member is situated on the second side of the conduction frame to direct light toward the front section of the enclosure; and



wherein any one of the inclination angles corresponding to the printed circuit boards of the plurality of light emitting assemblies is at least one degree different than any other one of the inclination angles.

10. The lighting system of claim 9, wherein the plurality of light emitting assemblies includes at least three light emitting assemblies.

11. The lighting system of claim 10, wherein for each one of the plurality of light emitting assemblies any one of the reflectors has an identical reflector shape as any other one of the reflectors.

12. The lighting system of claim 11, wherein the reflector shape comprises a set of sections, each section from the set of sections configured to reflect a light emitted by a light source adjacent to that section.

13. The lighting system of claim 12, wherein each section from the set of sections includes a curved profile.

14. The lighting system of claim 11, wherein the reflector shape includes a reflective coating formed from a polycarbonate resin.

15. The lighting system of claim 9, wherein the plurality of light emitting assemblies includes first, second, and third light emitting assemblies having corresponding first, second, and third printed circuit boards, mounted at corresponding first, second, and third inclination angles, and wherein the first inclination angle is in a range of 15-20 degrees, the second inclination angle is in a range of 20-22 degrees, and the third inclination angle is in a range of 22-25 degrees.

16. The lighting system of claim 9 wherein the plurality of light emitting assemblies is mounted between the conduction frame and a back side of the enclosure inside of the enclosure.

17. The lighting system of claim 9 wherein the enclosure includes a front housing assembly configured to seal the enclosure when being fastened to a front mounting frame of a front side of the enclosure.

18. The light system of claim 17 wherein the plurality of light emitting assemblies is mounted between the conduction frame and the front housing assembly.

19. A lighting system comprising: an enclosure having a back side, and a front side, the front side including a front mounting frame; a universal power supply; an electromagnetic interference filter circuit; a conduction frame fastened to the enclosure, wherein the conduction frame has a first side facing the back side, a second side facing the front side of the enclosure, and a central opening; one or more light emitting assemblies fastened to the conduction frame, wherein each of the one or more light emitting assemblies has a conduction member and a light source fastened to the conduction member, wherein the conduction member is fastened to the first side of the conduction frame and passes through the central opening such that the light source attached to the conduction member is situated on the second side of the conduction frame to direct light toward the front side of the enclosure; and a front housing assembly configured to seal the enclosure when being fastened to the front mounting frame of the front side, the front housing assembly including: a front housing member having a front housing groove at a back side of the front housing member, the back side of the front housing member facing the one or more light emitting assemblies; a flexible gasket configured to be inserted into the front housing groove; a flat bezel lens configured to allow a light emitted from the one or more light sources of the one or more light emitting assemblies to exit the enclosure; a nichrome wire heater positioned between the flexible gasket and the flat bezel lens; and a retainer plate being configured to be fastened to the back side of the front housing member causing securing the flat bezel lens, the nichrome wire heater and the flexible gasket to the back side of the front housing member.

20. The lighting system of claim 19, wherein the nichrome wire heater is configured to regulate a temperature of the flat bezel lens, ensuring required transparency of the flat bezel lens.

21. The lighting system of claim 19, wherein the front mounting frame of the front side includes a front side groove having a selected profile, the lighting system further comprising a flexible O-ring

having a circular profile and configured to be inserted into the front side groove, such that at least a portion of the flexible O-ring is extending beyond the front side groove, and wherein the fastening of the front housing assembly to the front mounting frame of the front side includes at least partially compressing the flexible O-ring.

---