

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400542
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Nakashima; Hiroyuki et al.

Control device, control method, and control program

Abstract

A control device includes an outside recognition unit, a parking control unit, and a registration processing unit. When the user selects the parking position, the registration processing unit is configured to detect feature points of the parking position, start a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point is acquirable, inquire of the user whether a registration for the designated parking position is needed after starting of the verification process, and register the parking position as the designated parking position based on a reply to whether the registration is needed received from the user.

Inventors: Nakashima; Hiroyuki (Tokyo, JP), Inui; Yoji (Kariya, JP), Ueda; Koki (Kariya, JP), Hayakawa; Kazutaka (Kariya, JP)

Applicant: HONDA MOTOR CO., LTD. (Tokyo, JP); AISIN CORPORATION (Aichi, JP)

Family ID: 1000008778695

Assignee: HONDA MOTOR CO., LTD. (Tokyo, JP); AISIN CORPORATION (Kariya, JP)

Appl. No.: 18/490876

Filed: October 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240135815 A1	Apr. 25, 2024
US 20240233538 A9	Jul. 11, 2024

Foreign Application Priority Data

JP	2022-169836	Oct. 24, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G08G1/14 (20060101); B60W30/06 (20060101); B60W50/00 (20060101); G06V20/58 (20220101)

U.S. Cl.:

CPC G08G1/143 (20130101); B60W30/06 (20130101); B60W50/00 (20130101); G06V20/586 (20220101); B60W2050/0005 (20130101); B60W2420/403 (20130101)

Field of Classification Search

CPC: G08G (1/143); B60W (30/06); B60W (50/00); B60W (2050/0005); B60W (2420/403); G06V (20/586); B62D (15/027); B62D (15/0285)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2013/0166190	12/2012	Ikeda et al.	N/A	N/A
2017/0118307	12/2016	Beaurepaire	N/A	H04W 4/40
2020/0242936	12/2019	Matsunaga et al.	N/A	N/A
2021/0107562	12/2020	Horiguchi et al.	N/A	N/A
2021/0245734	12/2020	Harai et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10 2013 015 348	12/2013	DE	N/A
2020-117128	12/2019	JP	N/A
2021-62685	12/2020	JP	N/A
2020/022075	12/2019	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report dated Apr. 5, 2024, Application No. EP 23205260.5; 10 pages. cited by applicant
Japanese Office Action Corresponding to JP 2022-169836, dated Mar. 25, 2025, 9 pages. cited by applicant

Primary Examiner: Pope; Daryl C

Attorney, Agent or Firm: Rankin, Hill & Clark LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is based on and claims priority under 35 USC 119 from Japanese Patent Application No. 2022-169836 filed on Oct. 24, 2022.

TECHNICAL FIELD

(2) The present disclosure relates to a control device, a control method, and a control program.

BACKGROUND ART

(3) In recent years, countermeasures have actively been taken to provide access to sustainable transportation systems considering vulnerable people among traffic participants. Research and development have been focused on further improvement in traffic safety and convenience through research and development for automatic driving technologies.

(4) In the related art, automatic parking control for detecting parking spaces and moving and parking vehicles automatically in the detected parking spaces has been known. Automatic parking control for registering designated parking spaces in advance, detecting the registered parking spaces, and moving and parking vehicles automatically has been also known. JP 2020-117128 A discloses a parking assistance device which acquires feature point information and stores the feature point information in a nonvolatile memory at intervals of a predetermined time while moving toward a desired parking position at which a vehicle is desired to be registered when a user performs a touch operation on a registration process start button of the parking position and then the user drives the vehicle by themselves and performs manual driving parking to move the vehicle toward “the desired parking position at which the vehicle is desired to be registered”.

(5) Incidentally, even when a memory registration process is performed based on a request from the user, feature points cannot be acquired in some cases because of weather, illumination, or the like. Here, in the parking assistance device of JP2020-117128A, the user performs the touch operation on the registration process start button of the parking position when the parking is started.

Therefore, despite of a desire for the registration, a situation where the parking position cannot be registered can occur. Accordingly, a scheme of inquiring whether the user requires registration after the feature points can be acquired and registering the parking position when a reply that the registration is needed is received from the user. Incidentally, to register the parking position, it is necessary to verify own position estimation for parking the vehicle of the user at a target parking position based on the acquired feature points and it is necessary to take a predetermined time for the verification. Therefore, after the reply that the registration is needed is received from the user, the user needs to wait for the predetermined time until the registration is completed. However, countermeasures for such point are not described in JP2020-117128A. Accordingly, there is room for improvement for such point in the technology of the related art.

SUMMARY OF INVENTION

(6) An object of the present disclosure is to provide a control device, a control method, and a control program capable of efficiently performing a registration process for a parking position. Accordingly, it is possible to make contribution to development of a sustainable transportation system.

(7) According to an aspect of the present disclosure, a control device for a moving body, the control device including an outside recognition unit configured to acquire recognition data which is a data of an outside of the moving body, a parking control unit configured to perform parking control to park the moving body at a parking position selected by a user of the moving body based on the recognition data, and a registration processing unit configured to register the parking position as a designated parking position, in which when the user selects the parking position, the registration processing unit is configured to detect feature points of the parking position, start a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired, inquire of the user whether a registration for the designated parking position is needed after starting of the verification process, and register the parking position as the designated parking position based on a reply to whether the registration is needed received from the user.

(8) According to another aspect of the present disclosure, there is provided a control method by a control device for a moving body, the control device including an outside recognition unit

configured to acquire recognition data which is data of an outside of the moving body, a parking control unit configured to perform parking control to park the moving body at a parking position selected by a user of the moving body based on the recognition data, and a registration processing unit configured to register the parking position as a designated parking position, in which, when the user selects the parking position, a processor of the control device is configured to: detect feature points of the parking position, start a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired, inquire of the user whether a registration for the designated parking position is needed after starting of the verification process, and register the parking position as the designated parking position based on a reply to whether the registration is needed received from the user.

(9) According to another aspect of the present disclosure, there is provided a control program by a control device for a moving body, the control device including an outside recognition unit configured to acquire recognition data which is data of an outside of the moving body, a parking control unit configured to perform parking control to park the moving body at a parking position selected by a user of the moving body based on the recognition data, and a registration processing unit configured to register the parking position as a designated parking position, in which, when the user selects the parking position, the control program causes a processor of the control device to execute processing of detecting feature points of the parking position, starting a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired, inquiring of the user whether a registration for the designated parking position is needed after starting of the verification process, and registering the parking position as the designated parking position based on a reply to whether the registration is needed received from the user.

(10) According to the present disclosure, it is possible to provide a control device, a control method, and a control program capable of efficiently performing a registration process for a parking position.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a side view illustrating an example of a vehicle in which a control device according to an embodiment is mounted.

(2) FIG. 2 is a top view illustrating the vehicle illustrated in FIG. 1.

(3) FIG. 3 is a block diagram illustrating an internal configuration of the vehicle illustrated in FIG. 1.

(4) FIG. 4 is a flowchart illustrating an example of a registration process for a parking position performed by a calculation unit.

(5) FIG. 5 is a flowchart illustrating an example of the registration process for the parking position performed by the calculation unit.

(6) FIG. 6 is a diagram illustrating an example of a bird's-eye view image displayed on a touch panel when automatic parking of a vehicle is started.

(7) FIG. 7 is a diagram illustrating an example of a parking frame selection screen displayed when a parking position is selected.

(8) FIG. 8 is a diagram illustrating a designated parking position selected through a parking frame selecting operation on the parking frame selection screen.

(9) FIG. 9 is a diagram illustrating an example of feature points of the designated parking position.

(10) FIG. 10 is a bird's-eye view image illustrating a state of a vehicle automatically parking at the designated parking position.

(11) FIG. 11 is a bird's-eye view image illustrating a state in which the automatic parking of the vehicle at the designated parking position is completed.

(12) FIG. 12 is a diagram illustrating an example of an inquiry screen for inquiring whether the registration is needed for the designated parking position.

(13) FIG. 13 is a diagram illustrating an example of a map related to the designated parking position registered in a storage unit.

(14) FIG. 14 is a diagram illustrating a vehicle parked in front of a parking lot for automatic parking.

(15) FIG. 15 is a diagram illustrating movement of a vehicle so that the designated parking position is located within a predetermined range regarding the vehicle.

DESCRIPTION OF EMBODIMENTS

(16) Hereinafter, a control device, a control method, and a control program according to the present disclosure will be described with reference to the appended drawings. It is assumed that the drawings are viewed in directions of reference numerals. In the present specification or the like, to simplify and clarify description, front and rear directions, left and right directions, and up and down directions are described in directions viewed from a driver of a vehicle **10** illustrated in FIGS. 1 and 2. In the drawings, Fr, Rr, L, R, U, and D denote front, rear, left, right, up, and down sides of the vehicle **10**, respectively.

(17) <Vehicle **10** Mounted with Control Device According to Present Disclosure>

(18) FIG. 1 is a side view illustrating the vehicle **10** in which a control device according to the present disclosure is mounted. FIG. 2 is a top view illustrating the vehicle **10** illustrated in FIG. 1. The vehicle **10** is an example of a moving body according to the present disclosure.

(19) The vehicle **10** is an automobile which includes a driving source (not illustrated) and wheels including a driving wheel driven by power of the driving source and a steerable steering wheel. In the embodiment, the vehicle **10** is a four-wheel automobile which includes a pair of left and right front wheels and a pair of left and right rear wheels. The driving source of the vehicle **10** is, for example, an electric motor. The driving source of the vehicle **10** may be an internal combustion engine such as a gasoline engine or a diesel engine, or may be a combination of an electric motor and an internal combustion engine. The driving source of the vehicle **10** may drive the pair of left and right front wheels, may drive the pair of left and right rear wheels, or may drive the pairs of left and right front and rear wheels. The front and rear wheels may be both steerable steering wheels or any one thereof may be a steerable steering wheel.

(20) The vehicle **10** further includes side mirrors **11L** and **11R**. The side mirrors **11L** and **11R** are mirrors (rearview mirrors) provided in the outside of the front doors of the vehicle **10** and used for the driver to check the rear side and the rear lateral side. The side mirrors **11L** and **11R** are fixed to the body of the vehicle **10** by rotational shafts extending in the vertical direction and can be opened and closed by rotating about the rotational shafts.

(21) The vehicle **10** further includes a front camera **12Fr**, a rear camera **12Rr**, a left side camera **12L**, and a right side camera **12R**. The front camera **12Fr** is a digital camera which is provided in the front of the vehicle **10** and captures the front side of the vehicle **10**. The rear camera **12Rr** is a digital camera which is provided in the rear of the vehicle **10** and captures the rear side of the vehicle **10**. The left side camera **12L** is a digital camera which is provided in the left side mirror **11L** of the vehicle **10** and captures the left side of the vehicle **10**. The right side camera **12R** is a digital camera which is provided in the right side mirror **11R** of the vehicle **10** and captures the right side of the vehicle **10**.

(22) <Internal Configuration of Vehicle **10**>

(23) FIG. 3 is a block diagram illustrating an example of an internal configuration of the vehicle **10** illustrated in FIG. 1. As illustrated in FIG. 3, the vehicle **10** includes a sensor group **16**, a navigation device **18**, a control electronic control unit (ECU) **20**, an electric power steering (EPS) system **22**, and a communication unit **24**. The vehicle **10** further includes a driving force control

system **26** and a braking force control system **28**.

(24) The sensor group **16** acquires various detected values used for control by the control ECU **20**. The sensor group **16** includes the front camera **12Fr**, a rear camera **12Rr**, the left side camera **12L**, and the right side camera **12R**. The sensor group **16** includes a front sonar group **32a**, a rear sonar group **32b**, a left side sonar group **32c**, and a right side sonar group **32d**. The sensor group **16** includes wheel sensors **34a** and **34b**, a vehicle speed sensor **36**, and an operation detection unit **38**.

(25) The front camera **12Fr**, the rear camera **12Rr**, the left side camera **12L**, and the right side camera **12R** acquire recognition data (for example, peripheral images) for recognizing the outside of the vehicle **10** by capturing the periphery of the vehicle **10**. The peripheral images captured by the front camera **12Fr**, the rear camera **12Rr**, the left side camera **12L**, and the right side camera **12R** are referred to as a front image, a rear image, a left side image, and a right side image, respectively. Images formed by the left side image and the right side image may also be referred to as side images.

(26) The front sonar group **32a**, the rear sonar group **32b**, the left side sonar group **32c**, and the right side sonar group **32d** emit ultrasonic waves to the periphery of the vehicle **10** and receive waves reflected from other objects. The front sonar group **32a** includes, for example, four sonars. The sonars included in the front sonar group **32a** are respectively provided in diagonally left front, left front, right front, and diagonally right front of the vehicle **10**. The rear sonar group **32b** includes, for example, four sonars. The sonars included in the rear sonar group **32b** are respectively provided in diagonally left rear, left rear, right rear, and diagonally right rear of the vehicle **10**. The left side sonar group **32c** includes, for example, two sonars. The sonars included in the left side sonar group **32c** are provided in left side front and left side rear of the vehicle **10**. The right side sonar group **32d** includes, for example, two sonars. The sonars included in the right side sonar group **32d** are provided in right side front and right side rear of the vehicle **10**.

(27) The wheel sensors **34a** and **34b** detect rotational angles of the wheels of the vehicle **10**. The wheel sensors **34a** and **34b** may be configured with angle sensors or may be configured with displacement sensors. The wheel sensors **34a** and **34b** output detection pulses whenever the wheels are rotated by a predetermined angle. The detection pulses output from the wheel sensors **34a** and **34b** are used to calculate a rotational angle of the wheels and a rotational speed of the wheels. Based on the rotational angle of the wheels, a movement distance of the vehicle **10** is calculated. The wheel sensor **34a** detects, for example, a rotational angle θ_a of the left rear wheel. The wheel sensor **34b** detects, for example, a rotational angle θ_b of the right rear wheel.

(28) The vehicle speed sensor **36** detects a speed of the body of the vehicle **10**, that is, a vehicle speed V , and outputs the detected vehicle speed V to the control ECU **20**. The vehicle speed sensor **36** detects the vehicle speed V based on, for example, rotation of a counter shaft of a transmission.

(29) The operation detection unit **38** detects operation content performed by a user using an operation input unit **14** and outputs the detected operation content to the control ECU **20**. The operation input unit **14** includes, for example, various user interfaces such as a side mirror switch switching between opening and closing states of the side mirrors **11L** and **11R**, and a shift lever (a select lever or a selector).

(30) The navigation device **18** detects a current position of the vehicle **10** using, for example, a global positioning system (GPS) and guides the user along a route to a destination. The navigation device **18** includes a storage device (not illustrated) including a map information database.

(31) The navigation device **18** includes a touch panel **42** and a speaker **44**. The touch panel **42** functions as an input device and a display device of the control ECU **20**. The speaker **44** outputs various types of guide information by a sound to a user (passenger) of the vehicle **10**.

(32) The touch panel **42** is configured such that various instructions can be input to the control ECU **20**. For example, the user can input an instruction related to movement support of the vehicle **10** via the touch panel **42**. The movement support includes parking support and leaving support of the vehicle **10**. The touch panel **42** is configured to display various screens related to the control

content of the control ECU **20**. For example, a screen related to the movement support of the vehicle **10** is displayed on the touch panel **42**. Specifically, a parking support button for requesting the parking support of the vehicle **10** and a leaving support button for requesting the leaving support are displayed on the touch panel **42**. The parking support button includes an automatic parking button for requesting parking by automatic steering of the control ECU **20** and an assistant parking button for requesting assistance during parking by an operation of the driver. The leaving support button includes an automatic leaving button for requesting leaving by automatic steering of the control ECU **20** and an assistant leaving button for requesting assistance during leaving by an operation of the driver. A constituent other than the touch panel **42**, for example, an information terminal such as a smartphone or a tablet terminal may be used as an input device or a display device.

(33) For example, “parking” is stopping associated with boarding and descending of an occupant, and temporary stopping by a traffic signal and the like is excluded. “Parking position” is a position at which the moving body stops, that is, a position at which parking is performed.

(34) The control ECU **20** includes an input/output unit **50**, a calculation unit **52**, and a storage unit **54**. The calculation unit **52** is configured with, for example, a central processing unit (CPU). The calculation unit **52** performs various types of control by controlling each unit based on a program stored in the storage unit **54**. The calculation unit **52** inputs and outputs a signal between each unit connected to the control ECU **20** via the input/output unit **50**. The calculation unit **52** is an example of a control device according to the present invention.

(35) The calculation unit **52** includes an outside recognition unit **55** which acquires outside recognition data of the vehicle **10**, a parking control unit **56** which performs parking control to park the vehicle **10** at the selected parking position, and a registration processing unit **58** which registers the selected parking position as a designated parking position.

(36) The outside recognition unit **55** acquires peripheral images (recognition data of an outside) of the vehicle **10** captured by the front camera **12Fr**, the rear camera **12Rr**, the left side camera **12L**, and the right side camera **12R** from each camera. The outside recognition unit **55** can also acquire outside recognition data of the vehicle **10** acquired by the sonar groups **32a** to **32d** or a radar.

(37) The parking control unit **56** performs parking support of the vehicle **10** through automatic steering in which an operation of a steering **110** is performed automatically under the control of the parking control unit **56**. In the automatic steering support, operations on an acceleration pedal (not illustrated), a brake pedal (not illustrated), and the operation input unit **14** are automatically performed. The parking control unit **56** performs assistant parking support when the driver performs the operations on the acceleration pedal, the brake pedal, and the operation input unit **14** and manually parks the vehicle **10**.

(38) For example, the parking control unit **56** performs automatic parking control to park the vehicle **10** at the selected parking position based on the recognition data of the outside of the vehicle **10** acquired by the front camera **12Fr**, the rear camera **12Rr**, the left side camera **12L**, and the right side camera **12R** and the selection of the parking position by the user.

(39) When the user selects a parking position at which the vehicle **10** is to be parked, the registration processing unit **58** detects feature points of the selected parking position. The registration processing unit **58** detects feature points of the parking position at a start point of the parking control by which the vehicle **10** is parked at the selected parking position. For example, the feature points are detected at a time point at which the vehicle **10** is temporarily stopped and the automatic parking button is operated when the automatic parking is started at a parking lot.

(40) When the feature points of the parking position can be acquired, the registration processing unit **58** starts a registration process of registering the parking position as a designated parking position. The registration process includes a verification process of verifying the feature points of the parking position. The verification process is a process of verifying position estimation of the vehicle **10** based on the feature points, that is, a process of verifying whether a relative position of

the vehicle **10** to the parking position can be estimated based on the feature points. The registration processing unit **58** starts the registration process for the designated parking position when the number of acquired feature points is equal to or greater than a predetermined number (for example, three or more).

(41) Even when the feature points of the parking positions cannot be acquired at the start point of the parking control, when the feature points can be acquired during the automatic parking at the parking position, the registration processing unit **58** may start the registration process of registering the parking position as a designated parking position at a time point at which the feature points can be acquired.

(42) The registration processing unit **58** inquires of the user about whether it is necessary to register the designated parking position after the starting of the verification process for the feature points. For example, the registration processing unit **58** inquires of the user whether the registration is needed for the designated parking position when the parking of the vehicle **10** at the parking position by the parking control is completed after the starting of the verification process for the feature points. The registration processing unit **58** inquires of the user whether the registration is needed for the designated parking position when the position of the vehicle **10** can be estimated based on the acquired feature points. The registration processing unit **58** registers the parking position selected by the user as the designated parking position in the storage unit **54** based on a reply to whether the registration is needed for the designated parking position received from the user.

(43) The registration processing unit **58** performs control to move the vehicle **10** so that, when the user selects the parking position, the selected parking position is located within a predetermined range regarding the vehicle **10**. The predetermined range is a range appropriate for detecting the feature points for the vehicle **10** which will be parked. For example, when the left side camera **12L** and the right side camera **12R** of the vehicle **10** are cameras appropriate for detecting the feature points, the predetermined range regarding the vehicle **10** is a lateral side of the vehicle **10**.

(44) The registration processing unit **58** starts a process of verifying position estimation of the vehicle **10** or does not perform the process of verifying the position estimation of the vehicle **10** after completion of the parking at the parking position of the vehicle **10** by the parking control when the feature points of the parking position at a start point of the parking control by which the vehicle **10** is parked at the selected parking position cannot be acquired. The registration processing unit **58** starts the process of verifying the position estimation of the vehicle **10** based on the feature points acquired during the parking of the vehicle **10** at the parking position and acquired after the completion of the parking.

(45) The registration processing unit **58** deletes data related to the registration process when a reply indicating that the registration is not needed is received from the user in response to the inquiry of whether the registration is needed. When the reply indicating the registration is not needed is received from the user in response to the inquiry of whether the registration is needed, the registration processing unit **58** may retain the data related to the registration process until a predetermined timing (for example, ignition-off) and may inquire again of the user whether the registration is needed, or output guide information regarding the registration to the user. The guide information regarding the registration is, for example, an advantage of subsequent parking by registering the designated parking position. The guide information regarding the registration may be output only when the designated parking position was not registered.

(46) The EPS system **22** includes a steering angle sensor **100**, a torque sensor **102**, an EPS motor **104**, a resolver **106**, and an EPS ECU **108**. The steering angle sensor **100** detects a steering angle θ of the steering **110**. The torque sensor **102** detects a torque TQ applied to the steering **110**.

(47) The EPS motor **104** enables automatic steering while supporting operation or parking of the steering **110** by an occupant by applying a driving force or a reaction force to a steering column **112** connected to the steering **110**. The resolver **106** detects a rotational angle θ_m of the EPS motor **104**.

The EPS ECU **108** is in charge of controlling the entire EPS system **22**. The EPS ECU **108** includes an input/output unit (not illustrated), a calculation unit (not illustrated), and a storage unit (not illustrated).

(48) The communication unit **24** enables wireless communication with another communication device **120**. The other communication device **120** is an information terminal such as a base station, a communication device of another vehicle, or a smartphone carried by a passenger of the vehicle **10**.

(49) The driving force control system **26** includes a driving ECU **130**. The driving force control system **26** performs driving force control of the vehicle **10**. The driving ECU **130** controls a driving force of the vehicle **10** by controlling an engine or the like (not illustrated) based on an operation on the acceleration pedal (not illustrated) by the user.

(50) The braking force control system **28** includes a braking ECU **132**. The braking force control system **28** performs braking force control of the vehicle **10**. The braking ECU **132** controls a braking force of the vehicle **10** by controlling a brake mechanism or the like (not illustrated) based on an operation on the brake pedal (not illustrated) by the user.

Control Example of Control Device (Calculation Unit **52**) in Automatic Parking

(51) Next, a registration process for a parking position performed by the calculation unit **52** of the vehicle **10** in the automatic parking will be described. FIGS. **4** and **5** are flowcharts illustrating an example of a registration process for a parking position performed by the calculation unit **52**. The calculation unit **52** starts a process illustrated in FIG. **4**, for example, when a touch operation is performed on the automatic parking button displayed on the touch panel **42**. The user who wants to park the vehicle **10** performs the touch operation on the automatic parking button, for example, when the user comes near a parking lot.

(52) First, the registration processing unit **58** of the calculation unit **52** determines whether to receive an automatic parking start operation to start the automatic parking of the vehicle **10** (step **S11**). The automatic parking start operation is, for example, a touch operation on the automatic parking button displayed on the touch panel **42**.

(53) When the automatic parking start operation is not received in step **S11** (No in step **S11**), the registration processing unit **58** repeats the process of step **S11**. When the automatic parking start operation is received in step **S11** (Yes in step **S11**), the registration processing unit **58** displays a parking frame selection screen on the touch panel **42** which can be operated by the user to select a parking position at which the vehicle **10** will be parked (step **S12**). The operation on the parking frame selection screen will be described below with reference to FIG. **7**.

(54) Subsequently, the registration processing unit **58** determines whether a parking frame selecting operation on the parking frame selection screen is received, that is, the parking position of the vehicle **10** is selected (step **S13**). Reception of the parking frame selection operation will be described with reference to FIG. **8**.

(55) When the parking frame selecting operation is not received in step **S13** (No in step **S13**), the registration processing unit **58** repeats the process of step **S13**. When the parking frame selecting operation is received in step **S13** (Yes in step **S13**), the registration processing unit **58** detects the feature points at the parking position selected through the parking frame selecting operation (step **S14**). The registration processing unit **58** starts detecting the feature points of a designated parking position **64** at a point at which the parking frame selecting operation of the user is received, that is, a start point of the parking control by which the vehicle **10** is parked at the selected designated parking position **64**. The registration processing unit **58** detects the feature points at the parking position based on peripheral images (recognition data of outside) of the vehicle **10** captured by the front camera **12Fr**, the rear camera **12Rr**, the left side camera **12L**, and the right side camera **12R**. The feature points of the parking position will be described with reference to FIGS. **9** and **13**.

(56) Subsequently, the registration processing unit **58** determines whether the feature points of the parking position were acquired (step **S15**).

(57) When the feature points of the parking position can be acquired in step S15 (Yes in step S15), the registration processing unit 58 starts the registration process including a process of verifying the position estimation of the vehicle 10 based on the acquired feature points (step S16). The verification of the position estimation of the vehicle 10 will be described below with reference to FIG. 9.

(58) Subsequently, when the registration process including the process of verifying the position estimation of the vehicle 10 is started in step S16, the parking control unit 56 of the calculation unit 52 determines whether an automatic parking execution operation is received (step S17). The automatic parking execution operation is an operation of starting movement of the vehicle 10 in the automatic parking and is, for example, a touch operation on a movement start button or an operation of releasing a brake of the stopping vehicle 10.

(59) When the automatic parking execution operation is not received in step S17 (No in step S17), the parking control unit 56 repeats the process of step S17. When the automatic parking execution operation is received in step S17 (Yes in step S17), the parking control unit 56 starts the automatic parking control to park the vehicle 10 at the selected parking position (step S18). The automatic parking control at the selected parking position will be described below with reference to FIG. 10.

(60) Subsequently, the parking control unit 56 determines whether the automatic parking control of the vehicle 10 is completed (step S19).

(61) When the automatic parking control is not completed in step S19 (No in step S19), the parking control unit 56 repeats the process of step S19. When the automatic parking control is completed in step S19 (Yes in step S19), the registration processing unit 58 determines whether the verification process of own position estimation of the vehicle 10 based on the feature points in the registration process started in step S16 is completed (step S20 of FIG. 5).

(62) Conversely, when the feature points of the parking position cannot be acquired in step S15, that is, the feature points of the parking position cannot be acquired at the start point of the automatic parking control (No in step S15), the parking control unit 56 determines whether the automatic parking execution operation is received (step S26). The automatic parking execution operation is similar to the automatic parking execution operation of step S17.

(63) When the automatic parking execution operation is not received in step S26 (No in step S26), the parking control unit 56 repeats the process of step S26. When the automatic parking execution operation is received in step S26 (Yes in step S26), the parking control unit 56 starts the automatic parking control to park the vehicle 10 at the selected parking position (step S27).

(64) Subsequently, the parking control unit 56 determines whether the automatic parking control of the vehicle 10 is completed (step S28).

(65) When the automatic parking control is not completed in step S28 (No in step S28), the parking control unit 56 repeats the process of step S28. When the automatic parking control is completed in step S28 (Yes in step S28), the registration processing unit 58 starts the registration process including the process of verifying the position estimation of the vehicle 10 based on the feature points acquired until the current time at which the automatic parking control is completed (during or after the automatic parking control) (step S29).

(66) Subsequently, the registration processing unit 58 determines whether the verification process of estimating an own position of the vehicle 10 based on the feature points in the registration process started in step S29 is completed (step S20 of FIG. 5).

(67) When the verification process of estimating the own position based on the feature points is not completed in step S20 (No in step S20), the registration processing unit 58 repeats the process of step S20. When the verification process of estimating the own position based on the feature points is completed in step S20 (Yes in step S20), the registration processing unit 58 determines whether the own position can be estimated based on the feature points (step S21).

(68) When the own position based on the feature points can be estimated in step S21 (Yes in step S21), the registration processing unit 58 displays an inquiry screen for inquiring whether the

registration is needed for the selected parking position on the touch panel **42** (step **S22**). The inquiry screen for inquiring whether the registration is needed will be described below in FIG. **12**.
(69) Subsequently, the registration processing unit **58** determines whether a reply is received from the user about the inquiry of whether the registration is needed.

(70) When a reply indicating that the registration is needed is received in step **S23** (Yes in step **S23**), the registration processing unit **58** registers the selected parking position as the designated parking position in the storage unit **54** (step **S24**). When a reply indicating that the registration is needed is not received in step **S23** (No in step **S23**), the registration processing unit **58** deletes data of the acquired feature points of the parking position (step **S25**). Registration of the designated parking position will be described below in FIG. **13**.

(71) When the own position based on the feature points cannot be estimated in step **S21** (No in step **S21**), the process proceeds to step **S25** and the registration processing unit **58** deletes the data of the acquired feature points of the parking position.

(72) Next, an image displayed on the touch panel **42** in the registration process for the parking position in the above-described automatic parking of the vehicle **10** will be described. FIGS. **6** to **13** are diagrams illustrating examples of screens displayed on the touch panel **42** in the registration process for the parking position.

(73) FIG. **6** is a diagram illustrating an example of a bird's-eye view image **60** displayed on the touch panel **42** of the vehicle **10** when the automatic parking of the vehicle **10** is started. As illustrated in FIG. **6**, the vehicle **10** is stopped in front of a parking lot **P** to park the vehicle **10** at the parking lot **P**. The registration processing unit **58** of the vehicle **10** displays the bird's-eye view image **60** on the touch panel **42** when an automatic parking start operation (for example, a touch operation on the automatic parking button) is received.

(74) The bird's-eye view image **60** is a synthesized image generated based on the recognition data of the outside of the vehicle **10** captured by the front camera **12Fr**, the rear camera **12Rr**, the left side camera **12L**, and the right side camera **12R**. In the bird's-eye view image **60** illustrated in FIG. **6**, the parking lot **P** and a plurality of plantings (obstructions) **61a** to **61f** are captured.

(75) In the bird's-eye view image **60**, a rectangular selected parking position **64a** used to select a parking position is displayed. The user of the vehicle **10** rents a parking region **62** set on the obstructions **61a** to **61f** side in the parking lot **P** as a monthly parking lot. A vehicle stopping in front of the parking lot **P** is an image in which the vehicle **10** is viewed from the upper side and a vehicle image **63** generated (captured) in advance and stored in the storage unit **54** or the like. The bird's-eye view image **60** in FIG. **6** is, for example, a bird's-eye view image displayed in step **S11** of FIG. **4**.

(76) FIG. **7** is a diagram illustrating an example of a parking frame selection screen **69** in which a display position of the selected parking position **64a** can be moved when a parking position of the vehicle **10** is selected. The parking frame selection screen **69** is overlapped on the bird's-eye view image **60** to be displayed in a partial region of the touch panel **42**. A cursor indicating a movement direction is displayed on the parking frame selection screen **69** and a display position of the selected parking position **64a** can be moved in an arrow direction through an operation on the cursor.

(77) In the parking frame selection screen **69**, a determination button **69a** for determining disposition of the selected parking position **64a**, a reset button **69b** for cancelling the disposition of the selected parking position **64a**, and a stop button **69c** for stopping the disposition of the selected parking position **64a** are displayed. The parking frame selection screen **69** in FIG. **7** is a parking frame selection screen displayed in step **S12** of FIG. **4**.

(78) FIG. **8** is a diagram illustrating the designated parking position **64** selected through the parking frame selection operation on the parking frame selection screen **69**. As illustrated in FIG. **8**, the determination button **69a** of the parking frame selection screen **69** is pressed after a position of the selected parking position **64a** is moved to surround the parking region **62** of the parking lot **P**.

Accordingly, the registration processing unit **58** selects the selected parking position **64a** moved to surround the parking region **62** as the designated parking position **64**. The bird's-eye view image **60** in FIG. **8** is a bird's-eye view image displayed in step **S13** of FIG. **4**.

(79) The user can also select the parking region **62** as the designated parking position **64** through manual selection, for example, by performing a swipe operation on the touch panel **42**. The manual selection of the designated parking position **64** can be performed by moving the position of the selected parking position **64a** by a swipe operation for the selected parking position **64a** to surround the parking region **62**, and then detaching a finger from the touch panel **42**.

(80) FIG. **9** is a diagram illustrating an example of the feature points detected with regard to the designated parking position **64** illustrated in FIG. **8**. When the designated parking position **64** is selected, the registration processing unit **58** starts detecting the feature points related to the designated parking position **64**. The feature points related to the designated parking position include feature points of the designated parking position itself and feature points in the periphery of the designated parking position.

(81) As the feature points of the designated parking position itself, for example, feature points or the like which is text such as “parking” displayed within the designated parking position can be exemplified. As the feature points in the periphery of the designated parking position, for example, characteristic buildings, obstructions, or the like present in the periphery can be exemplified.

(82) The registration processing unit **58** detects objection feature points **65a** to **65f** indicating positions of the obstructions **61a** to **61f** present around the designated parking position **64** from captured images (camera images) acquired by the outside recognition unit **55**, for example, as illustrated in FIG. **9**. When the feature points of the designated parking position **64** are acquired, the registration processing unit **58** estimates the camera position with regard to the acquired feature points (a position of the camera such as the front camera **12Fr** performing capturing) and starts the verification process of estimating a relative position of the vehicle **10** to the designated parking position **64** based on the estimated camera position. Specifically, the registration processing unit **58** estimates the camera position with regard to the feature points chronologically (maps the camera position to a map of the feature points) and estimates a relative position of the vehicle **10** to the designated parking position **64** based on the chronologically estimated camera positions, an odometry, and the like. The bird's-eye view image **60** in FIG. **9** is a bird's-eye view image displayed from steps **S14** to **S15** of FIG. **4**.

(83) FIG. **10** is a diagram illustrating the bird's-eye view image **60** illustrating a state of the vehicle **10** started to be automatically parked toward the designated parking position **64**. The parking control unit **56** of the vehicle **10** performs automatic parking control to park the vehicle **10** at the designated parking position **64** based on the selected designated parking position **64** and the recognition data of the outside of the vehicle **10** captured by the front camera **12Fr**, the rear front **12Rr**, the left side camera **12L**, and the right side camera **12R**. The bird's-eye view image **60** in FIG. **10** is, for example, a bird's-eye view image displayed in step **S18** of FIG. **4**.

(84) FIG. **11** illustrates the bird's-eye view image **60** illustrating a state in which the automatic parking of the vehicle **10** at the designated parking position **64** is completed. When the automatic parking at the designated parking position **64** is completed, the registration processing unit **58** of the vehicle **10** determines whether a position of the vehicle **10** with regard to the designated parking position **64** can be estimated based on the feature points. When it is determined that the position of the vehicle **10** with regard to the designated parking position **64** can be estimated, the registration processing unit **58** inquires of the user about whether to register the designated parking position **64** selected by the user as a “designated parking position” of the vehicle **10**.

(85) FIG. **12** is a diagram illustrating an example of an inquiry screen **70** for inquiring of the user whether the registration is needed for the designated parking position **64**. The inquiry screen **70** is displayed on the touch panel **42**. As illustrated in FIG. **12**, an inquiry message **71** such as “Do you want to register current parking position in memory?” and a “Register” button **72** and a “Do not

register” button **73** for selecting whether the registration is needed, which are operational buttons, are displayed on the inquiry screen **70**. The inquiry screen **70** in FIG. **12** is, for example, an inquiry screen displayed in step **S22** of FIG. **4**.

(86) FIG. **13** is a diagram illustrating an example of a map **M** related to the designated parking position **64** registered in the storage unit **54**. When a reply indicating that the registration for registering the designated parking position **64** is needed is received from the user on the inquiry screen **70**, the registration processing unit **58** of the vehicle **10** registers information indicating association between the detected obstruction feature points **65a** to **65f** and the selected designated parking position **64** as the map **M** in the storage unit **54**.

(87) The map **M** in FIG. **13** is, for example, a map registered in step **S24** of FIG. **4**. In FIGS. **11** to **13** described above, the cases where the own position can be estimated based on the feature points and a reply indicating that the registration is needed is made from the user were described.

However, for example, when the own position cannot be estimated or a reply indicating that the registration is not needed is made from the user despite the fact that the own position can be estimated, the registration processing unit **58** erases the feature point data related to the acquired designated parking position **64**.

(88) As described above, the registration processing unit **58** of the calculation unit **52** (control device) detects the feature points related to the designated parking position **64** when the designated parking position **64** is selected through the parking frame selecting operation, starts the verification process of verifying the position estimation of the vehicle **10** based on the feature points when the feature points can be acquired, determines whether the position of the vehicle **10** can be estimated based on the feature points when the automatic parking of the vehicle **10** at the designated parking position **64** is completed, and inquires whether the registration is needed for the designated parking position **64** when the position estimation can be performed.

(89) In such configuration, whether the registration is needed for the designated parking position **64** are inquired of the user when the position of the vehicle **10** can be estimated based on the acquired feature points. Therefore, it is possible to prevent a situation in which the position estimation of the vehicle **10** fails, and despite receiving the reply indicating that the registration is needed from the user, the position cannot be registered. Before whether the registration is needed for the designated parking position **64** is inquired of the user, the process of verifying the position estimation of the vehicle **10** based on the feature points is started from a time point at which the feature points related to the designated parking position **64** can be acquired. Therefore, it is possible to shorten a time from receiving an instruction to register the designated parking position **64** to completing the registration.

(90) The registration processing unit **58** starts detecting the feature points of the designated parking position **64** at a point at which a selection of the designated parking position **64** through the parking frame selecting operation of the user is received, that is, a start point of the parking control by which the vehicle **10** is parked at the selected designated parking position **64**. Therefore, when the feature points of the designated parking position **64** can be acquired not during the parking control but at the start point of the parking control, the process of estimating the position of the vehicle **10** based on the feature points can be started from the detected time point. Accordingly, it is possible to shorten a time from receiving the instruction to register the designated parking position **64** from the user to completion of the registration.

(91) <Stop Position of Vehicle **10** at Selected Designated Parking Position **64**>

(92) Next, a position at which the vehicle **10** is stopped with regard to the designated parking position **64** when the feature points related to the selected designated parking position **64** are detected will be described with reference to FIGS. **14** and **15**.

(93) FIG. **14** is a diagram illustrating the vehicle **10** stopped in front of the parking lot **P** to park the vehicle **10** in the parking lot **P**. In FIG. **14**, the selected parking position **64a** is moved to surround the parking region **62** of the parking lot **P** through a cursor operation of the parking frame selection

screen **69** and a position of the selected parking position **64a** is selected as the designated parking position **64**.

(94) Incidentally, for the designated parking position **64** selected in FIG. **14**, a partial region **81** is located outside of a predetermined range θ with respect to the stopped vehicle **10**. For the vehicle **10**, the predetermined range θ is a range appropriate for detecting the feature points of buildings, obstructions, or the like present around the vehicle. The predetermined range θ is a range corresponding to an angle of field of, for example, the left side camera **12L** mounted in the vehicle **10**.

(95) Accordingly, when the designated parking position **64** selected as such is located outside of the predetermined range θ with respect to the vehicle **10**, the registration processing unit **58** performs control to move the vehicle **10** so that the designated parking position **64** is located within the predetermined range θ with respect to the vehicle **10**.

(96) FIG. **15** is a diagram illustrating a state in which the vehicle **10** is moved rearward so that the designated parking position **64** is located within the predetermined range θ with respect to the vehicle **10**. The registration processing unit **58** starts a process of detecting the feature points related to the selected designated parking position **64** when the designated parking position **64** is located within the predetermined range θ with respect to the vehicle **10** as in FIG. **15**.

(97) In the example illustrated in FIG. **14**, the vehicle **10** is stopped so that the designated parking position **64** is located on the left side of the vehicle **10**, so the predetermined range θ corresponding to an angle of field of the left side camera **12L** was described. But the present invention is not limited thereto. For example, the vehicle **10** may be moved so that the designated parking position **64** is located within a predetermined range corresponding to an angle of field of the right side camera **12R** when the vehicle **10** is stopped so that the designated parking position **64** is located on the right side of the vehicle **10**, moved so that the designated parking position **64** is located within a predetermined range corresponding to an angle of field of the front camera **12Fr** when the vehicle **10** is stopped so that the designated parking position **64** is located in front of the vehicle **10**, or moved so that the designated parking position **64** is located within a predetermined range corresponding to an angle of field of the rear camera **12Rr** when the vehicle **10** is stopped so that the designated parking position **64** is located behind the vehicle **10**.

(98) When the left side camera **12L** and the right side camera **12R** of the vehicle **10** are cameras appropriate to detect the feature points in the vehicle **10**, the vehicle **10** may be moved so that the designated parking position **64** is located within a predetermined range corresponding to an angle of field of the left side camera **12L** or the right side camera **12R** although the vehicle **10** is stopped so that the designated parking position **64** is located in front of or behind the vehicle **10**.

(99) As such, by moving the vehicle **10** so that the designated parking position **64** is located within the predetermined range θ with respect to the vehicle **10** when the automatic parking of the vehicle **10** is started, it is possible to appropriately acquire the feature points related to the designated parking position **64**, and thus it is possible to automatically park the vehicle **10** at the designated parking position **64** accurately.

(100) The embodiment of the present invention has been described above, but the present invention is not limited to the foregoing embodiment and modifications, improvements, or the like can be made as appropriate.

(101) For example, in the foregoing embodiment, the case where the vehicle **10** is automatically parked by automatic steering has been described, but the present invention is not limited thereto. For example, the present invention may be applied to parking support in which assistance is performed when the vehicle **10** is parked by an operation of a driver.

(102) In the foregoing embodiment, the case where the bird's-eye view image **60** or the like is displayed on the touch panel **42** of the vehicle **10** has been described, but the present invention is not limited thereto. For example, the bird's-eye view image **60** or the like may be displayed on a display screen of an information terminal (for example, a smartphone or the like) carried by a

passenger of the vehicle **10** via the communication unit **24**.

(103) In the foregoing embodiment, the case where information such as a map including feature points of the designated parking position is registered in the storage unit **54** of the vehicle **10** has been described, but the present invention is not limited thereto. For example, such information may be registered in a storage unit of another device such as an information terminal or a server communicably connected to the vehicle **10**.

(104) In the foregoing embodiment, the example in which the moving body is a vehicle (a four-wheeled automobile) has been described, but the present invention is not limited thereto. For example, the moving body may be a vehicle such as a two-wheeled vehicle or a segway. The idea of the present invention is not limited to a vehicle and can be applied to a robot, a ship, an airplane, or the like which includes a driving source and can be moved by power of the driving source.

(105) The control method described in the above-described embodiment can be implemented by causing a computer to execute a control program prepared in advance. The control program is recorded on a computer-readable storage medium and is executed by being read from the storage medium. The control program may be provided in a form in which the control program is stored in a non-transitory storage medium such as a flash memory or may be provided via a network such as the Internet. A computer which executes the control program may be included in the control device, may be included in an electronic device such as a smartphone, a tablet terminal, or a personal computer capable of communicating with the control device, or may be included in a server device capable of communicating with the control device and the electronic device.

(106) In the present specification, at least the following factors are described. Constituents in parentheses indicate corresponding constituents in the foregoing embodiment, but the present invention is not limited thereto.

(107) (1) A control device (the calculation unit **52**) for a moving body (the vehicle **10**), the control device including: an outside recognition unit (the outside recognition unit **55**) configured to acquire recognition data which is a data of an outside of the moving body; a parking control unit (the parking control unit **56**) configured to perform parking control to park the moving body at a parking position (the selected parking position **64a**) selected by a user of the moving body based on the recognition data; and a registration processing unit (the registration processing unit **58**) configured to register the parking position as a designated parking position (the designated parking position **64**), in which when the user selects the parking position, the registration processing unit is configured to: detect feature points (the obstruction feature points **65a** to **65f**) of the parking position; start a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired, inquire of the user whether a registration for the designated parking position is needed after starting of the verification process; and register the parking position as the designated parking position based on a reply to whether the registration is needed received from the user.

(108) According to (1), when the feature points of the parking position can be acquired, whether the registration is needed for the parking position are inquired of the user. Therefore, it is possible to prevent a situation in which the acquisition of the feature points fails, and despite receiving a reply indicating that the registration is needed from the user, the position cannot be registered. Thus, usability is improved. Since the verification process for the feature points of the parking position is started before inquiry of whether the registration is needed for the parking position to the user, it is possible to shorten a time from receiving the reply indicating that the registration is needed from the user to completion of the registration, and thus usability is improved.

(109) (2) The control device according to (1), in which the registration processing unit is configured to inquire of the user whether the registration is needed when a parking at the parking position by the parking control is completed after the starting of the verification process.

(110) According to (2), since the verification process for the feature points is performed even during the parking control of the moving body, it is possible to shorten a time from completion of

the parking of the moving body to completion of the registration.

(111) (3) The control device according to (1) or (2), in which the registration processing unit is configured to start the registration process when the number of the feature points is equal to or greater than a predetermined number.

(112) According to (3), it is possible to accurately perform the verification process for the feature points based on feature points of which the number is equal to or greater than the predetermined number.

(113) (4) The control device according to any one of (1) to (3), in which the verification process is a process of verifying position estimation of the moving body based on the feature points.

(114) According to (4), information indicating that the position of the moving body can be estimated based on the feature points is necessary as information regarding the designated parking position to be designated.

(115) (5) The control device according to (4), in which the registration processing unit is configured to inquire of the user whether the registration is needed when a position of the moving body can be estimated based on the feature points.

(116) According to (5), when the position of the moving body can be estimated based on the feature points, whether the registration is needed is inquired of the user. Therefore, it is possible to prevent a situation in which the position estimation of the moving body fails, and despite receiving a reply indicating that the registration is needed from the user, the position cannot be registered. Thus, usability is improved.

(117) (6) The control device according to any one of (1) to (5), in which the registration processing unit is configured to detect the feature points at a start point of the parking control.

(118) According to (6), when the feature points can be acquired not during the parking control of the moving body but at the start point of the parking control, the registration process can be started from the detected time point. Therefore, it is possible to shorten a time from receiving a registration instruction from the user to completion of the registration.

(119) (7) The control device according to any one of (1) to (6), in which when the user selects the parking position, the registration processing unit is configured to perform control to move the moving body so that the parking position is located within a predetermined range regarding the moving body.

(120) According to (7), for example, by setting the predetermined range to a range in which the feature points of the parking position are easily detected, it is possible to accurately acquire the feature points of the parking position.

(121) (8) The control device according to any one of (1) to (7), in which when the feature points cannot be acquired at a start point of the parking control, the registration processing unit is configured to start the registration process or configured not to perform the registration process after a parking at the parking position by the parking control is completed.

(122) According to (8), when the feature points at the start point of the parking control cannot be acquired, it is possible to perform the registration process based on the feature points acquired after completion of the parking at the parking position.

(123) (9) The control device according to any one of (1) to (8), in which when a reply indicating that the registration is not needed is received from the user in response to an inquiry of whether the registration is needed, the registration processing unit is configured to: delete data regarding the registration process, maintain data regarding the registration process until a predetermined timing and inquires again whether the registration is needed, or output guide information related to the registration to the user.

(124) According to (9), it is possible to effectively process data related to the registration process in response to a request from the user or according to a registration history of the user.

(125) (10) A control method by a control device for a moving body, the control device including an outside recognition unit configured to acquire recognition data which is data of an outside of the

moving body, a parking control unit configured to perform parking control to park the moving body at a parking position selected by a user of the moving body based on the recognition data, and a registration processing unit configured to register the parking position as a designated parking position, in which when the user selects the parking position, a processor of the control device is configured to: detect feature points of the parking position; start a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired; inquire of the user whether a registration for the designated parking position is needed after starting of the verification process; and register the parking position as the designated parking position based on a reply to whether the registration is needed received from the user.

(126) According to (10), when the feature points of the parking position can be acquired, whether the registration is needed for the parking position is inquired of the user. Therefore, it is possible to prevent a situation in which the acquisition of the feature points fails, and despite receiving a reply indicating that the registration is needed from the user, the position cannot be registered. Thus, usability is improved. Since the verification process for the feature points of the parking position is started before inquiry of whether the registration is needed for the parking position to the user, it is possible to shorten a time from receiving the reply indicating that the registration is needed from the user to completion of the registration, and thus usability is improved.

(127) (11) A control program by a control device for a moving body, the control device including an outside recognition unit configured to acquire recognition data which is data of an outside of the moving body, a parking control unit configured to perform parking control to park the moving body at a parking position selected by a user of the moving body based on the recognition data, and a registration processing unit configured to register the parking position as a designated parking position, in which when the user selects the parking position, the control program causes a processor of the control device to execute processing of: detecting feature points of the parking position; starting a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired; inquiring of the user whether a registration for the designated parking position is needed after starting of the verification process; and registering the parking position as the designated parking position based on a reply to whether the registration is needed received from the user.

(128) According to (11), when the feature points of the parking position can be acquired, whether the registration is needed for the parking position is inquired of the user. Therefore, it is possible to prevent a situation in which the acquisition of the feature points fails, and despite receiving a reply indicating that the registration is needed from the user, the position cannot be registered. Thus, usability is improved. Since the verification process for the feature points of the parking position is started before inquiry of whether the registration is needed for the parking position to the user, it is possible to shorten a time from receiving the reply indicating that the registration is needed from the user to completion of the registration, and thus usability is improved.

Claims

1. A control device for a moving body, the control device comprising a processor configured to: acquire recognition data which is a data of an outside of the moving body; perform parking control to park the moving body at a parking position selected by a user of the moving body based on the recognition data; and register the parking position as a designated parking position, wherein: when the user selects the parking position, the processor is configured to: detect feature points of the parking position; start a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired; control an associated display device of the moving body to inquire of the user whether a registration for the designated parking position is needed after starting of the verification process;

- register the parking position as the designated parking position based on a reply to whether the registration is needed received from the user; and perform control to move the moving body so that the parking position is located within a predetermined range regarding the moving body.
2. The control device according to claim 1, wherein the processor is configured to control the associated display device of the moving body to inquire of the user whether the registration is needed when a parking at the parking position by the parking control is completed after the starting of the verification process.
 3. The control device according to claim 1, wherein the processor is configured to start the registration process when the number of the feature points is equal to or greater than a predetermined number.
 4. The control device according to claim 1, wherein the verification process is a process of verifying position estimation of the moving body based on the feature points.
 5. The control device according to claim 4, wherein the processor is configured to control the associated display device of the moving body to inquire of the user whether the registration is needed when a position of the moving body can be estimated based on the feature points.
 6. The control device according to claim 1, wherein the processor is configured to detect the feature points at a start point of the parking control.
 7. The control device according to claim 1, wherein when the feature points cannot be acquired at a start point of the parking control, the processor is configured to start the registration process or configured not to perform the registration process after a parking at the parking position by the parking control is completed.
 8. The control device according to claim 1, wherein when a reply indicating that the registration is not needed is received from the user in response to an inquiry of whether the registration is needed, the processor is configured to: delete data regarding the registration process, maintain data regarding the registration process until a predetermined timing and control the associated display device of the moving body to inquire again whether the registration is needed, or output guide information related to the registration to the user.
 9. A control method by a control device for a moving body, the control device including a processor configured to acquire recognition data which is data of an outside of the moving body, perform parking control to park the moving body at a parking position selected by a user of the moving body based on the recognition data, and register the parking position as a designated parking position, wherein when the user selects the parking position, the processor of the control device: detects feature points of the parking position; starts a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired; controls an associated display device of the moving body to inquire of the user whether a registration for the designated parking position is needed after starting of the verification process; registers the parking position as the designated parking position based on a reply to whether the registration is needed received from the user; and performs control of the moving body so that the parking position is located within a predetermined range regarding the moving body.
 10. A non-transitory computer-readable storage medium storing a control program by a control device for a moving body, the control device including a processor configured to acquire recognition data which is data of an outside of the moving body, perform parking control to park the moving body at a parking position selected by a user of the moving body based on the recognition data, and register the parking position as a designated parking position, wherein when the user selects the parking position, the control program causes the processor of the control device to execute processing of: detecting feature points of the parking position; starting a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired; inquiring of the user whether a registration for the designated parking position is needed after starting of the

verification process; registering the parking position as the designated parking position based on a reply to whether the registration is needed received from the user; and performing control to move the moving body so that the parking position is located within a predetermined range regarding the moving body.

11. A control device for a moving body, the control device comprising a processor configured to: acquire recognition data which is a data of an outside of the moving body; perform parking control to park the moving body at a parking position selected by a user of the moving body based on the recognition data; and register the parking position as a designated parking position, wherein: when the user selects the parking position, the processor is configured to: detect feature points of the parking position; start a registration process of registering the parking position as the designated parking position, including a verification process for the feature points when the feature point can be acquired; inquire of the user whether a registration for the designated parking position is needed after starting of the verification process; and register the parking position as the designated parking position based on a reply to whether the registration is needed received from the user, and when the feature points cannot be acquired at a start point of the parking control, the processor is configured to start the registration process or configured not to perform the registration process after a parking at the parking position by the parking control is completed.
