

# US Patent & Trademark Office

## Patent Public Search | Text View

|                      |                    |
|----------------------|--------------------|
| United States Patent | 12401110           |
| Kind Code            | B2                 |
| Date of Patent       | August 26, 2025    |
| Inventor(s)          | Kim; Gyusub et al. |

### Electronic device comprising antenna

#### Abstract

An electronic device is provided. The electronic device includes a housing including a lateral member including a first side surface, a second side surface, and a third side surface, a first conductive portion segmented through a first segmentation portion, a substrate including a ground, and a wireless communication circuit disposed on the substrate, the first conductive portion includes a first power feed unit, a second power feed unit, a first ground part, and a second ground part.

**Inventors:** Kim; Gyusub (Suwon-si, KR), Kim; Jiho (Suwon-si, KR), Seol; Kyungmoon (Suwon-si, KR), An; Seongyong (Suwon-si, KR), Lee; Minkyung (Suwon-si, KR), Jang; Kyihyun (Suwon-si, KR), Jeong; Myunghun (Suwon-si, KR), Choi; Nakchung (Suwon-si, KR)

**Applicant:** Samsung Electronics Co., Ltd. (Suwon-si, KR)

**Family ID:** 1000008778712

**Assignee:** Samsung Electronics Co., Ltd. (Suwon-si, KR)

**Appl. No.:** 18/493239

**Filed:** October 24, 2023

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20240106103 A1   | Mar. 28, 2024    |

#### Foreign Application Priority Data

|    |                 |               |
|----|-----------------|---------------|
| KR | 10-2022-0121327 | Sep. 26, 2022 |
| KR | 10-2022-0140147 | Oct. 27, 2022 |

Related U.S. Application Data

continuation parent-doc WO PCT/KR2023/014812 20230926 PENDING child-doc US 18493239

Publication Classification

Int. Cl.: H01Q1/22 (20060101); H01Q1/48 (20060101); H01Q5/40 (20150101)

U.S. Cl.:

CPC H01Q1/22 (20130101); H01Q1/48 (20130101); H01Q5/40 (20150115);

Field of Classification Search

CPC: H01Q (1/22); H01Q (1/243); H01Q (1/38-48); H01Q (1/52); H01Q (5/30-40)

References Cited

U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl. | CPC        |
|--------------|-------------|---------------|----------|------------|
| 9098241      | 12/2014     | Cho et al.    | N/A      | N/A        |
| 10498033     | 12/2018     | Zhu et al.    | N/A      | N/A        |
| 11101827     | 12/2020     | Kim           | N/A      | H01Q 5/35  |
| 11184987     | 12/2020     | Jung et al.   | N/A      | N/A        |
| 2020/0127404 | 12/2019     | Seo et al.    | N/A      | N/A        |
| 2020/0321988 | 12/2019     | Kim et al.    | N/A      | N/A        |
| 2021/0021018 | 12/2020     | Yoon et al.   | N/A      | N/A        |
| 2021/0135351 | 12/2020     | Son           | N/A      | H01Q 5/328 |
| 2021/0226319 | 12/2020     | Sung et al.   | N/A      | N/A        |
| 2022/0006176 | 12/2021     | Froese et al. | N/A      | N/A        |
| 2022/0158331 | 12/2021     | Jeon et al.   | N/A      | N/A        |
| 2022/0166867 | 12/2021     | Nam et al.    | N/A      | N/A        |
| 2022/0223998 | 12/2021     | Jang et al.   | N/A      | N/A        |
| 2023/0085200 | 12/2022     | Oh et al.     | N/A      | N/A        |
| 2023/0239385 | 12/2022     | Lee et al.    | N/A      | N/A        |

FOREIGN PATENT DOCUMENTS

| Patent No.      | Application Date | Country | CPC |
|-----------------|------------------|---------|-----|
| 10-2019-0089375 | 12/2018          | KR      | N/A |
| 10-2020-0045661 | 12/2019          | KR      | N/A |
| 10-2020-0089330 | 12/2019          | KR      | N/A |
| 10-2020-0101234 | 12/2019          | KR      | N/A |
| 10-2021-0116380 | 12/2020          | KR      | N/A |
| 10-2022-0021400 | 12/2021          | KR      | N/A |
| 10-2022-0046309 | 12/2021          | KR      | N/A |
| 10-2022-0068889 | 12/2021          | KR      | N/A |
| 10-2022-0102464 | 12/2021          | KR      | N/A |

OTHER PUBLICATIONS

*Primary Examiner:* Islam; Hasan

*Attorney, Agent or Firm:* Jefferson IP Law, LLP

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation application, claiming priority under § 365(c), of an International application No. PCT/KR2023/014812, filed on Sep. 26, 2023, which is based on and claims the benefit of a Korean patent application number 10-2022-0121327, filed on Sep. 26, 2022, in the Korean Intellectual Property Office, and of a Korean patent application number 10-2022-0140147, filed on Oct. 27, 2022, in the Korean Intellectual Property Office, the disclosure of each of which is incorporated by reference herein in its entirety.

### **TECHNICAL FIELD**

(1) The disclosure relates to an electronic device comprising an antenna.

### **BACKGROUND ART**

(2) Electronic devices are gradually becoming slimmer to meet consumers' purchase desires as the functional gap of each manufacturer decreases, and they are being developed to increase the rigidity of electronic devices, strengthen design aspects, and at the same time differentiate their functional elements. As part of this trend, an electronic device may include at least one antenna, which must be provided for communication among its components. Such an antenna may be implemented through a metal bezel (e.g., a lateral member) used as a part of a housing of an electronic device and is being developed to exhibit excellent radiation performance.

(3) The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

### **DISCLOSURE**

#### **Technical Problem**

(4) The volume and number of antennas used in the electronic device may be determined according to the frequency, bandwidth and/or type of each service. For example, a low band (LB) of about 600 megahertz (MHz) to 960 MHz, a mid band (MB) of about 1700 MHz to 2200 MHz, a high band (HB) of about 2300 MHz to 2800 MHz, or a high frequency band of about 3 gigahertz (GHz) to 300 GHz (e.g., fifth generation (5G) (new radio (NR))) (e.g., ultra-high band (UHB)/frequency range 1 (FR1), about 3.2 GHz~4.5 GHz) may be used as the main communication band. As another example, various wireless communication services such as Bluetooth™ (BT), global positioning system (GPS), or wireless fidelity (WI-FI) may be used. While a plurality of antennas must be included in an electronic device to support the above-mentioned communication bands, in an electronic device having a diversified operating structure (e.g., a rollable electronic device or a foldable electronic device), the space for antennas to be placed may be reduced. To overcome this, service bands with similar frequency bands can be combined and designed to be separated into several antennas.

(5) The electronic device may include at least one housing structure for preparing a space for accommodating electronic components. The housing structure may include a lateral member used as at least a portion of a side surface of the electronic device. In an embodiment, the lateral member

may be at least partially formed of a metal material (e.g., a conductive member, a conductive portion, or a conductive material) to reinforce the rigidity of the electronic device and/or perform a designated function (e.g., an antenna function), and the remaining portion may be formed of a polymer material (e.g., a non-conductive member, a non-conductive portion, or a non-conductive material) combined with a metal material. For example, the conductive portion of the lateral member may include at least one antenna formed through at least one non-conductive portion (e.g., a segmentation portion). For example, the conductive portion is segmented through at least one segmentation portion, and by feeding power to both sides of the segmentation portion respectively, it can be implemented as at least two antennas operating in various frequency bands.

(6) However, when antennas, having a power feed structure through two power feed units disposed on the left and right sides of the same side based on the segmentation portion, operate simultaneously (e.g., carrier aggregation (CA) mode or 4Rx mode), since the distribution of the current is formed in the same direction (e.g., a horizontal direction), isolation between antennas may be lowered and radiation performance may be deteriorated.

(7) Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide an electronic device including an antenna that may help improve radiation performance through proper segmentation and power feed of a conductive member used as a lateral member.

(8) Another aspect of the disclosure is to provide an electronic device including an antenna that may help improve isolation of antennas when power is fed to both sides of a segmentation portion.

(9) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

#### Technical Solution

(10) In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes at least one housing including a lateral member, the lateral member includes a first side surface, a second side surface extending from a first end of the first side surface, and a third side surface extending from a second end of the first side surface, a first conductive portion formed in a loop shape and segmented through a first segmentation portion when the first side surface is viewed from the outside, a substrate disposed in an inner space of the at least one housing and including a ground, and a wireless communication circuit disposed on the substrate and configured to transmit or receive a wireless signal in at least one frequency band through the first conductive portion. The first conductive portion includes a first power feed unit electrically connected to the wireless communication circuit through a first point in one direction of the first segmentation portion, a second power feed unit electrically connected to the wireless communication circuit through a second point in the other direction of the first segmentation portion, a first ground part electrically connected to the ground through the third point between the first segmentation portion and the first point in one direction, and a second ground part electrically connected to the ground through the fourth point between the second point and the first point in the other direction.

#### Advantageous Effects

(11) According to various embodiments, isolation can be improved even if the antennas operate simultaneously by being induced to have an electrical path (or current distribution) of different directions each other through a power feed structure in which, when one side of the electronic device is viewed from the outside, a loop-shaped conductive portion segmented through the segmentation portion is formed and power is fed to both sides based on the segmentation portion.

(12) Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

---

# Description

## DESCRIPTION OF DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram of an electronic device in a network environment according to an embodiment of the disclosure;

(3) FIGS. 2A and 2B are diagrams illustrating front surface and rear surface of an electronic device in a slide-in state according to various embodiments of the disclosure;

(4) FIGS. 3A and 3B are diagrams illustrating front surface and rear surface of an electronic device in a slide-out state according to various embodiments of the disclosure;

(5) FIG. 4 is an exploded perspective view of an electronic device according to an embodiment of the disclosure;

(6) FIG. 5A is a cross-sectional view of an electronic device taken along line 5a-5a of FIG. 2A according to an embodiment of the disclosure;

(7) FIG. 5B is a cross-sectional view of an electronic device in an intermediate state according to an embodiment of the disclosure;

(8) FIG. 5C is a cross-sectional view of an electronic device taken along line 5c-5c of FIG. 3A according to an embodiment of the disclosure;

(9) FIG. 6A is a partial perspective view of a first lateral member viewed from the front surface according to an embodiment of the disclosure;

(10) FIG. 6B is a partial perspective view of a first lateral member viewed from a rear surface according to an embodiment of the disclosure;

(11) FIG. 7 is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure;

(12) FIG. 8A is a diagram illustrating a current distribution of a first lateral member when the first antenna of FIG. 7 is operated according to an embodiment of the disclosure;

(13) FIG. 8B is a diagram illustrating current distribution of the first lateral member when the second antenna of FIG. 7 is operated according to an embodiment of the disclosure;

(14) FIG. 8C is a graph illustrating an isolation degree when the first and second antennas of FIG. 7 are operated according to an embodiment of the disclosure;

(15) FIG. 8D is a graph comparing the performance of a single operation of the first antenna of FIG. 7 and a simultaneous operation of the first and second antennas according to an embodiment of the disclosure;

(16) FIG. 8E is a graph comparing performances of a single operation of the second antenna of FIG. 7 and a simultaneous operation of the first and second antennas according to an embodiment of the disclosure;

(17) FIG. 9 is a configuration diagram of an electronic device including an additional ground part according to an embodiment of the disclosure;

(18) FIG. 10 is a graph comparing radiation performance according to the presence or absence of an additional ground part according to an embodiment of the disclosure;

(19) FIG. 11A is a diagram illustrating current distribution according to the operation of the first antenna of FIG. 7 according to an embodiment of the disclosure;

(20) FIG. 11B is a diagram illustrating current distribution according to the operation of the second antenna of FIG. 7 according to an embodiment of the disclosure;

(21) FIG. 12 is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure;

(22) FIG. 13 is a graph illustrating a change in frequency band of the first antenna of FIG. 12 by

configuring variable circuits according to an embodiment of the disclosure;

(23) FIG. **14** is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure;

(24) FIG. **15** is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure;

(25) FIG. **16** is a graph illustrating a change in frequency band of the second antenna of FIG. **15** by configuring variable circuits according to an embodiment of the disclosure;

(26) FIG. **17** is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure;

(27) FIG. **18** is a graph comparing isolation degrees of the first antenna and the third antenna of FIG. **17** with or without a filter according to an embodiment of the disclosure;

(28) FIG. **19** is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure;

(29) FIGS. **20A** and **20B** are diagrams of an electronic device including an antenna disposition structure according to various embodiments of the disclosure;

(30) FIGS. **21** and **22** are diagrams of an electronic device including an antenna disposition structure according to various embodiments of the disclosure;

(31) FIGS. **23A** and **23B** are views of an electronic device including a loop-shaped conductive portion according to various embodiments of the disclosure; and

(32) FIGS. **24A** and **24B** are views of an electronic device including a loop-shaped conductive portion according to various embodiments of the disclosure.

(33) Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

#### MODE FOR DISCLOSURE

(34) The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

(35) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

(36) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

(37) FIG. **1** is a block diagram illustrating an electronic device in a network environment according to an embodiment of the disclosure.

(38) Referring to FIG. **1**, an electronic device **101** in a network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, a memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connection terminal **178**, a haptic module **179**, a camera module

**180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, a drive motor control module **181**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connection terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(39) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** may include the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(40) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(41) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**. The non-volatile memory may include an internal memory **136** and an external memory **138**.

(42) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

- (43) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).
- (44) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.
- (45) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the strength of force incurred by the touch.
- (46) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.
- (47) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.
- (48) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.
- (49) The connection terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connection terminal **178** may include, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphone connector).
- (50) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.
- (51) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.
- (52) The power management module **188** may manage power fed to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).
- (53) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(54) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(55) The wireless communication module **192** may support a 5G network, after a fourth generation (4G) network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the millimeter wave (mmWave) band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 gigabits per second (Gbps) or more) for implementing eMBB, loss coverage (e.g., 164 decibels (dB) or less) for implementing mMTC, or U-plane latency (e.g., 0.5 milliseconds (ms) or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(56) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as

part of the antenna module **197**.

(57) According to various embodiments, the antenna module **197** may form an mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, an RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a lateral) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(58) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI).

(59) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic device **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic device (e.g., electronic devices **102** and **104** or the server **108**). For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) on the basis of 5G communication technology or IoT-related technology.

(60) FIGS. 2A and 2B are diagrams illustrating front surface and rear surface of an electronic device in a slide-in state according to various embodiments of the disclosure.

(61) FIGS. 3A and 3B are diagrams illustrating front surface and rear surface of an electronic device in a slide-out state according to various embodiments of the disclosure.

(62) Electronic device **200** of FIGS. 2A, 2B, 3A, and 3B may be at least partially similar to the electronic device **101** of FIG. 1 or may further include other embodiments of the electronic device.

(63) Referring to FIGS. 2A, 2B, 3A, and 3B, an electronic device **200** may include a first housing **210**, a second housing **220** slidably coupled in a designated direction (e.g., first direction {circle around (1)} or second direction {circle around (2)}) (e.g.,  $\pm y$ -axis direction) from the first housing **210**, and a flexible display **230** (e.g., a rollable display, an expandable display, a stretchable display) disposed to be supported through at least a portion of the first housing **210** and the second housing **220**. In an embodiment, the second housing **220** may be slidably coupled to the first housing so that it may be slid out in a first direction (first direction {circle around (1)}) with respect to the first housing **210**, or it may be slid in the second direction {circle around (2)}) opposite to the first direction (first direction {circle around (1)}). In an embodiment, the electronic device **200** may transition to a slide-in state (e.g., the slide-in state) by at least a portion of the second housing **220** being accommodated in at least a portion of a first space **2101** formed through the first housing **210**. In an embodiment, the electronic device **200** may transition to a slide-out

state (e.g., the slide-out state) by at least a portion of the second housing **220** being moved in an outward direction (e.g., first direction {circle around (1)}) from the first space **2101**. In an embodiment, the electronic device **200**, in the slide-out state, may form at least partially the same plane as at least a portion of the second housing **220**, and in the slide-in state, it may include a support member (e.g., support member **240** of FIG. 4) (e.g., a bendable member, a bendable support member, an articulated hinge module, or a multi-bar assembly) accommodated at least partially into the first space **2101** of the first housing **210** in a bending manner. In an embodiment, at least a portion of the flexible display **230** may be disposed in such a way that it is attached to at least a portion of the second housing **220**. In an embodiment, at least a portion of the remaining portion of the flexible display **230** may be attached to the support member **240** (e.g., the support member **240** of FIG. 4). In an embodiment, at least a portion of the flexible display **230**, in a slide-in state, may be disposed to be invisible from the outside by being accommodated into the first space **2101** of the first housing **210** in a bent manner while being supported by the support member (e.g., the support member **240** of FIG. 4). In an embodiment, at least a portion of the flexible display **230**, in a slide-out state, may be disposed to be visible from the outside while being supported by the support member (e.g., the support member **240** of FIG. 4) that forms at least partially the same plane as the second housing **220**.

(64) According to various embodiments, the electronic device **200** may include a first housing **210** that includes a first lateral member **211** and a second housing **220** that includes a second lateral member **221**. In an embodiment, the first lateral member **211** may include a first side surface **2111** having a first length; a second side surface **2112** extending in a direction (e.g., the y-axis direction) perpendicular to one end of the first side surface **2111** and having a second length; and a third side surface **2113** extending parallel to the second side surface **2112** from the other end of the first side surface **2111** and having a second length. In an embodiment, the first lateral member **211** may be at least partially formed of a conductive member (e.g., metal). In some embodiments, the first lateral member **211** may be formed by combining a conductive member and a non-conductive member (e.g., polymer). In an embodiment, the first housing **210** may include a first extension member **212** extending from at least a portion of the first lateral member **211** to at least a portion of the first space **2101**. In an embodiment, the first extension member **212** may be integrally formed with the first lateral member **211**. In some embodiments, the first extension member **212** may be formed separately from the first lateral member **211** and structurally coupled with the first lateral member **211**.

(65) According to various embodiments, the second lateral member **221** may include a fourth side surface **2211** having a third length, a fifth side surface **2212** extending to correspond to the second side surface **2112** in a direction perpendicular to one end of the fourth side surface **2211** (e.g., -y axis direction) and having a fourth length, and a sixth side surface **2213** extending to correspond to the third side surface **2113** in a direction parallel to the fifth side surface **2212** from the other end of the fourth side surface **2211** and having a fourth length. In an embodiment, the second lateral member **221** may be at least partially formed of a conductive member (e.g., metal). In some embodiments, the second lateral member **221** may be formed by combining a conductive member and a non-conductive member (e.g., polymer). In an embodiment, at least a portion of the second lateral member **221** may include a second extension member **222** extending to at least a portion of a second space **2201** of the second housing **220**. In an embodiment, the second extension member **222** may be integrally formed with the second lateral member **221**. In some embodiments, the second extension member **222** may be formed separately from the second lateral member **221** and structurally combined with the second lateral member **221**.

(66) According to various embodiments, the second side surface **2112** and the fifth side surface **2212** may be slidably coupled to each other. In an embodiment, the third side surface **2113** and the sixth side surface **2213** may be slidably coupled to each other. In an embodiment, in the slide-in state, the fifth side surface **2212** may be disposed substantially invisible from the outside by

overlapping with the second side surface **2112**. In an embodiment, in the slide-in state, the sixth side surface **2213** may be substantially invisible from the outside by overlapping with the third side surface **2113**. In some embodiments, at least a portion of the fifth side surface **2212** and the sixth side surface **2213** may be disposed to be at least partially visible from the outside in a slide-in state. In an embodiment, in the slide-in state, the second extension member **222** may be disposed substantially invisible from the outside by overlapping with the first extension member **212**. In some embodiments, the second extension member **222** may be disposed to be at least partially visible from the outside in the slid-in state.

(67) According to various embodiments, the first housing **210** may include a first rear surface cover **213** coupled to at least a portion of the first lateral member **211**. In an embodiment, the first rear surface cover **213** may be disposed in a manner coupled with at least a portion of the first extension member **212**. In some embodiments, the first rear surface cover **213** may be integrally formed with the first lateral member **211**. In an embodiment, the first rear surface cover **213** may be formed of polymer, coated or colored glass, ceramic, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of these materials. In some embodiments, the first rear surface cover **213** may extend to at least a portion of the first lateral member **211**. In some embodiments, the first rear surface cover **213** may be omitted, and at least a portion of the first extension member **212** may be replaced with the first rear surface cover **213**.

(68) According to various embodiments, the second housing **220** may include a second rear surface cover **223** coupled to at least a portion of the second lateral member **221**. In an embodiment, the second rear surface cover **223** may be disposed in a manner that is combined with at least a portion of the second extension member **222**. In some embodiments, the second rear surface cover **223** may be integrally formed with the second lateral member **221**. In an embodiment, the second rear surface cover **223** may be formed of polymer, coated or colored glass, ceramic, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of these materials. In some embodiments, the second rear surface cover **223** may extend to at least a portion of the second lateral member **221**. In some embodiments, the second rear surface cover **223** may be omitted, and at least a portion of the second extension member **222** may be replaced with the second rear surface cover **223**.

(69) According to various embodiments, the flexible display **230** may include a first portion **230a** (e.g., a flat portion) always visible from the outside and a second portion **230b** (e.g., a bendable portion or a bending portion) extending from the first portion **230a** and accommodated in a manner that is at least partially bent into the first space **2101** of the first housing **210** to be invisible from the outside in a slide-in state. In an embodiment, the first portion **230a** may be disposed to be supported by the second housing **220**, and the second portion **230b** may be disposed to receive support at least partially from the support member (e.g., the support member **240** of FIG. 4). In an embodiment, the second portion **230b** of the flexible display **230** may form substantially the same plane as the first portion **230a** and be disposed to be visible from the outside while being supported by the support member (e.g., the support member **240** of FIG. 4) in a state that the second housing **220** slides out along the first direction (first direction {circle around (1)}). In an embodiment, the second portion **230b** of the flexible display **230** may be accommodated in a manner that is bent into the first space **2101** of the first housing **210** and be disposed to be invisible from the outside in a state that the second housing **220** slides in along the second direction (second direction {circle around (2)}). Accordingly, the display area of the flexible display **230** can be varied as the second housing **220** is moved in a sliding manner along a designated direction (e.g.,  $\pm y$ -axis direction) from the first housing **210**.

(70) According to various embodiments, the flexible display **230** may have a variable length in a first direction (first direction {circle around (1)}) according to the sliding movement of the second housing **220** moving relative to the first housing **210**. For example, in the slide-in state, the flexible display **230** may have a first display area corresponding to a first length **L1** (e.g., an area

corresponding to the first portion **230a**). In an embodiment, the flexible display **230**, in the slide-out state, may be expanded to correspond to a third length **L3** longer than the first length **L1** and to have a second display area (e.g., an area including the first portion **230a** and the second portion **230b**) larger than the first display area according to the sliding movement of the second housing **220** additionally moved by a second length **L2** relative to the first housing **210**.

(71) According to various embodiments, the electronic device **200** may include at least one of an input device (e.g., a microphone **203-1**) disposed in the second space **2201** of the second housing **220**, an audio output device (e.g., a receiver **206** and/or a speaker **207** for a call), sensor modules **204** and **217**, a camera module (e.g., a first camera module **205** or a second camera module **216**), a connector port **208**, a socket device **218**, a key input device **219**, or an indicator (not shown). In an embodiment, the electronic device **200** may include another input device (e.g., a microphone **203**) disposed in the first housing **210**. In another embodiment, the electronic device **200** may be configured so that at least one of the above-described components is omitted or other components are additionally included. In some embodiments, at least one of the above-described components may be disposed in the first space **2101** of the first housing **210**.

(72) According to various embodiments, the input device may include a microphone **203-1**. In some embodiments, the input device (e.g., the microphone **203-1**) may include a plurality of microphones disposed to detect the direction of sound. The audio output device may include, for example, the receiver **206** and the speaker **207** for a call. In an embodiment, the speaker **207** may correspond to the outside through at least one speaker hole formed in the second housing **220** in a position always exposed to the outside regardless of the slide-in/the slide-out state (e.g., the fifth side surface **2212**). In an embodiment, the connector port **208** may correspond to the outside through a connector port hole formed in the second housing **220** in a slide-out state. In some embodiments, the connector port **208** may correspond to the outside through an opening formed in the first housing **210** and formed to correspond to the connector port hole. In some embodiments, the receiver **206** for a call may include a speaker (e.g., a piezo speaker) operating while excluding a separate speaker hole.

(73) According to various embodiments, the sensor modules **204** and **217** may generate electrical signals or data values corresponding to an internal operating state of the electronic device **200** or an external environmental state. In an embodiment, the sensor modules **204** and **217** may include, for example, a first sensor module **204** (e.g., a proximity sensor or an illuminance sensor) disposed on the front surface of the electronic device **200** and/or a second sensor module **217** (e.g., a heart rate monitoring (HRM) sensor) disposed on the rear surface of the electronic device **200**. In an embodiment, the first sensor module **204** may be disposed below the flexible display **230** on the front surface of the electronic device **200**. In an embodiment, the first sensor module **204** and/or the second sensor module **217** may include at least one of a proximity sensor, an illuminance sensor, a time of flight (TOF) sensor, an ultrasonic sensor, a fingerprint recognition sensor, a gesture sensor, a gyro sensor, an air pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a bio sensor, a temperature sensor, or a humidity sensor.

(74) According to various embodiments, the camera module may include a first camera module **205** disposed on the front side of the electronic device **200** and a second camera module **216** disposed on the rear surface of the electronic device **200**. In an embodiment, the electronic device **200** may include a flash (not shown) located near the second camera module **216**. In an embodiment, the camera modules **205** and **216** may include one or a plurality of lenses, an image sensor, and/or an image signal processor. In an embodiment, the first camera module **205** may be disposed under the flexible display **230** and be configured to photograph a subject through a part of an active area (e.g., a display area) of the flexible display **230**.

(75) According to various embodiments, the first camera module **205** among the camera modules and part of the first sensor module **204** among the sensor modules **204** and **217** may be disposed to detect the external environment through the flexible display **230**. For example, the first camera

module **205** or part of the first sensor module **204** may be disposed in the second space **2201** of the second housing **220** to be in contact with the external environment through a transparent area or a perforated opening formed in the flexible display **230**. In an embodiment, an area facing the first camera module **205** of the flexible display **230** may be formed as a transmissive area having a designated transmittance as a part of a display area displaying content. In an embodiment, the transmissive area may be formed to have a transmittance in a range of about 5% to about 20%. Such a transmissive area may include an area overlapping with an effective area (e.g., an angle of view area) of the first camera module **205** through which light for generating an image formed by an image sensor passes. For example, the transmissive area of the flexible display **230** may include an area in which a pixel arrangement density and/or a wiring density are lower than the surrounding area. For example, a transmissive area may replace the aforementioned opening. For example, some types of the first camera module **205** may include an under display camera (UDC). In some embodiments, some types of the first sensor module **204** may be disposed to perform their function in the second space **2201** of the second housing **220** without being visually exposed through the flexible display **230**.

(76) According to various embodiments, a slide-in/a slide-out operation of the electronic device **200** may be automatically performed. For example, the slide-in/the slide-out operation of the electronic device **200** may be performed through gear-coupling of a driving motor (e.g., the driver motor control module **181** of FIG. **1** or a driving motor **260** of FIG. **4**) including a pinion gear (e.g., pinion gear **261** of FIG. **4**) disposed in the first space **2101** of the first housing **210**, with a rack gear (e.g., a rack gear **2221** of FIG. **4**) disposed in the second space **2201** of the second housing **220** and gear-coupled with the pinion gear **261**. In some embodiments, the driving motor **260** including the pinion gear **261** may be disposed in the second space **2201** of the second housing **220** and the rack gear **2221** coupled to the pinion gear **261** may be disposed in the first space **2101** of the first housing **210**. For example, the processor (e.g., processor **120** of FIG. **1**) of the electronic device **200** may operate a driving motor (e.g., the driving motor **260** of FIG. **4**) disposed inside the electronic device **200** in the case of detecting a triggering operation to switch from a slide-in state to a slide-out state or to switch from a slide-out state to a slide-in state. In an embodiment, the triggering signal may include a signal according to a selection (e.g., a touch) of an object displayed on the flexible display **230** or a signal according to a manipulation of a physical button (e.g., a key button) included in the electronic device **200**. In some embodiments, a slide-in/a slide-out operation of the electronic device **200** may be performed manually by the manipulation of a user.

(77) According to various embodiments, the electronic device **200** has a structure in which the second housing **220** slides in and/or slides out relative to the first housing **210** along a longitudinal direction (e.g., a vertical direction) (e.g., a  $\pm y$ -axis direction) of the electronic device **200**, but is not limited thereto. For example, the electronic device **200** may have a structure in which the second housing **220** slides in and/or slides out relative to the first housing **210** along a width direction (e.g., a horizontal direction) (e.g., a  $\pm x$ -axis direction) perpendicular to a length direction of the electronic device **200**. In some embodiments, the electronic device **200** may be formed such that the length of the first side surface **2111** of the first housing **210** is longer than the length of the second side surface **2112**. In this case, the length of the fourth side surface **2211** of the second housing **220** may also be formed to be longer than the length of the fifth side surface **2212** corresponding to this.

(78) According to various embodiments, the electronic device **200** may include at least one antenna element (e.g., antenna element **224b** of FIG. **4**) electrically connected to the wireless communication circuit (e.g., the wireless communication module **192** of FIG. **1**) disposed in an inner space (e.g., the second space **2201** of the second housing **220**). In some embodiments, the electronic device **200** may be disposed in an inner space (e.g., the first space **2101** or the second space **2201**), and it may include further at least one antenna module (e.g., an mmWave antenna module or mmWave antenna structure) disposed to transmit or receive the wireless signal in a

frequency band ranging from 3 GHz to 100 GHz through another wireless communication circuit (e.g., the wireless communication module **192** of FIG. **1**).

(79) According to an embodiment of the disclosure, the electronic device **200** may include at least one antenna A disposed through at least a portion of the first lateral member **211** of the first housing **210**. In an embodiment, the at least one antenna A, when viewing the first side surface **2111** from the outside (e.g., when viewing the first side surface **2111** from the front), may be formed in a loop shape (e.g., a ring shape), and it may include a first conductive portion **310** (e.g., a first conductive member) at least partially segmented through a first segmentation portion **320** (e.g., a non-conductive portion or a polymer). In an embodiment, the first conductive portion **310** may be segmented from a surrounding second conductive portion **311** at the second side surface **2112** through a second segmentation portion **321** (e.g., a non-conductive portion or polymer). In an embodiment, the first conductive portion **310** may be segmented at the third side surface **2113** from a surrounding third conductive portion **312** through a third segmentation portion **322** (e.g., a non-conductive portion or a polymer). Therefore, the first conductive portion **310** may be disposed as a unit conductive member separated from the surrounding conductive portions (e.g., the second and third conductive portions **311** and **312**) through the second and third segmentation portions **321** and **322**, and it may be used as at least one antenna A. In an embodiment, the electronic device **200** may include a wireless communication circuit (e.g., the wireless communication module **192** of FIG. **1**) electrically connected to the first conductive portion **310**. In an embodiment, the wireless communication circuit (e.g., the wireless communication module **192** of FIG. **1**) may be configured to transmit or receive at least one frequency band (e.g., about 600 MHz to 9000 MHz) (e.g., a legacy band or NR band) through the first conductive portion **310**. In an embodiment, the electronic device **200** may include a side surface cover **2111a** disposed on the first side surface **2111** to cover at least a portion of the first segmentation portion **320** (covered or concealed). In some embodiments, the loop-shaped first conductive portion **310** used as the at least one antenna A may be formed on at least one side surface of the second side surface **2112** and/or the third side surface **2113**. In some embodiments, the loop-shaped first conductive portion **310** used as the at least one antenna A may be formed at least one side surface of the fourth side surface **2211**, the fifth side surface **2212**, or the sixth side surface **2213** of the second housing **220**.

(80) According to an embodiment of the disclosure, in at least one antenna A1, an isolation can be improved even if the antennas operate simultaneously by being induced to have an electrical path (or current distribution) of different directions each other through a power feed structure in which power is fed to both sides of the first conductive portion **310** based on the first segmentation portion.

(81) FIG. **4** is an exploded perspective view of an electronic device according to an embodiment of the disclosure.

(82) In describing the electronic device **200** of FIG. **4**, the same reference numerals are assigned to components substantially the same as those of the electronic device **200** of FIGS. **2A**, **2B**, **3A**, and **3B**, and detailed descriptions thereof may be omitted.

(83) Referring to FIG. **4**, the electronic device **200** may include a first housing **210** including a first space **2101**, a second housing **220** slidably coupled to the first housing **210** and including a second space **2201**, a support member **240** fixed to at least a portion of the second housing **220** and at least partially bendably accommodated in the first space **2101** according to a slide-in operation, a flexible display **230** disposed to be supported by at least a portion of the support member **240** and the second housing **220**, and a driving module (e.g., a driving mechanism) driving the second housing **220** in a slide-in direction (e.g., -y axis direction) and/or in a slide-out direction (e.g. +y axis direction) from the first housing **210**. In an embodiment, the first housing **210** may include a first lateral member **211** and a first rear surface cover **213** coupled to at least a portion (e.g., at least a portion of the first extension member **212**) of the first lateral member **211**. In an embodiment, the second housing **220** may include a second lateral member **221** and a second rear surface cover **223**

coupled to at least a portion (e.g., at least a portion of the second extension member **222**) of the second lateral member **221**. In an embodiment, the driving module may include a driving motor **260** disposed in the first space **2101** and including a pinion gear **261** and a rack gear **2221** disposed to be gear-coupled to the pinion gear **261** in the second space **2201**. In an embodiment, the driving module may include further a deceleration module (e.g., a deceleration gear assembly) disposed to reduce rotational speed and increase a driving force by being coupled with the driving motor **260**. In an embodiment, the driving motor **260** may be disposed to be supported through a motor bracket **260a** disposed in a support bracket **225** which is disposed in the first space **2101** of the first housing **210**. In an embodiment, the driving motor **260**, in the first space **2101**, may be fixed in the end (e.g., the edge area) of the support bracket **225** in the slide-out direction (e.g., y axis direction). In an embodiment, the rack gear **2221** may be disposed in such a way as to be fixed to the second extension member **222** of the second housing **220**. In some embodiments, the rack gear **2221** may be formed integrally with at least a portion of the second extension member **222** by being injected. In an embodiment, the rack gear **2221** may be disposed to have a length in a direction parallel to the sliding direction) (e.g.,  $\pm y$ -axis direction). Accordingly, when the electronic device **200** is assembled, the pinion gear **261** may maintain a gear-coupled state with the rack gear **2221**, and, as a result, the second housing **220** may be moved relative to the first housing **210** by the pinion gear **261** receiving the driving force of the driving motor **260** being moved along the rack gear **2221**. In an embodiment, the sliding distance of the second housing **220** may be determined by the length of the rack gear **2221**.

(84) According to various embodiments, the electronic device **200** may include a plurality of electronic components disposed in the second space **2201**. In an embodiment, the plurality of electronic components may include a first substrate **251** (e.g., a main board), a second camera module **216** disposed around the first substrate **251**, a speaker **207**, and a connector port **208** and a microphone **203-1**. In an embodiment, since the plurality of electronic components are disposed around the first substrate **251** in the second space **2201** of the second housing **220**, efficient electrical connection may be possible. In some embodiments, at least one of the plurality of electronic components described above may be disposed in the first space **2101** of the first housing **210**.

(85) According to various embodiments, the electronic device **200** may include a rear bracket **224** disposed between the second extension member **222** and the second rear surface cover **223** in the second housing **220**. In an embodiment, the rear bracket **224** may be disposed to cover at least a portion of the plurality of electronic components. In an embodiment, the rear bracket **224** may be structurally coupled to at least a portion of the second extension member **222**. In some embodiments, the rear bracket **224** may be omitted. In an embodiment, the rear bracket **224** may cover a plurality of electronic components and may be disposed to support the second rear surface cover **223**. In an embodiment, the rear bracket **224** may include an opening **224a** (e.g., a through hole) formed in an area corresponding to the second camera module **216** and/or a sensor module (e.g., the second sensor module **217** of FIG. 3B) or a notch area **224c** (e.g., a cutting part). In an embodiment, the rear bracket **224** may include at least one antenna element **224b**. In an embodiment, the at least one antenna element **224b** may be disposed on an outer surface (e.g., the surface facing  $-z$ -axis) of the rear bracket **224** when it is formed of an injection material (e.g., an antenna carrier) of a dielectric material. In an embodiment, the at least one antenna element **224b** may include a laser direct structuring (LDS) antenna pattern formed on an outer surface of the rear bracket **224**. In some embodiments, the at least one antenna element **224b** may include a conductive plate attached to the outer surface of the rear bracket **224**, a conductive paint formed on the outer surface, or a conductive pattern. In some embodiments, the at least one antenna element **224b** may be disposed in a built-in manner when the rear bracket **224** is injected. In an embodiment, the at least one antenna element **224b** may be configured to transmit or receive wireless signals in a designated frequency band (e.g., a legacy band) by being electrically

connected to a wireless communication circuit (e.g., the wireless communication module **192** of FIG. **1**) disposed on the first substrate **251**. In an embodiment, the second camera module **216** and/or the second sensor module **217** may be disposed to detect an external environment through the opening **224a** or notch area **224a**. In an embodiment, at least an area corresponding to the second camera module **216** and/or the second sensor module **217** of the second rear surface cover **223** may be transparently processed. In some embodiments, the second rear surface cover **223** may include a through hole formed in an area corresponding to at least the second camera module **216** and/or the second sensor module **217**. In this case, the through hole may be covered through the transparent window. In some embodiments, the second camera module **216** and/or second sensor module **217** may be configured to operate only when the electronic device **200** is in a slide-out state.

(86) According to various embodiments, the electronic device **200** may include the support bracket **225** disposed in the first space **2101** of the first housing **210**. In an embodiment, the support bracket **225** may be disposed at one end and have a support part **2252** formed in a curved outer surface to support the rear surface of the support member **240** that is bent during a sliding operation transitioning from a slide-out state to a slide-in state. In an embodiment, the support bracket **225** may include a support structure for supporting and fixing the driving motor **260** through the motor bracket **260a**. In an embodiment, the support bracket **225** may include a battery seat **2251** for accommodating the battery. In an embodiment, the driving motor **260** may be disposed at the most end (e.g., edge) of the support bracket **225** in a slide-out direction (e.g., the y-axis direction). For example, when the assembly of the electronic device **200** is completed, the driving motor **260** may help minimize the size and/or length of a flexible board F1 (e.g., the flexible printed circuit board (FPCB) that electrically connects the first substrate **251** and the driving motor **260** by being disposed relatively close to the first substrate **251** among the electronic components disposed on the first housing **210**. In an embodiment, the electronic device **200** may include a pair of guide rails **226** disposed on both sides of the support bracket **225** to guide both ends of the support member **240** in a sliding direction.

(87) According to various embodiments, the first housing **210** may include the second camera module **216** disposed on the second housing **220** when the electronic device **200** is in a slide-in state in the first extension member **212** and/or an opening **212a** (e.g., a through hole) disposed in an area corresponding to the second sensor module **217**. In an embodiment, the second camera module **216** and/or the second sensor module **217**, when the electronic device **200** is in a slide-in state, may detect the external environment through the opening **212a** formed in the first housing **210**. In some embodiments, an area of the first rear surface cover **213** corresponding to the second camera module **216** and/or the second sensor module **217** may be transparently processed.

(88) According to various embodiments, the electronic device **200** may include a second substrate **252** (e.g., a sub substrate) and an antenna member **253** disposed between the first extension member **212** and the first rear surface cover **213** in the first housing **210**. In an embodiment, the second substrate **252** and the antenna member **253** may be disposed on at least a portion of the first extension member **212**. In an embodiment, the second substrate **252** and the antenna member **253** may be electrically connected to the first substrate **251** through at least one electrical connection member (e.g., a flexible printed circuit board (FPCB) or a flexible radio frequency (RF) cable (FRC)). In an embodiment, the antenna member **253** may include a multi-function coil or multi-function core (MFC) antenna for performing a wireless charging function, a near field communication (NFC) function, and/or an electronic payment function. In some embodiments, the antenna member **253** may be electrically connected to the first substrate **251** through the second substrate **252** by being electrically connected to the second substrate **252**. In some embodiments, the second substrate **252** and/or the antenna member **253** may be connected to the first substrate **251** through at least a portion of the flexible board F1 connecting the driving motor **260** and the first substrate **251**.

(89) FIG. 5A is a cross-sectional view of an electronic device taken along line 5a-5a of FIG. 2A according to an embodiment of the disclosure. FIG. 5B is a cross-sectional view of an electronic device in an intermediate state according to an embodiment of the disclosure. FIG. 5C is a cross-sectional view of an electronic device taken along line 5c-5c of FIG. 3A according to an embodiment of the disclosure.

(90) In the description of the electronic device **200** of FIGS. 5A to 5C, the same reference numerals are assigned to components substantially the same as those of the electronic device **200** of FIG. 4, and detailed descriptions thereof may be omitted.

(91) Referring to FIGS. 5A to 5C, the electronic device **200** may include a first housing **210** having a first space **2101**, a second housing **220** having a second space **2201**, a support member **240** connected to the second housing **220** and at least partially accommodated in the first space **2101** in a slide-in state, a flexible display **230** disposed to receive support of at least a portion of the support member **240** and at least a portion of the second housing **220**, and a driving motor **260** disposed in the first space **2101** and including a pinion gear (e.g., the pinion gear **261** of FIG. 4) gear-coupled to a rack gear (e.g., the rack gear **2221** of FIG. 4) of the second space **2201**. In an embodiment, the driving motor **260** may move automatically the second housing **220** relative to the first housing **210** in a slide-in direction (second direction {circle around (2)}) or in a slide-out direction (first direction {circle around (1)}) through the gear-coupling of the pinion gear (e.g., the pinion gear **261**) and the rack gear (e.g., the rack gear **2221**).

(92) According to various embodiments, in the slide-in state of the electronic device **200** (the state of FIG. 5A), at least a portion of the second housing **220** may be accommodated in the first space **2101** of the first housing **210**. In an embodiment, at least a portion of the flexible display **230** may be disposed to be invisible from the outside by being accommodated along with the supporting member **240** in a manner of being bent into the first space **2101**. In this case, the first display area (e.g., the display area corresponding to the first portion **230a** of FIG. 3A) of the flexible display **230** may be exposed to the outside.

(93) According to various embodiments, the electronic device **200** may transition from an intermediate state (the state shown in FIG. 5B) to a slide-out state (the state shown in FIG. 5C) by controlling driving of the driving motor **260**. In some embodiments, the electronic device **200** may be configured to stop in a designated intermediate state between a slide-in state and a slide-out state (free stop function). In some embodiments, the electronic device **200** may transition to a slide-in state, an intermediate state, or a slide-out state through a user's manipulation in a state in which driving force is not provided to the driving motor **260**.

(94) According to various embodiments, at least a portion of the second housing **220** may transition to a slide-out state exposed to the outside at least partially from the first housing **210** along the first direction (first direction {circle around (1)}) by driving the driving motor **260**. In an embodiment, the part of the flexible display **230** slid into the first space **2101** may be at least partially exposed to the outside by the flexible display **230** being supported by the support bracket **225** in the slide-out state of the electronic device **200** (the state of FIG. 5C) and moving together with the support member **240**. In this case, the second display area (e.g., the display area including the first portion **230a** and the second portion **230b** of FIG. 3A) of the flexible display **230**, which is larger than the first display area, may be exposed to the outside.

(95) According to various embodiments, the electronic device **200** may include a battery B disposed through the battery seat **2251** of the support bracket **225** fixed to the first space **2101** of the first housing **210**. In an embodiment, since the battery B is disposed in the first housing **210**, a separate driving gap for avoiding interference with surrounding structures according to movement may not be required. Accordingly, the battery B may help reduce sagging of the flexible display **230** and improve operational reliability by being expanded in thickness in such a way of approaching or contacting the rear surface of the support member **240** from the battery seat **2251** of the support bracket **225** so that the battery volume is relatively increased and the moving support

member **240** is supported. In some embodiments, the battery B may be disposed in the second space **2201** of the second housing **220**.

(96) FIG. **6A** is a partial perspective view of a first lateral member viewed from the front surface according to an embodiment of the disclosure. FIG. **6B** is a partial perspective view of a first lateral member viewed from a rear surface according to an embodiment of the disclosure.

(97) Referring to FIGS. **6A** and **6B**, an electronic device (e.g., the electronic device **200** of FIG. **3A**) may include a first lateral member **211** disposed as at least a portion of a first housing (e.g., the first housing **210** of FIG. **3A**). In an embodiment, the first lateral member **211** may include a first side surface **2111** disposed on the lower side (e.g., -y axis direction) of the electronic device **200**, a second side surface **2112** extending substantially vertically from both ends of the first side surface **2111**, and a third side surface **2113**. In an embodiment, the first lateral member **211** may include a conductive member **211a** (e.g., metal) and a non-conductive member **211b** (e.g., polymer) combined with the conductive member **211a**. In an embodiment, the conductive member **211a** and the non-conductive member **211b** may be coupled through injection or structurally coupled. In an embodiment, the conductive member **211a** may form at least a portion of a side surface (e.g., first, second, and third side surfaces **2111**, **2112**, and **2113**) of the electronic device **200** and be visible from the outside. In an embodiment, the first lateral member **211** may include the first extension member **212** extending into the inner space of the first housing **210** (e.g., the first space **2101** of FIG. **3A**). In an embodiment, at least a portion of the first extension member **212** may be formed of the non-conductive member **211b**.

(98) According to various embodiments, the electronic device **200** may include the first conductive portion **310** formed through at least a portion of the first lateral member **211**. In an embodiment, when the first conductive portion **310** is viewed from the outside, the first conductive portion **310** may be formed in a loop shape (e.g., a ring shape or a loop shape), and at least a portion may be segmented through the first segmentation portion **320** (e.g., non-conductive portions or polymers). In this case, an internal opening **3101** (e.g., a slot or a slit) formed by the first segmentation portion **320** and the loop-shaped first conductive portion **310** may be filled with the non-conductive member **211b**. In an embodiment, the internal opening **3101** may be formed in various shapes, such as a circle, an oval, a quadrangle, or a quadrangle with both ends curved. In an embodiment, the first conductive portion **310** may be segmented from the second conductive portion **311** on the second side surface **2112** through the second segmentation portion **321**. In an embodiment, the first conductive portion **310** may be segmented from the surrounding third conductive portion **312** through the third segmentation portion **322** on the third side surface **2113**. In an embodiment, the second segmentation portion **321** and the third segmentation portion **322** may be filled with the non-conductive member **211b**. Therefore, the first conductive portion **310** may be disposed as a unit conductive member separated from the surrounding conductive portions (e.g., the second and third conductive portions **311** and **312**) through the second and third segmentation portions **321** and **322**, and it may be used as at least one antenna. In an embodiment, the first conductive portion **310**, the second conductive portion **311**, or the third conductive portion **312** may be segmented from the conductive member **211a** through the segmentation portions **320**, **321**, and **322**.

(99) According to various embodiments, the first lateral member **211** may be disposed on at least a portion area of the first extension member **212** and include a plurality of exposed connection pieces **310a**. In an embodiment, the plurality of connection pieces **310a** may be electrically separated from the surrounding conductive member **211a** through the non-conductive member **211b** and electrically connected to at least a portion of the first conductive portion **310**. In an embodiment, the plurality of connection pieces **310a** may extend from the first conductive portion **310** or may be individually disposed and electrically connected to the first conductive portion **310**. In an embodiment, the plurality of connection pieces **310a** may be electrically connected through the substrate (e.g., the second substrate **252** of FIG. **4**) disposed to be supported through the first extension member **212** and an electrical connection member (e.g., C-clip). For example, the first

conductive portion **310** may be electrically connected to a wireless communication circuit (e.g., the wireless communication module **192** of FIG. **1**) disposed on a substrate (e.g., the second substrate **252** of FIG. **4**) through the plurality of connection pieces **310a**. In some embodiments, the wireless communication circuit **192** may be electrically connected to the second substrate **252** disposed in the first housing **210** and may be disposed on the substrate (e.g., the first substrate **251** in FIG. **4**) disposed in the second housing **220**.

(100) FIG. **7** is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure.

(101) The first lateral member **211** of FIG. **7** may be at least partially similar to the first lateral member **211** of FIGS. **6A** and **6B**, or may further include other embodiments of the first lateral member **211**.

(102) Referring to FIG. **7**, the electronic device **200** may include a first lateral member **211** disposed as at least a portion of the first housing (e.g., the first housing **210** of FIG. **3A**). In an embodiment, the first lateral member **211** may include the first conductive portion **310** segmented into unit conductive portions by at least a portion of the conductive member (e.g., the conductive member **211a** of FIG. **6A**) being segmented through at least one segmentation portion (e.g., the second segmentation portion **321** and the third segmentation portion **322**). In an embodiment, the first conductive portion **310** may be formed in a loop shape in which a portion of the first conductive portion **310** is open through the first segmentation portion **320** on the first side surface **2111**. In an embodiment, the first conductive portion **310** may maintain a state electrically disconnected from surrounding conductive portions (e.g., the second conductive portion **311** and the third conductive portion **312**) through a second segmentation portion **321** disposed on a portion of the second side surface **2112** and a third segmentation portion **322** disposed on a portion of the third side surface **2113**. In an embodiment, the first segmentation portion **320** may be disposed in a symmetrical position on the left and right sides or may be formed in an asymmetrical position skewed to one side.

(103) According to various embodiments, the electronic device **200** may include a substrate (e.g., the second substrate **252**) disposed in the first housing **210** and including a ground G, and a wireless communication circuit **192** disposed on the substrate **252**. In an embodiment, the first conductive portion **310** can be electrically connected, at least in part, to the substrate **252** at at least one location. For example, the first conductive portion **310** may be electrically connected to the wireless communication circuitry **192** at at least one location. In an embodiment, the first conductive portion **310** may be electrically connected to the ground G of the substrate **252** at at least one location. In an embodiment, the wireless communication circuit **192** may be electrically connected to the processor **120** (e.g., the communication processor (CP)) disposed on the substrate **252**.

(104) According to various embodiments, the first conductive portion **310** may include a first power feed unit PF1 electrically connected to the wireless communication circuit **192** at a first point P1 between the second side surface **2112** and the first segmentation portion **320** in one direction of the first segmentation portion **320** (e.g., third direction {circle around (3)}). In an embodiment, the first power feed unit PF1 may be electrically connected to the wireless communication circuit **192** through a first electrical path **2521** (e.g., an electrical wire) disposed on the substrate **252**. In an embodiment, the electronic device **200** may include a matching circuit M1 (e.g., a capacitor and/or an inductor) disposed in the first electrical path **2521**. In an embodiment, the first conductive portion **310** may include a second power feed unit PF2 electrically connected to the wireless communication circuit **192** at a second point P2 between the third side surface **2113** and the first segmentation portion **320** in the other direction of the first segmentation portion **320** (e.g., fourth direction {circle around (4)}). In an embodiment, the second power feed unit PF2 may be electrically connected to the wireless communication circuit **192** through a second electrical path **2522** (e.g., an electrical wire) disposed on the substrate **252**. In an embodiment, the electronic

device **200** may include a matching circuit **M2** (e.g., a capacitor and/or an inductor) disposed in the second electrical path **2522**. In an embodiment, the first conductive portion **310** may include a first ground part **G1** electrically connected to the ground **G** of the substrate **252** at a third point **P3** between the first segmentation portion **320** and the first point **P1** in the direction of the second side surface **2112** (e.g., third direction {circle around (3)}). In an embodiment, the first conductive portion **310** may include a second ground part **G2** electrically connected to the ground **G** of the substrate **252** at a fourth point **P4** between the second point **P2** and the third side surface **2113** in the direction of the third side surface **2113** (e.g., fourth direction {circle around (4)}). In an embodiment, the fourth point **P4** may be disposed closer to the second point **P2** than to the first point **P1**. In an embodiment, the first power feed unit **PF1**, the second power feed unit **PF2**, the first ground part **G1** and/or the second ground part **G2** may be the position of the plurality of connection pieces **310a** extended from the first conductive portion **310** of FIG. **6A**. In an embodiment, the first power feed unit **PF1**, the second power feed unit **PF2**, the first ground part **G1** and/or the second ground part **G2** may be disposed collinearly in the loop-shaped first conductive portion **310**.

(105) According to various embodiments, the electronic device **200** may include a pair of antennas **A1** and **A2** including at least a portion of the first conductive portion **310**. In an embodiment, the pair of antennas **A1** and **A2** may include a first antenna **A1** in which power is fed through the first power feed unit **PF1** and which has a first electrical length **EP1** from the first ground part **G1** to the second ground part **G2**, not through the first segmentation portion **320**, and a second antenna **A2** in which power is fed through the second power feed unit **PF2** and which has a second electrical length **EP2** from the second ground part **G2** to the first ground part **G1**, through the first segmentation portion **320**. In an embodiment, the first electrical length **EP1** may be configured to be longer than the second electrical length **EP2**. Accordingly, the first antenna **A1** operating through the first power feed unit **PF1** may operate in the first frequency band (e.g., low band), and the second antenna **A2** operating through the second power feed unit **PF2** may operate in a second frequency band (e.g., mid band and/or high band) higher than the first frequency band.

(106) The antennas **A1** and **A2** configured through the loop-shaped first conductive portion **310** according to various embodiments of the disclosure may not share the first segmentation portion **320** even if they operate simultaneously by having the electrical length in opposite directions (e.g., third direction {circle around (3)} and fourth direction {circle around (4)})) that goes away from the first segmentation portion **320** each other with respect to the first segmentation portion **320**. The disposition structure of the power feed units **PF1** and **PF2** and the ground parts **G1** and **G2** may help increase isolation of the two antennas **A1** and **A2**.

(107) FIG. **8A** is a diagram illustrating a current distribution of a first lateral member when the first antenna of FIG. **7** is operated according to an embodiment of the disclosure. A part (a) of the FIG. **8A** is diagrams illustrating rear surface the first housing **210** of the electronic device **200**. A part (b) of the FIG. **8A** is diagrams illustrating front surface the first housing **210** of the electronic device **200**. It may be identified that, in the first conductive portion **310**, a high current density is distributed from the first ground part **G1** to the second ground part **G2** through a portion of the front surface of the first lateral member **211** without passing through the first segmentation portion **320** based on the first power feed unit **PF1**.

(108) FIG. **8B** is a diagram illustrating current distribution of the first lateral member when the second antenna of FIG. **7** is operated according to an embodiment of the disclosure. A part (a) of the FIG. **8B** is diagrams illustrating rear surface the first housing **210** of the electronic device **200**. A part (b) of the FIG. **8B** is diagrams illustrating the first side surface **2111** of the first housing **210** of the electronic device **200**. It may be identified that, in the first conductive portion **310**, a high current density is distributed between the first ground part **G1** and the second ground part **G2** through the first segmentation portion **320** based on the second power feed unit **PF2**.

(109) This may mean that isolation between the two antennas **A1** and **A2** is increased because of mutual interference by forming current densities at positions that do not overlap with each other

even when the two antennas **A1** and **A2** operate simultaneously.

(110) FIG. **8C** is a graph illustrating an isolation degree when the first and second antennas of FIG. **7** are operated according to an embodiment of the disclosure. It may be identified that excellent isolation of  $-15$  dB or less is expressed in low band, mid band, and high band when the first and second antennas **A1** and **A2** of FIG. **7** are operated.

(111) FIG. **8D** is a graph comparing the performance of a single operation of the first antenna of FIG. **7** and a simultaneous operation of the first and second antennas according to an embodiment of the disclosure. It may be identified that the radiation efficiency when the first antenna **A1** operates alone and the radiation efficiency when the first antenna **A1** and the second antenna **A2** operate at the same time are substantially the same. This may mean that even if the first antenna **A1** and the second antenna **A2** operate simultaneously, interference by the counterpart antenna is reduced and isolation is increased.

(112) FIG. **8E** is a graph comparing performances of a single operation of the second antenna of FIG. **7** and a simultaneous operation of the first and second antennas according to an embodiment of the disclosure. It may be identified that the radiation efficiency when the second antenna **A2** operates alone and the radiation efficiency when the first antenna **A1** and the second antenna **A2** operate at the same time are substantially the same. This may mean that even if the first antenna **A1** and the second antenna **A2** operate simultaneously, interference by the counterpart antenna is reduced and isolation is increased.

(113) FIG. **9** is a configuration diagram of an electronic device including an additional ground part according to an embodiment of the disclosure.

(114) In describing the electronic device of FIG. **9**, the same reference numerals are assigned to components substantially the same as those of the electronic device of FIG. **7**, and detailed descriptions thereof may be omitted.

(115) Referring to FIG. **9**, the electronic device **200** may include a loop-shaped first conductive portion **310** disposed on a first side surface **2111** and segmented through a first segmentation portion **320**. In an embodiment, the first conductive portion **310** may be segmented from the surrounding conductive portions (e.g., the second conductive portion **311** and/or the third conductive portion **312**) through the second segmentation portion **321** disposed on the second side surface **2112** and the third segmentation portion **322** disposed on the third side surface **2113**.

(116) According to various embodiments, the first conductive portion **310** may include a third ground part **G3** disposed on the fifth point **P5** between the second ground part **G2** and the third side surface **2113** in the third side surface **2113** direction (e.g., fourth direction {circle around (4)}) and electrically connected to the ground **G** of the substrate **252**, and a fourth ground part **G4** disposed on the sixth point **P6** between the third ground part **G3** and the third side surface **2113** and electrically connected to the ground **G** of the substrate **252**. In an embodiment, the third ground part **G3** or the fourth ground part **G4** may be provided to increase the degree of isolation by reducing the phenomenon in which the first antenna **A1** is interfered by the second power feed unit **PF2**. In some embodiments, the third ground part **G3** or the fourth ground part **G4** may be omitted. In some embodiments, the first conductive portion **310** may include further at least one additional ground part disposed between the fourth ground part **G4** and the first power feed unit **PF1** in a third side surface direction (e.g., fourth direction {circle around (4)}) from the fourth ground part **G4**.

(117) According to various embodiments, the first conductive portion **310** may include a fifth ground part **G5** disposed on the seventh point **P7** between the first ground part **G1** and the first segmentation portion **320** in the second side surface **2112** direction (e.g., third direction {circle around (3)}) and electrically connected to the ground **G** of the substrate **252**, and a sixth ground part **G6** electrically connected to the ground **G** of the substrate **252** in the eighth point **P8** between the fifth ground part **G5** and the first segmentation portion **320**. In an embodiment, the fifth ground part **G5** or the sixth ground part **G6** may be provided to increase the degree of isolation by reducing the phenomenon in which the second antenna **A2** is interfered by the second power feed unit **PF2**.

In some embodiments, the fifth ground part G5 or the sixth ground part G6 may be omitted. In some embodiments, the first conductive portion 310 may include further at least one additional ground part disposed between the sixth ground part G6 and the first segmentation portion 320.

(118) FIG. 10 is a graph comparing radiation performance according to the presence or absence of an additional ground part according to an embodiment of the disclosure.

(119) Referring to FIG. 10, it may be identified that excellent isolation of -15 dB or less is expressed in all of low band (LB) and mid band (MB) in the case that each of the ground parts G1 and G2 is included for the first antenna A1 and the second antenna A2 of FIG. 7 (graph 1001), and the third and fourth ground parts G3 and G4 are added for the first antenna A1 and the fifth and sixth ground parts G5 and G6 are added for the second antenna A2 (graph 1002).

(120) According to various embodiments, it may be identified that, when the third and fourth ground parts G3 and G4 and the fifth and sixth ground parts G5 and G6 are added, isolation between the first antenna A1 and the second antenna A2 (graph 1002) is increased more than the isolation (graph 1001) of the first and second antennas A1 and A2 having one of each ground part G1 and G2 for the first and second antennas A1 and A2. This may mean that the added ground parts G3, G4, G5, and G6 can help increase isolation of the first and second antennas A1 and A2.

(121) FIG. 11A is a diagram illustrating current distribution according to the operation of the first antenna of FIG. 7 according to an embodiment of the disclosure. The first antenna A1 fed with power through the first power feed unit PF1 operates through a portion of the first conductive portion 310 and a portion of the second side surface 2112 having a length in the y-axis direction, the direction of the surface current applied to the electronic device 200 may be substantially parallel to the y-axis direction.

(122) FIG. 11B is a diagram illustrating current distribution according to the operation of the second antenna of FIG. 7 according to an embodiment of the disclosure. In the second antenna A2 fed with power through the second power feed unit PF2, the electrical length is determined as a part corresponding to the first side surface 2111 of the first conductive portion 310 by the first ground part G1 and the second ground part G2, and only the first segmentation portion 320 operates through coupling, the surface current applied to the electronic device 200 may be substantially parallel to the x-axis direction.

(123) This may mean that even when the first antenna A1 and the second antenna A2 are simultaneously operated, surface currents are induced in different directions and isolation is increased.

(124) FIG. 12 is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure.

(125) In describing the electronic device 200 of FIG. 12, the same reference numerals are assigned to components substantially the same as those of the electronic device 200 of FIG. 7, and detailed descriptions thereof may be omitted.

(126) Referring to FIG. 12, the first conductive portion 310 may include, in the third side surface 2113 direction (e.g., fourth direction {circle around (4)}), a third ground part G3 disposed at the fifth point P5 between the second ground part G2 and the third side surface 2113 and electrically connected to the ground G of the substrate 252, and a fourth ground part G4 disposed at the sixth point P6 between the third ground part G3 and the third side surface 2113 and electrically connected to the ground G of the substrate 252. In an embodiment, the electronic device 200 may include a first variable circuit T1 (tunable IC or switching device) disposed in an electrical path connecting the ground G of the substrate 252 and the third ground part G3, and/or a second variable circuit T2 (tunable IC or switching device) disposed in an electrical path connecting the ground G of the substrate 252 and the fourth ground part G4. In an embodiment, the first variable circuit T1 and/or the second variable circuit T2, for example, may include a switching device and a plurality of passive elements (e.g., capacitor or inductor) switched to either one through the switching device. In some embodiments, the first variable circuit T1 and/or the second variable

circuit **T2** may include only a switching device selectively connecting the third ground part **G3** and/or the fourth ground part **G4** to the ground **G** of the substrate **252**. In an embodiment, the first variable circuit **T1** or the second variable circuit **T2** may be disposed under the control of the processor **120** and may be electrically connected to one of each ground parts **G3** and **G4** in various ways according to state information of the electronic device **200**. For example, the processor **120** may electrically connect (short) or disconnect (open) the third ground part **G3** to the ground **G** of the substrate **252** through the first variable circuit **T1**. In an embodiment, the processor **120** may electrically connect (short) or disconnect (open) the fourth ground part **G4** to the ground **G** of the substrate **252** through the second variable circuit **T2**. In an embodiment, the processor **120** may also connect the passive element having a designated value to the third ground part **G3** and/or the fourth ground part **G4** through the control of the first variable circuit **T1** and/or the second variable circuit **T2**. In an embodiment, the operating frequency band of the first antenna **A1** may be shifted through the first variable circuit **T1** and/or the second variable circuit **T2** under the control of the processor **120**.

(127) FIG. **13** is a graph illustrating a change in frequency band of the first antenna of FIG. **12** by configuring variable circuits according to an embodiment of the disclosure.

(128) Referring to FIG. **13**, the first antenna **A1** may be operated in the first frequency band (graph **1301**) of a low band (LB) when the fourth ground part **G4** is electrically connected to the ground **G** of the substrate **252** through the second variable circuit **T2**. In an embodiment, the first antenna **A1** may be operated in the second frequency band (graph **1302**) lower than the first frequency band of the low band when the fourth ground part **G4** is electrically disconnected from the ground **G** of the substrate **252** through the second variable circuit **T2**, and the third ground part **G3** is connected to the ground **G** of the substrate **252** through the first variable circuit **T1**. In an embodiment, the first antenna **A1** may be operated in the third frequency band (graph **1303**) lower than the second frequency band of the low band when the third ground part **G3** and the fourth ground part **G4** are electrically disconnected from the substrate **252** through the first variable circuit **T1** and the second variable circuit **T2**. This may mean that the operating frequency band of the first antenna **A1** may be freely shifted through appropriate control of the first variable circuit **T1** and/or the second variable circuit **T2**.

(129) FIG. **14** is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure.

(130) In describing the electronic device **200** of FIG. **14**, the same reference numerals are assigned to components substantially the same as those of the electronic device **200** of FIG. **7**, and detailed descriptions thereof may be omitted.

(131) Referring to FIG. **14**, the first conductive portion **310** may include, in the third side surface **2113** direction (e.g., fourth direction {circle around (4)}), a third ground part **G3** disposed at the fifth point **P5** between the second ground part **G2** and the third side surface **2113** and electrically connected to the ground **G** of the substrate **252**, and a fourth ground part **G4** disposed at the sixth point **P6** between the first power feed unit **PF1** and the first ground part **G1** and electrically connected to the ground **G** of the substrate **252**. In an embodiment, the electronic device **200** may include a first variable circuit **T1** (tunable IC or switching device) disposed in an electrical path connecting the ground **G** of the substrate **252** and the third ground part **G3**, and/or a second variable circuit **T2** (tunable IC or switching device) disposed in an electrical path connecting the ground **G** of the substrate **252** and the fourth ground part **G4**. In an embodiment, the first variable circuit **T1** and/or the second variable circuit **T2**, for example, may include a switching device and a plurality of passive elements (e.g., capacitor or inductor) switched to either one through the switching device. In some embodiments, the first variable circuit **T1** and/or the second variable circuit **T2** may include only a switching device selectively connecting the third ground part **G3** and/or the fourth ground part **G4** to the ground **G** of the substrate **252**. In an embodiment, the first variable circuit **T1** or the second variable circuit **T2** may be disposed under the control of the

processor **120** and may be electrically connected to one of each ground parts **G3** and **G4** in various ways according to state information of the electronic device **200**. For example, the processor **120** may electrically connect (short) or disconnect (open) the third ground part **G3** to the ground **G** of the substrate **252** through the first variable circuit **T1**. In an embodiment, the processor **120** may electrically connect (short) or disconnect (open) the fourth ground part **G4** to the ground **G** of the substrate **252** through the second variable circuit **T2**. In an embodiment, the processor **120** may also connect the passive element having a designated value to the third ground part **G3** and/or the fourth ground part **G4** through the control of the first variable circuit **T1** and/or the second variable circuit **T2**. In an embodiment, the operating frequency band of the first antenna **A1** may be shifted through the first variable circuit **T1** and/or the second variable circuit **T2** under the control of the processor **120**.

(132) FIG. **15** is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure.

(133) In describing the electronic device **200** of FIG. **15**, the same reference numerals are assigned to components substantially the same as those of the electronic device **200** of FIG. **7**, and detailed descriptions thereof may be omitted.

(134) Referring to FIG. **15**, the first conductive portion **310** may include, in the second side surface **2112** direction (e.g., third direction {circle around (3)}), a third ground part **G3** disposed at the fifth point **P5** between the first ground part **G1** and the first segmentation portion **320** and electrically connected to the ground **G** of the substrate **252**, and a fourth ground part **G4** disposed at the sixth point **P6** between the first segmentation portion **320** and the second power feed unit **PF2** and electrically connected to the ground **G** of the substrate **252**. In an embodiment, the electronic device **200** may include a first variable circuit **T1** (tunable integrated circuit (IC) or switching device) disposed in an electrical path connecting the ground **G** of the substrate **252** and the third ground part **G3**, and/or a second variable circuit **T2** (tunable IC or switching device) disposed in an electrical path connecting the ground **G** of the substrate **252** and the fourth ground part **G4**. In an embodiment, the first variable circuit **T1** and/or the second variable circuit **T2**, for example, may include a switching device and a plurality of passive elements (e.g., capacitor or inductor) switched to either one through the switching device. In some embodiments, the first variable circuit **T1** and/or the second variable circuit **T2** may include only a switching device selectively connecting the third ground part **G3** and/or the fourth ground part **G4** to the ground **G** of the substrate **252**. In an embodiment, the first variable circuit **T1** or the second variable circuit **T2** may be disposed under the control of the processor **120** and may be electrically connected to one of each ground parts **G3** and **G4** in various ways according to state information of the electronic device **200**. For example, the processor **120** may electrically connect (short) or disconnect (open) the third ground part **G3** to the ground **G** of the substrate **252** through the first variable circuit **T1**. In an embodiment, the processor **120** may electrically connect (short) or disconnect (open) the fourth ground part **G4** to the ground **G** of the substrate **252** through the second variable circuit **T2**. In an embodiment, the processor **120** may also connect the passive element having a designated value to the third ground part **G3** and/or the fourth ground part **G4** through the control of the first variable circuit **T1** and/or the second variable circuit **T2**. In an embodiment, the operating frequency band of the second antenna **A2** may be shifted through the first variable circuit **T1** and/or the second variable circuit **T2** under the control of the processor **120**.

(135) FIG. **16** is a graph illustrating a change in frequency band of the second antenna of FIG. **15** by configuring variable circuits according to an embodiment of the disclosure.

(136) Referring to FIG. **16**, the second antenna **A2** may be operated in the first frequency band (graph **1601**) of a mid band (MB)/high band (HB) (hereinafter mid/high band) when the third ground part **G3** and the fourth ground part **G4** are connected (short) to the ground **G** of the substrate **252** through the first variable circuit **T1** and the second variable circuit **T2**. In an embodiment, the second antenna **A2** may be operated in the second frequency band (graph **1602**) of mid/high band

lower than the first frequency band when the third ground part G3 is connected to the ground G of the substrate 252 through the first variable circuit T1, and the fourth ground part G4 is connected to an inductor having a designated value (e.g., 10 nanohenry (nH)) through the second variable circuit T2. In an embodiment, the second antenna A2 may be operated in a third frequency band (graph 1603) of mid/high band lower than the second frequency band when the third ground part G3 is connected to the ground G of the substrate 252 through the first variable circuit T1, and the fourth ground part G4 is disconnected (open) from the ground G of the substrate 252 through the second variable circuit T2. In an embodiment, the second antenna A2 may be operated in a fourth frequency band (graph 1604) of mid/high band lower than the third frequency band when the third ground part G3 is disconnected (open) from the ground G of the substrate 252 through the first variable circuit T1, and the fourth ground part G4 is disconnected (open) from the ground G of the substrate 252 through the second variable circuit T2. In an embodiment, the second antenna A2 may be operated in a fifth frequency band (graph 1605) of mid/high band lower than the fourth frequency band when the third ground part G3 is disconnected from the ground G of the substrate 252 through the first variable circuit T1 and is connected to the capacitor having a designated value through the second variable circuit T2. For example, the second antenna A2 may mean that the operating frequency band may be shifted in various ways through proper control of the first variable circuit T1 and/or the second variable circuit T2.

(137) FIG. 17 is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure.

(138) In describing the electronic device 200 of FIG. 17, the same reference numerals are assigned to components substantially the same as those of the electronic device 200 of FIG. 7, and detailed descriptions thereof may be omitted.

(139) Referring to FIG. 17, the electronic device 200 may include a second conductive portion 311 segmented through the second segmentation portion 321 on the second side surface 2112 of the first lateral member 211 and/or a third conductive portion 312 segmented through the third segmentation portion 322 on the third side surface 2113. In an embodiment, the second conductive portion 311 may include a third power feed unit PF3 disposed at a fifth point P5 spaced apart from the second segmentation portion 321 and electrically connected to the wireless communication circuit 192 of the substrate 252 through a third electrical path 2523. In an embodiment, the electronic device 200 may include a matching circuit M3 disposed in the third electrical path 2523. In an embodiment, the second conductive portion 311 may include a third ground part G3 disposed at a sixth point P6 spaced apart from the fifth point P5 in a direction away from the second segmentation portion 321 (e.g., the +y-axis direction) and electrically connected to the ground G of the substrate 252. In an embodiment, at least a portion of the second conductive portion 311 may be operated as a third antenna A3 in a designated frequency band (e.g., mid band and/or high band) through a third power feed unit PF3 and a third ground part G3. In an embodiment, the third antenna A3 may operate as a slot antenna or a slit antenna. In an embodiment, the frequency band of the third antenna A3 may be determined according to the location of the third ground part G3. This configuration of the third antenna A3 may help improve the phenomenon that circuit loss increases because of the excessive use of a diplexer in the first antenna A1.

(140) According to various embodiments, since the first antenna A1 and the third antenna A3 are operated by sharing the second segmentation portion 321, isolation may be deteriorated. To improve this phenomenon, the electronic device 200 may include a low-pass filter (LPF) disposed in the first electrical path 2521 connecting the first power feed unit PF1 and the wireless communication circuit 192. In an embodiment, the low-pass filter (LPF) may help improve the isolation of the first antenna A1 and the third antenna A3 and the efficiency of the mid/high band of the third antenna A3 by forcibly reducing the efficiency of the mid band and/or high band of the first antenna A1.

(141) FIG. 18 is a graph comparing isolation degrees of the first antenna and the third antenna of

FIG. 17 with or without a filter according to an embodiment of the disclosure.

(142) Referring to FIG. 18, it may be identified that when the low-pass filter (LPF) is not used, the isolation between the first antenna A1 and the third antenna A3 appears to be about -10 db or more in the mid band and high band (area 1801). In an embodiment, it may be identified that when the low-pass filter (LPF) is used for the first antenna A1, the isolation between the first antenna A1 and the third antenna A3 appears to be about -15 db or less in the mid band and high band (area 1802). This may mean that even if the second segmentation portion 321 is commonly used for the first antenna A1 and the third antenna A3, when the low-pass filter (LPF) is applied to the feed line of the first antenna A1, the isolation between the two antennas A1 and A3 is increased.

(143) FIG. 19 is a diagram of an electronic device including an antenna disposition structure according to an embodiment of the disclosure.

(144) In describing the electronic device 200 of FIG. 19, the same reference numerals are assigned to components substantially the same as those of the electronic device 200 of FIG. 7, and detailed descriptions thereof may be omitted.

(145) Referring to FIG. 19, the first conductive portion 310 may include a third power feed unit PF3 disposed at a fifth point P5 between the first segmentation portion 320 and the first ground part G1 in the second side surface 2112 direction (e.g., third direction {circle around (3)}) and electrically connected to the wireless communication circuit 192 of the substrate 252 through the third electrical path 2523. In an embodiment, the first conductive portion 310 may include a third ground part G3 disposed at a sixth point P6 between the first segmentation portion 320 and the third power feed unit PF3 in the second side surface 2112 direction (e.g., third direction {circle around (3)}) and electrically connected to the ground G of the substrate 252. In an embodiment, the electronic device 200 may include a matching circuit M3 disposed in the third electrical path 2523. In an embodiment, at least a portion of the first conductive portion 310 may be operated as a third antenna A3 in the designated frequency band (e.g., mid band and/or high band) through the third power feed unit PF3, the first ground part G1 and the third ground part G3. In this case, the second antenna A2 may have an electrical length passing through the second ground part G2 and the third ground part G3. In some embodiments, as shown in FIG. 17, the electronic device 200 may include further a fourth antenna (e.g., the third antenna A3 of FIG. 17) having a power feed unit (e.g., the third power feed unit PF3 of FIG. 17) disposed on at least a portion of the second conductive portion 311.

(146) FIGS. 20A and 20B are diagrams of an electronic device including an antenna disposition structure according to various embodiments of the disclosure.

(147) In the description of the electronic device 200 of FIGS. 20A and 20B, the same reference numerals are assigned to components substantially the same as those of the electronic device 200 of FIG. 7, and detailed descriptions thereof may be omitted.

(148) Referring to FIG. 20A, the first conductive portion 310 may be configured to use the entire third side surface 2113 of the first lateral member 211 without the third segmentation portion (e.g., the third segmentation portion 322 of FIG. 7).

(149) Referring to FIG. 20B, in the configuration of FIG. 20A, the first conductive portion 310 may include a third power feed unit PF3 electrically connected to the wireless communication circuit 192 of the substrate 252 at the fifth point P5 between the second ground part G2 and the third side surface 2113 through the third electrical path 2523 in the direction of the third side surface 2113 (e.g., fourth direction CI). In an embodiment, the third power feed unit PF3 may be disposed on at least a portion of the first conductive portion 310 on the first side surface 2111 of the first lateral member 211 and may be used as the third antenna A3.

(150) FIGS. 21 and 22 are diagrams of an electronic device including an antenna disposition structure according to various embodiments of the disclosure.

(151) In describing the electronic device 200 of FIGS. 21 and 22, the same reference numerals are assigned to components substantially the same as those of the electronic device 200 of FIG. 7, and

detailed descriptions thereof may be omitted.

(152) Referring to FIG. 21, the electronic device 200 may include further a fourth segmentation portion 323 formed between the second ground part G2 and the third side surface 2113 of the first conductive portion 310 in the third side surface 2113 direction (e.g., fourth direction {circle around (4)}). In this case, the electronic device 200 may include a fourth conductive portion 313 segmented through the first segmentation portion 320 and the fourth segmentation portion 323 of the first conductive portion 310. In an embodiment, the first conductive portion 310 may include a third ground part G3 electrically connected to the ground G of the substrate 252 at the fifth point P5 between the fourth segmentation portion 323 and the third side surface 2113 in the third side surface 2113 direction (e.g., fourth direction {circle around (4)}). In an embodiment, the first antenna A1 may be operated in a frequency band (e.g., low band) corresponding to the first electrical length EP1 using the first conductive portion 310 from the first ground part G1 to the third ground part G3 through the first power unit PF1. In an embodiment, the second antenna A2 may be operated in a frequency band (e.g., mid band and/or high band) corresponding to the second electrical length EP2 using a portion of the first conductive portion 310 and a portion of the fourth conductive portion 313 from the first ground part G1 to the second ground part G2 through the first segmentation portion 320.

(153) Referring to FIG. 22, in the configuration of FIG. 21, the electronic device 200 may include a third power feed unit PF3 electrically connected to the wireless communication circuit 192 of the substrate 252 through the third electrical path 2523 at the sixth point P6 between the second ground part G2 and the fourth segmentation portion 323. In an embodiment, the electronic device 200 may include a matching circuit M3 disposed in the third electrical path 2523. In an embodiment, the electronic device 200 may include a third antenna A3 operating in a frequency band (e.g., mid band and/or high band) corresponding to a third electrical length EP3 from the second ground part G2 to the third ground part G3 through the fourth segmentation portion 323.

(154) FIGS. 23A and 23B are views of an electronic device including a loop-shaped conductive portion according to various embodiments of the disclosure.

(155) Electronic device 600 of FIGS. 23A and 23B may be at least partially similar to the electronic device 101 of FIG. 1 or may further include other embodiments of the electronic device.

(156) Referring to FIGS. 23A and 23B, an electronic device 600 may include a bar-type electronic device. In an embodiment, the electronic device 600 may include a housing 610 (e.g., a housing structure including a front surface cover 611 facing in a first direction (e.g., a z-axis direction), a rear surface cover 612 facing in a direction opposite to the front surface cover 611 (e.g., a -z-axis direction), and a lateral member 613 disposed to surround a space between the front surface cover 611 and the rear surface cover 612. In an embodiment, the lateral member 613 may include a conductive member 613a and a non-conductive member 613b combined with the conductive member 613a. In an embodiment, the lateral member 613 may include a first side surface 6131 disposed on the lower side (e.g., -y axis direction) of the electronic device 600 and having a first length, a second side surface 6132 extending in a direction perpendicular to the first side surface 6131 and having a second length longer than the first length, a third side surface 6133 extending in a direction parallel to the first side surface 6131 from the second side surface 6132 and having a first length, and a fourth side surface 6134 extending from the third side surface 6133 to the first side surface 6131 in a direction parallel to the second side surface 6132 and having a second length. In an embodiment, the electronic device 600 may include a display 601 disposed in an inner space and visible from the outside through at least a portion of the front surface cover 611. In an embodiment, the electronic device 600 may include at least one camera device 602 and at least one sensor module 603 disposed in an internal space and disposed to detect an external environment through at least a portion of the front surface cover 611 and/or at least a portion of the display 601. In an embodiment, the electronic device 600 may include at least one speaker device 604 and 605, a microphone device 606 and/or an interface connector port 607 disposed to operate through at

least a portion of the lateral member **613**. In an embodiment, the at least one speaker device **604** and **605** may include a receiver disposed between the lateral member **613** and the front surface cover **611**, and an external speaker **605** disposed to operate through the lateral member **613**. In an embodiment, the electronic device **600** may include at least one other camera device **608** disposed to detect an external environment through at least a portion of the rear surface cover **612**.

(157) According to various embodiments, in the first side surface **6131** of the electronic device **600**, an opening **6101** and a first segmentation portion **631** may include a loop-shaped conductive portion **630** (e.g., the first conductive portion **310** of FIG. 7) filled with a non-conductive member **613b**. In an embodiment, the conductive portion **630** may be segmented from other parts of the conductive member **613a** through a second segmentation portion **632** and a third segmentation portion **633** respectively disposed on the second side surface **6132** and the fourth side surface **5134**. In an embodiment, the second segmentation portion **632** and the third segmentation portion **633** may also be filled with a non-conductive member **613b**. In an embodiment, the conductive portion **630** may be operated as at least one antenna A operating in at least one frequency band. In some embodiments, the loop-shaped conductive portion **630** may be disposed on at least one of the second side surface **6132**, the third side surface **6133**, and the fourth side surface **6134**.

(158) FIGS. **24A** and **24B** are views of an electronic device including a loop-shaped conductive portion according to various embodiments of the disclosure.

(159) Electronic device **700** of FIGS. **24A** and **24B** may be at least partially similar to the electronic device **101** of FIG. **1** or may further include other embodiments of the electronic device.

(160) Referring to FIGS. **24A** and **24B**, an electronic device **700** may include a rollable-type (bar-type) electronic device. In an embodiment, the electronic device **700** may include a first housing **710**, a second housing **720** (e.g., a slide structure) coupled to be slid out of the first housing **710** in a first direction (e.g., an x-axis direction) and to be slid in in a direction opposite to the first direction (e.g., an -x-axis direction), and a flexible display **230** disposed to be supported by the first housing **710** and the second housing **720**, and of which display area is variable by being accommodated in the inner space of the first housing **710** to be at least partially invisible from the outside in a slide-in state. In an embodiment, the first housing **710** may include a first lateral member **711**. In an embodiment, the first lateral member **711** may include a first side surface **7111** disposed on the lower side of the electronic device **700** (e.g., the -y-axis direction) and having a first length, a second side surface **7112** extending in a direction perpendicular to the first side surface **7111** and having a second length longer than the first length, and a third side surface **7113** extending in a direction parallel to the first side surface **7111** from the second side surface **7112** and having a first length. In an embodiment, the second housing **720** may include a second lateral member **721**. In an embodiment, the second lateral member **721** may include a fourth side surface **7211** disposed on the lower side of the electronic device **700** (e.g., the -y-axis direction) and corresponding to the first side surface **7111**, a fifth side surface **7212** extending in a direction perpendicular to the fourth side surface **7211** and having a length substantially similar to that of the second side surface **7112**, and a sixth side surface **7213** extending from the fifth side surface **7212** and corresponding to the third side surface **7113**. In an embodiment, the first lateral member **711** may be formed of a conductive member **711a** and a non-conductive member **711b** combined with the conductive member **711a**.

(161) According to various embodiments, in at least a portion of the first side surface **7111** of the electronic device **700**, an opening **7101** and a first segmentation portion **731** may include a loop-shaped conductive portion **730** (e.g., the first conductive portion **310** of FIG. 7) filled with a non-conductive member **711b**. In an embodiment, the conductive portion **730** may be segmented from other parts of a conductive member **711a** through a second segmentation portion **732** and a third segmentation portion **733** disposed on the first side surface **7111** and the second side surface **7112** respectively. In an embodiment, the second segmentation portion **732** and the third segmentation portion **733** may also be filled with a non-conductive member **711b**. In an embodiment, the

conductive portion **730** may be operated as at least one antenna A operating in at least one frequency band. In some embodiments, the loop-shaped conductive portion **730** may also be disposed at at least one of a first side surface **7111**, a third side surface **7113**, a fourth side surface **7211**, a fifth side surface **7212**, or a sixth side surface **7213**.

(162) Although not shown, the loop-shaped conductive portion used as at least one antenna may be applied to at least a portion of at least one side of the first housing and the second housing of the foldable electronic device in which the first housing and the second housing are foldably coupled to each other through a hinge device.

(163) According to various embodiments, an electronic device (e.g., the electronic device **200** of FIG. 7) may include: at least one housing (e.g., the first housing **210** of FIG. 3A) including a lateral member (e.g., the first lateral member **211** of FIG. 7) that includes a first side surface (e.g., the first side surface **2111** of FIG. 7), a second side surface (e.g., the second side surface **2112** of FIG. 7) extended vertically from one end of the first side surface, and a third side surface (e.g., the third side surface **2113**) extended vertically from the end of the second side surface; a first conductive portion (e.g., the first conductive portion **310** of FIG. 7) disposed in a loop-shape when the first side surface is viewed from the outside, and segmented through the first segmentation portion (e.g., the first segmentation portion **320** of FIG. 7); a substrate (e.g., the substrate **252** of FIG. 7) disposed in the inner space of the housing and including a ground (e.g., the ground G of FIG. 7); and a wireless communication circuit (e.g., the wireless communication circuit **192** of FIG. 7) disposed on the substrate and configured to transmit and receive the wireless signal through the first conductive portion in at least one frequency band. The first conductive portion may include a first power feed unit (e.g., the first power feed unit PF1 of FIG. 7) electrically connected to the wireless communication circuit through a first point (e.g., the first point P1 of FIG. 7) between the first segmentation portion and the second side surface; a second power feed unit (e.g., the second power feed unit PF2 of FIG. 7) electrically connected to the wireless communication circuit through a second point (e.g., the second point P2 of FIG. 7) between the first segmentation portion and the third side surface; a first ground part (e.g., the first ground part G1 of FIG. 7) electrically connected to the ground through a third point (e.g., the third point P3 of FIG. 7) in a direction toward the second side surface from the first segmentation portion; a second ground part (e.g., the second ground part G2 of FIG. 7) electrically connected to the ground through a fourth point (e.g., the fourth point P4 of FIG. 7) between the second point and the third side surface.

(164) According to various embodiments, the wireless communication circuit may be configured to transmit or receive a wireless signal in a first frequency band through the first power feed unit, and it may be configured to transmit and receive a wireless signal in at least one second frequency band higher than the first frequency band through the second power feed unit.

(165) According to various embodiments, the first frequency band may include a low band, and the second frequency band may include a mid band and/or a high band.

(166) According to various embodiments, the first and second power feed units and the first and second ground parts may be disposed on the same line in the first conductive portion.

(167) According to various embodiments, the first lateral member may include a conductive member and a non-conductive member coupled to the conductive member, and the first segmentation portion may be filled with the non-conductive member.

(168) According to various embodiments, the first conductive portion may be segmented from a surrounding conductive member through a second segmentation portion formed on the second side surface and a third segmentation portion formed on the third side surface.

(169) According to various embodiments, a second conductive portion segmented through the second segmentation portion may be included in the second side surface, and a third power feed unit electrically connected to the wireless communication circuit may be included in the fifth point spaced apart from the second segmentation portion.

(170) According to various embodiments, a low-pass filter (LPF) disposed in an electrical path

electrically connecting the first power feed unit and the wireless communication circuit may be included.

(171) According to various embodiments, the first conductive portion may be operated as an antenna through the first portion connected to the first power feed unit and disposed on the first side surface, and a portion of the second side surface extended from the first portion.

(172) According to various embodiments, the first conductive portion may be connected to the second power feed unit and operate as a second antenna through a second part disposed on the first side surface.

(173) According to various embodiments of the disclosure, at least one first additional ground part disposed to be electrically connected to the ground of the substrate at at least one point between the fourth point and the third side surface, and at least one second additional ground part disposed to be electrically connected to the ground of the substrate at at least one point between the third point and the first segmentation portion in a direction toward the second side surface from the first segmentation portion, may be included.

(174) According to various embodiments, a first variable circuit disposed in an electrical path connecting the at least one first additional ground part and a second variable circuit disposed in an electrical path connecting the at least one second additional ground part may be included.

(175) According to various embodiments, the first variable circuit and/or the second variable circuit may include a switching circuit and at least one passive element that is switched through control of the switching circuit, and the switching circuit may perform the switching operation through the control of at least one processor.

(176) According to various embodiments, at least a portion of the first conductive portion may be operated as a first antenna to be configured to transmit or receive a wireless signal in a first frequency band through the first power feed unit, and the first frequency band may be determined through the first variable circuit.

(177) According to various embodiments, at least a portion of the first conductive portion may be operated as a second antenna to be configured to transmit and receive a wireless signal in at least one second frequency band higher than the first frequency band through the second power feed unit, and the second frequency band may be determined through the second variable circuit.

(178) According to various embodiments, the first conductive portion may include a third power feed unit electrically connected to the wireless communication circuit at a fifth point between the first segmentation portion and the first ground in a direction toward the second side surface from the first segmentation portion, and a third ground part electrically connected to the ground of the substrate at a sixth point between the first segmentation portion and a third power feed unit in a direction toward the second side surface from the first segmentation portion.

(179) According to various embodiments, a second conductive portion disposed through a second segmentation portion formed between the first segmentation portion and the third side surface may be included, and the first conductive portion may include a third ground part electrically connected to the ground of the substrate at the fifth point between the second segmentation portion and the third side surface.

(180) According to various embodiments, the second conductive portion may include a third power feed unit electrically connected to the wireless communication circuit at a sixth point between the second ground part and the second segmentation portion.

(181) According to various embodiments, the at least one housing may include a front surface cover, a rear surface cover facing the opposite direction to the front surface cover, the lateral member surrounding a space between the front surface cover and the rear surface cover, and a display disposed in the space to be visible from the outside through a front surface cover, and at least a portion of the first side surface may be disposed substantially vertically from the display surface.

(182) According to various embodiments, at least one housing may include a first housing and a

second housing slidably coupled from the first housing, and the lateral member may be disposed on the first housing.

(183) According to various embodiments, the first conductive portion may maintain a state of being electrically disconnected from a second conductive portion and a third conductive portion through a second segmentation portion and a third segmentation portion, respectively, and the second conductive portion is disposed on a portion of the second side surface and the third segmentation portion is disposed on a portion of the third side surface.

(184) According to various embodiments, a first antenna in which power is fed through the first power feeder of the first conductive portion, the first antenna having a first electrical length from the first ground part to the second ground part not through the first segmentation portion and a second antenna in which power is fed through the second power feeder of the first conductive portion, the second antenna having a second electrical length from the second ground part to the first ground part through the first segmentation portion, the first electrical length is longer than the second electrical length.

(185) According to various embodiments, the first antenna operating through the first power feeder operates in a first frequency band and the second antenna operating through the second power feeder operates in a second frequency band higher than the first frequency band.

(186) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the of the disclosure as defined by the appended claims and their equivalents.

## Claims

1. An electronic device comprising: at least one housing comprising a lateral member, the lateral member comprising: a first side surface, a second side surface extending vertically from a first end of the first side surface, and a third side surface extending vertically from a second end of the first side surface; a first conductive portion disposed in a loop-shape and segmented through a first segmentation portion when the first side surface is viewed from outside; a substrate disposed in an inner space of the at least one housing and including a ground; and a wireless communication circuit disposed on the substrate and configured to transmit and receive, through the first conductive portion, a wireless signal in at least one frequency band, wherein the first conductive portion comprises: a first power feeder electrically connected to the wireless communication circuit through a first point disposed between the first segmentation portion and the second side surface, a second power feeder electrically connected to the wireless communication circuit through a second point disposed between the first segmentation portion and the third side surface, a first ground part electrically connected to the ground through a third point disposed between the first segmentation portion and the first point in a direction toward the second side surface from the first segmentation portion, and a second ground part electrically connected to the ground through a fourth point disposed between the second point and the third side surface.
2. The electronic device of claim 1, wherein the wireless communication circuit is further configured to: transmit or receive a first wireless signal in a first frequency band through the first power feeder; and transmit or receive a second wireless signal in at least one second frequency band higher than the first frequency band through the second power feeder.
3. The electronic device of claim 2, wherein the first frequency band comprises a low band, and wherein the second frequency band comprises at least one of a mid band or a high band.
4. The electronic device of claim 1, wherein the first and second power feeders and the first and second ground parts are disposed on a same line in the first conductive portion.
5. The electronic device of claim 1, wherein the lateral member further comprises a conductive member and a non-conductive member combined with the conductive member, and wherein the

first segmentation portion is filled with the non-conductive member.

6. The electronic device of claim 1, wherein the first conductive portion is segmented from a surrounding conductive member through a second segmentation portion formed on the second side surface and a third segmentation portion formed on the third side surface.

7. The electronic device of claim 6, further comprising: a second conductive portion segmented through the second segmentation portion in the second side surface; and a third power feeder electrically connected to the wireless communication circuit at a fifth point spaced apart from the second segmentation portion.

8. The electronic device of claim 6, further comprising: a low-pass filter (LPF) disposed in an electrical path electrically connecting the first power feeder to the wireless communication circuit.

9. The electronic device of claim 6, wherein the first conductive portion operates as a first antenna through a first portion connected to the first power feeder and disposed on the first side surface and a portion of the second side surface extended from the first portion.

10. The electronic device of claim 6, wherein the first conductive portion operates as a second antenna through a second portion connected to the second power feeder and disposed on the first side surface.

11. The electronic device of claim 1, further comprising: at least one first additional ground part electrically connected to the ground of the substrate through at least one point between the fourth point and the third side surface; and at least one second additional ground part electrically connected to the ground of the substrate through at least one point between the third point and the first segmentation portion in a direction toward the second side surface from the first segmentation portion.

12. The electronic device of claim 11, further comprising: a first variable circuit disposed in an electrical path connecting the at least one first additional ground part; and a second variable circuit disposed in an electrical path connecting the at least one second additional ground part.

13. The electronic device of claim 12, further comprising: at least one processor, wherein at least one of the first variable circuit or the second variable circuit comprises: a switching circuit; and at least one passive element that is switched through control of the switching circuit, and wherein the switching circuit is configured to perform a switching operation through control of the at least one processor.

14. The electronic device of claim 12, wherein at least a portion of the first conductive portion operates as a first antenna configured to transmit or receive a first wireless signal in a first frequency band through the first power feeder, and wherein the first frequency band is determined through the first variable circuit.

15. The electronic device of claim 14, wherein at least a portion of the first conductive portion operates as a second antenna configured to transmit or receive a second wireless signal in at least one second frequency band higher than the first frequency band through the second power feeder, and wherein the second frequency band is determined through the second variable circuit.

16. The electronic device of claim 1, wherein the first conductive portion comprises: a third power feeder electrically connected to the wireless communication circuit at a fifth point disposed between the first segmentation portion and the first ground part in a direction toward the second side surface from the first segmentation portion; and a third ground part electrically connected to the ground of the substrate at a sixth point disposed between the first segmentation portion and the third power feeder in a direction toward the second side surface from the first segmentation portion.

17. The electronic device of claim 1, further comprising: a second conductive portion disposed through a second segmentation portion formed between the first segmentation portion and the third side surface, wherein the first conductive portion includes a third ground part electrically connected to the ground of the substrate at a fifth point disposed between the second segmentation portion and the third side surface.

18. The electronic device of claim 17, wherein the second conductive portion comprises a third

power feeder electrically connected to the wireless communication circuit at a sixth point disposed between the second ground part and the second segmentation portion.

19. The electronic device of claim 1, wherein the at least one housing further comprises: a front surface cover facing a first direction; a rear surface cover facing a second direction opposite to the first direction, the lateral member surrounding a space between the front surface cover and the rear surface cover; and a display visible from the outside through the front surface cover, and wherein at least a portion of the first side surface is disposed substantially vertically from a surface of the display.

20. The electronic device of claim 1, wherein the at least one housing further comprises: a first housing; and a second housing slidably coupled to the first housing, and wherein the lateral member is disposed in the first housing.

---