

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408573
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Sears; Richard B.

Vertical tiller

Abstract

A vertical tiller comprises a rider disc or foot at the bottom of a helix or screw/auger, with the assemble further comprising angled winged appendages having angled sweep sections. The assembly further comprises a turned leading appendage. The turned leading appendage keeps the assembly relatively vertical to prevent the other appendages from fouling, cutting or entangling with cloth, wire or other elements often found at the bottom of planting pots, wire baskets and planting beds. The vertical tiller performs maceration and aeration within soil and provides a level of safety by the angled appendages that bounce off of a user's foot. The invention is well suited for remixing and amending soil and is intended for light soils having minimal rocks and large roots. The disclosed wing design assists having greater control over the tiller which is useful in selective tilling to promote soil biota.

Inventors:	Sears; Richard B. (San Rafael, CA)
Applicant:	Sears; Richard B. (San Rafael, CA)
Family ID:	96950291
Appl. No.:	17/882220
Filed:	August 05, 2022

Related U.S. Application Data

us-provisional-application US 63229733 20210805

Publication Classification

Int. Cl.: A01B33/06 (20060101); A01C5/02 (20060101); E21B11/00 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: A01B (33/06); A01B (33/022); A01B (1/16); A01B (35/28); A01B (45/026); A01B (1/14); A01B (1/065); A01B (1/00); A01C (5/02); E21B (11/005); E21B (10/44)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1363444	12/1919	Van Den Heuvel	404/124	A01B 35/28
3094178	12/1962	Newbold	N/A	N/A
4074780	12/1977	Gilbert	175/323	E21B 10/44
4986368	12/1990	Underwood	172/430	E21B 10/44
5133269	12/1991	Charneski	175/21	A01C 5/02
5716132	12/1997	Chou	N/A	N/A
5810093	12/1997	Howard	N/A	N/A
6119787	12/1999	Garcia	172/25	E21B 7/005
6227317	12/2000	Severns	N/A	N/A
6955227	12/2004	Motosko	172/111	B01F 27/1143
8479842	12/2012	Tucceri	N/A	N/A
2002/0175005	12/2001	Chou	175/385	A01B 1/00
2007/0086271	12/2006	Hamilton	N/A	N/A
2008/0135267	12/2007	Karczewski	172/378	A01B 1/14
2009/0110502	12/2008	Brooks	N/A	N/A

Primary Examiner: Sebesta; Christopher J

Assistant Examiner: Scoville; Blake E

Attorney, Agent or Firm: www.NielsenPatents.com

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This utility patent application claims the benefit and priority date of U.S. application 63/229,733 filed on Aug. 5, 2021, the contents of which are incorporated herein as if restated herein.

COPYRIGHT AND TRADEMARK NOTICE

(1) This application includes material which is subject or may be subject to copyright and/or trademark protection. The copyright and trademark owner(s) has no objection to the facsimile reproduction by any of the patent disclosure, as it appears in the Patent and Trademark Office files or records, but otherwise reserves all copyright and trademark rights whatsoever.

BACKGROUND OF THE INVENTION

(1) Field of the Invention

(2) The invention generally relates to soil mixing systems. More particularly, the invention relates to means and methods of mixing soil in cloth pots and wire mesh planting beds.

(2) Description of the Related Art

(3) The known related art fails to anticipate or disclose the principles of the present invention.

(4) In the related art, general mixing blade systems are known, but don't perform well in cloth pots or wire mesh planting beds. The known prior art fails to protect a user's foot and fails to protect cloth, wire mesh or other materials sometimes used to surround a planting pot or planting bed.

(5) Thus, there is a need in the art for the presently disclosed embodiments.

BRIEF SUMMARY OF THE INVENTION

(6) The present invention overcomes shortfalls in the related art by presenting an unobvious and unique combination and configuration of methods and components to construct and use a vertical tiller having a helical blade system and rounded disc button bottom and wherein the wings, appendages or blades are canted to avoid damage to a soil container or operator of the system.

Disclosed embodiments may have one or more helixes with each helix having one or more wings. The wings may have edges of various degrees of smoothness. The wings may be attached, stamped, welded or forged on a helix at any angle. The disclosed wings overcome various shortfalls in the prior art in that the wings provide controlled movement of the tiller when the tiller is tilted. The sweeping distal edges of the wings provide a good purchase upon the ground to move or walk the tiller in a desired location. The maneuverability of the disclosed embodiments allows a user selectively till discrete portions of a planting bed and to leave portions undisturbed when in turn promotes and preserves soil biota. The indiscriminate tilling of the related art encourages tilling of an entire plant bed, which is detrimental to soil biota.

(7) The disclosed embodiments may also include a turned leading wing that presents a horizontal leading surface to the ground so as to prevent injury to a user and to prevent damage to an underlayment such as cloth, wire mesh and other products found at the bottom of or surrounding a planting pot or planting bed. Such planting materials are sometimes collectively referred to as "fabric" and may further include wire mesh, weed barrier or any material used for farming and gardening.

(8) The disclosed embodiments are useful in mixing soil, amending soil, root cutting, adding fertilizer to soil and other uses. The disclosed embodiments are useful in pots with fabric on the bottom, gopher wire and other applications wherein fragile or delicate components are present.

(9) The disclosed embodiments provide superior maceration and aeration to soil by use of the disclosed sweeping angled winged appendages.

(10) These and other objects and advantages will be made apparent when considering the following detailed specification when taken in conjunction with the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 depicts a perspective view of a disclosed embodiment

(2) FIG. 2 depicts a perspective view of a disclosed tiller assembly

(3) FIG. 3 depicts a perspective view of a disclosed tiller assembly

(4) FIG. 4 depicts a perspective view of a disclosed tiller assembly

(5) FIG. 5 depicts a bottom perspective view of a disclosed tiller assembly

(6) FIG. 6 depicts a bottom and side perspective view of a disclosed tiller assembly

(7) FIG. 7 depicts a side perspective view a disclosed tiller assembly

(8) FIG. 8 depicts an enlarged and perspective view of a turned leading wing

(9) FIG. 9 depicts an enlarged and perspective bottom view of a disclosed tiller assembly

(10) FIG. 10 depicts a top view of a disclosed tiller assembly

REFERENCE NUMERALS IN THE DRAWINGS

(11) **100** a disclosed embodiment in general **120** means of attachment to a rotational force **200** tiller

assembly **210** shaft **220** helix **222** outer edge of helix **226** inner edge of helix **230** wing or appendage **232** sweeping distal edge of wing **235** cambered transition between sweeping edge **232** and first vertical return **237** **237** first vertical return from helix to cambered transition **235** **239** second vertical return from normal edge **243** of wing to helix **243** normal edge or transition between sweeping edge **232** of wing to second vertical return **239** **250** turned leading wing **255** distal edge piece of turned leading wing **250** **300** rider disc or button **320** lower circular surface of rider disc **330** outer circular wall of rider disc **300**

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

(12) The following detailed description is directed to certain specific embodiments of the invention. However, the invention can be embodied in a multitude of different ways as defined and covered by the claims and their equivalents. In this description, reference is made to the drawings wherein like parts are designated with like numerals throughout.

(13) Unless otherwise noted in this specification or in the claims, all of the terms used in the specification and the claims will have the meanings normally ascribed to these terms by workers in the art.

(14) Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise,” “comprising” and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in a sense of “including, but not limited to.” Words using the singular or plural number also include the plural or singular number, respectively. Additionally, the words “herein,” “above,” “below,” and words of similar import, when used in this application, shall refer to this application as a whole and not to any particular portions of this application.

(15) The above detailed description of embodiments of the invention is not intended to be exhaustive or to limit the invention to the precise form disclosed above. While specific embodiments of, and examples for, the invention are described above for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize. For example, while steps are presented in a given order, alternative embodiments may perform routines having steps in a different order. The teachings of the invention provided herein can be applied to other systems, not only the systems described herein. The various embodiments described herein can be combined to provide further embodiments. These and other changes can be made to the invention in light of the detailed description.

(16) Any and all the IDS references and U.S. patents and applications are incorporated herein by reference. Aspects of the invention can be modified, if necessary, to employ the systems, functions and concepts of the various patents and applications described above to provide yet further embodiments of the invention.

(17) FIG. 1 depicts a disclosed embodiment **100** in general which may comprise a shaft **210**, one or more tiller assemblies **200**. A top section of the shaft may comprise means of attachment to a rotational power source such as a power head. Means of attachment may include a chuck and/or a threaded rod.

(18) FIG. 2 depicts a helix assembly **200** comprising one or more wings **230** with a lower section of the helix **220** comprising a turned leading wing **250**. The turned leading wing overcomes shortfalls in the related art as the turned leading wing is the lowest of the wings and comprises a distal edge piece, as shown in FIG. 8 as reference number **255**. The distal edge piece **255** may have an upward angle in the range of 10 to 35 degrees from the base section of the turned leading wing. This angle presents the distal edge piece as a relatively flat member when the helix assembly veers from a vertical position. Thus, the distal edge piece keeps the helix assemble from auguring into the area to be tilled when the assemble veers to a side. Also, the distal edge piece overcomes shortfalls in the prior art by presenting a flat surface to the ground and thus not cutting, tearing or otherwise damaging cloth, wire or other material that is often found in planting pots and planting beds. The distal edge piece also protects the foot of a user by being relatively flat when the tool is tilted, thus

not cutting the foot of the user. While the disclosed embodiments are designed to be used in vertical position, it is reasonably forceable for a user to allow the tool to become tilted during use. Inconsistencies in soil, the existence of dirt clots and possible fluctuations in torque from the rotational power source located at the top of the tool further increase the chances of the tool becoming tilted during use.

(19) FIG. 3 features the disclosed rider disc **300** which may be disposed at the inferior or lower end of the shaft **210**. The rider disc may comprise a lower circular surface **320** and an outer circular wall **330**. The rider disc, so configured overcomes shortfalls in the known prior art as the rider disc may ride upon cloth, weed fabric, steel mesh and other materials often found at the bottom of or within a planting. The lower flat circular surface **320** and outer circular wall **330** allow the rider disc to overcome shortfalls in the known prior art by not providing means of become ensnared by or damaging fabric. The flat and circular surfaces of the rider disc provide the best means of supporting the helix assembly over fabric such that the wings are elevated and thus unlikely to damage the fabric. As the rider disc is smooth, flat and round, the rider disc has no sharp edges to damage the fabric.

(20) FIG. 4 shows a lower view of the rider disc as discussed above but also shows the useful features of the wings **230** that allow the wings to mix and or circulate soil and to provide maceration and aeration functions without damaging fabric. A wing **230** may comprise or be defined by a first vertical return or edge **237** that starts at an outer edge **222** of the helix **220**. The first vertical edge may then become or disposed upon a cambered corner or cambered transition **235** or cambered junction. The cambered edge **235** may then transition to or be disposed upon a sweeping outer edge **232**, the other end of the sweeping outer edge may then be disposed upon or become a sharp angle or angle in the range of 80 to 110 degrees and may be defined as a normal transition **243**. The normal transition may then become or be disposed upon a second vertical return **239** which ends or is further defined by an outer edge of the helix.

(21) The architecture of the disclosed wings overcome shortfalls in the art by providing a side or lateral surface, when the tiller is tilted, such that the wings provide propulsion or movement or “walk” to the tiller which allows a user to steer the tiller to perform tilling upon selected areas of a grow area so as to not mix or disturb the entire grow area. By mixing just parts of a grow area, the existing soil biota may be preserved and then cultivated to the rest of the mixed grow area.

(22) The artful combination of components and curvatures of the disclosed wings overcome shortfalls in the known related art as the helix may be rotated such that the cambered edge **235** becomes the first point of contact with fabric that happens to be above the rider disc or turned leading wing **250**. The fabric is not likely to tear due to the cambered shape of the leading edge of the wing. Fabric is further protected and less likely to tear due to the sweeping or curved outer surface of the sweeping distal edge **232** of the wing. The sweeping distal edge gently guides the fabric off of the wing and helix. The first vertical return **237** is shorter than the second vertical return **239** to ensure that any involved fabric is gently moved or urged away from the helix during rotation.

(23) The turned leading wing **250** has similar features of the other wings **230**, with the exception, as discussed above, of having a distal edge piece angled to provide flat support upon the ground when the tool is tilled. The distal edge piece protects a user's feet from injury, and also protects fabric as the bottom side of the distal edge piece is relatively flat with respect to any underlying or contained fabric.

(24) FIG. 5 shows the helix assembly from the bottom and how the turned leading wing **250** is at the bottom of the helix as compared to the plurality of wings **230**.

(25) FIG. 6 shows the distal edge piece **255** disposed at the distal end of the turned leading wing **250**. The shaft is shown in attachment to an inner edge **226** of the helix.

(26) FIG. 7 shows the features of the turned leading wing **250** as discussed above.

(27) FIG. 8 shows how the distal edge piece **255** of the turned leading wing is angled in a relatively

upward direction.

(28) FIG. 9 depicts lower portions of a helix assembly.

(29) FIG. 10 provides a top view of a helix assembly.

(30) In the best mode known to date, the helix and the wings are disposed at an angle in the range of 4 to 20 degrees.

Claims

1. A system (**100**) for mixing soil while protecting underlying weed fabric, the system comprising:
a) a tiller assembly comprising a helix (**220**) the helix comprising a plurality of wings (**230**) with each wing comprising a first vertical return (**237**) attached to an outer edge (**222**) of the helix, the first vertical return also attached to a cambered transition (**235**) with the cambered transition attached to a sweeping distal edge (**232**) with the sweeping distal edge attached to a normal edge (**243**) with the normal edge attached to a second vertical return (**239**) with the second vertical return attached to the outer edge of the helix; b) the helix further comprising a turned leading wing (**250**) the turned leading wing disposed at the lowest end of the helix, the turned leading wing comprising a distal edge piece (**255**) in angled attachment to the turned leading wing; and c) the tiller assembly centrally attached to a shaft (**210**) the shaft having an inferior end centrally attached to a rider disc (**300**) the rider disc comprising a outer circular wall (**330**) and a lower circular surface (**320**).
 2. The system of claim 1 wherein the shaft further includes an upper end with the upper end having means of attachment to a torque.
 3. The system of claim 1 wherein the system comprises a plurality of tiller assemblies attached to the shaft.
 4. The system of claim 1 wherein the distal edge piece is attached to the turned leading wing at an angle in the range of 10 to 35 degrees.
 5. The system of claim 1 wherein the plurality of wings are attached to the helix at an angle in the range of 4 to 20 degrees.
-