

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409358
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Shen; Lingpeng

Dumbbell assembly

Abstract

A dumbbell assembly includes a dumbbell, and the dumbbell includes a dumbbell rod, dumbbell pieces and fixing plates; the dumbbell rod includes a grip rod and two telescopic rods connected to the grip rod. The dumbbell piece includes a first surface and a second surface which are opposite to each other, a mounting hole is formed in each dumbbell piece, a first guide portion which is obliquely arranged on the first surface, a second guide portion which is obliquely arranged on the second surface, the first guide portion is matched with the second guide portion, and the first guide portion and the second guide portion are located at the two opposite ends of the dumbbell piece respectively in the first direction. The installation difficulty of the action of installing the dumbbell rod into the dumbbell base is reduced.

Inventors:	Shen; Lingpeng (Xiamen, CN)
Applicant:	XIAMEN EDDE SPORTS TECHNOLOGY CO., LTD. (Xiamen, CN)
Family ID:	96434296
Assignee:	XIAMEN EDDE SPORTS TECHNOLOGY CO., LTD. (Xiamen, CN)
Appl. No.:	18/418230
Filed:	January 20, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250235733 A1	Jul. 24, 2025

Publication Classification

Int. Cl.: A63B21/072 (20060101); A63B21/075 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: A63B (21/0724); A63B (21/0726); A63B (21/0728); A63B (21/0722); A63B (21/072);
 A63B (21/075); A63B (21/0622); A63B (21/0624); A63B (21/063)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0305852	12/2008	Hoglund	482/107	A63B 21/075
2018/0008878	12/2017	Myre	N/A	A63B 21/0726
2019/0366142	12/2018	Dale	N/A	A63B 21/0724
2023/0173328	12/2022	Wu	482/107	A63B 21/075
2023/0321474	12/2022	Nalley	482/107	A63B 21/4035
2025/0025738	12/2024	Li	N/A	A63B 21/0726

Primary Examiner: Anderson; Megan

Assistant Examiner: Dicuia; Jonathan A

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to the technical field of training equipment, in particular to a dumbbell assembly.

BACKGROUND

(2) Dumbbells are simple equipment used to enhance muscle strength training, including fixed weight dumbbells and adjustable weight dumbbells.

(3) Traditional adjustable weight dumbbells are mainly composed of dumbbell rods and dumbbell pieces, and dumbbell bases for storage. The dumbbell pieces to be assembled are stacked and stored on the dumbbell base. When adjusting the weight, the dumbbell rod and the dumbbell pieces assembled on the dumbbell rod must be loaded into the dumbbell base, and then the number of dumbbell pieces assembled on the dumbbell rod needs to be adjusted. Due to the limitation of the structure of the dumbbell piece, when the dumbbell rod is installed into the dumbbell base, the installation angle is relatively high, so that the installation of the dumbbell rod becomes difficult, resulting in troublesome adjustment of the counterweight of the dumbbell.

SUMMARY

(4) The purpose of the present disclosure is to provide a dumbbell assembly without the technical problems including the installation of the dumbbell rod into the dumbbell base and adjusting the counterweight.

(5) In order to solve the above problems, the disclosure provides a dumbbell assembly, which includes a dumbbell and a dumbbell base for placing the dumbbell, and the dumbbell includes: a dumbbell rod, including a grip rod and two telescopic rods connected to the grip rod, the grip rod and the telescopic rod are coaxially arranged, and the rotation of the grip rod can drive the two telescopic rods to move away or towards each other along an axial direction of the grip rod;

dumbbell pieces, each dumbbell piece includes a first surface and a second surface opposite to each other, and the dumbbell piece is provided with a mounting hole passing through the first surface and the second surface and allowing the telescopic rod to pass through, there is a first guide portion on the first surface, the first guide portion is inclined and extends from the edge of the first surface toward the middle of the first surface, and there is a second guide portion on the second surface, the second guide portion is arranged obliquely and extends from the edge of the second surface toward the middle of the second surface, an inclination angle of the first guide portion is same as the second guide portion, and an inclination direction of the first guide portion is same as the second guide portion, along the first direction, the first guide portion and the second guide portion are respectively located at opposite ends of the dumbbell piece, wherein the first direction is perpendicular to the axial direction of the mounting hole; two fixing plates, which are respectively sheathed on two ends of the grip rod, and the fixing plate is used for supporting the dumbbell rod and connecting the dumbbell pieces.

(6) In one embodiment, the fixing plate includes an inner side surface and an outer side surface facing away from each other, the outer side surface is a side away from the middle of the grip rod, and the outer side is provided with the same structure as the first guide portion. The third guiding portion extends from the edge of the outer side surface toward the middle of the outer side surface.

(7) In one embodiment, the outer side surface of the fixing plate and the first surface of the dumbbell piece are provided with a first engaging structure, the second surface of the dumbbell piece is provided with a second engaging structure, and the second engaging structure can cooperate with the first engaging structure on the fixing plate or the adjacent dumbbell piece, so that the fixing plate is axially connected with at least one of the dumbbell pieces.

(8) In one embodiment, the first engaging structure is a slot extending along the first direction and forming a socket at one end; The second engaging structure is a socket plate, which is protruded from the surface of the dumbbell piece and extends along the first direction, and the socket plate can be inserted into the slot from the socket; at least one of the slot and the socket plate is provided with a clamp slot extending along the first direction, and the other is provided with a protrusion extending along the first direction, and the protrusion and the clamp slot are engaged with each other.

(9) In one embodiment, the first guide portion extends from the edge of the first surface to the socket and is obliquely connected to the bottom surface of the slot, and the second guide portion is located at an end away from the socket; an inclination angle between the first guide portion and the bottom surface of the slot is 10° - 30° .

(10) In one embodiment, the grip rod includes an installation cavity, and the two telescopic rods are movably arranged in the installation cavity; the surface of the telescopic rod is provided with a spiral groove, and the grip rod is provided with a guide column extending radially, the guide column extends into the spiral groove, and the grip rod can drive the guide column to rotate and move in the spiral groove, so that the telescopic rod extends out or retracts into the installation cavity of the grip rod; the surface of the telescopic rod is provided with a flat section extending along its axial direction.

(11) In one embodiment, the dumbbell further includes a rotating plate, the rotating plate is fixedly sleeved on the grip rod, and the rotating plate and the dumbbell piece are respectively connected to opposite sides of the fixing plate; one of the fixing plate and the rotating plate is provided with glass ball screws, and the other is provided with a plurality of ball holes distributed along the circumference, the grip rod can drive the rotating plate to rotate, and make the the balls of the glass ball screw snap into the ball holes.

(12) In one embodiment, the dumbbell further includes a safety lock, the safety lock is arranged on the rotating plate and the fixing plate, and is used for locking the rotating plate and the fixing plate.

(13) In one embodiment, the safety lock includes a safety buckle and a spring, the fixing plate is provided with a first limiting groove, and the rotating plate is provided with a second limiting

groove communicated with the first limiting groove. groove; one end of the safety buckle is installed in the first limiting groove and can move in the first limiting groove along the radial direction of the fixing plate, and the other end is installed in the second limiting groove and can move in or out of the second limiting groove along the radial direction of the rotating plate; the spring extends along the radial direction of the fixing plate and one end is abutted against the installation buckle, and the other end is abutted against the inner wall of the first limiting groove, and the safety buckle can be pressed along the fixing plate to move out of the second limiting groove.

(14) In one embodiment, the safety buckle is exposed on the edge of the fixing plate, and the dumbbell base is provided with an unlocking projection opposite to the safety buckle, and the unlocking projection is used to press the safety buckle and the spring.

(15) The dumbbell assembly provided by the present disclosure includes a dumbbell and a dumbbell base, and the dumbbell includes a dumbbell rod, dumbbell pieces and fixing plates. Because each dumbbell piece includes a first surface and a second surface facing away, the first guide portion is provided on the first surface, the first guide portion is arranged obliquely and extends from the edge of the first surface toward the middle of the first surface, and the second surface is provided with a second guide portion, the second guide portion is arranged obliquely and extends from the edge of the second surface toward the middle of the second surface, along the first direction, the first guide portion and the second guide portion are respectively arranged at the two ends of the dumbbell piece. Therefore, during the process of putting the dumbbell pieces into the dumbbell base, the first guide portion and the second guide portion on the adjacent dumbbell piece can guide and cooperate. In this way, on the one hand, the first guide portion and the second guide portion form an avoidance space, which can reduce interference, reduce the constraint standard when the dumbbell is lowered to the dumbbell base, improve the error tolerance rate during the lowering process, so that the dumbbell can be smoothly loaded into the dumbbell base when it has a certain inclination angle (caused by the user's grip angle); on the other hand, the first guide portion is used in conjunction with the second guide portion, and has a correction function, so that the lowering angle can be corrected synchronously during the dumbbell lowering process, so that the dumbbell can fall into the dumbbell base along the vertical direction. To sum up, the dumbbell assembly provided by the present disclosure, by improving the structure of the dumbbell pieces and designing the first guide portion and the second guide portion on the dumbbell pieces, can reduce the difficulty of installing the dumbbell rod into the dumbbell base, and solve the problem of adjusting the weight of the dumbbell, troublesome technical problems, improve the convenience and user experience of dumbbells.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to more clearly illustrate the technical solutions in the embodiments of the present disclosure or the prior art, the following will briefly introduce the drawings that need to be used in the description of the embodiments or the prior art. Obviously, the accompanying drawings in the following description are only some embodiments of the present disclosure. Those skilled in the art can further obtain other drawings based on these drawings without creative work.

(2) FIG. 1 is a schematic structural view of a dumbbell assembly provided in the embodiment of the present disclosure.

(3) FIG. 2 is a front view of the dumbbell assembly shown in FIG. 1.

(4) FIG. 3 is sectional view of the dumbbell assembly shown in FIG. 1.

(5) FIG. 4 is a structural schematic diagram of the first side surface of the dumbbell piece in the dumbbell assembly shown in FIG. 1.

- (6) FIG. 5 is a structural schematic diagram of the second side surface of the dumbbell piece in the dumbbell assembly shown in FIG. 1.
- (7) FIG. 6 is side view of a dumbbell piece in the dumbbell assembly shown in FIG. 1.
- (8) FIG. 7 is a schematic diagram of the structure of the dumbbell rod and the fixing plate in the dumbbell assembly shown in FIG. 1.
- (9) FIG. 8 is the first of the schematic diagrams for use of the dumbbell assembly shown in FIG. 1.
- (10) FIG. 9 is the second schematic diagram of the use of the dumbbell assembly shown in FIG. 1.
- (11) FIG. 10 is the third schematic diagram of the use of the dumbbell assembly shown in FIG. 1.
- (12) FIG. 11 is a schematic diagram of the structure of the dumbbell base in the dumbbell assembly shown in FIG. 1.
- (13) FIG. 12 is a schematic diagram of the structure of the telescopic rod in the dumbbell assembly shown in FIG. 1.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (14) In order to make the purpose, technical solution and advantages of the present disclosure clearer, the present disclosure will be further described in detail below in conjunction with the accompanying drawings and embodiments. It should be understood that the specific embodiments described here are only used to explain the present disclosure, not to limit the present disclosure.
- (15) It should be noted that when a component is referred to as being “fixed on” or “disposed on” another component, it may be directly or indirectly on the other component. When an element is referred to as being “connected to” another element, it can be directly or indirectly connected to the other element. The orientation or positional relationship indicated by the terms “upper”, “lower”, “left”, “right”, etc. are based on the orientation or positional relationship shown in the drawings, and are for convenience of description only, rather than indicating or implying the referred device or elements must have a specific orientation, be constructed and operate in a specific orientation and therefore should not be construed as limiting the patent. The terms “first” and “second” are only used for descriptive purposes, and cannot be understood as indicating or implying relative importance or implicitly specifying the quantity of technical features. “plurality” means two or more, unless otherwise clearly and specifically defined.
- (16) Reference to “one embodiment,” “some embodiments,” or “an embodiment” in the specification of this disclosure means that a particular feature, structure, or characteristic described in connection with the embodiment is included in one or more embodiments of the disclosure. Thus, appearances of the phrases “in one embodiment,” “in some embodiments,” “in other embodiments,” etc. in various places in this specification are not necessarily all refer to the same embodiment, but mean “one or more but not all embodiments” unless specifically stated otherwise. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner in one or more embodiments.
- (17) As shown in FIG. 1 and FIG. 2, the present disclosure provides a dumbbell assembly **100**, including a dumbbell **1** and a dumbbell base **2** for placing the dumbbell **1**, wherein the dumbbell **1** includes a dumbbell rod **11**, dumbbell pieces **12** and two fixing plates **13**, by adjusting the number of assembled dumbbell pieces **12** on the dumbbell rod **11** can realize the adjustment of the weight of the dumbbell **1**.
- (18) As shown in FIG. 2 and FIG. 3, the dumbbell rod **11** includes a grip rod **111** and two telescopic rods **112** connected to the grip rod **111**. The grip rod **111** and the telescopic rod **112** are arranged coaxially (e.g. FIG. 3, the direction shown by X in the middle) and moves away or towards each other. The telescopic rod **112** is used to install the dumbbell pieces **12**, and the number of dumbbell pieces **12** that can be hung on is related to its length.
- (19) As shown in FIG. 3, FIG. 4 and FIG. 5, each dumbbell piece **12** includes a first surface **121** and a second surface **122** opposite to each other, and the dumbbell piece **12** is provided with a mounting hole **123** passing through the first surface **121** and the second surface **122** and allowing the telescopic rod **112** to pass through. As shown in FIG. 3 and FIG. 4, there is a first guide portion

124 on the first surface **121**, the first guide portion **124** is arranged obliquely and extends from the edge of the first surface **121** toward the middle of the first surface **121**. As shown in FIG. 3 and FIG. 5, there is a second guide portion **125** on the second surface **122**, the second guide portion **125** is inclined and extends from the edge of the second surface **122** toward the middle of the second surface **122**. As shown in FIG. 6, the inclination angle of the first guide portion is same as the second guide portion, and a inclination direction of the first guide portion **124** is same as the second guide portion **125**, along the first direction (such as FIG. 3 The direction indicated by Y in the middle), the first guide portion **124** and the second guide portion **125** are respectively located at opposite ends of the dumbbell piece **12**, and the first guide portion **124** and the second guide portion **125** can be used together. At the positions of the first guide portion **124** and the second guide portion **125**, the thickness of the dumbbell pieces **12** decreases gradually. Wherein, the first direction is perpendicular to the axial direction of the mounting hole **123**. As shown in FIG. 3, the dumbbell pieces **12** are stacked and placed in the dumbbell base **2**, and the first surface **121** and the second surface **122** of the adjacent dumbbell pieces **12** are attached to each other. One of the first guide portion **124** and the second guide portion **125** is rotated to the top, and the other is rotated to the bottom, so that the first guide portion **124** and the second guide portion **125** on the adjacent dumbbell piece **12** can guide and cooperate.

(20) As shown in FIG. 2 and FIG. 7, the fixing plates **13** are sheathed on both ends of the grip rod **111** for supporting the dumbbell rod **11** and for connecting the dumbbell pieces **12**. As shown in FIG. 3, the dumbbell rod **11**, the dumbbell pieces **12** and the fixing plates **13** can be placed on the dumbbell base **2**, and the fixing plates **13** are sleeved on the grip rod **111** of the dumbbell rod **11** to support the dumbbell rod **11**, so that the dumbbell rod **11** is aligned with the mounting holes **123** of the dumbbell pieces **12**.

(21) The specific usage of the above-mentioned dumbbell assembly **100** is as follows: firstly, the dumbbell **1** is placed on the dumbbell base **2**, a plurality of dumbbell pieces **12** are stacked and placed in the accommodation groove **21** of the dumbbell base **2**, and the telescopic movement of the dumbbell rod **11** The rod **112** is aligned with the mounting hole **123** of the dumbbell piece **12**. When it is necessary to increase the counterweight, the grip rod **111** of the dumbbell **1** can be rotated so that the telescopic rod **112** extends to a preset length and the telescopic rod **112** penetrates into the mounting hole **123** of the dumbbell piece **12**, thereby increasing the amount of hanging the dumbbell on the telescopic rod **112**. The number of pieces **12** increases the counterweight of dumbbell **1**; when the counterweight needs to be reduced, the grip rod **111** can be rotated in reverse to make the telescopic rod **112** retract to a preset length, so as to release the connection between the telescopic rod **112** and part of the dumbbell pieces **12**, thereby reducing the number of dumbbell pieces **12** is hung on the telescopic rod **112** to reduce the weight of the dumbbell **1**. As shown in FIG. 8, FIG. 9 and FIG. 10, the operator can complete the pick-and-place action of the dumbbell **1** by grasping the grip rod **111**.

(22) The dumbbell assembly **100** provided in this disclosure includes a dumbbell **1** and a dumbbell base **2**, and the dumbbell **1** includes a dumbbell rod **11**, a dumbbell piece **12** and a fixing plate **13**. Since the dumbbell piece **12** includes opposite first surfaces **121** and second surfaces **122**, the first surface **121** has a first guide portion **124**, the first guide portion **124** is arranged obliquely and faces the first surface **121** from the edge of the first surface **121**. Extending in the middle of the second surface **122**, there is a second guide portion **125**, the second guide portion **125** is inclined and extends from the edge of the second surface **122** toward the middle of the second surface **122**, along the first direction, the first guide portion **124** and the second guide portion **125** are respectively arranged on the two ends of the dumbbell piece **12**, so that when the dumbbell piece **12** is put into the dumbbell base **2**, the first guide portion **124** and the second guide portion **125** on the adjacent dumbbell pieces **12** can guide and cooperate. In this way, on the one hand, the first guide portion **124** and the second guide portion **125** form an avoidance space, which can reduce interference, reduce the constraint standard when the dumbbell **1** is lowered to the dumbbell base **2**,

and improve the error tolerance rate during the lowering process, so that the dumbbell **1** can further be smoothly loaded into the dumbbell base **2** when it has a certain inclination angle (caused by the user's grip angle). The lowering angle can be corrected synchronously, so that the dumbbell **1** can be dropped into the dumbbell base **2** along the vertical direction. To sum up, the dumbbell assembly **100** provided by the present disclosure, by improving the structure of the dumbbell piece **12** and designing the first guide portion **124** and the second guide portion **125** on the dumbbell pieces **12**, can reduce the difficulty in the installation of the dumbbell rod **11** into the dumbbell base **2**, solve the technical problem of the troublesome operation of the dumbbell **1** to adjust the counterweight, and improve the convenience and user experience of the dumbbell **1**.

(23) As shown in FIG. **3** and FIG. **4**, the mounting hole **123** is opened in the center of the dumbbell piece **12**, and its shape is similar to the axial cross-section shape of the telescopic rod **112**, so that the dumbbell **1** can be turned in any direction during use, and the weight of the dumbbell **1** is evenly distributed in all directions.

(24) As shown in FIG. **3** and FIG. **7**, the fixing plate **13** includes an inner side surface **131** and an outer side surface **132** opposite to each other, and the outer side surface **132** is a side away from the middle of the grip rod **111**. Wherein, the middle of the grip rod **111** is the axial midpoint of the grip rod **111**. As shown in FIG. **3** and FIG. **8**, the dumbbell piece **12** is connected to the fixing plate **13**, and the second surface **122** of the dumbbell piece **12** is attached to the outer side surface **132** of the fixing plate **13**.

(25) For further improving the smoothness of dumbbell rod **11** loading dumbbell base **2** actions, as shown in FIG. **3**, FIG. **8** and FIG. **9**, the outer side surface **132** of the fixing plate **13** is provided with a third guide portion **133** having the same structure as the first guide portion **124**, and the third guide portion **133** extends from the edge of the outer side surface **132** toward the middle of the outer side surface **132**. Set up in this way, in the process of loading the dumbbell base **2** with the dumbbell rod **11** that is not hung with the dumbbell piece **12**, as shown in FIG. **3**, FIG. **8** and FIG. **10**, the third guide portion **133** on the fixing plate **13** can guide and cooperate with the second guide portion **125** of the dumbbell piece **12** provided on the dumbbell base **2**, thereby reducing the difficulty of installing the unloaded dumbbell rod **11** and further improving the stability of the dumbbell **1**.

(26) In the dumbbell assembly **100** provided in this disclosure, the dumbbell piece **12** is hung on the telescopic rod **112** of the dumbbell rod **11**, and the fixed connection between the dumbbell piece **12** and the dumbbell rod **11** is not unique.

(27) In some embodiments, as shown in FIG. **3**, FIG. **4** and FIG. **7**, the outer side surface **132** of the fixing plate **13** and the first surface **121** of the dumbbell piece **12** are provided with a first engaging structure **14**. As shown in FIG. **3**, FIG. **5** and FIG. **7**, the second surface **122** of the dumbbell piece **12** is provided with a second engaging structure **15**, and the second engaging structure **15** can be engaged with the fixing plate **13** or the first engaging structure **14** on the adjacent dumbbell piece **12**, so that the fixing plate **13** is axially connected with at least one dumbbell piece **12**. In this way, the dumbbell pieces **12** and the fixing plates **13**, as well as between the adjacent dumbbell pieces **12**, can be snapped together through the engaging structure, and the axial fixed connection can be realized, so that the telescopic rod **112** can be inserted into the mounting hole **123** of the dumbbell pieces **12**. After that, the axial and radial fixation of the dumbbell pieces **12** can be realized, and the fixed connection between the dumbbell pieces **12** and the dumbbell rod **11** can be realized. The connection structure between the dumbbell pieces **12** and the dumbbell rod **11** is reasonable and easy to assemble and disassemble.

(28) Or, in some embodiments, a matching threaded structure can further be provided on the wall of the telescopic rod **112** and the mounting hole **123** of the dumbbell piece **12**, and the dumbbell pieces **12** and the telescopic rod **112** can be axially fixed by threaded connection, so as to realize the dumbbell piece **12** is fixedly connected with dumbbell rod **11**.

(29) When the engaging structure is used to connect the fixing plate **13** and the dumbbell pieces **12**,

the type of the engaging structure is not unique.

(30) In some embodiments, as shown in FIG. 4, the first engaging structure **14** is a slot extending along a first direction and forming a socket at one end. As shown in FIG. 5, the second engaging structure **15** is a socket plate, which protrudes from the surface of the dumbbell piece **12** and extends along the first direction, and the socket plate can be plugged into the slot from the socket. At least one of the slot and the socket plate is provided with a slot extending along the first direction, and the other is provided with a protrusion extending along the first direction, and the protrusion is engaged with the slot. Such arrangement, on the one hand, the slot and the socket plate are simple in structure, and the fixing plate **13** and the dumbbell piece **12** are easy to disassemble; on the other hand, when the dumbbell **1** is placed on the dumbbell base **2**, the first surface **121** of the outermost dumbbell piece **12** The first surface **121** of the dumbbell piece **12** is provided with slots, and the structure is reasonable.

(31) Optionally, two opposite groove walls of the slot are provided with card slots, the socket plate protrudes from the surface of the dumbbell piece **12**, and the two opposite sides of the socket plate form card protrusions.

(32) Further, as shown in FIG. 4, the slot is a dovetail slot and the width of the socket along the second direction is greater than the width of the end of the slot away from the socket. Wherein, the second direction is perpendicular to the first direction and the axial direction of the mounting hole **123**. Such setting can reduce the difficulty of aligning the slot and the plug board, thereby reducing the difficulty of assembling the slot and the plug board, and further improving the convenience of use of the dumbbell assembly **100**.

(33) Further, the cross-sectional shape of the slot can be square, V-shaped or U-shaped, etc.

(34) Or, in some embodiments, the first engaging structure **14** and the second engaging structure **15** can further be designed as a plug board, and the third engaging structure can be designed as a slot adapted to the plug board, and The specific structure of the groove and the plug plate, and the placement of the dumbbell piece **12** during use are designed according to actual conditions, and are not limited here.

(35) It should be noted that the first direction is used to illustrate the relative positions of the first guide portion **124** and the second guide portion **125**, as well as the structure of the slot and the plug board, and any direction on the surface of the fixing plate **13** or the dumbbell piece **12** can be selected. The direction is as the first direction. In actual use, in order to ensure that the dumbbell **1** can be used normally, it is necessary to adjust the installation angle of the dumbbell piece **12** and the dumbbell rod **11** so that the defined first direction and the vertical direction (such as FIG. 3 in the direction indicated by Y) and keep the notch of the socket turned to the bottom. And, in actual use, since the dumbbell piece **12** is placed vertically, the axial direction of the mounting hole **123** is consistent with the axial direction of the grip rod **111** and the telescopic rod **112**, so no distinction is made here.

(36) In an embodiment provided by this disclosure, as shown in FIG. 3 and FIG. 4, the first engaging structure **14** is a slot, and the slot includes a socket. The first guide portion **124** extends from the edge of the first surface **121** to the socket and is obliquely connected to the bottom surface of the slot. The second guide portion **125** is located away from the socket.

(37) Similarly, the third guiding portion **133** extends from the edge of the outer side surface **132** to the socket of the corresponding slot, and is obliquely connected to the bottom surface of the corresponding slot.

(38) Further, the angle between the first guide portion **124** and the bottom surface of the slot is 10°-30° (The angle α shown in FIG. 6). Optionally, in an embodiment, the angle between the first guide portion **124** and the bottom surface of the slot is 22.5°. With such arrangement, the structure of the first guiding part **124** and the second guiding part **125** is reasonable, and the guiding effect is good.

(39) In an embodiment provided by this disclosure, as shown in FIG. 8 and FIG. 10, the end of the

plug board away from the socket has a fourth guide portion **126**, and the inclination direction of the fourth guide portion **126** is consistent with that of the second guide portion **125**. The fourth guide portion **126** can be in contact with the first surface **121** of the adjacent dumbbell piece **12** and has a certain guiding effect, which is beneficial to further improving the smoothness of the dumbbell rod **11** being put into the dumbbell base **2**.

(40) In the dumbbell assembly **100** provided in the present disclosure, the connection mode between the telescopic rod **112** and the grip rod **111** is not unique.

(41) In some embodiments, as shown in FIG. 3 and FIG. 12, the grip rod **111** includes an installation cavity, and two telescopic rods **112** are arranged in the installation cavity. The surface of the telescopic rod **112** is provided with a spiral groove **1121**, and the grip rod **111** is provided with a guide column **113** extending radially thereon. The column **113** moves in the spiral groove **1121**, thereby converting the rotation of the grip rod **111** into the linear movement of the telescopic rod **112**, so that the telescopic rod **112** extends out or retracts into the installation cavity of the grip rod **111**. With such arrangement, the structure of the grip rod **111** and the telescopic rod **112** is simple, and the telescopic rod **112** is easy to adjust.

(42) It can be understood that the number of dumbbell pieces **12** that can be assembled with the telescopic rod **112** is related to the length that extends out of the installation cavity of the grip rod **111**.

(43) Further, in order to improve the convenience of use, the grip rod **111** is provided with anti-slip threads.

(44) Further, as shown in FIG. 12, the surface of the telescopic rod **112** is provided with a flat section **1122** extending along its axial direction to ensure that the telescopic rod **112** can move in a straight line.

(45) It can be understood that, in some embodiments, the axial section of the telescopic rod **112** is circular, and the inner side surface of the grip rod **111** and the outer side surface of the telescopic rod **112** are provided with a matching thread structure, and are threaded through the thread structure to rotate the grip rod **111**, which can drive the telescopic rod **112** to rotate and move linearly along the grip rod **111**.

(46) When adjusting the counterweight of the dumbbell **1**, it is necessary to adjust the extension length of the telescopic rod **112** by rotating the grip rod **111**, wherein the movement size of the telescopic rod **112** is related to the rotation angle of the grip rod **111**, and the design of the actual movement size of the telescopic rod **112** should be based on the dumbbell piece **12** to be disassembled.

(47) In order to conveniently control the rotation angle of the grip rod **111** and the moving size of the telescopic rod **112**, the dumbbell assembly **100** provided by the present disclosure, as shown in FIG. 3 and FIG. 8, the dumbbell **1** further includes a rotating plate **16**, the rotating plate **16** is fixedly sleeved on the grip rod **111**, the rotating plate **16** and the dumbbell piece **12** are respectively connected to the opposite sides of the fixing plate **13**, specifically, the rotating plate **16** is connected to the inner side surface **131** of the fixing plate **13**. One of the fixing plate **13** and the rotating plate **16** is provided with glass ball screws, and the other is provided with a plurality of ball holes distributed along the circumference. The grip rod **111** can drive the rotating plate **16** to rotate, and the balls of the glass ball screws can be clamped into the ball hole. The glass ball screw and the ball hole can be regarded as a gear adjuster. The balls of the glass ball screw slide into different ball holes, which can reflect different gear positions and correspond to the weight of the dumbbell **1**. When the ball of the glass ball screw slides into the ball hole, it can make a sound, and the user can control the rotation of the grip rod **111** according to the sound instruction.

(48) Optionally, glass ball screws are provided on the side of the fixing plate **13** connected to the rotating plate **16**, and ball holes are provided on the side of the rotating plate **16** connected to the fixing plate **13**.

(49) It should be noted that the ball holes are distributed on the rotation track of the rotating plate

16, and the specific distribution needs to be designed according to the dumbbell pieces **12**. If a plurality of dumbbell pieces **12** have the same weight and the same thickness, then a plurality of ball holes are evenly distributed along the circumference. If a plurality of dumbbell pieces **12** have the different weight and the different thickness, then the distance of different ball holes is different, and the distance is proportional to the thickness of the dumbbell pieces **12**.

(50) In addition, the fixing plate **13** can be sleeved on the grip rod **111** through a ring or the like, and the grip rod **111** can rotate relative to the ring, and the fixing plate **13** does not rotate with the grip rod **111** during the rotation process. The connection mode between the fixing plate **13** and the grip rod **111** can be designed according to the actual situation, which is not limited here.

(51) As shown in FIG. 3, the grip rod **111** is sleeved with a rotating plate **16** and a fixing plate **13**, and the grip rod **111** is provided with a through hole. One end of the guide column **113** is fixedly connected to the rotating plate **16**, and the other end passes through the through hole and is inserted into the accommodating cavity of the grip rod **111**, rotating the grip rod **111** can drive the guide column **113** and the rotating plate **16** to rotate together.

(52) Further, the surface of the rotating plate **16** is marked with counterweight data.

(53) The dumbbell assembly **100** provided by the disclosure, as shown in FIG. 3, the dumbbell **1** further includes a safety lock **17**, which is arranged on the rotating plate **16** and the fixing plate **13** for locking the rotating plate **16** and the fixing plate **13**. Before adjusting the weight of dumbbell **1**, it needs to be unlocked first. By adopting the above design, the use safety of the dumbbell **1** can be improved.

(54) Further, as shown in FIG. 3, the safety lock **17** includes a safety buckle **171** and a spring **172**, the fixing plate **13** is provided with a first limiting groove, and the rotating plate **16** is provided with a second limiting groove communicating with the first limiting groove. One end of the safety buckle **171** is installed in the first limiting groove and can move in the first limiting groove along the radial direction of the fixing plate **13**, and the other end is installed in the second limiting groove and can move in along the radial direction of the rotating plate **16**. Or move out of the second limiting groove. The spring **172** extends radially along the fixing plate **13** and one end is against the mounting buckle, and the other end is against the inner wall of the first limiting groove. The safety buckle **171** is pressed and can move along the radial direction of the fixing plate **13** to move out of the second limit slot. Adopt above-mentioned design, safety lock **17** is reasonable in structure, easy to use.

(55) The safety buckle **171** is provided with a accommodation groove, and the spring **172** is partly installed in the accommodation groove.

(56) As shown in FIG. 3, FIG. 10 and FIG. 11, the safety buckle **171** is exposed on the edge of the fixing plate **13**, and the dumbbell base **2** is provided with an unlocking projection **22** opposite to the safety buckle **171**, and the unlocking projection **22** is used to press the safety buckle **171** and the spring **172**. As shown in FIG. 11, the unlocking projection **22** is located at the bottom of the accommodation groove **21**. With the above design, when the dumbbell **1** is placed on the dumbbell base **2**, it can be automatically unlocked and the operation is simple.

(57) The dumbbell assembly **100** includes a plurality of dumbbell pieces **12** with similar shapes so that the multiple dumbbell pieces **12** can be assembled together. The weights of the multiple dumbbell pieces **12** can be the same or different.

(58) In an embodiment provided by the present disclosure, the weight of the dumbbell rod **11**, the fixing plate **13** and the rotating plate **16** is 51b, and the dumbbell **1** includes 8 replaceable dumbbell pieces **12**, and the 8 pieces of dumbbell pieces **12** have the same structure and the weight of each piece is 2.5 lb, the dumbbell **1** can adjust the weight range from 2.5 to 25 lb.

(59) To sum up, the dumbbell assembly **100** provided by the present disclosure, by improving the structure of the dumbbell piece **12** and designing the first guide portion **124** and the second guide portion **125** on the dumbbell piece **12**, can reduce difficulty of the installation of the dumbbell rod **11** into the dumbbell base **2**, solve the technical problem of the troublesome operation of the

dumbbell 1 to adjust the counterweight, and improve the convenience and user experience of the dumbbell 1.

(60) The above embodiments are only used to illustrate the technical solutions of the present disclosure, rather than to limit them; although the present disclosure has been described in detail with reference to the foregoing embodiments, those of ordinary skill in the art should understand that: it can still apply to the foregoing embodiments. Modifications to the technical solutions recorded, or equivalent replacements for some of the technical features; and these modifications or replacements do not make the essence of the corresponding technical solutions deviate from the spirit and scope of the technical solutions of each embodiment of the disclosure, and should be included in the scope of protection of this disclosure.

Claims

1. A dumbbell assembly, comprising: a dumbbell and a dumbbell base for placing the dumbbell, and the dumbbell comprises: a dumbbell rod, wherein the dumbbell comprises a grip rod and two telescopic rods connected to the grip rod, the grip rod and the two telescopic rods are coaxially arranged, and a rotation of the grip rod can drive the two telescopic rods to move along an axial direction of the grip rod away or towards each other; a plurality of dumbbell pieces, wherein each dumbbell piece comprises a first surface and a second surface opposite to each other, and each dumbbell piece is provided with a mounting hole passing through the first surface and the second surface and allowing the telescopic rod to pass through, the first surface is provided with a first guide portion, the first guide portion is inclined and extends from an edge of the first surface toward a middle of the first surface, and the second surface is provided with a second guide portion, the second guide portion is inclined and extends from an edge of the second surface toward a middle of the second surface, an inclination angle of the first guide portion is same as the second guide portion, and an inclination direction of the first guide portion is same as the second guide portion, along a first direction, the first guide portion and the second guide portion are respectively located at opposite ends of each dumbbell piece, wherein the first direction is perpendicular to an axial direction of the mounting hole; two fixing plates, wherein the two fixing plates are respectively sheathed on two ends of the grip rod, and the two fixing plates are used for supporting the dumbbell rod and connecting the dumbbell pieces.
2. The dumbbell assembly according to claim 1, wherein each fixing plate comprises an inner side surface and an outer side surface which are opposite to each other, the outer side surface is away from a middle of the grip rod, and the outer side surface is provided with a third guide portion having a same structure as the first guide portion, the third guiding portion extends from an edge of the outer side surface toward a middle of the outer side surface.
3. The dumbbell assembly according to claim 2, wherein the outer side surface of each fixing plate and the first surface of the dumbbell piece are provided with a first engaging structure, and the second surface of the dumbbell piece is provided with a second engaging structure, and the second engaging structure can cooperate and engage with the fixing plate or the first engaging structure on an adjacent dumbbell piece, so that the fixing plate is axially connected with at least one of the dumbbell pieces.
4. The dumbbell assembly according to claim 3, wherein the first engaging structure is a slot extending along the first direction and forming a socket at one end; the second engaging structure is a socket plate, which is protruded from the second surface of each dumbbell piece and extends along the first direction, and the socket plate can be inserted into the slot from the socket; at least one of the slot and the socket plate is provided with a clamp slot extending along the first direction, and the other is provided with a protrusion extending along the first direction, and the protrusion and the clamp slot are engaged with each other.
5. The dumbbell assembly according to claim 4, wherein the first guide portion extends from the

edge of the first surface to the socket and is obliquely connected to a bottom surface of the slot, and the second guide portion is located at an end away from the socket; an inclination angle between the first guide portion and the bottom surface of the slot is 10° - 30° .

6. The dumbbell assembly according to claim 1, wherein the grip rod comprises an installation cavity, and the two telescopic rods are movably arranged in the installation cavity; a surface of the telescopic rod is provided with a spiral groove, and the grip rod is provided with a guide column extending radially, the guide column extends into the spiral groove, and the grip rod can drive the guide column to rotate and move in the spiral groove, so that the telescopic rod extends out or retracts into the installation cavity of the grip rod; the surface of the telescopic rod is provided with a flat section extending along its axial direction.
