

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410697
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Crane; Don

Downhole sand and gas separator

Abstract

A downhole separator for separating a three-phase fluid produced in an oil or gas well. The downhole separator including a tubular body and a radial directed opening in an uphole end of the tubular body for allowing the three-phase fluid to enter the downhole separator while also permitting a gas component of the three-phase fluid to exit the downhole separator. The downhole separator also including a dip tube disposed inside the tubular body for delivering a primarily liquid component of the three-phase fluid to be processed and a first annulus area disposed between the dip tube and the tubular body. A method of separating components of a three-phase fluid produced in an oil or gas well. The method includes the step of pumping the three-phase fluid into a downhole separator to separate the three-phase fluid into the separate components.

Inventors:	Crane; Don (Snyder, TX)
Applicant:	Endurance Lift Solutions, LLC (Gainesville, TX)
Family ID:	96096758
Assignee:	Endurance Lift Solutions, LLC (Gainesville, TX)
Appl. No.:	18/392175
Filed:	December 21, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250207492 A1	Jun. 26, 2025

Publication Classification

Int. Cl.: E21B43/38 (20060101); E21B43/12 (20060101); E21B43/34 (20060101)

U.S. Cl.:

CPC **E21B43/385** (20130101); **E21B43/121** (20130101); **E21B43/128** (20130101);
E21B43/35 (20200501); **E21B43/38** (20130101);

Field of Classification Search

CPC: E21B (43/35)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1379477	12/1920	Perry	166/105.1	F04B 47/005
1507927	12/1923	Miller	210/458	F04B 53/1037
1651968	12/1926	Claudius	210/123	E21B 43/38
1655817	12/1927	Marsh	166/105.5	E21B 43/38
1672687	12/1927	Penrod	417/434	E21B 43/38
2029323	12/1935	Jones	166/105.1	E21B 43/35
2429043	12/1946	Barnhart	166/105.1	E21B 43/38
2440651	12/1947	Bell	285/333	E21B 17/042
3289608	12/1965	Laval, Jr.	55/455	E21B 43/35
4900433	12/1989	Dean	210/512.3	E21B 43/36
5295537	12/1993	Trainer	166/105.3	E21B 43/38
5411088	12/1994	LeBlanc	166/105.1	B01D 19/0042
5553669	12/1995	Trainer	166/105.1	B01D 29/48
5653286	12/1996	McCoy	166/105.5	E21B 43/38
6039121	12/1999	Kisman	166/372	E21B 43/38
6481499	12/2001	Lopes	166/250.03	E21B 43/35
7377314	12/2007	Gonzalez	166/105.5	E21B 43/38
8136600	12/2011	Fowler	166/267	E21B 43/36
10408035	12/2018	Kennedy	N/A	E21B 43/121
11525348	12/2021	Xiao	N/A	E21B 43/38
2001/0004017	12/2000	Lopes	96/204	E21B 43/38
2004/0244987	12/2003	Crews	166/105	E21B 43/35
2016/0333681	12/2015	Mazzanti	N/A	E21B 43/35
2021/0215024	12/2020	Brown	N/A	E21B 17/1078
2021/0324722	12/2020	Xiao	N/A	E21B 43/38
2022/0003103	12/2021	Xiao	N/A	E21B 43/121
2022/0381129	12/2021	Ellithorp	N/A	E21B 43/38
2023/0064086	12/2022	Fotiades	N/A	E21B 43/34

Primary Examiner: Michener; Blake

Attorney, Agent or Firm: Hall Estill Law Firm

Background/Summary

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(1) Not applicable.

CROSS-REFERENCE TO RELATED APPLICATIONS

(2) Not applicable.

BACKGROUND OF THE DISCLOSURE

1. Field of the Invention

(3) The present disclosure relates to a downhole separator for separating gas and sand (or other solid material) from fluids produced in oil and gas wells.

2. Description of the Related Art

(4) Producing dynamic wells in which both gases and solids are present can create certain challenges. When gases and solids are produced with fluids from a well and delivered to other oil and gas equipment, such as pumps, the run life of the other oil and gas equipment can be shortened. Typical solutions to this problem are accomplished with complicated and expensive equipment.

(5) Accordingly, there is a need for a separator that can efficiently separate gas and solids from fluids produced in oil and gas wells.

SUMMARY OF THE DISCLOSURE

(6) The present disclosure is directed to a downhole separator for separating a three-phase fluid produced in an oil or gas well. The downhole separator including a tubular body and a radial directed opening in an uphole end of the tubular body for allowing the three-phase fluid to enter the downhole separator while also permitting a gas component of the three-phase fluid to exit the downhole separator. The downhole separator also including a dip tube disposed inside the tubular body for delivering a primarily liquid component of the three-phase fluid to be processed and a first annulus area disposed between the dip tube and the tubular body.

(7) The present disclosure also directed to a method of separating components of a three-phase fluid produced in an oil or gas well. The method includes the step of pumping the three-phase fluid into a downhole separator to separate the three-phase fluid into the separate components.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a side elevation view of a downhole separator constructed in accordance with the present disclosure.

(2) FIG. 2 is a partial cross-section and partial side elevation view of the downhole separator constructed in accordance with the present disclosure.

(3) FIG. 3 is another partial cross-section and partial side elevation view of the downhole separator constructed in accordance with the present disclosure.

DETAILED DESCRIPTION OF THE DISCLOSURE

(4) Referring now to the drawings, FIGS. 1-3 show a downhole separator **10** in a wellbore **12** where production materials, such as a three-phase fluid containing gases **13a**, liquids **13b** and solids **13c**, can be produced from the surrounding formation **14**. The wellbore **12** could also have casing (not shown) installed therein. The separator **10** can be in fluidic communication with a pump (not shown) that is used to pull liquids up from the wellbore **12** and through the separator **10**. The liquid in the wellbore **12** typically includes gases and solids, such as sand, that can be harmful to the pump. The separator **10** is employed to remove the gases and solids from the liquid being drawn to the pump. In certain situations, the wellbore **12** can have casing (not shown) installed therein and the casing and formation **14** can be perforated to permit the production materials to flow into the wellbore **12**.

(5) The separator **10** includes an upper jacket **16** with radial directed ports **18** disposed therein to permit the three-phase fluid (liquid, gas and solids) to flow into the separator **10**, a body **20**

attached to the upper jacket **16**, a dip tube **22** that extends at least partially through the body **20** and the upper jacket **18**. The body **20** and the upper jacket **18** can be collectively referred to as the tubular body. The ports **18** are also designed to permit accumulated gases to flow out of the separator **10**. In one embodiment, there is at least one uphole port **18a** and at least one downhole port **18b**. In one embodiment, there could be multiple uphole ports **18s** and multiple downhole ports **18b**. The dip tube **22** has a passageway **24** disposed therein that delivers the liquid/fluid to the pump. A first annulus area **26** is created between the body **20** and the dip tube **22**. The first annulus area **26** is in fluid communication with the ports **18** disposed in the upper jacket **16**.

(6) In another embodiment, the separator **10** can include a shroud **28** supported on a downhole end **30** of the dip tube **22**. A second annulus area **32** exists between the shroud **28** and the body **20** and is in fluid communication with the first annulus area **26**. The shroud **28** is wider than the dip tube **22**, which causes the first annulus area **26** to be wider than the second annulus area **32**. The size differences (radial directed width) between the annulus areas **26** and **32** and the width differences (diameter) between the shroud **28** and the dip tube **22** contribute to the operational aspects of the separator **10**. The separator **10** can also include an adapter **34** disposed between the shroud **28** and the dip tube **22**. The adapter **34** can include a lower end **36** that can be threadably engaged with the shroud **18** and an upper end **38** that can be threadably engaged with the dip tube **22**.

(7) In another embodiment, the separator **10** can include lower jacket member **40** disposed on a downhole end **42** of the body **20**. The lower jacket member **40** directs the solids separated out to a desired solids collector. The lower jacket member **40** can include an angled inner surface **42** to direct the solids downward in the separator **10**.

(8) The ports **18** in the upper jacket **16** can be sized and shaped such that the liquids, solids and gases can flow into the separator **10** via the ports **18**, but also permit gases that enter the separator **10** to coalesce and flow back out of the separator **10**. The gases that flow back out of the separator **10** via the ports **18** will flow uphole above the upper jacket **16** in the wellbore **12** to coalesce with any gases that did not flow into the separator **10**. The shape of the ports **18** can be any shape such that the separator **10** works as desirable, such as square, rectangular, round, oval, oblong, and the like. The larger sized ports **18** allow the gas component to vent therethrough without breaking surface tension of the gas component bubbles. In one embodiment, the ports **18** are larger than about 0.5 inches across in any direction. In another embodiment, the ports **18** are larger than about 0.75 inches across in any direction. In yet another embodiment, the ports **18** are larger than about 1 inch across in any direction. In a further embodiment, the ports **18** are larger than about 1.25 inches across in any direction. In an even further embodiment, the ports **18** are larger than about 1.5 inches across in any direction.

(9) The present disclosure is also directed to a method of separating the production materials with the downhole separator **10**. In use, the production materials are pulled into the first annulus area **26** of the separator **10** via the ports **18**. The separator **10** is set up such that the production materials flow through the first annulus area **26** at a velocity of less than about 0.5 ft per second. Pulling the production materials at a flow rate that causes the velocity of the production materials through the first annulus area **26** to be less than about 0.5 ft per second allows the gas component in the production materials to combine and flow upward and out of the separator **10** via the ports **18**. Gas component bubbles will coalesce to form larger bubbles in the low velocity zone of the first annulus area **26**.

(10) The liquid and solid components of the production materials then flow from the first annulus area **26** to the second annulus area **32**, which is narrower than the first annulus area **26**. The narrower second annulus area **32** causes the velocity of the liquid component and the solid component of the production materials to increase in the second annulus area **32**. The increased velocity through the second annulus area **32** creates an inertial effect, which causes the solid component to be forced in an outer radial direction in the separator **10**.

(11) The liquid component and the solid component, which is being forced outward, flow into an

area below the shroud **18**. The combination of the open area below the shroud **18**, which causes the velocity of the liquid and solid component to slow down, the inertial flow effect and the increased velocity on the solid component of the production materials causes the solid component to continue past the bottom of the shroud **18** and separate from the liquid component. The liquid component is then pulled up into and through the shroud **18** and the dip tube **22** to the pump.

(12) Accordingly, this disclosure includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the disclosure unless otherwise indicated herein or otherwise clearly contradicted by context.

Claims

1. A downhole separator for separating a three-phase fluid produced in an oil or gas well, the downhole separator comprising: a tubular body; a plurality of radial directed openings disposed in and about a circumference of an uphole end of the tubular body for allowing the three-phase fluid to enter the downhole separator while also permitting a gas component of the three-phase fluid to exit the downhole separator, the radial directed openings being square shaped and has side lengths larger than about 1.25 inches, at least two of the openings disposed on opposing sides of the uphole end of the tubular body; a dip tube disposed inside the tubular body for delivering a primarily liquid component of the three-phase fluid to be processed, the downhole separator free of axially disposed tubing between the dip tube and the tubular body; and a first annulus area disposed between the dip tube and the tubular body.
2. The downhole separator of claim 1 further comprising a shroud disposed on a downhole end of the dip tube that is wider than the dip tube.
3. The downhole separator of claim 1 wherein the tubular body is comprised of a body portion and an upper jacket.
4. The downhole separator of claim 3 wherein the radial directed opening is in a sidewall of the upper jacket.
5. The downhole separator of claim 4 wherein the sidewall of the upper jacket is thicker than a sidewall of the body portion of the tubular body.
6. The downhole separator of claim 1 wherein the downhole separator includes multiple radial directed openings and the openings are included in an uphole series of radial directed openings in the uphole end of the tubular body and in a downhole series of radial directed openings in the uphole end of the tubular body.
7. The downhole separator of claim 6 wherein the uphole series of radial directed openings are in generally a first plane and the downhole series of openings are in generally a second plane.
8. A method of separating components of a three-phase fluid produced in an oil or gas well, the method comprising: pumping the three-phase fluid into a downhole separator to separate the three-phase fluid into the separate components, the downhole separator comprises: a tubular body; a plurality of radial directed openings disposed in and about a circumference of an uphole end of the tubular body for allowing the three-phase fluid to enter the downhole separator while also permitting a gas component of the three-phase fluid to exit the downhole separator, the radial directed openings being square shaped and has side lengths larger than about 1.25 inches, at least two of the openings disposed on opposing sides of the uphole end of the tubular body; a dip tube disposed inside the tubular body for delivering a primarily liquid component of the three-phase fluid from the oil or gas well, the downhole separator free of axially disposed tubing between the dip tube and the tubular body; and a first annulus area disposed between the dip tube and the tubular body where a gas component of the three-phase fluid is separated therefrom.
9. The method of claim 8 wherein the three-phase fluid is pumped through a part of the downhole separator at a velocity of less than 0.5 feet per second.

10. The method of claim 8 further comprising a shroud disposed on a downhole end of the dip tube that is wider than the dip tube.
 11. The method of claim 8 wherein the tubular body is comprised of a body portion and an upper jacket.
 12. The method of claim 11 wherein the radial directed opening is in a sidewall of the upper jacket.
 13. The method of claim 12 wherein the sidewall of the upper jacket is thicker than a sidewall of the body portion of the tubular body.
 14. The method of claim 8 wherein the downhole separator includes multiple radial directed openings and the openings are included in an uphole series of radial directed openings in the uphole end of the tubular body and in a downhole series of radial directed openings in the uphole end of the tubular body.
 15. The method of claim 14 wherein the uphole series of radial directed openings are in generally a first plane and the downhole series of openings are in generally a second plane.
-