


(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0216545	A1 *	8/2012	Sennoun	F02K 3/115 60/785
2013/0040545	A1 *	2/2013	Finney	B64D 13/06 454/71
2013/0269357	A1 *	10/2013	Wichmann	F02C 3/34 60/726
2013/0269360	A1 *	10/2013	Wichmann	F02C 6/18 60/773
2016/0369705	A1 *	12/2016	Mackin	F02C 6/08
2017/0016395	A1 *	1/2017	Kim	F02C 6/08
2017/0074171	A1 *	3/2017	Takenaka	F02C 7/224
2017/0106985	A1 *	4/2017	Stieger	B64D 13/02
2017/0113808	A1 *	4/2017	Bond	B64D 41/00
2017/0138201	A1 *	5/2017	Takata	F01D 5/085
2018/0080383	A1 *	3/2018	Snape	F02C 6/08
2018/0163627	A1 *	6/2018	Suciu	F02C 9/18
2018/0258859	A1 *	9/2018	Suciu	F02K 3/115
2018/0266330	A1 *	9/2018	Widener	F23R 3/045
2019/0162121	A1 *	5/2019	Staubach	F02C 7/32
2019/0353103	A1 *	11/2019	Roberge	F02C 7/32
2019/0360349	A1 *	11/2019	Schwarz	F02C 3/073
2019/0360398	A1 *	11/2019	Qiu	F02C 7/14
2020/0232394	A1 *	7/2020	Herring	F02C 7/32
2021/0061476	A1 *	3/2021	Van Den Ende	F02C 7/18
2021/0348564	A1 *	11/2021	Mackin	F02C 7/047
2022/0185485	A1	6/2022	Galzin et al.	
2022/0235707	A1 *	7/2022	Millhaem	F02C 6/08
2022/0397062	A1 *	12/2022	Terwilliger	F02C 7/141
2023/0228214	A1 *	7/2023	Miller	F02K 3/04 60/785
2023/0399111	A1 *	12/2023	Takami	B64D 35/00
2024/0003293	A1 *	1/2024	Takami	F02C 9/18

* cited by examiner






FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2




FIG. 3

1

BOOST COMPRESSOR AUGMENTATION FOR HYBRID ELECTRIC THERMAL MANAGEMENT SYSTEMS

TECHNICAL FIELD

This disclosure relates generally to gas turbines. More specifically, this disclosure relates to boost compressor augmentation for hybrid electric thermal management systems.

BACKGROUND

Industry-wide design trends for gas turbine engines have included a general push towards incorporating hybrid electric systems, which use high-power motor generators and motor controllers powered by gas turbine aircraft engines. However, this presents new challenges associated with the management of waste heat. Because specified operating requirements for aircraft, such as maximum hot day (MHD) requirements, have not changed, the fact that larger electric generators create more heat can present significant technical problems in rejecting the increased excess heat. This can be particularly true during certain operating modes, such as taxiing, landing, and idling, when the volume of air passing through nacelles is low. While increasing the size of a hybrid electric system's heat exchangers to better reject excess heat in low air-flow operating conditions may solve the problem of increasing the system's heat management capacity in theory, this is typically not a viable solution due in part to increased weight and drag associated with larger heat exchangers.

SUMMARY

This disclosure relates to boost compressor augmentation for hybrid electric thermal management systems.

In a first embodiment, a system includes a nacelle and a fan disposed at an intake of the nacelle. The system also includes a gas turbine, where the gas turbine is contained within a first portion of the nacelle. The gas turbine includes a compressor stage, a core stage, and a turbine stage through which a core stream of gas passes through the fan, the compressor stage, the combustor stage, and the turbine stage. The system further includes a first heat exchanger disposed in a second portion of the nacelle, where a fan stream passes through the second portion of the nacelle. In addition, the system includes a boost compressor, a first switching valve, a second switching valve, and a third switching valve. The first switching valve is configured to receive gas from the fan stream, direct the received gas to the second switching valve in an "a" position, and direct the received gas to the turbine stage in a "b" position. The second switching valve is configured to direct gas to the boost compressor, receive gas from the first switching valve in an "a" position, and receive gas from a high pressure bleed from the compressor stage in a "b" position. The third switching valve is configured to receive gas from the boost compressor, direct compressed gas to the first heat exchanger in an "a" position and direct the compressed gas to the turbine stage in a "b" position.

In a second embodiment, a method includes operating a fan disposed at an intake of a nacelle and a gas turbine contained within a first portion of the nacelle. The gas turbine includes a compressor stage, a combustor stage, and a turbine stage through which a core stream of gas passes through the fan, the compressor stage, the combustor stage, and the turbine stage. The method also includes operating a

2

first heat exchanger disposed in a second portion of the nacelle, where a fan stream passes through the second portion of the nacelle. The method further includes using a first switching valve to receive gas from the fan stream and to direct the received gas to a second switching valve in an "a" position or to the turbine stage in a "b" position. The method also includes using the second switching valve to direct gas to a boost compressor and to receive gas from the first switching valve in an "a" position or from a high pressure bleed from the compressor stage in a "b" position. In addition, the method includes using a third switching valve receive gas from the boost compressor and direct compressed gas to the first heat exchanger in an "a" position or to the turbine stage in a "b" position.

Examples of systems according to this disclosure include systems wherein the system further comprises a controller configured to switch the system between a low-flow mode and a flight mode, wherein in the low-flow mode, the first switching valve is in the "a" position, the second switching valve is in the "a" position, and the third switching valve is in the "a" position and wherein in the flight mode, the first switching valve is in the "b" position, the second switching valve is in the "b" position, and the third switching valve is in the "b" position.

Examples of systems according to this disclosure include systems comprising a second heat exchanger, wherein gas from the boost compressor passes the second heat exchanger in the low-flow mode.

Examples of systems according to this disclosure include systems wherein the controller is configured to determine at least one of: an airspeed below a threshold airspeed or an activation of a weight on wheels switch, and in response to the determination, switch the system to the low-flow mode; or determine at least one of: an airspeed above a threshold airspeed or a deactivation of a weight on wheels switch, and in response to the determination, switch the system to the flight mode.

Examples of systems according to this disclosure include systems wherein the boost compressor is an electrically powered compressor; and the boost compressor is configured to be powered by one or more of an aircraft battery, high spool power extraction from the gas turbine, or low spool power extraction from the gas turbine.

Examples of systems according to this disclosure include systems, wherein the first heat exchanger comprises a body portion containing one or more channels for passage of a liquid coolant; a first inlet configured to admit moving gas from the fan stream; and a second inlet configured to admit compressed gas from the boost compressor.

Examples of systems according to this disclosure include systems, wherein the liquid coolant is one or more of water, fuel, or oil.

Examples of systems according to this disclosure include systems, wherein, in flight mode, the first switching valve is configured to direct gas from the fan stream to one or more active clearance control systems in the turbine stage.

Examples of systems according to this disclosure include systems wherein, in flight mode, the third switching valve is configured to provide compressed air to a turbine cooling and leakage air ("TCLA") boost system.

Examples of systems according to this disclosure include systems wherein the controller is configured to progressively switch from the low-flow mode to the flight mode such that compressed gas from the boost compressor is provided to both the first heat exchanger and the turbine stage of the gas turbine.

3

Examples of methods according to this disclosure include methods comprising switching between a low-flow mode and a flight mode wherein, in the flight mode, the first switching valve is in the “b” position, the second switching valve is in the “b” position, and the third switching valve is in the “b” position.

Examples of methods according to this disclosure include methods comprising operating a second heat exchanger, wherein, in the low-flow mode, gas from the boost compressor passes the second heat exchanger.

Examples of methods according to this disclosure include methods comprising switching to the low-flow mode based on a determination of one or more of: an airspeed below a threshold airspeed or an activation of a weight on wheels switch and switching to the flight mode based on a determination of one or more of: an airspeed above a threshold airspeed or a deactivation of a weight on wheels switch.

Examples of methods according to this disclosure include methods wherein the boost compressor is an electrically powered compressor, and the boost compressor is powered by one or more of an aircraft battery, high spool power extraction from the gas turbine, or low spool power extraction from the gas turbine.

Examples of methods according to this disclosure include methods wherein the first heat exchanger comprises a body portion containing one or more channels for passage of a liquid coolant, a first inlet configured to admit moving gas from the fan stream and a second inlet configured to admit compressed gas from the boost compressor.

Examples of methods according to this disclosure include methods wherein the liquid coolant is one or more of water, fuel, or oil.

Examples of methods according to this disclosure include methods wherein, in flight mode, the first switching valve is configured to direct gas from the fan stream to one or more active clearance control systems in the turbine stage.

Examples of methods according to this disclosure include methods wherein, in flight mode, the third switching valve is configured to provide compressed air to a turbine cooling and leakage air (“TCLA”) boost system.

Examples of methods according to this disclosure include methods comprising progressively switching from the low-flow mode to the flight mode such that compressed gas from the boost compressor is provided to both the first heat exchanger and the turbine stage of the gas turbine.

Other technical features may be readily apparent to one skilled in the art from the following figures, descriptions, and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of this disclosure, reference is made to the following description, taken in conjunction with the accompanying drawings, in which:

FIGS. 1A-1D illustrate an example system according to embodiments of this disclosure;

FIG. 2 illustrates an example dual-mode heat exchanger according to embodiments of this disclosure; and

FIG. 3 illustrates an example method according to this disclosure.

DETAILED DESCRIPTION

FIGS. 1 through 3, described below, and the various embodiments used to describe the principles of the present disclosure are by way of illustration only and should not be construed in any way to limit the scope of this disclosure.

4

Those skilled in the art will understand that the principles of the present disclosure may be implemented in any type of suitably arranged device or system.

As noted above, while enhancing the overall performance of an aircraft and providing greater electrification (such as higher voltages) for onboard main buses, the performance gains provided modern hybrid electric systems for aircraft come at the expense of greater waste heat produced by the electrical generation apparatus. While not an issue during the bulk of an aircraft’s use cycle (such as cruising at altitude), managing and rejecting the added waste heat can present significant problems during descent, taxiing and idling, particularly when the outside temperature approaches the MHD limit specified for the aircraft.

Further, as previously noted, installing more or larger heat exchangers (“HEX”) to reject heat from the hybrid electrical system is, for many applications, not a viable option, in that it requires redesigning the engine nacelles (which in turn can affect the design of other components of the airframe), or a decidedly sub-optimal option, in that it requires adding the weight and drag of an enlarged heat exchanger assembly.

Embodiments according to this disclosure reconcile the technical challenge of rejecting the additional waste heat created by improvements in hybrid electric power systems while remaining within the spatial constraints of existing nacelle form factors, and, at the same time, not incurring the weight penalties associated with larger heat exchangers. More specifically, embodiments according to the present disclosure leverage the supply of compressed air available for cooling of turbine blades to augment the airflow over an existing heat exchanger assembly during low-airflow operating conditions in which the volume of cool air passing over the heat exchangers due to the normal operation of the gas turbine and (for taxiing and landing situations) the air being forced into the heat exchanger through the forward motion of the aircraft, is insufficient to draw off the heat accumulating in the thermal management system. Put differently, embodiments according to this disclosure augment the capacity of an existing heat exchanger to draw off system heat by redirecting compressed air from an existing air supply (for example, an air supply to a turbine cooling and leakage air (“TCLA”) boost system) to the heat exchanger during low-airflow operating conditions.

FIGS. 1A through 1D illustrate example embodiments of a system incorporating boost compressor augmentation for hybrid electric thermal management systems according to this disclosure. For consistency and convenience of cross-reference, elements common to more than one of FIGS. 1A-1D are numbered similarly.

Referring to the illustrative example of FIG. 1A, all of the components and possible connections between components of an example system 100 are shown in the figure. The examples shown in FIGS. 1B and 1C show connections for the passage of working fluids which support two different modes of operation of system 100.

As shown in the figures, system 100 comprises a nacelle 101, wherein nacelle 101 can be a nacelle for a gas turbine (for example, a turbofan 105) disposed on a wing or fuselage of an airframe. As shown in FIG. 1A, nacelle 101 comprises an intake fan 107 at a forward orifice of nacelle 101. In many embodiments, intake fan 107 is driven by a low-pressure driveshaft (also referred to as a “low spool”) of turbofan engine 105.

When driven, intake fan 107 pulls air into nacelle 101, wherein a first portion of the air drawn into nacelle 101 forms a core stream of gas, which is further drawn into turbofan 105, passing through a compressor stage 109, a

5

combustor stage **111**, and then a turbine stage **113**. The operation of turbofan **105** both provides mechanical energy in the form of thrust (from hot gas being ejected from the turbine stage) to propel the aircraft, as well as rotational energy from the combustion cycle driving one or more driveshafts of turbofan **105**. The rotational energy drawn from the one or more driveshafts of turbofan **105** can be used to drive one or more electrical generators. Skilled artisans will appreciate that the electrical generators and other electrical apparatus necessarily generate heat. Accordingly, system **100** can include one or more thermal management systems **115**, which provide for the circulation of a liquid coolant (for example, air, water, or oil) past heat-generating electrical apparatus. As shown in the figure, thermal management system **115** directs liquid coolant in a circuit which includes the heat-generating apparatus, and one or more heat exchangers **117**.

The one or more heat exchangers **117** can be disposed in a second portion of nacelle **101**, wherein outside air is drawn in by fan **107** and directed through the second portion nacelle **101** to form a fan stream. In contrast to the gases moving through turbofan **105**, which are forced through the system by the action of the turbofan **105**, the air moving through fan stream moves passively, and is neither compressed nor combusted during its passage through the second portion of nacelle **101**. When the aircraft is cruising at speed, fan **107** moves comparatively large volumes of air over heat exchanger **117**, which is disposed in the fan stream. These comparatively large volumes of air ensure that heat exchanger **117** can, under most operating conditions, readily reject the excess heat generated by an electrical apparatus. In simpler terms, when the aircraft of which system **100** is a part is moving quickly and at altitude, there is abundant very cold air for drawing off excess heat through heat exchanger **117**.

However, when the aircraft of which system **100** is a part is moving comparatively slowly (for example, during taxiing, or idling), fan **107** draws in comparatively smaller volumes of (potentially warmer) air into the fan stream than when cruising at altitude. The diminished air flow in such operating conditions means that waste heat can more readily accumulate in heat exchanger **117**-a technical problem which embodiments according to this disclosure address without increasing (and in some cases, decreasing) the overall mass and drag of system **100**.

As shown in the figures, system **100** further comprises a boost compressor **119**, which is configured to receive uncompressed gas and output compressed gas. In hybrid systems, or systems with large amounts of electrification, boost compressor **119** is an electrically driven compressor, and comprises electric motor **121**. Electric motor **121** can be driven from a plurality of power sources, including, without limitation, an onboard electrical battery, a generator connected to a low spool (for example, a driveshaft connected to fan **107**) or a generator connected to a high spool (for example, a driveshaft connected to turbine stage **113**). In some embodiments, boost compressor **119** can be the compressor for an existing component or sub-system of system **100**, such as a turbine cooling and leakage air ("TCLA") boost compressor, which when the aircraft of which system **100** is a part is cruising at altitude, operates to provide a supply of comparatively cool air to cool turbine stage **113** and to provide a boost of air to offset power losses due to leakage (for example, leakage around turbine blade tips). During low-flow situations, TCLA boost is generally not required as turbofan **105** is operating at only a fraction of its peak power. Thus, where boost compressor **119** is a TCLA

6

boost compressor, is can often be idle or operating at low power during low-flow operating situations.

As shown in the figures, system **100** further comprises one or more active clearance controls **123a** and **123b**, which pass a flow of cool air from the fan stream to turbine stage **113** to provide additional cooling to turbine stage **113** to control the clearance between fan tips and the air seals of turbine stage **113**.

As shown in the figures, system **100** can include a first switching valve **125**, a second switching valve **127** and a third switching valve **129**, which can each be actuated between at least two positions by a controller (for example, a microcontroller in thermal management system **115**). According to embodiments, first switching valve **125** is configured to receive air from the fan stream, and in a first position (shown as "a" in the figures), direct the air to second switching valve **127**. When in a second position (shown as "b" in the figures), first switching valve **125** directs the air received from the fan stream to turbine stage **113**. In this illustrative example, when first switching valve **125** is in its second position, fan stream air is directed to a first, high pressure turbine active clearance control **123a** and a second, low pressure turbine active clearance control **123b**.

Second switching valve **127** is configured to direct air to boost compressor **119**. In a first position (shown as a' in the figures), second switching valve **127** receives air from first switching valve **125**. In a second position (shown as b' in the figures), second switching valve **127** receives compressed air from a high pressure compressor bleed port of compressor stage **109** of turbofan **105**.

Third switching valve **129** is configured to receive compressed air from boost compressor **119**. In a first position (shown as a" in the figures), third switching valve **129** directs the compressed air to heat exchanger **117**. In this way, additional cool air is made available to carry off excess waste heat in the cooling liquid passing through heat exchanger **117**. In a second position (shown as b" in the figures), third switching valve **129** directs the compressed air to turbine stage **113**. In this illustrative example, when in its second position, third switching valve **129** directs compressed air to a TCLA boost for turbine stage **113**.

According to various embodiments, one or more controllers (for example, a controller provided as part of thermal management system **115**) can switch first, second and third switching valves **125-129** together to provide a low-flow mode of operation and a flight mode of operation, according to the current operating state of the aircraft. In the low-flow mode, each of switching valves **125-129** are in the positions shown in the figures as a, a' and a", wherein gas from the high pressure bleed port of compressor stage **109** is provided, via boost compressor **119** to heat exchanger **117**. Additionally, the controller can switch first, second and third switching valves **125-129** simultaneously to the positions shown as b, b' and b" in the figures to provide a flight mode of operation for via conditions in which large volumes of fast-moving, cool air are available to reject heat from heat exchanger **117**, and the immediate performance concern is to maximize the efficiency of turbofan **105**. In some embodiments, the controller can be configured to switch between flight mode and low-flow mode based on a determination that one or more operating conditions is met. For example, in response to detecting one or more of: an airspeed dropping below a threshold speed (for example, 160 knots) or triggering of a weight on wheels switch, the controller can be configured to fully (or, in the case of progressive switching) progressively switch first, second and third switching valves **125-129** from a flight mode to a low-flow mode.

Similarly, in response to detecting one or more of the airspeed crossing above a threshold speed, or deactivation of a weight on wheels switch, the controller can be configured to either fully or progressively switch first, second and third switching valves **125-129** to flight mode. In embodiments wherein switching between low-flow and flight mode is done progressively, the switching can be performed over a predetermined transition range. For example, the system can be configured to gradually switch from a fully low-flow mode to a fully flight mode as the airspeed of the aircraft increases over a predetermined speed window (for example, 120 knots to 160 knots).

Referring to the illustrative example of FIG. 1B, a second view of system **100**, in which only the connections supporting the low-flow mode of system **100** are shown, is provided. As shown in FIG. 1B, when in low-flow mode, there are two cycles of working fluids. In a first cycle **191**, liquid coolant (for example, water, fuel or oil) is circulated between thermal management system **115** and heat exchanger **117**, such that working fluid heated by the electrical components is carried to heat exchanger **117**, where a combination of compressed air from boost compressor **119** and any available air from the fan stream passes over the exterior of heat exchanger **117** to cool the working fluid, which is then returned to thermal management system **115**.

When in low-flow mode, air from the fan stream moves in cycle **193**, wherein it is taken from the fan stream, directed to boost compressor **119** via first switching valve **125** and second switching valve **127**, and then further directed by third switching valve **129** to provide an auxiliary supply of cooling air to pass over heat exchanger **117**, following which it the cycled air is returned to the fan stream.

It should be noted that the modes of operation described with reference to FIGS. 1B and 1C are not mutually exclusive, and that switching valves **125-129** can also be configured such that the output of boost compressor **119** can be provided to both turbine stage **113** and heat exchanger **117**. For example, as the aircraft transitions from its initial climb to cruising, thermal management system **115** may progressively actuate switching valves **125-129** to increasingly divert the output of boost compressor **119** to turbine stage **113** (for example, to a TCLA stage), rather than performing a hard switch between low-flow mode and flight mode.

Referring to the illustrative example of FIG. 1C, a third view of system **100**, connections supporting a flight mode are shown, is provided. Referring to the illustrative example of FIG. 1C, in addition to first cycle **191**, switching valves **125-129** are configured to provide a first flow **195**, taking compressed air from the high pressure compressor bleed port of compressor stage **109**, and passing it to the TCLA boost via boost compressor **119**, and a second flow **197**, wherein air from the fan stream is directed, via first switching valve **125** to first and second active clearance controls **123a** and **123b**.

While this disclosure notes that the technical and practical benefits of using the outputs of existing onboard compressors to increase the heat rejection capacity of a thermal management system without the potential weight and design penalties or replacing an existing heat exchanger or otherwise changing an existing heat exchanger configuration, the present disclosure should be construed as disclaiming embodiments which incorporate additional heat exchangers or otherwise alter an existing heat exchanger architecture. As shown in FIG. 1D, instead of a unitary heat exchanger **117** (as shown in FIGS. 1A-1C), system **100** can, instead, have a first heat exchanger **117A** and a second heat exchanger

117B, wherein second heat exchanger **117B** receives cooling air exclusively from the fan stream within nacelle **101**, while first heat exchanger **117A** can also receive cooling air from boost compressor **119**.

FIG. 2 illustrates an example of a dual mode heat exchanger **200** according to embodiments of this disclosure. Referring the explanatory example of FIG. 2, dual mode heat exchanger **200** comprises a body **205**, including a first air inlet **207** and an air exhaust **211**. One or more coolant channels **209** (for example, uninsulated tubes of conductive material, such as aluminum) pass within body **205**. Dual mode heat exchanger **200** also includes an air exhaust **211**, and a second air inlet **213**. Like heat exchanger **117** in FIGS. 1A-1C, dual mode heat exchanger can be disposed in a portion of a nacelle downstream of a turbine fan, and through which a fan flow of air is passively fed to first air inlet **207**. In some embodiments, first air inlet **207** comprises an orifice surrounding the coolant tubes and comprising a plurality of fins connected to coolant channels **209**, wherein the fins operate to increase the surface area over which the fan flows. Second air inlet **213** is connected to a line fed by a switching valve of the system (for example, third switching valve **129**) and is configured to receive compressed air from a boost compressor when the dual mode hybrid electric system is operating in a low flow mode. Both the air admitted to dual mode heat exchanger **200** via first air inlet **207** and second air inlet **213** exit dual mode heat exchanger **200** via air exhaust **211**.

FIG. 3 illustrates operations of an example method **300** of operating a system (for example, system **100** in FIGS. 1A-1D) according to various embodiments of this disclosure.

According to various embodiments, at operation **305**, a system is switched to a low-flow mode. The system includes a nacelle (for example, nacelle **101**), a fan (for example, fan **107**) disposed at an intake of the nacelle, a gas turbine (for example, turbofan **105**), wherein the gas turbine is contained within a first portion of the nacelle, and the gas turbine comprises a compressor stage, a combustor stage and a turbine stage, through which a core stream of gas passes through the fan, the compressor stage, the combustor stage and the turbine stage, a first heat exchanger (for example, heat exchanger **117**) disposed in a second portion of the nacelle, a boost compressor (for example, boost compressor **119**), a first switching valve (for example, first switching valve **125**), a second switching valve (for example, second switching valve **127**), and a third switching valve (for example, third switching valve **129**), wherein the first switching valve is configured to receive gas from the fan stream, and in an "a" position, direct the received gas to the second switching valve, and in a "b" position, direct the received gas to the turbine stage, wherein the second switching valve is configured to direct gas to the boost compressor, and in an "a" position, receive gas from the first switching valve, and in a "b" position, receive gas from a high pressure bleed from the compressor stage, and wherein the third switching valve is configured to receive gas from the boost compressor, and in an "a" position, direct compressed gas to the first heat exchanger, and in a "b" position, direct the compressed gas to the turbine stage, switching the system to a low-flow mode, wherein the first switching valve is in the "a" position, the second switching valve is in the "a" position, and the third switching valve is in the "a" position. At operation **305**, the first, second and third switching valves are switched to the a, a', and a" positions respectively.

At operation 310, the system is switched from the low-flow mode to flight mode, such that the output of the boost compressor is directed to the turbine stage of the gas turbine. According to certain embodiments, operation 310 can be performed by switching the first, second and third switching valves to the b, b' and b" positions respectively.

It may be advantageous to set forth definitions of certain words and phrases used throughout this patent document. The terms "include" and "comprise," as well as derivatives thereof, mean inclusion without limitation. The term "or" is inclusive, meaning and/or. The phrase "associated with," as well as derivatives thereof, may mean to include, be included within, interconnect with, contain, be contained within, connect to or with, couple to or with, be communicable with, cooperate with, interleave, juxtapose, be proximate to, be bound to or with, have, have a property of, have a relationship to or with, or the like. The phrase "at least one of," when used with a list of items, means that different combinations of one or more of the listed items may be used, and only one item in the list may be needed. For example, "at least one of: A, B, and C" includes any of the following combinations: A, B, C, A and B, A and C, B and C, and A and B and C.

The description in the present disclosure should not be read as implying that any particular element, step, or function is an essential or critical element that must be included in the claim scope. The scope of patented subject matter is defined only by the allowed claims. Moreover, none of the claims invokes 35 U.S.C. § 112 (f) with respect to any of the appended claims or claim elements unless the exact words "means for" or "step for" are explicitly used in the particular claim, followed by a participle phrase identifying a function. Use of terms such as (but not limited to) "mechanism," "module," "device," "unit," "component," "element," "member," "apparatus," "machine," "system," "processor," or "controller" within a claim is understood and intended to refer to structures known to those skilled in the relevant art, as further modified or enhanced by the features of the claims themselves, and is not intended to invoke 35 U.S.C. § 112 (f).

While this disclosure has described certain embodiments and generally associated methods, alterations and permutations of these embodiments and methods will be apparent to those skilled in the art. Accordingly, the above description of example embodiments does not define or constrain this disclosure. Other changes, substitutions, and alterations are also possible without departing from the spirit and scope of this disclosure, as defined by the following claims. For example, while described as a gas turbine engine throughout, it is understood that the present disclosure is applicable with any type of turbine engine, such as that fueled with traditional hydrocarbon fuel or other non-traditional fuels, such as sustainable aviation fuel (SAF), liquid hydrogen (LH2) and/or the like.

What is claimed is:

1. A system comprising:

a nacelle;

a fan disposed at an intake of the nacelle;

a gas turbine contained within a first portion of the nacelle, the gas turbine comprising a compressor stage, a combustor stage, and a turbine stage through which a core stream of gas passes through the fan, the compressor stage, the combustor stage, and the turbine stage;

a first heat exchanger disposed in a second portion of the nacelle, wherein a fan stream passes through the second portion of the nacelle;

a boost compressor;

a first switching valve;

a second switching valve; and

a third switching valve;

wherein the first switching valve is configured to receive gas from the fan stream, direct the received gas to the second switching valve in an "a" position, and direct the received gas to the turbine stage in a "b" position; wherein the second switching valve is configured to direct gas to the boost compressor, receive gas from the first switching valve in an "a" position, and receive gas from a high pressure bleed from the compressor stage in a "b" position; and

wherein the third switching valve is configured to receive gas from the boost compressor, direct compressed gas to the first heat exchanger in an "a" position and direct the compressed gas to the turbine stage in a "b" position.

2. The system of claim 1, wherein:

the system further comprises a controller configured to switch the system between a low-flow mode and a flight mode;

in the low-flow mode, the first switching valve is in the "a" position, the second switching valve is in the "a" position, and the third switching valve is in the "a" position; and

in the flight mode, the first switching valve is in the "b" position, the second switching valve is in the "b" position, and the third switching valve is in the "b" position.

3. The system of claim 2, wherein the controller is configured to:

determine at least one of: an airspeed below a threshold airspeed or an activation of a weight on wheels switch, and in response to the determination, switch the system to the low-flow mode; or

determine at least one of: an airspeed above a threshold airspeed or a deactivation of a weight on wheels switch, and in response to the determination, switch the system to the flight mode.

4. The system of claim 2, wherein, in flight mode, the first switching valve is configured to direct the gas from the fan stream to one or more active clearance control systems in the turbine stage.

5. The system of claim 2, wherein, in flight mode, the third switching valve is configured to provide the compressed gas to a turbine cooling and leakage air ("TCLA") boost system.

6. The system of claim 2, wherein the controller is configured to progressively switch from the low-flow mode to the flight mode such that the compressed gas from the boost compressor is provided to both the first heat exchanger and the turbine stage of the gas turbine.

7. The system of claim 1, wherein:

the boost compressor is an electrically powered compressor; and

the boost compressor is configured to be powered by one or more of an aircraft battery, a high spool power extraction from the gas turbine, or a low spool power extraction from the gas turbine.

8. The system of claim 1, wherein the first heat exchanger comprises:

a body portion containing one or more channels for passage of a liquid coolant;

a first inlet configured to admit moving gas from the fan stream; and

11

a second inlet configured to admit the compressed gas from the boost compressor.

9. The system of claim 8, wherein the liquid coolant is one or more of water, fuel, or oil.

10. A method comprising:

operating a fan disposed at an intake of a nacelle and a gas turbine contained within a first portion of the nacelle, the gas turbine comprising a compressor stage, a combustor stage, and a turbine stage through which a core stream of gas passes through the fan, the compressor stage, the combustor stage, and the turbine stage;

operating a first heat exchanger disposed in a second portion of the nacelle, wherein a fan stream passes through the second portion of the nacelle;

using a first switching valve to receive gas from the fan stream and to direct the received gas to a second switching valve in an "a" position or to the turbine stage in a "b" position;

using the second switching valve to direct gas to a boost compressor and to receive gas from the first switching valve in an "a" position or from a high pressure bleed from the compressor stage in a "b" position; and

using a third switching valve to receive gas from the boost compressor and to direct compressed gas to the first heat exchanger in an "a" position or to the turbine stage in a "b" position.

11. The method of claim 10, further comprising: switching between a low-flow mode and a flight mode; and

wherein, in the flight mode, the first switching valve is in the "b" position, the second switching valve is in the "b" position, and the third switching valve is in the "b" position.

12. The method of claim 11, further comprising:

switching to the low-flow mode based on a determination of one or more of: an airspeed below a threshold airspeed or an activation of a weight on wheels switch; and

12

switching to the flight mode based on a determination of one or more of: an airspeed above a threshold airspeed or a deactivation of a weight on wheels switch.

13. The method of claim 11, wherein, in flight mode, the first switching valve is configured to direct the gas from the fan stream to one or more active clearance control systems in the turbine stage.

14. The method of claim 11, wherein, in flight mode, the third switching valve is configured to provide the compressed gas to a turbine cooling and leakage air ("TCLA") boost system.

15. The method of claim 11, further comprising:

progressively switching from the low-flow mode to the flight mode such that the compressed gas from the boost compressor is provided to both the first heat exchanger and the turbine stage of the gas turbine.

16. The method of claim 10, wherein:

the boost compressor is an electrically powered compressor; and

the boost compressor is powered by one or more of an aircraft battery, a high spool power extraction from the gas turbine, or a low spool power extraction from the gas turbine.

17. The method of claim 10, wherein the first heat exchanger comprises:

a body portion containing one or more channels for passage of a liquid coolant;

a first inlet configured to admit moving gas from the fan stream; and

a second inlet configured to admit the compressed gas from the boost compressor.

18. The method of claim 17, wherein the liquid coolant is one or more of water, fuel, or oil.

* * * * *