

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412430
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Macaluso; Anthony

Systems and methods for managing a vehicle's energy via a wireless network

Abstract

The disclosure is directed to methods and systems for provisioning mobile electric vehicles with various operational settings data transmitted over the air. A vehicle or its components may operate according to operational settings corresponding to operational settings data included in the vehicle components. A server that is remote to the vehicle may comprise operational settings data and may transmit operational settings data to the vehicle. The server may transmit operational settings data automatically, such as on a periodic basis, in response to a request, such as from a user or from a vehicle component or anytime new or updated operational settings data are available for the vehicle or its components.

Inventors:	Macaluso; Anthony (San Diego, CA)
Applicant:	Macaluso; Anthony (San Diego, CA)
Family ID:	96095522
Appl. No.:	18/395271
Filed:	December 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250209863 A1	Jun. 26, 2025

Publication Classification

Int. Cl.: G07C5/00 (20060101); B60L1/00 (20060101); B60L53/66 (20190101); B60L55/00 (20190101); B60L58/12 (20190101); B60L58/20 (20190101)

U.S. Cl.:

Field of Classification Search**CPC:** G07C (5/008); B60L (58/12)**References Cited****U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1751577	12/1929	Cole	N/A	N/A
2451965	12/1947	Longenecker	N/A	N/A
2660443	12/1952	Miller	N/A	N/A
3859589	12/1974	Rush	N/A	N/A
3891044	12/1974	Tiede	N/A	N/A
3943370	12/1975	Watanabe	N/A	N/A
3961678	12/1975	Hirano et al.	N/A	N/A
3978936	12/1975	Schwartz	N/A	N/A
3990098	12/1975	Mastrangelo	N/A	N/A
4214160	12/1979	Fies et al.	N/A	N/A
4314160	12/1981	Boodman et al.	N/A	N/A
4351405	12/1981	Fields	N/A	N/A
4364448	12/1981	Ikuma	N/A	N/A
4404513	12/1982	Campan	N/A	N/A
4476947	12/1983	Rynbrandt	N/A	N/A
4539496	12/1984	Thomas et al.	N/A	N/A
4579188	12/1985	Facer	N/A	N/A
4602694	12/1985	Weldin	N/A	N/A
5045646	12/1990	Musachio	N/A	N/A
5078227	12/1991	Becker	N/A	N/A
5086857	12/1991	Dale	N/A	N/A
5105776	12/1991	Tsuchiya	N/A	N/A
5316101	12/1993	Gannon	N/A	N/A
5412293	12/1994	Minezawa et al.	N/A	N/A
5491390	12/1995	McGreen	N/A	N/A
5671821	12/1996	McGreen	N/A	N/A
5680907	12/1996	Weihe	N/A	N/A
5710504	12/1997	Pascual et al.	N/A	N/A
5735363	12/1997	Horovitz et al.	N/A	N/A
5767663	12/1997	Lu	N/A	N/A
5921334	12/1998	Al-Dokhi	N/A	N/A
5982152	12/1998	Watanabe	N/A	N/A
5992553	12/1998	Morrison	N/A	N/A
6008626	12/1998	Sato	N/A	N/A
6064178	12/1999	Miller	N/A	N/A
6065557	12/1999	von Keyserling	N/A	N/A
6220381	12/2000	Damron et al.	N/A	N/A
6390215	12/2001	Kodama	N/A	N/A
6502842	12/2002	Ko	N/A	N/A

6531838	12/2002	Parks	N/A	N/A
6703716	12/2003	Chiu	N/A	N/A
6717280	12/2003	Bienville	N/A	N/A
6987327	12/2005	Lucatero	N/A	N/A
7145256	12/2005	Koharcheck	N/A	N/A
7183746	12/2006	Carter	N/A	N/A
7279799	12/2006	McCauley	N/A	N/A
7514803	12/2008	Wilks	N/A	N/A
7547980	12/2008	Harrison	N/A	N/A
7560904	12/2008	Alvarez-Troncoso	N/A	N/A
7628236	12/2008	Brown	N/A	N/A
7667438	12/2009	Ashtiani	N/A	N/A
7753010	12/2009	Rutledge	N/A	N/A
7913783	12/2010	Elmaleh	N/A	N/A
8063609	12/2010	Salasoo et al.	N/A	N/A
8089168	12/2011	Chevrette	N/A	N/A
8206263	12/2011	Tsuchikawa	N/A	N/A
8253359	12/2011	Tanaka	N/A	N/A
8347999	12/2012	Koelsch et al.	N/A	N/A
8573346	12/2012	Duignan	N/A	N/A
8643201	12/2013	Scott	N/A	N/A
8651209	12/2013	Hartjen, III	N/A	N/A
8712620	12/2013	Jackson	N/A	N/A
8723344	12/2013	Dierickx	N/A	N/A
8796987	12/2013	Scheucher	N/A	N/A
8872368	12/2013	Kim et al.	N/A	N/A
8907631	12/2013	Gurries	N/A	N/A
8928281	12/2014	Murase et al.	N/A	N/A
9048513	12/2014	Butzmann	N/A	N/A
9136729	12/2014	Ashinghurst	N/A	N/A
9236761	12/2015	Strothmann	N/A	N/A
9242698	12/2015	Frieden	N/A	N/A
9321357	12/2015	Caldeira et al.	N/A	N/A
9376971	12/2015	Luther et al.	N/A	N/A
9415660	12/2015	Koelsch	N/A	N/A
9457666	12/2015	Caldeira et al.	N/A	N/A
9575743	12/2016	Chun	N/A	G06F 8/654
9656660	12/2016	Baliff	N/A	N/A
9726240	12/2016	David et al.	N/A	N/A
9793833	12/2016	Johnson	N/A	N/A
9816475	12/2016	Buchanan et al.	N/A	N/A
9904948	12/2017	Taira	N/A	N/A
9981553	12/2017	Schafer et al.	N/A	N/A
10077056	12/2017	Fields et al.	N/A	N/A
10077752	12/2017	Lee et al.	N/A	N/A
10157050	12/2017	Kotani et al.	N/A	N/A
10252727	12/2018	Braun	N/A	N/A
10293702	12/2018	Tu et al.	N/A	N/A
10436167	12/2018	Namuduri	N/A	N/A
10513180	12/2018	Quill	N/A	N/A

10586024	12/2019	Patton	N/A	N/A
10664917	12/2019	Wasserman	N/A	N/A
10666077	12/2019	Dharia	N/A	H02J 7/0071
10787089	12/2019	Macaluso	N/A	N/A
10795380	12/2019	Patton	N/A	N/A
10797564	12/2019	Griggs	N/A	N/A
10850713	12/2019	O'Hara	N/A	N/A
10889186	12/2020	Schutt	N/A	N/A
10903679	12/2020	Schmalzrieth et al.	N/A	N/A
11007878	12/2020	Kamino et al.	N/A	N/A
11072254	12/2020	Macaluso	N/A	N/A
11117481	12/2020	Macaluso	N/A	N/A
11130415	12/2020	Macaluso	N/A	N/A
11133729	12/2020	Macaluso	N/A	N/A
11159042	12/2020	Familiant et al.	N/A	N/A
11222750	12/2021	Macaluso	N/A	N/A
11289974	12/2021	Macaluso	N/A	N/A
11299054	12/2021	Macaluso	N/A	N/A
11318856	12/2021	Macaluso	N/A	N/A
11322311	12/2021	Macaluso	N/A	N/A
11362525	12/2021	Feng	N/A	N/A
11368031	12/2021	Griffiths et al.	N/A	N/A
11431225	12/2021	Macaluso	N/A	N/A
11432123	12/2021	Macaluso	N/A	N/A
11458853	12/2021	Macaluso	N/A	N/A
11472306	12/2021	Macaluso	N/A	N/A
11548399	12/2022	Macaluso	N/A	N/A
11551486	12/2022	Everett et al.	N/A	N/A
11577606	12/2022	Macaluso	N/A	N/A
11587740	12/2022	Macaluso	N/A	N/A
11615923	12/2022	Macaluso	N/A	N/A
11618332	12/2022	Macaluso	N/A	N/A
11626775	12/2022	Macaluso	N/A	N/A
11627449	12/2022	Macaluso	N/A	N/A
11628724	12/2022	Macaluso	N/A	N/A
11641572	12/2022	Macaluso	N/A	N/A
11685276	12/2022	Macaluso	N/A	N/A
11722869	12/2022	Macaluso	N/A	N/A
11738641	12/2022	Macaluso	N/A	N/A
11757332	12/2022	Macaluso	N/A	N/A
11780466	12/2022	Shah	N/A	N/A
11785433	12/2022	Macaluso	N/A	N/A
11837411	12/2022	Macaluso	N/A	N/A
11850963	12/2022	Macaluso	N/A	N/A
11897355	12/2023	Macaluso	N/A	N/A
11897506	12/2023	Shah	N/A	N/A
11904708	12/2023	Macaluso	N/A	N/A
11916466	12/2023	Macaluso	N/A	N/A
11919387	12/2023	Macaluso	N/A	N/A
11919412	12/2023	Macaluso	N/A	N/A

11919413	12/2023	Macaluso	N/A	N/A
11938825	12/2023	Sukhatankar et al.	N/A	N/A
11955875	12/2023	Macaluso	N/A	N/A
11970073	12/2023	Macaluso	N/A	N/A
11985579	12/2023	Macaluso	N/A	N/A
11999250	12/2023	Macaluso	N/A	N/A
12003167	12/2023	Macaluso	N/A	N/A
12103416	12/2023	Macaluso	N/A	N/A
12157366	12/2023	Macaluso	N/A	N/A
2003/0071464	12/2002	Chiu	N/A	N/A
2003/0139859	12/2002	Hanada	N/A	N/A
2003/0184258	12/2002	VonderHaar	N/A	N/A
2003/0222502	12/2002	Takahashi	N/A	N/A
2004/0012205	12/2003	Sua-An	N/A	N/A
2004/0245783	12/2003	Gilbreth	N/A	N/A
2004/0257043	12/2003	Takaoka	N/A	N/A
2004/0262062	12/2003	Berberi et al.	N/A	N/A
2005/0093370	12/2004	Amano et al.	N/A	N/A
2005/0224263	12/2004	Vasilantone	N/A	N/A
2005/0284676	12/2004	King	N/A	N/A
2006/0091857	12/2005	Nakanishi	N/A	N/A
2006/0238258	12/2005	D'Amore	N/A	N/A
2006/0250902	12/2005	Bender	N/A	N/A
2007/0013244	12/2006	Kinkaid	N/A	N/A
2007/0024266	12/2006	Yurgil	N/A	N/A
2007/0075677	12/2006	Alvarez-Troncoso	N/A	N/A
2007/0090702	12/2006	Schiller	N/A	N/A
2007/0164693	12/2006	King	N/A	N/A
2007/0187957	12/2006	Harrison	N/A	N/A
2007/0208468	12/2006	Sankaran et al.	N/A	N/A
2008/0053716	12/2007	Scheucher	N/A	N/A
2008/0066979	12/2007	Carter	N/A	N/A
2008/0215700	12/2007	Pillar et al.	N/A	N/A
2008/0223637	12/2007	Bartilson	N/A	N/A
2008/0281663	12/2007	Hakim	N/A	N/A
2008/0289890	12/2007	Stoltzfus	N/A	N/A
2008/0297109	12/2007	Sandberg et al.	N/A	N/A
2009/0033254	12/2008	Nagashima et al.	N/A	N/A
2009/0079417	12/2008	Mort et al.	N/A	N/A
2009/0145674	12/2008	Lee	N/A	N/A
2009/0168305	12/2008	Fleig et al.	N/A	N/A
2009/0194998	12/2008	Lin	N/A	N/A
2009/0206779	12/2008	Wobben	N/A	N/A
2009/0230766	12/2008	Miyama	N/A	N/A
2009/0250276	12/2008	Goodwin et al.	N/A	N/A
2009/0256450	12/2008	Chevrette	N/A	N/A
2009/0261787	12/2008	Cegnar	N/A	N/A
2009/0295224	12/2008	Kobayashi	N/A	N/A
2010/0001866	12/2009	Ichikawa	N/A	N/A
2010/0019718	12/2009	Salasoo et al.	N/A	N/A

2010/0076825	12/2009	Sato	N/A	N/A
2010/0116574	12/2009	Gilmore	N/A	N/A
2010/0117600	12/2009	Fazakas	N/A	N/A
2010/0164334	12/2009	Schiller	N/A	N/A
2010/0168945	12/2009	Ohno	N/A	N/A
2010/0222952	12/2009	Yamaguchi	N/A	N/A
2010/0270810	12/2009	Liebermann et al.	N/A	N/A
2010/0327600	12/2009	Koelsch	N/A	N/A
2011/0012560	12/2010	Sakakibara et al.	N/A	N/A
2011/0014501	12/2010	Scheucher	N/A	N/A
2011/0025068	12/2010	Campbell	N/A	N/A
2011/0083918	12/2010	Kshatriya	N/A	N/A
2011/0089760	12/2010	Castelaz et al.	N/A	N/A
2011/0100735	12/2010	Flett	N/A	N/A
2011/0106329	12/2010	Donnelly et al.	N/A	N/A
2011/0140518	12/2010	Hattori	N/A	N/A
2011/0163717	12/2010	Gale	N/A	N/A
2011/0167455	12/2010	Gao	725/50	H04H 60/73
2011/0189507	12/2010	Reis	N/A	N/A
2011/0200193	12/2010	Blitz et al.	N/A	N/A
2011/0231044	12/2010	Fassnacht	N/A	N/A
2011/0302078	12/2010	Failing	N/A	N/A
2011/0320074	12/2010	Erlston et al.	N/A	N/A
2012/0012406	12/2011	Stoicoviciu	N/A	N/A
2012/0037438	12/2011	Schultz	N/A	N/A
2012/0054095	12/2011	Lesandro et al.	N/A	N/A
2012/0068537	12/2011	Hintz et al.	N/A	N/A
2012/0129577	12/2011	Vaknin	N/A	N/A
2012/0139487	12/2011	Kim	N/A	N/A
2012/0237799	12/2011	Jiang	N/A	N/A
2012/0309455	12/2011	Klose et al.	N/A	N/A
2012/0330486	12/2011	Jingu	N/A	N/A
2013/0015668	12/2012	Chang et al.	N/A	N/A
2013/0049459	12/2012	Hatanaka	N/A	N/A
2013/0067253	12/2012	Tsuda	N/A	N/A
2013/0081886	12/2012	Jaberian	N/A	N/A
2013/0091033	12/2012	Goodman	N/A	N/A
2013/0096759	12/2012	Breton et al.	N/A	N/A
2013/0119665	12/2012	Berberi	N/A	N/A
2013/0257144	12/2012	Caldeira et al.	N/A	N/A
2013/0257145	12/2012	Caldeira et al.	N/A	N/A
2013/0261907	12/2012	McQuade	N/A	N/A
2013/0266826	12/2012	Cowperthwaite	N/A	N/A
2013/0307479	12/2012	Kim	N/A	N/A
2013/0332014	12/2012	Jackson	N/A	N/A
2014/0001905	12/2013	Schawitsch	N/A	N/A
2014/0091573	12/2013	Berberi	N/A	N/A
2014/0132063	12/2013	Kakiuchi	N/A	N/A
2014/0132155	12/2013	Strothmann	N/A	N/A
2014/0197780	12/2013	Imamura	N/A	N/A

2014/0210398	12/2013	Powell	N/A	N/A
2014/0244082	12/2013	Caron	N/A	N/A
2014/0266004	12/2013	Andrews, Jr.	N/A	N/A
2014/0266070	12/2013	Kurtzman	N/A	N/A
2014/0283092	12/2013	Mowatt et al.	N/A	N/A
2014/0285209	12/2013	Stichowski et al.	N/A	N/A
2014/0350764	12/2013	Arai et al.	N/A	N/A
2014/0368041	12/2013	Tu et al.	N/A	N/A
2015/0008867	12/2014	Smychkovich	N/A	N/A
2015/0014991	12/2014	Al Jaeedi et al.	N/A	N/A
2015/0054428	12/2014	Osborne	N/A	N/A
2015/0089981	12/2014	Renfro	N/A	N/A
2015/0210287	12/2014	Penilla et al.	N/A	N/A
2015/0222553	12/2014	Macdonald et al.	N/A	N/A
2015/0249362	12/2014	Bridgelall et al.	N/A	N/A
2015/0260835	12/2014	Widmer et al.	N/A	N/A
2015/0262154	12/2014	Wolfson	N/A	N/A
2015/0343909	12/2014	Hikiri	N/A	N/A
2015/0346233	12/2014	Slepov	N/A	N/A
2015/0347121	12/2014	Harumoto	N/A	N/A
2015/0363855	12/2014	Wu et al.	N/A	N/A
2016/0034952	12/2015	Parkin et al.	N/A	N/A
2016/0071338	12/2015	McQuade et al.	N/A	N/A
2016/0089981	12/2015	Kodawara	N/A	N/A
2016/0105020	12/2015	Guo	N/A	N/A
2016/0111907	12/2015	Lynds	N/A	N/A
2016/0144720	12/2015	Nakabayashi	N/A	N/A
2016/0164373	12/2015	Liao et al.	N/A	N/A
2016/0185243	12/2015	Zhou	N/A	N/A
2016/0189311	12/2015	Erickson et al.	N/A	N/A
2016/0207418	12/2015	Bergstrom	N/A	N/A
2016/0236578	12/2015	Liao	N/A	N/A
2016/0243960	12/2015	Wood	N/A	N/A
2016/0297317	12/2015	Huang et al.	N/A	N/A
2016/0298589	12/2015	Setterberg	N/A	N/A
2016/0348788	12/2015	Lemmers	N/A	N/A
2017/0036551	12/2016	Wu	N/A	N/A
2017/0063124	12/2016	Yu et al.	N/A	N/A
2017/0077534	12/2016	Guidry et al.	N/A	N/A
2017/0086084	12/2016	Jarvis	N/A	H04M 3/2236
2017/0117720	12/2016	Yung	N/A	N/A
2017/0131999	12/2016	Dolby et al.	N/A	N/A
2017/0142766	12/2016	Kim	N/A	N/A
2017/0176540	12/2016	Omi	N/A	N/A
2017/0190261	12/2016	Cheng	N/A	N/A
2017/0191459	12/2016	Zhang	N/A	N/A
2017/0217442	12/2016	Rios, III	N/A	N/A
2017/0259764	12/2016	Da Silva Carvalho	N/A	N/A
2017/0302094	12/2016	Lynds	N/A	N/A
2017/0305424	12/2016	Augst	N/A	N/A

2017/0363433	12/2016	Tennent et al.	N/A	N/A
2017/0366017	12/2016	Clay et al.	N/A	N/A
2017/0366112	12/2016	Zhou	N/A	N/A
2018/0009329	12/2017	Tellez	N/A	N/A
2018/0012196	12/2017	Ricci	N/A	N/A
2018/0062555	12/2017	Sagawa	N/A	N/A
2018/0083469	12/2017	Bauer et al.	N/A	N/A
2018/0126866	12/2017	Nozawa	N/A	N/A
2018/0154779	12/2017	Chol	N/A	N/A
2018/0156144	12/2017	Inoue	N/A	N/A
2018/0166750	12/2017	Chang	N/A	N/A
2018/0189049	12/2017	Madrid	N/A	N/A
2018/0198846	12/2017	Srinivasan	N/A	N/A
2018/0204173	12/2017	Painter et al.	N/A	N/A
2018/0204253	12/2017	Painter et al.	N/A	N/A
2018/0204281	12/2017	Painter et al.	N/A	N/A
2018/0205242	12/2017	Kelly-Morgan et al.	N/A	N/A
2018/0215272	12/2017	Vitullo et al.	N/A	N/A
2018/0254732	12/2017	Smolenaers	N/A	N/A
2018/0312159	12/2017	Jent, II	N/A	N/A
2018/0328745	12/2017	Nagy et al.	N/A	N/A
2018/0351397	12/2017	Aharoni	N/A	N/A
2018/0370537	12/2017	Wu	N/A	N/A
2019/0001804	12/2018	Wilhide	N/A	N/A
2019/0004580	12/2018	Wilhide	N/A	N/A
2019/0044359	12/2018	Gordon et al.	N/A	N/A
2019/0077254	12/2018	Stanley	N/A	N/A
2019/0081502	12/2018	Botts	N/A	N/A
2019/0103639	12/2018	Guglielmo et al.	N/A	N/A
2019/0138952	12/2018	Han	N/A	N/A
2019/0140245	12/2018	Mensch	N/A	N/A
2019/0176802	12/2018	Kim	N/A	N/A
2019/0184843	12/2018	Jung et al.	N/A	N/A
2019/0199104	12/2018	Shim	N/A	N/A
2019/0202429	12/2018	Richter	N/A	N/A
2019/0212997	12/2018	Sangameswaran et al.	N/A	N/A
2019/0215376	12/2018	Kang	N/A	N/A
2019/0217720	12/2018	Treharne et al.	N/A	N/A
2019/0245375	12/2018	Schmalzrieth et al.	N/A	N/A
2019/0263385	12/2018	Zhou	N/A	N/A
2019/0292973	12/2018	Jiang et al.	N/A	N/A
2019/0296541	12/2018	Mensch	N/A	N/A
2019/0308510	12/2018	Beaurepaire	N/A	N/A
2019/0329650	12/2018	Quill	N/A	N/A
2019/0351895	12/2018	Ben-Ari	N/A	N/A
2019/0351899	12/2018	Adam	N/A	N/A
2019/0351948	12/2018	Derissaint	N/A	N/A
2019/0353710	12/2018	Rocci	N/A	N/A
2019/0359080	12/2018	Hellgren	N/A	N/A
2019/0362922	12/2018	Bae et al.	N/A	N/A

2019/0383627	12/2018	Nangeroni et al.	N/A	N/A
2020/0006716	12/2019	Wagoner	N/A	N/A
2020/0039379	12/2019	Schlosser	N/A	N/A
2020/0062138	12/2019	Smolenaers	N/A	N/A
2020/0063640	12/2019	Lee	N/A	N/A
2020/0094695	12/2019	Bowman	N/A	N/A
2020/0101858	12/2019	Kuroda	N/A	N/A
2020/0136414	12/2019	Patsos	N/A	N/A
2020/0153351	12/2019	Jiao	N/A	N/A
2020/0174780	12/2019	Gintz	N/A	N/A
2020/0184591	12/2019	Balu et al.	N/A	N/A
2020/0186620	12/2019	Golgiri et al.	N/A	N/A
2020/0202645	12/2019	Gintz	N/A	N/A
2020/0203986	12/2019	Barreau	N/A	N/A
2020/0204702	12/2019	Park	N/A	N/A
2020/0207209	12/2019	Engel	N/A	N/A
2020/0226850	12/2019	Bower	N/A	N/A
2020/0238929	12/2019	Wippler	N/A	N/A
2020/0241555	12/2019	Dogishi	N/A	N/A
2020/0244088	12/2019	Will et al.	N/A	N/A
2020/0249822	12/2019	Penilla	N/A	N/A
2020/0258325	12/2019	Maria	N/A	N/A
2020/0265480	12/2019	Swinson	N/A	N/A
2020/0276904	12/2019	Deaton	N/A	N/A
2020/0277021	12/2019	Biderman	N/A	N/A
2020/0294401	12/2019	Kerecsen	N/A	G07C 5/008
2020/0295412	12/2019	Chen	N/A	N/A
2020/0324763	12/2019	Switkes et al.	N/A	N/A
2020/0353839	12/2019	Tarchinski et al.	N/A	N/A
2020/0353882	12/2019	Beiser	N/A	N/A
2020/0376967	12/2019	Furukawa	N/A	B60L 50/40
2020/0381784	12/2019	Yamamoto	N/A	N/A
2020/0384879	12/2019	Ebisu et al.	N/A	N/A
2021/0001737	12/2020	Hoess et al.	N/A	N/A
2021/0065073	12/2020	Maeda et al.	N/A	N/A
2021/0080943	12/2020	Iwamoto et al.	N/A	N/A
2021/0094433	12/2020	Badger, II	N/A	N/A
2021/0110323	12/2020	Munoz et al.	N/A	N/A
2021/0157571	12/2020	Ogawa	N/A	N/A
2021/0167988	12/2020	Harata et al.	N/A	N/A
2021/0173411	12/2020	Rao et al.	N/A	N/A
2021/0173635	12/2020	Shin	N/A	G01R 31/3647
2021/0183175	12/2020	Dunger	N/A	N/A
2021/0188101	12/2020	Abu Qahouq et al.	N/A	N/A
2021/0188115	12/2020	Kazuno	N/A	N/A
2021/0197687	12/2020	Searcy	N/A	N/A
2021/0201599	12/2020	Shionoya	N/A	N/A
2021/0213952	12/2020	Willison	N/A	N/A
2021/0229687	12/2020	Hashimoto et al.	N/A	N/A
2021/0284043	12/2020	Wang et al.	N/A	N/A

2021/0288506	12/2020	Tanaka	N/A	N/A
2021/0312544	12/2020	Inoue et al.	N/A	N/A
2021/0334913	12/2020	Klein	N/A	N/A
2021/0342896	12/2020	Swinson	N/A	N/A
2021/0347225	12/2020	Johnson et al.	N/A	N/A
2021/0405996	12/2020	Takatsuna et al.	N/A	N/A
2022/0016941	12/2021	Sams	N/A	N/A
2022/0028627	12/2021	Macaluso	N/A	N/A
2022/0050143	12/2021	Maeda et al.	N/A	N/A
2022/0052582	12/2021	Giannotta	N/A	N/A
2022/0105793	12/2021	Sukhatankar	N/A	N/A
2022/0109314	12/2021	Pena	N/A	N/A
2022/0111758	12/2021	Ijaz et al.	N/A	N/A
2022/0144258	12/2021	Lind	N/A	B60W 30/0953
2022/0179641	12/2021	Harata et al.	N/A	N/A
2022/0179644	12/2021	Harata et al.	N/A	N/A
2022/0204012	12/2021	Ko	N/A	H04L 67/535
2022/0212638	12/2021	Georgeson	N/A	N/A
2022/0229446	12/2021	Switkes	N/A	G08G 1/0129
2022/0247201	12/2021	Chen	N/A	N/A
2022/0253301	12/2021	Harata et al.	N/A	N/A
2022/0261836	12/2021	Kimomura et al.	N/A	N/A
2022/0270177	12/2021	Chintakindi	N/A	N/A
2022/0301775	12/2021	Macaluso	N/A	N/A
2022/0314837	12/2021	Gupta	N/A	N/A
2022/0328271	12/2021	Patwardhan et al.	N/A	N/A
2022/0329019	12/2021	Lanjekar et al.	N/A	N/A
2022/0334818	12/2021	McFarland	N/A	N/A
2022/0334822	12/2021	Sakakibara	N/A	G06F 8/65
2022/0340035	12/2021	Kim et al.	N/A	N/A
2022/0374027	12/2021	Watts et al.	N/A	N/A
2022/0399581	12/2021	Wood	N/A	N/A
2022/0402390	12/2021	Smolenaers	N/A	N/A
2022/0402399	12/2021	Staats	N/A	N/A
2023/0005305	12/2022	Sakurai et al.	N/A	N/A
2023/0038222	12/2022	Howell	N/A	N/A
2023/0068432	12/2022	Upadhyay et al.	N/A	N/A
2023/0104789	12/2022	Inui	701/22	B60L 58/16
2023/0123166	12/2022	Deighton	N/A	N/A
2023/0130832	12/2022	Dunn	320/109	H02J 7/0048
2023/0142500	12/2022	Marzoughi et al.	N/A	N/A
2023/0154692	12/2022	Macaluso	N/A	N/A
2023/0155401	12/2022	Kuranuki et al.	N/A	N/A
2023/0171574	12/2022	Macaluso	N/A	N/A
2023/0187145	12/2022	Macaluso	N/A	N/A
2023/0187757	12/2022	Pouyadou	N/A	N/A
2023/0261509	12/2022	Dalal et al.	N/A	N/A
2023/0302962	12/2022	Couture et al.	N/A	N/A
2024/0087810	12/2023	Macaluso	N/A	N/A
2024/0109442	12/2023	Macaluso	N/A	N/A

2024/0174107	12/2023	Macaluso	N/A	N/A
2024/0178722	12/2023	Macaluso	N/A	N/A
2024/0208326	12/2023	Macaluso	N/A	N/A
2024/0258823	12/2023	Macaluso	N/A	N/A
2024/0258824	12/2023	Macaluso	N/A	N/A
2024/0259773	12/2023	Macaluso	N/A	N/A
2024/0322647	12/2023	Macaluso	N/A	N/A
2024/0367512	12/2023	Macaluso	N/A	N/A
2024/0406695	12/2023	Macaluso	N/A	N/A
2025/0010741	12/2024	Macaluso	N/A	N/A
2025/0196632	12/2024	Macaluso	N/A	N/A
2025/0201950	12/2024	Macaluso	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019025	12/1989	CA	N/A
202100372	12/2021	CH	N/A
202294336	12/2011	CN	N/A
102963263	12/2012	CN	N/A
108473063	12/2012	CN	N/A
104732790	12/2014	CN	N/A
106846153	12/2016	CN	N/A
107117038	12/2016	CN	N/A
108539841	12/2017	CN	N/A
108599384	12/2017	CN	N/A
109976778	12/2018	CN	N/A
110549902	12/2018	CN	N/A
110633815	12/2018	CN	N/A
107804326	12/2019	CN	N/A
110795138	12/2019	CN	N/A
110889601	12/2019	CN	N/A
111932337	12/2019	CN	N/A
111954615	12/2019	CN	N/A
112977043	12/2020	CN	N/A
113479111	12/2020	CN	N/A
215398141	12/2021	CN	N/A
102017008723	12/2017	DE	N/A
102019220366	12/2020	DE	N/A
102011018457	12/2021	DE	N/A
1 253 698	12/2001	EP	N/A
3 246 776	12/2019	EP	N/A
2 681 512	12/2020	EP	N/A
2880816	12/2020	ES	N/A
2325201	12/1997	GB	N/A
2511831	12/2013	GB	N/A
2585496	12/2020	GB	N/A
2002-257026	12/2001	JP	N/A
2003-278633	12/2002	JP	N/A
2011-132873	12/2010	JP	N/A
2015-027164	12/2014	JP	N/A

2016-170600	12/2015	JP	N/A
6687274	12/2019	JP	N/A
6898339	12/2020	JP	N/A
2020-0020016	12/2019	KR	N/A
102266609	12/2020	KR	N/A
WO 09/149769	12/2008	WO	N/A
WO 10/133863	12/2009	WO	N/A
WO 11/078748	12/2010	WO	N/A
WO 11/148531	12/2010	WO	N/A
WO 17/030354	12/2016	WO	N/A
WO 17/057528	12/2016	WO	N/A
WO 17/143079	12/2016	WO	N/A
WO 17/213079	12/2016	WO	N/A
WO 18/046979	12/2017	WO	N/A
WO 18/083279	12/2017	WO	N/A
WO 19/034169	12/2018	WO	N/A
WO 19/117894	12/2018	WO	N/A
WO 19/145777	12/2018	WO	N/A
WO 19/219997	12/2018	WO	N/A
WO 19/240783	12/2018	WO	N/A
WO 20/170233	12/2019	WO	N/A
WO 20/191367	12/2019	WO	N/A
WO 21/187071	12/2020	WO	N/A
WO 22/015017	12/2021	WO	N/A
WO 22/132807	12/2021	WO	N/A
WO 22/219510	12/2021	WO	N/A
WO 23/160878	12/2022	WO	N/A
WO 24/002525	12/2023	WO	N/A

Primary Examiner: Oh; Harry Y

Attorney, Agent or Firm: Knobbe, Martens, Olson & Bear, LLP

Background/Summary

FIELD OF THE DISCLOSURE

(1) The present disclosure relates to over-the-air provisioning of electric vehicle operational settings.

BACKGROUND

(2) Electric vehicles often include devices and components necessary or desirable for operation such as for the generation, management, storage and consumption of energy. Electric vehicle components and devices can include batteries and battery management systems. The devices and components of electric vehicles may operate in a variety of manners, according to a variety of settings, for example manufacturing settings. The operational settings of various electric vehicle devices and components are often static. Thus, changing, updating or altering an electric vehicle's operational settings can be challenging if not impossible, for example, requiring the purchase and installation of new, replacement and/or additional components in order to effectuate different operational settings. Furthermore, the operational settings of a vehicle's components may not allow

the components to function with other components having different operational settings. This may limit the options of available components that may be used in a vehicle, for example making it difficult or impossible to replace an original vehicle battery with a battery from a different manufacturer. As such, systems and methods to allow for the simple, efficient and quick updating and/or altering of electric vehicle operational settings are desirable.

SUMMARY

(3) Various embodiments of systems, methods and devices within the scope of the appended claims each have several aspects, no single one of which is solely responsible for the desirable attributes described herein. Without limiting the scope of the appended claims, the description below describes some prominent features.

(4) Details of one or more embodiments of the subject matter described in this specification are set forth in the accompanying drawings and the description below. Other features, aspects, and advantages will become apparent from the description, the drawings, and the claims. Note that relative dimensions of the following figures may not be drawn to scale.

(5) A computer system can communicate vehicle data and can comprise: one or more hardware computer processors configured to execute a plurality of computer executable instructions to cause the computer system to: access data relating to a vehicle operational status, wherein the data includes at least an energy status of one or more energy storage devices of the vehicle; access third party rules associated with a third party, wherein the third party rules indicate a portion of the data to communicate to the third party; prepare a dataset according to the third party rules including the portion of the data; and communicate the dataset to the third party associated with the third party rules.

(6) In some implementations, the third-party rules further indicate a data format, and the one or more hardware computer processors are further configured to execute the plurality of computer executable instructions to cause the computer system to update a format of the dataset according to the data format indicated by the third-party rules.

(7) In some implementations, updating the format of the dataset includes updating the dataset with metadata.

(8) In some implementations, updating the format of the dataset includes obfuscating the dataset.

(9) In some implementations, updating the format of the dataset includes supplementing the dataset with additional data.

(10) In some implementations, the third-party rules indicate when to communicate the dataset to the third party, and the one or more hardware computer processors are further configured to execute the plurality of computer executable instructions to cause the computer system to communicate the dataset to the third party according to when the third-party rules indicate to communicate the dataset.

(11) In some implementations, the third-party rules further indicate a time to communicate the dataset to the third party.

(12) In some implementations, the third-party rules further indicate a schedule to communicate the dataset to the third party.

(13) In some implementations, the third-party rules further indicate conditions under which to communicate the dataset to the third party.

(14) In some implementations, the computer system is remote to the vehicle.

(15) In some implementations, the computer system is disposed within the vehicle.

(16) In some implementations, the data further includes a status of an on-board power generation system of the vehicle including an energy generation status of the on-board power generation system.

(17) In some implementations, the data further includes a status of a driven mass of the vehicle.

(18) In some implementations, the data further includes a status of an electrical switch in communication with the one or more energy storage devices.

- (19) In some implementations, the data further includes an estimated remaining operating time of the one or more energy storage devices of the vehicle and an estimated remaining operating distance of the one or more energy storage devices of the vehicle.
- (20) In some implementations, the data further includes a geographic location of the vehicle and a geographic location of a destination.
- (21) In some implementations, the data further includes a distance travelled by the vehicle.
- (22) In some implementations, the one or more energy storage devices of the vehicle include a battery and a capacitor.
- (23) A computer-implemented method can comprise: accessing data relating to a vehicle operational status; wherein the data includes at least an energy status of one or more energy storage devices of the vehicle; accessing third-party rules associated with a third party; wherein the third party rules indicate a portion of the data to communicate to the third party; preparing a dataset according to the third party rules including the portion of the data; and communicating the dataset to the third party associated with the third-party rules.
- (24) Non-transitory computer-readable media can include computer-executable instructions that, when executed by a computing system, cause the computing system to perform operations comprising: accessing data relating to a vehicle operational status, wherein the data includes at least an energy status of one or more energy storage devices of the vehicle; accessing third party rules associated with a third party, wherein the third party rules indicate a portion of the data to communicate to the third party; preparing a dataset according to the third-party rules including the portion of the data; and communicating the dataset to the third party associated with the third-party rules.
- (25) The present disclosure provides a system for over-the-air provisioning of a vehicle's operational settings. The system may include, for example, a server, remote to the vehicle, and including operational settings data. The server may be configured to: receive a request for operational settings data; and in response to receiving said request, transmit operational settings data to the vehicle; and one or more components of the vehicle configured to operate according to one or more operational settings. The one or more components may include a transceiver configured to communicate wirelessly with the server to send requests to the server and to receive operational settings data from the server; a memory including executable software instructions, the memory configured to update the instructions in response to receiving operational settings data from the server; and a processor configured to execute the software instructions to cause the component to function according to the one or more operational settings corresponding to the operational settings data received from the server.
- (26) In some embodiments, the server may be configured to receive the request for operational settings data from a user or from the vehicle.
- (27) In some embodiments, the server is further configured to: receive a request from a user for operational settings options; and in response to receiving said request, transmit operational settings options to the user.
- (28) In some embodiments, the one or more components of the vehicle include one or more of an energy storage device, an energy generation system, a vehicle management system, a motor or a component interface device.
- (29) In some embodiments, the server is configured to, in response to receiving, at the server, the request for operational settings data, determine whether operational settings data are available.
- (30) In some embodiments, the server is configured to, in response to receiving, at the server, the request for operational settings data, determine a status of current operational settings data of the vehicle.
- (31) In some embodiments, the system may further include a third-party server remote to the vehicle and remote to the server. The third-party server may include operational settings data and the server configured to communicate wirelessly with the third-party server to send and receive

data.

(32) In some embodiments, the server is configured to record download event information to a history log.

(33) The present disclosure provides a method for over-the-air provisioning of a vehicle's operational settings. The method may include, for example, receiving, at a server remote to the vehicle, a request for operational settings data; in response to receiving said request, transmitting operational settings data from the server to the vehicle; receiving, at a component of the vehicle, the operational settings data; storing, in a memory of the component, the operational settings data, the operational settings data including executable software instructions; and executing, at a processor of the component, the executable software instructions of the operational settings data to cause the component to operate according to an operational setting corresponding to the operational settings data.

(34) In some implementations, receiving the request for operational settings data at the server includes receiving the request from the vehicle or a user.

(35) In some implementations, the method can further include receiving, at the server, a first request from a user for operational settings options; and in response to receiving said first request, transmitting to the user, operational settings options from the server to the user.

(36) In some implementations, the method can further include in response to receiving, at the server, the request for operational settings data, determining whether operational settings data are available.

(37) In some implementations, the method can further include in response to receiving, at the server, the request for operational settings data, determining a status of current operational settings data of the vehicle.

(38) In some implementations, determining the status of the operational settings data of the vehicle includes querying the vehicle for data relating to its current operational settings data; determining operational settings data that are accessible to the server and available for the vehicle; and comparing the operational settings data accessible to the server with the current operational settings data of the vehicle.

(39) In some implementations, determining the status of the operational settings data of the vehicle includes accessing a history log of download event information to determine the current operational settings data of the vehicle; determining operational settings data that are accessible to the server and available for the vehicle; and comparing the operational settings data accessible to the server with the current operational settings data of the vehicle.

(40) The present disclosure provides a method for over-the-air provisioning of a vehicle's operational settings. The method can include, for example, detecting, by a first component of the vehicle, a second component of the vehicle; determining, by the first component, an operational incompatibility between the first and second components; transmitting, by the first component, a request for operational settings data to a server remote to the vehicle; receiving, from the server, operational settings data at the first component; updating executable software instructions of the first component according to the operational settings data; and executing the updated executable software instructions to cause the first component to operate according to an operational setting corresponding to the operational settings data to render the first component compatible with the second component.

(41) In some implementations, the first component of the vehicle includes one or more of an energy storage device, an energy generation system, a vehicle management system, a motor or a component interface device.

(42) In some implementations, the method can further include in response to receiving, at the server, the request for operational settings data, determining, by the server, whether operational settings data are available.

(43) In some implementations, the method can further include in response to receiving, at the

server, the request for operational settings data, determining, by the server, a status of current operational settings data of the vehicle.

(44) In some implementations, determining the status of the operational settings data of the vehicle includes querying the vehicle for data relating to its current operational settings data; determining operational settings data that are accessible to the server and available for the vehicle; and comparing the operational settings data accessible to the server with the current operational settings data of the vehicle.

(45) The present disclosure provides a system for over-the-air provisioning of a vehicle's operational settings. The system can include, for example, a roller configured to contact a wheel of the vehicle, the roller configured to rotate in response to a rotation of the wheel when the roller is in contact with the wheel; an actuator configured to apply a first force to the roller to cause the roller to contact the wheel of the vehicle with a second force; a generator rotatably coupled with the roller and configured to generate an electrical output in response to a rotation of the roller; and an interface device in communication with the actuator. The interface device may include a transceiver configured to communicate wirelessly with a remote server to receive operational settings data from the server; a memory including executable software instructions and configured to update the software instructions in response to receiving operational settings data from the server; and a processor configured to execute the software instructions to cause the actuator to operate according to the operational settings data received from the server.

(46) In some embodiments, the operational settings data includes operational settings for adjusting the first force, and the actuator can be configured to adjust the first force applied to the roller according to the operational settings data.

(47) In some embodiments, the operational settings include conditions for adjusting the first force, and the conditions can include an air pressure of the wheel, a vertical motion of the wheel, a velocity of the vehicle, a rotational velocity of the wheel, an acceleration of the vehicle, or an amount of electrical output generated at the generator.

(48) In some embodiments, the actuator is configured to increase, according to the operational settings data, the first force applied to the roller in response to a vertical motion of the wheel exceeding a threshold.

(49) In some embodiments, the actuator is configured to increase, according to the operational settings data, the first force applied to the roller in response to an air pressure of the wheel falling below a threshold.

(50) In some embodiments, the actuator is configured to increase, according to the operational settings data, the first force applied to the roller in response to an electrical output of the generator falling below a threshold.

(51) In some embodiments, the operational settings data includes operational settings for changing a position of the roller, and the actuator can be configured to change the position of the roller according to the operational settings data.

(52) In some embodiments, the operational settings include conditions for adjusting the position of the roller, and the conditions can include an air pressure of the wheel, a vertical motion of the wheel, a velocity of the vehicle, a rotational velocity of the wheel, an acceleration of the vehicle, or an amount of electrical output generated at the generator.

(53) In some embodiments, the roller positions include an extended position in which the roller is in contact with the wheel, and a retracted position in which the roller is a distance from the wheel.

(54) In some embodiments, the actuator is configured to transition the roller, according to the operational settings data, to a retracted position in response to a vertical motion of the wheel exceeding a threshold.

(55) In some embodiments, the actuator is configured to transition the roller, according to the operational settings data, to a retracted position in response to an air pressure of the wheel falling below a threshold.

(56) In some embodiments, the actuator is configured to transition the roller, according to the operational settings data, to a retracted position in response to an electrical output of the generator falling below a threshold.

(57) In some embodiments, the actuator applies the first force to the roller via one or more of a flexible arm, a mechanical spring, a gas spring, a piston, a suspension system, a shaft, a strut, hydraulics, pneumatics, a lever, a gear, or a pulley.

(58) The present disclosure provides a method for over-the-air provisioning of a vehicle's operational settings. The method can include, for example, rotating a roller in response to a rotation of a wheel of the vehicle when the roller is in contact with the wheel; applying, via an actuator, a first force to the roller to cause the roller to contact the wheel of the vehicle with a second force; generating, via a generator rotatably coupled with the roller, an electrical output in response to a rotation of the roller; receiving, at an interface device of the vehicle, operational settings data from a remote server; storing, in a memory of the interface device, the operational settings data, the operational settings data including executable software instructions; and executing, at a processor of the interface device, the executable software instructions of the operational settings data to cause the actuator to operate according to the operational settings data received from the server.

(59) In some implementations, the operational settings data includes operational settings for adjusting the first force, and the method can further include adjusting, via the actuator, the first force applied to the roller according to the operational settings data.

(60) In some implementations, the operational settings include conditions for adjusting the first force, and the conditions can include an air pressure of the wheel, a vertical motion of the wheel, a velocity of the vehicle, a rotational velocity of the wheel, an acceleration of the vehicle, or an amount of electrical output generated at the generator.

(61) In some implementations, the operational settings data includes operational settings for changing a position of the roller, the method can further include changing, via the actuator, the position of the roller according to the operational settings data.

(62) In some implementations, the operational settings include conditions for adjusting the position of the roller, and the conditions can include an air pressure of the wheel, a vertical motion of the wheel, a velocity of the vehicle, a rotational velocity of the wheel, an acceleration of the vehicle, or an amount of electrical output generated at the generator.

(63) In some implementations, the roller positions include an extended position in which the roller is in contact with the wheel, and a retracted position in which the roller is a distance from the wheel.

(64) The present disclosure provides a device for over-the-air provisioning of a vehicle's operational settings. The device can include, for example, a transceiver configured to communicate wirelessly with a remote server to receive operational settings data from the server; a memory including executable software instructions and configured to update the software instructions in response to receiving operational settings data from the server; and a processor configured to execute the software instructions to cause an actuator to operate according to the operational settings data received from the server. The actuator can be configured to apply a first force, according to the operational settings data, to a roller to cause the roller to contact a wheel of the vehicle with a second force. The roller can be configured to rotate in response to a rotation of the wheel when the roller is in contact with the wheel. The actuator can be configured to transition the roller, according to the operational settings data, from a first position to a second position.

(65) In some implementations, the operational settings data includes one or more conditions for adjusting the first force, and the processor can be further configured to execute the updated software instructions to cause the actuator to adjust the first force applied to the roller according to the one or more conditions of the operational settings data.

(66) In some implementations, the one or more conditions include an air pressure of the wheel, a vertical motion of the wheel, a velocity of the vehicle, a rotational velocity of the wheel, an

acceleration of the vehicle, or an amount of electrical output generated by a generator in response to a rotation of the roller.

(67) In some implementations, the processor is further configured to execute the updated software instructions to cause the actuator to increase, according to the operational settings data, the first force applied to the roller in response to a vertical motion of the wheel exceeding a threshold.

(68) In some implementations, the processor is further configured to execute the updated software instructions to cause the actuator to increase, according to the operational settings data, the first force applied to the roller in response to an air pressure of the wheel falling below a threshold.

(69) In some implementations, the processor is further configured to execute the updated software instructions to cause the actuator to increase, according to the operational settings data, the first force applied to the roller in response to an electrical output generated by a generator falling below a threshold.

(70) In some implementations, the operational settings data includes one or more conditions for changing a position of the roller, wherein the processor is further configured to execute the updated software instructions to cause the actuator to change the position of the roller according to the one or more conditions of the operational settings data.

(71) In some implementations, the operational settings include conditions for adjusting the position of the roller, wherein the one or more conditions include an air pressure of the wheel, a vertical motion of the wheel, a velocity of the vehicle, a rotational velocity of the wheel, an acceleration of the vehicle, or an amount of electrical output generated by a generator in response to a rotation of the roller.

(72) In some implementations, the roller positions include an extended position in which the roller is in contact with the wheel, and a retracted position in which the roller is a distance from the wheel.

(73) In some implementations, the processor is further configured to execute the updated software instructions to cause the actuator to transition the roller, according to the operational settings data, to a retracted position in response to a vertical motion of the wheel exceeding a threshold.

(74) In some implementations, the processor is further configured to execute the updated software instructions to cause the actuator to transition the roller, according to the operational settings data, to a retraced position in response to an air pressure of the wheel falling below a threshold.

(75) In some implementations, the processor is further configured to execute the updated software instructions to cause the actuator to transition the roller, according to the operational settings data, to a retraced position in response to an electrical output generated by a generator falling below a threshold.

(76) In some implementations, the actuator is configured to apply the first force to the roller via one or more of a flexible arm, a mechanical spring, a gas spring, a piston, a suspension system, a shaft, a strut, hydraulics, pneumatics, a lever, a gear, or a pulley.

(77) Disclosed herein is a vehicle management system for over-the-air provisioning of a vehicle's operational settings. The vehicle management system may comprise: a transceiver, a computer readable storage medium having program instructions embodied therewith, and a processor. The transceiver can be configured to communicate wirelessly with a remote server to receive operational settings data from the server. The computer readable storage medium can be configured to update the program instructions according to operational settings data received from the server. The processor can be configured to execute the updated program instructions to cause the vehicle management system to operate according to an operational setting corresponding to the operational settings data received from the server. In some implementations, when operating according to the operational setting, the vehicle management system is configured to: communicate a signal to a switch to cause the switch to transition between an open state and a closed state to control an energy flow between a first energy storage device and a second energy storage device. In some implementations, in the closed state the switch is configured to electrically couple the first energy

storage device to the second energy storage device to allow an energy to transfer from the first energy storage device to the second energy storage device.

(78) In some implementations, the first energy storage device includes a capacitor.

(79) In some implementations, the second energy storage device includes a battery.

(80) In some implementations, when operating according to the operational setting, the vehicle management system is further configured to: communicate the signal to the switch to cause the switch to transition between the open state and the closed state once in substantially real time as the operational settings data are received from the server.

(81) In some implementations, when operating according to the operational setting, the vehicle management system is further configured to: communicate the signal to the switch to cause the switch to transition between the open state and the closed state every time one or more conditions occurs.

(82) In some implementations, when operating according to the operational setting, the vehicle management system is further configured to: communicate the signal to the switch to cause the switch to transition between the open state and the closed state based at least in part on one or more of a geographic location of the vehicle, a distance travelled by the vehicle, or a distance between the vehicle and a desired destination.

(83) In some implementations, the system may further comprise a voltage sensor in electrical communication with the first or second energy storage device. The voltage sensor can be configured to detect a voltage level of the first or second energy storage device.

(84) In some implementations, when operating according to the operational setting, the vehicle management system is further configured to: communicate the signal to the switch to cause the switch to transition to the closed state, in response to determining that the voltage level in the second energy storage device is below a low threshold level; and cause the switch to transition to the open state, in response to determining that the voltage level in the second energy storage device is above a high threshold level.

(85) In some implementations, when operating according to the operational setting, the vehicle management system is further configured to: communicate the signal to the switch to cause the switch to transition to the closed state, in response to determining that the voltage level in the first energy storage device is above a high threshold level, and cause the switch to transition to the open state, in response to determining that the voltage level in the first energy storage device is below a low threshold level.

(86) In some implementations, when operating according to the operational setting, the vehicle management system is further configured to communicate the signal to the switch to cause the switch to transition to the closed state, in response to determining that a voltage differential between the first and second energy storage device is above a threshold level.

(87) In some implementations, the system can further comprise a current sensor in electrical communication with the second energy storage device and configured to detect a current or amperage conducted from the second energy storage device to a load.

(88) In some implementations, when operating according to the operational setting, the vehicle management system is further configured to communicate the signal to the switch to cause the switch to transition to the closed state when a current or amperage conducted from the battery to the load exceeds a threshold level.

(89) Disclosed herein is a computing system for over-the-air provisioning of a vehicle's operational settings. The computing system can comprise: a computer readable storage medium having program instructions embodied therewith; and one or more processors configured to execute the program instructions. The one or more processors can be configured to execute the program instructions to cause the computing system to receive information relating to an operation or status of the vehicle and in response to receiving said information, wirelessly transmit operational settings options to a user. The one or more processors can be configured to execute the program instructions

to cause the computing system to receive, from the user, a selection of one or more of the operational settings options. The one or more processors can be configured to execute the program instructions to cause the computing system to in response to receiving a user selection, wirelessly transmit, to the vehicle, operational settings data corresponding to the one or more operational settings selected by the user, wherein the operational settings data are configured, when executed, to cause the vehicle to operate according to the one or more operational settings selected by the user.

(90) In some implementations, the one or more processors are further configured to execute the program instructions to cause the computing system to maintain a history log including information relating to transmitting the operational settings data to the vehicle.

(91) In some implementations, the one or more processors are further configured to execute the program instructions to cause the computing system to update generate a charge to the user in response to transmitting the operational settings data to the vehicle.

(92) In some implementations, wirelessly transmitting operational settings options to the user includes transmitting the operational settings options to a mobile device via a text message.

(93) In some implementations, wirelessly transmitting operational settings options to the user includes transmitting the operational settings options to a control dashboard of the vehicle.

(94) In some implementations, receiving the selection of one or more of the operational settings options from the user includes receiving a text message from a mobile device.

(95) In some implementations, the information relating to the operation or status of the vehicle includes one or more of a charge level of a battery of the vehicle, an estimated remaining operating time of the vehicle, an estimated remaining operating distance of the vehicle, a distance travelled by the vehicle, a distance between the vehicle and a desired destination, a geographic location of the vehicle, or a geographic location of a desired destination.

(96) In some implementations, the operational settings data are configured, when executed, to cause an energy generation system of the vehicle to operate according to the one or more operational settings selected by the user.

(97) In some implementations, the operational settings data are configured, when executed, to cause an energy management system of the vehicle to operate according to the one or more operational settings selected by the user.

(98) Disclosed herein is an energy system for storing and providing energy to a vehicle. The energy system may comprise: a capacitor storage device, and an energy storage device. The capacitor storage device can be configured to receive a first portion of energy from an energy source. The capacitor storage device can be configured to store the first portion energy as an electric field of the capacitor storage device. The capacitor storage device can be configured to convey the first portion energy to a battery storage device or to an electrical load of the vehicle. The energy storage device can be configured to receive a second portion of energy from an energy source. The energy storage device can be configured to store the second portion of energy. The energy storage device can be configured to convey the second portion energy to the battery storage device or to the electrical load of the vehicle. The energy storage device can have a higher amp-hour rating than the capacitor storage device. The energy storage device can have a lower voltage rating than the capacitor storage device.

(99) In some implementations, the energy storage device includes one or more cells electrically connected in parallel.

(100) In some implementations, the capacitor storage device includes one or more cells electrically connected in series.

(101) In some implementations, the energy storage device has a higher C rating than the capacitor storage device.

(102) In some implementations, the energy storage device is configured to discharge a greater continuous current or burst current than the capacitor storage device.

- (103) In some implementations, the energy storage device includes one or more capacitors.
- (104) In some implementations, the energy storage device includes one or more batteries.
- (105) In some implementations, the energy storage device is removably electrically coupled with the battery via a mechanical connection.
- (106) In some implementations, the energy storage device is coupled with the battery via a friction fit.
- (107) Disclosed herein is a system for managing energy storage. The system can comprise a capacitor storage device, a battery, a switch, and a controller. The capacitor storage device can be configured to receive a first portion of energy from an energy source. The capacitor storage device can be configured to store the first portion energy as an electric field of the capacitor storage device. The battery can be configured to electrically couple to the capacitor storage device. The battery can be configured to receive energy from the capacitor storage device via one or more diodes biased toward the battery. The switch can be configured to transition between an open state and a closed state. The switch can be configured to electrically couple the battery to the ultracapacitor when in the closed state to conduct an energy between the ultracapacitor and the battery. The switch can be configured to electrically disconnect the battery from the ultracapacitor when in the open state to prevent conducting an energy between the ultracapacitor and the battery. The controller may be in electrical communication with the switch and may be configured to cause the switch to transition between the open state and the closed state.
- (108) In some implementations, the energy source includes is one or more solar panels or solar cells.
- (109) In some implementations, the energy source includes a turbine.
- (110) In some implementations, the energy source includes is a generator.
- (111) In some implementations, the energy source includes is a charging station.
- (112) In some implementations, the energy source is disposed on a housing of a vehicle.
- (113) Various combinations of the above and below recited features, embodiments, implementations, and aspects are also disclosed and contemplated by the present disclosure.
- (114) Additional implementations of the disclosure are described below in reference to the appended claims, which may serve as an additional summary of the disclosure.
- (115) In various implementations, systems and/or computer systems are disclosed that comprise a computer-readable storage medium having program instructions embodied therewith, and one or more processors configured to execute the program instructions to cause the systems and/or computer systems to perform operations comprising one or more aspects of the above- and/or below-described implementations (including one or more aspects of the appended claims).
- (116) In various implementations, computer-implemented methods are disclosed in which, by one or more processors executing program instructions, one or more aspects of the above- and/or below-described implementations (including one or more aspects of the appended claims) are implemented and/or performed.
- (117) In various implementations, computer program products comprising a computer-readable storage medium are disclosed, wherein the computer-readable storage medium has program instructions embodied therewith, the program instructions executable by one or more processors to cause the one or more processors to perform operations comprising one or more aspects of the above- and/or below-described implementations (including one or more aspects of the appended claims).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A illustrates an example vehicle such as an electric vehicle that may be provisioned

according to over-the-air systems and methods described herein.

(2) FIGS. 1B-1C are block diagrams illustrating example embodiments of a component interface device.

(3) FIG. 1D is a block diagram illustrating an example implementation of a vehicle management system with a capacitor module and battery.

(4) FIG. 2 is a block diagram illustrating an example vehicle component that may be used in a vehicle for over-the-air-provisioning of the vehicle.

(5) FIG. 3 is a block diagram illustrating an example system for over-the-air provisioning of a vehicle's operational settings.

(6) FIGS. 4-6 are flowcharts illustrating example processes for over-the-air provisioning of a vehicle's operational settings.

(7) FIG. 7A is a flowchart illustrating an example process for over-the-air provisioning of a vehicle's operational settings.

(8) FIG. 7B is a flowchart illustrating an example process for communicating vehicle related data to a third party.

(9) FIG. 8 is a diagram of an exemplary "fifth" wheel configured to drive or power an on-board charging system (OBCS) of a vehicle.

(10) FIG. 9 is a diagram of a fifth wheel mechanically coupled to two generators.

(11) FIG. 10 illustrates an example implementation of a fifth wheel in a vehicle.

(12) FIG. 11 is block diagram illustrating an example implementation of a gearbox.

(13) FIGS. 12A-12B illustrate example implementations of a roller configured to contact a wheel.

(14) FIGS. 13A-13B illustrate example implementations of one or more rollers configured to contact a sidewall surface of a wheel.

(15) FIG. 14A is a block diagram illustrating an example energy system.

(16) FIG. 14B illustrates an example implementation of an energy system including a solar charging station used to charge a vehicle.

(17) FIG. 14C illustrates an example implementation of an energy system including one or more solar panels and/or solar cells and a vehicle.

(18) FIG. 15A is a block diagram illustrating an example energy system.

(19) FIG. 15B illustrates an example implementation of an energy system including a turbine charging station used to charge a vehicle.

(20) FIG. 15C illustrates an example implementation of an energy system including one or more turbines and a vehicle.

(21) FIG. 15D illustrates an example implementation of an energy system including one or more turbines and an aircraft.

(22) FIG. 15E illustrates an example implementation of an energy system including one or more turbines and a watercraft.

DETAILED DESCRIPTION

Overview

(23) Example systems and methods for over-the-air provisioning of a vehicle's operational settings are described herein. A system for over-the-air provisioning of a vehicle's operational settings can include a server remote to the vehicle which can include or have access to operational settings data. The server can transmit (e.g., wirelessly) the operational settings data to the vehicle. Operational settings data can affect how a vehicle or its components function.

(24) Various methods exist for transmitting operational settings data to a vehicle (e.g., from a remote server). Operational settings data can be transmitted to the vehicle in response to a request (e.g., from the vehicle or its components, or from a user), automatically such as on a periodic basis, anytime operational settings data (updated or new) are available for the vehicle or anytime updated or new operational settings data are required or desired for improving performance of a vehicle or its components.

(25) Various example systems and methods for over-the-air provisioning of an electric vehicle's operational settings are described herein, for example, with reference to the figures. The various systems, methods and their implementations are given as examples and are not meant to be limiting of the present disclosure.

(26) In some implementations, Vehicle Components may refer to any of the components of a vehicle such as an energy storage device (e.g., battery, capacitor), an energy generation system (e.g., a generator), a motor, a vehicle management system, a component interface device, driven masses, rollers, flexible arms, suspension systems (e.g., of driven masses and/or rollers), etc. The vehicle components may operate according to operational settings and may be provisioned over-the-air.

(27) In some implementations, Operational Settings may refer to any of the various settings according to which a vehicle or its components may operate.

(28) In some implementations, (Operational) Settings Data may refer to data for provisioning the operational functionality of a vehicle or its components. Settings data may include executable software instructions or files including the same. In some embodiments, operational settings data can include program instructions that when executed cause a vehicle component to perform one or more operations one time (e.g., a one-time operation). In some embodiments, operational settings data can include program instructions that when executed cause a vehicle component to perform one or more operations a multiple times, repeatedly, indefinitely, every time one or more conditions occurs, or the like. In some embodiments, operational settings data may include program instructions that when executed cause a vehicle component to perform one or more operations immediately (e.g., in substantially real-time as when the settings data are received at the component). In some embodiments, operational settings data may include program instructions that when executed cause a vehicle component to perform one or more operations at a future time (e.g., at a time after the settings data are received at the component).

(29) In some implementations, Operational Settings Options may refer to any of the various operational settings that may be available to a vehicle for download and which a user may review and select.

(30) In some implementations, Operational Settings Server (OSS) may refer to a server, remote to a vehicle, that may communicate with the vehicle. The OSS may be configured to store various operational setting data that can be downloaded to a vehicle.

(31) In some implementations, User may refer to a person or entity that may be associated with a vehicle and may communicate with the OSS for requesting operational settings data to be downloaded to the vehicle.

(32) In some implementations, Vehicle Management System may refer to a system or device for controlling or managing the operational functionality of a vehicle or its components. The vehicle management system may communicate with the OSS and may manage the provisioning of the vehicle such as requesting, downloading, storing operational settings data. The vehicle management system may comprise and/or may be referred to herein as a battery management system. The vehicle management system may include a processor or other similar computing device.

(33) In some implementations, Component Interface Device may refer to a device or system electrically coupled to two or more components of a vehicle that may act as an interface between the components to allow the components to operate with each other in the vehicle. In some embodiments, the component interface device may be provisioned (e.g., over-the-air) with operational settings data.

(34) Example Systems for Over-the-Air Provisioning

(35) FIG. 1A illustrates an example vehicle **100** such as an electric vehicle that may be provisioned according to over-the-air systems and methods described herein. As shown, the vehicle **100** can include various components such as a motor **104**, a generation system **109** (e.g., a generator), a

vehicle management system **107** (such as a battery management system), a component interface device **105**, one or more energy storage devices **102** (e.g., batteries, deep-cycle batteries, battery fields, capacitors, ultracapacitors, hypercapacitors) and the like. As shown, the energy storage devices **102** may be added to, or removed from, the vehicle, for example in a modular fashion. In some embodiments, energy storage devices **102** may be replaced with energy storage devices of a different type of device (such as switching a battery to a capacitor) or to energy storage devices of the same type but of a different make or model (such as switching a battery from one manufacturer to a battery of a different manufacturer). In some embodiments, energy storage devices **102** used in a vehicle at one time may include devices of different types or makes or models. Some or all of the various components may be provisioned (e.g., over-the-air) as described herein. FIG. **1A** is provided as an example and is not intended to be limiting. In some embodiments, the components may be arranged in a different manner (e.g., different locations in the vehicle) than what is shown in FIG. **1A**. In some embodiments, the vehicle may include more or less components or different types of components than what is shown in FIG. **1A**.

(36) In some embodiments, the one or more energy storage devices **102** may include one or more capacitor modules in combination with one or more batteries. For example, the one or more energy storage devices **102** may include one or more capacitor modules installed alongside one or more batteries may be connected in series or in parallel. For example, a capacitor module may be connected in series or parallel with a battery when supplementing the voltage in the battery or when charging the battery. Therefore, the battery and the capacitor modules may provide voltage support to each other. As such, the capacitor modules may provide supplemental energy when the battery are discharged or be used in place of the battery altogether.

(37) In some embodiments, the capacitor modules provide a burst of energy on demand to the battery and/or to the motor. For example, the capacitor modules are coupled to the vehicle (or another) controller that monitors a charge level of the battery and/or an energy demand of the motors. The controller may control coupling of the capacitor modules to the battery to charge the battery with the burst of energy from the capacitor modules when the charge level of the battery falls below a threshold value or may couple the capacitor modules to the battery to supplement an output energy of the battery.

(38) FIG. **1B** is a block diagram illustrating an example embodiment of various components of a vehicle including a vehicle management system **121**, optionally a component interface device **123** in some embodiments, one or more energy storage devices **125a**, **125b**, and one or more switch(es) **127**.

(39) The energy storage devices **125a**, **125b** can include capacitors, batteries, or the like. The switch(es) **127** can electrically couple the energy storage devices **125** to each other. The switch(es) **127** can electrically couple the energy storage devices **125** to a load. The switch(es) **127** may be configured to transition between states to allow or prevent a flow of energy therethrough.

(40) The vehicle management system **121** may be electrically coupled to the component interface device **123** which in turn may be electrically coupled to one or more energy storage devices **125a**, **125b** and/or switches **127**. In some implementations, vehicle management system **121** may be directly electrically coupled to one or more energy storage devices **125a**, **125b** and/or switches **127**. The electrical coupling between the components, as described, may facilitate the communication of data between the components which may affect how the components function and function together. In some embodiments, the components may be electrically coupled via wires. In some embodiments, the components may be electrically coupled wirelessly.

(41) The vehicle management system **121** may control operation of the one or more energy storage devices **125a**, **125b**. For example, the vehicle managements system **121** may determine and/or control the conditions under which the energy storage device **125** is charged, discharged, the rate of charging or discharging, the maximum or minimum charge held by the energy storage device, and may coordinate charging and discharging between multiple energy storage devices **125**. The

vehicle management system **121** may control operation of the energy storage devices **125** according to operational settings, such as according to operational settings data provisioned to the vehicle management system **121** over-the-air.

(42) The vehicle management system **121** may control operation of the switch(es) **127**. The vehicle management system **121** may control operation of the switch(es) **127** according to operational settings, such as according to operational settings data provisioned to the switch(es) **127** over-the-air. For example, the vehicle management system **121** may control when the switch(es) **127** transition between states to control whether the switch(es) **127** allow energy to pass through or prevent energy from passing therethrough. Accordingly, the vehicle management system **121** may control or adjust an electrically coupling between components by controlling the switch(es) **127**. For example, the vehicle management system **121** may control whether the energy storage devices **125** are electrically coupled to each other by controlling transitioning of the switch(es) **127** between operative states. As another example, the vehicle management system **121** may control whether the energy storage devices **125** are electrically coupled to a load by controlling transitioning of the switch(es) **127** between operative states.

(43) Advantageously, operational settings data used to control the energy storage devices **125** and/or switch(es) **127** may be provisioned (e.g., over-the-air to the vehicle management system **131** and/or component interface device **133**). Provisioning the operational settings data may allow the operational settings to be updated such as periodically, automatically, in response to a request, and/or on demand. Updating the operational settings (e.g., via over-the-air provisioning) of the various components can improve operational efficiency and/or performance of the system by dynamically adjusting operational settings according to real-time needs and conditions. For example, operational settings data can be provisioned over-the-air to update operational settings to improve performance based on changes in energy levels of the energy storage devices **125**, energy requirements of a load, operating conditions, such as temperature, geographic location, geographic destination, estimated time and/or distance to destination, or the like.

(44) The vehicle management system **121**, the energy storage devices **125a**, **125b**, and switch(es) **127** may each include parameters, for example, operational settings data included on the component that may be executed by a computing device to control operation of the respective components. The operational settings included on each respective component (vehicle management system **121**, energy storage device **125**) may have been encoded during manufacturing (e.g., manufacturer's settings) or may have been configured during an initial configuration of the component. In some embodiments, the operational settings of the vehicle management system **121**, energy storage device **125**, and/or and switch(es) **127** may be static and it may be impossible or difficult to change the operational settings of said components. In some embodiments, the operational settings of the components such as the vehicle management system **121**, energy storage device **125**, or and switch(es) **127** may be quickly updated, for example via over-the-air provisioning as described herein. In some embodiments, the components such as the vehicle management system **121**, energy storage device **125**, or and switch(es) **127** may only operate with certain other components (e.g., types, makes, models) based on the configuration of the operational settings. For example, the operational settings of a component may be required to be compatible with operational settings of other components for the components to function together.

(45) A component interface device **123** may facilitate the interaction between a vehicle management system **121** and other components such as an energy storage device **125** and/or switch **127**, for example in embodiments where the operational settings of the vehicle management system **121**, energy storage device **125**, and/or switch **127** are static and/or are not initially configured for compatible functionality with one another.

(46) The component interface device **123** may include parameters, for example, operational settings data included on the component interface device **123** that may be executed by a computing device to control operation of the component interface device **123**.

(47) The component interface device **123** may be configured to detect an energy storage device **125** as well as a type, make or model of the energy storage device **125**. For example, the component interface device **123** may be configured to determine whether the energy storage device is a battery or a capacitor as well as other characteristics of the energy storage device (e.g., make or model). The component interface device **123** may be configured to detect and determine characteristics of the vehicle management system **121**. The component interface device **123** may be configured to detect and determine characteristics of the switch(es) **127**.

(48) The component interface device **123** may be configured to determine (e.g., type or characteristics of) the operational settings data included on the energy storage device **125**, the vehicle management system **121**, and/or the switch(es) **127**, for example by parsing the operational settings data of the other components or detecting an identifier of the operational settings data such as an operational settings data tag or header included in the operational settings data and containing information relating to the characteristics of the operational settings data. The component interface device **123** may be configured to facilitate an operational compatibility between the vehicle management system **121**, energy storage device **125**, and/or switch(es) **127** for example in embodiments where the operational settings data of the vehicle management system **121**, energy storage device **125**, and/or switch(es) **127** would not otherwise be compatible.

(49) As an example of facilitating an operational compatibility, the component interface device **123** may receive an electrical communication (e.g., via wires or wirelessly) from the vehicle management system **121**, for example, including data relating to instructions to control an operation of the energy storage device **125**. The component interface device **123** may determine (or may have previously determined) the operational settings data of the energy storage device **125**. If the operational settings data of the energy storage device **125** is not compatible with the operational settings data of the vehicle management system **121** (e.g., such that the energy storage device **125** would not “understand” the instructions and/or data communicated from the vehicle management system **121**), the component interface device **123** may “translate” the data communicated from the vehicle management system **121** to a form that is compatible with the operational settings data of the energy storage device **125**, for example, by generating new data and/or altering the data received from the vehicle management system **121**. The component interface device **123** may be configured to perform similar operations of translating data communicated from the energy storage device **125** to the vehicle management system **121**.

(50) The component interface device **123** may control the interacting between two components based on operational settings data of the component interface device **123**. For example, the component interface device **123** may interface a vehicle management system **121** with a certain energy storage device **125a** according a first operational settings data of the component interface device **123**. A second energy storage device **125b** may be added to the vehicle which may replace or supplement energy storage device **125b**. The component interface device **123** may not be configured according to the first operational settings data to facilitate operational compatibility between the vehicle management system **121** and the energy storage device **125b**. However, the component interface device **123** may be provisioned (e.g., over-the-air as described herein) with second operational settings data which may configure the component interface device **123** to facilitate operational compatibility between the vehicle management system **121** and the energy storage device **125b**.

(51) FIG. 1B is provided as an example and is not intended to be limiting. In some embodiments, the component interface device **123** may be configured, e.g., according to one or more sets of operational settings data, to facilitate operational compatibility between the vehicle management system **121** and any number of energy storage devices **125**, such as one energy storage device **125** or more than two energy storage devices **125**. In some embodiments, the component interface device **123** may be configured, e.g., according to one or more sets of operational settings data, to facilitate operational compatibility between the vehicle management system **121** and a variety of

different types, makes and/or models of energy storage devices **125** such as capacitors, batteries, and/or other energy storage devices described herein.

(52) The example components discussed above with reference to FIG. **1B** are not intended to be limiting. In some embodiments, the component interface device **123** may facilitate an operational compatibility between any two components such as, for example, between any combination of the following components: energy storage devices, switches, energy generation systems, motors, vehicle management systems, other component interface devices, and the like. In some embodiments, the vehicle management system **121** may be in communication with a server (e.g., OSS) remote to the vehicle management system **121**. The vehicle management system **131** may communicate data to the remote server. For example, the vehicle management system may collect data relating to the operations of the energy storage devices **125a**, **125b** and/or the switch(es) **127** and communicate the data to the remote server.

(53) FIG. **1C** is a block diagram illustrating an example embodiment of various components of a vehicle including a vehicle management system **131**, optionally a component interface device **133** in some embodiments, one or more driven masses **136**, one or more rollers **138**, a gearbox **132**, and a suspension system **134**. The vehicle management system **131** and component interface device **133** may include structural and/or operational features similar to those discussed with reference to FIG. **1B**, for example.

(54) The driven mass(es) **136** can include one or more rollers, one or more fifth wheels, and/or one or more turbines, such as a water or wind turbine. In some implementations, a roller, a driven mass, a fifth wheel, and/or a turbine may include similar structural and/or operational features. In some implementations, the terms “roller”, “driven mass”, “fifth wheel”, and/or “turbine” may be used interchangeably.

(55) The vehicle management system **131** is in communication with the component interface device **133**. The component interface device **133** is in communication with one or more driven masses **136**, the roller(s) **138**, the gearbox **132**, and the suspension system **134**. In some implementations, the vehicle management system **131** is in direct communication with the one or more driven masses **136**, the roller(s) **138**, the gearbox **132**, and the suspension system **134**. In some embodiments, the vehicle management system **131** and/or component interface device **133** may be provisioned (e.g., over-the-air) with operational settings data to control an operation of the one or more driven masses **136**, the one or more rollers **138**, the gearbox **132**, and/or the suspension system **134**.

(56) As an example, the vehicle management system **131** and/or component interface device **133** may control, according to operational settings data, a position of the driven mass(es) **136** relative to a ground surface and/or a position of the roller(s) **138** relative to a wheel of the vehicle. As another example, the vehicle management system **131** and/or component interface device **133** may control, according to operational settings data, a force with which the driven mass(es) **136** are applied to a ground surface and/or a force with which the roller(s) **138** are applied to a wheel such as via one or more actuators. Adjusting (e.g., increasing) a force with which the driven mass(es) **136** and/or roller(s) are applied to a ground surface and/or a wheel of the vehicle may improve contact of the driven mass(es) **136** and/or rollers with the ground and/or wheel, such as on uneven terrain.

(57) As another example, the vehicle management system **131** and/or component interface device **133** may control, according to operational settings data, the gearbox **132**. The gearbox may rotatably couple the driven mass(es) **136** and/or roller(s) **138** to a generator. The gearbox **132** may include one or more gears of various diameters. The vehicle management system **131** and/or component interface device **133** may control a ratio of rotation between a driven mass **136** and/or roller **138** rotatably coupled to the gearbox **132** and a generator rotatably coupled to the gearbox **132**. The operational settings according to which the vehicle management system **131** and/or component interface device **133** controls the gearbox **132** may determine the conditions under which the gearbox **132** adjusts a ratio of rotation.

(58) As another example, the vehicle management system **131** and/or component interface device **133** may control, according to operational settings data, the suspension system **134**. The suspension system **134** may house the driven mass(es) **136** and/or roller(s) **138**. The suspension system **134** may be independent of a suspension system of the vehicle. The suspension system **134** may operate to transition the driven mass(es) **136** and/or roller(s) **138** between engaged/disengaged states and/or extended/retracted states. In some implementations, the engaged state and the extended state may include similar operational features. In some implementations, the disengaged state and the retracted state may include similar operational features. In some implementations, the term “engaged state” and the term “extended state” may be used interchangeably. In some implementations, the term “disengaged state” and the term “retracted state” may be used interchangeably. The vehicle management system **131** and/or component interface device **133** may control whether the suspension system **134** transitions between states. The operational settings according to which the vehicle management system **131** and/or component interface device **133** controls the suspension system **134** may determine the conditions under which the suspension system **134** transitions between states.

(59) Advantageously, operational settings data used to control the driven mass(es) **136**, roller(s) **138**, gearbox **132**, and/or suspension system **134** may be provisioned (e.g., over-the-air to the vehicle management system **131** and/or component interface device **133**). Provisioning the operational settings data may allow the operational settings to be updated such as periodically, automatically, in response to a request, and/or on demand. Updating the operational settings (e.g., via over-the-air provisioning) of the various components can improve operational efficiency and/or performance of the system by dynamically adjusting operational settings according to real-time needs and conditions. For example, operational settings data can be provisioned over-the-air to update operational settings to improve performance based on changes in a terrain surface on which the vehicle travels, changes in wheels used on the vehicle, changes in a pressure of the vehicle wheels and/or driven mass(es) **136**, or the like.

(60) FIG. 1C is given as an example and is not intended to be limiting. In some embodiments, the component interface device **133** may be in communication with one or more components, devices, or systems associated with the driven mass(es) **136** and/or roller(s) **138**. For example, the component interface device **133** may be in communication with a suspension system, a flexible arm (e.g., of a roller), a shaft, an actuator, a piston, a gear, a lever, a pulley, a spring, or the like to effectuate control of the driven mass(es) **136** and/or roller(s) **138**, such as a position or applied force thereof.

(61) In some embodiments, the vehicle management system **131** may be in communication with a server (e.g., OSS) remote to the vehicle management system **131**. The vehicle management system **131** may communicate data to the remote server. The vehicle management system **131** can communicate data relating to the driven mass(es) **136**, roller(s), gearbox **135** and/or suspension system **134**. For example, the vehicle management system **131** can communicate an indication of whether and/or how often the vehicle has entered into power saving mode. As another example, the vehicle management system **131** can communicate an indication of whether and/or how often the vehicle has initiated a power generator, the amount of energy being generated by an on-board power generation system, such as a power generation system including a driven mass or roller, an air pressure of a driven mass, circumstances under which a driven mass is in an extended position or a retracted position, and/or any other data or information tracked or collected about the vehicle or vehicle operations. For example, the vehicle management system **131** can communicate an indication that a driven mass **136** is engaged with the ground and/or a wheel. As another example, the vehicle management system **131** can communicate an indication that a roller **138** has engaged with a wheel. As another example, the vehicle management system **131** can communicate data regarding the gearbox **132** such as the ratio of gears between driven mass(es) **136** and a generator to control energy output. As another example, the vehicle management system **131** can

communicate data regarding the suspension system **134** such as vehicle weight, whether the vehicle is on an uneven surface, or the like.

(62) FIG. 1D is a block diagram illustrating an example embodiment of an energy system **150** for providing and storing energy. In this example, the energy system **150** includes a vehicle management system **140**, an energy source **155**, one or more electrical interfaces **153** (e.g., **153a**, **153b**), energy storage device **141**, energy storage device **145**, and a load **157**. In some implementations, the energy system **150** can optionally include energy storage device **143**. In some implementations, the energy system **150** can include a plurality of energy storage devices **143**. In some implementations, the energy system **150** can optionally include one or more diodes, such as diode **158a**, diode **158b**, diode **148a**, diode **148b**, diode **148c**, and/or diode **148d**. In some implementations, the energy system **150** can optionally include one or more switches, such as switch **146a**, switch **146b**, switch **146c**, and/or switch **146d**. In some implementations, the energy system **150** can optionally include energy storage device **147**.

(63) In some embodiments, the energy source **155** can include a power grid or Mains electricity. In some embodiments the energy source **155** can include an energy generation or regeneration system. For example, the energy source **155** can include one or more of: a generator, a driven mass, a fifth wheel, a roller, a turbine such as a water and/or wind turbine, a regenerative braking system, a solar power generation system such as solar panels or solar cells. In some implementations, the energy source **155** may be included within a vehicle. For example, the energy source **155** may include an on-board power generation system disposed within and/or on a vehicle and that is mobile with the vehicle. In some implementations, the energy source **155** may be separate from a vehicle. For example, the energy source **155** may be stationary or in a fixed location such as a charging station.

(64) The energy storage device **141** can be electrically coupled to the energy source **155** via an electrical interface **153a**. For example, the energy storage device **141** can be removably coupled (electrically, physically) with the energy source **155** via the electrical interface **153a**. The electrical interface **153a** can include a plug and/or a socket such as a standard 110 volt outlet wall socket configured to receive an electrical plug. The energy storage device **141** can be electrically coupled with the energy source **155** via one or more electrical wires, cables, or cords. The energy storage device **143** can be electrically coupled to the energy source **155** via an electrical interface **153b** in a same or similar manner as described above with respect to energy storage device **141** and electrical interface **153a**.

(65) The energy storage device **141** can be electrically coupled with the energy source **155** via a diode **158a**. The diode **158a** can be biased toward the capacitor module and configured to allow an energy (e.g., a current or amperage) to flow from the energy source **155** to the energy storage device **141**. The diode **158a** may prevent an energy from flowing from the energy storage device **141** to the energy source **155**. Advantageously, the diode **158a** may facilitate retaining an energy at the energy storage device **141** when the energy storage device **141** has a higher energy level (e.g., higher voltage) than the energy source energy source **155**, such as during a power outage and/or when a power generation system is not producing energy. In some embodiments, more than one diode may be disposed between the energy source **155** and the energy storage device **141**. The energy storage device **143** can be electrically coupled with the energy source **155** via a diode **158b** in a same or similar manner as described above with respect to energy storage device **141** and diode **158a**.

(66) The energy storage device **141** can include one or more capacitors, ultracapacitors, and/or supercapacitors. A plurality of capacitors in the energy storage device **141** can be electrically connected in series and/or parallel. In some embodiments, the energy storage device **141** can be configured to store up to 400 volts of electrical energy. For example, the energy storage device **141** may store about 100 to 200 volts, about 200 to 300 volts, or about 300 to 400 volts. In some embodiments, the energy storage device **141** can be configured to store less than 100 volts such as about 50 volts or about 25 volts.

(67) The switch **146a** can include one or more of an electrical switch, a relay, or the like. The switch **146a** can operate according to one or more states including an open state and a closed state. In the closed state, the switch **146a** can conduct energy (e.g., current or amperage) such as from the energy storage device **141** to the energy storage device **145**. In the open state, the switch **146a** may not conduct energy (e.g., from the energy storage device **141** to the energy storage device **145**). The switch **146a** may transition between the open and closed states. In some embodiments, the switch **146a** transitions between the open and closed states automatically, such as in response to a signal from the vehicle management system **140**.

(68) The switch **146a** is electrically coupled with the energy storage device **145**. As shown, the switch **146a** is electrically coupled to the energy storage device **145** via diode **148a**. In some embodiments, the energy system **150** may not include diode **148a**.

(69) In some embodiments, the energy storage device **145** may be electrically coupled to the switch **146a** (and/or energy storage device **141**) via one or more electrical wires, cables, cords, or the like, which may be configured to withstand high voltages (e.g., 400 volts) and/or high amperage (e.g., 400 amperes). The energy storage device **145** may be electrically coupled to the energy storage device **141** via one or more electrical connectors, such as a plug, a socket, or the like. The energy storage device **145** and the energy storage device **141** may be removably coupled via the electrical connectors.

(70) When the switch is in the closed state, energy may transfer from the energy storage device **141** to the energy storage device **145**, such as via the diode **148a**. The energy storage device **141** can be electrically connected with the energy storage device **145** in series and/or parallel. When a voltage differential between energy storage device **141** and the energy storage device **145** exceeds a certain threshold, energy may be amenable to flow from the energy storage device **141** to the energy storage device **145**. For example, in some embodiments, the diode **148a** may be configured with a certain resistance preventing current from passing through the diode **148a** until a threshold voltage across the diode **148a** is achieved. As the voltage differential across the diode **148a** (e.g., between the energy storage device **141** and energy storage device **145**) increases, the diode **148a** may “open” to allow a current to pass in a single direction through the diode **148a**.

(71) The switch **146b** may include similar or the same operational and/or structural features as described above with respect to switch **146a**. The energy storage device **143** may transfer energy to the energy storage device **145** via the switch **146b** in a same or similar manner as described above with respect to energy storage device **141** transferring energy to energy storage device **145** via switch **146a**.

(72) The energy storage device **145** can include one or more batteries such as lithium ion batteries, lithium polymer batteries, and/or batteries that include one or more other materials for storing energy, such as zinc, carbon, magnesium, manganese, mercury, alkaline, silver, nickel, metal hydride, cadmium, lead, and the like. In some embodiments, the energy storage device **145** can include a battery field. In some embodiments, the energy storage device **145** can include. In some embodiments, energy storage device **145** can be configured to store up to 400 volts of electrical energy. For example, the energy storage device **145** may store about 100 to 200 volts, about 200 to 300 volts, or about 300 to 400 volts. In some embodiments, the energy storage device **145** can be configured to store less than 100 volts such as about 50 volts or about 25 volts. In some embodiments, the energy storage device **145** may comprise a plurality of batteries, such as a battery field. The plurality of batteries may be electrically connected to one another in series and/or in parallel.

(73) In some implementations, the energy storage device **145** is electrically coupled with energy storage device **147**. In some implementations, the energy storage device **145** is directly electrically coupled to the load **157**.

(74) In some implementations, the energy storage device **145** may be structurally and/or functionally similar or the same as energy storage device **147**. In some implementations, the energy

storage device **145** may be structurally and/or operationally different from energy storage device **147**. For example, energy storage device **145** and energy storage device **147** each be configured to store a different amount of energy (e.g., voltage). As another example, energy storage device **145** and energy storage device **147** can each be configured with a different specific power (e.g., power density), specific energy (e.g., energy density), charge time, charging rate, life cycle, and/or internal resistance. As another example, energy storage device **145** may be a different type of device or component than energy storage device **147**. In some embodiments, energy storage device **145** is a capacitor and energy storage device **147** is a battery. In some embodiments, energy storage device **145** is a first type of battery and energy storage device **147** is a second type of battery. In some embodiments, energy storage device **145** and energy storage device **147** include various types of lithium ion batteries and/or lithium polymer batteries. In some embodiments, the energy storage devices **145**, **147** include various materials for storing energy, such as zinc, carbon, magnesium, manganese, mercury, alkaline, silver, nickel, metal hydride, cadmium, lead, and the like.

(75) In some embodiments, energy storage device **141** and/or **143** has a smaller specific energy than energy storage device **145** or energy storage device **147**. In some embodiments, energy storage device **145** has a smaller specific energy than energy storage device **147**. In some embodiments, energy storage device **141** and/or **143** has a greater specific power than energy storage device **145** or energy storage device **147**. In some embodiments, energy storage device **145** has a greater specific power than energy storage device **147**.

(76) In one example implementation, the energy storage device **141** and/or **143** charges quickly (e.g., quicker than energy storage devices **145** and/or **147**) and stores the energy as an electric field. The energy storage device **141** and/or **143** then conveys energy to the energy storage device **145** (which may charge quicker than energy storage device **147**), and which stores the energy conveyed from the energy storage device **141** and/or **143**. The energy storage device **145** can convey energy to the energy storage device **147** where energy is stored before being provided to the load **157**.

(77) Advantageously, the energy storage device **145** may facilitate a transfer of energy from the energy storage device **141** and/or **143** to the energy storage device **147** by providing an “intermediate” storage device that is more amenable to receiving energy from the energy storage device **141** and/or **143**.

(78) In some implementations, the energy storage device **141** may be electrically coupled to the load **157**. For example, the energy storage device **141** may be coupled to the load **157** via one or more of switch **146c** and/or diode **148c**. In some implementations, the energy storage device **143** may be electrically coupled to the load **157**. For example, the energy storage device **143** may be coupled to the load **157** via one or more of switch **146d** and/or diode **148d**. Switch(es) **146c** and/or **146d** may include operational and/or structural features similar to those discussed above with respect to switch(es) **146a** and/or **146b**. For example, the energy storage device(s) **141**, **143** may transfer energy to the load **157** via switch(es) **146c** and/or **146d**. Diode(s) **148c** and/or **148d** may include operational and/or structural features similar to those discussed above with respect to diode(s) **148a** and/or **148b**. For example, the energy storage device(s) **141**, **143** may transfer energy to the load **157** via diode(s) **148c** and/or **148d**. In some implementations, the energy storage device **141** may transfer energy to the energy storage device **145** at a same time as transferring energy to the load **157**. In some implementations, the energy storage device **143** may transfer energy to the energy storage device **145** at a same time as transferring energy to the load **157**.

(79) The energy storage device **147** can be electrically coupled to the load **157**. The load **157** may include a device or component configured to consume energy. The load **157** may draw energy from the energy storage device **147** as the load **157** operates. For example, the load **157** may demand current or amperage from the energy storage device **147** depending on the energy requirements of the load **157**. As the load **157** draws current or amperage from the energy storage device **147**, a voltage level of the energy storage device **147** may reduce. As the load **157** requires more energy, more current or amperage may be transferred from the energy storage device **147** to the load **157**.

resulting in greater voltage loss at the energy storage device **145**. In some embodiments, the load **157** may include a vehicle, such as a car, truck, golf cart, tractor, tractor-trailer, or the like. For example, the load **157** may be a motor of a vehicle.

(80) As shown in this example embodiment, the energy system **150** further includes a vehicle management system **140**. The vehicle management system **140** may include similar structural and/or operational features to vehicle management system **121** and/or vehicle management system **131** described herein. The vehicle management system **140** may be implemented in a vehicle and may be in communication (e.g., wired and/or wireless) with one or more components of the vehicle. The vehicle management system **140** may control operation or functionality of the vehicle or various components thereof. The vehicle management system **140** can include one or more memory or storage devices configured to store executable instructions (e.g., software instructions) that when executed perform one or more operations. The vehicle management system **140** can include one or more hardware processors configured to execute instructions to cause the vehicle management system **140** and/or other components of the energy system **150** to perform one or more operations.

(81) In some embodiments, the vehicle management system **140** can optionally include a voltage sensor **142** and/or a current sensor **144**. In some embodiments, the vehicle management system **140** may optionally be in communication with a voltage sensor and/or a current sensor remote to the vehicle management system **140**. The voltage sensor **142** can be configured to determine voltage levels and/or differentials at the energy source **155**, energy storage device **141**, **143**, **145**, and/or **147**, and/or at the load **157**. The current sensor **144** can be configured to determine an electrical current or amperage flowing through the energy system **150** such as from the energy source to energy storage device **141** and/or **143**, from energy storage device **141** and/or **143** to energy storage device **145**, from energy storage device **141** and/or **143** to the load **157**, from energy storage device **145** to energy storage device **147** and/or the load **157**, or from energy storage device **147** to the load **157**.

(82) The vehicle managements system **140** may be in communication with the energy source **155**, energy storage device(s) **141**, **143**, **145**, and/or **147**, switch(es) **146a**, **146b**, **146c**, and/or **146d**, and/or the load **157**. The vehicle management system **140** may communicate with one or more components of the energy system **150** via a wired and/or wireless connection. For example, the vehicle management system **140** may be remote to one or more components of the energy system **150** and may communicate with the other components over a wireless network to control one or more operations of the components. The vehicle management system **140** may control the operation of the components based at least in part on information from the voltage sensor **142**, the current sensor **144**, and/or according to one or more operational settings.

(83) The vehicle management system **140** may control operation of the energy system **150**, or components thereof, such as switch(es) **146a**, **146b**, **146c**, and/or **146d**, to control a flow of energy in the energy system such as between energy storage devices. For example, the vehicle management system **140** may communicate a signal to the switch **146a** to transition to a closed state in which the energy storage device **141** is in electrical communication with the energy storage device **145** and configured to transmit energy to the energy storage device **145**. As another example, the vehicle management system **140** may communicate a signal to the switch **146a** to transition to an open state in which the energy storage device **141** is not in electrical communication with the energy storage device **145** and in which energy does not flow from the energy storage device **141** to the energy storage device **145**. The vehicle management system **140** may control energy flow from the energy storage device **141** to the energy storage device **145** (e.g., by controlling switch operation) based at least in part on information from the voltage sensor **142**, the current sensor **144**, and/or according to one or more operational settings. The vehicle management system **140** may similarly control operation of switch(es) **146b**, **146c**, and/or **146d**.

(84) The vehicle management system **140** may be in communication with a server (e.g., OSS)

remote to the vehicle management system **140** and/or remote to the vehicle. The vehicle management system **140** may communicate data to the remote server. The vehicle management system **140** can communicate data relating to the operation of the energy system **150**. For example, the vehicle management system **140** may communicate operational settings. As another example, the vehicle management system **140** can communicate voltages such as voltages detected by the voltage sensor **142**, such as voltages at, and/or voltage differentials between, the energy source **155**, any of the energy storage devices **141**, **143**, **145**, **147**, and/or the load **157**. As another example, the vehicle management system **140** can communicate currents or amperage flowing through the energy system **150**, such as currents detected by the current sensor **144**. As another example, the vehicle management system **140** can communicate an estimated remaining operating time of an energy storage device **141**, **143**, **145**, **147**, such as indicators of how long an energy storage device has sufficient energy to continually power the vehicle at a current operational status. As another example, the vehicle management system **140** can communicate an estimated remaining operating distance of an energy storage device **141**, **143**, **145**, **147**, such as the distance over which an energy storage device may continue to operate. As another example, the vehicle management system **140** can communicate data relating to the operation of switch(es) **146b**, **146c**, and/or **146d**, such as whether a switch is open or closed, an amount of time a switch has been open or closed, a schedule of when the switches are scheduled to open or close, or the like.

(85) The vehicle management system **140** can communicate data relating to the operation of the vehicle. For example, the vehicle management system **140** may communicate a distance traveled by the vehicle such as “continuously”, or total distance travelled since a particular time or location, or total distance travelled ever. As other examples, the vehicle management system **140** may communicate a time the vehicle has been operating such as operating continuously, a vehicle's velocity, a vehicle's location, a desired destination, an estimated remaining operating time or distance of the vehicle given the energy status of the energy storage device(s) of the vehicle, an indication of whether the vehicle is expected to arrive at a desired destination given the energy status of the energy storage device(s) of the vehicle.

(86) The vehicle management system **140** may receive from a remote server operational settings data which may include one or more executable software instructions that when executed by a hardware processor are configured to control an operation of the vehicle management system **140** and/or an operation of one or more of the components in communication with the vehicle management system **140**.

(87) In one example implementation, the vehicle management system **140** receives operational settings data from a remote server relating to controlling a switch such as any of switches **146a**, **146b**, **146c**, and/or **146d** (e.g., transitioning between open and closed states). In some embodiments, the vehicle management system **140** can receive operational settings data that when executed cause the vehicle management system **140** to perform an operation immediately (e.g., at a substantially same time as when the vehicle management system **140** receives the operational settings data). For example, the vehicle management system **140** may generate and transmit a signal to the switch **146a** to cause the switch **146a** to transition between an open and closed state immediately after receiving and executing operational settings data. In some embodiments, the vehicle management system **140** can receive operational settings data that when executed cause the vehicle management system **140** to perform an operation at a future time (e.g., at a time that is after the vehicle management system **140** receives the operational settings data). For example, the vehicle management system **140** may receive and execute operational settings data that causes the vehicle management system **140** to generate and transmit a signal to the switch **146a** to cause the switch **146a** to transition between an open and closed state whenever certain conditions are satisfied for an indefinite amount of time moving forward (e.g., until the vehicle management system **140** receives updated operational settings data). For example, the operational settings data, when executed, may cause the vehicle management system to cause the switch **146a** to transition

between an open and closed state whenever the vehicle has travelled a certain distance, when a voltage of one or more energy storage devices reaches a threshold value, when a load of the vehicle (e.g., a motor) is demanding a certain current draw from an energy storage device, when an energy generation system of the vehicle is operating or producing a threshold amount of energy, or the like.

(88) Example Energy Storage Devices

(89) The energy storage device **141** may include one or more capacitors such as ultracapacitor(s) and/or supercapacitor(s). The energy storage device **141** may include one or more batteries, such as a lithium-ion battery, lithium-polymer battery, alkaline battery, lead-acid battery, or the like. In some implementations, the energy storage device **143** may be a same or similar type of device as the energy storage device **141** and/or may include similar operational ratings. In some implementations, the energy storage device **143** may be a different type of device than energy storage device **141** and/or may include different operational ratings. The energy storage device **143** may optionally be electrically coupled with the energy storage device **141** such as in series and/or parallel. In some implementations, the energy storage device **143** may not be directly electrically coupled with the energy storage device **141**.

(90) The energy storage device **143** may be removably mechanically and/or electrically coupled with the energy system **150** and/or components thereof, such as the energy source **155**, energy storage device **141**, energy storage device **145**, energy storage device **147**, etc. The energy storage device **143** may be removable electrically coupled with the energy system **150** via a mechanical connection. For example, the energy storage device **143** may establish an electrical connection with the energy system **150** a via friction fit.

(91) The energy storage device **143** may have a high amp-hour rating. For example, the energy storage device **143** may have an amp-hour rating of less than 10 Ah, less than 25 Ah, less than 50 Ah, less than 75 Ah, or less than 100 Ah. The energy storage device **143** may have a higher amp-hour rating than the energy storage device **141**. The energy storage device **143** may have low voltage rating. For example, the energy storage device **143** may have a voltage rating of less than 1V, less than 5V, less than 10V, less than 20V, or the like. The energy storage device **143** may have a lower voltage rating than the energy storage device **141**. In some implementations, the energy storage device **143** may have a same or similar watt-hour rating as the energy storage device energy storage device **141**, where watt-hour rating is equal to the amp-hour rating multiplied by the voltage rating. The following table is provided as a non-limiting example of one implementation:

(92) TABLE-US-00001 Watt-hours Amp-hours Voltage energy storage device 141 720 Wh 20 Ah 36 V energy storage device 143 720 Wh 60 Ah 12 V

(93) As shown in the example above, the energy storage device **141** may have a voltage rating of 36V, an amp-hour rating of 20 Ah, and a watt-hour rating of 720 Wh. The energy storage device **143** may also have a watt-hour rating of 720 Wh with a voltage rating of 12V, an amp-hour rating of 60 Ah. In some implementations, the energy storage device **143** may have a different watt-hour rating than the energy storage device **141**.

(94) Advantageously, the energy storage device **141** and the energy storage device **143** can provide a large voltage and a large current to the energy storage device **145**. For example, the energy storage device **141** may be configured with a large voltage rating (e.g., relative to the energy storage device **143**) and the energy storage device **143** may be configured with a large amp-hour rating (e.g., relative to the energy storage device **141**). Advantageously, the energy storage device **143** increases the amount of amperage provided to the energy storage device **145** without unnecessarily increasing voltage which may be costly and require large amounts of space. For example, with reference to the example table provided above, energy storage device **141** may be electrically coupled to energy storage device **145** and can provide 20 Ah and 36V thereto. If a user desires to increase the amperage provided to the energy storage device **145** by an additional 60 Ah, rather than purchase and install three additional energy storage devices similar to energy storage

device **141** (e.g., $3 \times 20 \text{ Ah} = 60 \text{ Ah}$), the user would only have to purchase and install the single energy storage device **143** to obtain the desired additional 60 Ah. In some implementations, a user may combine a plurality of energy storage devices **143** to achieve a desired amp-hour rating.

(95) The energy storage device **143** may include one or more cells. A cell may be an anode and cathode separated by an electrolyte used to produce a voltage and current. The cells may be arranged in series and/or parallel. In some implementations, the cells of energy storage device **143** may be arranged in parallel which may yield a relatively high amp-hour rating of the energy storage device **143** and a relatively low voltage rating of the energy storage device **143**. The energy storage device **141** may include one or more cells. The cells may be arranged in series and/or parallel. In some implementations, the cells of energy storage device **141** may be arranged in series which may yield a relatively high voltage rating of the energy storage device **141** and a relatively low amp-hour rating of the energy storage device **141**.

(96) The energy storage device **143** may have a high C rating. For example, the energy storage device **143** may have a C rating of less than 5 C, less than 10 C, less than 20 C, less than 30 C, less than 40 C, less than 50 C, less than 100 C, or less than 150 C. The energy storage device **143** may have a higher C rating than the energy storage device **141**. A high C rating may facilitate faster charge and/or discharge times of the energy storage device **143**. For example, the energy storage device **143** may be configured to discharge a large amount of current while maintaining a substantially constant voltage. The energy storage device **143** may have a high maximum current output where maximum current output is equal to C rating multiplied by amp-hour rating. The energy storage device **143** may have a high continuous charge/discharge current, and/or a high burst charge/discharge current.

(97) The energy storage device **143** may have a high E rating. The energy storage device **143** may have a higher E rating than the energy storage device **141**. The energy storage device **143** may have a high specific power. The energy storage device **143** may have a higher specific power than the energy storage device **141**.

(98) The energy storage device **143** may be electrically coupled with the energy storage device **145** via one or more high voltage wires or cables configured to hold a large voltage. The energy storage device **143** may be electrically coupled with the energy storage device **145** via one or more low voltage wires or cables and/or which may be configured to conduct a large current.

(99) FIG. 2 is a block diagram illustrating an example vehicle component **200** of a vehicle that may be provisioned over-the-air. The vehicle component **200** may comprise any of the example components described herein, for example with reference to FIGS. 1A-1D, such as an energy storage device, a generation system, a motor, a vehicle management system, a driven mass or roller system, or a component interface device. In some embodiments, the vehicle component **200** may comprise a vehicle management system. In some embodiments, the vehicle management system may control how other components of the vehicle operate, for example, according to executable software instructions on a processor of the vehicle management system. The vehicle management system can receive operational settings data to update, replace, edit and/or revise the executable software instructions to thereby alter its own operation and/or the operation of any of the other components in the vehicle.

(100) In some embodiments, the vehicle component **200** may comprise a component interface device. In some embodiments, the component interface device may facilitate an operational compatibility between two or more components, for example as described with reference to FIG. 1B. The component interface device can receive operational settings data to update, replace, edit and/or revise executable software instructions included thereon to thereby alter its own operation, for example, to configure the component interface device to facilitate operational compatibility between new, additional or replacement components.

(101) In some embodiments, a vehicle may comprise multiple components that include structural and/or operational features similar to those shown in example vehicle component **200**. For example,

a battery of a vehicle as well as a vehicle management system of a vehicle as well as a component interface device may all include structural and/or operational features for communicating with a server and receiving and storing operational setting data as described herein. In some embodiments, components of a vehicle with structural and/or operational features for over-the-air provisioning may each communicate with a server independently from all other components of the vehicle or may communicate in a coordinated manner such that their communication is organized or controlled, for example, by the vehicle managements system. In some embodiments, components of a vehicle with structural and/or operational features for over-the-air provisioning may each communicate with a unique server or with the same server.

(102) The vehicle component **200** can include a transceiver **205**, a wireless communicator **210**, a processor **215**, a storage medium **220** and a memory **225**. The transceiver **205** may be connected to the wireless communicator **210** which can comprise an antenna or other similar device for facilitating communicating data to and from a remote server (e.g., OSS described herein). As used herein, phrases referring to communicating with the vehicle (such as sending requests from a vehicle to a server or receiving settings data from a server) may comprise communicating with a component of the vehicle such as example component **200**.

(103) The transceiver **205** can be connected to a processor **215** that can control the operation of the vehicle component **200**, including the operation of the transceiver **205**. The storage medium **220**, which may be removable, read-only, or read/write media and may be magnetic-based, optical-based, semiconductor-based media, or a combination of these, may store operating system software for the vehicle component **200** and may also store at least some settings data. The memory **225** may store additional, information, such as applications that may be loaded into the vehicle component **200**. In addition, some or all of the settings data for the vehicle component **200** may be stored in the memory **225**. Both the memory **225** and the storage medium **220** can be connected to the processor **215**. The processor **215** may operate in accordance with executable software, applications, or other instructions stored in the memory **225** and/or the storage medium **220**.

(104) In some implementations, memory **225** and/or storage medium **220** may store pre-configured instructions for executing operational settings in a vehicle. In some implementations, the memory **225** and/or storage medium **220** may store instructions for executing an application or program to allow a user to interact with the component **200**, for example to request or select operational settings. In some implementations, the memory **225** and/or storage medium **220** may store instructions for communicating with a remote server, for example to retrieve settings data therefrom or to send requests thereto.

(105) FIG. 3 is a block diagram illustrating an example system **300** for over-the-air provisioning of a vehicle's operational settings. A vehicle **325** (and/or user **340**) and operational settings server (OSS) **305** may be in communication with each other, for example, via a wireless communications path which may allow geographically dispersed devices, systems, databases, servers and the like to connect (e.g., wirelessly) and to communicate (e.g., transfer data) with each other. For example, in some embodiments, the vehicle **325** (and/or user **340**) and OSS **305** may communicate with each other via a wireless network which may comprise a local area network (LAN), a personal area network (PAN) a metropolitan area network (MAN), a wide area network (WAN) or the like. In some embodiments, the vehicle **325** (and/or user **340**) and OSS **305** may communicate with each other via radio waves transmitted via antennas, satellites, Bluetooth technology or the like. In some embodiments, the vehicle **325** (and/or user **340**) and OSS **305** may communicate with each other using any combination of the foregoing examples.

(106) The vehicle **325** (and/or user **340**) may communicate data (e.g., via a wireless communication path) to the OSS **305**. For example, the vehicle **325** (and/or user **340**) may send requests to the OSS **305** for operational settings data. The requests can include general requests for operational settings data and/or requests for specific operational settings data. The user **340** may send requests to the OSS **305** for operational settings options. The vehicle **325** (and/or user **340**)

may send information relating to operational settings data currently included in the vehicle to inform the OSS **305** of the operational settings data possessed by the vehicle such as which settings data or which versions of settings data are possessed by the vehicle.

(107) In some embodiments, the vehicle **325** (and/or user **340**) may communicate data (e.g., via a wireless communication path) to the OSS **305** relating to an operation or status of the vehicle. For example, the vehicle **325** may communicate to the OSS **305** information relating to a charge status of the vehicle, a charges status of one or more energy storage devices of the vehicle, a geographical location of the vehicle, a geographic location of a desired destination, an estimated time and/or distance the vehicle may continue to operate (e.g., with a certain charge status), a distance travelled by the vehicle, or the like.

(108) The OSS **305** may communicate data (e.g., via a wireless communication path) to the vehicle **325** (and/or user **340**). For example, the OSS **305** may send operational settings data to the vehicle **325** to control one or more operations of the vehicle (e.g., energy status, energy generation status, or the like). The OSS **305** may send data relating to operational settings options to a user **340** for example to provide information to the user **340** relating to which operational settings are available for download to the vehicle **325** so that the user **340** may select which operational settings to download to the vehicle **325**. In some embodiments, the OSS **305** may communicate with a user **340** via one or more of a phone, a computing device, a tablet, a vehicle navigation system or control system, or the like. For example, the OSS **305** may transmit a text message to a phone of a user **340**. As another example, the OSS **305** may transmit a message to a control dashboard of a vehicle to be read by a user. As another example, the OSS **305** may communicate an email to a user **340** (e.g., to notify the user that the OSS **305** and/or billing server **335** has charged the user). In some implementations, the vehicle **325** (e.g., a vehicle management system of the vehicle) may communicate to the OSS **305** a charge status of the vehicle, a geographic location of the vehicle, and/or a desired geographic destination.

(109) Operational settings data may be stored on an operational settings server (OSS) **305** and transmitted (e.g., via wireless communication) to the vehicle **325**. When operational settings are downloaded from the OSS **305**, the OSS **305** can collect download event information and send it to a transaction manager **330**. The download event information can include the time of the download, the settings data that was downloaded, the reason for the download, the vehicle and/or user associated with the download etc. The transaction manager **330** can combine the download event information with other information, such as operational settings pricing structure and developer data for the downloaded operational settings, to produce usage records. The transaction manager **330** can send the usage records to a billing server **335**, which may perform billing services, such as generating invoices. In some embodiments, the billing server **335** may issue a charge to a user according to the operational settings data transmitted from the OSS **305** to a vehicle associated with the user. For example, the billing server **335** (and/or the OSS **305**) may charge a user depending on the number and/or types of operational settings data downloaded from the OSS **305** to a vehicle related to the user (e.g., associated with an account of the user). In addition, the billing server **335** may allow an operational settings developer, and/or a third party **315a** associated with the OSS **305** to run a report and find out how many users have downloaded and/or are subscribing to a particular service offering or operational setting.

(110) The OSS **305** may be associated with a particular operator or with a third party **315a**. In some implementations, the OSS **305** may be operated by a third party **315a** that offers the operational settings for a variety of vehicle and/or vehicle component types, for example according to different manufacturers according to their respective various requirements and specifications. In some implementations, the OSS **305** may be operated by multiple third parties **315a-315b** that each provide unique operational settings, for example each according to a different vehicle type and/or vehicle component or component type.

(111) In some embodiments, the OSS **305** may offer pass-through access to third party operational

settings data, such that the operational settings are stored and managed on a server associated with the third party **315a**. In some embodiments, most or all of the available applications may be stored and managed on the OSS **305**. The operator of the OSS **305** may have agreements with the third parties **315a-315b** to offer the operational settings and to provide for payment to the third parties **315a-315b**.

(112) In some embodiments, the OSS **305** may communicate data (e.g., via a wireless communication path) to the third parties **315a-315b**. For example, the OSS **305** may send data relating to the vehicle, such as a vehicle operation status, to the third parties **315a-315b** to communicate one or more operations of the vehicle (e.g., energy status, energy generation status, or the like). The OSS **305** may communicate data (e.g., via a wireless communication path) to the third parties **315a-315b** based on third party rules. The third party rules may dictate which data the third parties **315a-315b** are to receive. The third party rules may dictate when the third parties **315a-315b** are to receive the data. The third party rules may dictate how the third parties **315a-315b** are to receive the data, such as format of the data. The third party rules may be different for each of the third parties **315a-315b**. For example, third party **315a** may have third party rules indicating that third party **315a** is to receive data regarding energy generation status of an on-board power generation system of a vehicle while third party **315b** may have third party rules indicating that third party **315b** is to receive data regarding energy status of an energy storage device of a vehicle. In some implementations, the vehicle **325**, such as a vehicle management system of the vehicle **325**, may communicate directly with the third parties **315a-315b**. For example, the vehicle **325** may directly communicate data relating to the vehicle to the third parties **315a-315b** according to the third party rules. While only third party **315a** and third party **315b** are depicted, it will be appreciated that only one third party may be in communication with the OSS **305** or that more than two third parties may be in communication with the OSS **305**.

(113) The third parties **315a-315b** may include one or more computing devices configured to communicate with other computing devices such as via wireless communication. The third parties **315a-315b** may include one or more servers. The third parties **315a-315b** may include an entity, organization, individual, or the like. The third parties **315a-315b** may be interested in receiving data relating to an operation of a vehicle. The third parties **315a-315b** may include a vehicle manufacturer that may be interested in receiving data relating to an operation of the vehicle's that it manufactures. The third parties **315a-315b** may include a parts manufacturer, such as an energy storage device manufacturer, or power generation system manufacturer that may be interested in receiving data relating to an operation of the vehicle parts that it manufactures. The third parties **315a-315b** may include a government entity that may be interested in receiving data relating to vehicle operation to improve safety measures relating to vehicular traffic safety. The third parties **315a-315b** may include an operational settings provider to develop software for implementing operational settings data that may be interested in receiving data relating to the performance of the operational settings in a vehicle. The third parties **315a-315b** may include a data collection organization that is interested in receiving data on a large scale, such as from numerous vehicles, to perform big data analytics, such as to develop consumer related analyses. The third parties **315a-315b** may include individuals, such as owners of vehicles, that may be interested in receiving data relating to the operation of their own vehicle(s).

(114) Example Operational Settings of an Electric Vehicle

(115) A vehicle or its components may operate according to various operational settings. Operational settings data (e.g., executable software instructions) may be downloaded to a vehicle component and may affect the how the component functions or operates. Examples are provided of various operational settings that may pertain to the various components of a vehicle.

(116) Operational settings data may affect how an energy storage device, such as a battery of a vehicle operates. For example, operational settings data can affect the rate at which a battery charges or discharges, the maximum or minimum voltage (e.g., energy charge) that a battery may

hold, whether a battery is charged or not charged, the conditions under which a battery is charged, when to start or stop charging a battery and the like. Operational settings data can affect where energy is stored, for example in vehicles including more than one energy storage device such as multiple batteries, multiple capacitors or batteries and capacitors. For example, according to one operational setting a vehicle may store energy in a first battery before storing energy in a second battery and vice versa according to a different operational setting. As another example, according to one operational setting, a vehicle may store energy in a capacitor before storing energy in a battery and vice versa according to a different operational setting. As another example, according to one operational setting, one energy storage device (e.g., capacitor) may receive and store energy until a certain threshold is reached that is defined by the operational setting before discharging energy into another energy storage device.

(117) Operational settings data may affect how an energy generation system of a vehicle operates. For example, operational settings data can affect a rate at which an energy generation system generates energy, when it generates energy, when it starts or stops generating energy, where to store or transfer generated energy and the like. For example, according to one operational setting, an energy generation system may generate energy only when the vehicle is accelerating (positive acceleration or negative acceleration) and according to another operational setting, an energy generation system may generate energy only when the vehicle is experiencing constant velocity and zero acceleration.

(118) Operational settings data may affect how a motor of a vehicle operates. For example, operational settings data can affect a rate at which the motor consumes energy, the sources from which the motor draws energy such as from a battery or a capacitor, and the like. As an example, according to one operational setting, the motor may draw energy at a certain rate from a first energy storage device under certain conditions and may draw energy at a certain rate from a second energy storage device under different conditions.

(119) Operational settings data may affect how a vehicle management system of a vehicle operates. For example, operational settings data can affect how a vehicle management system interacts with and/or controls other components of a vehicle. As an example, according to one operational setting, the vehicle management system may manage a vehicle's energy (e.g., generation, storage, consumption) in one way and in a different way according to a different operational setting. In some embodiments, a vehicle management system may control energy flow between components of a vehicle (e.g., between a capacitor and a battery) via a switch according to operational settings data. In some embodiments, the operational settings data for controlling operation of the switch may include any number of criteria and/or conditions for operating the switch (e.g., transition between open and closed states). Criteria and/or conditions can include battery voltage, capacitor voltage, battery amperage (e.g., delivered to a load), capacitor amperage (e.g., receive from an energy source), or the like. In some embodiments, the operational settings data for controlling operation of the switch may include logic based on levels, changes, rates of change, changes in rate of change, etc., present values and/or historical values of any of the preceding example criteria or conditions. In some embodiments, criteria and/or conditions of an operational setting can include geographical location of the vehicle, a distance travelled by the vehicle, a distance between the vehicle and a desired destination, or the like. As an example, a vehicle management system may cause a switch to transition to a closed state to allow energy to flow between energy storage devices every time the vehicle travels a certain distance (e.g., 10 miles, 30 miles, 100 miles, or the like).

Example Implementation

(120) In an example implementation, the vehicle **325** may communicate to the OSS **305** that the vehicle **325** is 10 miles from a desired destination (e.g., home) and that a battery of the vehicle has sufficient energy to continue to power the vehicle at a current operational status for 5 more miles before discontinuing operation due to low charge. In response, the OSS **305** can transmit a communication to the user **340** (e.g., via a text message to a phone of the user, via a message to a

control dashboard of the vehicle **325**, or the like) to notify the user **340** that they are 10 miles away from a destination and that the battery of the vehicle **325** only has sufficient charge to operate the vehicle **325** for another 5 miles. The OSS **305** may provide operational settings options to the user **340** which can include, for example, an option to flow energy into a battery to charge the battery to increase the range of the vehicle (e.g., from 5 to greater than 10 miles) so that the vehicle may reach the desired destination, an option to enter a power saving mode, an option to initiate operation of a power generation system (e.g., rollers in extended position) to generate energy to be slowed into the battery, or the like. In some implementations, the operational settings options may be simplified to be easy to understand by a user **340**. For example, the operational settings options may be a question such as "Do you want to extend vehicle range by an additional 10 miles?" In some implementations, the operational settings options may not reflect entirely the operational settings data that would correspond thereto. For example, a user **340**, when reviewing operational settings options, may not care about every detail of the operational settings data that would be necessary to effectuate the operational settings options. In some implementations, the OSS **305** may determine the operational settings data that correspond most accurately to the selected operational settings options to most effectively implement the selected options. The user **340** may communicate a selected operational settings option to the OSS **305** (e.g., via text message or the like). In response to receiving the user's **340** selected option, the OSS **305** may generate operational settings data corresponding to the selected option to transmit to the vehicle **325** to cause the vehicle to operate according to the selected operational setting. For example, the OSS **305** may transmit operational settings data to the vehicle **325** to cause a vehicle management system to electrically connect a capacitor module to a battery (e.g., via a switch) to flow energy from the capacitor to the battery and/or to cause an energy generation system (e.g., roller(s). driven mass(es)) to transition to an extended position to generate energy to be flowed into the battery.

(121) Operational settings data may affect operational compatibility between various components of a vehicle. For example, operational settings data may configure one component to interface (e.g., electrically couple and communicate) with another component. For example, operational settings data may allow a vehicle management system to interface with any of the other components. As an example, a new component that is installed or included in the vehicle may operate according to manufacturer's specifications and may as a result not function properly (or at all) with other components of the vehicle. The new component or other components of the vehicle may download operational settings data to allow the new component to interface with the other components of the vehicle.

(122) Operational settings data may affect how one or more driven masses operate. Operational settings data may control operation of a driven mass based on one or more factors, including for example, the amount of energy being generated by rotation of the driven mass, the velocity of the vehicle, the air pressure of the driven mass, a motion of the driven mass (e.g., vertical motion caused by uneven terrain), a geographic location of the vehicle, a distance travelled, by the vehicle, a desired destination, and the like. As an example, operational settings data may control the circumstances under which a driven mass is in an extended position (e.g., in contact with the ground) or in a retracted position (e.g., not in contact with the ground). For example, according to certain operational settings data, a driven mass may be in an extended position when the vehicle is traveling in excess of a threshold velocity. As another example, operational settings data may control the conditions under which a driven mass transitions between an extended or retracted position, such as based on whether a threshold amount of energy is being generated by rotation of the driven mass. As another example, operational settings data may control the force with which a driven mass is exerted onto a ground surface. For example, according to certain operational settings data, a driven mass may be applied to a ground surface with greater force (e.g., when a ground surface is uneven) to ensure continual contact with the ground surface, and may be applied to the ground surface with less force (e.g., when the ground surface is flat). The force with which a driven

mass is applied to the ground, and/or position of the driven mass may be adjusted or controlled according to the operational settings data by one or more structural features of (e.g., associated with) the driven mass, including, for example, flexible arms, mechanical springs, gas springs, pistons, suspension systems, shafts, struts, hydraulics, pneumatics, levers, gears, pulleys, actuators, hinges, pivots, joints, or the like.

(123) Operational settings data may affect how one or more rollers operate. Operational settings data may control operation of rollers based on one or more factors, including for example, the amount of energy being generated by rotation of the roller, the velocity of the vehicle, the air pressure of a wheel with which a roller is in contact, a motion of a wheel with which the roller is in contact (e.g., vertical motion caused by uneven terrain), a geographic location of the vehicle, a distance travelled, by the vehicle, a desired destination, and the like. As an example, operational settings may control the circumstances under which a roller is in an extended position (e.g., in contact with a wheel of a vehicle) or in a retracted position (e.g., not in contact with the wheel). For example, according to certain operational settings data, a roller may be in an extended position when the vehicle is traveling in excess of a threshold velocity. As another example, operational settings data may control the conditions under which a roller transitions between an extended or retracted position, such as based on whether a threshold amount of energy is being generated by rotation of the roller. As another example, operational settings data may control the force with which a roller is exerted onto a wheel. For example, according to certain operational settings data, a roller may be applied to a wheel with greater force such as when a ground surface is uneven and the wheel is experiencing significant vertical motion to ensure continual contact with the wheel throughout a range of vertical motion, and may be applied to the wheel with less force such as when the ground surface is flat and the wheel is experiencing minimal vertical motion. As another example, the force with which a roller is applied to a wheel and/or position of the roller may be adjusted based on the wheel air pressure (e.g., increase force to ensure roller contacts wheel when wheel air pressure is low, or transition to retracted position when substantial contact between roller and wheel cannot be achieved due to low wheel air pressure, and the like). The force with which a roller is applied to the wheel, and/or position of the roller may be adjusted or controlled according to the operational settings data by one or more structural features of (e.g., associated with) the roller, including, for example, flexible arms, mechanical springs, gas springs, pistons, suspension systems, shafts, struts, hydraulics, pneumatics, levers, gears, pulleys, actuators, hinges, pivots, joints, or the like.

(124) Operational settings data may affect how an autonomous driving system of a vehicle operates. For example, a remote server may periodically update an autonomous driving system (e.g., with the most recent algorithms, data, or the like) by provisioning the vehicle with the latest operational settings data relating to the autonomous driving system. Advantageously, complex operational systems of the vehicle (e.g., autonomous driving systems) may remain up-to-date by fast and simple provisioning of operational settings data without the need for costly and lengthy hardware updates. Operational settings data may similarly affect other systems of the vehicle such as navigational systems.

(125) In certain embodiments, one or all of the components of a vehicle may not be configured for over-the-air provisioning. In such embodiments, a component interface device may advantageously be used to facilitate operational compatibility between components, for example rather than directly provisioning the components themselves. For example, a component interface device may be installed in a vehicle and may be provisioned (e.g., over-the-air) with various operational settings data as required or desired to configure the component interface device to integrate and operate with other components of the vehicle and to facilitate operational compatibility between any of the other components in the vehicle such as between a vehicle management system and an energy storage device.

(126) In some embodiments, a component interface device may be used when the other

components of the vehicle are configured for over-the-air provisioning.

(127) Advantageously, provisioning vehicle components may reduce the need for costly, technical or otherwise challenging servicing of the vehicle (e.g., mechanical or electrical fixes) to allow for a new component to integrate in a vehicle such as when a new battery is installed. Provisioning may also allow for components to be installed in a vehicle that would otherwise not be able to integrate and function in said vehicle. For example, by provisioning vehicle components with operational settings data, components from various manufacturers that would otherwise not be capable of functioning together, may be integrated into a vehicle and operate according to a desired manner.

(128) Operational settings data may affect functionality of other computer-based components of a vehicle, such as navigation, stereo, driver assistance systems and the like. Operational settings data may comprise software patches or fixes such as for disabled vehicle components or vehicle components that are not functioning correctly.

(129) Example Methods for Over-the-Air Provisioning

(130) FIGS. 4-7A are flowcharts illustrating example processes for over-the-air provisioning of a vehicle's operational settings. Various methods may exist for the over-the-air provisioning of a vehicle's operational settings. For example, the operational settings may be provisioned automatically on a periodic basis, the operational settings may be provisioned in response to a request (such as from a user or vehicle), or in response to a detected new vehicle component or in response to detected altered operation of the vehicle or in response to some other input. As further examples, a vehicle's operational settings may be provisioned during an initial configuration of the vehicle and/or the vehicle's operational settings or may be provisioned when new operational settings are available. The example processes shown in FIGS. 4-7A are provided as example and are not intended to be limiting. In some embodiments, the flowcharts may include more or less blocks than what are shown in the FIGS.

(131) FIG. 4 is a flowchart illustrating an example **400** process for over-the-air provisioning of a vehicle's operational settings. Example process **400**, or any portion thereof, may be implemented on a server that may be remote to the vehicle, such as OSS described with reference to FIG. 3. At block **401**, the server may receive a request for operational settings data from the vehicle. In some embodiments, the request may be a general request, for example a request for all available operational settings data or the request may be a specific request for specific operational settings data. In some embodiments, the vehicle may transmit the request upon an initial configuration of the vehicle or its various components. In some embodiments, the vehicle may transmit the request automatically on a periodic basis, for example, to continually check if the vehicle has received the most up-to-date operational settings. In some embodiments, at block **401**, the server may receive a request from a user. In some embodiments, the request may be received via wireless communication. In some embodiments, the request may be communicated to the server from a component of the vehicle such as a vehicle management system of the vehicle or a component interface device of the vehicle.

(132) At block **403**, the server may check if operational settings data is available. For example, the vehicle may have requested any available updated settings data and the server, at block **403**, may check if any updated settings data is available or if the vehicle has the most updated settings data already. If settings data is available, the server may proceed to block **405** and if not, may proceed to block **401**.

(133) At block **405**, the server may send operational settings data to the vehicle or component thereof, such as a vehicle management system or a component interface device. The settings data may be sent to the vehicle over a wireless communications path. In some embodiments, the operational settings data sent at block **405** may include all settings data available on the server or a subset thereof, such as specific operational settings data in response to a request for specific operational settings data.

(134) FIG. 5 is a flowchart illustrating an example process **500** for over-the-air provisioning of a

vehicle's operational settings. Example process **500**, or any portion thereof, may be implemented on a server that may be remote to the vehicle, such as OSS **305** described with reference to FIG. **3**. The communications between the user, server, and vehicle as described in example process **500** may be done via a wireless communications path.

(135) At block **501**, the server may optionally receive a request from a user for operational settings options. For example, a user may desire to view one or more operational settings available for a vehicle or components of a vehicle.

(136) At block **502**, the server may optionally receive information relating to a vehicle operation and/or status. In some embodiments, the server may receive said information from vehicle management system. For example, a vehicle management system may transmit to the server, a status of current operational settings data of the vehicle, a charge status of the vehicle, an energy generation status of the vehicle, operating conditions of the vehicle, estimated remaining battery life or operating time of the vehicle, or the like.

(137) At block **503**, the server may send data relating to operational settings options to the user. This may allow a user to view one or more operational settings that are available for download to the vehicle from the server. The server may communicate the operational settings options to the user via one or more of a text message, email message, internet message, or the like.

(138) At block **505**, the server may receive a selection of an operational setting from the user. For example, the user, after having reviewed available operational settings, may select one or more of the available settings and send a request to the server to download to the vehicle said operational setting(s).

(139) At block **507**, the server may send, to a vehicle, operational settings data corresponding to the option selected by the user.

(140) At block **509**, the server may optionally update one or more of a history log, a user account, and/or billing records. For example, in response to sending the operational settings data to the vehicle, the server may record to a history log the details of the transaction (e.g., time, which settings were downloaded, etc.) and may generate a charge to the user for the transaction.

(141) FIG. **6** is a flowchart illustrating an example process **600** for requesting operational settings data from a server. Example process **600**, or any portion thereof, may be implemented on a component a vehicle such as example component **200** described with reference to FIG. **2** herein, for example on a processor of the component. In some embodiments, example process **600** can be implemented on a processor of a vehicle management system or a component interface device.

(142) At block **601**, a processor of vehicle component (e.g., vehicle management system or a component interface device) may monitor the components of a vehicle. For example, the processor of a particular vehicle component (e.g., vehicle management system or a component interface device) may be in communication with other components of the vehicle. The processor may monitor the components of the vehicle to detect whether vehicle components have been added to the vehicle (e.g., established a new communication with the processor) and/or removed from the vehicle (e.g., terminated an existing communication with the processor).

(143) At block **602**, the processor may determine if a new vehicle component has been detected. For example, the processor may detect when a vehicle battery has been replaced with a different vehicle battery (e.g., a new battery of the same type as the old battery or a new battery of a different type than the old battery). As another example, the processor may detect a component that has never before been included in the vehicle, such as a second additional battery, where the vehicle has only ever had one battery, or some other additional energy storage device such as an ultracapacitor. If the processor detects a new component, the processor may proceed to block **603**.

(144) At block **603**, the processor may determine whether operational settings data is required or desired for the component detected at block **602** to operate properly within the vehicle. For example, the new component or other components of the vehicle may require a more up-to-date version of operational settings and/or new operational settings data for the new component to

function properly or optimally with the vehicle and the vehicle's other components. If settings data is not required or desired, the processor may return to block **601** and if settings data is required or desired for the new component or other components, the processor may continue to block **605**. (145) At block **605**, the processor may send a request (e.g., to a remote server) for the operational settings data that is required and/or desired. The processor may communicate with the server via a wireless communications path. In response to the request, the remote server may send the operational settings data to the vehicle as described elsewhere herein, for example according to the examples provided. In some embodiments, the operational settings data may be sent to the component of the requesting processor (e.g., vehicle management system, component interface device) and/or to another component such as the new component, for example, if the new component is configured for over-the-air provisioning.

(146) FIG. 7A is a flowchart illustrating an example process **700** for sending operational settings data to a vehicle. Example process **700**, or any portion thereof, may be implemented on a server that may be remote to the vehicle, such as OSS described with reference to FIG. 3. At block **701**, the server may check the status of a vehicle's operational settings. For example, the server may check which settings data and/or which version of settings data is currently possessed by the vehicle. The server may check the status by querying the vehicle for data relating to its current operational settings (e.g., sending a request to the vehicle for information relating to the operational settings of the vehicle). The server may query the vehicle via a wireless communications path as described elsewhere herein. In some embodiments, the server may keep a history log of download event information and/or have access to such a log such as on a third-party server. The download event information such as recorded in a history log can include one or more of a time of transmitting operational settings data from the server to the vehicle, the operational settings data that have been transmitted from the server to the vehicle, a reason for transmitting operational settings data from the server to the vehicle, the identity of a vehicle sending the request to the server, the identity of a vehicle receiving the operational settings data from the server or the identity of a user sending the request to the server. The history log of download event information may allow the server to know which operational settings the vehicle currently has without having to query the vehicle.

(147) At block **703**, the server may determine whether operation settings are available for the vehicle. For example, the server may determine whether a more up-to-date version of the vehicles current operational settings data are available for the vehicle and/or may determine whether new operational settings data are available for the vehicle. The server may compare the vehicle's current operational settings with all operational settings included in the server or accessible by the server or a subset thereof. If the server includes or has access to more or different operational settings than what are currently included in the vehicle, this may indicate that new and/or more up-to-date operational settings are available for the vehicle that may be desirable and/or required for the vehicle or its components to operate (e.g., optimally). If, at block **703**, the server determines that operational settings are not available, the server may return to block **701**, and otherwise may proceed to block **705**.

(148) At block **705**, the server may send operational settings data to the vehicle. The operational settings data may include a more up-to-date version of the vehicle's current settings data and/or may include settings data that are new to the vehicle. The server may send the settings data to the vehicle via a wireless communications path as described elsewhere herein.

(149) FIG. 7B is a flowchart illustrating an example process **750** for communicating data to a third party. Example process **750**, or any portion thereof, may be performed by a hardware computer processor. For example, process **750**, or any portion thereof, may be implemented on a server that may be remote to the vehicle, such as OSS shown and/or described with reference to FIG. 3. As another example, process **750**, or any portion thereof, may be implemented by one or more computer processors of a vehicle such as by a vehicle management system of a vehicle. At block

711, the processor may access data relating to vehicle operation or status. In some implementations, the processor may retrieve the data from memory. In some implementations, the processor may receive the data, such as via a wireless communications path, from a remote computing device. For example, the processor may receive data from a vehicle such as from a vehicle management system. As another example, the processor may receive the data from a user (e.g., such as from a computing device operated by the user such as a smart phone). As another example, the processor may receive the data from a publicly available network (e.g., from an internet database). The data can include any of the example data discussed herein, such as any of the example data discussed with reference to FIGS. **1B-1D**, for example. The data can include publicly available information (e.g., weather conditions, road maps, traffic conditions, or the like).

(150) At block **713**, the processor may access third party rules. The third party rules may be associated with a third party. In some implementations, the processor may retrieve the third party rules from memory. In some implementations, the processor may receive the third party rules, such as via a wireless communications path, from a remote computing device, such as a remote server. In some implementations, the processor may access third party rules from multiple third parties. The third party rules may include instructions, settings, logic, parameters, preferences, conditions, or the like. The third party rules may dictate which data the third party is to receive from the processor. The third party rules may dictate how and/or when the third party is to receive the data. Third party rules may be set by respective third parties. For example, each third party may set specific preferences of which data that third party is to receive. The amount of control a third party has over the third party rules associated with the third party may vary. For example, a pay service may be implemented to vary the amount of control a third party may have to set or create third party rules. For example, the degree to which a third party has control to set their third party rules or the degree to which a third party has access to data may vary depending on the amount of money the third party has paid. In another example, the third parties may be on a tiered system where higher tiers are granted greater control or access through the third party rules (e.g., the longer a third party is subscribed to receive the data, the higher tier the third party is placed into). The third party rules may also include formatting information and timing preferences as to how the information should be presented to the third party and when the information should be presented to the third party.

(151) At block **715**, the processor can determine what data to communicate to a third party based on the third party rules. In some implementations, the processor may communicate less than all of the data accessed at block **711**. In some implementations, the processor may communicate all of the data accessed at block **711**. In some implementations, the processor may communicate additional data other than the data that is accessed at block **711**. The processor can prepare a dataset such as by creating a dataset including the data determined to be communicated to the third party. The dataset may be a copy of data that is accessed at block **711**.

(152) At block **717**, the processor can determine a format to communicate the dataset based on the third party rules. For example, the third party rules may dictate that data should be formatted in a table, a chart, a list, a graph, or any other format based on the third party preferences. As another example, the third party rules can also dictate formatting information such as date format (e.g., “mm/dd/yyyy” or “yyyy/mm/dd”), units of measurement, appearance of unit tags (e.g., ‘V’, “volts,” or no unit tag), and/or other types of formatting preferences. Accordingly, one third party may receive the same data as a different third party but in a different format based on each third party's third party rules. In some implementations, the processor may modify the data and/or determine related data to send based on third party rules. For example, the processor can determine which geographic location data to communicate based on third party rules, such as whether to communicate a vehicle's GPS coordinate data, a vehicle's street address location, a vehicle's zip code location, and/or a city name the vehicle is in, etc.

(153) At block **719**, the processor can optionally update the dataset based on the third party rules.

For example, the processor can reformat or restructure the data. For example, if the processor has determined that the third party rules dictate that dates should follow a “yyyy/mm/dd” format, the processor can update one or more dates in the data to that format. As another example, the processor can supplement the data with supplemental data. For example, the processor could add metadata to the data, such as tags for parsing or indexing the data. As another example, the processor can remove data from the dataset such as by cleaning the data. As another example, the processor can obfuscate the data such as by encrypting the data according to third party rules. Obfuscating the data may secure sensitive data such as by preventing access to the data except to an appropriate third party or other party with appropriate permissions to access the data.

(154) At block **721**, the processor can determine when to send the dataset based on third party rules. The processor may communicate data according to a schedule dictated by the third party rules. For example, the third party rules may dictate that the processor is to communicate data hourly, or daily, or weekly, etc. In another example, the third party rules may dictate that the processor is to communicate data at a specific time. In this example, the processor may not send the dataset until that time. In this way, a third party can control when they are sent the dataset (e.g., a third party in a different time zone may prevent the dataset from being sent at an inconvenient time such as during the night). In another example, the third party rules may dictate that the processor is to communicate data in response to a certain condition (e.g., a vehicle energy storage device is at a certain threshold energy level, the vehicle is at a particular geographic location, such as at home, the vehicle has been parked and turned off, the vehicle is plugged in and charging, etc.). In another example, the processor may communicate data in response to a request such as from a third party.

(155) At block **723**, the processor can communicate the dataset to a third party, such as to a third party computing device such as a server. For example, the processor can communicate the dataset via a wireless communication path as described elsewhere herein such as with reference to FIG. 3. The processor may communicate the dataset to a third party associated with the third party rules accessed at block **713**. In some implementations, the processor may communicate the dataset to a plurality of third parties. In some implementations, the processor may communicate a plurality of datasets to a plurality of third parties, such as a unique dataset to each respective third party.

(156) FIG. 8 is a diagram of an exemplary “fifth” wheel **802** configured to drive or power an on-board charging system (OBCS) **810** of a vehicle **800**. The fifth wheel **802** may also be referred to herein as a driven mass, roller, or the like. The term “fifth wheel” as used herein is not intended to be limiting and is used for illustrative and/or exemplary purposes only. For example, the fifth wheel **802** may be implemented in a vehicle with more than four or more than five wheels, such as a semi-truck or tractor-trailer. As another example, the fifth wheel **802** may be implemented in a vehicle with less than five wheels or less than four wheels, such as a motorcycle. The term “fifth wheel” is not intended to be limiting of the number of wheels of the vehicle in which the fifth wheel may be implemented. The OBCS can include one or more of a capacitor, battery, or other energy storage device. The fifth wheel **802** as shown is in an extended state such that the fifth wheel **802** is in contact with the ground or road surface and, thus, rotates while the vehicle **800** is in motion. The controller may extend or retract the fifth wheel **802** such that the fifth wheel **802** is not always in contact with the ground or road surface. In some embodiments, the fifth wheel **802** is replaced with or integrated as a small motor or geared component driven by a drive shaft, motor, wheel, or other driven component of the vehicle **800**. In some embodiments, the small motor or geared component may include a small fixed gear electric motor that rotates the shaft at a desirable rotations per minute (RPM). For discussion herein, the fifth wheel **802** will be described as being driven when in contact with the ground, though any other means of being driven (for example, the small motor or geared component driven by a drive shaft) is envisioned. As such, the fifth wheel **802**, whether in contact with the ground or integrated with another drive component within the vehicle **800**, rotates in response to the vehicle **800** being driven to move or otherwise moving. In some embodiments, although the fifth wheel **802** is in contact with the ground, the fifth wheel **802**

may not carry a significant portion of weight of the vehicle **800**. As such, in some embodiments, a minimal or small amount of drag will be created or caused by the fifth wheel **802**. A controller may be configured to control the amount of drag that the fifth wheel **802** creates (for example, how much pressure the fifth wheel **802** exerts downward on the road surface).

(157) The fifth wheel **802** is coupled to a drive shaft (herein referred to as the “shaft”) **806**. As the fifth wheel **802** rotates, the shaft **806** also rotates at a same, similar, or corresponding rate as the fifth wheel **802**. In some embodiments, the fifth wheel **802** and the shaft **806** may be coupled such that the shaft **806** rotates at a greater or reduced rate as compared to the fifth wheel **802**. In some embodiments, the shaft **806** is coupled to a support structure **807**. The support structure **807** may be attached to the frame or body of the vehicle **800** and allow for the fifth wheel **802** to be extended or retracted as needed while supported by the vehicle **800**. Two sprockets or gears **808a** and **808b** are disposed on the shaft **806** such that when the shaft **806** rotates, the sprockets **808a** and **808b** also rotate. In some embodiments, the sprockets **808a** and **808b** and the shaft **806** may be coupled such that the sprockets **808a** and **808b** rotate at a greater or reduced rate as compared to the shaft **806**.

(158) The sprockets **808a** and **808b** engage with a chain, belt, gearing, pulley, or similar device **804a** and **804b**, respectively. The chains **804a** and **804b** cause one or more devices (not shown in this figure) coupled via the chains **804a** and **804b** to rotate at a rate that corresponds to the rate of rotation of the sprockets **808a** and **808b**. In some embodiments, the one or more devices coupled to the sprockets **808a** and **808b** via the chains, gearing, pulley, or similar device **804a** and **804b** are components of or otherwise coupled to the OBCS **810**. For example, the devices to which the sprockets **808a** and **808b** are coupled via the chains (and so forth) **804a** and **804b** provide power (for example, by way of kinetic energy) to the OBCS **810** to enable the OBCS **810** to charge the vehicle **800** while the vehicle **800** is in motion. Thus, in some embodiments, the devices to which the sprockets **808a** and **808b** are coupled via the chains **804a** and **804b** may include generators, alternators, or similar mechanical to electrical energy conversion devices, as described in further detail below. In some embodiments, the small motor described above may act as a fail over motor to drive the shaft driving the generators **902a** and **902b** should one of the chains **804a** and **804b** fail.

(159) In some embodiments, the vehicle **800** includes multiple fifth wheels **802**, sprockets **808**, and/or chains **804** coupling the sprockets **808** to one or more devices. The one or more fifth wheels **802** and the corresponding one or more sprockets **808** may rotate with one or more corresponding shafts **806**. In some embodiments, each fifth wheel **802** is mounted via its respective shaft **806** to its own support structure **807**. In some embodiments, each fifth wheel **802**, when additional fifth wheels **802** exist, is coupled to its own energy conversion device(s) through one or more sprockets **808** and chains **804** that rotate with the corresponding shaft **806** of the additional fifth wheels **802**. By including additional fifth wheels **802**, more mechanical energy may be converted to electrical energy for supply by the OBCS **810** as compared to with a single fifth wheel **802**.

(160) FIG. 9 is a diagram of the fifth wheel **802** of FIG. 8 mechanically coupled to two generators **902a** and **902b** that convert mechanical rotation of the fifth wheel **802** into electrical energy outputs, in accordance with an exemplary embodiment. In some embodiments, the generators **902a** and **902b** may be replaced with alternators or similar electricity generating devices. Each of the generators **902a** and **902b** has a rotor coupled to a drive pulley **904a** and **904b**, respectively. The drive pulley **904** of each generator **902** may rotate, causing the corresponding rotor to rotate and causing the generators **902** to generate an electrical energy output via a cable (not shown in this figure). The drive pulleys **904a** and **904b** are coupled to the fifth wheel **802** via one of the sprockets **808a** and **808b** and one of the chains **804a** and **804b**, respectively. The cable may supply any generated electrical energy output to the OBCS **810** as an input energy to the OBCS **810**. In some embodiments, the two generators **902a** and **902b** may be replaced by any number of generators **902**, from a single generator to many generators. In some embodiments, the generators **902** may generate AC electricity or DC electricity, depending on the application. When the generators **902**

generate AC power, an AC-to-DC converter may be used to condition and convert the generated electricity for storage. When the generators **902** generate DC power, a DC-to-DC converter may be used to condition the generated electricity for storage.

(161) As described above, the fifth wheel **802** is designed to rotate when the vehicle **800** is in motion and the fifth wheel **802** is extended and/or otherwise in contact with the ground or road surface (or otherwise being driven while the vehicle is in motion). When the fifth wheel **802** rotates, that rotation causes the shaft **806** to rotate, causing the sprockets **808a** and **808b** to also rotate. Accordingly, the chains **804a** and **804b** coupled to the sprockets **808a** and **808b** move or rotate around the sprockets **808a** and **808b**, respectively. The movement of the chains **804a** and **804b** while the vehicle **800** is in motion and the fifth wheel **802** is in contact with the ground causes the pulleys **904a** and **904b** of the rotors of the generators **902a** and **902b**, respectively, to rotate. As described above, the rotation of the pulleys **904** of the generators **902** causes the rotors of the generators **902** to rotate to cause the generators **902** to generate the electrical energy output via the cable, where the electrical energy output corresponds to the mechanical rotation of the pulleys **904**. Thus, rotation of the fifth wheel **802** causes the generators **902a** and **902b** to generate electrical energy outputs. In some embodiments, the generators **902a** and **902b** (in combination and/or individually) may generate electrical energy outputs at greater than 400 VAC (for example in a range between 120 VAC and 480 VAC) delivering up to or more than 120 kW of power to the OBCS **810**. In some embodiments, the power output of the generators **902a** and **902b**, in combination and/or individually, may range between 1.2 kilowatts (kW) and 120 kW, for example 1.2 kW, 3.3 kW, 6.6 kW, 22 kW, 26 kW, 62.5 kW, and 120 kW, and so forth. In some embodiments, the generators **902a** and **902b** provide up to or more than 150 kW of power. The power provided by the generators may be adjusted by adjusting the particular generators used or by otherwise limiting an amount of power being delivered from the OBCS **810** to the battery (or similar charge storage devices), as needed.

(162) In some embodiments, the fifth wheel **802** may be designed to be smaller in diameter than the other wheels of the vehicle **800**. By making the fifth wheel **802** smaller in diameter than the other wheels of the vehicle **800**, the fifth wheel **802** may rotate more revolutions per distance traveled than the other wheels of the vehicle. Accordingly, the fifth wheel **802** rotates at a faster RPM than the other wheels of the vehicle. The shaft **806**, coupled to the fifth wheel **802**, has a smaller diameter than the fifth wheel **802**. The sprockets **808a** and **808b** coupled to the shaft **806** have a larger diameter than the shaft **806** but a smaller diameter than the fifth wheel **802**. In some embodiments, the diameters of the various components (for example, the fifth wheel **802**, the shaft **806** and/or the sprockets **808a** and **808b**) may be varied to further increase the rate of rotation (or rotational speed) of the corresponding components. In some embodiments, the diameter of the fifth wheel **802** may be reduced further as compared to the other wheels of the vehicle. In some embodiments, gearing between the fifth wheel **802** and the shaft **806** and/or between the shaft **806** and the sprockets **808a** and **808b** may further increase the difference in the rotational rates or speeds of the various components as compared to a wheel of the vehicle **800**.

(163) As shown in FIG. 9, the pulleys **904** (and the rotors) of the generators **902** have a smaller diameter than the sprockets **808**. Accordingly, the pulleys **904** may rotate at a faster or greater RPM than the sprockets **808** and the fifth wheel **802**. Accordingly, the rotors of the generators **902** coupled to the pulleys **904** may rotate at a faster RPM (as compared to the fifth wheel **802**) and generate electrical energy that is output to the OBCS **810** via the cable described above. In some embodiments, adjusting the diameters of the various components described herein to cause the pulleys **904a** and **904b** to rotate at different RPMs and can cause the generators **902a** and **902b** to generate different amounts of power for transmission to the OBCS **810** (for example, faster rotation may result in more power generated by the generators **902a** and **902b** than slower rotation). By varying the sizing of the various components, the rotors of the generators **902a** and **902b** may rotate at greater or smaller rotation rates. The greater the rotational rate, the more power that is

generated by the generators **902a** and **902b**. Thus, to maximize power generation by the generators **902a** and **902b**, the various components (for example, the fifth wheel **802**, the shaft **806**, the sprockets **808**, the pulleys **904**, and so forth), may be sized to maximize the rotation rate of and power generated by the generators **902**.

(164) In some embodiments, the sprockets **808a** and **808b** may have a diameter that is approximately half the diameter of the fifth wheel **802**. For example, a ratio of the diameter of the fifth wheel **802** to the sprockets **808a** and **808b** may be approximately 2:1 such that the sprockets **808a** and **808b** rotate at approximately twice the rotational speed or RPMs as the fifth wheel **802**. More specifically, the diameter of the sprockets **808a** and **808b** may be between 3" and 5", where the diameter is one of 3", 4", and 5". Similarly, the sprockets **808a** and **808b** may have a larger diameter than the pulleys **904a** and **904b**; for example, the pulleys **904a** and **904b** may have diameters of less than 5" (more specifically, one or more of 1", 2", 3", 4", and 5", inclusive). The resulting rotation of the pulleys **904a** and **904b** occurs at sufficiently high, sustained speeds or RPMs that the corresponding generators **902a** and **902b** generate electrical power at levels sufficient to energy the OBCS **810** to charge the battery of the vehicle **800** while the vehicle **800** is in motion.

(165) As the rotors for the generators **902a** and **902b** rotate, they induce a magnetic field within windings in stator coils of the generators **902a** and **902b**. The magnetic field generated within the coils may be controlled (for example, increased or decreased) by changing a number of coils in each of the generators **902a** and **902b**, thus changing the sizing of the generators **902a** and **902b**. The energy generated by the generators **902a** and **902b** may be varied (for example, increased or decreased) by introducing and/or changing a number of capacitors or other components utilized in conjunction with the generators **902a** and **902b** (for example, within the generators **902a** and **902b** or in series downstream of the generators **902a** and **902b**), and/or by using a permanent magnet coil in the generators **902**. The magnetic field generated within the coils may be directly related to the energy (for example, a current) generated by the generators **902a** and **902b**. In some embodiments, the magnetic field is related to the torque on the generator such that as the torque on the generator increases, the magnetic field rises. As such, to reduce wear and tear on components in the vehicle **800** and to optimize voltage generation, the magnetic field is managed as described herein. In some embodiments, when the fifth wheel **802** comprises the small motor as described above, the small motor is an AC or DC motor and acts as a fail over device that is coupled directly to the rotors of the generators **902** such that the small motor is able to drive the generator should the pulley **804**, the fifth wheel **802**, or other device coupling the fifth wheel **802** to the generators **902** fail.

(166) In some embodiments, the extending and retracting of the fifth wheel **802** may occur based on communications with a controller that monitors the state of charge of a battery and/or demand from a motor. For example, when the controller determines that the battery requires a charge or the motor demands electricity (for example, the vehicle **800** is accelerating), the controller issues a signal to a fifth wheel **802** control system that causes the fifth wheel **802** to be extended to be in contact with the ground or road surface while the vehicle **800** is in motion. Once the fifth wheel **802** reaches an RPM of at least 1000 RPM, the rate of rotation (for example, the RPMs) of the fifth wheel **802** may be controlled and/or monitored such that the battery is charged such that the charge of the battery is maintained or increased or such that the motor is provided with sufficient energy to drive the vehicle **800**. For example, if the controller determines that the battery needs to be charged while the vehicle **800** is in motion, the controller may issue the signal to charge the battery to the fifth wheel **802** system. This signal may cause the fifth wheel **802** system to extend the fifth wheel **802** to contact the ground or road surface. When the fifth wheel **802** reaches 1000 RPM while the vehicle **800** is moving, the generators **902a** and **902b** generate sufficient electrical energy to charge the battery at a rate greater than it is being discharged by the motor to move the vehicle **800** or to feed the motor at a level sufficient to fully drive the vehicle **800**. As the controller monitors the charge of the battery or the demand from the motor, when the charge level or the charge state of the

battery or the motor demand reaches a second threshold, the controller may issue a second signal to stop charging the battery or stop feeding the motor. This second signal may cause the fifth wheel **802** to be retracted or otherwise disconnect the feed of electricity from the battery or the motor.

(167) In some embodiments, retracting the fifth wheel **802** occurs in a controlled matter. In some embodiments, the fifth wheel **802** continues to rotate when it is initially retracted and no longer in contact with the ground or road surface. As such, the generators **902a** and **902b** coupled to the fifth wheel **802** continue to generate electrical energy while the fifth wheel **802** continues to rotate based on its inertia. The controller may issue the second signal before the battery is fully charged so as to not waste any energy generated by the generators **902a** and **902b**. In some embodiments, energy generated by the generators **902a** and **902b** may be offloaded from the vehicle **800**, for example to a land-based grid or energy storage device (for example, a home battery, and so forth).

(168) In some embodiments, the controlled deceleration of the rotation of the fifth wheel **802** when the fifth wheel **802** is retracted occurs due to a brake or similar component that causes the fifth wheel **802** to stop rotating in a controlled manner. In some embodiments, the brake may include a physical brake or other slowing techniques. In some embodiments, the braking of the fifth wheel **802** is regenerative to provide energy to the battery or the motor while the fifth wheel **802** is braking.

(169) In some embodiments, as described above, the fifth wheel **802** extends in response to the first signal from the controller requesting that the battery of the vehicle **800** be charged. As noted above, the fifth wheel **802** may have a mass that allows the fifth wheel **802** to continue to rotate under inertia, etc., when the fifth wheel **802** is retracted and no longer in contact with the ground or road surface while the vehicle **800** is in motion. In some embodiments, the fifth wheel **802** is coupled to the flywheel or similar component that spins under the inertia, etc., after the fifth wheel **802** is retracted from the ground or road surface. Based on the inertia of the fifth wheel **802** or the flywheel or similar component, mechanical energy may be generated from the movement of the vehicle **800** and stored for conversion to electricity (for example, by the generators **902a** and **902b**, etc.).

(170) Once the fifth wheel **802** is extended to contact the ground or road surface, the fifth wheel **802** begins rotating when the vehicle **800** is moving. Due to the smaller size of the fifth wheel **802**, as described above, the fifth wheel **802** rotates with more RPMs than the other wheels of the vehicle **800**. While the fifth wheel **802** rotates, the sprockets **808a** and **808b** described above also rotate, causing the generators **902a** and **902b** to generate electrical energy. The continued reduction in diameters of components between the other wheels of the vehicle **800** and the pulleys **904** of the generators **902** ensures that the generators **902** rotate at a sufficiently fast rate (RPMs) that they generate power to supply to the OBCS **810**, as described herein. The electrical energy is fed to the OBCS **810**, which charges the vehicle **800** via the charging port of the vehicle **800**, or directly to the motor. The fifth wheel **802** is retracted in response to the second signal from the controller, and may or may not continue to rotate and generate electricity under its inertia.

(171) As described above, due to the mass and other properties of the fifth wheel **802** or the flywheel or similar components, the fifth wheel **802** or the fly wheel or similar components may continue to rotate or otherwise maintain some mechanical energy though the fifth wheel **802** is no longer in contact with the ground or road surface while the vehicle **800** is moving. In some embodiments, the fifth wheel **802**, once it reaches the 1000 RPMs described above, is able to maintain its rotation even though the fifth wheel **802** is no longer being “driven” by the ground or road surface when the vehicle **800** is moving. As such, the generators **902a** and **902b** are able to continue to generate electrical energy for charging the battery or feeding the motor of the vehicle **800** via the OBCS **810**. In some embodiments, the fifth wheel **802** or the flywheel or similar components may continue to generate mechanical energy that is converted to electrical energy by the generators **902a** and **902b** until the fifth wheel **802** or flywheel or similar components are stopped using the brake or similar components, as described above, or until the fifth wheel **802** or

flywheel or similar components stop rotating due to friction. In some embodiments, the fifth wheel **802** or flywheel may be replaced with a geared motor or similar component that is smaller in diameter than the other wheels of the vehicle.

(172) In some embodiments, the fifth wheel **802** may be configured to not be in contact with the ground (for example in a position stored upward from the ground) as the vehicle accelerates (for example from rest) to reduce the drag on the vehicle as the vehicle accelerates and so to minimize the energy reduction in an energy storage device (e.g., ultracapacitor, battery) required for acceleration of the vehicle. The fifth wheel **802** may be configured to drop, for example automatically, to contact the ground to begin generating energy as discussed herein when the vehicle is not accelerating (for example from rest), for example when the vehicle has reached a substantially constant, non-zero velocity for example 25 miles per hour. The fifth wheel may be configured to automatically raise (to avoid contact with the ground to reduce drag on the vehicle) when the vehicle is accelerating and/or when the vehicle's acceleration is above a certain threshold, when the vehicle is accelerating within certain velocities and/or when the vehicle is moving within threshold velocities. The fifth wheel may be configured to automatically drop (to contact the ground to generate energy) when the vehicle is not accelerating, and/or when the vehicle's acceleration is below a certain threshold and/or when the vehicle is moving within threshold velocities.

(173) FIG. **10** is an alternate fifth wheel system **1000** illustrating the fifth wheel of FIG. **8** mechanically coupled to a generation unit **1010** that converts a mechanical rotation of the fifth wheel into an electrical energy output to the vehicle **800**, for example the battery or the capacitor module. In some embodiments, the OBCS **810** described herein comprises the generation unit **1010** (for example, instead of or in addition to the generators **902a** and **902b** described above). The generation unit **1010** and the generators **902a** and **902b** may be used interchangeably herein. In some embodiments, the generation unit **1010** may be directly coupled to the battery, the capacitor module, and/or the motor. The system **1000** includes the fifth wheel **802** as supported by the support structure **807** as shown in FIG. **8**. In some embodiments, the support structure **807** includes an independent suspension system **1002** that enables the fifth wheel **802** and the corresponding components coupled to the fifth wheel **802** to move vertically and/or horizontally relative to the ground or the road surface or the vehicle **800** to react or respond to variations in the road or road surface. The independent suspension **1002** may operate independently of the suspension of the vehicle **800**, thus allowing the fifth wheel **802** and corresponding components to move differently from the vehicle **800**, allowing the fifth wheel system **1000** to “float freely” relative to the vehicle **800**. The independent suspension **1002** may help protect the components coupled to the fifth wheel **802** (for example, the components shown in FIG. **10**) by reducing the effects of the variations in the road or road surface to the components. In some embodiments, the independent suspension **1002** includes one or more shocks, struts, linkages, springs, shock absorbers, or similar components that help enable, compensate for, and/or reduce the vertical and/or horizontal movement of the fifth wheel **802** and coupled components. In some embodiments, the independent suspension **1002** also includes various components that improve stability of the components of the OBCS **810** described herein. For example, the independent suspension **1002** may include a stabilization bracket **1012** disposed between a flywheel **1008** and a generation unit **1010**, described in more detail below. The stabilization bracket **1012** disposed between the flywheel **1008** and the generation unit **1010** may provide stabilizing supports between two components that move or have moving parts. The generation unit **1010** may include the generator **902** described above or an alternator or any corresponding component(s) that generate electricity from mechanical energy. The generation unit **1010** may harvest the mechanical/kinetic energy from the movement of the vehicle **800** (or from the inertia caused by the movement of the vehicle **800**) prior to a build-up of friction or heat or other conditions that may otherwise cause energy to be lost by the vehicle **800** (for example, to the heat or other conditions), thereby saving and storing energy that would otherwise be lost or wasted.

(174) The alternate system **1000** further may include the fifth wheel **802** configured to rotate or spin on the shaft **806**. As described above, the rotation of the fifth wheel **802** causes the shaft **806** to rotate and further causes the sprocket **808** and chain **804** to rotate. The chain **804** is coupled to a second shaft **704**, for example via a second pulley or sprocket **709** rotated by the chain **804**. In some embodiments, the shaft **806** is coupled to the second shaft **704** via another means, for example a direct coupling, a geared coupling, and so forth. In some embodiments, the sprockets **808** and **709** (or similar components) and so forth may be sized to allow for balancing of rotational speeds between the various components. For example, the sprockets **808** on the shaft **806** and corresponding sprockets or gearing on the second shaft **704** are sized to balance rotations between the fifth wheel **802** and the generation unit **1010**. In some embodiments, the sizing for the sprockets **808** and **709** (and similar components) is selected to control the electricity generated by the generation unit **1010**.

(175) The generation unit **1010** may be electrically coupled to a capacitor (for example, one of the capacitor modules), the battery, the motor, and/or a cut-off switch. The cut-off switch may disconnect the output of the generation unit **1010** from the capacitor, the battery, and/or the motor such that electrical energy generated by the generation unit **1010** may be transferred to the battery, the capacitor module, or to the motors as needed. In some embodiments, the cut-off switch can be controlled by an operator or the controller of the vehicle **800** or the second controller of the OBCS **810**. For example, the controller of the vehicle **800** or the OBCS **810** may receive, identify, and/or determine an interrupt signal to initiate the dump. In response to the interrupt signal, the controller may disconnect the output of the generation unit **1010** from the battery, the capacitor module, and/or the motor. Disconnecting the output of the generation unit **1010** from the capacitor, the battery, and/or the motor may ensure that any residual electrical energy in one or more components of the OBCS **810** (for example, the generation unit **1010**) is transferred or “dumped” to the battery and/or the capacitor module and therefore control a supply of back-up high voltage. In some embodiments, during the dump, the output of the generation unit **1010** may be connected to a dump load or similar destination when disconnected from the capacitor module, the battery, and/or the motor to prevent damage to any coupled electrical components. In some embodiments, the dump load may comprise a back-up battery, capacitor, or similar energy storage device. In some embodiments, the voltage dump may occur for a period of time and/or at periodic intervals defined by one or more of a time for example since a previous dump, a distance traveled by the vehicle for example since the previous dump, a speed of the vehicle for example since the previous dump, and a power generated and/or output by the generation unit **1010**, for example since the previous dump. After the dump is complete (for example, the period of time expires), then the controller may disconnect the dump load from the generation unit output (for example, at a generation unit terminal) and reconnect the battery, the capacitor module, and the motor.

(176) In some embodiments, the voltage dump may comprise opening a contactor that is positioned downstream of the generation unit **1010** or the generators **902**. Opening the contactor may disconnect the generation unit **1010** or the generators **902** from the downstream components (for example, the load components for the generation unit **1010** or the generators **902**). In some embodiments, the controls for initiating and/or deactivating the dump are conveniently located for the vehicle operator to access or coupled to the controller for the vehicle **800**.

(177) In some embodiments, the generation unit **1010** outputs the generated electrical energy in pulses or with a constant signal. For example, the operator or the controller of the vehicle **800** or the second controller of the OBCS **810** In some embodiments, the generation unit **1010** is switchable between outputting the electrical energy in pulses or in the constant signal. The operator may control whether the output is pulsed or constant or the OBCS **810** may automatically control whether the output is pulsed or constant without operator intervention based on current demands of the vehicle **800** and so forth. In some embodiments, when the output is pulsed, the operator and/or the OBCS **810** can control aspects of the pulsed signal, including a frequency of the pulse, an

amplitude of the pulse, a duration of each pulse, and so forth. Similarly, when the output is constant, the operator and/or the OBCS **810** may control aspects of the constant signal, including a duration of the signal and an amplitude of the signal.

(178) In some embodiments, the operator of the vehicle **800** can control the height of the fifth wheel **802**. For example, the operator determines when to lower the fifth wheel **802** so that it is in contact with the road or a road surface, thereby causing the fifth wheel **802** to rotate. The operator may have controls for whether the fifth wheel **802** is in a raised position, where it is not in contact with the road, or in a lowered position, where it is in contact with the road. Additionally, or alternatively, the operator may have options to control specifics of the raised or lowered position, for example how low to position the fifth wheel **802**. Such controls may allow the operator to control the amount of force that the fifth wheel **802** provides on the road or road surface, which may impact the electrical energy generated by the OBCS **810**. For example, when the fifth wheel **802** is pressing down on the road surface with a large amount of force, then this force may create more resistance against the fifth wheel **802** rotating when the vehicle **800** is moving, thereby reducing the electrical energy generated by the OBCS **810**. On the other hand, when the force on the fifth wheel **802** is small amount of force, then the fifth wheel **802** may lose contact with the road or road surface depending on variations in the road surface, thereby also reducing the electrical energy generated by the OBCS **810**. Thus, the controls may provide the operator with the ability to tailor the downward force exerted by the fifth wheel **802** on the road based on road conditions and based on the need for power. In some embodiments, the OBCS **810** may automatically control the force of the fifth wheel **802** on the road to maximize electrical energy generation based on monitoring of the road surface and electrical energy being generated.

(179) Additionally, the operator of the vehicle **800** may choose to extend the fifth wheel **802** so that it contacts the road or retract the fifth wheel **802** so that it does not contact the road based on draft or drag conditions. For example, if the drag increases or is expected to increase based on various conditions, the operator may choose to retract the fifth wheel **802** or keep the fifth wheel **802** retracted. If the drag decreases or is expected to decrease based on conditions, then the operator may choose to extend the fifth wheel **802** or keep it extended. In some embodiments, the OBCS **810** may automatically extend and/or retract the fifth wheel **802** based on drag or potential drag conditions without the operator's involvement.

(180) In some embodiments, the controller may enable retraction and/or extension of one or more of the multiple fifth wheels **802**. Such control of the fifth wheels **802** may be based on an analysis of charge remaining in the energy storage components of the electric powered devices and/or a speed or other conditions of power generation using the fifth wheels **802**. In some instances, the controller may determine that one or more of the fifth wheels should be extended to generate power based on the movement and/or other conditions of the electric powered device.

(181) In some instances, the fifth wheel **802** is coupled to a gearbox allowing one or more ratios of rotating components to be adapted to the movement of the electric powered device or vehicle. The gearbox may allow the ratios of rotating components to be adjusted to change the amount of power generated by the fifth wheels **802**, where the gearbox can allow for increased power generation as needed depending on various conditions.

(182) In some instances, the fifth wheel **802** may be coupled to a gearbox allowing one or more ratios of rotating components to be adapted to the movement of the vehicle, enabling the OBCS **810** and/or an operator to mechanically control and/or adjust rates at which electricity is generated by generators coupled to the fifth wheel(s) **802**. For example, the gearbox can enable changing of ratios between the rotation of the fifth wheel(s) **802** of the vehicle based on a speed at which the vehicle is traveling or a grade on which the vehicle is traveling, thereby impacting rotations of the generator and electricity produced by the generator. For example, if the vehicle is traveling slowly or up-hill, or traveling against a current, or into a headwind, the gearbox can be adjusted such that the ratio of the generator and the fifth wheels **802** are closer to each other. If the vehicle is traveling

quickly or down-hill, or with a current, or with a tail-wind, the gearbox can be adjusted such that the ratio of the generator and the fifth wheels **802** are such that a single rotation of the fifth wheel **802** results in multiple rotations of the generator via the gearbox, and so forth.

(183) FIG. **11** is block diagram illustrating an example implementation of a gearbox **1105**. The gearbox **1105** may include one or more gears which may be one or more sizes. The gearbox **1105** can be coupled to one or more driven mass(es) **1103** and a generator **1107**. The driven mass(es) **1103** can include one or more rollers, as described herein, and/or one or more “fifth” wheels, as described herein. In some implementations, the driven mass(es) **1103** can include one or more turbines such as a water and/or wind turbine. The gearbox **1105** can adjust a rotational velocity of a rotatable component of the generator **1107** with a rotational velocity of a rotatable component of the driven mass(es) **1103**. For example, the driven mass(es) **1103** may be rotatably coupled to a first gear of the gearbox **1105** and the generator **1107** may be rotatably coupled to a second gear of the gearbox **1105**. The first and second gears of the gearbox **1105** may be rotatably coupled. The first and second gears may be different sizes, including having different diameters, such that rotation of the first gear at a first angular velocity causes rotation of the second gear at a second angular velocity. The gearbox **1105** can change a ratio of angular velocity between the driven mass(es) **1103** and the generator **1107** by changing a gear to which the driven mass(es) **1103** and/or generator **1107** is rotatably coupled. The gearbox **1105** can adjust the ratio of rotation, such as by changing the gear to which the driven mass(es) **1103** and the generator **1107** is rotatably coupled, according to user input and/or according to operational settings, according to any of the examples discussed herein.

(184) FIG. **12A** is a diagram illustrating an example embodiment of an apparatus **1200** comprising a roller rotatably couplable to a wheel of a vehicle. As shown in FIG. **12A**, the apparatus **1200** may comprise a roller **1202**, a shaft **1204** and a generator **1206**. The roller **1202** may comprise a substantially cylindrical shape comprising a length, a diameter, a curved surface and a center axis. A curved surface of the roller **1202** may be in substantial physical contact with a curved surface of the wheel **1201**. The center axis of the roller **1202** may be substantially parallel to a center axis of the wheel **1201**. The roller **1202** may be configured to rotate about its center axis. The roller **1202** may be rotatably couplable to a wheel **1201** of the vehicle such that rotation of the wheel **1201** causes rotation of the roller **1202**. The roller **1202** may rotate in an opposite direction than the wheel **1201**, for example as shown in FIG. **12A**. The roller **1202** may rotate at a greater rotational velocity than the wheel **1201**.

(185) With continued reference to FIG. **12A**, the roller **1202** may be rotatably coupled to a shaft **1204** such that rotation of the roller **1202** can cause rotation of the shaft **1204**. The shaft **1204** may rotate about an axis that is substantially parallel to the axis of the roller **1202** and may rotate in a same direction as the roller **1202**, for example as shown in FIG. **12A**. In some embodiments, the shaft **1204** may be fixedly rotatably coupled to the roller **1202** such that the shaft **1204** can only rotate when the roller **1202** rotates. In some embodiments, the shaft **1204** may be configured to rotate when the roller **1202** is not rotating. For example, after a roller **1202** discontinues rotating, the shaft **1204** may continue to rotate, for example due to rotational inertia. For example, the roller **1202** and/or shaft **1204** may comprise a one-way ratchet device that causes the shaft **1204** to rotate when the roller **1202** rotates and allows the shaft **1204** to continue to rotate for a period of time even after the roller **1202** stops rotating. In some embodiments, the shaft **1204** may be configured to not rotate when the roller **1202** is rotating. For example, in a disengaged state, as discussed in greater detail herein, the roller **1202** may rotate in response to rotation of a vehicle wheel but may not cause rotation of the shaft **1204** to generate energy at the generator **1206**.

(186) The shaft **1204** may be operably coupled to a generator **1206**. The generator **1206** may be configured to generate energy (e.g., an electrical output) in response to mechanical movement such as the rotation of the shaft **1204**. The generator **1206** may be electrically coupled to the vehicle and may provide generated energy to the vehicle, for example to a motor of the vehicle and/or to an

energy storage device of the vehicle that includes one or more batteries and/or capacitors (e.g., ultracapacitors) or one or more hypercapacitors.

(187) FIG. 12B is a diagram illustrating an example embodiment of an apparatus **1200** comprising a roller that is removably coupled to a wheel of a vehicle. The apparatus **1200** may exist in one of (1) an engaged state or (2) a disengaged state. In the engaged state, the roller **1202** may be in physical contact with the wheel **1201** (e.g., rotatably coupled to the wheel **1201**) in which the rotation of the wheel **1201** causes the roller **1202** to rotate. In some embodiments, in the disengaged state, the roller **1202** may not be in physical contact with the wheel **1201** such that rotation of the wheel **1201** does not cause the roller **1202** to rotate. In some embodiments, in the disengaged state, the roller **1202** may be in physical contact with the wheel **1201** such that rotation of the wheel **1201** causes the roller **1202** to rotate but the roller **1202** may not be rotatably coupled to the shaft **1204** such that rotation of the roller **1202** does not cause the shaft **1204** (or other similar component) to rotate to cause generation of energy at the generator **1206**.

(188) FIG. 12B shows a roller **1202** in an example disengaged state such that the roller **1202** is not in physical contact with the wheel **1201** and will not rotate in response to a rotation of the wheel **1201**. The roller **1202** may transition between the engaged and the disengaged states. In some embodiments, the roller **1202** may transition between the engaged and the disengaged states automatically, for example, based at least in part on an energy demand of the vehicle (e.g., an energy demand of a motor of the vehicle) and/or a rotational velocity of the wheel **1201**. In some embodiments, the roller **1202** may transition between the engaged and the disengaged states in response to a user input, such as a driver of the vehicle activating a user input device, such as a button, lever, or switch.

(189) FIG. 13A is a diagram illustrating an example embodiment of the apparatus **1300** comprising one or more rollers rotatably couplable to a sidewall of a wheel of a vehicle. As shown in FIG. 13A, the apparatus **1300** may comprise one or more rollers **1302**, a shaft **1304** and a generator **1306**. Each of the one or more rollers **1302** may comprise a substantially cylindrical shape and may further comprise a length, a diameter, a curved surface and a center axis. A curved surface of each of the one or more rollers **1302** may be in substantial physical contact with a sidewall surface of the wheel **1301**. The center axis of each of the one or more rollers **1302** may be substantially orthogonal to a center axis of the wheel **1301**. Each of the one or more rollers **1302** may be configured to rotate about its center axis. Each of the one or more rollers **1302** may be rotatably couplable to the wheel **1301** of the vehicle such that rotation of the wheel **1301** causes rotation of each of the one or more rollers **1302**. Each of the one or more rollers **1302** may rotate at a greater rotational velocity than the wheel **1301**.

(190) The roller(s) **1302** may be configured to be in physical contact with a sidewall of the wheel **1301** at any distance away from a center axis of the wheel. For example, the roller(s) **1302** may be in physical contact with a sidewall of the wheel **1301** close to the center axis of the wheel or far from a center axis of the wheel. The roller(s) **1302** may rotate at a greater rotational velocity when in physical contact with the sidewall of the wheel **1301** far from a center axis of the wheel **1301** than when in physical contact with the sidewall of the wheel **1301** near a center axis of the wheel **1301**.

(191) With continued reference to FIG. 13A, the roller(s) **1302** may be rotatably coupled to a shaft **1304** such that rotation of the roller(s) **1302** causes rotation of the shaft **1304**. The roller **1302** may be coupled (e.g., rotatably coupled) to the shaft **1304** for example via one or more coupling devices as required or desired such as gears, sprockets, chains, belts, pulleys and the like. The shaft **1304** may rotate about an axis that is substantially orthogonal to the axes of the roller(s) **1302**. In some embodiments, the shaft **1304** may be fixedly rotatably coupled to the roller(s) **1302** such that the shaft **1304** can only rotate when the roller(s) **1302** rotate. In some embodiments, the shaft **1304** may be configured to rotate when one or more of the roller(s) **1302** is not rotating, for example, after a roller **1302** discontinues rotating, the shaft **1304** may continue to rotate, for example due to

rotational inertia. For example, the roller(s) **1302** and/or shaft **1304** may comprise a one-way ratchet device that causes the shaft **1304** to rotate when the roller(s) **1302** rotate and allows the shaft **1304** to continue to rotate even when one of the roller(s) **1302** is not rotating (e.g., has stopped rotating). In some embodiments, the shaft **1304** may be configured to not rotate when one or more of the roller(s) **1302** are rotating. For example, in a disengaged state, as discussed in greater detail herein, the roller(s) **1302** may rotate in response to rotation of a vehicle wheel but may not cause rotation of the shaft **1304** to generate energy at the generator **1306**.

(192) The shaft **1304** may be operably coupled to a generator **1306**. The generator **1306** may be configured to generate energy (e.g., an electrical output) in response to mechanical movement such as the rotation of the shaft **1304**. The generator **1306** may be electrically coupled to the vehicle and may provide generated energy to the vehicle, for example to a motor of the vehicle and/or to an energy storage device of the vehicle that includes one or more batteries and/or capacitors (e.g., ultracapacitors) or one or more supercapacitors.

(193) FIG. **13B** is a diagram illustrating an example embodiment of the apparatus **1300** comprising one or more rollers that are removably coupled to a sidewall of a wheel of a vehicle. The apparatus **1300** may exist in one of (1) an engaged state or (2) a disengaged state. In the engaged state, the roller(s) **1302** may be in physical contact with the wheel **1301** (e.g., rotatably coupled to a sidewall of the wheel **1301**) in which the rotation of the wheel **1301** causes the roller(s) **1302** to rotate. In some embodiments, in the disengaged state, the roller(s) **1302** may not be in physical contact with the wheel **1301** such that rotation of the wheel **1301** does not cause the roller(s) **1302** to rotate. In some embodiments, in the disengaged state, the roller(s) **1302** may be in physical contact with the wheel **1301** such that rotation of the wheel **1301** causes the roller(s) **1302** to rotate but the roller(s) **1302** may not be rotatably coupled to the shaft **1304** such that rotation of the roller(s) **1302** does not cause the shaft **1304** (or other similar component) to rotate to cause generation of energy at the generator **1306**.

(194) FIG. **13B** shows roller(s) **1302** in an example disengaged state such that the roller(s) **1302** are not in physical contact with the wheel **1301** and will not rotate in response to a rotation of the wheel **1301**. The roller(s) **1302** may transition between the engaged and the disengaged states. In some embodiments, the roller(s) **1302** may transition between the engaged and the disengaged states automatically, for example, based at least in part on an energy demand of the vehicle (e.g., an energy demand of a motor of the vehicle) and/or a rotational velocity of the wheel **1301**. In some embodiments, the roller(s) **1302** may transition between the engaged and the disengaged states in response to a user input, such as a driver of the vehicle toggling a user input device such as a button, switch or lever.

(195) The rotational inertia of the rollers **1302** in the example embodiment of FIGS. **13A-13B** and other examples herein can be changed, for example increased or decreased. Increasing the rotational inertia of the rollers can cause more or less friction to be applied to the wheel **1301** and also cause more or less energy to be generated at the generator **1306**. For example, more energy would be required to rotate a roller **1302** with a high rotational inertia than would be required to rotate a roller **1302** with less rotational inertia. Thus, a roller **1302** with high rotational inertia could more quickly decelerate the rotation of the wheel **1301** while simultaneously causing more energy to be generated at the generator **1306** than a roller with lower rotational inertia. For example, when acceleration or a constant speed of the vehicle is desired, the rotational inertia of the roller(s) **1302** may be low to apply less friction to the wheel **1301** (which may thereby cause less energy to be generated at the generator **1306**) and when deceleration of the vehicle is desired (e.g., stopping), the rotational inertia of the roller(s) **1302** may be high to apply more friction to the wheel **1301** (which may thereby cause more energy to be generated at the generator **1306**). Thus, for any given desired mode of operation of the vehicle (e.g., acceleration, deceleration) a maximum energy may be generated at the generator **1306** by changing a rotational inertia of the rollers **1302**.

(196) In some implementations, the rotational inertia of the rollers **1302** can change automatically

for example in response to an energy demand of the motor of the vehicle, a rotational velocity of the wheel, and/or desired braking etc. In some implementations, the rotational inertia of the rollers can change in response to a manual user input. The rotational inertia of the roller **1302** can be changed by changing a state of the roller **1302**, the shaft **1304** (or other coupling device), and/or changing a state of the generator **1306**. In some implementations, a gearbox may change the rotational inertia of the roller **1302** by changing a gear ratio between the roller **1302** and the generator **1306**.

(197) FIG. **14A** is a block diagram illustrating an example energy system **1400**. The energy system **1400** may include similar structural and/or operation features as example energy system **150** shown and/or described herein. The energy system **1400** can include an energy source **1401**, energy storage device **1403**, energy storage devices **1405**, and a load **1407**. In some implementations, the energy system **1400** can optionally include an electrical interface **1402**, a diode **1404A**, a switch **1406A**, and/or a diode **1404B**.

(198) The energy source **1401** can include an energy generation or regeneration system. In some implementations, the energy source **1401** can include a solar power generation system. The energy source **1401** can include one or more solar panels and/or solar cells configured to generate an electrical voltage and/or current in response to exposure to light. In some implementations, the energy source **1401** may be included within a vehicle. For example, the energy source **1401** may include an on-board power generation system disposed within and/or on a vehicle and that is mobile with the vehicle. In some implementations, the energy source **1401** may be separate from a vehicle. For example, the energy source **1401** may be stationary or in a fixed location such as a charging station.

(199) The electrical interface **1402** can include a plug configured to mechanically and/or electrically couple the energy source **1401** to the energy storage device **1403**. The energy storage device **1403** may be removably coupled to the energy source **1401** via the electrical interface **1402**.

(200) The diode **1404A** can include one or more diodes configured to conduct an electrical current in one direction. The diode **1404A** can be biased toward the energy source **1403**. The diode **1404A** may be configured to conduct an electrical current from the energy source **1401** to the energy storage device **1403**. The diode **1404A** may be configured to prevent an electrical current from passing from the energy storage device **1403** to the energy source **1401**. The diode **1404A** may act as an insulator and prevent an electrical current from passing until a voltage across the diode **1404A** exceeds a threshold. The diode **1404A** may open to allow a current to pass in response to a voltage across the diode **1404A** exceeding a threshold.

(201) The energy storage device **1403** can include one or more devices configured to store energy such as a voltage. The energy storage device **1403** can include one or more capacitors, such as ultracapacitors and/or supercapacitors. The energy storage device **1403** may be configured to receive energy from the energy source **1401** via the electrical interface **1402** and/or the diode **1404A**.

(202) The switch **1406** can include one or more electrical switches, relays, circuits, or the like. The switch **1406** may be configured to transition between open and closed states. In a closed state, the switch **1406** may be configured to conduct an electrical current. In a closed state, the switch **1406** may be configured to prevent an electrical current from passing.

(203) The diode **1404B** may include similar structural and/or operational features as any of the other diodes shown and/or described herein, such as diode **1404A**.

(204) The energy storage device **1405** may receive energy from the energy storage device **1403** via the switch **1406** and/or diode **1404B**. The energy storage device **1405** can include one or more devices configured to store energy such as a voltage. The energy storage device **1405** can include one or more batteries. The energy storage device **1405** can include a battery field or battery array. The energy storage device **1405** can include one or more lithium batteries, such as lithium ion batteries, lithium polymer batteries, or the like.

(205) The load **1407** may receive energy from the energy storage device **1405**. The load **1407** can include a device configured to consume energy or power. The load **1407** can include a motor of a vehicle.

(206) FIG. **14B** illustrates an example implementation of an energy system including a solar charging station **1451** used to charge a vehicle **1450**. The solar charging station **1451** can include one or more solar panels and/or solar cells **1459**. The solar charging station **1451** can include one or more energy storage devices such as capacitors and/or batteries. The solar panels **1459** may be configured to generate a voltage and/or current in response to light. The solar charging station **1451** may be configured to store energy generated by the solar panels **1459** in one or more storage devices of the solar charging station **1451**.

(207) The vehicle **1450** may include one or more energy storage devices such as capacitors and/or batteries. The vehicle **1450** may be configured to receive energy from the solar charging station **1451**. For example, the vehicle **1450** may receive energy from the solar panels **1459** and/or from an energy storage device of the solar charging station **1451**. The vehicle **1450** may be configured to store energy from the solar charging station **1451** in a capacitor storage device of the vehicle **1450** such as an ultracapacitor or supercapacitor. The vehicle **1450** may transfer energy from a capacitor storage device to a battery storage device of the vehicle **1450** and/or to a load of the vehicle **1450**. Advantageously, the vehicle **1450** may be configured to receive a large amount of energy from the solar charging station **1451** in a short amount of time to store in an electric field of a capacitor storage device which may reduce charge times of the vehicle **1450**.

(208) FIG. **14C** illustrates an example implementation of an energy system including one or more solar panels and/or solar cells **1461** and a vehicle **1460**. The solar panels **1461** may be configured to generate a voltage and/or current in response to light. The solar panels **1461** may be disposed on a surface of the vehicle **1460**. For example, the solar panels **1461** may be disposed on a roof surface of the vehicle **1460**, on a hood surface of the vehicle **1460**, on a trunk surface of the vehicle **1460**, or the like. In some implementations, the solar panels **1461** may be disposed on a side surface of the vehicle **1460** such as on a door of the vehicle **1460**. Advantageously, the solar panels **1461** may be mobile with the vehicle **1460** and may generate energy as the vehicle **1460** travels.

(209) The vehicle **1460** may include one or more energy storage devices such as capacitors and/or batteries. The vehicle **1460** may be configured to receive energy from the solar panels **1461**. The vehicle **1460** may be configured to store energy from the solar panels **1461** in a capacitor storage device of the vehicle **1460** such as an ultracapacitor or supercapacitor. The vehicle **1460** may transfer energy from a capacitor storage device to a battery storage device of the vehicle **1460** and/or to a load of the vehicle **1460**. Advantageously, the vehicle **1460** may be configured to receive a large amount of energy from the solar panels **1461** in a short amount of time to store in an electric field of a capacitor storage device which may reduce charge times of the vehicle **1460**.

(210) FIG. **15A** is a block diagram illustrating an example energy system **1500**. The energy system **1500** may include similar structural and/or operation features as any of the other example energy systems shown and/or described herein, such as energy system **150** and/or energy system **1400**. The energy system **1500** can include an energy source **1501**, energy storage device **1503**, energy storage devices **1505**, and a load **1507**. In some implementations, the energy system **1500** can optionally include an electrical interface **1502**, a diode **1504A**, a switch **1506A**, and/or a diode **1504B**.

(211) In some embodiments the energy source **1501** can include an energy generation or regeneration system. For example, the energy source **1501** can include one or more turbines. A turbine can include one or more blades, fans, vanes, and/or rotors. A turbine can include one or more generators. A turbine can be configured to generate energy, such as an electrical current and/or voltage in response to a rotation of the turbine. A turbine can be configured to rotate in response to a fluid flow across the turbine such as a water flow and/or air flow. In some implementations, the energy source **1501** may be included within a vehicle. For example, the energy source **1501** may include an on-board power generation system disposed within and/or on a

vehicle and that is mobile with the vehicle. In some implementations, the energy source **1501** may be separate from a vehicle. For example, the energy source **1501** may be stationary or in a fixed location such as a charging station.

(212) The energy storage device **1503** can include one or more devices configured to store energy such as a voltage. The energy storage device **1503** can include one or more capacitors, such as ultracapacitors and/or supercapacitors. The energy storage device **1503** may be configured to receive energy from the energy source **1501** via the electrical interface **1502** and/or the diode **1504A**.

(213) The energy storage device **1505** may receive energy from the energy storage device **1503** via the switch **1506** and/or diode **1504B**. The energy storage device **1505** can include one or more devices configured to store energy such as a voltage. The energy storage device **1505** can include one or more batteries. The energy storage device **1505** can include a battery field or battery array. The energy storage device **1505** can include one or more lithium batteries, such as lithium ion batteries, lithium polymer batteries, or the like.

(214) The load **1507** may receive energy from the energy storage device **1505**. The load **1507** can include a device configured to consume energy or power. The load **1507** can include a motor of a vehicle.

(215) FIG. **15B** illustrates an example implementation of an energy system including a turbine charging station **1521** used to charge a vehicle **1520**. The turbine charging station **1521** can include one or more turbines **1529** which may include blades, fans, rotors, or the like, and which may be configured to rotate in response to movement of a fluid, such as air or water, across the turbine **1529**. The turbine charging station **1521** can include one or more generators configured to generate energy in response to a rotation of the turbine **1529**. The turbine charging station **1521** can include one or more energy storage devices such as capacitors and/or batteries. The turbine charging station **1521** may be configured to store energy generated by the turbines **1529** and/or generators in one or more storage devices of the turbine charging station **1521**.

(216) The vehicle **1520** may include one or more energy storage devices such as capacitors and/or batteries. The vehicle **1520** may be configured to receive energy from the turbine charging station **1521**. For example, the vehicle **1520** may receive energy from the turbine **1529**, generator, and/or from an energy storage device of the turbine charging station **1521**. The vehicle **1520** may be configured to store energy from the turbine charging station **1521** in a capacitor storage device of the vehicle **1450** such as an ultracapacitor or supercapacitor. The vehicle **1520** may transfer energy from a capacitor storage device to a battery storage device of the vehicle **1520** and/or to a load of the vehicle **1520**. Advantageously, the vehicle **1520** may be configured to receive a large amount of energy from the turbine charging station **1521** in a short amount of time to store in an electric field of a capacitor storage device which may reduce charge times of the vehicle **1520**.

(217) FIG. **15C** illustrates an example implementation of an energy system including one or more turbines **1551** and a vehicle **1550**. The vehicle **1550** can include a commercial vehicle such as a semi-truck. FIG. **15C** is not intended to be limiting. In some implementations, the vehicle **1550** can include any vehicle configured to travel on a ground surface such as a car, a truck, a bus, a golf cart, a bike, a scooter, a motorcycle, construction equipment, farm equipment such as a tractor, or the like. The turbines **1551** may be configured to rotate in response to movement of a fluid, such as air, across the turbines **1551**. The turbines **1551** may be disposed on a surface of the vehicle **1550**. For example, the turbines **1551** may be disposed on a roof surface of the vehicle **1550**, on a side surface of the vehicle **1550**, on a bottom surface of the vehicle or the like. Advantageously, the turbines **1551** may be mobile with the vehicle **1550** and may generate energy as the vehicle **1550** travels.

(218) The vehicle **1550** may include a generator **1552**. The generator **1552** may generate energy in response to a rotation of the turbine **1551**. The vehicle **1550** may include one or more energy storage devices such as energy storage device **1553** and energy storage device **1555**. Energy storage

device **1553** can include one or more capacitors such as ultracapacitors and/or supercapacitors. Energy storage device **1555** can include one or more batteries. The energy storage device **1553** may be configured to receive and store energy from the generator **1552**. The energy storage device **1553** may transfer energy to the energy storage device **1555** and/or to the motor **1557**. Advantageously, the energy storage device **1553** may be configured to receive a large amount of energy from the generator **1552** in a short amount of time to store in an electric field of the energy storage device **1553** which may reduce charge times of the vehicle **1550**.

(219) FIG. **15D** illustrates an example implementation of an energy system including one or more turbines **1561** and a vehicle **1560**. The vehicle **1560** can include an aircraft such as an airplane. The turbines **1561** may be configured to rotate in response to movement of a fluid, such as air, across the turbines **1561**. The turbines **1561** may be disposed on a surface of the vehicle **1560**.

Advantageously, the turbines **1561** may be mobile with the vehicle **1560** and may generate energy as the vehicle **1560** travels.

(220) The vehicle **1560** may include a generator **1562**. The generator **1562** may generate energy in response to a rotation of the turbine **1561**. The vehicle **1560** may include one or more energy storage devices such as energy storage device **1563** and energy storage device **1565**. Energy storage device **1563** can include one or more capacitors such as ultracapacitors and/or supercapacitors.

Energy storage device **1565** can include one or more batteries. The energy storage device **1563** may be configured to receive and store energy from the generator **1562**. The energy storage device **1563** may transfer energy to the energy storage device **1565** and/or to the motor **1567**. Advantageously, the energy storage device **1563** may be configured to receive a large amount of energy from the generator **1562** in a short amount of time to store in an electric field of the energy storage device **1563** which may reduce charge times of the vehicle **1560**.

(221) FIG. **15E** illustrates an example implementation of an energy system including one or more turbines **1571** and a vehicle **1570**. The vehicle **1570** can include a watercraft such as a boat. The turbines **1571** may be configured to rotate in response to movement of a fluid, such as air and/or water, across the turbines **1571**. The turbines **1571** may be disposed on a surface of the vehicle **1570**. For example, the turbines **1571** may be disposed on a bottom surface of the vehicle **1570** that is submerged beneath water. As another example, the turbines **1571** may be disposed on an upper surface of the vehicle **1570** that is exposed to air. Advantageously, the turbines **1571** may be mobile with the vehicle **1570** and may generate energy as the vehicle **1570** travels.

(222) The vehicle **1570** may include a generator **1572**. The generator **1572** may generate energy in response to a rotation of the turbine **1571**. The vehicle **1570** may include one or more energy storage devices such as energy storage device **1573** and energy storage device **1575**. Energy storage device **1573** can include one or more capacitors such as ultracapacitors and/or supercapacitors.

Energy storage device **1575** can include one or more batteries. The energy storage device **1573** may be configured to receive and store energy from the generator **1572**. The energy storage device **1573** may transfer energy to the energy storage device **1575** and/or to the motor **1577**. Advantageously, the energy storage device **1573** may be configured to receive a large amount of energy from the generator **1572** in a short amount of time to store in an electric field of the energy storage device **1573** which may reduce charge times of the vehicle **1570**.

Additional Embodiments

(223) As used herein, “system,” “instrument,” “apparatus,” and “device” generally encompass both the hardware (for example, mechanical and electronic) and, in some implementations, associated software (for example, specialized computer programs for graphics control) components.

(224) It is to be understood that not necessarily all objects or advantages may be achieved in accordance with any particular embodiment described herein. Thus, for example, those skilled in the art will recognize that certain embodiments may be configured to operate in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other objects or advantages as may be taught or suggested herein.

(225) Each of the processes, methods, and algorithms described in the preceding sections may be embodied in, and fully or partially automated by, code modules executed by one or more computer systems or computer processors including computer hardware. The code modules may be stored on any type of non-transitory computer-readable medium or computer storage device, such as hard drives, solid state memory, optical disc, and/or the like. The systems and modules may also be transmitted as generated data signals (for example, as part of a carrier wave or other analog or digital propagated signal) on a variety of computer-readable transmission mediums, including wireless-based and wired/cable-based mediums, and may take a variety of forms (for example, as part of a single or multiplexed analog signal, or as multiple discrete digital packets or frames). The processes and algorithms may be implemented partially or wholly in application-specific circuitry. The results of the disclosed processes and process steps may be stored, persistently or otherwise, in any type of non-transitory computer storage such as, for example, volatile or non-volatile storage.

(226) Many other variations than those described herein will be apparent from this disclosure. For example, depending on the embodiment, certain acts, events, or functions of any of the algorithms described herein can be performed in a different sequence, can be added, merged, or left out altogether (for example, not all described acts or events are necessary for the practice of the algorithms). Moreover, in certain embodiments, acts or events can be performed concurrently, for example, through multi-threaded processing, interrupt processing, or multiple processors or processor cores or on other parallel architectures, rather than sequentially. In addition, different tasks or processes can be performed by different machines and/or computing systems that can function together.

(227) The various illustrative logical blocks, modules, and algorithm elements described in connection with the embodiments disclosed herein can be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, and elements have been described herein generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. The described functionality can be implemented in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the disclosure.

(228) The various features and processes described herein may be used independently of one another, or may be combined in various ways. All possible combinations and sub-combinations are intended to fall within the scope of this disclosure. In addition, certain method or process blocks may be omitted in some implementations. The methods and processes described herein are also not limited to any particular sequence, and the blocks or states relating thereto can be performed in other sequences that are appropriate. For example, described blocks or states may be performed in an order other than that specifically disclosed, or multiple blocks or states may be combined in a single block or state. The example blocks or states may be performed in serial, in parallel, or in some other manner. Blocks or states may be added to or removed from the disclosed example embodiments. The example systems and components described herein may be configured differently than described. For example, elements may be added to, removed from, or rearranged compared to the disclosed example embodiments.

(229) The various illustrative logical blocks and modules described in connection with the embodiments disclosed herein can be implemented or performed by a machine, such as a general purpose processor, a digital signal processor (“DSP”), an application specific integrated circuit (“ASIC”), a field programmable gate array (“FPGA”) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor can be a microprocessor, but in the alternative, the processor can be a controller, microcontroller, or state machine, combinations of the same, or the like. A processor can include electrical circuitry configured to process

computer-executable instructions. In another embodiment, a processor includes an FPGA or other programmable devices that performs logic operations without processing computer-executable instructions. A processor can also be implemented as a combination of computing devices, for example, a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. Although described herein primarily with respect to digital technology, a processor may also include primarily analog components. For example, some, or all, of the signal processing algorithms described herein may be implemented in analog circuitry or mixed analog and digital circuitry. A computing environment can include any type of computer system, including, but not limited to, a computer system based on a microprocessor, a mainframe computer, a digital signal processor, a portable computing device, a device controller, or a computational engine within an appliance, to name a few.

(230) The elements of a method, process, or algorithm described in connection with the embodiments disclosed herein can be embodied directly in hardware, in a software module stored in one or more memory devices and executed by one or more processors, or in a combination of the two. A software module can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of non-transitory computer-readable storage medium, media, or physical computer storage known in the art. An example storage medium can be coupled to the processor such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium can be integral to the processor. The storage medium can be volatile or nonvolatile. The processor and the storage medium can reside in an ASIC. The ASIC can reside in a user terminal. In the alternative, the processor and the storage medium can reside as discrete components in a user terminal.

(231) Conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment.

(232) Disjunctive language such as the phrase “at least one of X, Y, or Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to present that an item, term, and so forth, may be either X, Y, or Z, or any combination thereof (for example, X, Y, and/or Z). Thus, such disjunctive language is not generally intended to, and should not, imply that certain embodiments require at least one of X, at least one of Y, or at least one of Z to each be present.

(233) Any process descriptions, elements, or blocks in the flow diagrams described herein and/or depicted in the attached figures should be understood as potentially representing modules, segments, or portions of code which include one or more executable instructions for implementing specific logical functions or steps in the process. Alternate implementations are included within the scope of the embodiments described herein in which elements or functions may be deleted, executed out of order from that shown or discussed, including substantially concurrently or in reverse order, depending on the functionality involved, as would be understood by those skilled in the art.

(234) Unless otherwise explicitly stated, articles such as “a” or “an” should generally be interpreted to include one or more described items. Accordingly, phrases such as “a device configured to” are intended to include one or more recited devices. Such one or more recited devices can also be collectively configured to carry out the stated recitations. For example, “a processor configured to carry out recitations A, B and C” can include a first processor configured to carry out recitation A

working in conjunction with a second processor configured to carry out recitations B and C.

(235) All of the methods and processes described herein may be embodied in, and partially or fully automated via, software code modules executed by one or more general purpose computers. For example, the methods described herein may be performed by the computing system and/or any other suitable computing device. The methods may be executed on the computing devices in response to execution of software instructions or other executable code read from a tangible computer readable medium. A tangible computer readable medium is a data storage device that can store data that is readable by a computer system. Examples of computer readable mediums include read-only memory, random-access memory, other volatile or non-volatile memory devices, CD-ROMs, magnetic tape, flash drives, and optical data storage devices.

(236) It should be emphasized that many variations and modifications may be made to the herein-described embodiments, the elements of which are to be understood as being among other acceptable examples. All such modifications and variations are intended to be included herein within the scope of this disclosure. The section headings used herein are merely provided to enhance readability and are not intended to limit the scope of the embodiments disclosed in a particular section to the features or elements disclosed in that section. The foregoing description details certain embodiments. It will be appreciated, however, that no matter how detailed the foregoing appears in text, the systems and methods can be practiced in many ways. As is also stated herein, it should be noted that the use of particular terminology when describing certain features or aspects of the systems and methods should not be taken to imply that the terminology is being re-defined herein to be restricted to including any specific characteristics of the features or aspects of the systems and methods with which that terminology is associated.

(237) Those of skill in the art would understand that information, messages, and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

Claims

1. An operational settings server (OSS) computer system for communicating vehicle data, the OSS computer system comprising: one or more hardware computer processors configured to execute a plurality of computer executable instructions to cause the OSS computer system to: access vehicle data originating from a vehicle management system and relating to an operational status of a vehicle, wherein the vehicle data indicates an energy status of one or more energy storage devices of the vehicle; access third-party rules originating from a remote server associated with a third party, wherein the third-party rules govern data communication between the remote server and the OSS computer system, wherein the third-party rules include: data preferences set by the third party indicating which portion of the vehicle data the third party is to receive, format preferences set by the third party indicating how the vehicle data should be presented to the third party, and timing preferences set by the third party indicating when the vehicle data should be provided to the third party; generate a dataset according to the data preferences of the third-party rules set by the third party, the dataset including the portion of the vehicle data indicated by the data preferences of the third-party rules and excluding another portion of the vehicle data as dictated by the data preferences of the third-party rules, wherein the portion of the vehicle data included in the dataset and the another portion of the vehicle data excluded from the dataset are based on a subscription of the third party; format the dataset into one or more of a table, chart, list, or graph according to the format preferences of the third-party rules set by the third party; and communicate the dataset to the remote server associated with the third party according to the timing preferences of the third-party rules set by the third party.

2. The OSS computer system of claim 1, wherein the one or more hardware computer processors are further configured to execute the plurality of computer executable instructions to cause the computer system to update the dataset with metadata.
3. The OSS computer system of claim 1, wherein the one or more hardware computer processors are further configured to execute the plurality of computer executable instructions to cause the computer system to obfuscate the dataset.
4. The OSS computer system of claim 1, wherein the one or more hardware computer processors are further configured to execute the plurality of computer executable instructions to cause the computer system to supplement the dataset with additional data.
5. The OSS computer system of claim 1, wherein the timing preferences of the third-party rules indicate a time to communicate the dataset to the remote server associated with the third party.
6. The OSS computer system of claim 1, wherein the timing preferences of the third-party rules indicate a schedule to communicate the dataset to the remote server associated with the third party.
7. The OSS computer system of claim 1, wherein the third-party rules indicate a condition for communicating the dataset to the remote server associated with the third party.
8. The OSS computer system of claim 1, wherein the vehicle data further includes a status of an on-board power generation system of the vehicle including an energy generation status of the on-board power generation system.
9. The OSS computer system of claim 1, wherein the vehicle data further includes a status of a driven mass of the vehicle.
10. The OSS computer system of claim 1, wherein the vehicle data further includes a status of an electrical switch in communication with the one or more energy storage devices.
11. The OSS computer system of claim 1, wherein the vehicle data further includes an estimated remaining operating time of the one or more energy storage devices of the vehicle and an estimated remaining operating distance of the one or more energy storage devices of the vehicle.
12. The OSS computer system of claim 1, wherein the vehicle data further includes a geographic location of the vehicle and a geographic location of a destination.
13. The OSS computer system of claim 1, wherein the vehicle data further includes a distance travelled by the vehicle.
14. The OSS computer system of claim 1, wherein the one or more energy storage devices of the vehicle includes a battery or a capacitor.
15. A computer-implemented method, comprising: accessing vehicle data originating from a vehicle management system and relating to an operational status of a vehicle; wherein the vehicle data indicates an energy status of one or more energy storage devices of the vehicle; accessing third-party rules originating from a remote server associated with a third party; wherein the third-party rules govern data communication with the remote server, wherein the third-party rules include: data preferences set by the third party indicating which portion of the vehicle data the third party is to receive, format preferences set by the third party indicating how the vehicle data should be presented to the third party, and timing preferences set by the third party indicating when the vehicle data should be provided to the third party; generating a dataset according to the data preferences of the third-party rules set by the third party, the dataset including the portion of the vehicle data indicated by the data preferences of the third-party rules and excluding another portion of the vehicle data as dictated by the data preferences of the third-party rules, wherein the portion of the vehicle data included in the dataset and the another portion of the vehicle data excluded from the dataset are based on a subscription of the third party; formatting the dataset into one or more of a table, chart, list, or graph according to the format preferences of the third-party rules set by the third party; and communicating the dataset to the remote server associated with the third party according to the timing preferences of the third-party rules set by the third party.
16. The computer-implemented method of claim 15, further comprising updating a format of the dataset according to the format preferences indicated by the third-party rules.

17. The computer-implemented method of claim 15, further comprising updating the dataset with metadata.
 18. The computer-implemented method of claim 15, further comprising obfuscating the dataset.
 19. The computer-implemented method of claim 15, further comprising supplementing the dataset with additional data.
 20. Non-transitory computer-readable media including computer-executable instructions that, when executed by an operational settings server (OSS) computing system, cause the OSS computing system to perform operations comprising: accessing vehicle data originating from a vehicle management system and relating to an operational status of a vehicle, wherein the vehicle data indicates an energy status of one or more energy storage devices of the vehicle; accessing third-party rules originating from a remote server associated with a third party, wherein the third-party rules govern data communication between the remote server and the OSS computer system, wherein the third-party rules include: data preferences set by the third party indicating which portion of the vehicle data the third party is to receive, format preferences set by the third party indicating how the vehicle data should be presented to the third party, and timing preferences set by the third party indicating when the vehicle data should be provided to the third party; generating a dataset according to the data preferences of the third-party rules set by the third party, the dataset including the portion of the vehicle data indicated by the data preferences of the third-party rules and excluding another portion of the vehicle data as dictated by the data preferences of the third-party rules, wherein the portion of the vehicle data included in the dataset and the another portion of the vehicle data excluded from the dataset are based on a subscription of the third party; formatting the dataset into one or more of a table, chart, list, or graph according to the format preferences of the third-party rules set by the third party; and communicating the dataset to the remote server associated with the third party according to the timing preferences of the third-party rules set by the third party.
 21. The non-transitory computer-readable media of claim 20, wherein the computer-executable instructions, when executed by the computing system, further cause the OSS computing system to perform operations comprising updating a format of the dataset according to the format preferences indicated by the third-party rules.
 22. The OSS computer system of claim 1, wherein a level of control granted to the third party to set the preferences of the third-party rules depends on a subscription of the third party.
 23. The computer-implemented method of claim 15, further comprising communicating the dataset to the remote server associated with the third party according to one or more of a time, a schedule, or a condition indicated by the timing preferences of the third-party rules.
 24. The non-transitory computer-readable media of claim 20, wherein the computer-executable instructions, when executed by the computing system, further cause the OSS computing system to perform operations comprising communicating the dataset to the remote server associated with the third party according to one or more of a time, a schedule, or a condition indicated by the timing preferences of the third-party rules.
 25. The non-transitory computer-readable media of claim 20, wherein the computer-executable instructions, when executed by the computing system, further cause the OSS computing system to perform operations comprising updating the dataset with metadata.
 26. The non-transitory computer-readable media of claim 20, wherein the computer-executable instructions, when executed by the computing system, further cause the OSS computing system to perform operations comprising obfuscating the dataset.
 27. The non-transitory computer-readable media of claim 20, wherein the computer-executable instructions, when executed by the computing system, further cause the OSS computing system to perform operations comprising supplementing the dataset with additional data.
-