

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12403384

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Lavallee; Alexandre et al.

Skate blade holder with blade attachment mechanism and blade therefor

Abstract

A skate and a replaceable skate blade are disclosed. The skate includes a boot and a blade assembly with a blade holder and a blade removably mounted to the holder. A locking pin is displaceable relative the blade holder between a blade locking position in which a tip of the locking pin is in engagement with the blade and a blade releasing position in which the tip of the locking pin is disengaged from the blade. A pin actuator is engageable by a user for translating the pin actuator along a longitudinal axis of the locking pin, wherein translation of the pin actuator induces translation of the locking pin along the longitudinal axis from the blade locking position to the blade releasing position. A biasing element reacts against the pin actuator and biasing the locking pin in the blade locking position.

Inventors: Lavallee; Alexandre (Ste-Anne-des-Lacs, CA), Cormack; Andrew (Deux-Montagnes, CA), Lapierre; Philippe (Montreal, CA), Harvey; Georges-Emmanuel (Laval, CA), Daoust; Bernard (Sutton, CA)

Applicant: SPORT MASKA INC. (Montreal, CA)

Family ID: 89170719

Assignee: SPORT MASKA INC. (N/A, N/A)

Appl. No.: 18/338986

Filed: June 21, 2023

Prior Publication Data

Document Identifier

Publication Date

US 20230405443 A1

Dec. 21, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: A63C1/16 (20060101)

U.S. Cl.:

CPC A63C1/16 (20130101);

Field of Classification Search

CPC: A63C (1/16); A63C (1/303)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3026118	12/1961	Pare	N/A	N/A
4251086	12/1980	Woolley	N/A	N/A
4353562	12/1981	Tiefenthal	N/A	N/A
5088749	12/1991	Olivieri	280/11.18	A63C 1/303
5123664	12/1991	DeMars	280/11.18	A63C 1/16
5332242	12/1993	Cann et al.	N/A	N/A
5484148	12/1995	Olivieri	N/A	N/A
5641169	12/1996	Bekessy	280/11.18	A63C 1/30
D396515	12/1997	Venier et al.	N/A	N/A
5988683	12/1998	Venier et al.	N/A	N/A
6039328	12/1999	Pawlowski et al.	N/A	N/A
6523835	12/2002	Lyden	N/A	N/A
D631120	12/2010	Salmon	N/A	N/A
8297627	12/2011	Smith, II	N/A	N/A
8353535	12/2012	Salmon et al.	N/A	N/A
8454030	12/2012	Corbeil	280/11.18	A63C 1/303
8534680	12/2012	Corbeil et al.	N/A	N/A
8550472	12/2012	Salmon	280/841	A63C 1/303
9717300	12/2016	Van Horne et al.	N/A	N/A
9855487	12/2017	Chartrand et al.	N/A	N/A
10894200	12/2020	Van Horne	N/A	A63C 1/303
2005/0167934	12/2004	Smith	N/A	N/A
2011/0121527	12/2010	Salmon et al.	N/A	N/A
2013/0038031	12/2012	Cruikshank et al.	N/A	N/A
2013/0285338	12/2012	Blois	N/A	N/A
2014/0062041	12/2013	Maars	N/A	N/A
2014/0284890	12/2013	Wuerthner	280/11.12	A63C 1/32
2017/0028291	12/2016	Green et al.	N/A	N/A
2022/0314100	12/2021	Yu	N/A	A63C 1/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
223321	12/1941	CH	N/A
H11225801	12/1998	JP	N/A
200435078	12/2006	KR	N/A
WO-2019218070	12/2018	WO	A43B 5/1641

OTHER PUBLICATIONS

WO-2019218070-A1 English Translation (Year: 2019). cited by examiner

KR-200435078-Y1 English Translation (Year: 2007). cited by examiner

JP-H11225801-A English Translation (Year: 1999). cited by examiner

Primary Examiner: Shriver, II; James A

Assistant Examiner: Walsh; Michael T.

Attorney, Agent or Firm: NORTON ROSE FULBRIGHT CANADA

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims priority on U.S. Patent Application No. 63/353,902 filed Jun. 21, 2022, and on U.S. Patent Application No. 63/370,698 filed Aug. 8, 2022, the entire contents of each of which are incorporated by reference herein.

TECHNICAL FIELD

(1) The application relates generally to ice skates and, more particularly, to ice skates having replaceable blades.

BACKGROUND

(2) Since skate boots are generally more durable than skate blades, it is known to provide skates with steel blades detachably received within a holder of the skate, such that the blades can be replaced when worn out or damaged. Furthermore, hockey players and/or equipment managers find value in carrying extra pre-sharpened blades that can be easily/rapidly replaced, during a game for example, which may be required to replace a worn or broken blade during a game or when sharpening of the existing blade is not possible. While existing blade attachment mechanisms are suitable for their intended purposes, improvements in such attachment mechanisms are sought.

SUMMARY

(3) There is accordingly provided a skate comprising: a boot; a blade assembly including: a blade holder attached beneath the boot, the blade holder having a bottom surface defining a groove and recesses extending upwardly from the groove, the blade holder having a socket defining a socket opening located in a lateral side of the blade holder; a blade removably mounted to the blade holder; a locking pin displaceable relative the blade holder along a longitudinal axis between a blade locking position in which a tip of the locking pin is in engagement with the blade and a blade releasing position in which the tip of the locking pin is disengaged from the blade; a pin actuator received within the socket of the blade holder, the pin actuator engageable by a user for translating the pin actuator along the longitudinal axis, the pin actuator engaged with the locking pin such that translation of the pin actuator induces translation of the locking pin along the longitudinal axis from the blade locking position to the blade releasing position; and a biasing element mounted to the blade holder to react against the pin actuator and biasing the locking pin in the blade locking

position.

(4) The skate as defined above and described herein may also include one or more of the following features, in whole or in part, and in any combination.

(5) In certain aspects, the blade includes a body defining an ice-engaging edge and a top edge opposite the ice-engaging edge, projections extending from the top edge and away from the ice-engaging edge, the blade moveable with respect to the blade holder between an engagement position in which the top edge is received in the groove and a disengagement position in which the blade is disengaged from the recesses and the groove.

(6) In certain aspects, one of the projections defines a cam surface that is rearwardly facing, and a tip-engaging wall surface merging with the cam surface at a turning point and extending inwardly into said one of the projections, the locking pin in engagement with the tip-engaging wall surface in the blade locking position and disengaged from the tip-engaging wall surface in the blade releasing position.

(7) In certain aspects, a slot is defined in said one of the projections, the tip-engaging wall surface defined by a top edge of the slot.

(8) In certain aspects, the tip of the locking pin has a top edge extending from the apex on an opposite side of the cam surface, at least part of the top edge contacting the tip-engaging wall surface of the projection in the blade locking position.

(9) In certain aspects, the top edge of the locking pin and the tip-engaging wall surface have a complementary outline.

(10) In certain aspects, the tip of the locking pin has an apex and a cam surface extending from the apex, the cam surface being curved.

(11) In certain aspects, the tip of the locking pin has an asymmetric shape relative to a horizontal plane containing the longitudinal axis of the locking pin.

(12) In certain aspects, a bellows extends between the pin actuator and an oppositely facing surface of the blade holder, the bellows surrounding peripherally the biasing element.

(13) In certain aspects, the pin actuator has an annular shape to receive the locking pin therein, the pin actuator having a forward-facing surface angled relative to the longitudinal axis, and a seating surface facing opposite to the forward-facing surface, the seating surface engaging the biasing element.

(14) In certain aspects, the pin actuator is fully recessed within the socket.

(15) In certain aspects, the pin actuator and the biasing element are fully recessed in the socket.

(16) In certain aspects, a damping feature defines an interface with a portion of the top edge of the blade when the blade is engaged with the blade holder, the damping feature located in the groove.

(17) In certain aspects, the blade holder has a front pedestal and a rear pedestal, the damping feature located underneath the rear pedestal.

(18) In certain aspects, the damping feature includes a strip of material softer than a material of the blade holder.

(19) In certain aspects, the blade holder has a front pedestal defining an internal cavity and a rear pedestal, a respective one of the recesses opening into the internal cavity.

(20) In certain aspects, the projections include a front projection and a rear projection, the front projection insertable into a respective one of the recesses defined in the front pedestal, the front projection being forwardly angled.

(21) In certain aspects, the front projection has a tapered shape that converges from a base of the front projection to a tip of the front projection.

(22) In certain aspects, a width of the front projection in a direction transverse to a fore-aft direction is substantially constant along its length.

(23) In certain aspects, at least the base of the front projection matingly engages respective one of the recesses defined in the front pedestal when the blade is in an in-use position.

(24) In certain aspects, the projections include a front projection and a rear projection, the rear

projection includes an apex and a cam surface extending from the apex, the cam surface of the rear projection slidably engaging the cam surface of the locking pin as the locking pin displaces between the blade locking position and the blade releasing position.

(25) There is also provided a locking mechanism for a blade holder compatible with a replaceable blade, the locking mechanism comprising: a locking pin mounted within the blade holder, the locking pin translatable relative to a longitudinal axis thereof between a blade locking position and a blade releasing position, the locking pin including a tip having an apex and a cam surface extending from the apex for engaging with a cam surface of the replaceable blade; a pin actuator receivable within a socket of the blade holder, the pin actuator engaged with the locking pin to displace the locking pin axially between the blade locking position and the blade releasing position, wherein axial displacement of the pin actuator along the longitudinal axis causes translation of the locking pin along the longitudinal axis; and a biasing element mounted to react against the pin actuator and biasing the locking pin in the blade locking position.

(26) The locking mechanism as defined above and described herein may also include one or more of the following features, in whole or in part, and in any combination.

(27) In certain aspects, the tip of the locking pin has an asymmetric shape relative to a horizontal plane containing a longitudinal axis of the locking pin, the cam surface being curved.

(28) In certain aspects, the biasing element includes a spring mounted about the locking pin.

(29) In certain aspects, the locking pin has a peripheral section at an end of the locking pin opposite to the tip, the peripheral section having a non-circular or asymmetric cross-section.

(30) In certain aspects, the peripheral section has at least one flat.

(31) In certain aspects, the tip has an apex from which extends the cam surface, the apex offset relative to the longitudinal axis.

(32) In certain aspects, the tip has a top edge extending from the apex, the top edge flat along at least part of the tip.

(33) In certain aspects, the pin actuator has an annular shape to receive the locking pin therein.

(34) In certain aspects, the pin actuator has a forward-facing surface angled relative to the longitudinal axis, and a seating surface facing in an opposite direction from the forward-facing surface, the seating surface engaging the biasing element.

(35) In certain aspects, a bellows peripherally surrounds the biasing element.

(36) There is further provided a replaceable blade for a skate, the replaceable blade comprising a body defining an ice-engaging edge, a top edge opposite the ice-engaging edge, a first projection and a second projection each extending upwardly from the body, the first and second projections configured for being received within a respective recess defined by a blade holder of the skate.

(37) The replaceable blade as defined above and described herein may also include one or more of the following features, in whole or in part, and in any combination.

(38) In certain aspects, the second projection defines a cam surface that is rearwardly facing, and a tip-engaging wall surface merging with the cam surface at a turning point and extending inwardly into the second projection.

(39) In certain aspects, the tip-engaging wall surface is flat.

(40) In certain aspects, the second projection has an apex, the tip-engaging wall surface located between the top edge of the body and the apex.

(41) In certain aspects, the cam surface has a convex curvature.

(42) In certain aspects, the cam surface extends from the apex to the tip-engaging wall surface.

(43) In certain aspects, the tip-engaging wall surface and the cam surface form an acute angle.

(44) In certain aspects, a slot is defined in the second projection, the slot inwardly extending between the top edge of the body and the apex, the tip-engaging wall surface defined by a top edge of the slot.

(45) In certain aspects, the slot has an asymmetric shape.

(46) In certain aspects, the slot has a bottom edge facing towards the top edge of the slot, the

bottom edge is curved.

(47) In certain aspects, the second projection is a rear projection of the replaceable blade, the rear projection engageable with a rear pedestal of a blade holder of the skate, the rear projection having a rearward-facing edge, the tip-engaging wall surface defined in the rearward-facing edge.

(48) In certain aspects, the first projection is a front projection, the front projection being forwardly angled.

(49) In certain aspects, the first projection has a tapered shape that converges from a base of the front projection to a tip of the front projection.

(50) In certain aspects, an upper section of the blade is adapted to be received within a groove of a blade holder of the skate, the upper section extending between a fore end to an aft end of the blade, the upper section having a thickness $T1$ measurable from the top edge to a boundary line that is offset with and generally parallel to the top edge, wherein the first projection has a height $H1$, the height $H1$ at least two times the thickness $T1$ of the upper section.

(51) In certain aspects, the height $H1$ is three times the thickness $T1$ of the upper section.

(52) In certain aspects, the groove of the blade holder has a depth DG and the front projection has a height $H1$. the height $H1$ is at least two times the depth DG .

(53) In certain aspects, the height $H1$ is three times the depth DG of the groove.

(54) There is also provided a skate comprising: a boot and a blade assembly; the blade assembly including: a blade holder attached beneath a sole of the boot, the blade holder having a bottom surface defining a groove and recesses extending upwardly from the groove; a blade including a body defining an ice-engaging edge and a top edge opposite the ice-engaging edge, projections extending from the top edge and away from the ice-engaging edge, a slot defined in one of the projections, the blade moveable with respect to the blade holder between an engagement position in which the top edge is received in the groove and a disengagement position in which the blade is disengaged from the recesses and the groove; a locking pin displaceable within the blade holder along a longitudinal axis between a locked position in which the locking pin is in engagement with the slot and an unlocked position in which the locking pin is disengaged from the slot; a pin actuator received within a socket of the blade holder, the socket having at least one socket opening located on one of opposed lateral sides of the blade holder, the pin actuator engageable by a user for translating the pin actuator along the longitudinal axis, the pin actuator engaged with the locking pin such that translation of the pin actuator induces translation of the locking pin along the longitudinal axis from the locked position to the unlocked position; and a spring mounted within the blade holder to react against the pin actuator and biasing the locking pin in the blade locked position.

(55) In certain embodiments, the blade includes a body defining an ice-engaging edge and a top edge opposite the ice-engaging edge, projections extending from the top edge and away from the ice-engaging edge, a slot defined in one of the projections, the blade moveable with respect to the blade holder between an engagement position in which the top edge is received in the groove and a disengagement position in which the blade is disengaged from the recesses and the groove.

(56) There is also provided a locking mechanism for a blade holder comprising: a locking pin mounted within the blade holder, the locking pin translatable relative to a longitudinal axis thereof between a locked blade position and a released blade position, the locking pin including a tip having an asymmetric shape relative to a horizontal plane extending through a longitudinal axis of the locking pin; a pin actuator within a socket of the blade holder via at least one opening of the socket, the pin actuator engaged with the locking pin to displace the locking pin axially between the locked blade position and the released blade position, wherein axial displacement of the pin actuator along the longitudinal axis causes translation of the locking pin along the longitudinal axis; and a spring mounted to react against the pin actuator and biasing the locking pin in the blade locked position.

(57) There is further provided a replaceable blade for a skate, the replaceable blade comprising a

body defining an ice-engaging edge, an elongated top edge opposite the ice-engaging edge, a first projection and a second projection each extending upwardly from the body, the first and second projections configured for being received within a respective recess defined by a blade holder of the skate, the second projection having an inwardly extending slot, the inwardly extending slot having an asymmetric shape.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Reference is now made to the accompanying figures in which:
- (2) FIG. 1 is a side, partially-sectioned, view of a skate having a blade assembly in accordance with one embodiment of the present disclosure;
- (3) FIG. 2 is an enlarged side, partially sectioned, view of the blade assembly of FIG. 1, showing a blade attachment mechanism disengaged from a blade;
- (4) FIG. 3a is a side, partially sectioned, view of the blade attachment mechanism of FIG. 2, shown engaged with a blade;
- (5) FIG. 3b is an enlarged view of the tip of a locking pin of the blade attachment mechanism of FIG. 3a, shown in a slot of the blade;
- (6) FIG. 4 is a exploded side view of the skate and blade assembly of FIG. 1;
- (7) FIG. 5 is a cross-sectional view of the blade assembly of FIGS. 1-2, with the blade attachment mechanism removed and shown with the blade in a disengaged position relative to a blade holder of the blade assembly;
- (8) FIG. 6 is a cross-sectional view of the blade assembly of FIG. 5, shown with a front projection of the blade partially inserted into a front recess in the blade holder;
- (9) FIG. 7 is a cross-sectional view of the blade assembly of FIG. 5, shown with the front projection of the blade inserted further into the front recess of the blade holder and a rear projection of the blade partially inserted into a rear recess of the blade holder;
- (10) FIG. 8 is a cross-sectional view of the blade assembly of FIG. 5, shown with the blade in an engagement position, with the front projection of the blade fully inserted into the front recess of the blade holder and the rear projection of the blade fully inserted into the rear recess of the blade holder; and
- (11) FIG. 9 is a bottom partial view of the blade assembly of FIGS. 1-2, shown without the blade.

DETAILED DESCRIPTION

- (12) Referring to FIG. 1, the ice skate **10** (e.g. an ice hockey skate—hereinafter simply “skate”) which includes a blade assembly **20** attached beneath a sole **18** of the boot **12**. The blade assembly **20** generally includes a blade holder **26** and a blade **24** that is removably attached to the blade holder **26**.
- (13) The blade holder **26** includes a front pedestal **30** having a top end configured to be connected to the sole **18** of the boot **12** near a toe portion **14** thereof, a rear pedestal **32** having a top end configured to be connected to the sole **18** of the boot **12** near a heel portion **16** thereof, and a bridge portion **34** interconnecting the front and rear pedestals **30**, **32**. As will be further described later, the pedestals **30**, **32** (or at least one of the pedestals) are hollowed and may define respective internal cavities.
- (14) The bottom surface **36** of the blade holder **26** has an elongated groove **40** defined therein, and the blade holder **26** further includes front and rear recesses **42**, **44** defined therein, extending upwardly from the elongated groove **40** in alignment with each pedestal **30**, **32**. The groove **40** and recesses **42**, **44** may not be in communication with internal cavities within the pedestals **30**, **32**. In the depicted embodiment, the front recess **42** communicates with the internal cavity of the front pedestal **30**. As depicted in FIGS. 5-9 and described below, the front recess **42** of the blade holder

26 communicates and is opened to an internal cavity **84** within the front pedestal **30** of the blade holder **26**. While the rear recess **44** may or may not communicate with an internal cavity in the rear pedestal **32** depending on the embodiment, in the depicted embodiment, the rear recess **44** is enclosed such that it is not in communication with any internal cavities within the rear pedestal **32**, and accordingly there is not any communication between an internal cavity of the rear pedestal **32** and the rear recess **44** that receives the rear projection **54** of the blade **24**.

(15) The blade **24** has a body **46** having a generally planar shape, preferably having a constant thickness. In a particular embodiment, the blade **24** is made of steel; however other appropriate materials may alternately be used. The body **46** defines an ice-engaging edge **48** configured to slide on ice, and an elongated top edge **50** opposite the ice-engaging edge **48**. Two projections **52**, **54** extend upwardly from the body **46**: a front projection **52** at the front of the blade **24**, and a rear projection **54** at the rear of the blade **24**. In the embodiment shown, the elongated top edge **50** is free of other projection between the two projections **52**, **54**. Other configurations are however contemplated, wherein the elongated top edge **50** extending between the two projections **52**, **54** may have one or more grooves, cut-outs and/or smaller projections thereon.

(16) The top edge **50** of the blade **24** and the elongated groove **40** of the holder **26** are configured and sized such as to be complementary and removably engageable together. The top edge **50** is received within the groove **40** when the blade **24** is attached to the blade holder **26**. As shown at least in FIG. **1** and with additional reference to FIG. **4**, an upper section **51** of the body **46** of the blade **24** is adapted to be received into the groove **40**. The upper section **51** extends between a fore end and an aft end of the blade **24**. The blade **24** may therefore be laterally supported on opposite sides of its body **46** by the upper section **51** of the body **46** along a substantial 90%)—or all—of the length of the blade **24**. The upper section **51** includes the top edge **50**. The upper section **51** has a thickness **T1** (see FIG. **4**) that is measured from the top edge **50**, or an imaginary line following the top edge **50**, towards the ice-engaging edge **48**. As illustrated in FIG. **4**, the upper section **51** may be defined longitudinally along the length of the blade **24**, and delimited by the top edge **50** and an boundary line that is offset with and generally parallel to the top edge **50**. Such thickness **T1** may correspond to the depth **DG** of the groove **40** (described below).

(17) The front projection **52** of the blade **24** and the front recess **42** are configured, positioned and sized so as to be removably engageable one into the other; the rear projection **54** of the blade **24** and the rear recess **44** are configured, positioned and sized so as to be removably engageable one into the other. More particularly, the projections **52**, **54** and recesses **42**, **44** are configured, positioned and sized such that the blade **24** and blade holder **26** are relatively moveable, with the projections **52**, **54** moveable within their respective recess **42**, **44**, between an engagement position and a disengagement position.

(18) In the engagement position of the blade **24** and holder **26**, abutting surfaces of the projections **52**, **54** and recesses **42**, **44** and interaction between a locking mechanism **28** (described further below) with the blade **24** assist in reducing unintended removal or disengagement of the projections **52**, **54** from the recesses **42**, **44**, thus maintaining the blade **24** in the holder **26**. In the disengagement position, the blade **24** is removed from the holder **26**; the projections **52**, **54** thus have appropriate freedom of movement within the respective recess **42**, **44** to allow disengagement of the blade **24** from the recesses **42**, **44** and elongated groove **40**. Movement between the engagement and disengagement positions of the blade **24** and holder **26** may include translation (e.g. along a longitudinal direction of the blade **24** and/or along an angled direction non-parallel to the longitudinal direction and the vertical direction) and/or rotation of the blade **24** (e.g. pivot around a point defined in or around the recess **42** of the front pedestal **30**), depending on the configuration of the projections **52**, **54** and recesses **42**, **44**. This will be described in further detail below, with reference to FIGS. **5-8**.

(19) As seen in FIG. **4**, the front recess **42** extends through a bottom wall of the front pedestal **30** so that the front projection **52** of the blade is matingly received into the front recess **42**.

(20) With further reference to FIG. 4, the front recess **42** has a front wall portion **42F** and a rear wall portion **42R** facing the front wall portion **42F** on an opposite side of the recess **42** in a fore-aft direction of the blade holder **26**. The front wall portion **42F** defines a bulge or convex surface **42FC** facing generally rearwardly. The convex surface **42FC** merges with the bottom of the groove **40**. Such convex surface **42FC** has a turning point and further extends pass the turning point upwardly and forwardly therefrom. As can be seen, the front wall portion **42F** generally form an acute angle **A1** with the portion of the bottom of the groove **40** extending forward of the front wall portion **42F**. The rounded corner defined by the convex surface **42FC** is configured to mate with a complementary portion of the projection **52**. The convex surface **42FC** and the complementary portion of the projection **52** may therefore form a male-female engagement, as will be further described later with reference to FIGS. 5-8. As shown, the front wall portion **42F** has a straight wall segment **42FS** extending upwardly from the convex surface **42FC** and merging therewith. The convex surface **42FC** and the straight wall segment **42FS** may form one continuous surface. Such straight wall segment **42FS** may also be configured to mate with a complementary portion of the projection **52**. The rear wall portion **42R** of the recess **42** merges with the bottom of the groove **40**. The rear wall portion **42R** has a straight wall segment **42RS** extending forwardly and upwardly from the bottom of the groove **40**. Such straight wall segment **42RS** is configured to mate with a complementary portion of the projection **52**.

(21) As shown, the front projection **52** extends at an angle, such that it is forwardly inclined (i.e. the front projection **52** of the blades extends upwardly and forwardly, to define a forward leaning male projection). The front projection **52** is also tapered, or converging, in shape, wherein the front projection **52** is wider (in a fore-aft direction of the blade **24**) at its base than at its remote tip. The forward inclination and/or the converging shape of the front projection **52** enables the front projection **52** of the blade **24** to be easily received within the front recess **42** when the blade **24** is being installed into the blade holder **26**, as will be described in further detail below with reference to FIGS. 5-8. The front projection **52** has a length **L1** that is defined from its base to its remote tip. Such length **L1** may be the length of a central line, which may be non-straight, extending from a middle of its base to the remote tip. The front projection **52** has a height **H1** which may be defined as a distance from the top edge **50** of the blade **24**, immediately adjacent of the base of the projection **52** and a tangent line at the tip of the projection that generally parallel to the top edge of the blade **24**. In at least some embodiments, such height **H1** is at least two times that of a depth **DG** of the groove **40** defined as a distance between the bottom of the groove **40** and the bottom surface **36** of the blade holder **26**. In an embodiment, the height **H1** is three times ($\pm 10\%$) that of the depth **DG**. Such proportions may correspond to the proportions of the height **H1** and the thickness **T1** (described above) of the upper section **51** of the blade **24**, where the thickness **T1** is measured immediately adjacent to the base of the front projection **52**, or aligned therewith. Having such a height **H1** relative to the depth **DG** of the groove **40** and/or thickness **T1** of the upper section **51** adapted to be received in the groove **40** may make unintended retraction of the projection **52** from the recess **42** more difficult than some alternative with lower height **H1**. Once fully mated within the cooperating front recess **42**, such a higher height projection **52** may cause the blade **24** to be less easily disconnected from the blade holder **26** in the event of warping or deformation of the blade holder (which can sometimes occur, for example, when the blade holder is hit by a puck).

(22) Referring now more particularly to FIG. 2 and the rear projection **54**, the rear projection **54** of the blade **24** has a generally pyramid or fin-like shape (when viewed from the side), and defines a forward-facing edge **53** and a rearward-facing edge **55** that extend up from the top edge **50** of the body **46** of the blade **24** and meet at an apex **57** of the rear projection **54**.

(23) As seen in FIG. 2, at least the rearward-facing edge **55** is slightly curved, or stated differently the rearward-facing edge **55** of the rear projection **54** has a greater curvature (e.g. radius of curvature about an axis transverse to the blade **24**) than that of the frontward-facing surface **53** of the rear projection **54**. In the depicted embodiment, the frontward-facing surface **53** is substantially

straight, although alternatives are possible. Accordingly, the curved rearward-facing edge 55 of the rear projection 54 of the blade 24 forms a curved surface having a convex curvature (which may also be referred to as a cam surface 55c) along which a tip 28a' of the locking pin 28a of the locking mechanism 28 is able to slide. In other embodiments, such cam surface 55c formed by the rearward-facing edge 55 may be at least partially straight, or even entirely straight, from the apex 57 and enable the sliding of the tip 28a' of the locking pin 28a of the locking mechanism 28. As can be seen in FIG. 2, the relative orientation of the cam surface 55c and the angle of attack of the locking pin 28a, or angle A3 between the longitudinal axis L and a tangent of the cam surface 55c is an obtuse angle so as to effect a pushing motion against the locking pin 28a when the projection 54 is inserted into the recess 44.

(24) Referring now to FIGS. 2 and 3, the rear projection 54 also includes a tip-engaging wall surface defined therein. Such tip-engaging wall surface is defined at an end of the cam surface 55c. The tip-engaging wall surface extends inwardly into the rear projection 54, from the cam surface 55c. The tip-engaging wall surface is adapted to engage with the tip 28a' of the locking pin 28a once such tip 28a' has slid on the cam surface 55c to gain the blade locking position as described below. In the depicted embodiment, such tip-engaging wall surface is defined by a slot 60 defined in the rear projection 54. The slot 60 is defined in the rearward-facing edge 55 of the rear projection 54 and is open rearwardly, as shown in FIG. 2. The slot 60 is located at a predetermined position above the top edge 50 of the body 46 of the blade 24, and more particularly at a point between the top edge 50 of the body of the blade 24 and the apex 57 of the rear projection 54. The slot 60 is sized, shaped and positioned to receive the tip 28a' of the locking pin 28a therein (as will be described in further detail below).

(25) In at least some embodiments, as seen in FIGS. 2 and 3, the slot 60 has an asymmetrical shape. More particularly, as shown, the slot 60 is defined at least in part by a top edge 60' that extends substantially linearly into the rear projection 54 from the rearward-facing edge 55, thereby forming the tip-engaging wall surface described above, and a bottom edge 60'' that is curved in this example. The bottom edge 60'' thus may differ from the top edge 60' to define the asymmetrical shape of the slot 60 in the rear projection 54 of the blade 24.

(26) As shown, the top edge 60' merges with the cam surface 55c at a turning point. In at least some embodiments, the top edge 60' and the cam surface 55c extending between the apex 57 and the slot 60 may form an angle A4 (FIG. 3b) that is equal or smaller than 90 degrees. Having an acute angle between the top edge 60' and the cam surface 55c allows said cam surface 55c to progressively push away the locking pin 28a along the longitudinal axis L of the locking pin 28a, as the locking pin 28a slides thereon during insertion of the projection 54 in a direction transverse to the longitudinal axis L.

(27) In embodiments where the cam surface 55c is curved, such angle may be measured between a projection line extending from the apex 57 to a turning point at the junction of the cam surface 55c and the top edge 60', and a projection line extending along the top edge 60' and crossing with the projection line at the turning point. Depending on the shape of the projection 54, e.g., more or less acute at the apex 57), and/or general orientation of the projection 54 when engaged in the recess 44 in the engagement position, the top edge 60' may extend at least partially away from the apex 57. Stated differently, the top edge 60' may extend in a direction having a vector component heading away from the apex 57. The slot 60 may thus extend downwardly relative to the apex 57, from its opening along the rearward-facing edge 55. In fact, the slot 60 may also be shaped as an opening that does not include a bottom edge 60'', in which case the slot 60 may instead define and be referred to as a cut-out or opening in the rear projection 54.

(28) The slot 60 is configured to be engaged by the locking mechanism 28 for either maintaining the elongated blade 24 within the blade holder 26 or for allowing the elongated blade 24 to be removed from the blade holder 26 for substituting the blade 24 by another blade.

(29) Further in accordance with the depicted embodiment, the slot 60 of the rear projection 54 faces

toward the rear, or the heel portion **16**, of the skate **10** whereas the front projection **52** extends forwardly toward the front, or the toe portion **14**, of the skate **10**.

(30) The different components of the blade holder assembly **20** having been set forth, the locking mechanism **28** is now described in further detail herein below. The locking mechanism **28** configured for maintaining the blade **24** and blade holder **26** in their engagement position may be connected to the rear pedestal **32**, and movable between a locked position (FIG. **3**) and an unlocked position (FIGS. **1** and **2**).

(31) Referring to FIGS. **1-4**, the locking mechanism **28** includes a locking pin **28a** engaged to the holder **26** and received in the aperture **64** (see FIGS. **4-5**). The locking pin **28a** has a tip **28a'** that defines an engagement end of the locking pin **28a** and which, in the locked position (blade locking position), protrudes into the recess **44** and is received in the slot **60** of the rear projection **54** of the blade **24** (see FIG. **3**), thus maintaining the rear projection **54** of the blade in the recess **44** of the blade holder **26**, and maintaining the blade **24** in the engagement position. In the unlocked position (blade releasing position), the locking pin **28a** is retracted by being longitudinally displaced along a longitudinal axis L of the pin **28a**, and accordingly disengaged from the rear projection **54**, so that the blade **24** can be removed. The locking pin **28a** is thus displaceable along the longitudinal axis L thereof between the locked position and the unlocked position. The locking pin **28a** is engaged with the slot **60** in the locked position and disengaged from the slot **60** in the unlocked position.

(32) As best seen in FIG. **3b**, the tip **28a'** of the locking pin **28a** may have a shape that is complementary to the shape of the slot **60**. More particularly, in the depicted embodiment, the tip **28a'** includes a top edge **31** of the locking pin **28a** and a cam surface **33** that extends away, rearwardly, from the top edge **31**. As such, the tip **28a'** of the locking pin **28a** has an asymmetric shape—which may be defined for example relative to a horizontal plane extending through/containing the longitudinal axis L. As shown, the tip **28a'** may have an apex **29**, from which extends the top edge **31** and/or the cam surface **33**. The apex **29** may not be aligned with the longitudinal axis L, i.e., it may be offset relative to the longitudinal axis L. The tip **28a'** of the locking pin **28a** acts somewhat like a door latch, in that the cam surface **33** is capable of easily sliding against the cam surface **55c** of the rearward-facing edge **55** of the rear projection **54** on the blade **24**, as the rear projection **54** of the blade **24** is inserted into the recess **44** of the blade holder **26**. The cam surface **55c** of the rear projection **54** and the cam surface **33** of the locking pin **28a** may therefore define parts of a cam assembly. In at least some embodiments, as shown, the cam surface **33** of the locking pin **28a** may be curved. Curvature of the cam surface **55c** of the rear projection **54** may have a constant or varying curvature along its length between the apex **57** and the turning point with the top edge **60'**. As shown, the curvature of the cam surface **33** is a convex curvature. During sliding engagement of the cam surface **33** of the locking pin **28a** and the cam surface **55c** of the projection **54**, the locking pin **28a** may progressively push the locking pin **28a** towards the unlocked position. Because the locking pin **28a** is biased in its extended (locked) position, as will be described in further detail below, once the tip **28a'** of the locking pin **28a** reaches the slot **60** in the rear projection **54** of the blade **24**, the tip **28a'** may project into the slot **60** and thereby retains the blade **24** in place on the blade holder **26**.

(33) In at least some embodiments, the top edge **31** of the locking pin **28a** may have a complementary outline with that of the top edge **60'**. Such complementary outline may be flat or straight, as shown. At least part of the top edge **31** of the locking pin **28a** may contact the top edge **60'** when in the locked position. In an embodiment, the top edge **31** of the locking pin **28** may be coplanar with the longitudinal axis L and/or coplanar with the top edge **60'**. Such coplanar configuration of the top edge **60'** and the top edge **31** of the locking pin **28a** may provide a greater contact surface between both the locking pin **28a** and the projection **54**. These factors, in combination with the extent to which the locking pin **28a** extends into the slot **60** may all contribute to better preventing unintended retraction of the locking pin **28a** from the slot **60**. The tip **28a'** of the locking pin **28a** may contact an end of the slot **60**, depending on the depth thereof,

when in the locked position; however this is optional. The slot **60** may be sized so as to receive the tip **28a'** while still having a clearance (no interference) with the end of the slot **60**. Similarly, the cam surface **33** of the locking pin **28a**—the surface facing towards the bottom edge **60''**—may not contact the bottom edge **60''** in the locked position. In some embodiments, however, the slot **60** may be sized and shaped so as to have mating engagement, or contact, between the bottom edge **60''** and the curved surface **33**.

(34) The locking mechanism **28** further includes a pin actuator **28b** which is mounted to the locking pin **28a** and translatable therewith along the longitudinal axis L. In one particular embodiment, the pin actuator **28b** is fixed in place on the locking pin **28a**, such that no relative movement therebetween is possible. Fixing may be thread engagement, or interference fit for example. By grasping the pin actuator **28b** and translating it along the longitudinal axis L, the locking pin **28a** is in turn translated axially along the axis L. In the depicted embodiment, for example, by grasping the pin actuator **28b** and translating it rearwardly (e.g. to the right in FIG. 3), in a direction away from tip **28a'**, the locking pin **28a** will be displaced from the locked position (as shown in FIG. 3) to the unlocked position (as shown in FIG. 2).

(35) In the depicted embodiment, the pin actuator **28b** has an annular shape. The pin actuator **28b** may be concentrically fixed to the locking pin **28a**. The locking pin **28a** may extend through the pin actuator **28b**. In at least some embodiments, as shown, the pin actuator **28b** has a textured surface **28b'** to facilitate grasping and/or limit slippage at contact for actuation of the locking mechanism **28**. The surface **28b'** is forwardly facing, such that, upon grasping, the user may apply a load on the surface **28b'** in the direction of translation so as to translate the pin actuator **28b** along the longitudinal axis L. In the embodiment shown, the surface **28b'** is angled relative to the longitudinal axis L. The surface **28b'** could be normal to the longitudinal axis L in other embodiments. Such surface **28b'** may not be textured in other embodiments. The pin actuator **28b** includes a seating surface **28b''** facing in an opposite direction as the surface **28b'**. The seating surface **28b''** is adapted to engage with the biasing element **70** and/or bellows **80**, which are described later.

(36) As seen in FIGS. 2 and 3, the pin actuator **28b** is accessible through a corresponding socket C defined in the blade holder **26** and extending from one lateral side of the blade holder **26** to the other, so that the pin actuator **28b** is accessible to the user via either one of the lateral sides of the blade holder **26**. The socket C could have other configurations in other embodiments. For example, in some variants, the socket C receiving the pin actuator **28b** may be opened only towards a medial side or lateral side of the blade holder **26**. The socket C could form a receptacle enclosure in which the pin actuator **28b** may partially be recessed, with access to such receptacle enclosure only possible from a single lateral side of the blade holder **26** or both lateral sides of the blade holder **26**, as shown. Access to the enclosure or pin actuator **28b** from both lateral sides (lateral and medial) of the blade holder **26** may facilitate a manual holding/pinching of the pin actuator **28b** for unlocking operation. In an embodiment, the pin actuator **28b** is sized to be fully recessed within the socket C. This may prevent undesired contacts in a translation direction with external objects, hence limit undesired activation of the locking mechanism **28** during skating or in a context of normal use, for instance the practice of hockey.

(37) The locking pin **28a** is biased in the locked position (FIG. 3), using a spring **70** (see FIG. 4) that is mounted about the locking pin **28a** and is concentric with the longitudinal axis L. The spring **70** is axially mounted between a surface of the blade holder **26** and the pin actuator **28b**, so as to exert a biasing force against the pin actuator **28b** in the direction of the rear projection **54** of the blade **24** (and more specifically in the direction of the slot **60** therein)—i.e. towards the left in FIG. 3. In one embodiment the spring **70** is a helical compression spring, as shown in FIG. 4. Alternately, the spring **70** may be another suitable spring or biasing element, including for example one or more spring blades and/or an elastomeric element, capable of generating the biasing force on the locking pin **28a** to bias it toward the locked (fully extended) position. In at

least some embodiments, the biasing element is fully recessed within the socket C.

(38) In the depicted embodiment, a bellows **80** may also be provided to surround and protect the spring **70**. In the depicted embodiment, the bellows **80** is a rubber or other suitable flexible material, and is capable of being collapsed—when the locking pin **28a** is retracted (FIG. 2)—and of expanding—when the locking pin **28a** is extended (FIG. 3). The bellows **80** accordingly serves to protect the spring **70** and a portion of the locking pin **28a** that would be otherwise exposed within the lateral openings of the socket C in the blade holder **26**. The bellows **80**, if present, may be fully recessed in the socket C.

(39) In some embodiments, the bellows **80** may contribute to the biasing force, but this is optional. The bellows **80** may offer low resistance to compression so as not to impede the retraction of the locking pin **28a** towards the unlocked position. As shown, the bellows **80** may extend from the pin actuator **28b** to an oppositely facing surface of the blade holder **26**. The bellows **80** may surround peripherally an entirety of the spring as shown. While item **80** is referred to as a bellows, it could also be referred to as a protective sleeve, resiliently deformable. When compressed between the pin actuator **28b** and the oppositely facing surface of the blade holder **26**, such protective sleeve may resiliently deform as the spring **70** is correspondingly compressed to retract the locking pin **28a** in the unlocked position.

(40) Optionally, a friction device, such as for example a rubber washer, may be used to limit travel of the locking pin **28a** and/or to help reduce vibrations caused by normal use of the skate from unwanted displacement of the locking pin **28a**.

(41) Rotation of the locking pin **28a** about the axis L may, such as in the depicted embodiment, be limited and/or completely prevented. For this purpose, an anti-rotation feature is provided. As shown, the anti-rotation feature is created by an engagement between a peripheral section (e.g. a rearmost portion) of the locking pin **28a** and an internal surface of the aperture **64** in the blade holder **26**. In the embodiment shown, the anti-rotation feature is created by the engagement of non-circular corresponding cross-sections of the peripheral section of the locking pin **28a** and of the internal surface of the aperture **64**. In an embodiment, as shown, the peripheral section **28a''** at the rear of the locking pin **28a** may have at least one flat so as to define a non-circular or asymmetric cross-section. The cross-section of the peripheral section **28a''** at the rear of the locking pin **28a** may have, for example, a rectangular or square cross-sectional shape. Other non-circular cross-section could be contemplated, such as other polygonal cross-sections (e.g., pentagonal, hexagonal, heptagonal, octagonal), or other cross-sections of irregular geometry. Flats are only one possibility that may form anti-rotation feature. Crenellations, undulations, peaks and valleys distributed about the peripheral section **28a''** are some other possibilities. The non-circular corresponding cross-sections may not be identical to one another as long as their engagement limits rotation of one relative to the other about the axis L. The anti-rotation features allow a translation displacement of the locking pin **28a** within the aperture **64**. As the locking mechanism **28** is actuated to retract the locking pin **28a**, the peripheral section **28a''** may slide or otherwise translationally move within the aperture **64**. Translational movement of the locking pin **28a** in the aperture **64** may be enabled by relaxed tolerance therebetween, e.g., sliding engagement. Lubricant, such as silicone lubricant, could be sprayed into the bellows **80** or in the aperture **64** before mounting the locking pin **28a** in place therein to allow even freer sliding.

(42) In a particular embodiment, the locking mechanism **28**, which remains at least in major part, and in some embodiments in entirety, outside of the pedestal's internal cavities, is easily accessible and engageable by the user, while still providing for sufficient retention of the blade **24** in the blade holder **26**.

(43) Referring now to FIGS. 5-8, the manner in which the blade **24** and the blade holder **26** are matingly engaged, and thus the manner that the blade **24** is received within (and removed from) the blade holder **26**, will now be described in further detail.

(44) In order to attach the blade **24** to the holder **26** using the locking mechanism **28** as described

above, the blade **24** may first be positioned into its final “in-use” position (i.e. to permit skating with the skate **10**) within the holder **26**. This position is shown in FIG. **8**. In order to insert the blade **24** into this position within the blade holder **26**, the following insertion process may be employed.

(45) Referring first to FIG. **5**, and as noted above, the front projection **52** of the blade **24** extends forwardly (i.e. towards the front of the blade) at an angle and may thus be defined as forward-leaning or forwardly inclined. The front projection **52** also has a base **72** that is wider (in a longitudinal or fore-aft direction of the blade **24**) than its tip **74**, when viewed from the side as in FIGS. **5-8**. The front projection **52** therefore converges towards its tip **74** (i.e. it is converging) and may also be said to be tapered, from its base **72** towards its tip **74**. The width of the front projection **52**, in a direction transverse to the fore-aft direction (or into the page in FIGS. **5-8**), may be substantially constant ($\pm 2\%$ of width) along its length from the base **72** to the tip **74**.

(46) Referring still to FIG. **5**, when the blade is to be inserted into the holder **26**, the tip **74** of the front projection **52** is first aligned with an outer opening **82** of the front recess **42** defined in the blade holder **26**, with the rear portion of the blade **24** and especially the rear projection **54** spaced apart from the holder **26**. The blade **24** may therefore be positioned, for example, at an angle relative to a substantially horizontally positioned blade holder **26**, as shown in FIG. **5**, so as to permit a smooth insertion of the front projection **52** of the blade **24** into the front recess **42** of the holder **26**.

(47) In the depicted embodiment, the front recess **42** opens into an internal cavity **84** defined within the front pedestal **30** of the blade holder **26**. As such, as the front projection **52** is inserted into the front recess **42**, the front projection **52** may slide (or otherwise engage) within the front recess **42** and the tip **74** of the front projection **52** may at least partially protrude into the internal cavity **84** within the front pedestal **30** (see FIGS. **7-8**, for example).

(48) As the front projection **52** of the blade **24** is being inserted into the front recess **42** of the holder **26**, via a sliding mating engagement, the blade **24** may rotate such that the blade **24** is in a partially-inserted position relative to the holder **26** as shown in FIGS. **6** and **7**. During this insertion of the front projection **52** into the front recess **42**, the blade **24** may also be slightly translated axially (in an forward direction). However, the relative rotational movement of the blade **24** relative to the holder **26** may be greater than the relative axial movement of the blade **24** relative to the holder **26**, as the blade **24** goes from its fully disengaged position to its fully engaged position (FIG. **8**).

(49) The front recess **42** of the blade holder **26** is sized so as to snugly receive or mate with the wider base **72** of the front projection **52** when the front projection **52** is fully inserted into the front recess **42** (FIG. **8**). The base **72** of the projection **52** may thus matingly engage with the convex surface **42FC** of the front wall portion **42F** of the recess **42** (described above). Such snuggle engagement may be a slide fit, for example. However, because of the tapered shape of the front projection **52**, as the front projection **52** is being slid into the front recess **42** (FIGS. **6-7**) a gap **78** is defined between a rearward facing surface of the front projection **52** and a forward facing wall, corresponding to the straight wall segment **42RS** described above with respect to FIG. **4**, of the front recess **42**. As shown in FIGS. **6** and **7**, this gap **78** will close as the front projection **52** is inserted further into the front recess **42**, until it is fully closed—i.e. the forward facing wall of the front recess **42** and the rearward facing surface, which may include both the straight wall segment **42FS** and the convex surface **42FC** described above, of the front projection **52** may be fully abutted against each other as shown in FIG. **8**. However, while this gap **78** remains as shown in FIGS. **6** and **7**, rotation of the blade **24** relative to the blade holder **24** is possible. A play between the front projection **52** and the front recess **42** when the front projection **52** is not fully engaged in the recess **42** may allow for such rotational degree of freedom.

(50) Accordingly, the converging tapered shape of the front projection **52** of the blade **24** allows for a rotational and translational movement of the blade **24** relative to the blade holder **26**, which

permits the blade **24** to be more easily inserted into position within the blade holder **26**. This would not be possible, or would at least be impeded, if the front projection **52** had a constant (i.e. non-tapered) thickness in the longitudinal direction and was received into a correspondingly shaped closed tunnel.

(51) The resulting fully-mated position of the front projection **52** and the front recess **42**, as shown in FIG. **8**, results in a mating connection between the blade **24** and the blade holder **26** that is more stable and secured.

(52) Referring to FIG. **9**, a damping feature of the blade holder **26** is shown at **90**. The damping feature **90** defines an interface with a portion of the top edge **50** of the blade **24** when the blade **24** is engaged in the groove **40** of the blade holder **26**. The damping feature **90** may damp vibrations or impact energy between the blade **24** and the blade holder **26**. The damping feature **90** may have energy absorption properties. The damping feature **90** may deform when compressed, as the blade **24** is inserted in the holder **26**. Manufacturing tolerances may cause small gaps or play between the blade **24** and the holder **26** and as such, the damping feature **90** may allow a better mating engagement between the blade **24** and the holder **26** at an interface thereof. As shown, the damping feature **90** extends in the groove **40**. The damping feature **90** may include a strip of material softer than the material of the holder **26**. For example, the strip may be made of a thin sheet of polyvinyl chloride (PVC) which may, due to its small thickness (e.g., between 0.1 mm and 0.5 mm) be easily deformable upon compression between the blade **24** and the holder **26**. The strip may be adhered to the holder **26** by an adhesive. The damping feature **90** could also form part of the holder **26**, such as by co-molding, for example. In the embodiment shown, the damping feature **90** is located underneath the rear pedestal **32**, within the groove **40**. The damping feature **90** extends rearwardly from the recess **44** engageable by the projection **54**. between a rear end of the holder **26** and the recess **44**. Even though the damping feature **90** may have some advantages, it may be optional in some embodiments.

(53) The above description is meant to be exemplary only, and one skilled in the art will recognize that changes may be made to the embodiments described without departing from the scope of the invention disclosed. For instance, the mechanism need not be located on the rear pedestal and may alternatively be located on the front pedestal. Still other modifications which fall within the scope of the present invention will be apparent to those skilled in the art, in light of a review of this disclosure, and such modifications are intended to fall within the appended claims.

Claims

1. A skate comprising: a boot; a blade assembly including: a blade holder attached beneath the boot, the blade holder having a bottom surface defining a groove and recesses extending upwardly from the groove, the blade holder having a socket defining a socket opening located in a lateral side of the blade holder; a blade removably mounted to the blade holder, the blade including a body defining an ice-engaging edge and a top edge opposite the ice-engaging edge, projections extending from the top edge and away from the ice-engaging edge, wherein one of the projections has a curved surface having a convex curvature, the curved surface defining a curved cam surface, a slot extending inwardly into said one of the projections from the curved cam surface; a locking pin displaceable relative the blade holder along a longitudinal axis between a blade locking position in which a tip of the locking pin is in engagement with the blade and a blade releasing position in which the tip of the locking pin is disengaged from the blade, the tip of the locking pin having a locking pin cam surface configured to slide along the curved cam surface of the blade; a pin actuator received within the socket of the blade holder, the pin actuator engageable by a user for translating the pin actuator along the longitudinal axis, the pin actuator engaged with the locking pin such that translation of the pin actuator induces translation of the locking pin along the longitudinal axis from the blade locking position to the blade releasing position; and a biasing

element mounted to the blade holder to react against the pin actuator and biasing the locking pin in the blade locking position.

2. The skate of claim 1, wherein the blade is moveable with respect to the blade holder between an engagement position in which the top edge is received in the groove and a disengagement position in which the blade is disengaged from the recesses and the groove.

3. The skate of claim 2, further comprising a damping feature defining an interface with a portion of the top edge of the blade when the blade is engaged with the blade holder, the damping feature located in the groove.

4. The skate of claim 1, wherein the curved cam surface of said one of the projections of the blade is rearwardly facing, and wherein a tip-engaging wall surface at least partially defines the slot merges with the curved cam surface at a turning point, the locking pin in engagement with the tip-engaging wall surface of the slot in the blade locking position and disengaged from the tip-engaging wall surface in the blade releasing position.

5. The skate of claim 4, wherein the slot has an asymmetrical shape, the tip-engaging wall surface of the slot including a top edge that extends substantially linearly into said one of the projections from the curved cam surface, a bottom edge of the slot facing and spaced apart from the top edge, the bottom edge being curved.

6. The skate of claim 5, wherein the top edge of the slot intersects with the curved cam surface at a point located between an apex of said one of the projections and the top edge of the body of the blade, an upper portion of the curved cam surface extending between the slot and the apex, and wherein an angle is defined between top edge of the slot and the upper portion of the curved cam surface, the angle being an acute angle.

7. The skate claim 4, wherein the tip of the locking pin has a top edge extending on an opposite side of the locking pin cam surface, at least part of the top edge contacting the tip-engaging wall surface of the projection in the blade locking position.

8. The skate of claim 1, wherein the tip of the locking pin has an apex and the locking pin cam surface extending from the apex, the locking pin cam surface being curved.

9. The skate of claim 1, wherein the tip of the locking pin has an asymmetric shape relative to a horizontal plane containing the longitudinal axis of the locking pin.

10. The skate of claim 1, further comprising a bellows extending between the pin actuator and an oppositely facing surface of the blade holder, the bellows surrounding peripherally the biasing element.

11. The skate of claim 1, wherein the pin actuator has an annular shape to receive the locking pin therein, the pin actuator having a forward-facing surface angled relative to the longitudinal axis, and a seating surface facing opposite to the forward-facing surface, the seating surface engaging the biasing element.

12. The skate of claim 1, wherein the pin actuator is fully recessed within the socket.

13. The skate of claim 1, wherein the pin actuator and the biasing element are fully recessed in the socket.

14. The skate of claim 1, wherein the blade holder has a front pedestal defining an internal cavity and a rear pedestal, a respective one of the recesses opening into the internal cavity.

15. The skate of claim 1, wherein the projections include a front projection and a rear projection, the front projection insertable into a respective one of the recesses defined in the front pedestal, the front projection being forwardly angled and having a tapered shape that converges from a base of the front projection to a tip of the front projection.

16. The skate of claim 1, wherein the projections include a front projection and a rear projection, the rear projection includes an apex and the curved cam surface extending from the apex, the curved cam surface of the rear projection slidably engaging a locking pin cam surface of the locking pin as the locking pin displaces between the blade locking position and the blade releasing position.

17. A replaceable blade for a skate having a locking pin adapted to removably engage the replaceable blade to a blade holder of the skate, the replaceable blade comprising: a body defining an ice-engaging edge, a top edge opposite the ice-engaging edge, a first projection and a second projection each extending upwardly from the body, the first and second projections configured for being received within a respective recess defined by the blade holder of the skate; wherein the second projection defines a rearwardly facing edge that forms a curved surface having a convex curvature, the curved surface defining a curved cam surface along which a tip of the locking pin is adapted to slide, and a slot that extends inwardly into the second projection from the curved cam surface, the slot adapted to receive the tip of the locking pin therein.

18. The replaceable blade of claim 17, wherein the first projection is a front projection, the front projection being forwardly angled and having a tapered shape that converges from a base of the front projection to a tip of the front projection.

19. The replaceable blade of claim 18, wherein the front projection has a length defined from the base to the tip of the front projection, the front projection having a height defined as a distance between the top edge of the body immediately adjacent the base of the front projection and a tangent line at the tip of the front projection generally parallel to the top edge of the body, and wherein the length is greater than the height.

20. The replaceable blade of claim 17, wherein an upper section of the replaceable blade is adapted to be received within a groove of a blade holder of the skate, the upper section extending between a fore end to an aft end of the replaceable blade, the upper section having a thickness $T1$ measurable from the top edge to a boundary line that is offset with and generally parallel to the top edge, wherein the first projection has a height $H1$, the height $H1$ being at least two times the thickness $T1$ of the upper section.

21. The replaceable blade of claim 17, wherein slot in the second projection has an asymmetrical shape, the slot being defined at least in part by a top edge that extends substantially linearly into the second projection from the curved cam surface and a bottom edge facing and spaced apart from the top edge, the bottom edge being curved.

22. The replaceable blade of claim 21, wherein the top edge of the slot intersects with the curved cam surface at a point located between an apex of the second projection and the top edge of the body of the replaceable blade, an upper portion of the curved cam surface extending between the slot and the apex, and wherein an angle is defined between top edge of the slot and the upper portion of the curved cam surface, the angle being an acute angle.
