

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403405
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Dan; Ten-Long et al.

Game packet delivery method and game packet delivery system

Abstract

A game packet delivery method and a game packet delivery system are provided. The method includes executing a game program by a user device; and transmitting at least one game packet related to the game program between the user device and a game server via a telecom server and a shared router in response to the execution of the game program. The shared router belongs to a decentralized network node, and the transmission of at least one game packet does not involve any server provided by cloud service providers. Therefore, the efficiency of transferring game packets between the user device and the game server can be improved, thereby improving the game experience of the end user. Besides, because the transmission of game packets does not go through the backbone network of the cloud service providers, it can also ensure the privacy of online games for users.

Inventors: Dan; Ten-Long (Taipei, TW), Teng; Wei-Sheng (Taipei, TW), Chiu; Ching-Chuan (Taipei, TW)

Applicant: ASUSTeK COMPUTER INC. (Taipei, TW)

Family ID: 89577612

Assignee: ASUSTeK COMPUTER INC. (Taipei, TW)

Appl. No.: 17/979732

Filed: November 02, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240024785 A1	Jan. 25, 2024

Foreign Application Priority Data

CN	202210870558.X	Jul. 22, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: A63F13/352 (20140101); A63F13/77 (20140101)

U.S. Cl.:

CPC A63F13/77 (20140902); A63F13/352 (20140902); A63F2300/513 (20130101); A63F2300/552 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8681656	12/2013	Sulc	370/254	H04W 40/38
2013/0184073	12/2012	Uchiyama	463/29	A63F 13/49
2018/0309664	12/2017	Balasubramanian	N/A	H04L 47/6255
2023/0042916	12/2022	Sole	N/A	G06Q 20/123
2023/0140933	12/2022	Gittleson	705/65	A63F 13/73
2024/0050861	12/2023	Choi	N/A	A63F 13/795

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112153155	12/2019	CN	N/A
112583712	12/2020	CN	N/A

Primary Examiner: Liddle; Jay Trent

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the priority benefit of China application serial no. 202210870558.X, filed on Jul. 22, 2022. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

(2) The disclosure relates to a game packet delivery method and a game packet delivery system.
Description of Related Art

(3) The world's largest cloud service providers include Amazon Web Services (AWS), Microsoft Azure and Google Cloud Platform. The large backbone networks set up by these cloud service providers can provide a variety of modular cloud services, including cloud computing, data storage, and online transactions. By charging users, most web application services can be completed through the cloud platforms provided by these cloud service providers. However, for some types of

applications (such as online games) that need to transmit information quickly, such a large backbone network will inevitably cause delays in information transmission, which affects the operation experience of end users.

SUMMARY

(4) According to the first aspect of this disclosure, a game packet delivery method is provided. The method includes executing a game program by a user device; and transmitting at least one game packet related to the game program between the user device and a game server via a telecom server and a shared router in response to the execution of the game program. Wherein the shared router belongs to a decentralized network node, and the transmission of at least one game packet does not involve any server provided by cloud service providers.

(5) According to the second aspect of this disclosure, a game packet delivery system is provided. The system includes a user device and a shared router. The user device is configured to execute a game program. The shared router is connected to the user device. The shared router is configured to cooperate with a telecom server to transmit at least one game packet related to the game program between the user device and a game server in response to the execution of the game program. The shared router belongs to a decentralized network node. The transmission of at least one game packet does not involve any server provided by cloud service providers.

(6) Based on the above, when the user device executes the game program, at least one game packet related to the game program can be transmitted between the user device and the game server via the telecom server and the shared router. In particular, the shared routers belong to decentralized network nodes, and the transmission of the game packets does not involve any servers provided by cloud service providers. Therefore, by avoiding the backbone network prone to packet transmission delay, the efficiency of transmitting game packets between the user device and the game server can be improved, thereby improving the game experience of the end user. Besides, because the transmission of game packets does not go through the backbone network of the cloud service providers, it can also ensure the privacy of online games for users.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic diagram of a game packet delivery system according to an embodiment of the application.

(2) FIG. 2 is a schematic diagram of a shared router according to an embodiment of the application.

(3) FIG. 3 is a schematic diagram of transmitting game packets according to an embodiment of the application.

(4) FIG. 4 is a flowchart of a game packet delivery method according to an embodiment of the application.

DESCRIPTION OF THE EMBODIMENTS

(5) Reference will now be made in detail to the exemplary embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numerals are used in the drawings and description to refer to the same or like parts.

(6) Referring to FIG. 1, the game packet delivery system **10** includes a user device **11**, a router group **12**, a telecom server **13**, a router group **14**, and a game server **15**.

(7) The user device **11** may include a smart phone, a tablet computer, a notebook computer, a desktop computer, an industrial computer or a game console (set) and other electronic devices with functions of information display, information processing and information transmission, and the type of the user device **11** is not limited thereto. In particular, the user device **11** may have a networking function. For example, the user device **11** may be connected to the Internet via a wired and/or wireless network interface card.

(8) The router group **12** may include routers **12(0)~12(A)**. The routers **12(0)~12(A)** can be used to transmit network packets between user device **11** and telecom server **13**. The total number of the routers **12(0)~12(A)** can be one or more, which is not limited in this case.

(9) The telecom server **13** may include servers provided by telecom operators around the world. The telecom server **13** can be used to provide local network basic services. For example, well-known telecom operators in China include China Mobile, China Telecom and China Unicom, etc. For another example, well-known telecom providers in the United States include AT&T and Verizon, etc. The total number of telecom servers **13** can be one or more, which is not limited in this case.

(10) The router group **14** may include routers **14(0)~14(B)**. The routers **14(0)~14(B)** can be used to transmit network packets between the telecom server **13** and the game server **15**. The total number of the routers **14(0)~14(B)** can be one or more, which is not limited in this case. In an embodiment, the router group **12** and the router group **14** can also be combined into the same router group.

(11) The game server **15** may include a server provided by a game operator. The game server **15** can be used to store game data associated with one or more game programs. In addition, game server **15** may provide a game access interface. Multiple players (or multiple user devices **11**) can perform online game interaction through the game access interface provided by the game server **15**.

(12) The user device **11** may execute the game program. The game package program includes the game program of online game (also known as network game). In response to the execution of the game program, the user device **11** may generate at least one game packet related to the game program. For example, in the process of executing the game program on the user device **11**, the generated game packet can continuously reflect the execution status of the game program.

 custom character user device **11**. For example, the game package may contain game data related to the game program executed by the user device **11**. The user device **11** can communicate with the game server **15** (and other players) via the game packets (or game data). In addition, the game server **15** can also transmit game packets related to the game program to the user device **11**.

(13) On the other hand, in response to the execution of the game program, at least one router in the router group **12** and/or **14** may cooperate with the telecom server **13** to transmit the game packets between the user device **11** and the game server **15**. For example, when the user device **11** executes the game program, the user device **11** can connect to the router **12(i)** via the wireless local area network (e.g. Wifi) provided by the router **12(i)**. Next, the game packet generated by the user device **11** executing the game program can be transmitted to the telecom server **13** via the router **12(i)**, and then transmitted to the game server **15** via the router **14(j)**.

(14) In an embodiment, the router **14(j)** can also replace the router **12(i)** and is responsible for transmitting game packets between the user device **11** and the telecom server **13** and between the telecom server **13** and the game server **15**. The router **12(i)** may include any one of routers **12(0)~12(A)**. The router **14(j)** may include any one of routers **14(0)~14(B)**. In addition, the total number of routers **12(i)** and **14(j)** may be one or more respectively, which is not limited in this case.

(15) It should be noted that, each router in the router groups **12** and **14** is a decentralized network node. Compared with centralized network nodes (that is, the routing rules of routers for network packets are uniformly determined by the control host or control node), each router in router groups **12** and **14** can determine the routing rules for network packets by itself. Therefore, there is no need to be under the control of a control host or a control node. In an embodiment, each router in the router groups **12** and **14** is also called a shared router or a shared server.

(16) In an embodiment, in the process of passing (e.g., routing) game packets from user device **11** to game server **15** and/or from game server **15** (e.g., routing) to user device **11**, the transmission of the game packets does not involve any servers provided by cloud service providers such as Amazon Web Services (AWS), Microsoft Azure and Google Cloud Platform. That is, in the process of delivering (e.g. routing) game packets, the game packets do not pass through the servers provided by the above or similar cloud service providers.

(17) From another point of view, in an embodiment, one or more servers provided by the above or similar cloud service providers may be ignored (e.g. bypassed) in the process of transmitting (e.g. routing) game packets. By ignoring (e.g. bypassing) one or more servers provided by the above or similar cloud service providers, the efficiency of transferring game packets between the user device and the game server can be improved, thereby improving the end user's gaming experience. Besides, because the transmission of game packets does not go through the backbone network of the cloud service providers (i.e., the server provided by the cloud service provider), it can also ensure the privacy of online games for users.

(18) In an embodiment, both the routers **12(i)** and **14(j)** include a blockchain router. That is, the routers **12(i)** and **14(j)** themselves can perform blockchain operations. For example, the routers **12(i)** and **14(j)** can execute programs such as calculation (i.e., mining) of virtual currency or cryptocurrency such as Bitcoin. In an embodiment, the routers **12(i)** and **14(j)** may belong to the same blockchain network.

(19) Referring to FIG. 1 and FIG. 2, the router **21** may be used to represent routers **12(i)** and/or **14(j)**.

(20) The router **21** includes a processor **211**, a memory circuit **212**, and a input and output (I/O) interface **213**. The processor **211** is responsible for the whole or part of the operation of the router **21**. For example, the processor **211** may include a central processing unit (CPU), a graphics processing unit (GPU), or other programmable general-purpose or special-purpose microprocessors, a digital signal processors (DSP), a programmable controller, Application Specific Integrated Circuit (ASIC), Programmable Logic Device (PLD), or other similar devices or combinations of these devices.

(21) The memory circuit **212** is used for storing data. For example, the memory circuit **212** may include a volatile memory circuit and a non-volatile memory circuit. The volatile memory circuit is used to store data volatily. For example, the volatile storage circuit may include random access memory (RAM) or similar volatile storage media. The non-volatile memory circuit is used to store data non-volatily. For example, the non-volatile storage circuit may include Read Only Memory (ROM), Solid State Disk (SSD), Hard Disk Drive (HDD), or similar non-volatile storage media.

(22) The I/O interface **213** may include various signal output/output devices, such as a communication circuit (for example, a network interface card), a mouse, a keyboard, a screen, a touch screen, a speaker and/or a microphone. The device type of I/O interface **213** is not limited in this case.

(23) In an embodiment, under the decentralized architecture, the processor **211** can calculate routing information according to a header information of the received game packets. For example, the routing information can reflect the shortest, fastest and/or best packet delivery path between the router **21** and the game server **15**. The processor **211** can transmit the game packets according to the routing information.

(24) In an embodiment, the header information of the game packets may contain the Internet's source Internet Protocol address, target IP address, source communication port and target communication port. The processor **211** can query a topology information according to the header information of the game packet and decide which router to transmit the game packet to according to the query result, or directly transmit the game packet to the user device **11** or the game server **15**. The topology information can be stored in the memory circuit **212**.

(25) In an embodiment, under the decentralized architecture, the processor **211** may update the topology information according to the topology changes of the decentralized network where the router **21** is located. For example, in response to a new node (i.e. router) being added to the decentralized network where router **21** is located or an old node (i.e. router) being removed from the decentralized network where router **21** is located, the processor **211** may update the topology information. The updated topology information may reflect the latest topology of the decentralized network where router **21** is located.

(26) In an embodiment, the processor **211** may share the updated information of the topology information to other nodes (i.e. routers) in the same decentralized network, so that the other nodes (i.e., routers) in the same decentralized network may synchronously update the topology information maintained by themselves. Besides, in an embodiment, the processor **211** may receive updated information of the topology information from other nodes (i.e., routers) in the same decentralized network. Then, the processor **211** may update the topology information according to the update information.

(27) In an embodiment, the processor **211** may calculate the routing information through a deep learning model or an artificial intelligence model. For example, the deep learning model or the artificial intelligence model can use various prediction models or algorithms such as convolutional neural networks (CNN), which are not limited in this case. The deep learning model or the artificial intelligence model can be trained to predict the shortest, fastest and/or best packet delivery paths for transmitting the game packets.

(28) In an embodiment, in response to the router **21** assisting in transmitting the game packets, the processor **211** may provide rewards to the online account associated with the router **21** via a reward program. For example, according to the system resources (such as time, network bandwidth and/or power consumption) used by the router **21** to assist in transmitting the game packets, the reward program may execute a reward redemption mechanism to provide rewards to an online account associated with the router **21**. For example, the rewards may include a specified amount of virtual currency (or cryptocurrency), free Wi-Fi connection time that can be used in certain connection environments, free Wi-Fi connection bandwidth or free virtual private network (VPN) can be used in specific connection environments, etc., as a feedback for the router **21** to assist in transmitting the game packets. For example, the reward program may be stored in memory circuit **212**.

(29) In an embodiment, the reward program may record information that the router **21** assists in transmitting the game packets and report the information to a remote server (also known as a reward server). The remote server (also known as a reward server) may provide corresponding rewards to the online account associated with the router **21** according to the information reported by the reward program.

(30) Referring to FIG. 3, it is assumed that a user device **31** includes the user device **11** of FIG. 1, and a game server **32** includes the game server **15** of FIG. 1.

(31) In the process of transmitting the game packet, the user device **31** may ignore (e.g. bypass) the servers **33(0)~33(C)** provided by the cloud service provider (or cloud service platform) **33**, and transmit the game packet to the game server **32** through the routers **34(0)~34(D)** belonging to the decentralized network node **34**. Similarly, the game server **32** may also ignore (e.g. bypass) the servers **33(0)~33(C)** provided by the cloud service provider (or cloud service platform) **33**, and transmit the game packet to the user device **31** through the routers **34(0)~34(D)** belonging to the decentralized network node **34**. In addition, the router **34(0)~34(D)** may belong to the same blockchain network.

(32) Referring to FIG. 4, in step **S401**, the game program is executed by the user device. In step **S402**, in response to the execution of the game program, at least one game packet related to the game program is transmitted between the user device and the game server via the telecom server and the shared router. In particular, the shared routers belong to decentralized network nodes, and the transmission of the game packets does not involve any routers provided by cloud service providers.

(33) However, each step in FIG. 4 has been described in detail above, and will not be repeated here. It is worth noting that each step in FIG. 4 can be implemented as multiple codes or circuits, which is not limited in this case. The method can be used in conjunction with the above exemplary embodiments, or can be used alone, and is not limited in this case.

(34) In summary, the embodiment can ignore (e.g. bypass) the servers provided by the cloud service provider and use the shared router that is a decentralized network node to transmit game

packets between the user device and the game server. Therefore, the transmission efficiency of game packets can be effectively improved. Besides, because the transmission of game packets does not go through the backbone network of the cloud service providers (i.e., the server provided by the cloud service provider), it can also ensure the privacy of online games for users.

(35) It should be noted that at last: above each embodiment is only in order to illustrate technical scheme of the invention, rather than its limitation. Although the invention has been described in detail with reference to the foregoing embodiments, those of ordinary skill in the art should understand that the technical solutions described in the foregoing embodiments can still be modified, or some or all of the technical features thereof can be equivalently replaced. And these modifications or replacements do not make the essence of the corresponding technical solutions depart from the scope of the technical solutions of the embodiments of the invention.

Claims

1. A game packet delivery method comprising: executing a game program by a user device; and transmitting at least one game packet related to the game program between the user device and a game server via a telecom server and a shared router in response to the execution of the game program, wherein the shared router belongs to a decentralized network node, and the transmission of at least one game packet does not involve any server provided by cloud service providers, providing rewards to online accounts associated with the shared router in response to the shared router assisting in transmitting the at least one game packet.
2. The game packet delivery method according to claim 1, wherein the shared router comprises a blockchain router.
3. The game packet delivery method according to claim 2, wherein the blockchain router comprises a first blockchain router and a second blockchain router, and the first blockchain router and the second blockchain router belong to the same blockchain network.
4. The game packet delivery method according to claim 1, wherein the step of transmitting the at least one game packet related to the game program between the user device and the game server via the telecom server and the shared router comprises: ignoring the server provided by the cloud service providers in the process of transmitting the at least one game packet.
5. The game packet delivery method according to claim 1, wherein the step of transmitting the at least one game packet related to the game program between the user device and the game server via the telecom server and the shared router comprises: calculating a routing information by the shared router according to a header information of the at least one game packet under a decentralized architecture; and transmitting the at least one game packet by the shared router according to the routing information.
6. A game packet delivery system comprising: a user device, configured to execute a game program; and a shared router, connected to the user device, wherein the shared router is configured to cooperate with a telecom server to transmit at least one game packet related to the game program between the user device and a game server in response to the execution of the game program, wherein the operation of transmitting the at least one game packet related to the game program between the user device and the game server by the shared router in conjunction with the telecom server comprises: the server provided by the cloud service providers are ignored in the process of transmitting the at least one game packet, the shared router belongs to a decentralized network node, and the transmission of at least one game packet does not involve any server provided by cloud service providers.
7. The game packet delivery system according to claim 6, wherein the shared router comprises a blockchain router.
8. The game packet delivery system according to claim 7, wherein the blockchain router comprises a first blockchain router and a second blockchain router, and the first blockchain router and the

second blockchain router belong to the same blockchain network.

9. The game packet delivery system according to claim 6, wherein the shared router is further configured to provide rewards to online accounts associated with the shared router in response to the shared router assisting in transmitting the at least one game packet.

10. The game packet delivery system according to claim 6, wherein the operation of transmitting the at least one game packet related to the game program between the user device and the game server by the shared router in conjunction with the telecom server comprises: a routing information is calculated by the shared router according to a header information of the at least one game packet under a decentralized architecture; and the at least one game packet is transmitted by the shared router according to the routing information.

11. A game packet delivery method comprising: executing a game program by a user device; and transmitting at least one game packet related to the game program between the user device and a game server via a telecom server and a shared router in response to the execution of the game program, wherein the step of transmitting the at least one game packet related to the game program between the user device and the game server via the telecom server and the shared router comprises: calculating a routing information by the shared router according to a header information of the at least one game packet under a decentralized architecture; and transmitting the at least one game packet by the shared router according to the routing information, wherein the shared router belongs to a decentralized network node, and the transmission of at least one game packet does not involve any server provided by cloud service providers.
