

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404162
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Martin; Joseph Daniel et al.

Hand-held beverage dispenser

Abstract

A hand-held beverage dispenser includes a handle body, within which multiple valve units are contained. Two sets of fluid flow paths are provided into the handle body. The sets of fluid flow paths are mutually exclusive one to the other. Each flow path of the first set is in fluid communication with each valve unit, whereas only a predetermined one of the second set of fluid flow paths is in fluid communication with each valve unit. Each valve unit includes a flow control valve and a selector valve. The selector valve determines on an ad hoc basis which of the first set of flow paths will be utilized at any given time, while the flow control valve provides single action simultaneous ON-OFF control of fluid flows through both the selected flow path and the predetermined flow path. A failsafe ensures correct operation of the selector valve of each valve unit.

Inventors: Martin; Joseph Daniel (Kaiserslautern, DE), Behe, Jr.; Anthony Joseph (Converse, TX), Rodriguez; Ricardo Abugarade (Schertz, TX), Dsouza; John (Live Oak, TX)

Applicant: LANCER CORPORATION (San Antonio, TX)

Family ID: 89078016

Assignee: Lancer Corporation (San Antonio, TX)

Appl. No.: 18/209686

Filed: June 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230399220 A1	Dec. 14, 2023

Related U.S. Application Data

continuation parent-doc US 17737469 20220505 US 11643318 20230509 child-doc US 18126410
continuation parent-doc US 17339917 20210604 US 11345584 20220531 child-doc US 17737469
continuation-in-part parent-doc US 18126410 20230325 US 12157659 child-doc US 18209686
us-provisional-application US 63353806 20220620
us-provisional-application US 63129380 20201222
us-provisional-application US 63034762 20200604

Publication Classification

Int. Cl.: B67D1/00 (20060101); B67D1/14 (20060101)

U.S. Cl.:

CPC B67D1/0084 (20130101); B67D1/1438 (20130101); B67D2001/0094 (20130101)

Field of Classification Search

CPC: B67D (1/0084); B67D (1/1438); B67D (2001/0094); B67D (1/0046)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3144967	12/1963	McClain	239/416.1	B67D 1/0084
3863810	12/1974	Hanson	D7/398	B67D 1/0084
4076148	12/1977	Carse	222/144.5	B67D 1/1416
4619378	12/1985	de Man	137/884	B67D 1/0084
4673108	12/1986	de Man	439/43	B67D 1/0084
4921140	12/1989	Belcham	200/332.2	B67D 1/0084
4986449	12/1990	Valiyee	222/144.5	B67D 1/0084
5056686	12/1990	Jarrett	222/144.5	B67D 1/0084
5152429	12/1991	Billings	222/144.5	B67D 1/10

Primary Examiner: Long; Donnell A

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to post-mix drink dispensing, and, more particularly, but not by way of limitation, to hand-held beverage dispensers for delivering post-mix beverages.

2. Description of the Related Art

(2) Post-mix type hand-held beverage dispensers, such as are often referred to as bar guns or soda guns are well-known conveniences in the food and bar service industries, enabling beverages to be prepared as they are dispensed by mixing together a beverage product, such as, for example, a syrup or like concentrate, and a diluent, such as, for example, carbonated water or plain water.

Although each of the variously utilized diluents is typically appropriate for use with a great variety of beverage products, any one beverage product will generally only be compatible with a particular diluent. Unfortunately, this presents a problem for currently available hand-held beverage dispensers implemented according to the current state of the art. In particular, the currently available hand-held beverage dispensers are simply not capable of readily changing the diluent to be utilized with respect to any particular fluid flow path through the dispenser.

(3) Accordingly, a hand-held post-mix type drink dispenser readily configurable to dispense any available diluent in connection with any beverage product flow path will create, and meet, new demand in the drink dispensing industry.

SUMMARY OF THE INVENTION

(4) A valve arrangement for selectively establishing beverage fluid flow paths through a hand-held beverage dispenser, for selectively dispensing a demanded one of a plurality of post-mix beverages, generally comprises a selector valve and a flow control valve, each of which is substantially contained within a hand-held beverage dispenser; and a plurality of flow paths from without the hand-held beverage dispenser to the selector valve. The selector valve is adapted to establish passage therethrough of a user selectable one of the plurality of flow paths, while blocking passage therethrough of each of the plurality of flow paths other than the user selected flow path. The flow control valve, which is functionally independent of the selector valve, is adapted, upon actuation, to enable fluid discharge from the selected one flow path to without the hand-held beverage dispenser. The flow control valve and the said selector valve are preferably formed about a single valve body, and most preferably the flow control valve is integrally formed with said selector valve within the single valve body.

(5) The valve arrangement for selectively establishing beverage fluid flow paths through a hand-held beverage dispenser preferably includes a plurality of selector valves substantially contained within the hand-held beverage dispenser. In this case, each flow path of the plurality of flow paths from without the hand-held beverage dispenser runs to each selector valve of the plurality of selector valves. Likewise, the valve arrangement comprises a corresponding flow control valve substantially contained within said hand-held beverage dispenser for each selector valve, each selector valve being functionally independent of the corresponding flow control valve. Actuation of a flow control valve thus enables fluid discharge from the corresponding one of the plurality of flow paths to without the hand-held beverage dispenser.

(6) The valve arrangement for selectively establishing beverage fluid flow paths through a hand-held beverage dispenser most preferably comprises an additional plurality of flow paths, which are mutually exclusive of the first plurality of flow paths. A predetermined corresponding one of the additional plurality of flow paths is provided from without the hand-held beverage dispenser to each of the plurality of flow control valves. Each flow control valve is thus further adapted, upon actuation, to enable fluid discharge from the corresponding one of the additional plurality of flow paths to without the hand-held beverage dispenser.

(7) In use of the most preferred embodiment of the valve arrangement for selectively establishing beverage fluid flow paths through a hand-held beverage dispenser, for selectively dispensing a demanded one of a plurality of post-mix beverages, each selection valve determines, on an ad hoc basis, which of the first plurality of flow paths will be utilized at any given time, while the flow control valve provides single action simultaneous ON-OFF control of fluid flows through both the selected flow path from the selector valve and the predetermined flow path to the flow control valve.

(8) In at least some implementations of the valve arrangement for selectively establishing beverage fluid flow paths through a hand-held beverage dispenser, the selector valve is rotationally operated. In at least this case, the valve arrangement preferably further comprises a configuration lock adapted to maintain each selector valve in a respective operable state, as opposed to being inadvertently left in a transitional state between operable states. In the preferred implementation of

the present invention, the configuration lock not only prevents inadvertent transition out of an operable state, but also precludes final assembly for use if any one of the selector valves is not in an operable state.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIGS. **1-3** illustrate a hand-held beverage dispenser according to a preferred embodiment, where:
- (2) FIG. **1** is a top rear end isometric view;
- (3) FIG. **2** is a right side elevational view; and
- (4) FIG. **3** is a bottom rear end isometric view.
- (5) FIGS. **4-5** illustrate the provision and selective removability of a nozzle housing of the hand-held beverage dispenser, where:
- (6) FIG. **4** is a partially exploded bottom front end isometric view; and
- (7) FIG. **5** is a partially exploded top front end isometric view.
- (8) FIG. **6** is a partially exploded top rear end isometric view illustrating the provision and selective removability of an aesthetic cover of the hand-held beverage dispenser.
- (9) FIGS. **7-8** illustrate various aspects of the constituent components of the hand-held beverage dispenser, where:
- (10) FIG. **7** is an exploded top rear end isometric view; and
- (11) FIG. **8** is an exploded bottom front end isometric view.
- (12) FIGS. **9-12** illustrate various aspects of a handle body of the hand-held beverage dispenser, where:
- (13) FIG. **9** is a top rear end isometric view;
- (14) FIG. **10** is a bottom front end isometric view;
- (15) FIG. **11** is a rear end elevational view; and
- (16) FIG. **12** is a bottom plan view.
- (17) FIGS. **13-16** illustrate various aspects of a piping system of the hand-held beverage dispenser, about which the handle body is formed, where:
- (18) FIG. **13** is a top front end isometric view;
- (19) FIG. **14** is a bottom rear end isometric view;
- (20) FIG. **15** is a top plan view; and
- (21) FIG. **16** is a cross-sectional elevational view taken along lines **16-16** of FIG. **15**.
- (22) FIG. **17** is a cross-sectional elevational view taken along lines **17-17** of FIG. **9** illustrating various aspects of the formation of the handle body.
- (23) FIGS. **18-19** illustrate various aspects of a representative one valve unit of the piping system of the hand-held beverage dispenser, where:
- (24) FIG. **18** is a top rear end isometric view; and
- (25) FIG. **19** is a cross-sectional elevational view taken along lines **19-19** of FIG. **18**.
- (26) FIGS. **20-28** are partially cut away views illustrating various aspects of a representative one valve body, corresponding to the representative one valve unit, of the piping system of the hand-held beverage dispenser, where:
- (27) FIG. **20** is a top rear end isometric view;
- (28) FIG. **21** is a bottom front end isometric view;
- (29) FIG. **22** is a right side elevational view;
- (30) FIG. **23** is a top plan view;
- (31) FIG. **24** is a rear end elevational view;
- (32) FIG. **25** is a front end elevational view;

(33) FIG. 26 is a cross-sectional elevational view taken along lines 26-26 of FIG. 23;

(34) FIG. 27 is a cross-sectional elevational view taken along lines 27-27 of FIG. 23; and

(35) FIG. 28 is a cross-sectional elevational view taken along lines 28-28 of FIG. 23.

(36) FIG. 29 is a schematic piping diagram illustrating the piping system of the hand-held beverage dispenser.

(37) FIGS. 30A-30D illustrate various aspects of the valve units of the piping system of the hand-held beverage dispenser, where:

(38) FIG. 30A is a first detail view taken from FIG. 29;

(39) FIG. 30B is a second detail view taken from FIG. 29;

(40) FIG. 30C is a third detail view taken from FIG. 29; and

(41) FIG. 30D is a fourth detail view taken from FIG. 29.

(42) FIGS. 31-36 illustrate various aspects of a structural body about which a selector valve trim assembly of the piping system of the hand-held beverage dispenser is integrally formed, where:

(43) FIG. 31 is a top isometric view;

(44) FIG. 32 is a bottom isometric view;

(45) FIG. 33 is a side elevational view;

(46) FIG. 34 is a top plan view;

(47) FIG. 35 is a cross-sectional elevational view taken along lines 35-35 of FIG. 34; and

(48) FIG. 36 is cross-sectional elevational view taken along lines 36-36 of FIG. 34.

(49) FIGS. 37-40 illustrate various aspects of the selector valve trim assembly, where:

(50) FIG. 37 is a top isometric view;

(51) FIG. 38 is a side elevational view;

(52) FIG. 39 is a top plan view; and

(53) FIG. 40 is a cross-sectional elevational view taken along lines 40-40 of FIG. 39.

(54) FIGS. 41-43 illustrate various aspects of an integral valve stem assembly of a flow control valve trim assembly of the piping system of the hand-held beverage dispenser, where:

(55) FIG. 41 is a top isometric view;

(56) FIG. 42 is a side elevational view; and

(57) FIG. 43 is a cross-sectional elevational view taken along lines 43-43 of FIG. 42.

(58) FIGS. 44-45 are exploded views illustrating various aspects of the arrangement of the flow control valve trim assembly with the selector valve trim assembly, where:

(59) FIG. 44 is a top isometric view; and

(60) FIG. 45 is a bottom isometric view.

(61) FIGS. 46A-46B illustrate various aspects of the cooperative adaptation of the flow control valve trim assembly and the selector valve trim assembly, in a first state of operation, where:

(62) FIG. 46A is a top isometric view; and

(63) FIG. 46B is a cross-sectional elevational view taken along lines 46B-46B of FIG. 46A.

(64) FIGS. 47A-47B illustrate various aspects of the cooperative adaptation of the flow control valve trim assembly and the selector valve trim assembly, in a second state of operation, where:

(65) FIG. 47A is a top isometric view; and

(66) FIG. 47B is a cross-sectional elevational view taken along lines 47B-47B of FIG. 47A.

(67) FIGS. 48-49 illustrate a selectively implementable preliminary stage of assembly of the preferred embodiment of the hand-held beverage dispenser, where:

(68) FIG. 48 is an exploded bottom front end isometric view of the handle body and a multiplicity of connector tubes and rods; and

(69) FIG. 49 is a bottom front end isometric view of the handle body and the multiplicity of connector tubes and rods.

(70) FIGS. 50-53 illustrate an upper seal of the valve unit of the hand-held beverage dispenser, where:

(71) FIG. 50 is a top isometric view;

(72) FIG. 51 is a bottom isometric view;

(73) FIG. 52 is a side elevational view;

(74) FIG. 53 is a cross-sectional elevational view taken along lines 53-53 of FIG. 52.

(75) FIGS. 54-57 illustrate the handle body and the upper seal of a valve unit in a first stage of assembly of the preferred embodiment of the hand-held beverage dispenser, where:

(76) FIG. 54 is a partially exploded top rear end isometric view;

(77) FIG. 55 is a top rear end isometric view;

(78) FIG. 56 is a cross-sectional elevational view taken along lines 56-56 of FIG. 55; and

(79) FIG. 57 is a top rear end isometric view, including the upper seal of each valve unit.

(80) FIGS. 58-60 illustrate population of an inverted handle body with the integral valve stem assembly of the flow control valve trim assembly, in a second stage of assembly of the preferred embodiment of the hand-held beverage dispenser, where:

(81) FIG. 58 is a partially exploded top rear end isometric view;

(82) FIG. 59 is a bottom front end isometric view; and

(83) FIG. 60 is a bottom front end isometric view, including the flow control valve trim assembly of each valve unit.

(84) FIGS. 61-63 illustrate population of the inverted handle body with a fully integral selector valve trim assembly and a poppet spring of the flow control valve trim assembly, in the second stage of assembly of the hand-held beverage dispenser, where:

(85) FIG. 61 is a partially exploded top rear end isometric view;

(86) FIG. 62 is a top rear end isometric view; and

(87) FIG. 63 is top plan view, including the selector valve trim assembly of each valve unit.

(88) FIGS. 64-65 illustrate various aspects of a valve trim retaining member of the preferred embodiment of the hand-held beverage dispenser, where:

(89) FIG. 64 is a top rear end isometric view; and

(90) FIG. 65 is a bottom plan view.

(91) FIGS. 66-67 illustrate the inverted handle body and the valve trim retaining member in a third stage of assembly of the preferred embodiment of the hand-held beverage dispenser, where:

(92) FIG. 66 is a partially exploded top rear end isometric view; and

(93) FIG. 67 is a top rear end isometric view.

(94) FIGS. 68A-68B are bottom plan views illustrating various aspects of the cooperative adaptation of the valve trim retaining member and a selector valve trim assembly in functional implementation of various aspects of the representative one valve unit, where:

(95) FIG. 68A depicts the selector valve trim assembly in a first operative state; and

(96) FIG. 68B depicts the selector valve trim assembly in a second operative state.

(97) FIGS. 69A-69E illustrate the valve trim retaining member and the selector valve trim assembly of the representative one valve unit, as configured in the first operative state illustrated in FIG. 68A but, for clarity, depicted in isolation, and where:

(98) FIG. 69A is a bottom plan view;

(99) FIG. 69B is a bottom rear end isometric view;

(100) FIG. 69C is a bottom front end isometric view;

(101) FIG. 69D is a right side elevational view; and

(102) FIG. 69E is a top plan view.

(103) FIGS. 70A-70E illustrate the valve trim retaining member and the selector valve trim assembly of the representative one valve unit, as configured in the second operative state illustrated in FIG. 68B but, for clarity, depicted in isolation, and where:

(104) FIG. 70A is a bottom plan view;

(105) FIG. 70B is a bottom rear end isometric view;

(106) FIG. 70C is a bottom front end isometric view;

(107) FIG. 70D is a right side elevational view; and

(108) FIG. 70E is a top plan view.

(109) FIGS. 71-76 illustrate various aspects of a bottom enclosure member of the preferred embodiment of the hand-held beverage dispenser, where:

(110) FIG. 71 is a top front end isometric view;

(111) FIG. 72 is a bottom rear end isometric view;

(112) FIG. 73 is a right side elevational view;

(113) FIG. 74 is a top plan view;

(114) FIG. 75 is a cross-sectional elevational view taken along lines 75-75 of FIG. 74; and

(115) FIG. 76 is a top rear end view.

(116) FIG. 77 is a partially exploded top rear end isometric view illustrating the inverted handle body and the bottom enclosure member, in a fourth stage of assembly of the preferred embodiment of the hand-held beverage dispenser.

(117) FIG. 78 is a bottom front end isometric view illustrating the handle body and the bottom enclosure member, on completion of the fourth stage of assembly of the preferred embodiment of the hand-held beverage dispenser

(118) FIGS. 79-81 illustrate the bottom enclosure member, the valve trim retaining member and the selector valve trim assembly of the representative one valve unit, as arranged in the fourth stage of assembly as illustrated in FIG. 78 but, for clarity, depicted in isolation, and where:

(119) FIG. 79 is a top rear end view;

(120) FIG. 80 is a rear end elevational view; and

(121) FIG. 81 is a cross-sectional bottom plan view taken along lines 81-81 of FIG. 80.

(122) FIGS. 82A-82B are partially cut away views, corresponding to the cross-sectional view of FIG. 81, illustrating various aspects of the isolated bottom enclosure member, the valve trim retaining member and the selector valve trim assembly of the representative one valve unit, as arranged in the fourth stage of assembly as illustrated in FIG. 78, and where:

(123) FIG. 82A is a bottom rear end isometric view from the right side; and

(124) FIG. 82B is a top front end isometric view from the left side.

(125) FIGS. 83A-83C illustrate a first exemplary button cap of the hand-held beverage dispenser, where:

(126) FIG. 83A is a top isometric view;

(127) FIG. 83B is a bottom plan view; and

(128) FIG. 83C is a cross-sectional elevational view taken along lines 83C-83C of FIG. 83A.

(129) FIGS. 84A-84C illustrate a second exemplary button cap of the hand-held beverage dispenser, where:

(130) FIG. 84A is a top isometric view;

(131) FIG. 84B is a bottom plan view; and

(132) FIG. 84C is a cross-sectional elevational view taken along lines 84C-84C of FIG. 84A.

(133) FIGS. 85-87 illustrate a fifth stage of assembly of the preferred embodiment of the hand-held beverage dispenser wherein a button cap is provided for operation of the flow control valve trim assembly of the representative one valve unit, and where:

(134) FIG. 85 is a partially exploded top rear end isometric view;

(135) FIG. 86 is a top rear end isometric view; and

(136) FIG. 87 is a top rear end isometric view, including the button cap for the flow control valve trim assembly of each valve unit.

(137) FIGS. 88-89 illustrate attachment of a post-mix type drink dispenser assembly to the handle body, in a sixth stage of assembly of the hand-held beverage dispenser, where:

(138) FIG. 88 is a partially exploded top front end isometric view; and

(139) FIG. 89 is a top rear end isometric view.

(140) FIGS. 90-92 illustrate various aspects of a top enclosure member of the preferred embodiment of the hand-held beverage dispenser, where:

- (141) FIG. **90** is a bottom plan view;
- (142) FIG. **91** is a bottom rear end isometric view; and
- (143) FIG. **92** is a top front end isometric view.
- (144) FIG. **93** is a partially exploded top rear end isometric view illustrating attachment of the top enclosure member to the handle body a seventh stage of assembly of the hand-held beverage dispenser.
- (145) FIGS. **94A-94B** illustrate various aspects of the assembled hand-held beverage dispenser, where:
- (146) FIG. **94A** is a top rear end isometric view; and
- (147) FIG. **94B** is a right side elevational view.
- (148) FIGS. **95A-95E** are partially cut away views generally corresponding to the partially cut away views of FIGS. **20-28**, and illustrating the representative one valve unit of the preferred embodiment of the hand-held beverage dispenser in a first operative state, where:
- (149) FIG. **95A** is a right side elevational view;
- (150) FIG. **95B** is a cross-sectional top plan view taken along lines **95B-95B** of FIG. **95A**;
- (151) FIG. **95C** is a top plan view; and
- (152) FIG. **95D** is a cross-sectional elevational view taken along lines **95D-95D** of FIG. **95C**.
- (153) FIG. **95E** is a schematic piping diagram corresponding to the views of FIGS. **95A-95D**.
- (154) FIGS. **96A-96D** are partially cut away views generally corresponding to the partially cut away views of FIGS. **20-28**, and illustrating the representative one valve unit of the preferred embodiment of the hand-held beverage dispenser in a second operative state, where:
- (155) FIG. **96A** is a right side elevational view;
- (156) FIG. **96B** is a cross-sectional top plan view taken along lines **96B-96B** of FIG. **96A**;
- (157) FIG. **96C** is a top plan view; and
- (158) FIG. **96D** is a cross-sectional elevational view taken along lines **96D-96D** of FIG. **96C**.
- (159) FIG. **96E** is a schematic piping diagram corresponding to the views of FIGS. **96A-96D**.
- (160) FIGS. **97A-97D** are partially cut away views generally corresponding to the partially cut away views of FIGS. **20-28**, and illustrating the representative one valve unit of the preferred embodiment of the hand-held beverage dispenser in a third operative state, where:
- (161) FIG. **97A** is a right side elevational view;
- (162) FIG. **97B** is a cross-sectional top plan view taken along lines **97B-97B** of FIG. **97A**;
- (163) FIG. **97C** is a top plan view; and
- (164) FIG. **97D** is a cross-sectional elevational view taken along lines **97D-97D** of FIG. **97C**.
- (165) FIG. **97E** is a schematic piping diagram corresponding to the views of FIGS. **97A-97D**.
- (166) FIGS. **98A-98D** are partially cut away views generally corresponding to the partially cut away views of FIGS. **20-28**, and illustrating the representative one valve unit of the preferred embodiment of the hand-held beverage dispenser in a fourth operative state, where:
- (167) FIG. **98A** is a right side elevational view;
- (168) FIG. **98B** is a cross-sectional top plan view taken along lines **98B-98B** of FIG. **98A**;
- (169) FIG. **98C** is a top plan view; and
- (170) FIG. **98D** is a cross-sectional elevational view taken along lines **98D-98D** of FIG. **98C**.
- (171) FIG. **98E** is a schematic piping diagram corresponding to the views of FIGS. **98A-98D**.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(172) As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention, which may be embodied in various forms. Figures are not necessarily to scale, and some features may be exaggerated to show details of particular components or steps.

Expressly Defined Terminology

Distinct

(173) In referring to various valves, whether in describing or claiming any of the present invention

or inventions, the term “distinct” means that each one of a plurality of referred to valves performs mutually exclusive functions, e.g., a first valve turning a flow on or off and a second valve selecting a single source from a plurality of sources when neither valve is provided with the capability to perform the function of the other.

Functionally Independent

(174) In referring to various valves, whether in describing or claiming any of the present invention or inventions, the term “functionally independent” means that each one of a plurality of referred to valves may be actuated, deactivated, operated or otherwise used in its normal function without regard to the state of any other such valve, and that actuation, deactivation, operation or other use of any such valve does not cause any change in state of any other such valve.

State

(175) In referring to referring to various valves or valve units, whether in describing or claiming any of the present invention or inventions, the term “state” means one configuration of a plurality of unique configurations of a single referred to valve, or one composite configuration of a plurality of unique composite configurations of a plurality of referred to valves operating together, in combination or otherwise cooperatively as a single unit.

Substantially Within

(176) In referring to the extents of a handle body of a hand-held beverage dispenser, whether in describing or claiming any of the present invention or inventions, the term “substantially within” means that a subject feature is within the outer extents of the handle body, which includes any portion of the feature that also forms any aspect of the outer extents of the handle body. The term expressly excludes any aspect of the feature that protrudes beyond the normal grip of the handle body, or interferes with control of the hand-held beverage dispenser, but includes any aspect of the feature that extends beyond the outer extents of the handle to form or interface with a control, or to form or interface with an inlet or outlet to or from the handle body, or is contained within a cover or the like that is ordinarily in place about the handle body in use of the hand-held beverage dispenser for dispensing a beverage product.

(177) Referring now to FIGS. 1-3 in particular, a preferred embodiment according to the present invention of a hand-held beverage dispenser 5 is shown to generally comprise a handle body 10 and a post-mix type drink dispenser assembly 275. As will be better understood further herein, the preferred embodiment of the hand-held beverage dispenser 5 further generally comprises a novel piping system 65, which is housed within the extents of the handle body 10. As shown in FIGS. 1-3, the handle body 10 has a top 18, a bottom 31, sides 47, and forward and rear ends 48, 52. A clamshell type housing assembly 17 includes an upper enclosure member 22 and a lower enclosure member 34, which together cover the handle body 10, and also present the outermost shape and appearance of a substantial portion of the handle body 10, including the forward end 48 thereof. As will be readily appreciated by those of ordinary skill in the relevant arts, the depicted hand-held beverage dispenser 5 is of the well-known class of beverage dispensers often referred to as bar guns or soda guns. Like other beverage dispensers of its class, the hand-held beverage dispenser 5 of the present invention is used for on demand dispensing of a selected one of a variety of post-mix beverages.

(178) As is well known to those of ordinary skill in the relevant arts, such post-mix beverages are prepared as they are dispensed from a bar gun by mixing together a beverage product and a diluent for the beverage product. The beverage product is typically beverage syrup or other concentrate, and the diluent for the concentrate is most often carbonated water or plain water. The present invention, however, is not limited in any fashion to or by these particular exemplary only beverage fluids, despite their typicality. In any case, a typical beverage diluent is generally appropriate for use with a great variety of beverage products. Conversely, a typical beverage product is generally only compatible with a particular diluent. Consequently, every beverage dispenser of the bar gun class must be formed, configured or otherwise adapted to deliver an appropriate diluent for any

selected beverage product, together with that selected beverage product, to the post-mix type drink dispenser assembly—in whatever manner the post-mix type drink dispenser assembly is implemented in connection with the particular hand-held beverage dispenser. As will be better understood further herein, the novel piping system **65** of the present invention is specially formed, configured and otherwise adapted to greatly facilitate matching an appropriate diluent with any particular beverage product as may be mixed together and dispensed from the hand-held beverage dispenser **5** of the present invention.

(179) In addition to implementing ad hoc selection of a diluent to be mixed with a particular beverage product, the novel piping system **65** of the present invention furthers other of Applicant's objects in providing the hand-held beverage dispenser **5** with functionally independent, single action, ON-OFF control of the flow of each post-mix beverage dispensed from the hand-held beverage dispenser **5**. As will be familiar to countless service industry employees worldwide, a plurality of ON-OFF flow controls **20a-20j** is accessible at the top **18** of the handle body **10** of the hand-held beverage dispenser **5**, as shown in FIGS. **1-3**.

(180) Each functionally independent ON-OFF flow control **20a-20j** for a corresponding post-mix beverage is actuated through the simple act of depressing the ON-OFF flow control **20a-20j** inward toward the handle body **10** of the hand-held beverage dispenser **5**. This single action in turn causes both the corresponding beverage product and the appropriate diluent for the beverage product to be mixed together and dispensed—as the desired post-mix beverage—from the post-mix type drink dispenser assembly **275** of the hand-held beverage dispenser **5**. Cooperating in the provision of such simple end-user control, the handle body **10** is most preferably ergonomically contoured about the sides **47** and bottom **31** to provide a secure, ambidextrous grip **46** for the end user of the hand-held beverage dispenser **5**. The resultant comfort in hand, and the ease of use of the simple ON-OFF flow controls **20a-20j**, enable the end user to effortlessly hold the post-mix type drink dispenser assembly **275** steady over a beverage vessel while any of the ON-OFF flow controls **20a-20j** is actuated—typically by thumb press.

(181) As shown in FIGS. **4-5**, the post-mix type drink dispenser assembly **275** of the hand-held beverage dispenser **5** is dependently coupled to the bottom **31** of the handle body **10** at a location adjacent the forward end **48** of the handle body **10**, and includes a mixer subassembly **276** in addition to the previously depicted nozzle housing **280**. The preferred embodiment of the hand-held beverage dispenser **5** of the present invention contemplates the provision of a universal handle body **10** and piping system **65** in an arrangement suitable for implementation and/or use with any of a wide range of post-mix type drink dispenser assemblies. Nonetheless, details of a post-mix type drink dispenser assembly, which operates in a manner consistent with the present invention for the provision of post-mix beverages, are shown and described in U.S. Pat. No. 11,208,313 B1 issued to Applicant on Dec. 28, 2021 for METHODS AND APPARATUS FOR POST-MIX DRINK DISPENSING. By this reference, U.S. Pat. No. 11,208,313 B1 is incorporated herein as though now set forth in its entirety. Although the nozzle housing **280** and the mixer subassembly **276** of the post-mix type drink dispenser assembly **275**, as configured in the general nature of the exemplary assembly, are both necessary components for properly mixing beverage fluids, the nozzle housing **280** is nonetheless adapted with the mixer subassembly **276** to be readily removable from the post-mix type drink dispenser assembly **275**, as implemented in the preferred embodiment of the hand-held beverage dispenser **5**.

(182) Integrating a post-mix type drink dispenser assembly **275** having a readily removable nozzle housing **280** into the preferred embodiment of the hand-held beverage dispenser **5** facilitates periodic cleaning of the post-mix type drink dispenser assembly **275**, in accordance with Applicant's object to provide the present inventions through an exemplary hand-held beverage dispenser **5** that nonetheless also includes such basic handling and maintenance features as typically expected by end users. In furtherance of these objects, the readily removable nozzle housing **280** includes a plurality of locking tabs **283** about an upper portion **282** of the inner surface

281 of nozzle housing **280**, as particularly shown in FIG. 5. The locking tabs are cooperatively adapted to operably engage mating nozzle housing locking members **279** provided about a lower portion **278** of the mixer subassembly **276**, as also shown in FIG. 5. As will be familiar to those of ordinary skill in the relevant arts as well as to service industry employees in general, the nozzle housing **280** locks in place with a partial twist in the clockwise direction about the mixer subassembly **276**, and is similarly released with a partial twist in the counterclockwise direction about the mixer **276**, as viewed from the bottom side **31** of the handle body **10**.

(183) As broadly compared to other types of post-mix beverage dispensers, beverage dispensers of the bar gun class are implemented with relatively limited functionality. For example, such beverage dispensers generally, if not universally, have no provision for adjustment or regulation of the flow rates therethrough of dispensed beverage fluids. However, as the beverage fluids pass through the implemented post-mix type drink dispenser assembly, at least the relative flow rates of a beverage product and its corresponding appropriate diluent are generally considered critical for obtaining the intended flavor, viscosity or other characteristics of a post-mix beverage. Accordingly, post-mix type beverage dispensers of the bar gun class rely on a discrete source, such as one of many readily commercially available flow control assemblies, to establish and regulate flow rates of provided beverage fluids. Like other beverage dispensers of the bar gun class the hand-held beverage dispenser **5** according to the present invention relies on an externally provided flow control assembly for the provision of appropriately regulated flows of beverage fluids. The details of such flow control assemblies, including details of the operation thereof, are well known to those of ordinary skill in the relevant arts.

(184) As is generally conventional in the relevant arts, a selected suitable flow control assembly is connected to the hand-held beverage dispenser **5** through a multiplicity of individual fluid lines, each of which is connected to, and in fluid communication with, one of a corresponding multiplicity of fluid inlets **66** provided at the rear end **52** of the handle body **10**, as particularly shown in FIG. 6. In turn, desired beverage fluids from the selected suitable flow control assembly may be introduced to each connected one of the multiplicity of fluid inlets **66** of the hand-held beverage dispenser **5** through the individual fluid lines. The multiplicity of individual fluid lines from the selected flow control assembly are most often collected together in a generally elongate, typically sheathed fluid line assembly. As is well known to those of ordinary skill in the relevant arts, the individual fluid lines typically terminate with connectors that are sized, shaped and otherwise adapted to provide fluid-tight interfaces between the individual fluid lines and the multiplicity of fluid inlets **66** of the hand-held beverage dispenser **5**. As also will be appreciated by those of ordinary skill in the relevant arts, any additional connector hardware or the like as may be required or otherwise desired to establish, and preferably secure, each of the individual fluid lines in fluid tight communication with a respective one of the fluid inlets **66** is readily provided within the level of ordinary skill in the relevant arts.

(185) The preferred embodiment of the hand-held beverage dispenser **5** of the present invention includes an easily removable, interlocking rear housing assembly **53**, such as may comprise an upper housing member **54** and a lower housing member **55** as shown in FIG. 6. As particularly shown in FIGS. 1 and 3, the rear housing assembly **53** provides an aesthetically pleasing enclosure for and about the connections between the individual fluid lines from a selected suitable flow control assembly and the multiplicity of fluid inlets **66** of the hand-held beverage dispenser **5**, and any additional connector hardware as may be implemented. The rear housing assembly **53** may also facilitate establishing or securing an operable connection between the fluid line assembly and the preferred embodiment of the hand-held beverage dispenser of the present invention as required or otherwise desired. The details of any additional connector hardware that may in any particular deployment be required, including details of the utilization thereof, and also details of the operation or utilization of the rear housing assembly **53** or an alternative therefor, are well known to those of ordinary skill in the relevant arts. It is particularly noted, however, it is also possible that either or

both of these features may be inventively provided beyond the scope of the present invention. In any case, and as also particularly shown in FIGS. **1** and **3**, the rear housing assembly **53** is readily attached to the rear end **52** of the handle body **10** with, for example, machine screws **56** or other conventional mounting hardware. Correspondingly, threaded holes **57**, which are sized, positioned and otherwise adapted to matingly receive the machine screws **56** or other conventional mounting hardware, are provided at the rear end **52** of the handle body **10** as particularly shown in FIG. **6**. (186) Through a set of corresponding, fully exploded views, FIGS. **7-8** illustrate various aspects of the constituent components of the exemplary hand-held beverage dispenser **5** as implemented in accordance with the present invention. In order to facilitate better understanding of the innovations implemented in the preferred embodiment of the hand-held beverage dispenser **5**, an overview of the features, assemblies and subassemblies of the hand-held beverage dispenser **5**, including various aspects of their functional relationships, is now provided with reference to FIGS. **7-8**. In particular, aspects of the novel piping system **65** of the hand-held beverage dispenser **5** as innovatively implement the capability to select a diluent to be mixed with any particular beverage product are identified. Additionally, other aspects of the hand-held beverage dispenser **5** as facilitate maintainability of the hand-held beverage dispenser **5** or end-user use of the diluent selection capability of the hand-held beverage dispenser **5** are identified. In any case, and with the aid of this overview, all of these and other aspects of the hand-held beverage dispenser **5** are more particularly set forth in the detailed discussions to follow.

(187) As shown in FIGS. **7-8**, the preferred embodiment of the hand-held beverage dispenser **5** is assembled about the previously discussed handle body **10**, which, as will be better understood further herein, includes many fluid conduits and like passages of the piping system **65** of the hand-held beverage dispenser **5**. In addition to the previously identified multiplicity of fluid inlets **66** provided at the rear end **52** of the handle body **10**, the handle body **10** also includes a multiplicity of fluid outlets **81** at the bottom **31** of the handle body **10** in a location adjacent the forward **48** end of the handle body **10**, as best shown in FIG. **8**. Each of the many fluid conduits and like passages of the piping system **10** is formed and fully defined by at least a segment of one or more fluid flow paths provided substantially within the extents of the handle body **10**, and running through the handle body **10** from one of the multiplicity of fluid inlets **66** to one of the multiplicity of fluid outlets **81**. The piping system **65** of the hand-held beverage dispenser **5** further includes a plurality of valve bodies **100a-100j** within the extents of the handle body **10**. Each of the plurality of valve bodies **100a-100j** runs through the handle body **10** between the bottom **31** of the handle body **10**, as particularly shown in FIG. **8**, and the top **18** of the handle body **10**, as particularly shown in FIG. **7**. Each of the plurality of valve bodies **100a-100j** is an integral component of the piping system **65** of the hand-held beverage dispenser **5**, and each of the previously identified fluid flow paths through the handle body **10**, from one of the multiplicity of fluid inlets **66** to one of the multiplicity of fluid outlets **81**, runs through one of the plurality of valve bodies **100a-100j**.

(188) In the preferred embodiment of the hand-held beverage dispenser **5**, each of the plurality of valve bodies **100a-100j** is populated with an inventive composite valve trim arrangement **91**, which as shown in FIGS. **7-8** includes a fully integral selector valve trim assembly **131**, for implementation of diluent selector valves **130a-130j**, and a flow control valve trim assembly **186**, for implementation of flow control valves **185a-185j**. As shown in the figures, each fully integral selector valve trim assembly **131** includes an open-topped cup **166**, which as will be better understood further herein implements an independently inventive multi-port, cylindrically formed gate valve, which is formed within a compact volume about a novel cylindrical valve gate **167** and capable of approximately $\frac{3}{8}$ turn or less operation.

(189) Each open-topped cup **166** of the diluent selector valves **130a-130j** inventively implements aspects of the flow control valves **185a-185j** in a cooperative arrangement of the diluent selector valves **130a-130j** with the flow control valves **185a-185j**. Notwithstanding this cooperative arrangement, however, the flow control valves **185a-185j** are both distinct and functionally

independent with respect to the diluent selector valves **130a-130j**. For clarity, it is also now emphasized that each of the provided plurality of diluent selector valves **130a-130j** is functionally independent with respect to all other provided diluent selector valves **130a-130j**, and likewise each of the provided plurality of flow control valves **185a-185j** is functionally independent with respect to all other provided flow control valves **185a-185j**.

(190) As shown in the figures, each flow control valve trim assembly **186** includes an integral valve stem assembly **187** and a poppet spring **219**. As will be better understood further herein each integral valve stem assembly **187** integrates a first flow control closure element **207**, a second flow control closure element **215** and a wiping seal **211**, which are implemented by overmolded reciprocating sealing members **205**, **213**. At this juncture, the highly integrated character of otherwise separate valve components, in addition to integration of disparate valves, should be emphasized as providing easier maintainability, as well as lessening the parts count potentially in the hands of end users. Finally, it is now emphasized that each valve body **100a-100j** is populated with a composite valve trim arrangement **91** including both a fully integral selector valve trim assembly **131** and a flow control valve trim assembly **186**, thereby implementing both a diluent selector valve **130a-130j** and a flow control valve **185a-185j** within each valve body **100a-100j** as a fully integral valve unit **90a-90j**.

(191) As particularly shown in FIG. **8**, each valve body **100a-100j** is populated through a circular open end **121** at the bottom **118** of the valve body **100a-100j**, each of which is readily accessible as necessary from the bottom **31** of handle body **10**. In use, however, each composite valve trim arrangement **91** is secured in place within its respective valve body **100a-100j** by a composite valve trim retaining member **245**, which is preferably provided as a rigid plate **246**, as shown in FIGS. **7-8**. As will be better understood further herein, the composite valve trim retaining member **245** not only secures each composite valve trim arrangement **91** operably in place, but also constrains the range of movement in operation of the diluent selector valves **130a-130j**, thereby greatly simplifying use of the diluent selector valves **130a-130j** by end users. As will be more fully described herein, the lower enclosure member **34** of the preferably provided clamshell type housing assembly **17** covers and encases both the lowermost portions of the composite valve trim arrangement **91**, and especially the diluent selector valves **130a-130j**, and the composite valve trim retaining member **245** during normal use of the hand-held beverage dispenser **5** of the present invention. The lower enclosure member **34** is also cooperatively adapted with the composite valve trim retaining member **245** to implement a failsafe for the diluent selector valves **130a-130j**, whereby the hand-held beverage dispenser **5** cannot be placed in normal use unless each diluent selector valve **130a-130j** is in a proper, even if incorrect, operable configuration. Further still, the cooperatively adapted lower enclosure member **34** and composite valve trim retaining member **245** implement a configuration lock, whereby once the hand-held beverage dispenser **5** is placed in normal use each diluent selector valve **130a-130j** is restrained in the configuration selected at deployment. These and other aspects of the operation of the inventive diluent selector valves **130a-130j** will be better understood in the detailed discussions to follow.

(192) FIGS. **7-8** also show aspects of the previously discussed simple ON-OFF flow controls **20a-20j** that enable end users to effortlessly hold the post-mix type drink dispenser assembly **275** steady over a beverage vessel while any of the ON-OFF flow controls **20a-20j** is actuated. As also shown in the figures, a subset **21** of flow controls **20i-20j** such as, for example, a subset **21** dedicated to dispensing only end-user selectable diluents, may include an alternatively shaped or otherwise configured button cap **240** to make the ON-OFF flow control **20i-20j** readily distinguishable from other ON-OFF flow controls **20a-20h** including a principal button cap **230**. In any case, each of the ON-OFF flow controls **20a-20j** is operably integrated with the flow control valve trim assembly **186** of a corresponding one of the flow control valves **185a-185j**. In particular, each ON-OFF flow control **20a-20j** for the exemplary implementation of the hand-held beverage dispenser **5** includes an operable integration of a corresponding button cap **230**, **240**, a valve stem **188** and a poppet

spring **219**, to form an actuator button as more fully described herein. To this end, an upper seal **225** for each valve unit **90a-90j** is provided to enable fluid tight passage of the top end **190** of a valve stem **188** through the top **101** of each corresponding valve body **100a-100i** from within to without the valve body **100a-100j**.

(193) FIGS. **7-8** show various details of the provision and arrangement of a post-mix type drink dispenser assembly **275**, including a readily removable nozzle housing **280** as previously noted to be a feature generally expected by end users. FIGS. **7-8** also show how various connector tubes **265** and rods **266**, together with a rubber or like material seal **277**, may be utilized as necessary or otherwise desired for attachment in fluid communication with the through the fluid outlets **81** from the handle body **10** of a particular post-mix type drink dispenser assembly **275**. Additionally, the figures show the provision of mounting holes **29** through the top **18** of the handle body **10**, at its forward end **48**, for receiving conventional mounting hardware **30**, such as the depicted machine screws, for attachment of a mixer subassembly **276** of a utilized **275** post-mix type drink dispenser assembly **275**.

(194) The hand-held beverage dispenser **5** according to the present invention, as implements the novel piping system **65** of the present invention, is formed about and substantially within the extents of an inventive handle body **10**, as is particularly shown in FIGS. **9-12**. Not unlike many hand-held beverage dispensers **5** of the bar gun class, the hand-held beverage dispenser **5** according to the present invention comprises a multiplicity of fluid inlets **66**, as particularly shown in FIGS. **9** and **11**, a multiplicity of fluid outlets **81**, as particularly shown in FIGS. **10** and **12**, and plurality of flow controls **20a-20j**, such as buttons or like actuators as previously discussed, for example with reference to FIGS. **1** and **7-8**. As will be appreciated by those of ordinary skill in the relevant arts, the provided flow controls **20a-20j** actuate various beverage fluid flows or combinations of fluid flows from the multiplicity of fluid inlets **66** to the multiplicity of fluid outlets **81**, where the actuated beverage fluid flows are directed to a post-mix type drink dispenser assembly **275** for mixing together as a desired beverage product, if required, and dispensing from the hand-held beverage dispenser **5**.

(195) As particularly shown in FIG. **11**, the multiplicity of fluid inlets **66** as provided in accordance with the depicted preferred implementation of the hand-held beverage dispenser **5** includes at least a first diluent inlet **67** and a second diluent inlet **68**, and a plurality of beverage product inlets **69a-69h**, there being provided one beverage product inlet for each beverage product to be dispensed. Similarly, and as particularly shown in FIG. **12**, the multiplicity of fluid outlets **81** as provided in accordance with the depicted preferred implementation of the hand-held beverage dispenser **5** includes an equal plurality of beverage product outlets **83a-83h** as are provided beverage product inlets **69a-69h**. On the other hand, the preferred implementation of the hand-held beverage dispenser **5** of the present invention includes a single, common diluents outlet **82**, as is generally conventional, although more could be provided.

(196) In a leap forward for the relevant arts, however, the novel piping system **65** of the present invention provides various flow paths through the hand-held beverage dispenser **5** between the multiplicity of fluid inlets **66** to the piping system **65** and the multiplicity of fluid outlets **81** from the piping system **65**, wherein at least some of the flow paths are selectively established. In particular and as will be better understood in the details set forth further herein, the novel piping system **65** of the present invention is adapted to enable, for each of a plurality of provided beverage products, end-user selection of any one of a plurality of provided diluents, whereafter the selected diluent is dispensed concurrently with the beverage product for which the selection has been made. To this end, and as previously discussed in the overview provided with particular reference to FIGS. **7-8**, each fluid flow path through the handle body **10** of the hand-held beverage dispenser **5**, as implemented according to the preferred embodiment of the present invention, runs through one of the plurality of valve bodies **100a-100j**, about which a corresponding valve unit **90a-90j** is implemented to include a diluent selector valve **130a-130j** and a flow control valve **185a-185j**.

(197) As will be better understood further herein, each diluent selector valve **130a-130j** enables ad hoc selection of one of a plurality of diluents for passage through the valve unit **90a-90j**, under the selective control of the correspondingly implemented flow control valve **185a-185j**. As shown in FIGS. **10** and **12**, each individual valve body **100a-100j** comprises a circular open end **121** at the bottom **118** of the valve body **100a-100j**. As shown in the figures, the bottom **118** of each valve body **100a-100j** according to this exemplary implementation forms, or is formed as, a portion of the bottom **31** of handle body **10**. As previously discussed in the overview provided with particular reference to FIGS. **7-8**, the circular open end **121** at the bottom **118** of the valve body **100a-100j** provides access to the corresponding composite valve trim arrangement **91**, whereby each diluent selector valve **130a-130j** may be operated to effect an ad hoc selection of one of a plurality of diluents for passage through the valve unit **90a-90j**.

(198) While each diluent selector valve **130a-130j** may be operated to effect an ad hoc selection of one of a plurality of diluents for passage through the valve unit **90a-90j**, passage through the valve unit **90a-90j** of the selected diluent is under the selective control of the correspondingly implemented flow control valve **185a-185j**, as previously noted. To this end, and as is particularly shown in FIG. **9**, a preferably cylindrical flow control valve actuator orifice **102** is formed at the top **101** of each valve body **100a-100j**, a portion of each of which is particularly shown in FIG. **9** at the top **18** of handle body **10**. As will be better understood further herein, the top end **190** of the generally cylindrical valve stems **188** about which is formed each flow control valve trim assembly **186** of the flow control valves **185a-185j**, as also shown in overview FIGS. **7-8**, protrudes through the respective cylindrical flow control valve actuator orifice **102**. As also will be better understood further herein, each of the plurality of ON-OFF flow controls **20a-20j**, as shown in FIGS. **1-3**, is operated through a button cap **230, 240** preferably removably attached to the top end **190** of each generally cylindrical valve stem **188** for user actuation of the corresponding one of the flow control valves **185a-185j**. As will be better understood further herein, actuation of a flow control valve **185a-185j** operates to effect passage through the valve unit **90a-90j** of the selected diluent, and, in the general case of there being a beverage product also introduced to the valve unit **90a-90j**, actuation of the flow control valve **185a-185j** also operates to effect concurrent passage through the valve unit **90a-90j** of the introduced beverage product.

(199) FIGS. **9-12** show various features of the handle body **10** particularly directed to external aspects of the hand-held beverage dispenser **5** of the present invention. As shown in FIG. **9**, a plurality of threaded holes **19** for removably affixing the upper enclosure member **22** of the clamshell type housing assembly **17**, as variously shown in FIGS. **1-8**, to the top **18** of the handle body **10** are provided in the top **18** of the handle body **10**. As is conventional in the art, the provided threaded holes **19** are cooperatively adapted to removably receive conventional mounting hardware **28** such as screws, as shown in FIGS. **7-8**. FIGS. **10** and **12** similarly show a plurality of threaded holes **33** for removably affixing the lower enclosure member **34** of the clamshell type housing assembly **17**, as variously shown in FIGS. **1-8**, to the bottom **31** of handle body **10**, and also a plurality of threaded holes **32** for removably affixing the composite valve trim retaining member **245**, as shown in FIGS. **7-8**, to the bottom **31** of handle body **10**. As is conventional in the art, the provided threaded holes **33** for affixing the lower enclosure member **34** are cooperatively adapted to removably receive conventional mounting hardware **44** such as screws, as shown in FIGS. **7-8**, and the provided threaded holes **32** for removably affixing the composite valve trim retaining member **245** are conventionally cooperatively adapted to removably receive conventional mounting hardware **254** such as screws, as also shown in FIGS. **7-8**.

(200) FIGS. **9-10** also particularly depict aspects of the handle body **10** provided by an overmold **13**, which as will be better understood further herein generally implements the relatively-soft-body features **14** of the handle body **10** beyond the novel piping system **65** of the present invention. The overmold **13** thus provides much of the general form of the handle body **10**. For example, the overmold **13** implements both functional and aesthetic features such as the contoured surfaces **15**

which go beyond aesthetics to provide ergonomic shapes, as well as conforming support for the upper and lower enclosure members **22, 34** of the clamshell type housing assembly **17**. The overmold **13** also implements provisions such as channels **16** particularly adapted to accommodate such features as snap fit joints molded or otherwise provided in connection with the clamshell type housing assembly **17**. Finally, the provision of the overmold **13** is particularly suited to filling the internal interstices **12**, voids and other like spaces in and about a structural framework **11**, which preferably implements the internally embodied aspects of the piping system **65** of the present invention and is more fully described herein with particular reference to FIGS. **13-17**.

(201) As described in the broad overview with reference to FIGS. **7-8**, the preferred embodiment of the hand-held beverage dispenser **5** includes many fluid conduits and like passages of a piping system **65** generally provided within the extents of the handle body **10** of the hand-held beverage dispenser **5**. As discussed in overview, the provided fluid conduits and like passages of the piping system **65** establish numerous fluid flow paths within the extents of the handle body **10**, each of which runs through the handle body **10** from one of a multiplicity of fluid inlets **66** to one of the multiplicity of fluid outlets **81**. As further noted in the overview, the piping system **65** of the hand-held beverage dispenser **5** further includes a plurality of valve bodies **100a-100j** within the extents of the handle body **10**, and, importantly, each of the identified fluid flow paths running through the handle body **10** runs from one of the multiplicity of fluid inlets **66** to one of the plurality of valve bodies **100a-100j**, and then from the corresponding one of the valve bodies **100a-100j** to a corresponding one of the multiplicity of fluid outlets **81**, the valve bodies **100a-100j** being integral components of the piping system **65**. In the most preferred embodiment of the hand-held beverage dispenser **5**, the portions of the provided fluid conduits and like passages of the piping system **65** terminating at a fluid outlet **81** are collected together at the top side **50** of a preferably unitarily formed toe plate **49** of the handle body **10**. As particularly shown in FIGS. **13-17**, the toe plate **49** is generally formed or otherwise provided at the bottom **31** of the handle body **10** in a location adjacent the forward **48** end of the handle body **10**. In accordance with this most preferred implementation, each fluid outlet **81** of the piping system **65** of the hand-held beverage dispenser **5** is arranged about the bottom side **51** of the toe plate **49** of the handle body **10**, as particularly shown in FIGS. **12** and **14**.

(202) As shown and described with reference to FIGS. **9-12**, the multiplicity of fluid inlets **66** includes at least a first diluent inlet **67** and a second diluent inlet **68**, and a plurality of beverage product inlets **69a-69h**. As previously noted, one beverage product inlet **69a-69h** is provided for each beverage product that a particular implementation of the hand-held beverage dispenser **5** is capable of dispensing. As also shown and described with reference to FIGS. **9-12**, the multiplicity of fluid outlets **81** includes an equal plurality of beverage product outlets **83a-83h** as are provided beverage product inlets **69a-69h**, and most preferably a single, common diluents outlet **82**. FIGS. **9-12** also show parts of the valve bodies **100a-100j**, thereby clearly showing at least the preferred arrangement and placement of the valve bodies **100a-100j** within the hand-held beverage dispenser **5**. Finally, the discussion of FIGS. **9-12** also notes that the preferred embodiment of the hand-held beverage dispenser **5** of the present invention implements the handle body **10** as an overmold **13** applied to a structural framework **11** for the handle body **10**.

(203) Referring now to FIGS. **13-16** in particular, the structural framework **11** for the handle body **10** according to the preferred implementation contemplates additively manufacturing the structural framework **11** from stainless steel or like material. Advantageously, Applicant has found this method of making the handle body **10** is particularly suited to manufacturing at least a large part of the necessary structural framework **11** in the forms of the fluid conduits and passages themselves. Utilization of the fluid conduits and passages of the piping system **65** for formation of the structural framework **11** also greatly facilitates providing the piping system **65** of the present invention substantially within the extents of the described handle body **10** of the hand-held beverage dispenser **5**.

(204) As particularly shown in FIGS. **13-16**, each of the multiplicity of fluid inlets **66** is placed in fluid communication with a corresponding one of the provided valve bodies **100a-100j** through a connecting one of various fluid conduits and like passages to the corresponding one of the provided valve bodies **100a-100j**. Likewise, each of the multiplicity of fluid outlets **81** is shown to be placed in fluid communication with a corresponding one of the provided valve bodies **100a-100j** through a connecting one of other various fluid conduits and like passages from the corresponding one of the provided valve bodies **100a-100j**. FIG. **17**, on the other hand, shows the handle body **10** of the hand-held beverage dispenser **5** in a cross-sectional view generally corresponding to the view of FIG. **16**, but with the overmold **13** applied. As particularly shown in FIG. **17**, especially as compared to FIG. **16**, the overmold **13** most preferably fills substantially all of the internal interstices **12**, voids and other like spaces in and about the fluid conduits and passages of the piping system **65** providing fluid communication between the valve bodies **100a-100j** and corresponding fluid inlets **66** and fluid outlets **81**.

(205) The views of FIGS. **13-17** are meant to exemplify such physical embodiments as may implement the necessary fluid communications within the extents of the handle body **10** of the piping system **65**. Accordingly, only a limited selection of the fluid conduits and like passages is identified in FIGS. **13-16** in order to preserve clarity. However, all of the fluid conduits and like passages provided according to this exemplary implementation are fully described in the discussions to follow, and particularly in the various descriptions with reference to the schematic piping diagrams of FIGS. **29** and **30A-30D**. Prior to setting forth these fluid communications in detail, however, additional details of the valve bodies **100a-100j**, and in particular details of the various inlet and outlet ports to and from the valve bodies **100a-100j**, are shown and described with reference to FIGS. **20-28**. As an aid in these further descriptions of the valve units **90a-90j**, an exemplary one valve unit **90d** is selected as generally representative of each of the valve units **90a-90j**, and the component parts thereof, including an exemplary one valve body **100d**. To this end, FIGS. **18-19** show the heretofore described exemplary handle body **10**, wherein the exemplary one valve body **100d** of the representative exemplary one valve unit **90d** is depicted with its composite valve trim arrangement **91** shown as substantially assembled operatively in place within the valve body **100d**, thereby identifying and illustrating various features of the representative one valve unit **90d** as in an operable configuration.

(206) As noted in the overview discussions of FIGS. **7-8**, the composite valve trim arrangement **91** for each of the valve bodies **100a-100j** includes a fully integral selector valve trim assembly **131** for implementation of the diluent selector valves **130a-130j**, and a flow control valve trim assembly **186** for implementation of the flow control valves **185a-185j**. Each fully integral selector valve trim assembly **131** is described as including an open-topped cup **166**, and each flow control valve trim assembly **186** is described as including an integral valve stem assembly **187** and a poppet spring **219**. Finally, an ON-OFF flow control **20a-20j** for each valve unit **90a-90j** is described as being operable through a button cap **230**, **240** attached to the top end **190** of a valve stem **188** of the flow control valve trim assembly **186** of a corresponding flow control valve **185a-185j**, wherefore an upper seal **225** for each valve unit **90a-90j** is provided.

(207) FIGS. **18-19** illustrate the provision of a composite valve trim arrangement **91** for the representative valve body **100d**, in implementation of the representative valve unit **90d** comprising a representative diluent selector valve **130d** and a representative flow control valve **185d**. As particularly shown in FIG. **19**, an open-topped cup **166** is cooperatively arranged, within the representative valve body **100d**, with an integral valve stem assembly **187** and a poppet spring **219**. In accordance with the previously discussed inventive cooperative arrangement of the diluent selector valve **130d** for the flow control valve **185d**, it is now particularly noted that the poppet spring **219** and a bottom end **203** of the integral valve stem assembly **187** are arranged within an interior portion of the open-topped cup **166**. Finally, as shown in FIGS. **18-19**, an upper portion **189** of the valve stem **188** passes through the upper seal **225** of the valve unit **90d**, where, as will be

better understood further herein, a user interface for the corresponding flow control **20d**, such as a button, may be operatively attached at the top end **190** of the upper portion **189** of the valve stem **188** for selective actuation of the implemented flow control valve **185d**.

(208) As will be better understood further herein, the integral valve stem assembly **187** and poppet spring **219**, as implement the flow control valve trim assembly **186**, operate longitudinally within the interior space of the open-topped cup **166**, without interference with or by any operation or lack thereof of the implemented diluent selector valve **130d**. Likewise, and as also will be better understood further herein, the open-topped cup **166**, as implements the fully integral selector valve trim assembly **131**, operates rotationally about the flow control valve trim assembly **186**, without interference with or by any operation or lack thereof of the implemented flow control valve **185d**. As a result, the implemented diluent selector valve **130d** and the implemented flow control valve **185d** are each both distinct and functionally independent with respect to the other, notwithstanding the extensive cooperative adaptation therebetween.

(209) Turning then to FIGS. **20-28**, partially cut away views of the representative exemplary valve body **100d** illustrate various aspects of the representative one valve body **100d** as viewed with virtually all other aspects of the handle body **10** cut away, thereby providing maximum visibility of the various features of the valve body **100d**, as though the valve body **100d** and only the immediately adjacent features of the handle body **10** are completely removed from the remainder of the hand-held beverage dispenser **5**. It is noted, however, that the representative valve body **100d** is utilized in further views and discussions to illustrate and describe aspects of the present invention in relation to a representative exemplary valve unit **90d** formed about and including the representative valve body **100d**.

(210) FIGS. **20-28** show the representative exemplary valve body **100d** comprising a generally axially symmetric body having a preferably cylindrical flow control valve actuator orifice **102** at the top **101** and a circular open end **121** at the bottom **118**. As particularly shown in FIGS. **20**, **23** and **26-27**, an annulus **103** is formed or otherwise provided at the base of the flow control valve actuator orifice **102**, and is sized, configured or otherwise adapted to retain the upper seal **225** for the implemented valve unit **90d** in place. As particularly shown in FIGS. **21** and **26-27**, the circular open end **121** at the bottom **118** of the valve body **100d**, exposes a cylindrical socket **119**. The provided cylindrical socket **119** is sized, configured or otherwise adapted for receiving a lower seal **172** of the valve unit **90d**, which as will be understood further herein is implemented as part of a plug **171** formed integrally with the selector valve trim assembly **131** of an implemented diluent selector valve **130d**. At this juncture, however, it is noted that the circular open end **121** most preferably comprises a chamfered or similarly relieved edge **122** to prevent damage to the lower seal **172**, and the cylindrical socket **119** most preferably comprises a beveled or similarly relieved edge **120** to prevent damage to a cylindrical valve gate **167** of the diluent selector valve **130d**, as more fully described herein.

(211) As particularly illustrated in FIGS. **26-28**, the valve body **100d** is preferably formed as a set of axially aligned, stacked cylinders with transitions therebetween, and wherein the interior structures are generally axially symmetric. In the exemplary implementation of the valve body **100d** according to the present invention, the stacked cylinders increase in diameter from top to bottom. As will be better understood further herein, this arrangement facilitates receiving the entirety of the composite valve trim arrangement **91** through the circular open end **121** at the bottom **118** of the valve body **100d** in population thereof. As particularly shown in FIGS. **26-28**, an upper chamber **104** of the valve body **100d** is formed or otherwise provided below the cylindrical flow control valve actuator orifice **102** at the top **101** of the valve body **100d**, an intermediate chamber **106** of the valve body **100d** is formed or otherwise provided below the upper chamber **104**, and a lower chamber **111** of the valve body **100d** is formed or otherwise provided below the intermediate chamber **106** and above the previously discussed cylindrical socket **119**.

(212) As shown in the figures, a beverage product outlet port **105** is formed or otherwise provided

through the side wall of the upper chamber **104**, and a beverage product inlet port **108** is formed or otherwise provided through and adjacent the top of the cylindrical interior wall **107** about the intermediate chamber **106**. The beverage product outlet port **105** is in direct fluid communication through a beverage product dispensing conduit **80d** with the corresponding beverage product outlet **83d** on the bottom side **51** of the toe plate **49** of the handle body **10**. Similarly, the beverage product inlet port **108** is in direct fluid communication, through a beverage product supply conduit **76d**, with the corresponding beverage product inlet **69d** at the rear end **52** of the handle body **10**.

(213) A diluent outlet port **110** is formed or otherwise provided through the cylindrical interior wall **107** in the lower portion of the intermediate chamber **106**. The diluent outlet port **110** is in fluid communication through a valve dispense branch **79d** with a common trunk **78** of a common diluents outlet manifold **77**. The common trunk **78** of the common diluents outlet manifold **77** is, in turn, in fluid communication with the single, common diluents outlet **82** at the bottom side **51** of the toe plate **49** of the handle body **10**. As will be better understood further herein, the common trunk **78** of the implemented common diluents outlet manifold **77** provides fluid communication for every diluent dispensed from the exemplary hand-held beverage dispenser **5**.

(214) A first diluent inlet port **116** and a second diluent inlet port **117** are each formed or otherwise provided through and adjacent the top of the cylindrical interior wall **112** about the lower chamber **111** of the valve body **100d**. As is well known to those of ordinary skill in the relevant arts post-mix diluents are typically mixed with post-mix beverage products in ratios on the order of five to one. In order to adequately sustain the substantially greater relative fluid flow rate of diluents into the valve body **100d** without compromising the compact character achieved for the valve unit **90d** notwithstanding implementation of new functionality, each diluent inlet port **116**, **117** is preferably formed or otherwise provided in a horizontally oriented obround or like shape.

(215) The first diluent inlet port **116** is in fluid communication through a valve supply branch **72d** with a common trunk **71** of a first diluent inlet manifold **70**. The common trunk **71** of the first diluent inlet manifold **70** is in turn in fluid communication with the first diluent inlet **67** at the rear end **52** of the handle body **10**. As will be better understood further herein, the common trunk **71** of the first diluent inlet manifold **70** provides fluid communication to each valve unit **90a-90j** for any diluent admitted into the hand-held beverage dispenser **5** through the first diluent inlet **67**.

Similarly, the second diluent inlet port **117** is in fluid communication through a valve supply branch **75d** with a common trunk **74** of a second diluent inlet manifold **73**. The common trunk **74** of the second diluent inlet manifold **73** is in turn in fluid communication with the second diluent inlet **68** at the rear end **52** of the handle body **10**. As also will be better understood further herein, the common trunk **74** of the second diluent inlet manifold **73** provides fluid communication to each valve unit **90a-90j** for any diluent admitted into the hand-held beverage dispenser **5** through the second diluent inlet **68**.

(216) The upper chamber **104** of the valve body **100d**, as particularly illustrated in FIGS. **26-28**, is formed or otherwise provided having an internal diameter sufficient to accommodate and permit a desired fluid flow about the upper portion **189** of the valve stem **188** of the representative flow control valve **185d**, as shown in FIG. **19** and more fully described herein. The cylindrical interior wall **107** about the intermediate chamber **106** and the cylindrical interior wall **112** about the lower chamber **111**, however, each implement or otherwise constrain operating features of the flow control valve **185d** and the diluent selector valve **130d**, respectively, in implementation of the operable valve unit **90d**. As such, the diameter of the cylindrical interior wall **107** about the intermediate chamber **106** and the diameter of the cylindrical interior wall **112** about the lower chamber **111** must, like other features of the intermediate chamber **106** and the lower chamber **111**, be specified or otherwise implemented consistent with other requirements of the implemented flow control valve **185d** and diluent selector valve **130d**.

(217) The cylindrical interior wall **107** about the intermediate chamber **106** defines a first valve body working segment of the valve unit **90d** that is particularly formed, configured or otherwise

adapted for the flow control valve **185d**. In particular, a first flow control closure element **207** operates within the first valve body working segment to control fluid flow, or communication, through an internal beverage product passage of the valve body **100d** running between the beverage product inlet port **108** and the beverage product outlet port **105**. In the exemplary implementation as will be better understood further herein, the internal diameter of the cylindrical interior wall **107** about the intermediate chamber **106** of the valve body **100d** is formed or otherwise provided having a first working diameter for the valve unit **90d** that is greater than the diameter of the upper chamber **104** of the valve body **100d**. Additionally, however, the transition, or step, between the intermediate chamber **106** and the upper chamber **104** of the valve body **100d** implements an upper valve seat **109** of the valve body **100d**, which is also particularly formed, configured or otherwise adapted as a feature of the implemented the flow control valve **185d**, as more fully described herein. As best shown in FIGS. **26-28**, the upper valve seat **109** is readily formed as a circumferential bevel between the cylindrical interior wall **107** about the intermediate chamber **106** of the valve body **100d** and the side wall of the upper chamber **104** of the valve body **100d**.

(218) The cylindrical interior wall **112** about the lower chamber **111**, on the other hand, defines a second valve body working segment of the valve unit **90d** that is particularly formed, configured or otherwise adapted for the diluent selector valve **130d**. In particular, a passage selection closure element **174** operates within the second valve body working segment to selectively enable fluid flow, or communication, through an exclusive one of at least a first internal diluent passage of the valve body **100d** and a second internal diluent passage of the valve body **100d**. The first internal diluent passage of the valve body **100d** runs between the first diluent inlet port **116** and the diluent outlet port **110** of the valve body **100d**, and the second internal diluent passage of the valve body **100d** runs between the second diluent inlet port **117** and the diluent outlet port **110** of the valve body **100d**. In the exemplary implementation, as will be better understood further herein, the internal diameter of the cylindrical interior wall **112** defining the lower chamber **111** of the valve body **100d** is formed or otherwise provided having a second working diameter for the valve unit **90d** that is substantially greater than the first working diameter for the valve unit **90d** defining the first valve body working segment of the valve unit **90d**.

(219) Like the transition between the intermediate chamber **106** and the upper chamber **104** of the valve body **100d**, the transition, or step, between the lower chamber **111** and the intermediate chamber **106** of the valve body **100d** implements a lower valve seat **115** of the valve body **100d**, which is particularly formed, configured or otherwise adapted as a feature of the implemented the flow control valve **185d**, as more fully described herein. Still further, however, the transition, or step, between the lower chamber **111** and the intermediate chamber **106** of the valve body **100d** implements a shoulder **113** between the lower chamber **111** and the intermediate chamber **106** that is particularly formed, configured or otherwise adapted as a feature of the implemented diluent selector valve **130d**, as more fully described herein. As best shown in FIGS. **26-28**, the lower valve seat **115** for the flow control valve **185d** is readily formed as a circumferential chamfer about the inside edge **114** of the shoulder **113**, as implemented for the diluent selector valve **130d**.

(220) With the foregoing details of the representative one valve body **100d** in hand, including in particular details of the various inlet and outlet ports into and out of the representative one valve body **100d**, as well as details of the various fluid conduits and like passages of the piping system **65** that place the various inlet and outlet ports of the valve body **100d** in fluid communication with corresponding ones of the multiplicity of fluid inlets **66** provided at the rear end **52** of the handle body **10** and with corresponding ones of the multiplicity of fluid outlets **81** on the bottom side **51** of the toe plate **49** of the handle body **10**, details of the various flow paths and relationships embodied by the piping system **65** of hand-held beverage dispenser **5** as previously described with particular reference to aspects of the representative one valve body **100d** are now extrapolated more fully to each valve body **100a-100j**, as applicable, thereby doubly ensuring clarity in the detailed descriptions to follow.

(221) As particularly shown in FIGS. 29 and 30A-30D, the hand-held beverage dispenser 5 comprises a set of manifolds for efficiently providing fluid communication of diluents into and out of each valve body 100a-100j. As schematically shown in the figures, a first diluent inlet manifold 70 comprises a common trunk 71 between the first diluent inlet 67 and a plurality of valve supply branches 72a-72j, each valve supply branch 72a-72j corresponding to one of the valve bodies 100a-100j. Similarly, a provided second diluent inlet manifold 73 comprises a common trunk 74 between the second diluent inlet 68 and a plurality of valve supply branches 75a-75j, each valve supply branch 75a-75j corresponding to one of the valve bodies 100a-100j. Still further, a common diluents outlet manifold 77 comprises a common trunk 78 between a plurality of valve dispense branches 79a-79j, each valve dispense branch 79a-79j corresponding to one of the valve bodies 100a-100j, and the single, common diluents outlet 82. Dedicated beverage product supply conduits 76a-76h and beverage product dispensing conduits 80a-80h, however, are respectively provided to and from each corresponding valve body 100a-100h. As previously discussed, a diluent selector valve 130a-130j and a functionally independent and distinct flow control valve 185a-185j are cooperatively implemented, as a valve unit 90a-90j, about each corresponding valve body 100a-100j.

(222) Referring particularly now to FIGS. 29 and 30A, and with reference to FIGS. 20-28 as necessary, a dedicated beverage product supply conduit 76a is provided between beverage product inlet 69a and beverage product inlet port 108 of corresponding valve body 100a for conveying a supplied beverage product from beverage product inlet 69a to valve body 100a. A dedicated beverage product dispensing conduit 80a is provided between beverage product outlet port 105 of valve body 100a and corresponding beverage product outlet 83a for selectively conveying the beverage product supplied through beverage product inlet port 108 of valve body 100a from valve body 100a and to beverage product outlet 83a, the selective conveyance being effected by operation of flow control valve 185a. A valve supply branch 72a is provided between common trunk 71 and first diluent inlet port 116 of corresponding valve body 100a for conveying a diluent supplied to common trunk 71 through first diluent inlet 67 from common trunk 71 to valve body 100a. A valve supply branch 75a is provided between common trunk 74 and second diluent inlet port 117 of corresponding valve body 100a for conveying a diluent supplied to common trunk 74 through second diluent inlet 68 from common trunk 74 to valve body 100a. A valve dispense branch 79a is provided between diluent outlet port 110 of corresponding valve body 100a and common trunk 78 for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port 116 of valve body 100a or the diluent supplied through second diluent inlet port 117 of valve body 100a from valve body 100a to common diluents outlet 82. The selection of one or the other of the diluent supplied through first diluent inlet port 116 or the diluent supplied through second diluent inlet port 117 for selective conveyance from valve body 100a to common diluents outlet 82 is determined by the state of diluent selector valve 130a. The selective conveyance of the selected diluent from valve body 100a to common diluents outlet 82 is effected by operation of flow control valve 185a.

(223) A dedicated beverage product supply conduit 76b is provided between beverage product inlet 69b and beverage product inlet port 108 of corresponding valve body 100b for conveying a supplied beverage product from beverage product inlet 69b to valve body 100b. A dedicated beverage product dispensing conduit 80b is provided between beverage product outlet port 105 of valve body 100b and corresponding beverage product outlet 83b for selectively conveying the beverage product supplied through beverage product inlet port 108 of valve body 100b from valve body 100b and to beverage product outlet 83b, the selective conveyance being effected by operation of flow control valve 185b. A valve supply branch 72b is provided between common trunk 71 and first diluent inlet port 116 of corresponding valve body 100b for conveying a diluent supplied to common trunk 71 through first diluent inlet 67 from common trunk 71 to valve body 100b. A valve supply branch 75b is provided between common trunk 74 and second diluent inlet

port **117** of corresponding valve body **100b** for conveying a diluent supplied to common trunk **74** through second diluent inlet **68** from common trunk **74** to valve body **100b**. A valve dispense branch **79b** is provided between diluent outlet port **110** of corresponding valve body **100b** and common trunk **78** for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port **116** of valve body **100b** or the diluent supplied through second diluent inlet port **117** of valve body **100b** from valve body **100b** to common diluents outlet **82**. The selection of one or the other of the diluent supplied through first diluent inlet port **116** or the diluent supplied through second diluent inlet port **117** for selective conveyance from valve body **100b** to common diluents outlet **82** is determined by the state of diluent selector valve **130b**. The selective conveyance of the selected diluent from valve body **100b** to common diluents outlet **82** is effected by operation of flow control valve **185b**.

(224) A dedicated beverage product supply conduit **76c** is provided between beverage product inlet **69c** and beverage product inlet port **108** of corresponding valve body **100c** for conveying a supplied beverage product from beverage product inlet **69c** to valve body **100c**. A dedicated beverage product dispensing conduit **80c** is provided between beverage product outlet port **105** of valve body **100c** and corresponding beverage product outlet **83c** for selectively conveying the beverage product supplied through beverage product inlet port **108** of valve body **100c** from valve body **100c** and to beverage product outlet **83c**, the selective conveyance being effected by operation of flow control valve **185c**. A valve supply branch **72c** is provided between common trunk **71** and first diluent inlet port **116** of corresponding valve body **100c** for conveying a diluent supplied to common trunk **71** through first diluent inlet **67** from common trunk **71** to valve body **100c**. A valve supply branch **75c** is provided between common trunk **74** and second diluent inlet port **117** of corresponding valve body **100c** for conveying a diluent supplied to common trunk **74** through second diluent inlet **68** from common trunk **74** to valve body **100c**. A valve dispense branch **79c** is provided between diluent outlet port **110** of corresponding valve body **100c** and common trunk **78** for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port **116** of valve body **100c** or the diluent supplied through second diluent inlet port **117** of valve body **100c** from valve body **100c** to common diluents outlet **82**. The selection of one or the other of the diluent supplied through first diluent inlet port **116** or the diluent supplied through second diluent inlet port **117** for selective conveyance from valve body **100c** to common diluents outlet **82** is determined by the state of diluent selector valve **130c**. The selective conveyance of the selected diluent from valve body **100c** to common diluents outlet **82** is effected by operation of flow control valve **185c**.

(225) Referring particularly now to FIGS. **29** and **30B**, and with reference to FIGS. **20-28** as necessary, a dedicated beverage product supply conduit **76d** is provided between beverage product inlet **69d** and beverage product inlet port **108** of corresponding valve body **100d** for conveying a supplied beverage product from beverage product inlet **69d** to valve body **100d**. A dedicated beverage product dispensing conduit **80d** is provided between beverage product outlet port **105** of valve body **100d** and corresponding beverage product outlet **83d** for selectively conveying the beverage product supplied through beverage product inlet port **108** of valve body **100d** from valve body **100d** and to beverage product outlet **83d**, the selective conveyance being effected by operation of flow control valve **185d**. A valve supply branch **72d** is provided between common trunk **71** and first diluent inlet port **116** of corresponding valve body **100d** for conveying a diluent supplied to common trunk **71** through first diluent inlet **67** from common trunk **71** to valve body **100d**. A valve supply branch **75d** is provided between common trunk **74** and second diluent inlet port **117** of corresponding valve body **100d** for conveying a diluent supplied to common trunk **74** through second diluent inlet **68** from common trunk **74** to valve body **100d**. A valve dispense branch **79d** is provided between diluent outlet port **110** of corresponding valve body **100d** and common trunk **78** for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port **116** of valve body **100d** or the diluent supplied through second

diluent inlet port **117** of valve body **100d** from valve body **100d** to common diluents outlet **82**. The selection of one or the other of the diluent supplied through first diluent inlet port **116** or the diluent supplied through second diluent inlet port **117** for selective conveyance from valve body **100d** to common diluents outlet **82** is determined by the state of diluent selector valve **130d**. The selective conveyance of the selected diluent from valve body **100d** to common diluents outlet **82** is effected by operation of flow control valve **185d**.

(226) A dedicated beverage product supply conduit **76e** is provided between beverage product inlet **69e** and beverage product inlet port **108** of corresponding valve body **100e** for conveying a supplied beverage product from beverage product inlet **69e** to valve body **100e**. A dedicated beverage product dispensing conduit **80e** is provided between beverage product outlet port **105** of valve body **100e** and corresponding beverage product outlet **83e** for selectively conveying the beverage product supplied through beverage product inlet port **108** of valve body **100e** from valve body **100e** and to beverage product outlet **83e**, the selective conveyance being effected by operation of flow control valve **185e**. A valve supply branch **72e** is provided between common trunk **71** and first diluent inlet port **116** of corresponding valve body **100e** for conveying a diluent supplied to common trunk **71** through first diluent inlet **67** from common trunk **71** to valve body **100e**. A valve supply branch **75e** is provided between common trunk **74** and second diluent inlet port **117** of corresponding valve body **100e** for conveying a diluent supplied to common trunk **74** through second diluent inlet **68** from common trunk **74** to valve body **100e**. A valve dispense branch **79e** is provided between diluent outlet port **110** of corresponding valve body **100e** and common trunk **78** for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port **116** of valve body **100e** or the diluent supplied through second diluent inlet port **117** of valve body **100e** from valve body **100e** to common diluents outlet **82**. The selection of one or the other of the diluent supplied through first diluent inlet port **116** or the diluent supplied through second diluent inlet port **117** for selective conveyance from valve body **100e** to common diluents outlet **82** is determined by the state of diluent selector valve **130e**. The selective conveyance of the selected diluent from valve body **100e** to common diluents outlet **82** is effected by operation of flow control valve **185e**.

(227) Referring particularly now to FIGS. **29** and **30C**, and with reference to FIGS. **20-28** as necessary, a dedicated beverage product supply conduit **76f** is provided between beverage product inlet **69f** and beverage product inlet port **108** of corresponding valve body **100f** for conveying a supplied beverage product from beverage product inlet **69f** to valve body **100f**. A dedicated beverage product dispensing conduit **80f** is provided between beverage product outlet port **105** of valve body **100f** and corresponding beverage product outlet **83f** for selectively conveying the beverage product supplied through beverage product inlet port **108** of valve body **100f** from valve body **100f** and to beverage product outlet **83f**, the selective conveyance being effected by operation of flow control valve **185f**. A valve supply branch **72f** is provided between common trunk **71** and first diluent inlet port **116** of corresponding valve body **100f** for conveying a diluent supplied to common trunk **71** through first diluent inlet **67** from common trunk **71** to valve body **100f**. A valve supply branch **75f** is provided between common trunk **74** and second diluent inlet port **117** of corresponding valve body **100f** for conveying a diluent supplied to common trunk **74** through second diluent inlet **68** from common trunk **74** to valve body **100f**. A valve dispense branch **79f** is provided between diluent outlet port **110** of corresponding valve body **100f** and common trunk **78** for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port **116** of valve body **100f** or the diluent supplied through second diluent inlet port **117** of valve body **100f** from valve body **100f** to common diluents outlet **82**. The selection of one or the other of the diluent supplied through first diluent inlet port **116** or the diluent supplied through second diluent inlet port **117** for selective conveyance from valve body **100f** to common diluents outlet **82** is determined by the state of diluent selector valve **130f**. The selective conveyance of the selected diluent from valve body **100f** to common diluents outlet **82** is effected by operation of flow

control valve **185f**.

(228) A dedicated beverage product supply conduit **76g** is provided between beverage product inlet **69g** and beverage product inlet port **108** of corresponding valve body **100g** for conveying a supplied beverage product from beverage product inlet **69g** to valve body **100g**. A dedicated beverage product dispensing conduit **80g** is provided between beverage product outlet port **105** of valve body **100g** and corresponding beverage product outlet **83g** for selectively conveying the beverage product supplied through beverage product inlet port **108** of valve body **100g** from valve body **100g** and to beverage product outlet **83g**, the selective conveyance being effected by operation of flow control valve **185g**. A valve supply branch **72g** is provided between common trunk **71** and first diluent inlet port **116** of corresponding valve body **100g** for conveying a diluent supplied to common trunk **71** through first diluent inlet **67** from common trunk **71** to valve body **100g**. A valve supply branch **75g** is provided between common trunk **74** and second diluent inlet port **117** of corresponding valve body **100g** for conveying a diluent supplied to common trunk **74** through second diluent inlet **68** from common trunk **74** to valve body **100g**. A valve dispense branch **79g** is provided between diluent outlet port **110** of corresponding valve body **100g** and common trunk **78** for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port **116** of valve body **100g** or the diluent supplied through second diluent inlet port **117** of valve body **100g** from valve body **100g** to common diluents outlet **82**. The selection of one or the other of the diluent supplied through first diluent inlet port **116** or the diluent supplied through second diluent inlet port **117** for selective conveyance from valve body **100g** to common diluents outlet **82** is determined by the state of diluent selector valve **130g**. The selective conveyance of the selected diluent from valve body **100g** to common diluents outlet **82** is effected by operation of flow control valve **185g**.

(229) A dedicated beverage product supply conduit **76h** is provided between beverage product inlet **69h** and beverage product inlet port **108** of corresponding valve body **100h** for conveying a supplied beverage product from beverage product inlet **69h** to valve body **100h**. A dedicated beverage product dispensing conduit **80h** is provided between beverage product outlet port **105** of valve body **100h** and corresponding beverage product outlet **83h** for selectively conveying the beverage product supplied through beverage product inlet port **108** of valve body **100h** from valve body **100h** and to beverage product outlet **83h**, the selective conveyance being effected by operation of flow control valve **185h**. A valve supply branch **72h** is provided between common trunk **71** and first diluent inlet port **116** of corresponding valve body **100h** for conveying a diluent supplied to common trunk **71** through first diluent inlet **67** from common trunk **71** to valve body **100h**. A valve supply branch **75h** is provided between common trunk **74** and second diluent inlet port **117** of corresponding valve body **100h** for conveying a diluent supplied to common trunk **74** through second diluent inlet **68** from common trunk **74** to valve body **100h**. A valve dispense branch **79h** is provided between diluent outlet port **110** of corresponding valve body **100h** and common trunk **78** for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port **116** of valve body **100h** or the diluent supplied through second diluent inlet port **117** of valve body **100h** from valve body **100h** to common diluents outlet **82**. The selection of one or the other of the diluent supplied through first diluent inlet port **116** or the diluent supplied through second diluent inlet port **117** for selective conveyance from valve body **100h** to common diluents outlet **82** is determined by the state of diluent selector valve **130h**. The selective conveyance of the selected diluent from valve body **100h** to common diluents outlet **82** is effected by operation of flow control valve **185h**.

(230) As previously noted, the most preferred implementation of the hand-held beverage dispenser **5** of the present invention contemplates a pair of ON-OFF flow controls **20i-20j**, each of which is dedicated to dispensing a diluent only through valve units **90i-90j** configured to only dispense diluents. As also previously noted, the most preferred implementations of the present invention contemplate that the provision of either the first diluent only or the second diluent only is also end-

user selectable. In order to meet these demands, the novel piping system **65** of the present invention omits the beverage product supply conduits and beverage product dispensing conduits, as otherwise would run to or from the corresponding adjunct valve units **90i-90j**. Additionally, each corresponding valve body **100i-100j** is formed or otherwise provided without a beverage product inlet port **108** or a beverage product outlet port **105**. On the other hand, the valve bodies **100i-100j** are formed or otherwise provided with internal structures identical to those of valve bodies **100a-100h**, thereby requiring no additional or different valve components for implementation of the desired features.

(231) Referring particularly now to FIGS. **29** and **30D**, and with reference to FIGS. **20-28** as necessary, a valve supply branch **72i** is provided between common trunk **71** and first diluent inlet port **116** of corresponding valve body **100i** for conveying a diluent supplied to common trunk **71** through first diluent inlet **67** from common trunk **71** to valve body **100i**. A valve supply branch **75i** is provided between common trunk **74** and second diluent inlet port **117** of corresponding valve body **100i** for conveying a diluent supplied to common trunk **74** through second diluent inlet **68** from common trunk **74** to valve body **100i**. A valve dispense branch **79i** is provided between diluent outlet port **110** of corresponding valve body **100i** and common trunk **78** for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port **116** of valve body **100i** or the diluent supplied through second diluent inlet port **117** of valve body **100i** from valve body **100i** to common diluents outlet **82**. The selection of one or the other of the diluent supplied through first diluent inlet port **116** or the diluent supplied through second diluent inlet port **117** for selective conveyance from valve body **100i** to common diluents outlet **82** is determined by the state of diluent selector valve **130i**. The selective conveyance of the selected diluent from valve body **100i** to common diluents outlet **82** is effected by operation of flow control valve **185i**.

(232) Likewise, a valve supply branch **72j** is provided between common trunk **71** and first diluent inlet port **116** of corresponding valve body **100j** for conveying a diluent supplied to common trunk **71** through first diluent inlet **67** from common trunk **71** to valve body **100j**. A valve supply branch **75j** is provided between common trunk **74** and second diluent inlet port **117** of corresponding valve body **100j** for conveying a diluent supplied to common trunk **74** through second diluent inlet **68** from common trunk **74** to valve body **100j**. A valve dispense branch **79j** is provided between diluent outlet port **110** of corresponding valve body **100j** and common trunk **78** for selectively conveying a separately selected one of either the diluent supplied through first diluent inlet port **116** of valve body **100j** or the diluent supplied through second diluent inlet port **117** of valve body **100j** from valve body **100j** to common diluents outlet **82**. The selection of one or the other of the diluent supplied through first diluent inlet port **116** or the diluent supplied through second diluent inlet port **117** for selective conveyance from valve body **100j** to common diluents outlet **82** is determined by the state of diluent selector valve **130j**. The selective conveyance of the selected diluent from valve body **100j** to common diluents outlet **82** is effected by operation of flow control valve **185j**.

(233) As previously noted, each fully integral selector valve trim assembly **131** includes an inventive specially formed open-topped cup **166** in implementation of the diluent selection valves **130a-130j** and other inventive aspects of the valve units **90a-90j** of the exemplary hand-held beverage dispenser **5**. In the most preferred implementation of the hand-held beverage dispenser **5**, the fully integral selector valve trim assembly **131** is implemented as a flexible yet resilient thermoplastic overmold **165** as applied to and including aspects of a preferably moldable, yet strong and durable thermoplastic structural body **132**. The structural body **132**, however, could alternatively be additively formed, milled, cast or otherwise formed. Although other materials may be utilized in other combinations for both the overmold **165** and structural body **132**, the open-topped cup **166** as formed for the exemplary hand-held beverage dispenser **5** according to the preferred embodiment includes a thermoplastic overmold **165** comprising a food grade polyether-based thermoplastic polyurethane. The structural body **132** as forms a rigid substrate for the overmold **165** in the exemplary implementation of the open-topped cup **166** comprises a food grade

amorphous copolyester or like material.

(234) Referring now to FIGS. **31-36**, the structural body **132** is formed or otherwise provided as a molded thermoplastic or alternatively formed as open-topped vessel **133**, in accordance with the described most preferred implementation. The preferred implementation of the open-topped vessel **133** generally comprises a substantially radially symmetric structure, and includes an upper portion **134**, a lower portion **135** and a lowermost flanged base portion **150**. The upper portion **134** of the open-topped vessel **133** implements the previously noted passage selection closure element **174** for the diluent selector valve **130d**. As will be better understood further herein, the passage selection closure element **174** for the diluent selector valve **130d** is implemented as an independently inventive cylindrical valve gate **167**, which is formed about the upper portion **134** of the open-topped vessel **133**. In addition to aspects of the fully integral selector valve trim assembly **131**, a lower seal **172** for the valve unit **90d** is implemented about the lower portion **135** of the open-topped vessel **133** as part of a plug **171**. As will be better understood further herein, the plug **171** is implemented more generally about the lowermost flanged base portion **150** of the open-topped vessel **133**.

(235) In definition of the open-topped vessel **133**, a tiered socket **137** is formed or otherwise provided through the top **136** of the structural body **132**, whereby a cylindrical chamber **139** of the open-topped cup **166** is implemented in an upper tier **138** of the tiered socket **137** and a preferably cylindrical receptacle **143** of the open-topped cup **166** is implemented in a lower tier **142** of the tiered socket **137**. For clarity, however, and as more fully described herein, the upper tier **138** generally defines the upper portion **134** of the open-topped vessel **133** and the implemented cylindrical chamber **139** of the open-topped cup **166**. The cylindrical interior wall **140** about the cylindrical chamber **139** defines a third valve body working segment of the valve unit **90d** that is particularly formed, configured or otherwise adapted for the flow control valve **185d**. In particular, a second flow control closure element **215** operates within this third valve body working segment to control fluid flow, or communication, through a user selected one of at least a first internal diluent passage of the valve body **100d** and a second internal diluent passage of the valve body **100d**. The first internal diluent passage runs between the first diluent inlet port **116** and the diluent outlet port **110** of the valve body **100d**, and the second internal diluent passage runs between the second diluent inlet port **117** and the diluent outlet port **110** of the valve body **100d**. As will be better understood further herein, the internal diameter of the cylindrical interior wall **140** about the cylindrical chamber **139** of the open-topped cup **166** is formed or otherwise provided having a third working diameter for the valve unit **90d** that is greater than the first working diameter for the valve unit **90d** defining the first valve body working segment of the valve unit **90d**, but is substantially less than the second working diameter for the valve unit **90d** defining the second valve body working segment of the valve unit **90d**. Within these constraints, the required substantiality of the differences between the second working diameter and the first and third working diameters is largely a matter of desired thickness of the cylindrical valve gate **167** implemented in connection with the open-topped cup **166** of the diluent selector valve **130d**, as also constrained by available space within the extents of the handle body **5** of the hand-held beverage dispenser **10**.

(236) The previously noted lower tier **142** is formed through the bottom **141** of the cylindrical chamber **139**, and within the lower portion **135**, below the bottom **141** of the cylindrical chamber **139**, of the open-topped vessel **133** to define a preferably cylindrical, closed-bottom receptacle **143**. The closed-bottom receptacle **143** is sized, shaped or otherwise adapted for receiving one end of the poppet spring **219** of the flow control valve trim assembly **186** conformingly about the outer circumference of the poppet spring **219**.

(237) A preferably radially symmetric outer wall **144** of the open-topped vessel **133** includes contours **145**, grooves **146** or like features for accommodating, as well as facilitating adherence and stability of, the overmold **165**, as will be better understood further herein. A top edge **147** of the open-topped vessel **133** is defined between the respective uppermost extents of the cylindrical

interior wall **140** about the cylindrical chamber **139** and the outer wall **144** of the open-topped vessel **133**. A plurality of posts **148** or like anchors project upwardly from the top edge **147** of the open-topped vessel **133** to facilitate adherence and stability of the overmold **165**. In an important aspect of the present invention, a horizontally oriented notch **149** is provided in the top edge **147** of the open-topped vessel **133**.

(238) A lowermost portion **150** of the open-topped vessel **133**, below the outer wall **144** of the open-topped vessel **133**, includes a cylindrical base **152** atop a circumferential flange **155**, which together form a closed bottom **151** of the open-topped vessel **133**, and thus the fully integral selector valve trim assembly **131**. The cylindrical base **152** conforms to, and has an outer diameter sufficiently less than the inside diameter of the circular open end **121** at the bottom **118** of the valve body **100d** as to enable the cylindrical base **152** to be readily slidingly received through the circular open end **121** and into the bottom **118** of the valve body **100d**. An annular ledge **153** is formed or otherwise provided atop the cylindrical base **152**. Although not critical, the top **154** of the annular ledge **153** is preferably formed or otherwise provided as a substantially planar surface to facilitate application and support of the overmold **165**.

(239) The circumferential flange **155** forms a substantially planar, annular top surface **156** about the cylindrical base **152** bounded by a preferably circular top rim **157** about the circumferential flange **155**. The diameter of the circumferential flange **155** at the top rim **157** is sufficiently greater than the diameter of the cylindrical base **152** such that the substantially planar, annular top surface **156** of the circumferential flange **155** is sized, shaped or otherwise adapted for flush engagement with, and preferably all about, the circular open end **121** at the bottom **118** of the valve body **100d**. A preferably circular bottom rim **159** about the circumferential flange **155**, however, is deeply chamfered or similarly relieved such that the diameter of the circumferential flange **155** at the bottom rim **159** is substantially less than the diameter of the circumferential flange **155** at the top rim **157**. As more fully described herein, the chamfered, beveled or otherwise relieved outer edge of the circumferential flange **155** enables very close conformance of the lower enclosure member **34** for the handle body **10** about the lowermost flanged base portion **150** of the open-topped vessel **133**.

(240) A cylindrical protuberance **162**, in the general nature of a trunnion, projects downwardly from the bottom side **161** of the closed bottom **151** of the open-topped vessel **133** of the diluent selector valve **130d** and thus the fully integral selector valve trim assembly **131**. A bottom face **163** of the cylindrical protuberance **162** includes a blind slot **164** for engagement by a standard slotted screwdriver or a like implement in operation of the diluent selector valve **130d** in accordance with the present invention, as more fully described herein. As will be better understood further herein, the cylindrical protuberance **162** is sized, shaped or otherwise adapted to substantially conformingly engage an arcuate notch **248** of the rigid plate **246** of the composite valve trim retaining member **245**, as introduced in the overview description of FIGS. 7-8. As operably placed in use, at least a portion of the bottom side **161** of the closed bottom **151** of the open-topped vessel **133**, and thus the fully integral selector valve trim assembly **131**, securely abuts a top side **247**, about the arcuate notch **248**, of the rigid plate **246**, as more fully described herein. Accordingly, the bottom side **161** of the closed bottom **151** of the open-topped vessel **133** forms a substantially planar, annular engagement surface **158** for the fully integral selector valve trim assembly **131**. As particularly illustrated in FIG. 32, the annular engagement surface **158** is formed or otherwise provided about the downwardly projecting cylindrical protuberance **162** and is bounded by the preferably circular bottom rim **159** about the circumferential flange **155**. The substantially reduced diameter of the circumferential flange **155** at the bottom rim **159**, as previously described, also substantially reduces the area of the substantially planar engagement surface **158**, which, as will be better understood further herein, is in frictional engagement with the top side **247** of the rigid plate **246** of the composite valve trim retaining member **245**.

(241) A downwardly projecting stop post **160** extends from the chamfered bottom rim **159** of the

circumferential flange **155**. The stop post **160** is formed, configured or otherwise adapted to operably engage various features of upwardly projecting locking barriers **40** formed or otherwise provided on the interior side **37** of the lower enclosure member **34**, interiorly bulging areas **43** of the lower enclosure member **34**, and edge segments **251** of the rigid plate **246** of the composite valve trim retaining member **245**, which are specially provided to implement stops **252** for the stop post **160**. Each of these features and engagements are described in greater detail further herein.

(242) As particularly shown in FIGS. **37-40**, the previously described overmold **165** is selectively applied to the structural body **132** providing the substrate for the overmold **165**, thereby cooperatively implementing the fully integral selector valve trim assembly **131** for the diluent selector valve **130d** in the preferred form of the open-topped cup **166**. For clarity, the most preferred implementation of the open-topped cup **166**, including the cylindrical valve gate **167**, contemplates a composite structure comprising a combination of overmold **165** and naked substrate, that is portions of the structural body **132** not covered by the overmold material and therefore remaining exteriorly exposed. The passage selection closure element **174** for the diluent selector valve **130d** of the exemplary hand-held beverage dispenser **5** according to the preferred embodiment is thus implemented as the compositely formed cylindrical valve gate **167**.

(243) The cylindrical valve gate **167** for the diluent selector valve **130d** is cooperatively formed between the cylindrical interior wall **140** about the cylindrical chamber **139** of the open-topped vessel **133**, and thus the open-topped cup **166**, and a cylindrical exterior surface **168** of the open-topped cup **166** as formed or otherwise provided by the overmold **165**. Consistent with the previously described lower chamber **111** of the valve body **100d**, the cylindrical exterior surface **168** of the open-topped cup **166** is formed or otherwise provided by the overmold **165** having a diameter closely conforming to the second working diameter for the valve unit **90d** defining the second valve body working segment of the valve unit **90d** such that when the open-topped cup **166** is operably received within the valve body **100d** it is freely but sealingly rotatable in place. As particularly shown in FIGS. **37** and **40**, application of the overmold **165** about the horizontally oriented notch **149** in the top edge **147** of the open-topped vessel **133** also forms a horizontally oriented notch **170** for the open-topped cup **166** of the diluent selector valve **181d** substantially coextensive with the horizontally oriented notch **149** of the open-topped vessel **133**.

(244) The overmold **165** also extends substantially coextensively over the top edge **147** of the open-topped vessel **133** to cooperatively form a preferably substantially planar upper edge **169** of the cylindrical valve gate **167**, and thus the open-topped cup **166**. As operably placed in use of the hand-held beverage dispenser **5**, the upper edge **169** of the open-topped cup **166** engages the shoulder **113** about the top of the lower chamber **111**, thereby joining the cylindrical chamber **139** of the open-topped cup **166** with the intermediate chamber **106** of the valve body **100d**. As joined, the first and third valve body working segments of the valve unit **90d** form a continuous valve body volume for implementation of the flow control valve **185d**. Although making use of common structure through at least the valve body **100d** and the open-topped cup **166**, the diluent selector valve **130d** and the flow the flow control valve **185d**, as implemented with the inventive composite valve trim arrangement **91** shown and described herein, are nonetheless both functionally independent and distinct.

(245) As previously noted, the lower seal **172** for the valve unit **90d** is implemented adjacent the lowermost portion of the selector valve trim assembly **131** that is received within the valve body **100d**. As shown in the figures, the lower seal **172** is provided by the overmold **165** below the cylindrical exterior surface **168** of the cylindrical valve gate **167**. In use of the hand-held beverage dispenser **5** of the present invention, the cylindrical valve gate **167** is operably received within the lower chamber **111** of the valve body **100d** defining the second valve body working segment of the valve unit **90d**. The lower seal **172** for the valve unit **90d**, however, is operably received within the cylindrical socket **119** at the bottom **118** of the valve body **100d**, and is cooperatively adapted with the cylindrical base **152** and circumferential flange **155** at the lowermost flanged base portion **150**

of the open-topped vessel **133** to form a plug **171** corresponding to the cylindrical socket **119**. (246) The cylindrical socket **119** at the bottom **118** of the valve body **100d** has an internal diameter that is coextensive with the circular open end **121** of the valve body **100d** and slightly greater than the second working diameter for the valve unit **90d** defined by the lower chamber **111** of the valve body **100d**. The greater diameter of the circular open end **121** and cylindrical socket **119** of the valve body **100d** permits the lower seal **172** for the valve unit **90d** to have a greater outer diameter than that of the cylindrical exterior surface **168** of the cylindrical valve gate **167**. This arrangement facilitates specification of the interface or other working characteristics for the lower seal **172** of the valve unit **90d** independent of the specified characteristics for the cylindrical exterior surface **168** of the cylindrical valve gate **167**, thereby ensuring a desired level of sealing engagement is achieved for each.

(247) As previously noted, each flow control valve trim assembly **186** includes an integral valve stem assembly **187** and a poppet spring **219**. As particularly shown in FIGS. **41-43**, the integral valve stem assembly **187** comprises a generally cylindrical, axially symmetric valve stem **188**, a first flow control closure element **207**, a second flow control closure element **215** and a wiping seal **211**. As shown in FIGS. **41-43**, but most particularly in FIG. **43**, the upper portion **189** of the valve stem **188** is substantially narrowed, as compared to the generally uniform diameter of the midsection **192** and lower portion **198** of the valve stem **188**. As previously noted, the upper portion **189** of the valve stem **188** is sized, shaped or otherwise configured or adapted to extend from within to without the valve body **100d** while in use, thereby implementing aspects of the ON-OFF flow control **20d** for manual actuation by a user of the flow control valve **185d**. The valve stem **188** also includes a keeper groove **191** adjacent the top end **190** of the valve stem **188** for retaining a button cap **230**, which will more fully described herein to also implement aspects of the ON-OFF flow control **20d**.

(248) As shown in FIGS. **41-43**, a first, upper reciprocating sealing member **205**, in the general form of a spool-shaped annular body **206**, is most preferably implemented about the midsection **192** of the valve stem **188** as an integral overmold of the valve stem **188**. The annular body **206** includes the first flow control closure element **207** and the wiping seal **211** for the flow control valve **185d**. The first flow control closure element **207** comprises a top surface **208** generally bounded by a cylindrical outer edge **210**. The top surface **208** of the first flow control closure element **207** includes a valve face **209**, which is formed, configured or otherwise adapted to sealingly engage the upper valve seat **109** of the flow control valve **185d**, as formed at the transition between the intermediate chamber **106** and the upper chamber **104** of the valve body **100d**. The wiping seal **211** includes an outer edge **212** that is sized, configured or otherwise adapted to operate against the cylindrical interior wall **107** of the intermediate chamber **106** as a reciprocating wiper. As more fully described herein, the reciprocating wiper formed by the outer edge **212** segregates, and provides fluid isolation between, the interior space of the valve body **100d** above the wiping seal **211** and the interior space of the valve body **100d** below the wiping seal **211**, as the flow control valve trim assembly **186** shifts longitudinally up and down within the exemplary valve body **100d**.

(249) In order to facilitate adherence of the overmold implementing the first, upper reciprocating sealing member **205**, and provide structure and stability during use for the spool-shaped annular body **206** implementing the first flow control closure element **207** and wiping seal **211**, a first retainer **193** is formed at the midsection **192** of the valve stem **188** for the first, upper reciprocating sealing member **205**. In particular, as shown in FIG. **43**, a first, upper annular disk **194** and a second, lower annular disk **195** of the first retainer **193** are milled or otherwise provided about the midsection **192** of the valve stem **188**. Additionally, a first, upper annular groove **196** and a second, lower annular groove **197** of the first retainer **193** are milled or otherwise provided about the midsection **192** between the first, upper annular disk **194** and the second, lower annular disk **195** of the first retainer **193**.

(250) As also shown in FIGS. 41-43, a second, lower reciprocating sealing member **213** in the general form of a discoid annular body **214** is most preferably implemented about the lower portion **198** of the valve stem **188** as an integral overmold of the valve stem **188**. The annular body **214** implements the second flow control closure element **215** includes a second flow control closure element **215** for the flow control valve **185d**, which comprises a top surface **216** generally bounded by a cylindrical outer edge **218**. The top surface **216** of the second flow control closure element **215** includes a valve face **217**, which is formed, configured or otherwise adapted to sealingly engage the lower valve seat **115** of the flow control valve **185d**, as formed at the transition between the lower chamber **111** and the intermediate chamber **106** of the valve body **100d**.

(251) In order to facilitate adherence of the overmold implementing the second, lower reciprocating sealing member **205**, and provide structure and stability during use for the discoid annular body **214** implementing the second flow control closure element **215**, a second retainer **199** is formed at the lower portion **198** of the valve stem **188** for the second, lower reciprocating sealing member **213**. In particular, as shown in FIG. 43, a first, upper annular disk **200** and a second, lower annular disk **201** of the second retainer **199** are milled or otherwise provided about the lower portion **198** of the valve stem **188**. Additionally, an annular groove **202** of the second retainer **199** is milled or otherwise provided about the lower portion **198** between the first, upper annular disk **200** and the second, lower annular disk **201** of the second retainer **199**.

(252) A downwardly projecting protuberance **204** from the bottom end **203** of the valve stem **188** is formed or otherwise provided in the general nature of a trunnion. In an important aspect of the cooperative integration of the open-topped cup **166** and the flow control valve trim assembly **186** forming the fully integrated selector valve trim assembly **131**, the downwardly projecting protuberance **204** of the valve stem **188** is sized, shaped or otherwise adapted to engage the free, reciprocating end of the poppet spring **219** while the opposite, generally fixed end of the poppet spring **219** is engaged within the closed-bottom receptacle **143** provided therefor in the open-topped cup **166** of the diluent selector valve **130d**.

(253) Referring now to the corresponding fully exploded views of FIGS. 44-45, the composite valve trim arrangement **91** is shown to comprise just three separable components, including the fully integral selector valve trim assembly **131**, for implementation of diluent selector valves **130a-130j**, and a flow control valve trim assembly **186**, for implementation of flow control valves **185a-185j**. As previously described, the flow control valve trim assembly **186** comprises an integral valve stem assembly **187** and a poppet spring **219**. As shown in FIGS. 44-45 and FIGS. 46A-46B and 47A-47B, an end of the poppet spring **219** is received within the open-topped cup **166** forming the selector valve trim assembly **131**, and is captured within the cylindrical receptacle **143** provided therefor through the bottom **141** of the cylindrical chamber **139**. As previously described, the opposite end of the poppet spring **219** is engaged by the downwardly projecting protuberance **204** provided therefor at the bottom end **203** of the valve stem **188**. As particularly shown in FIGS. 46B and 47B, the second, lower reciprocating sealing member **213** of the integral valve stem assembly **187** operates, as previously described, within the third valve body working segment of the valve unit **90d**, as defined by the cylindrical interior wall **140** about the cylindrical chamber **139** of the open-topped cup **166**. FIG. 46B shows the composite valve trim arrangement **91** as in a first operational state, wherein the flow control valve **185d** is at rest in the OFF, or closed, configuration. FIG. 47B, on the other hand, shows the composite valve trim arrangement **91** as in a second operational state, wherein the integral valve stem assembly **187** has been operated to press against the poppet spring **219** and further into the third valve body working segment of the valve unit **90d**, thereby actuating the flow control valve **185d** in the ON, or open, configuration.

(254) In a selectively implementable preliminary stage of assembly of the preferred embodiment of the hand-held beverage dispenser **5** of the present invention, as particularly illustrated in FIGS. 48-49, a multiplicity of connector tubes **265** may be press fit into the various fluid outlets **81** as necessary or otherwise desired, for example to provide or enhance compatibility with fluid

connectors or other aspects of the particular mixer subassembly **276** of the post-mix type drink dispenser assembly **275** selected for use in connection with the hand-held beverage dispenser **5** of the present invention. Additionally, or alternatively, rods **266** may be provided and similarly attached to the handle body **10** to plug or otherwise close unused inlets of the utilized mixer subassembly **276**. In order to prevent damage to more delicate components of the hand-held beverage dispenser **5** during press fit of like attachment operations, it may be preferable if possible to complete any such manufacturing operations in an early stage of assembly prior to integration with the handle body **10** of any such delicate or otherwise likely to be damaged components.

(255) Referring now to FIGS. **50-53**, various details of the upper seal **225** for the exemplary valve unit **90d** of the present invention are shown and described. In the preferred implementation of the valve unit **90d** of the present invention, the upper seal **225** is formed as a grommet-shaped plug **226** comprising rubber or like material. The plug **226** is provided with a circumferential shoulder **227** about the top, which will be more fully described herein as resting upon the top **101** of the exemplary valve body **100d** about the flow control valve actuator orifice **102** when operably placed for use. As previously noted, the plug **226** comprises a central orifice **228** running longitudinally through the plug **226** and sized, shaped or otherwise adapted to slidably but sealingly engage a coextensive length of the outer surface of the upper portion **189** of the generally cylindrical valve stem **188**. As particularly shown in FIGS. **51** and **53**, the bottom edge of the central orifice **228** is preferably chamfered or otherwise relieved to prevent loss of integrity or other damage to the upper seal **225** during assembly of the valve unit **90d**. The top edge of the central orifice **228** may also be chamfered or otherwise relieved as necessary or otherwise desired in a particular implementation as shown in the figures. The plug **226** also has a retention groove **229** formed about the midsection of the plug **226**, which is sized, shaped or otherwise adapted to engage the corresponding annulus **103** formed within the flow control valve actuator orifice **102** of the exemplary valve body **100d**. As will be appreciated by those of ordinary skill in the relevant arts in view of this exemplary description, the described arrangement of the upper seal **225** and flow control valve actuator orifice **102** firmly secures the plug **226** operably in place when the central orifice **228** is occupied by the upper portion **189** of the valve stem **188**.

(256) As illustrated in FIGS. **54-57**, a first stage of assembly of the hand-held beverage dispenser **5** according to the preferred embodiment of the present invention begins with insertion of an upper seal **225** for the flow control valve **185d** into the flow control valve actuator orifice **102** of the exemplary valve body **100d**. Upon application of gentle top down force, such as by a thumb press, the upper seal **225** of the flow control valve **185d** will readily take the correct position within the flow control valve actuator orifice **102** of the exemplary valve body **100d**, with the retention groove **229** fully engaged by the annulus **103** formed within the flow control valve actuator orifice **102**, and the circumferential shoulder **227** resting securely at the top **101** of the exemplary valve body, as shown in FIGS. **55-56**. This process for operably placing the upper seal **225** substantially within the exemplary valve body **100d** is then repeated until each of the valve bodies **100a-100j** is fitted with an upper seal **225**, as shown in FIG. **57**.

(257) As particularly illustrated in FIGS. **58-60**, a second stage of assembly of the hand-held beverage dispenser **5** according to the preferred embodiment of the present invention begins with insertion of an integral valve stem assembly **187** through the circular open end **121** at the bottom **118** of the valve body **100d**, as shown in FIG. **58**. The inserted integral valve stem assembly **187** is then manually or otherwise worked through the interior chambers of the valve body **100d** until the top end **190** of the valve stem **188** passes through and emerges from the previously inserted upper seal **225** at the top **101** of the valve body **100d**, as shown in FIG. **59**. This process is then repeated until each of the valve bodies **100a-100j** is populated with an integral valve stem assembly **187**. As illustrated in FIGS. **61-63**, the second stage of assembly of the hand-held beverage dispenser **5** then continues with placement of a poppet spring **219** followed by a fully integral selector valve trim assembly **131** through the circular open end **121** at the bottom **118** of the valve body **100d**, as

shown in FIG. 61, and firmly seating the selector valve trim assembly 131 in place, as shown in FIG. 62. This process is then repeated until each of the valve bodies 100a-100j is fully populated with a composite valve trim arrangement 91, including an integral selector valve trim assembly 131, flow control valve trim assembly 186 and a poppet spring 219, as shown in FIG. 63 illustrating the completion of stage two.

(258) At this juncture in the assembly of the valve units 90a-90j, it is emphasized that as depicted in FIG. 63 each composite valve trim arrangement 91 is only initially placed within a respective valve body 100a-100j. Much of each composite valve trim arrangement 91 is merely resting in place, and the full composite valve trim arrangement 91 for each valve unit 90a-90j must be secured operatively in place within a respective valve body 100a-100j. In the exemplary implementation of the hand-held beverage dispenser 5 of the preferred embodiment the composite valve trim arrangements 91 are all simultaneously secured in place using an inventive purpose built composite valve trim retaining member 245, as particularly shown in FIGS. 64-66.

(259) As previously noted, the composite valve trim retaining member 245 not only secures each composite valve trim arrangement 91 operably in place, but also constrains the range of movement in operation of the diluent selector valves 130a-130j. To doubly ensure clarity, it is emphasized that even with the composite valve trim retaining member 245 operably secured in place the full functionality of each of the diluent selector valves 130a-130j is accessible and freely usable. A diluent selection may be freely made notwithstanding that the hand-held beverage dispenser 5 of the preferred embodiment may be fully pressurized in fluid communication with provided beverage products and diluents. That said, however, the composite valve trim retaining member 245 is also cooperatively adapted, as more fully described herein, with the lower enclosure member 34 to implement both a failsafe ensuring a correct state for each of the diluent selector valves 130a-130j prior to normal use, and a configuration lock ensuring that no configuration of the diluent selector valves 130a-130j changes during normal use of the hand-held dispenser 5. In operation of the failsafe, the hand-held beverage dispenser 5 cannot be placed in normal use unless each diluent selector valve 130a-130j is in a proper, even if incorrect, operable configuration. Once the hand-held beverage dispenser 5 is properly configured in condition for normal use, however, the configuration lock restrains each diluent selector valve 130a-130j in the configuration selected at deployment. In the preferred exemplary implementation of the hand-held beverage dispenser 5, the failsafe acts on all of the diluent sector valves 130a-130j concurrently, and the configuration lock also acts on all of the diluent sector valves 130a-130j concurrently. Additionally, both the failsafe and the configuration lock are employed through a single otherwise required action of the user or other party responsible for configuration of the hand-held beverage dispenser 5.

(260) As partially shown in FIGS. 64-65 in particular, the specially formed novel composite valve trim retaining member 245 generally comprises a rigid plate 246 having various unitary, machined, milled, drilled or otherwise provided or formed holes, notches and other features for interoperability with the handle body 10, valve units 90a-90j and the lower enclosure member 34 for the handle body 10. The novel specially formed composite valve trim retaining member 245 primarily functions to secure each composite valve trim arrangement 91 operably in place within a corresponding one of the valve bodies 100a-100j, while nonetheless permitting operation of the diluent selector valves 100a-100j. In particular, the composite valve trim retaining member 245 allows, and provides, user access for sufficient rotation of each fully integral selector valve trim assembly 131 to enable straightforward ad hoc user selection of either the first diluent or the second diluent for each corresponding valve body 100a-100j. Although the composite valve trim retaining member 245 is cooperatively adapted with other features or aspects of the hand-held beverage dispenser 5 to implement important and inventive advancements in the relevant arts, each such implementation is fully realized without compromise of the preferred implementations of the systems, methods and articles implementing or contributing to the ad hoc diluent selection features according to the present invention.

(261) The rigid plate **246** generally implementing the preferred embodiment of the composite valve trim retaining member **245** is sized, shaped or otherwise adapted to concurrently conformingly abut with the previously described substantially planar, annular engagement surface **158** formed about the downwardly projecting cylindrical protuberance **162** at a bottom side **161** of each of the diluent selector valves **130a-130j**. To this end, a preferably arcuate notch **248** is milled, drilled or otherwise provided or formed in the rigid plate **246** for each of the diluent selector valves **130a-130j** of the hand-held beverage dispenser **5**. Each of the arcuate notches **248** is bounded by a corresponding set of adjacent edge segments **251** of the rigid plate **246**, which are specially formed of otherwise provided concomitantly with the provision of the arcuate notches **248**.

(262) Each arcuate notch **248** includes a circular end **267** that is sized, shaped or otherwise adapted to conformingly collar a portion of the downwardly projecting cylindrical protuberance **162** of the corresponding one of the diluent selector valves **130a-130j**, in the general manner of a receptacle for a trunnion. Accordingly, each of the plurality of arcuate notches **248** is arranged about the rigid plate **246** such that the circular end **267** of the notch **248** is axially aligned with a corresponding one of the valve units **90a-90j** when the composite valve trim retaining member **245** is operably in place at the bottom **31** of the handle body **10**. As particularly shown in FIG. **65**, each arcuate notch **248** may be formed as a major segment of a circle, whereby the ends **250** of the opening **249** to the arcuate notch **248**, and thus also the corresponding ends **250** of the adjacent edge segments **251**, are defined by the chord forming the arcuate notch **248**. As will be better understood further herein, a portion of each adjacent edge segment **251** at a corresponding end **250** provides an alternative one of either a first or second stop **252** for the previously described downwardly projecting stop post **160** of a corresponding selector valve trim assembly **131**.

(263) As shown and illustrated in FIGS. **64-66**, a plurality of mounting holes **253** for the composite valve trim retaining member **245** are provided as otherwise conventional thread clearing holes through the rigid plate **246**. Likewise, a corresponding plurality of otherwise conventional fasteners, such as the plurality of machine screws **254** depicted in FIGS. **66-67**, are provided for releasably engaging the previously mentioned threaded holes **32**, which are tapped, chased or otherwise formed in the bottom **31** of the handle body **10**. As shown in FIGS. **64-67**, a set of hardware pass-through holes **255**, in addition to the plurality of mounting holes **253**, are provided through the rigid plate **246** to facilitate attachment of the lower enclosure member **34**, over and about and as cooperatively adapted with the composite valve trim retaining member **245**, to the bottom **31** of the handle body **10**. Like the composite valve trim retaining member **245**, the lower enclosure member **34** is removably affixed to the bottom **31** of the handle body **10** utilizing otherwise conventional fasteners, such as the previously mentioned machine screws **44**, for releasably engaging the also previously mentioned corresponding threaded holes **33**, which are tapped, chased or otherwise formed in the bottom **31** of the handle body **10**, as all will be better understood further herein.

(264) The composite valve trim retaining member **245** also includes various indicia of alignment **257**, as particularly shown in FIG. **65**. In the exemplary implementation of the composite valve trim retaining member **245** of the preferred embodiment of the hand-held beverage dispenser **5**, the provided indicia of alignment **257** particularly include the letter C, as the end user will be instructed and understand indicates a first diluent consisting of carbonated water, and the letter W, as the end user will be instructed and understand indicates a second diluent consisting of plain water. In any case and as illustrated in FIG. **65**, the provided indicia of alignment **257** are arranged about the bottom side **256** of the rigid plate **246** of the of the composite valve trim retaining member **245**, where about each particular indicium is located in close proximity to a single one of each previously described adjacent edge segment **251** of the rigid plate **246**. As particularly shown in FIG. **65**, the indicia of alignment **257** are alternately provided such that for each set of stops **252** corresponding to a particular one of the valve units **90a-90j** one of the first and second stops **252** is identified as corresponding with the first diluent, which in this exemplary description consists of

carbonated water, and the other of the first and second stops **252** is identified as corresponding with the second diluent, which in this exemplary description consists of plain water.

(265) In any case, and as a matter of practical utility for the provided indicia of alignment **257**, each set of the provided indicia of alignment **257** corresponding to a particular one of the valve units **90a-90j** is formed, positioned and otherwise cooperatively adapted with a corresponding indicium of alignment **173** of the selector valve trim assembly **131** of the particular one of the valve units **90a-90j**. As will be better understood further herein, the end user will be instructed and understand that the previously described downwardly projecting stop post **160** of each selector valve trim assembly **131** is to be utilized as an indicium of alignment **173** of the selector valve trim assembly **131**. As also will be better understood further herein, the indicium of alignment **173** implemented by the downwardly projecting stop post **160** of each selector valve trim assembly **131** is indicative of the operable position of the previously described horizontally oriented notch **170** in the cylindrical valve gate **167** of the open-topped cup **166** of a particular one of the diluent selector valves **130a-130j**.

(266) Referring now to FIGS. **66-67** in particular, the composite valve trim retaining member **245** is operably affixed to the bottom **31** of the handle body **10** in a third stage of assembly of the handheld beverage dispenser **5**, whereby each of the initially placed composite valve trim arrangements **91**, as depicted in FIG. **63**, is secured operably in place to establish at this juncture fully functional valve units **90a-90j**. As illustrated in FIG. **66**, the composite valve trim retaining member **245** is generally affixed to the bottom **31** of handle body **10** by first placing the rigid plate **246** adjacent the initially populated handle body **10**, taking care to ensure that each of the previously described cylindrical protuberances **162** of the diluent selector valves **130a-130j** is received within a corresponding one of the arcuate notches **248** about the rigid plate **246** and axially aligned with the circular end **267** of the arcuate notch **248**, and that the top side **247** of the rigid plate **246** rests in substantially planar engagement with each of the previously described annular engagement surfaces **158** formed about the downwardly projecting cylindrical protuberances **162**. In order to achieve the correct application of the composite valve trim retaining member **245** about each selector valve trim assembly **131** according to the foregoing discussions, each selector valve trim assembly **131** must either be initially oriented in a proper selection state, or initially oriented with the previously discussed stop post **160** of the selector valve trim assembly **131** manually confined to its minor arc of travel between first and second stops **252**, as correspondingly provided by the composite valve trim retaining member **245**, and as will be better understood further herein. In any case, the provided machine screws **254** are conventionally utilized to secure the composite valve trim retaining member **245**—as correctly applied about each selector valve trim assembly **131**—to the bottom **31** of handle body **10**, as particularly shown in FIG. **67**.

(267) With the third stage of assembly completed, as illustrated in FIGS. **67** and **68A-68B**, each of the valve units **90a-90j** is in a fully functional configuration. Referring now to FIG. **68A** in particular, the exemplary valve unit **90d** is shown as configured to dispense a first diluent, which in the exemplary representation is carbonated water as indicated by the letter C. As particularly illustrated in FIG. **68A**, the downwardly projecting stop post **160** for the exemplary diluent selector valve **130d**, as implements the corresponding indicium of alignment **173** for the diluent selector valve **130d**, is positioned adjacent the one of the corresponding stops **252** most proximate to the particular corresponding indicium of alignment **257** of the composite valve trim retaining member **245** comprising the letter C. In FIG. **68B**, on the other hand, the exemplary valve unit **90d** is shown as configured to dispense a second diluent, which in the exemplary representation is plain water as indicated by the letter W. As particularly illustrated in FIG. **68B**, the downwardly projecting stop post **160** for the exemplary diluent selector valve **130d**, as implements the corresponding indicium of alignment **173** for the diluent selector valve **130d**, is positioned adjacent the other one of the corresponding stops **252**, which is in this case most proximate to the particular corresponding indicium of alignment **257** of the composite valve trim retaining member **245** comprising the letter

W.

(268) As will in light of this exemplary description be readily appreciated by those of ordinary skill in the art, the hand-held beverage dispenser **5** may be transitioned from the configuration of FIG. **68A**, which represents a first state of the diluent selector valve **130d**, to the configuration of FIG. **68B**, which represents a second state of the diluent selector valve **130d**, as well as from the second state of the diluent selector valve **130d** back to the first state of the diluent selector valve **130d**, by operation, from either depicted configuration, of the diluent selector valve **130d**. To transition from the first state, as shown in FIG. **68A**, to the second state, as shown in FIG. **68B**, an end user simply uses a standard slotted screwdriver or like implement to otherwise conventionally engage the blind slot **164**, as formed on the bottom face **163** of the cylindrical protuberance **162** of the composite valve trim arrangement **91** of the diluent selector valve **130d**, to rotate the composite valve trim arrangement **91** clockwise, as viewed in FIGS. **68A-68B**, causing the stop post **160** to swing along a minor arc beginning at the stop **252** corresponding to the first diluent, exemplified in FIG. **68A** as consisting of carbonated water, until further clockwise rotation of the composite valve trim arrangement **91** is arrested as the stop post **160** is blocked by the stop **252** corresponding to the second diluent, exemplified in FIG. **68B** as consisting of plain water. Alternatively, to transition from the second state, as shown in FIG. **68B**, to the first state, as shown in FIG. **68A**, an end user uses the standard slotted screwdriver or other selected implement, as operably engaged with the blind slot **164**, to rotate the composite valve trim arrangement **91** of the diluent selector valve **130d** counterclockwise, as viewed in FIGS. **68A-68B**, causing the stop post **160** to swing along the minor arc beginning at the stop **252** corresponding to the second diluent, exemplified in FIG. **68B** as consisting of plain water, until further counterclockwise rotation of the composite valve trim arrangement **91** is arrested as the stop post **160** is blocked by the stop **252** corresponding to the first diluent, exemplified in FIG. **68A** as consisting of carbonated water.

(269) At this juncture, it is particularly emphasized that in the stage of assembly depicted in FIGS. **68A-68B** each stop post **160**, as provided in connection with any particular diluent selector valve **130a-130j**, is limited to travel along a minor arc between adjacent stops **252** corresponding to the particular diluent selector valve **130a-130j**, whereas travel along the major arc is precluded by the presence of the rigid plate **246** of the composite valve trim retaining member **245**. Additionally, it is noted that each selector valve trim assembly **131** is cooperatively adapted with the composite valve trim retaining member **245** such that each operating state of a diluent selector valve **130a-130j** corresponds to a configuration of the diluent selector valve **130a-130j** wherein the stop post **160** of the diluent selector valve **130a-130j** is in contact with a corresponding one of the adjacent stops **252**. That said, it is again emphasized that the composite valve trim retaining member **245** not only secures each composite valve trim arrangement **91** operably in place, but also constrains the range of movement in operation of the diluent selector valves **130a-130j**. The composite valve trim retaining member **245** also facilitates user selection of a diluent by providing positive tactile indication that a proper selection state is selected as a stop post **160** rotates into contact with an adjacent stop **252**. Still further, the composite valve trim retaining member **245** additionally facilitates user selection of a diluent by providing a clear visual indication of which diluent is selected. To this point it is noted that the composite valve trim retaining member **245**, as presents the visual indications identifying alternative diluents as the implemented indicia of alignment **257**, is readily removed and replaced in order to present any chosen indicia of alignment **257**, such as may accommodate variance of provided diluents, alternative languages, a desire to utilized symbols, or any other indication providing practical utility.

(270) In order to reinforce the foregoing discussions as particularly directed toward operations of the diluent selector valves **130a-130j** relative to the composite valve trim retaining member **245**, as well as to emphasize various aspects of the cooperative adaptation of the diluent selection valves **130a-130j** and the composite valve trim retaining member **245** as particularly pertain to features of the hand-held beverage dispenser **5** discussed further herein, FIGS. **69A-69E** and corresponding

FIGS. 70A-70E illustrate the previously detailed fully integral valve trim assembly **131** of the exemplary diluent selector valve **130d** and the rigid plate **246** embodying the composite valve trim retaining member **245**. Although FIGS. 69A-69E and 70A-70E depict the fully integral valve trim assembly **131** and rigid plate **246** in isolation, the figures all show the fully integral valve trim assembly **131** and the rigid plate **246**, each one relative to the other, in a proper operable configuration—that is, where each one is positioned relative to the other as would be properly positioned in a proper operable configuration within a fully assembled hand-held beverage dispenser **5** of the preferred embodiment, as deployed for use in a ready-to-dispense configuration. Each of the views of FIGS. 69A-69E depict the fully integral valve trim assembly **131** and the rigid plate **246** in an identical proper configuration, and FIGS. 70A-70E depict the fully integral valve trim assembly **131** and the rigid plate **246** in an identical proper configuration other than the configuration depicted in FIGS. 69A-69E. In particular, the views of FIGS. 69A-69E adhere to a first valid operable state of the diluent selector valve **130d** as illustrated in FIG. 68A, wherein the exemplary valve unit **90d** is properly configured to dispense a first diluent, which for purposes of the exemplary representation is carbonated water as indicated within the indicia of alignment **257** by the letter C. The views of FIGS. 70A-70E, on the other hand, adhere to a second valid operable state of the diluent selector valve **130d** as illustrated in FIG. 68B, wherein the exemplary valve unit **90d** is properly configured to dispense a second diluent, which for purposes of the exemplary representation is plain water as indicated within the indicia of alignment **257** by the letter W. Finally, the five viewpoints illustrated in FIGS. 70A-70E correspond sequentially with the same five viewpoints illustrated in FIGS. 69A-69E.

(271) Referring now to FIGS. 69A-69E, as generally correspond to FIG. 68A, and to FIGS. 70A-70E, as generally correspond to FIG. 68B, the fully integral valve trim assembly **131** is shown as though the fully integral valve trim assembly **131** is rotatably received within the corresponding valve body **100d**, and rotatably secured operably within the valve body **100d** by the rigid plate **246** of the composite valve trim retaining member **245** as though the rigid plate **246** is affixed to the bottom **31** of the handle-body **10**. As particularly shown in FIGS. 69A-69C and 70A-70C, the previously described cylindrical protuberance **162**, as projects downwardly from the bottom side **161** of the fully integral selector valve trim assembly **131**, is axially aligned with the previously described circular end **267** of a corresponding one of the arcuate notches **248** of the rigid plate **246**, and at least a portion of the cylindrical protuberance **162** is collared by the circular end **267** of the corresponding one of the arcuate notches **248**.

(272) As illustrated in FIGS. 69B-69D and 70B-70D, neither the rotatably collared cylindrical protuberance **162** nor the previously discussed downwardly projecting stop post **160** of the fully integral selector valve trim assembly **131** projects below the rigid plate **246**. Both the rotatably collared cylindrical protuberance **162** and the downwardly projecting stop post **160**, however, project below the top side **247** of the rigid plate **246**, as also illustrated in FIGS. 69B-69D and 70B-70D. In order then for the cylindrical protuberance **162** to be properly operably received within the arcuate notch **248**, such that the top side **247** of the rigid plate **246** is in substantially flush engagement with the previously described substantially planar engagement surface **158** about the downwardly projecting cylindrical protuberance **162**, the fully integral valve trim assembly **131** must be rotationally positioned relative to the rigid plate **246** such that the stop post **160** is not radially aligned with any portion of the rigid plate **246**.

(273) With the composite valve trim retaining member **245** correctly placed about the selector valve trim assembly **131**, as particularly illustrated in FIGS. 69A-69C and 70A-70C, it is clear that the rigid plate **246** limits the position of the stop post **160** to the minor arc of travel running generally along the circular bottom rim **159** of the previously described circumferential flange **155**, as best shown in FIGS. 69A and 70A, between the two stops **252**, as defined by the previously described adjacent edge segments **251** of the rigid plate **246**, as best shown in FIGS. 69B-69C and 70B-70C. As should be understood, the composite posts valve trim retaining member **245**, as

heretofore described, only constrains the range of movement in operation of the diluent selector valves **130d**, and in particular constrains the diluent selector valves **130d** to bidirectional rotation between a first valid operable state of the diluent selector valve **130d** and a second valid operable state of the diluent selector valve **130d**.

(274) In the previously discussed first valid operable state of the diluent selector valve **130d**, corresponding to FIG. **68A** and as illustrated in FIGS. **69A-69E**, however, the downwardly projecting stop post **160** of the fully integral selector valve trim assembly **131** is positioned in contact with the stop **252** defined by the adjacent edge segments **251** of the rigid plate **246** most proximate to a first indicium of alignment **257** identifying the first diluent. For purposes of the exemplary representation, the first indicium of alignment **257** is the letter C, which is particularly shown in FIGS. **69A-69C** as applied to or otherwise provided on the bottom side **256** of the rigid plate **246**, where the first indicium of alignment **257** identifies the first diluent as carbonated water. In the previously discussed second valid operable state of the diluent selector valve **130d**, corresponding to FIG. **68B** and as illustrated in FIGS. **70A-70E**, on the other hand, the downwardly projecting stop post **160** of the fully integral selector valve trim assembly **131** is positioned in contact with the stop **252** defined by the adjacent edge segments **251** of the rigid plate **246** most proximate to a second indicium of alignment **257** identifying the second diluent. For purposes of the exemplary representation, the second indicium of alignment **257** is the letter W, which is particularly shown in FIGS. **70A-70C** as applied to or otherwise provided on the bottom side **256** of the rigid plate **246**, where the second indicium of alignment **257** identifies the second diluent as plain water.

(275) As shown in FIGS. **69C** and **70B**, and more particularly in FIG. **44**, this particular exemplary implementation contemplates a horizontally oriented notch **170** in the upper edge **169** of the cylindrical valve gate **167** substantially opposite the location about the fully integral selector valve trim assembly **131** at which is provided the downwardly projecting stop post **160**. It is noted that the downwardly projecting stop post **160** of the fully integral selector valve trim assembly **131** is indicative of the operable position of the horizontally oriented notch **170** of the cylindrical valve gate **167**, to which end it affirms a condition of state, but in and of itself says nothing about the actual location of the horizontally oriented notch **170**, or any other component. To be sure, the location about the fully integral selector valve trim assembly **131** for implementation of the downwardly projecting stop post **160** is a matter of best providing the various functionality of the stop post **160**. The location about the fully integral selector valve trim assembly **131** for implementation of the horizontally oriented notch **170** in the upper edge **169** of the cylindrical valve gate **167**, on the hand, is largely dictated by the requirements of implementing the very dense piping system **65** of the hand-held beverage dispenser **5** substantially within the extents of the handle body **10**.

(276) In the first valid operable state of the diluent selector valve **130d**, the horizontally oriented notch **170** in the upper edge **169** of the cylindrical valve gate **167**, as particularly shown in FIG. **69E**, is operably aligned with the first diluent inlet port **116** of the valve body **100d**, as particularly shown in FIG. **26**, which is in fluid communication with a first valve supply branch **72d** of the piping system **65** for conveying a first diluent to the diluent selector valve **130d**, as particularly shown in FIG. **23**. In the second valid operable state of the diluent selector valve **130d**, the horizontally oriented notch **170** in the upper edge **169** of the cylindrical valve gate **167**, as particularly shown in FIG. **70E**, is operably aligned with the second diluent inlet port **117** of the valve body **100d**, as particularly shown in FIG. **26**, which is in fluid communication with a second valve supply branch **75d** of the piping system **65** for conveying a second diluent to the diluent selector valve **130d**, as particularly shown in FIG. **23**. Selection of one or the other of the first and second valid operable states of the diluent selector valve **130d** is effected, on an ad hoc basis, by simply rotating the fully integral valve trim assembly **131** clockwise or counterclockwise, as the case may be, until further rotation is blocked by contact between the downwardly projecting stop

post **160** and the stop **252** corresponding to the newly selected valid operable state of the diluent selector valve **130d**. In the simple to operate implementation according to the preferred embodiment of the diluent selector valve **130d**, the end user can be confident that the diluent selector valve **130d** has been set to a valid operable state, and that the desired diluent will be dispensed, upon no more than simply detecting the unmistakable blocking contact.

(277) As previously noted in the overview discussions with particular reference to FIGS. 7-8, the lower enclosure member **34** of the preferably provided clamshell type housing assembly **17** not only covers and encases the lowermost portions of the composite valve trim arrangement **91** and the composite valve trim retaining member **245** during normal use of the hand-held beverage dispenser **5**, but is also specially formed or otherwise cooperatively adapted with the composite valve trim retaining member **245** to implement both a configuration lock, whereby each diluent selector valve **130a-130j** is restrained in the valid operable state for which each diluent selector valve **130a-130j** is configured at deployment, and a failsafe, whereby the hand-held beverage dispenser **5** cannot be deployed in a normal, ready-to-use condition unless each of the diluent selector valves **130a-130j** is in a proper operable configuration—that is, each of the diluent selector valves **130a-130j** is properly configured for a valid operable state, even though the particular valid operable state for any one or more of the diluent selector valves **130a-130j** may not be correct—that is, the valid operable state may not be that which the end user or other party responsible for configuration of the hand-held beverage dispenser **5** intends.

(278) Referring then to FIGS. 71-76, a preferred implementation of the lower enclosure member **34**, as may be formed as part of a clamshell type housing assembly **17** shown in FIGS. 1-3, is shown for the exemplary implementation of the hand-held beverage dispenser **5** as a single body manufacture generally comprising an aesthetically pleasing exterior, and including features for enhancing end-user experience with the hand-held beverage dispenser **5**. For example, and as particularly shown in FIGS. 71-73, portions of the exterior of the lower enclosure member **34** are provided with knurls **45** or other features for facilitating a secure grasp by a user of the handle body **10** notwithstanding the generally fast-paced, and often wet, environments in which the hand-held beverage dispenser **5** will typically be used. To be sure, end users of beverage dispensers of the bar gun class will generally expect any commercially suitable offering to include exterior features in the general nature of the knurls **45** implemented in the hand-held beverage dispenser **5** according to the preferred embodiment of the present invention. That said, the knurls **45** as implemented in the ambidextrous grip **46** for the preferred embodiment of the hand-held beverage dispenser **5** are specially formed to also implement or otherwise be compatible with inventive aspects of the lower enclosure member **34** as provided on the interior side **37** of the lower enclosure member **34**.

(279) As particularly shown in FIGS. 71 and 74-76, the interior side **37** of the lower enclosure member **34** includes a plurality of upwardly projecting locking barriers **40** at a lower portion of the interior side **37** of the lower enclosure member **34** and adjacent each of the upwardly projecting side panels **35**. As shown in the figures, each of the upwardly projecting locking barriers **40** is arcuate in form, and includes a top side **42** bounded by vertical ends **41** of the arcuate locking barrier **40**. As additionally shown in the figures, however, an intermediate portion of at least some of the locking barriers **40**, between the corresponding vertical ends **41**, may be formed as or by interiorly bulging areas **43** of the interior side **37** of the lower enclosure member **34**. As shown in FIGS. 71 and 74-76, but most particularly in FIG. 75, the interiorly bulging areas **43** are implemented through a special functional arrangement of the previously described otherwise aesthetic knurls **45**.

(280) The lower enclosure member **34** also includes features for removably attaching the lower enclosure member **34** to the bottom **31** of handle body **10**. For example, a plurality of mounting holes **39** for the lower enclosure member **34**, as particularly shown in FIGS. 72 and 76 are provided as otherwise conventional thread clearing holes through the bottom panel **36** of the lower enclosure member **34** for passage of the threaded ends of the previously described machine screws **44**

corresponding to the threaded holes **33** at the bottom **31** of handle body **10**. As also shown in FIG. **72**, the exterior end of each mounting hole **39** is most preferably countersunk as may be required to enable flush insertion of the machine screws **44** or other mounting hardware provided for the lower enclosure member **34**, thereby ensuring that a user may comfortably grasp the handle body **10**.

(281) As previously described, the lower enclosure member **34** is attached in very close conformance about the lowermost flanged base portions **150** of the open-topped vessels **133** of the enclosed diluent selector valves **130a-130j**, and is also cooperatively adapted with the composite valve trim retaining member **245** in implementation of both the previously noted failsafe and configuration lock for the diluent selector valves **130a-130j**. As will be better understood further herein, the previously described locking barriers **40**, including those portions thereof formed by the interiorly bulging areas **43** of the lower enclosure member **34**, are particularly vertically spaced with respect to the rigid plate **246** implementing the composite valve trim retaining member **245** as the lower enclosure member **34** is operably affixed to the handle body **10**. In order to maintain the required spatial relationship between the cooperatively adapted lower enclosure member **34** and the rigid plate **246**, the mounting holes **39** are provided through upwardly projecting bosses **38** formed along the interior side **37** of the bottom panel **36** and spaced or otherwise adapted to align with the corresponding hardware pass through holes **255** in the composite valve trim retaining member **245**, which in turn align with the corresponding threaded holes **33** in the bottom **31** of the handle body **10**. Additionally, however, the bosses **38** also facilitate insertion of the machine screws **44** or like mounting hardware into the distally located threaded holes **33** at the bottom **31** of the handle body **10**. For implementations where the lower enclosure member **34** is formed of plastics or like material, the provision of the bosses **38** also prevents flexing of the lower enclosure member **34** as likely to result in cracking or breaking of the lower enclosure member **34**.

(282) In a fourth stage of assembly of the hand-held beverage dispenser **5** according to the preferred embodiment of the present invention illustrated in FIGS. **77-78** the lower enclosure member **34** is removably affixed to the bottom **31** of the handle body **10**. As particularly shown in FIG. **77**, conventional fasteners, such as the previously mentioned machine screws **44**, releasably engage the corresponding threaded holes **33** in the bottom **31** of the handle body **10**. Each machine screw **44** passes through the corresponding mounting hole **39** through the bottom panel **36**, and extending through the boss **38** of the lower enclosure member **34**, and then through the corresponding hardware pass-through hole **255** in the rigid plate **246** of the composite valve trim retaining member **245**, and finally into threaded engagement with the corresponding threaded hole **33** formed in the bottom **31** of the handle body **10**, all of which are axially aligned in the assembled hand-held beverage dispenser **5**, as represented in FIG. **78**. As illustrated in FIG. **78**, the lower enclosure member **34**, composite valve trim retaining member **245** and the handle body **10** are operably attached each one to each other, including the upwardly projecting locking barriers **40** and interiorly bulging areas **43** of the interior side **37** of the lower enclosure member **34** and the corresponding features of each valve unit **90a-90j**. To remove the lower enclosure member **34**, however, as will be more fully described herein as a necessary step in the selection of a new state of operation for the diluent selector valves **130a-130j**, the machine screws **44** or other conventional hardware are removed and the lower enclosure member **34** is simply pulled away or otherwise separated from the handle body **10** of the hand-held beverage dispenser **5**.

(283) FIGS. **79-80** show the fully integral selector valve trim assembly **131** of the exemplary diluent selector valve **130d**, the rigid plate **246** implementing the composite valve trim retaining member **245**, and the lower enclosure member **34** in isolation, in the general manner of the features illustrated in FIGS. **69A-69E**, and wherein the fully integral selector valve trim assembly **131**, the rigid plate **246** and the lower enclosure member **34** are all illustrated, each one relative to each other one, in the proper operable configuration as previously described with particular reference to FIG. **68A**. FIG. **81** shows a cross-sectional view of the components, and FIGS. **82A-82B** show the cross-sectional view from other viewpoints.

(284) As shown in FIGS. **81** and **82A-82B**, the upwardly projecting locking barriers **40** and interiorly bulging areas **43** of the lower enclosure member **34** together with the stops **252** formed by the rigid plate **246** implementing the composite valve trim retaining member **245**, as operably assembled with the diluent selector valve **130d** clearly cooperate to fully restrain any rotation of the diluent selector valve **130d**. Additionally, as is particularly clear with reference to FIGS. **82A-82B**, the lower enclosure member **34** is prevented from operably engaging with and about the composite valve trim retaining member **245**, and thus the handle body **10**, in any configuration wherein the downwardly projecting stop post **160**, as carried by the diluent selector valve **130d**, is rotated into any position other than as configured in either the first operable state, as shown in FIGS. **69A-69E**, or the second operable state, as shown in FIGS. **70A-70E**.

(285) FIGS. **83A-83C** show an exemplary button cap **230** as is particularly suitable for the flow control valve **185d** of the hand-held beverage dispenser **5**. The button cap **230** is attached to the top end **190** of the cylindrical valve stem **188** of the composite valve trim arrangement **91** for the valve unit **90d**, as retained operably in place within the valve body **100d** such that the top end **190** of the valve stem **188** protrudes through the upper seal **225** for the flow control valve **185d**, as shown in FIG. **85** and more fully described herein. In the exemplary hand-held beverage dispenser **5** according to the preferred embodiment, the attached button cap **230** implements aspects of the ON-OFF flow control **20d** for manual actuation by a user of the flow control valve **185d**, as previously described.

(286) As shown in FIGS. **83A-83C**, the preferred implementations of the button cap **230** include an overhanging side **231** or, depending on the shape of the button cap **230**, overhanging sides **231**. In any case, the overhanging sides **231** are provided to operate cooperatively with the top **101** of the valve body **100d** to facilitate achieving a low profile valve control **20d**. The overhanging sides **231** also aid in preventing ingress of beverage fluids or like matter into the button cap **230**, or about the upper seal **225** for the flow control valve **185d** and the top end **190** of the valve stem **188**.

(287) As particularly shown in FIGS. **83B-83C**, a snap ring **233** for engaging the top of top end **190** of the valve stem **188** is formed within the interior space **232** of the button cap **230**, as generally bounded by the overhanging sides **231**. As shown in the figures, the implemented snap ring **233** generally comprises a pair of spaced tabs **234**, each of which includes a notch **239** in the shape of a minor arc of a circle to cooperatively form a longitudinally oriented central aperture **235** between the tabs **234**. Additionally, each of the tabs **234** has an interiorly projecting foot **236** formed about the bottom edge of the aperture **235**, which is sized, shaped or otherwise adapted to engage the keeper groove **191** provided about the top end **190** of the cylindrical valve stem **188**, as previously described and particularly shown in FIGS. **41-43**.

(288) The implemented button cap **230** also comprises a pair of oppositely disposed alignment and retention tabs **237**. As will be understood further herein, the alignment and retention tabs **237** cooperate with corresponding tab guide slots **25** formed within the upper enclosure member **22** for the handle body **10** to maintain the button cap **230** on the top end **190** of the valve stem **188**. Furthermore, the cooperatively adapted retention tabs **237** and tab guide slots **25** also keep the button cap **230** at a desired rotation about the valve stem **188**, thereby ensuring any printed matter applied to the top of the button cap **230** is properly viewable.

(289) FIGS. **84A-84C** show an alternatively shaped button cap **240**, which comprises functionally identical structure within the interior space **232** bounded by the alternatively shaped overhanging sides **241**. As shown in the figures, the alternatively shaped button cap **240** identically implements a snap ring **233** within the interior space **232** of the button cap **240**. The snap ring **232** generally comprises spaced tabs **234** forming a central aperture **235** with an interiorly projecting foot **236** adapted to engage the keeper groove **191** at the top end **190** of the valve stem **188**. Alignment and retention tabs **237** are also provided about the alternatively shaped overhanging sides **241**. Any subset of the principal button caps **230**, or particular implementation of an alternatively shaped button cap **240**, may also include a tactile feature **242** for distinguishing or further distinguishing

one or more of the button caps **230**, **240** from others. As shown in FIGS. **84A** and **84C**, such a tactile feature **242** may, for example, comprise a raised ridge or like structure.

(290) As more fully described herein, the alignment and retention tabs **237** for the alternatively shaped button caps **240** are cooperatively adapted with the tab guide slots **25** of the upper enclosure **22** for the handle body **10**, as described for the principal button cap **230**. However, the alignment and retention tabs **237** as project outwardly from alternatively shaped overhanging sides **241** need not be identically sized or shaped as compared to the principal button cap **230**. Alignment and retention tabs **237** projecting from alternatively shaped overhanging sides **241** will generally vary as required to interface with or otherwise accommodate the alternatively shaped overhanging sides **241**. That said, any particular implementation of an alternatively shaped button cap **240** is most preferably limited to shapes that do not compromise any cooperative adaptations of the button cap **240**, as described with respect to the principal button cap **230**.

(291) In a fifth stage of assembly of the hand-held beverage dispenser **5** illustrated in FIGS. **85-87**, a selected button cap **230** is attached to the top end **190** of each valve stem **188**. As shown in FIG. **85**, a button cap **230** is attached to the top end **190** of the valve stem **188** protruding from the representative valve body **100d** by simply axially aligning the central aperture **235** of the button cap **230** with the targeted valve body **100d**, and pressing the button cap **230** downward over and about the top end **190** of the valve stem **188**. Contact with the top end **190** of the valve stem **188** will cause the spaced tabs **234** of the button cap **230** to flex outward and slightly upward enabling the central aperture **235** to receive the top end **190** of the valve stem **188** as the button cap continues downward. Upon engagement of the interiorly projecting foot **236** of the button cap **230** with the keeper groove **191** about the top end **190** of the valve stem **188**, the spaced tabs **234** will snap back into position, thereby initially securing the button cap **230** in place, as shown in FIG. **86**. This process is repeated until a selected button cap **230** is applied to every flow control valve **185a-185j**, as shown in FIG. **87**. As also shown in FIG. **87**, an alternatively shaped button cap **240** is applied to flow control valves **185i-185j** of valve units **90i-90j**, which as previously described each dispense diluents only, and for which it may be desired to more prominently distinguish the corresponding subset **21** of flow controls **20i-20j**.

(292) On completion of the fifth stage of assembly of the hand-held beverage dispenser, as described with reference to FIGS. **85-87**, each flow control **20a-20j** is fully implemented in the form of an actuator button for a respective one of the plurality of fully implemented flow control valves **185a-185j**. As previously described, the exemplary implementation of each flow control **20a-20j** for a respective flow control valve **185a-185j** comprises an operable integration of a corresponding set of a button cap **230**, **240**, a valve stem **188** and a poppet spring **219**, to form an actuator button for the respective flow control valve **185a-185j**. The partially assembled hand-held beverage dispenser **5** is also ready for placement of the upper enclosure member **22**.

(293) It is noted, however, that the exemplary hand-held beverage dispenser **5** of the preferred embodiment implements a full length upper enclosure member **22** and also provides for selective removability of the mixer subassembly **276** of a utilized post-mix type drink dispenser assembly **275**. Because the exemplary preferred implementation of the latter feature requires removal of the upper enclosure member **22**, a sixth stage of assembly of the hand-held beverage dispenser **5** contemplates attachment of a mixer subassembly **276** as required or otherwise desired. As particularly shown in FIG. **88**, the mixer subassembly **276** and a rubber or like material seal **277** are attached about the previously provided connector tubes **265** and rods **266**, and then secured in place with screws **30** running through mounting holes **29** provided therefor in the handle body **10**. With the hand-held beverage dispenser **5** now assembled to the state depicted in FIG. **89**, the upper enclosure member **22** is placed about and secured to the top **18** of the handle body **10** in a seventh stage of assembly of the hand-held beverage dispenser **5**.

(294) FIGS. **90-93** show a full length implementation of the upper enclosure member **22**, as provided to enclose the top **18** of the handle body **10** of the hand-held beverage dispenser **5** and

aspects of the ON-OFF flow controls **20a-20j** at the top **18** of the handle body **10**, as shown in FIG. **93**. A pair of downwardly projecting bosses **26** are provided on the bottom side **23** of the upper enclosure member **22** to provide a desired spacing between the bottom side **23** of the upper enclosure member **22** and the top **18** of the handle body **10**, and to prevent flexing or breakage of the readily removable and replaceable upper enclosure member **23** during attachment to the handle body **10**. Mounting holes **27** for the upper enclosure member **22** are provided through the upper enclosure member **22** and into and through each provided boss **26**. As best shown in FIGS. **92-93**, the mounting holes are preferably countersunk through the upper enclosure member **22** to enable flush insertion of conventional mounting hardware for the upper enclosure member **22**, such as, for example, screws **28** or the like, thereby ensuring that a user may comfortably grasp the handle body **10**.

(295) The provided upper enclosure member **22** is also specially adapted to retain each attached button cap **230**, **240** of the ON-OFF flow controls **20a-20j** operably in place in a fixed orientation, as previously noted, and to also guide the vertical translation of the button caps **230**, **240** as the ON-OFF flow controls **20a-20j** are actuated or released. As best shown in FIGS. **90-91**, a button cap guide **24** for each implemented ON-OFF flow control **20a-20j** projects downwardly from the bottom side **23** of the upper enclosure member **22**, and is sized, shaped or otherwise adapted to allow passage of each particular button cap **230**, **240** for which the particular upper enclosure member **22** is manufactured to support. Each of the downwardly projecting button cap guides **24** includes a pair of tab guide slots **25**, which are sized, shaped and disposed about each button cap guide **24** to operatively receive the alignment and retention tabs **237** as provided about the button cap **230**, **240** for which the particular button cap guide **24** has been adapted to receive.

(296) In addition to traditional printed matter or coloring, the button caps **230**, **240** may take any number of shapes, or be provided with any number of surface treatments, such as ridges, bumps, depressions or the like, as previously noted, or any other visually, tactilely or similarly readily perceptible features consistent with maintaining the previously described desired cooperative adaptations of the button caps **230**, **240** with the upper enclosure member **22**. As such, changing one button cap **230** for another of a differing shape, or other characteristic, is a simple matter of removing the upper enclosure member **22**, removing a first button cover **230** from the valve body **100a-100j** for which the change is desired, affixing a second button cover **240** of the desired shape, and replacing the removed upper enclosure member **22** with a different upper enclosure member **22** having button cap guides **24** corresponding to the substituted button cap **240**. The convenience with which such a change may be made is of particular utility in the connection with the hand-held beverage dispenser **5** as preferably implemented according to the invention, where the on demand ability to select any available diluent for use with any valve unit **90a-90j** only increases the likelihood that a user would change the beverage product dispensed through a particular valve unit **90a-90h** which then also increases the likelihood that a user would also desire a change in shape of a button cap **230**, **240** for a particular valve unit **90a-90h**.

(297) In any case, with a button cap **230**, **240** attached to the top end **190** of each valve stem **188**, as shown in FIG. **93**, the hand-held beverage dispenser **5** is ready for placement of the upper enclosure member **22** in a seventh stage of assembly of the hand-held beverage dispenser **5**. As illustrated in FIG. **93**, the upper enclosure member is set in place on the top **18** of the handle body **10**, taking care to ensure compatibility with any utilized alternatively shaped button caps **240**, such as those provided for the subset **21** of ON-OFF flow controls **20i-20j** implemented for actuating the flow control valves **185i-185j** of the valve units **90i-90j** configured to dispense a diluent only. The downwardly projecting button cap guides **24** at the bottom side **23** of the upper enclosure member **22** conformingly receive each button cap **230**, **240**. As each button cap **230**, **240** is received within a corresponding button cap guide **24**, the tab guide slots **25** disposed about the button cap guide **24** also capture the alignment and retention tabs **237** provided on the received button cap **230**, **240**. The upper enclosure member **22** is then conventionally attached to the top **18** of the handle body **10**

by inserting the provided screws **28** through the mounting holes **27** and bosses **26** the upper enclosure member **22** and engaging the corresponding threaded holes **19** provided at the top **10** of the handle body **10**, as shown in FIGS. **93** and **94A**. On completion of the seventh stage of assembly of the hand-held beverage dispenser **5**, as shown in FIGS. **94A-94B**, the hand-held beverage dispenser **5** is fully assembled and ready for use.

(298) If at any time in preparation for use or during deployment in use of the hand-held beverage dispenser **5** a then desired diluent is not already selected for use in connection with a particular ON-OFF flow control **20a-20j**, a user or other party responsible for configuration of the hand-held beverage dispenser **5** may quickly and easily make the desired selection. What is more, the selection of a diluent may be made wherever the hand-held beverage dispenser **5** is found and without regard for the state of use in which it is found. To doubly ensure clarity, a selection of state for any diluent selector valve **130a-130j** can be made at the location of a hand-held beverage dispenser **5** that is otherwise fully deployed in use, after which the hand-held beverage dispenser **5** can be returned to full service without priming, pressurization or any other preparatory action.

(299) To make a new diluent selection in use of the hand-held beverage dispenser **5** for the beverage corresponding to the exemplary ON-OFF flow control **20d** a user first removes the lower enclosure member **34** to expose the bottom **31** of the handle body **10**, as previously described in detail with reference to FIGS. **77-78**. In removing the lower enclosure member **34**, the user gains access to the bottom side **161** of the closed bottom **151** of the open-topped cup **166** of the diluent selector valve **130d** of the valve unit **90d**, as particularly shown in FIGS. **68A-68B** with the composite valve trim retaining member **245** operably secured in place. As is well understood in light of the foregoing detailed disclosures, diluent selector valve **130d** corresponds to ON-OFF flow control **20d**. The user, however, will generally have little if any knowledge of the internal arrangements of the hand-held beverage dispenser **5**, but is instructed that the correct user interface for selection of one diluent or the other is located at the bottom **31** of the handle-body **10**, and directly aligned below and with the ON-OFF flow control **20d** of interest. Having thus identified the bottom side **161** of the exemplary diluent selector valve **130d** as that of interest, the user utilizes the downwardly projecting stop post **160** provided along the chamfered bottom rim **159** as a readily visually perceptible indicium of alignment **173** for the open-topped cup **166** in conjunction with the particular adjacent indicia of alignment **257** on the bottom side **256** of the composite valve trim retaining member **245** to easily determine the diluent selection for the beverage product of interest corresponding to the ON-OFF flow control **20d**.

(300) In particular, the user will generally identify the desired diluent by reference to the particular indicia of alignment **257** on the bottom side **256** of the composite valve trim retaining member **245** about the diluent selector valve **130d** of interest. For example, in the exemplary implementation the letter W indicates plain water, and the letter C indicates carbonated water. As previously described, the radial orientation of the open-topped cup **166**, and thus the horizontally oriented notch **170** of the open-topped cup **166**, determines whether the first diluent or the second diluent may flow into the valve unit **90d** of interest. In the exemplary implementation of the hand-held beverage dispenser **5** according to the preferred embodiment, the open-topped cup **166** may take a first operable state in the radial orientation as shown in FIGS. **69A-69E**, or a second operable state in the radial orientation as shown in FIGS. **70A-70E**.

(301) In the first operable state the downwardly projecting stop post **160** utilized as the indicium of alignment **173** for the open-topped cup **166** abuts a stop **252** defined by a first one of the two adjacent edge segments **251** of the composite valve trim retaining member **245**. As illustrated in FIGS. **69A-69E**, the downwardly projecting stop post **160** abuts a stop **252** directly adjacent a first one of the particular indicia of alignment **257** on the bottom side of the composite valve trim retaining member **245**. As clearly illustrated in FIG. **68A** corresponding to the first operable state, the user will readily identify and understand that for the ON-OFF flow control **20d** of interest the hand-held beverage dispenser **5** of the present invention is configured in FIG. **68A** to dispense

carbonated water as a first diluent.

(302) In the second operable state the downwardly projecting stop post **160** utilized as the indicium of alignment **173** for the open-topped cup **166** abuts a stop **252** defined by a second one of the two adjacent edge segments **251** of the composite valve trim retaining member **245**. As illustrated in FIGS. **70A-70E**, the downwardly projecting stop post **160** abuts a stop **252** directly adjacent a second one of the particular indicia of alignment **257** on the bottom side of the composite valve trim retaining member **245**. As clearly illustrated in FIG. **68B** corresponding to the second operable state, the user will readily identify and understand that for the ON-OFF flow control **20d** of interest the hand-held beverage dispenser **5** of the present invention is configured in FIG. **68B** to dispense plain water as a second diluent.

(303) Able to readily and reliably identify the correct proper location for the downwardly projecting stop post **160**, the user makes use of a standard slotted screwdriver or like implement to engage the blind slot **164** at the bottom side **161** of the open-topped cup **166** to effect a desired radial orientation of the open-topped cup **166**, as previously described in detail. Having made the desired diluent selection, the user replaces the lower enclosure member **34**, as previously described in detail. As also previously described in detail, the inventive failsafe as provided according to the preferred embodiment is fully functional within act of operably placing the lower enclosure member **34** without more. Accordingly, the user simply will not be able to replace the lower enclosure member **34** unless every diluent selector valve **130a-130j** is at least in a proper operable configuration. With the lower enclosure member **34** operably in place over and about the properly configured diluent selector valves **130a-130j** and before returning the hand-held beverage dispenser **5** to service, the user secures the replaced lower enclosure member **34** to the handle body **10** with, for example, the provided machine screws **44**, as previously described in detail. In the act of securing the lower enclosure member **34** to the handle body **10**, the inventive configuration lock according to the preferred embodiment is also fully functional without more.

(304) FIGS. **95A-95E**, **96A-96E**, **97A-97E** and **98A-98E**, and various other figures as will be identified where they are found to be particularly instructive, illustrate the four major exemplary states of operation of the representative valve unit **90d**, each of which is now described. In particular the following discussions will describe in detail various flow paths through the valve unit **90d**; fluid flows within or relating to the valve unit **90d**; relationships between the components of the valve unit **90d** and other components of the piping system **65** specifically and/or the hand-held beverage dispenser **5** or even external components generally; and user interactions with the valve unit **90d**. FIGS. **95A-95E** illustrate a first state of operation of the integrated valve unit **90d** as configured to utilize the first diluent while the ON-OFF flow control **20d** is not actuated. **96A-96E** illustrate a second state of operation of the integrated valve unit **90d** as configured to utilize the first diluent while the ON-OFF flow control **20d** is actuated. FIGS. **97A-97E** illustrate a third state of operation of the integrated valve unit **90d** as configured to utilize the second diluent while the ON-OFF flow control **20d** is not actuated. FIGS. **98A-98E** illustrate a fourth state of operation of the integrated valve unit **90d** as configured to utilize the second diluent while the ON-OFF flow control **20d** is actuated.

(305) In the first state of operation of the integrated valve unit **90d** as implemented in FIGS. **95A-95E**, the diluent selector valve **130d** is configured to select a first diluent, of a type known to a user, for use in dispensing a beverage product associated by the user with the representative ON-OFF flow control **20d**. Although not necessarily known to the user, the user-selected diluent is supplied under pressure to the hand-held beverage dispenser **5** through the first diluent inlet **67** at the rear end **52** of the handle body **10**. As also not necessarily known to the user, the representative ON-OFF flow control **20d** establishes the state of the representative flow control valve **185d** of valve unit **90d**. As illustrated in the figures, the ON-OFF flow control **20d** is not actuated or otherwise operated in the first state of operation of the integrated valve unit **90d**, and thus, although not necessarily known to the user, the normally closed flow control valve **185d** is not actuated, and

therefore closed. Accordingly, beverage fluids, including a beverage product supplied under pressure to the hand-held beverage dispenser **5** through beverage product inlet **69d** at the rear end **52** of the handle body **10**, will not pass through the valve body **100d** of the valve unit **90d** or otherwise be dispensed from the hand-held beverage dispenser **5**.

(306) Selecting the first diluent for dispensing a beverage from the hand-held beverage dispenser **5** with ON-OFF flow control **20d** causes the horizontally oriented notch **170** through the upper edge **169** of the cylindrical valve gate **167** of the open-topped cup **166** of the diluent selector valve **130d** to operably align with the first diluent inlet port **116** of the valve body **100d**, as particularly shown in FIG. **95B**. As shown in FIGS. **95B** and **95E**, alignment in this first operable state of the diluent selector valve **130d** creates an open flow path through the diluent selector valve **130d** allowing the first diluent to flow from supply branch **72d**, through the first diluent inlet port **116** of the valve body **100d** and into the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**. Simultaneously, however, selection of the first diluent also causes an intact portion of the cylindrical valve gate **167** of the open-topped cup **166** of the diluent selector valve **130d** to operably align with the second diluent inlet port **117** of the valve body **100d**, as also particularly shown in FIG. **95B**, which creates a flow blocking gate within the diluent selector valve **130d**. Thus, in the first operable state of the diluent selector valve **130d**, as is selected according to the second state of operation of the integrated valve unit **90d**, flow of the second diluent from supply branch **75d** is prevented by the diluent selector valve **130d** from being introduced into the cylindrical chamber **139**, as shown in FIGS. **95B** and **95E**.

(307) In the previously defined first state of operation of the integrated valve unit **90d**, a beverage product may be supplied under pressure from any suitable flow control assembly in fluid communication with the beverage product inlet **69d** at the rear end **52** of the handle body **10**. Through priming or prior use of the hand-held beverage dispenser **5**, a supplied beverage product is conveyed through the dedicated beverage product supply conduit **76d** between the beverage product inlet **69d** and the beverage product inlet port **108** of the valve body **100d** and introduced through the beverage product inlet port **108** to the intermediate chamber **106** of the valve body **100d**. As particularly shown in FIGS. **26**, **28** and **96D**, the beverage product inlet port **108** introduces the beverage product into the intermediate chamber **106** upstream of the upper valve seat **109** for the flow control valve **185d**.

(308) As particularly shown in FIG. **95D**, the flow control valve **185d** is implemented as a coupled set of normally closed poppet-type valves, where an upper one of the poppet-type valves controls flow through the valve body **100d** of a beverage product. In the at rest normally closed state of the flow control valve **185d**, the poppet spring **219** at the bottom end **203** of the valve stem **188** applies an upward biasing force to the valve stem **188**. The upward biasing force produced by the poppet spring **219**, as may be joined by any additional upward forces produced by pressurized beverage fluids within the valve body **100d**, holds the valve stem **188** of the flow control valve **185d** in the uppermost position for the valve stem **188** within the valve body **100d**. Accordingly, the upper reciprocating sealing member **205** carried by the valve stem **188** is also at an uppermost position within the valve body **100d**, whereat the valve face **209** formed at the top surface **208** of the upper reciprocating sealing member **205** is sealingly engaged with the corresponding upper valve seat **109** provided within the valve body **100d** for the at rest flow control valve **185d**. At rest in this normally closed state of the flow control valve **185d**, the flow control valve **185d** prevents passage of beverage product from the intermediate chamber **106** to the upper chamber **104** of the valve body **100d**.

(309) Because in the defined first state of operation of the integrated valve unit **90d** the ON-OFF flow control **20d** is not actuated or otherwise operated, no sufficient downward force is applied to the valve stem **188** to overcome the upward biasing force applied to the bottom end **203** of the valve stem **188** by the provided poppet spring **219**, and any additional upwardly applied fluid forces within the valve body **100d**, to shift the valve stem **188**, and thus the upper reciprocating

sealing member **205** carried by the valve stem **188**, downward within the valve body **100d**.

Accordingly, the valve face **209** formed at the top surface **208** of the upper reciprocating sealing member **205** remains sealingly engaged with the corresponding upper valve seat **109** provided within the valve body **100d** for the at rest flow control valve **185d**. Still at rest in the normally closed state of the flow control valve **185d**, the flow control valve **185d** continues to prevent passage of beverage product from the intermediate chamber **106** to the upper chamber **104** of the valve body **100d**.

(310) Concurrently with the supply of a beverage product to the valve body **100d**, a first diluent may be supplied under pressure from any suitable flow control assembly in fluid communication with the first diluent inlet **67** at the rear end **52** of the handle body **10**, as previously described. Through priming or prior use of the hand-held beverage dispenser **5**, a supplied first diluent is conveyed through the common trunk **71** of the first diluent inlet manifold **70** and a dedicated valve supply branch **72d** from the common trunk **71** between the first diluent inlet **67** and the first diluent inlet port **116** of the valve body **100d**. Because in the defined first state of operation of the integrated valve unit **90d** the diluent selector valve **130d** is configured in a first operable state to select the first diluent, the diluent selector valve **130d** establishes an open flow path through the diluent selector valve **130d** between the first diluent inlet port **116** and the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**. Accordingly, the first diluent is further conveyed from the first diluent inlet port **116** of the valve body **100d** and into the cylindrical chamber **139** of the open-topped cup **166**. As particularly shown in FIGS. **26-27** and **95A-95B**, the cooperatively adapted first diluent inlet port **116** and diluent selector valve **130d** introduce the first diluent into the cylindrical chamber **139** upstream of the lower valve seat **115** for the flow control valve **185d**. Simultaneously, an intact portion of the cylindrical valve gate **167** of the open-topped cup **166** sealingly obstructs the second diluent inlet port **117** of the valve body **100d**, as particularly shown in FIG. **95B**. Accordingly, the diluent selector valve **130d** in the first operable state thereof prevents introduction to the cylindrical chamber **139** of any fluid flowing to or through the second inlet port **117**.

(311) A lower one of the poppet-type valves provided in implementation of the flow control valve **185d** controls flow through the valve body **100d** of a diluent, as particularly shown in FIG. **95D**. In the at rest normally closed state of the flow control valve **185d**, the poppet spring **219** at the bottom end **203** of the valve stem **188** applies an upward biasing force to the valve stem **188**. The upward biasing force produced by the poppet spring **219**, as may be joined by any additional upward forces produced by pressurized beverage fluids within the valve body **100d**, holds the valve stem **188** of the flow control valve **185d** in the uppermost position for the valve stem **188** within the valve body **100d**. Accordingly, the lower reciprocating sealing member **213** carried by the valve stem **188** is also at an uppermost position within the valve body **100d**, whereat the valve face **217** formed at the top surface **216** of the lower reciprocating sealing member **213** is sealingly engaged with the corresponding lower valve seat **115** provided within the valve body **100d** for the at rest flow control valve **185d**. At rest in this normally closed state of the flow control valve **185d**, the flow control valve **185d** prevents passage of diluent from the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**, to the intermediate chamber **106** of the valve body **100d**.

(312) Because in the defined first state of operation of the integrated valve unit **90d** the ON-OFF flow control **20d** is not actuated or otherwise operated, no sufficient downward force is applied to the valve stem **188** to overcome the upward biasing force applied to the bottom end **203** of the valve stem **188** by the provided poppet spring **219**, and any additional upwardly applied fluid forces within the valve body **100d**, to shift the valve stem **188**, and thus the lower reciprocating sealing member **213** carried by the valve stem **188**, downward within the valve body **100d**.

Accordingly, the valve face **217** formed at the top surface **216** of the lower reciprocating sealing member **213** remains sealingly engaged with the corresponding lower valve seat **115** provided

within the valve body **100d** for the at rest flow control valve **185d**. Still at rest in the normally closed state of the flow control valve **185d**, the flow control valve **185d** continues to prevent passage of diluent from the cylindrical chamber **139** of the open-topped cup **166** to the intermediate chamber **106** of the valve body **100d**.

(313) In the second state of operation of the integrated valve unit **90d** as implemented in FIGS. **96A-96E**, the diluent selector valve **130d** is configured to select a first diluent, of a type known to a user, for use in dispensing a beverage product associated by the user with the representative ON-OFF flow control **20d**. Although not necessarily known to the user, the user-selected diluent is supplied under pressure to the hand-held beverage dispenser **5** through the first diluent inlet **67** at the rear end **52** of the handle body **10**. As also not necessarily known to the user, the representative ON-OFF flow control **20d** establishes the state of the representative flow control valve **185d** of valve unit **90d**. As illustrated in the figures, the ON-OFF flow control **20d** is actuated or otherwise operated in the second state of operation of the integrated valve unit **90d**, and thus, although not necessarily known to the user, the normally closed flow control valve **185d** is actuated, and therefore open. Accordingly, beverage fluids, including a beverage product supplied under pressure to the hand-held beverage dispenser **5** through beverage product inlet **69d** at the rear end **52** of the handle body **10**, pass through the valve body **100d** of the valve unit **90d** to be mixed together and dispensed from the hand-held beverage dispenser **5**.

(314) Selecting the first diluent for dispensing a beverage from the hand-held beverage dispenser **5** with ON-OFF flow control **20d** causes the horizontally oriented notch **170** through the upper edge **169** of the cylindrical valve gate **167** of the open-topped cup **166** of the diluent selector valve **130d** to operably align with the first diluent inlet port **116** of the valve body **100d**, as particularly shown in FIG. **96B**. As shown in FIGS. **96B** and **96E**, alignment in this first operable state of the diluent selector valve **130d** creates an open flow path through the diluent selector valve **130d** allowing the first diluent to flow from supply branch **72d**, through the first diluent inlet port **116** of the valve body **100d** and into the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**. Simultaneously, however, selection of the first diluent also causes an intact portion of the cylindrical valve gate **167** of the open-topped cup **166** of the diluent selector valve **130d** to operably align with the second diluent inlet port **117** of the valve body **100d**, as also particularly shown in FIG. **96B**, which creates a flow blocking gate within the diluent selector valve **130d**. Thus, in the first operable state of the diluent selector valve **130d**, as is selected according to the second state of operation of the integrated valve unit **90d**, flow of the second diluent from supply branch **75d** is prevented by the diluent selector valve **130d** from being introduced into the cylindrical chamber **139**, as shown in FIGS. **96B** and **96E**.

(315) In the previously defined second state of operation of the integrated valve unit **90d**, a beverage product may be supplied under pressure from any suitable flow control assembly in fluid communication with the beverage product inlet **69d** at the rear end **52** of the handle body **10**. Through priming or prior use of the hand-held beverage dispenser **5**, a supplied beverage product is conveyed through the dedicated beverage product supply conduit **76d** between the beverage product inlet **69d** and the beverage product inlet port **108** of the valve body **100d** and introduced through the beverage product inlet port **108** to the intermediate chamber **106** of the valve body **100d**. As particularly shown in FIGS. **26**, **28** and **96D**, the beverage product inlet port **108** introduces the beverage product into the intermediate chamber **106** upstream of the upper valve seat **109** for the flow control valve **185d**.

(316) As particularly shown in FIG. **96D**, the flow control valve **185d** is implemented as a coupled set of normally closed poppet-type valves, where an upper one of the poppet-type valves controls flow through the valve body **100d** of a beverage product. In the at rest normally closed state of the flow control valve **185d**, the poppet spring **219** at the bottom end **203** of the valve stem **188** applies an upward biasing force to the valve stem **188**. The upward biasing force produced by the poppet spring **219**, as may be joined by any additional upward forces produced by pressurized beverage

fluids within the valve body **100d**, holds the valve stem **188** of the flow control valve **185d** in the uppermost position for the valve stem **188** within the valve body **100d**. Accordingly, the upper reciprocating sealing member **205** carried by the valve stem **188** is also at an uppermost position within the valve body **100d**, whereat the valve face **209** formed at the top surface **208** of the upper reciprocating sealing member **205** is sealingly engaged with the corresponding upper valve seat **109** provided within the valve body **100d** for the at rest flow control valve **185d**. At rest in this normally closed state of the flow control valve **185d**, the flow control valve **185d** prevents passage of beverage product from the intermediate chamber **106** to the upper chamber **104** of the valve body **100d**.

(317) Because in the defined second state of operation of the integrated valve unit **90d** the ON-OFF flow control **20d** is actuated or otherwise operated, a sufficient downward force applied to the valve stem **188** overcomes the upward biasing force applied to the bottom end **203** of the valve stem **188** by the provided poppet spring **219**, and any additional upwardly applied fluid forces within the valve body **100d**, to shift the valve stem **188**, and thus the upper reciprocating sealing member **205** carried by the valve stem **188**, downward within the valve body **100d**, as shown in FIGS. **96A** and **96D**. As the valve stem **188** and thus the upper reciprocating sealing member **205** shift downward, flow from the intermediate chamber **106** to the upper chamber **104** of the valve body **100d** is immediately enabled, whereby beverage product immediately flows from the intermediate chamber **106** to the upper chamber **104**. As the valve stem **188** and the upper reciprocating sealing member **205** continue to shift the short distance downward to reach maximum displacement, as shown in FIGS. **96A** and **96D**, the flow of beverage product quickly reaches maximum rate. In any case, the beverage product flowing into the upper chamber **104** passes unobstructed from the upper chamber **104** through the beverage product outlet port **105** of the valve body **100d**, and is conveyed through the dedicated beverage dispensing conduit **80d** between the beverage product outlet port **105** and the beverage product outlet **83d** at the bottom **31** and adjacent the forward end **48** of the handle body **10**. The beverage product is then there conducted into and through the post-mix type drink dispenser assembly **275**, where, in accordance with the second state of operation of the integrated valve unit **90d**, the beverage product is mixed together with the user-selected first diluent as they are dispensed together into a beverage vessel, in a manner well known to those of ordinary skill in the relevant arts.

(318) Concurrently with the supply of a beverage product to the valve body **100d**, a first diluent may be supplied under pressure from any suitable flow control assembly in fluid communication with the first diluent inlet **67** at the rear end **52** of the handle body **10**, as previously described. Through priming or prior use of the hand-held beverage dispenser **5**, a supplied first diluent is conveyed through the common trunk **71** of the first diluent inlet manifold **70** and a dedicated valve supply branch **72d** from the common trunk **71** between the first diluent inlet **67** and the first diluent inlet port **116** of the valve body **100d**. Because in the defined second state of operation of the integrated valve unit **90d** the diluent selector valve **130d** is configured in a first operable state to select the first diluent, the diluent selector valve **130d** establishes an open flow path through the diluent selector valve **130d** between the first diluent inlet port **116** and the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**. Accordingly, the first diluent is further conveyed from the first diluent inlet port **116** of the valve body **100d** and into the cylindrical chamber **139** of the open-topped cup **166**. As particularly shown in FIGS. **26-27** and **96A-96B**, the cooperatively adapted first diluent inlet port **116** and diluent selector valve **130d** introduce the first diluent into the cylindrical chamber **139** upstream of the lower valve seat **115** for the flow control valve **185d**. Simultaneously, an intact portion of the cylindrical valve gate **167** of the open-topped cup **166** sealingly obstructs the second diluent inlet port **117** of the valve body **100d**, as particularly shown in FIG. **96B**. Accordingly, the diluent selector valve **130d** in the first operable state thereof prevents introduction to the cylindrical chamber **139** of any fluid flowing to or through the second inlet port **117**.

(319) A lower one of the poppet-type valves provided in implementation of the flow control valve **185d** controls flow through the valve body **100d** of a diluent, as particularly shown in FIG. **96D**. In the at rest normally closed state of the flow control valve **185d**, the poppet spring **219** at the bottom end **203** of the valve stem **188** applies an upward biasing force to the valve stem **188**. The upward biasing force produced by the poppet spring **219**, as may be joined by any additional upward forces produced by pressurized beverage fluids within the valve body **100d**, holds the valve stem **188** of the flow control valve **185d** in the uppermost position for the valve stem **188** within the valve body **100d**. Accordingly, the lower reciprocating sealing member **213** carried by the valve stem **188** is also at an uppermost position within the valve body **100d**, whereat the valve face **217** formed at the top surface **216** of the lower reciprocating sealing member **213** is sealingly engaged with the corresponding lower valve seat **115** provided within the valve body **100d** for the at rest flow control valve **185d**. At rest in this normally closed state of the flow control valve **185d**, the flow control valve **185d** prevents passage of diluent from the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**, to the intermediate chamber **106** of the valve body **100d**.

(320) Because in the defined second state of operation of the integrated valve unit **90d** the ON-OFF flow control **20d** is actuated or otherwise operated, a sufficient downward force applied to the valve stem **188** overcomes the upward biasing force applied to the bottom end **203** of the valve stem **188** by the provided poppet spring **219**, and any additional upwardly applied fluid forces within the valve body **100d**, to shift the valve stem **188**, and thus the lower reciprocating sealing member **213** carried by the valve stem **188**, downward within the valve body **100d**, as shown in FIGS. **96A** and **96D**. As the valve stem **188** and thus the lower reciprocating sealing member **213** shift downward, flow from the cylindrical chamber **139** of the open-topped cup **166** to the intermediate chamber of the valve body **100d** is immediately enabled, whereby the first diluent immediately flows from the cylindrical chamber **139** to the intermediate chamber **106**. As the valve stem **188** and the lower reciprocating sealing member **213** continue to shift the short distance downward to reach maximum displacement, as shown in FIGS. **96A** and **96D**, the flow of the first diluent quickly reaches maximum rate. In any case, the first diluent flowing into the intermediate chamber **106** passes unobstructed from the intermediate chamber **106** through the diluent outlet port **110** of the valve body **100d**, and is conveyed through the dedicated valve dispense branch **79d** to the common trunk **78** and the common trunk **78** of the common diluents outlet manifold **77** between the diluent outlet port **110** and the single common diluents outlet **82** at the bottom **31** and adjacent the forward end **48** of the handle body **10**. The first diluent is then there conducted into and through the post-mix type drink dispenser assembly **275**, where the user-selected first diluent is mixed together with the beverage product as they are dispensed together into a beverage vessel, in a manner well known to those of ordinary skill in the relevant arts.

(321) In the third state of operation of the integrated valve unit **90d** as implemented in FIGS. **97A-97E**, the diluent selector valve **130d** is configured to select a second diluent, of a type known to a user, for use in dispensing a beverage product associated by the user with the representative ON-OFF flow control **20d**. Although not necessarily known to the user, the user-selected diluent is supplied under pressure to the hand-held beverage dispenser **5** through the second diluent inlet **68** at the rear end **52** of the handle body **10**. As also not necessarily known to the user, the representative ON-OFF flow control **20d** establishes the state of the representative flow control valve **185d** of valve unit **90d**. As illustrated in the figures, the ON-OFF flow control **20d** is not actuated or otherwise operated in the third state of operation of the integrated valve unit **90d**, and thus, although not necessarily known to the user, the normally closed flow control valve **185d** is not actuated, and therefore closed. Accordingly, beverage fluids, including a beverage product supplied under pressure to the hand-held beverage dispenser **5** through beverage product inlet **69d** at the rear end **52** of the handle body **10**, will not pass through the valve body **100d** of the valve unit **90d** or otherwise be dispensed from the hand-held beverage dispenser **5**.

(322) Selecting the second diluent for dispensing a beverage from the hand-held beverage dispenser 5 with ON-OFF flow control 20d causes the horizontally oriented notch 170 through the upper edge 169 of the cylindrical valve gate 167 of the open-topped cup 166 of the diluent selector valve 130d to operably align with the second diluent inlet port 117 of the valve body 100d, as particularly shown in FIG. 97B. As shown in FIGS. 97B and 97E, alignment in this second operable state of the diluent selector valve 130d creates an open flow path through the diluent selector valve 130d allowing the second diluent to flow from supply branch 75d, through the second diluent inlet port 117 of the valve body 100d and into the cylindrical chamber 139 of the open-topped cup 166, as operably received within the lower chamber 111 of the valve body 100d. Simultaneously, however, selection of the second diluent also causes an intact portion of the cylindrical valve gate 167 of the open-topped cup 166 of the diluent selector valve 130d to operably align with the first diluent inlet port 116 of the valve body 100d, as also particularly shown in FIG. 97B, which creates a flow blocking gate within the diluent selector valve 130d. Thus, in the second operable state of the diluent selector valve 130d, as is selected according to the third state of operation of the integrated valve unit 90d, flow of the first diluent from supply branch 72d is prevented by the diluent selector valve 130d from being introduced into the cylindrical chamber 139, as shown in FIGS. 97B and 97E.

(323) In the previously defined third state of operation of the integrated valve unit 90d, a beverage product may be supplied under pressure from any suitable flow control assembly in fluid communication with the beverage product inlet 69d at the rear end 52 of the handle body 10. Through priming or prior use of the hand-held beverage dispenser 5, a supplied beverage product is conveyed through the dedicated beverage product supply conduit 76d between the beverage product inlet 69d and the beverage product inlet port 108 of the valve body 100d and introduced through the beverage product inlet port 108 to the intermediate chamber 106 of the valve body 100d. As particularly shown in FIGS. 26, 28 and 97D, the beverage product inlet port 108 introduces the beverage product into the intermediate chamber 106 upstream of the upper valve seat 109 for the flow control valve 185d.

(324) As particularly shown in FIG. 96D, the flow control valve 185d is implemented as a coupled set of normally closed poppet-type valves, where an upper one of the poppet-type valves controls flow through the valve body 100d of a beverage product. In the at rest normally closed state of the flow control valve 185d, the poppet spring 219 at the bottom end 203 of the valve stem 188 applies an upward biasing force to the valve stem 188. The upward biasing force produced by the poppet spring 219, as may be joined by any additional upward forces produced by pressurized beverage fluids within the valve body 100d, holds the valve stem 188 of the flow control valve 185d in the uppermost position for the valve stem 188 within the valve body 100d. Accordingly, the upper reciprocating sealing member 205 carried by the valve stem 188 is also at an uppermost position within the valve body 100d, whereat the valve face 209 formed at the top surface 208 of the upper reciprocating sealing member 205 is sealingly engaged with the corresponding upper valve seat 109 provided within the valve body 100d for the at rest flow control valve 185d. At rest in this normally closed state of the flow control valve 185d, the flow control valve 185d prevents passage of beverage product from the intermediate chamber 106 to the upper chamber 104 of the valve body 100d.

(325) Because in the defined third state of operation of the integrated valve unit 90d the ON-OFF flow control 20d is not actuated or otherwise operated, no sufficient downward force is applied to the valve stem 188 to overcome the upward biasing force applied to the bottom end 203 of the valve stem 188 by the provided poppet spring 219, and any additional upwardly applied fluid forces within the valve body 100d, to shift the valve stem 188, and thus the upper reciprocating sealing member 205 carried by the valve stem 188, downward within the valve body 100d. Accordingly, the valve face 209 formed at the top surface 208 of the upper reciprocating sealing member 205 remains sealingly engaged with the corresponding upper valve seat 109 provided

within the valve body **100d** for the at rest flow control valve **185d**. Still at rest in the normally closed state of the flow control valve **185d**, the flow control valve **185d** continues to prevent passage of beverage product from the intermediate chamber **106** to the upper chamber **104** of the valve body **100d**.

(326) Concurrently with the supply of a beverage product to the valve body **100d**, a second diluent may be supplied under pressure from any suitable flow control assembly in fluid communication with the second diluent inlet **68** at the rear end **52** of the handle body **10**, as previously described. Through priming or prior use of the hand-held beverage dispenser **5**, a supplied second diluent is conveyed through the common trunk **74** of the second diluent inlet manifold **73** and a dedicated valve supply branch **75d** from the common trunk **74** between the second diluent inlet **68** and the second diluent inlet port **117** of the valve body **100d**. Because in the defined third state of operation of the integrated valve unit **90d** the diluent selector valve **130d** is configured in a second operable state to select the second diluent, the diluent selector valve **130d** establishes an open flow path through the diluent selector valve **130d** between the second diluent inlet port **117** and the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**. Accordingly, the second diluent is further conveyed from the second diluent inlet port **117** of the valve body **100d** and into the cylindrical chamber **139** of the open-topped cup **166**. As particularly shown in FIGS. **26**, **28** and **97A-97B**, the cooperatively adapted second diluent inlet port **117** and diluent selector valve **130d** introduce the second diluent into the cylindrical chamber **139** upstream of the lower valve seat **115** for the flow control valve **185d**. Simultaneously, an intact portion of the cylindrical valve gate **167** of the open-topped cup **166** sealingly obstructs the first diluent inlet port **116** of the valve body **100d**, as particularly shown in FIG. **97B**. Accordingly, the diluent selector valve **130d** in the third operable state thereof prevents introduction to the cylindrical chamber **139** of any fluid flowing to or through the first inlet port **116**.

(327) A lower one of the poppet-type valves provided in implementation of the flow control valve **185d** controls flow through the valve body **100d** of a diluent, as particularly shown in FIG. **97D**. In the at rest normally closed state of the flow control valve **185d**, the poppet spring **219** at the bottom end **203** of the valve stem **188** applies an upward biasing force to the valve stem **188**. The upward biasing force produced by the poppet spring **219**, as may be joined by any additional upward forces produced by pressurized beverage fluids within the valve body **100d**, holds the valve stem **188** of the flow control valve **185d** in the uppermost position for the valve stem **188** within the valve body **100d**. Accordingly, the lower reciprocating sealing member **213** carried by the valve stem **188** is also at an uppermost position within the valve body **100d**, whereat the valve face **217** formed at the top surface **216** of the lower reciprocating sealing member **213** is sealingly engaged with the corresponding lower valve seat **115** provided within the valve body **100d** for the at rest flow control valve **185d**. At rest in this normally closed state of the flow control valve **185d**, the flow control valve **185d** prevents passage of diluent from the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**, to the intermediate chamber **106** of the valve body **100d**.

(328) Because in the defined third state of operation of the integrated valve unit **90d** the ON-OFF flow control **20d** is not actuated or otherwise operated, no sufficient downward force is applied to the valve stem **188** to overcome the upward biasing force applied to the bottom end **203** of the valve stem **188** by the provided poppet spring **219**, and any additional upwardly applied fluid forces within the valve body **100d**, to shift the valve stem **188**, and thus the lower reciprocating sealing member **213** carried by the valve stem **188**, downward within the valve body **100d**. Accordingly, the valve face **217** formed at the top surface **216** of the lower reciprocating sealing member **213** remains sealingly engaged with the corresponding lower valve seat **115** provided within the valve body **100d** for the at rest flow control valve **185d**. Still at rest in the normally closed state of the flow control valve **185d**, the flow control valve **185d** continues to prevent

passage of diluent from the cylindrical chamber **139** of the open-topped cup **166** to the intermediate chamber **106** of the valve body **100d**.

(329) In the fourth state of operation of the integrated valve unit **90d** as implemented in FIGS. **98A-98E**, the diluent selector valve **130d** is configured to select a second diluent, of a type known to a user, for use in dispensing a beverage product associated by the user with the representative ON-OFF flow control **20d**. Although not necessarily known to the user, the user-selected diluent is supplied under pressure to the hand-held beverage dispenser **5** through the second diluent inlet **68** at the rear end **52** of the handle body **10**. As also not necessarily known to the user, the representative ON-OFF flow control **20d** establishes the state of the representative flow control valve **185d** of valve unit **90d**. As illustrated in the figures, the ON-OFF flow control **20d** is actuated or otherwise operated in the second state of operation of the integrated valve unit **90d**, and thus, although not necessarily known to the user, the normally closed flow control valve **185d** is actuated, and therefore open. Accordingly, beverage fluids, including a beverage product supplied under pressure to the hand-held beverage dispenser **5** through beverage product inlet **69d** at the rear end **52** of the handle body **10**, pass through the valve body **100d** of the valve unit **90d** to be mixed together and dispensed from the hand-held beverage dispenser **5**.

(330) Selecting the second diluent for dispensing a beverage from the hand-held beverage dispenser **5** with ON-OFF flow control **20d** causes the horizontally oriented notch **170** through the upper edge **169** of the cylindrical valve gate **167** of the open-topped cup **166** of the diluent selector valve **130d** to operably align with the second diluent inlet port **117** of the valve body **100d**, as particularly shown in FIG. **98B**. As shown in FIGS. **98B** and **98E**, alignment in this second operable state of the diluent selector valve **130d** creates an open flow path through the diluent selector valve **130d** allowing the second diluent to flow from supply branch **75d**, through the second diluent inlet port **117** of the valve body **100d** and into the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**. Simultaneously, however, selection of the second diluent also causes an intact portion of the cylindrical valve gate **167** of the open-topped cup **166** of the diluent selector valve **130d** to operably align with the first diluent inlet port **116** of the valve body **100d**, as also particularly shown in FIG. **98B**, which creates a flow blocking gate within the diluent selector valve **130d**. Thus, in the second operable state of the diluent selector valve **130d**, as is selected according to the fourth state of operation of the integrated valve unit **90d**, flow of the first diluent from supply branch **72d** is prevented by the diluent selector valve **130d** from being introduced into the cylindrical chamber **139**, as shown in FIGS. **98B** and **98E**.

(331) In the previously defined fourth state of operation of the integrated valve unit **90d**, a beverage product may be supplied under pressure from any suitable flow control assembly in fluid communication with the beverage product inlet **69d** at the rear end **52** of the handle body **10**. Through priming or prior use of the hand-held beverage dispenser **5**, a supplied beverage product is conveyed through the dedicated beverage product supply conduit **76d** between the beverage product inlet **69d** and the beverage product inlet port **108** of the valve body **100d** and introduced through the beverage product inlet port **108** to the intermediate chamber **106** of the valve body **100d**. As particularly shown in FIGS. **26**, **28** and **98D**, the beverage product inlet port **108** introduces the beverage product into the intermediate chamber **106** upstream of the upper valve seat **109** for the flow control valve **185d**.

(332) As particularly shown in FIG. **98D**, the flow control valve **185d** is implemented as a coupled set of normally closed poppet-type valves, where an upper one of the poppet-type valves controls flow through the valve body **100d** of a beverage product. In the at rest normally closed state of the flow control valve **185d**, the poppet spring **219** at the bottom end **203** of the valve stem **188** applies an upward biasing force to the valve stem **188**. The upward biasing force produced by the poppet spring **219**, as may be joined by any additional upward forces produced by pressurized beverage fluids within the valve body **100d**, holds the valve stem **188** of the flow control valve **185d** in the

uppermost position for the valve stem **188** within the valve body **100d**. Accordingly, the upper reciprocating sealing member **205** carried by the valve stem **188** is also at an uppermost position within the valve body **100d**, whereat the valve face **209** formed at the top surface **208** of the upper reciprocating sealing member **205** is sealingly engaged with the corresponding upper valve seat **109** provided within the valve body **100d** for the at rest flow control valve **185d**. At rest in this normally closed state of the flow control valve **185d**, the flow control valve **185d** prevents passage of beverage product from the intermediate chamber **106** to the upper chamber **104** of the valve body **100d**.

(333) Because in the defined fourth state of operation of the integrated valve unit **90d** the ON-OFF flow control **20d** is actuated or otherwise operated, a sufficient downward force applied to the valve stem **188** overcomes the upward biasing force applied to the bottom end **203** of the valve stem **188** by the provided poppet spring **219**, and any additional upwardly applied fluid forces within the valve body **100d**, to shift the valve stem **188**, and thus the upper reciprocating sealing member **205** carried by the valve stem **188**, downward within the valve body **100d**, as shown in FIGS. **98A** and **98D**. As the valve stem **188** and thus the upper reciprocating sealing member **205** shift downward, flow from the intermediate chamber **106** to the upper chamber **104** of the valve body **100d** is immediately enabled, whereby beverage product immediately flows from the intermediate chamber **106** to the upper chamber **104**. As the valve stem **188** and the upper reciprocating sealing member **205** continue to shift the short distance downward to reach maximum displacement, as shown in FIGS. **98A** and **98D**, the flow of beverage product quickly reaches maximum rate. In any case, the beverage product flowing into the upper chamber **104** passes unobstructed from the upper chamber **104** through the beverage product outlet port **105** of the valve body **100d**, and is conveyed through the dedicated beverage dispensing conduit **80d** between the beverage product outlet port **105** and the beverage product outlet **83d** at the bottom **31** and adjacent the forward end **48** of the handle body **10**. The beverage product is then there conducted into and through the post-mix type drink dispenser assembly **275**, where, in accordance with the fourth state of operation of the integrated valve unit **90d**, the beverage product is mixed together with the user-selected second diluent as they are dispensed together into a beverage vessel, in a manner well known to those of ordinary skill in the relevant arts.

(334) Concurrently with the supply of a beverage product to the valve body **100d**, a second diluent may be supplied under pressure from any suitable flow control assembly in fluid communication with the second diluent inlet **68** at the rear end **52** of the handle body **10**, as previously described. Through priming or prior use of the hand-held beverage dispenser **5**, a supplied second diluent is conveyed through the common trunk **74** of the second diluent inlet manifold **73** and a dedicated valve supply branch **75d** from the common trunk **74** between the second diluent inlet **68** and the second diluent inlet port **117** of the valve body **100d**. Because in the defined fourth state of operation of the integrated valve unit **90d** the diluent selector valve **130d** is configured in a second operable state to select the second diluent, the diluent selector valve **130d** establishes an open flow path through the diluent selector valve **130d** between the second diluent inlet port **117** and the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**. Accordingly, the second diluent is further conveyed from the second diluent inlet port **117** of the valve body **100d** and into the cylindrical chamber **139** of the open-topped cup **166**. As particularly shown in FIGS. **26**, **28** and **98A-98B**, the cooperatively adapted second diluent inlet port **117** and diluent selector valve **130d** introduce the second diluent into the cylindrical chamber **139** upstream of the lower valve seat **115** for the flow control valve **185d**. Simultaneously, an intact portion of the cylindrical valve gate **167** of the open-topped cup **166** sealingly obstructs the first diluent inlet port **116** of the valve body **100d**, as particularly shown in FIG. **98B**. Accordingly, the diluent selector valve **130d** in the third operable state thereof prevents introduction to the cylindrical chamber **139** of any fluid flowing to or through the first inlet port **116**.

(335) A lower one of the poppet-type valves provided in implementation of the flow control valve **185d** controls flow through the valve body **100d** of a diluent, as particularly shown in FIG. **98D**. In the at rest normally closed state of the flow control valve **185d**, the poppet spring **219** at the bottom end **203** of the valve stem **188** applies an upward biasing force to the valve stem **188**. The upward biasing force produced by the poppet spring **219**, as may be joined by any additional upward forces produced by pressurized beverage fluids within the valve body **100d**, holds the valve stem **188** of the flow control valve **185d** in the uppermost position for the valve stem **188** within the valve body **100d**. Accordingly, the lower reciprocating sealing member **213** carried by the valve stem **188** is also at an uppermost position within the valve body **100d**, whereat the valve face **217** formed at the top surface **216** of the lower reciprocating sealing member **213** is sealingly engaged with the corresponding lower valve seat **115** provided within the valve body **100d** for the at rest flow control valve **185d**. At rest in this normally closed state of the flow control valve **185d**, the flow control valve **185d** prevents passage of diluent from the cylindrical chamber **139** of the open-topped cup **166**, as operably received within the lower chamber **111** of the valve body **100d**, to the intermediate chamber **106** of the valve body **100d**.

(336) Because in the defined fourth state of operation of the integrated valve unit **90d** the ON-OFF flow control **20d** is actuated or otherwise operated, a sufficient downward force applied to the valve stem **188** overcomes the upward biasing force applied to the bottom end **203** of the valve stem **188** by the provided poppet spring **219**, and any additional upwardly applied fluid forces within the valve body **100d**, to shift the valve stem **188**, and thus the lower reciprocating sealing member **213** carried by the valve stem **188**, downward within the valve body **100d**, as shown in FIGS. **98A** and **98D**. As the valve stem **188** and thus the lower reciprocating sealing member **213** shift downward, flow from the cylindrical chamber **139** of the open-topped cup **166** to the intermediate chamber of the valve body **100d** is immediately enabled, whereby the first diluent immediately flows from the cylindrical chamber **139** to the intermediate chamber **106**. As the valve stem **188** and the lower reciprocating sealing member **213** continue to shift the short distance downward to reach maximum displacement, as shown in FIGS. **98A** and **98D**, the flow of the first diluent quickly reaches maximum rate. In any case, the first diluent flowing into the intermediate chamber **106** passes unobstructed from the intermediate chamber **106** through the diluent outlet port **110** of the valve body **100d**, and is conveyed through the dedicated valve dispense branch **79d** to the common trunk **78** and the common trunk **78** of the common diluents outlet manifold **77** between the diluent outlet port **110** and the single common diluents outlet **82** at the bottom **31** and adjacent the forward end **48** of the handle body **10**. The first diluent is then there conducted into and through the post-mix type drink dispenser assembly **275**, where the user-selected second diluent is mixed together with the beverage product as they are dispensed together into a beverage vessel, in a manner well known to those of ordinary skill in the relevant arts.

(337) Supplemental to the many foregoing detailed descriptions of various user interactions with the preferred implementation of the hand-held beverage dispenser **5** according to the second embodiment, the manner of use for the hand-held beverage dispenser **5** is now set forth end-to-end. Preparatory steps for deployment and use of the hand-held beverage dispenser **5**, include identifying and providing a suitable post-mix type drink dispenser assembly **275**, as is capable of properly dispensing the desired complement of post-mix beverages; identifying and providing a suitable flow control assembly, consistent with the intended beverage complement; and identifying and providing such related components as carbonators or cooling systems, and may be required for the intended service. In any case, the final preparatory steps include installation, if necessary, of the “back-room” components, such as bag-in-box systems, point-of-use components, such as a manifold system, and provision of connecting tubulars. Each of these preparatory steps, however, is well within the ordinary skill in the relevant arts, and may readily be accomplished by those new to the arts with the assistance of installation technicians, restaurant consultants, and the like.

(338) With the supporting components readied, a first step prior to use of the hand-held beverage

dispenser **5** is to connect the handle body **10** to a flow control assembly adapted to supply at least one pressurized beverage product and a plurality of pressurized diluents at appropriately regulated flow rates. As is well known to those of ordinary skill in the relevant arts, any of the many commercially available flow control assemblies is connected to the hand-held beverage dispenser **5** through a multiplicity of individual fluid lines conventionally mated with the fluid inlets **66** provided at the rear end **52** of the handle body **10**. As will be appreciated by those of ordinary skill in the relevant arts, the individual fluid lines through which the flow control assembly will supply pressurized fluids at appropriate flow rates, should include a plurality of beverage product lines for connection to the beverage product inlets **69a-69h**, as well as at least two diluent lines for connection to the first diluent inlet **67** and the second diluent inlet **68**. At the other end, a suitable post-mix type drink dispenser assembly **275**, as will be dependently coupled to the bottom **31** of the handle body **10** at a location adjacent the forward end **48** of the handle body **10**, should be installed by a preferably skilled person. For end use, however, an appropriate nozzle housing **280** for the mixer **276** of the post-mix type drink dispenser assembly **275** should be twisted on. As is well known to those of ordinary skill in the relevant arts, the nozzle housing **280** for the mixer **276** of the implemented post-mix type drink dispenser assembly **275** is readily removable to facilitate periodic cleaning of the post-mix type drink dispenser assembly **275**.

(339) With the hand-held beverage dispenser **5** installed for use, and beverage products and diluents made available through connecting tubulars, the very simple end use of the hand-held beverage dispenser **5** relies entirely on single-button, ON-OFF type operation. As has been described, a plurality of ON-OFF flow controls **20a-20j** is familiarly accessed at the top **18** of the handle body **10** of the hand-held beverage dispenser **5**, and the flow controls are **20a-20j** usually actuated by a simple thumb press, as is very familiar to those of ordinary skill in the relevant arts as well as to service industry employees in general.

(340) In use of the inventive diluent selection features of the present invention, the fluid inlets **66** of the hand-held beverage dispenser **5** are conventionally placed, or assigned for placement, in fluid communication with outlets from a flow control assembly or any other like source of at least one flow regulated pressurized beverage product and a plurality of flow regulated pressurized diluents. The end-user charged with configuration or reconfiguration of the hand-held beverage dispenser **5** will then, for at least each of the provided beverage products, utilize a corresponding one of the inventively implemented diluent selector valves **130a-130h** to select one of the plurality of diluents for dispensing with the corresponding beverage product. The end-user may also, however, similarly set up the diluent selector valve **130i-130j** implemented in connection with the either or both of the previously described diluents only valve units **90i-90j**. If desired and not yet completed, the end-user charged with configuration or reconfiguration of the hand-held beverage dispenser **5** will often also attach or otherwise place a suitable post-mix type drink dispenser assembly **275**, such as are well known in the relevant arts, in fluid communication with the fluid outlets **81** from the hand-held beverage dispenser **5**.

(341) As has been described in detail herein, and with reference to the described exemplary implementation, the foregoing diluent selections are readily made as follows: (1) the user disassembles the lower enclosure member **34** from the bottom **31** of the handle body **10** by removing the mounting screws **44** and pulling away the lower enclosure member **34**; (2) the user will identify the desired diluent by for example, the letter W for plain water, or the letter C for carbonated water, and will simply rotate the diluent selector to point the arrowhead to the desired diluent, such as, for example, to the letter C to select carbonated water; and (3) once any desired change is made to the diluent selector valve **130a-130j** the user will reassemble the lower enclosure member **34** with the bottom **31** of the handle body **10** conventionally using the earlier removed screws.

(342) With the hand-held beverage dispenser **5** deployed for operation as described, and the desired diluents selected, the end-user will depress, or otherwise operate, one of the ON-OFF flow controls

20a-20h to actuate the corresponding flow control valve **185a-185h**, and dispense a desired beverage product with its selected diluent. Additionally, certain ON-OFF flow controls **20i-20j** may correspond to flow control valves **185i-185j** that are implemented in valve bodies **90i-90j** adapted to dispense a diluent alone.

Claims

1. A valve arrangement for selectively establishing beverage fluid flow paths through a hand-held beverage dispenser, said valve arrangement comprising: a valve unit including a composite valve trim assembly substantially contained within a hand-held beverage dispenser; a plurality of flow paths to said valve unit and a fixed flow path from said valve unit; wherein said composite valve trim assembly is adapted to: establish passage into said valve unit of a user selectable one of said plurality of flow paths; block passage into said valve unit of each said plurality of flow paths other than said one of said plurality of flow paths; and establish passage from said one of said plurality of flow paths to said fixed flow path from said valve unit; and wherein establishment of passage into said valve unit of a user selectable one of said plurality of flow paths is functionally independent of establishment of passage to said fixed flow path of said one of said plurality of flow paths.
2. The valve arrangement as recited in claim 1, wherein said composite valve trim assembly implements a poppet-type valve adapted to establish passage from said one of said plurality of flow paths to said fixed flow path from said valve unit.
3. The valve arrangement as recited in claim 1, said valve arrangement further comprising: a dedicated flow path to said valve unit and a dedicated flow path from said valve unit; and wherein said composite valve trim assembly is adapted to establish passage from said dedicated flow path to said valve unit to said dedicated flow path from said valve unit.
4. The valve arrangement as recited in claim 3, wherein said composite valve trim assembly implements a gate valve adapted to establish passage into said valve unit of a user selectable one of said plurality of flow paths and block passage into said valve unit of each said plurality of flow paths other than said one of said plurality of flow paths.
5. The valve arrangement as recited in claim 4, wherein said gate valve includes a cylindrical valve gate.
6. The valve arrangement as recited in claim 5, wherein said gate valve is rotationally operated.
7. The valve arrangement as recited in claim 4, wherein said composite valve trim assembly implements a linked set of poppet-type valves adapted to concurrently establish passage from said one of said plurality of flow paths to said fixed flow path from said valve unit and to establish passage from said dedicated flow path to said valve unit to said dedicated flow path from said valve unit.
8. The valve arrangement as recited in claim 3, wherein said composite valve trim assembly implements a linked set of poppet-type valves adapted to concurrently establish passage from said one of said plurality of flow paths to said fixed flow path from said valve unit and to establish passage from said dedicated flow path to said valve unit to said dedicated flow path from said valve unit.
9. A valve arrangement for selectively establishing beverage fluid flow paths through a hand-held beverage dispenser, said valve arrangement comprising: a valve unit including a composite valve trim assembly substantially contained within a hand-held beverage dispenser; a plurality of flow paths to said valve unit and a fixed flow path from said valve unit; wherein said composite valve trim assembly implements a gate valve adapted to: establish passage into said valve unit of a user selectable one of said plurality of flow paths; and block passage into said valve unit of each said plurality of flow paths other than said one of said plurality of flow paths; wherein said composite valve trim assembly is adapted to establish passage from said one of said plurality of flow paths to said fixed flow path from said valve unit; and wherein establishment of passage into said valve unit

of a user selectable one of said plurality of flow paths is functionally independent of establishment of passage to said fixed flow path of said one of said plurality of flow paths.

10. The valve arrangement as recited in claim 9, wherein said gate valve includes a cylindrical valve gate.

11. The valve arrangement as recited in claim 10, wherein said gate valve is rotationally operated.

12. The valve arrangement as recited in claim 9, wherein said composite valve trim assembly implements a poppet-type valve adapted to establish passage from said one of said plurality of flow paths to said fixed flow path from said valve unit.
