

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405617
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tsai; Chiu-Teng et al.

Multidirectional docking apparatus and methods for charging a device

Abstract

Docking apparatus and methods for providing charging power to a power storage device of an external device, the docking apparatus including a docking portion for the external device to dock with; a plurality of power-supply contacts mounted on a surface of the docking portion and arranged in an L shape; and a control circuit configured to detect whether the external device docks with the docking portion and supply power to the power-supply contacts on the docking portion in response to detecting that the external device docks with the docking portion.

Inventors: Tsai; Chiu-Teng (Tainan, TW), Lin; Yi-Bin (Tainan, TW), Fu; Chao-Wen (Tainan, TW)

Applicant: GEOSAT Aerospace & Technology Inc. (Tainan, TW)

Family ID: 89434061

Assignee: GEOSAT AEROSPACE & TECHNOLOGY INC. (Tainan, TW)

Appl. No.: 18/345403

Filed: June 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240002070 A1	Jan. 04, 2024

Related U.S. Application Data

us-provisional-application US 63357811 20220701

Publication Classification

Int. Cl.: G05D1/661 (20240101); B64U70/90 (20230101); B64U80/25 (20230101); G05D1/243 (20240101); H02J7/00 (20060101); H01R13/66 (20060101)

U.S. Cl.:

CPC G05D1/661 (20240101); B64U70/90 (20230101); B64U80/25 (20230101); G05D1/243 (20240101); H02J7/0036 (20130101); H02J7/0044 (20130101); H01R13/6683 (20130101)

Field of Classification Search

CPC: B64U (80/25); B64U (70/90); B64U (2101/30); B64F (1/35); H02J (7/0036)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0094686	12/2020	Metzner	N/A	G08B 19/00
2023/0137016	12/2022	Wiegman	320/107	G01R 31/66

Primary Examiner: Collins; Timothy D

Assistant Examiner: Heston; Justin Michael

Attorney, Agent or Firm: McClure, Qualey & Rodack, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) The present application claims priority to U.S. Provisional Application No. 63/357,811, filed on Jul. 1, 2022, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present application relates to docking apparatus for charging a device, and more particularly, to multidirectional docking apparatus and methods for charging a device.

BACKGROUND

(2) When a device needs to be charged, a user usually needs to align the device's charging connector with a charger's connector before electrically connecting the device to the charger. The alignment may require additional attention and time from the user. It may cause inconvenience and inefficiency to the user. If a device to be charged is an unmanned device, the unmanned device and/or a charger may require an additional mechanism for aligning their connectors. The additional mechanism may cause additional power consumption and/or cost increase and require additional operation time.

SUMMARY

(3) Embodiments of the present application provide apparatus and methods for providing charging power to an external device.

(4) These embodiments include docking apparatus for providing charging power to a power storage device of an external device. The docking apparatus includes a docking portion for the external device to dock with. The docking apparatus also includes a plurality of power-supply contacts

mounted on a surface of the docking portion and arranged in an L shape. The docking apparatus also includes a control circuit configured to detect whether the external device docks with the docking portion and supply power to the power-supply contacts on the docking portion in response to detecting that the external device docks with the docking portion.

(5) These embodiments also include an unmanned aerial vehicle (UAV) system. The UAV system includes a UAV including a power storage device and a plurality of charging contacts. The UAV system also includes a docking station including a docking portion for the UAV to dock with. The docking apparatus also includes a plurality of power-supply contacts mounted on a surface of the docking portion and arranged in an L shape. The docking apparatus also includes a control circuit configured to detect whether the external device docks with the docking portion and supply power to the power-supply contacts on the docking portion in response to detecting that the external device docks with the docking portion.

(6) These embodiments further include a method for providing charging power to an unmanned aerial vehicle (UAV). The method includes controlling the UAV to fly above and align with a docking portion of docking apparatus, aligning a plurality of charging contacts of the UAV with a plurality of power-supply contacts on the docking portion, and decreasing a height of the UAV to dock with the docking portion, so that two or more of the charging contacts of the UAV are electrically coupled to two or more of the power-supply contacts of the docking portion.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an exemplary docking station for providing charging power to an exemplary unmanned aerial vehicle (UAV), according to some embodiments of the present disclosure.

(2) FIG. 2 is a block diagram of the exemplary docking station for providing charging power to the exemplary UAV in FIG. 1, according to some embodiments of the present disclosure.

(3) FIG. 3 is a block diagram of the exemplary UAV in FIG. 1, according to some embodiments of the present disclosure.

(4) FIGS. 4A, 4B, and 4C are diagrams of exemplary L-shape power-supply contacts of the exemplary docking station in FIG. 1 and exemplary charging contacts of exemplary UAVs, according to some embodiments of the present disclosure.

(5) FIGS. 5A, 5B, and 5C are diagrams of exemplary cross-shape power-supply contacts of an exemplary docking station and exemplary charging contacts of exemplary UAVs, according to some embodiments of the present disclosure.

(6) FIGS. 6A, 6B, and 6C are diagrams of exemplary nine-square power-supply contacts of an exemplary docking station and exemplary charging contacts of exemplary UAVs, according to some embodiments of the present disclosure.

(7) FIG. 7 is a flow chart of an exemplary method for providing charging power to the exemplary UAV in FIG. 1, according to some embodiments of the present disclosure.

DETAILED DESCRIPTION

(8) Reference will now be made in detail to exemplary embodiments, examples of which are illustrated in the accompanying drawings. The following description refers to the accompanying drawings in which the same numbers in different drawings represent the same or similar elements unless otherwise represented. The implementations set forth in the following description of exemplary embodiments do not represent all implementations consistent with the invention. Instead, they are merely examples of apparatus and methods consistent with aspects related to the invention as recited in the appended claims.

(9) FIG. 1 illustrates an exemplary docking station **100** for providing charging power to an exemplary unmanned aerial vehicle (UAV) **200**, according to some embodiments of the present

disclosure. As shown in FIG. 1, docking station **100** includes a docking portion **110** for UAV **200** to dock with. Docking station **100** also includes power-supply contacts **121**, **122**, and **123** mounted on a surface of docking portion **110** and arranged in an L shape from a top-view perspective **126**. UAV **200** includes a power storage device (e.g., a battery) (not shown) and charging contacts **221**, **222**, and **223** mounted on its downward surface. Charging contacts **221**, **222**, and **223** are arranged in an L shape from a bottom view perspective **128** (FIG. 1) or from a top view perspective (FIG. 4A). As shown in FIG. 1, UAV **200** and docking portion **110** have a square shape. The embodiments in the present disclosure are not limited square docking portion **110**. For example, the embodiments may also be adapted for practice with a rectangular docking portion. Some embodiments not including operations regarding corners of a docking portion may work on docking portions of any shape.

(10) As shown in FIG. 1, a UAV system includes docking station **100** and UAV **200**. UAV **200** may fly around indoors or outdoors to perform a mission and fly back to dock with docking station **100** for charging its power storage device (e.g., the battery). When UAV **200** docks with docking station **100** in an operative direction, charging contacts **221**, **222**, and **223** of UAV **200** are respectively coupled to power-supply contacts **121**, **122**, and **123** of docking station **100**. When the contacts are coupled, docking station **100** is configured to supply power to charge UAV **200**.

(11) In some embodiments, from a perspective of docking station **100**, UAV **200** is an external device. Docking station **100** is configured to provide charging power to the power storage device (e.g., the battery) of UAV **200** when UAV **200** docks with docking station **100**. In some embodiments, the external device to dock with docking station **100** may be a laptop, a tablet, a smartphone, an appliance, an electronic component, a gadget, a machine, a medical device, a vehicle, an unmanned vehicle, an automatic vehicle, or any other apparatus having a power storage device to be charged. The power storage device of the external device may be a rechargeable battery, a secondary battery, a storage battery, an electrostatic double-layer capacitor, an electrochemical pseudocapacitor, a hybrid capacitor, a lithium-ion capacitor, or any other energy storage device or component.

(12) FIG. 2 is a block diagram of exemplary docking station **100** for providing charging power to exemplary UAV **200** in FIG. 1, according to some embodiments of the present disclosure. As shown in FIG. 2, docking station **100** includes a power-supply contact assembly **120**, a battery charging integrated circuit (IC) **130**, a docking detector circuit **140**, and a connector **150**. Docking station **100** is coupled to a power adaptor **101** via connector **150**. Power adaptor **101** is coupled to a power source (not shown) and configured to supply power to docking station **100**. Battery charging integrated circuit (IC) **130** and docking detector circuit **140** are a control circuit of docking station **100**. Power-supply contact assembly **120** includes power-supply contacts **121**, **122**, and **123** (FIG. 1).

(13) UAV **200** includes a micro-controller unit (MCU) **210**, motors **212**, a charging contact assembly **220**, an artificial intelligence (AI) image signal processor (AISP) **230**, a battery **240**, a power management integrated circuit (PMIC) **241**, a power distribution circuit **242**, an electronic speed controller (ESC) **280**, and cameras and sensors (FIG. 3). Charging contact assembly **220** includes charging contacts **221**, **222**, and **223** (FIG. 1). While MCU **210** is configured to perform and control operations for docking, AISP **230** may be configured to process images for flight missions. In some embodiments, AISP **230** may be configured to facilitate image recognition required in docking operations.

(14) The control circuit (battery charging IC **130** and docking detector circuit **140**) of docking station **100** is configured to detect whether UAV **200** docks with docking portion **110**. For example, the control circuit of docking station **100** is configured to detect whether two or more of power-supply contacts **121**, **122**, and **123** (FIG. 1) on docking portion **110** (FIG. 1) are electrically coupled to two or more of charging contacts **221**, **222**, and **223** (FIG. 1) of UAV **200** by testing whether conductive contact is made between power-supply contacts **121**, **122**, and **123** and charging contacts **221**, **222**, and **223**. As another example, power-supply contact assembly **120** and charging

contact assembly **220** may have additional contacts (not shown) corresponding to each other. The control circuit of docking station **100** is configured to test if a conductive contact is made by these additional contacts to determine whether UAV **200** docks with docking station **100** in an operative direction. The operative direction means that all charging contacts of UAV **200** are electrically coupled to all corresponding power-supply contacts of docking station **100**. In some embodiments, the operative direction means that at least two of the charging contacts of UAV **200** are electrically coupled to at least two power-supply contacts of docking station **100** to receive a positive and a negative voltage for charging battery **240**.

(15) When UAV **200** docks with docking station **100** in the operative direction, the control circuit detects that UAV **200** docks with docking portion **110**. In response to detecting that UAV **200** docks with docking portion **110**, battery charging IC **130** of the control circuit is configured to supply power to power-supply contacts **121**, **122**, and **123** on docking portion **110**. Because UAV **200** docks with docking station **100** in the operative direction, charging contacts **221**, **222**, and **223** of UAV **200** are coupled to corresponding power-supply contacts **121**, **122**, and **123**, respectively. In UAV **200**, PMIC **241** is configured to control power distribution circuit **242** to distribute supplied power from charging contacts **221**, **222**, and **223** to battery **240**. As a result, docking station **100** is configured supply power to charge battery **240** of UAV **200**, as shown in FIG. 2.

(16) FIG. 3 is a block diagram of exemplary UAV **200** in FIG. 1, according to some embodiments of the present disclosure. As shown in FIG. 3, UAV **200** includes MCU **210**, an inertial measurement unit (IMU) **211**, motors **212**, AISP **230**, battery **240**, a memory **250**, a main camera **260**, a downward viewing camera **261**, a light detection and ranging (LiDAR) sensor **262**, an optical flow sensor **263**, a laser distance sensor **264**, and a Wi-Fi/Bluetooth low energy (BLE) transceiver **270**. MCU **210** is configured to execute instructions stored in memory **250** to control UAV **200** to perform a flight mission based on images captured by main camera **260** and downward viewing camera **261**, data sensed by IMU **211**, LiDAR sensor **262**, optical flow sensor **263**, and laser distance sensor **264**, and/or received Wi-Fi/BLE signals. AISP **230** is configured to perform image processing of the images and sensed data for the flight mission and/or for flight operations.

(17) Optical flow sensor **263** is configured to capture images of docking portion **110** and recognize motion of docking portion **110** in the images caused by descending motion of UAV **200**. In some embodiments, MCU **210** or AISP **230** is configured to control UAV **200** to fly above and align with docking portion **110** based, at least in part, on the sensed data (images) of optical flow sensor **263**.

(18) FIG. 4A is a diagram of exemplary L-shape power-supply contacts **121**, **122**, and **123** of exemplary docking station **100** in FIG. 1 and exemplary L-shape charging contacts **221**, **222**, and **223** of exemplary UAV **200** in FIG. 1, according to some embodiments of the present disclosure. As shown in FIG. 4A, docking portion **110** of docking station **100** has three power-supply contacts **121**, **122**, and **123** arranged in a first L shape from a top view perspective. UAV **200** has three charging contacts **221**, **222**, and **223** arranged in a second L shape from the top view perspective. Dimensions of the first and second L shapes are the same. Docking portion **110** includes four corners.

(19) When UAV **200** needs to charge its battery **240** (FIGS. 2 and 3) or completes its flight mission, MCU **210** (FIG. 3) is configured to execute the instructions stored in memory **250** to control UAV **200** to fly back to and approach docking station **100** based on, for example, signal strength of Wi-Fi/BLE signals estimated by Wi-Fi/BLE transceiver **270**, images of docking portion **110** acquired by downward viewing camera **261** and/or sensed by optical flow sensor **263**, images captured by main camera **260**, and/or acceleration and rotation data measured by IMU **211** (FIG. 3).

Alternatively, UAV **200** is configured to record its flight routes in memory **250** when it departs from docking station **100**. When UAV **200** completes its flight mission, MCU **210** (FIG. 3) is configured to execute the instructions stored in memory **250** to control UAV **200** to fly back to and approach docking station **100** based on the recorded routes in memory **250**.

(20) When UAV **200** flies back to and approaches docking station **100** to dock, MCU **210** (FIG. 3)

is configured to execute the instructions stored in memory 250 to control UAV 200 to fly above and align with docking portion 110 by matching adjacent template corner images 110-C1 and 110-C2, retrieved from memory 250, with corners of docking portion 110 in downward images acquired by downward viewing camera 261. For example, when UAV 200 flies back to and approaches docking station 100 to dock, downward viewing camera 261 of UAV 200 is configured to acquire downward images. Laser distance sensor 264 is configured to sense downward distances between UAV 200 and docking portion 110. MCU 210 (FIG. 3) is configured to, or control AISP 230 (FIG. 3) to receive one or more of the downward images acquired by downward viewing camera 261 (FIG. 3) and/or the distance data sensed by laser distance laser 264 or LiDAR sensor 262. MCU 210 or AISP 230 is configured to recognize template corner images 110-C1 and 110-C2 in the downward images by, for example, template matching. In some embodiments, in calculating match rates between template corner images 110-C1 and 110-C2 and the downward images, MCU 210 or AISP 230 is configured to adjust the image sizes of template corner images 110-C1 and 110-C2 or of the downward images based on the distance data. After MCU 210 or ASIP 230 recognizes the two corners of square docking portion 110 based on the downward images, or based on the downward images and the distance data, MCU 210 is configured to control UAV 200 to fly above and align two adjacent corners of UAV 200 with the two corners of docking portion 110 corresponding to template corner images 110-C1 and 110-C2.

(21) In some embodiments, MCU 210 or AISP 230 is configured to recognize two corners at two opposite vertices of square docking portion 110 in the downward images by the template matching, instead of adjacent corners, for UAV 200 to fly above and align with docking portion 110. In some embodiments, MCU 210 or AISP 230 is configured to recognize three or four corners of docking portion 110 in the downward images by the template matching, for UAV 200 to fly above and align with docking portion 110.

(22) In some embodiments, MCU 210 or AISP 230 is configured to recognize two corners at two opposite vertices of square docking portion 110 based on image data sensed by optical flow sensor 263, for UAV 200 to fly above and align with docking portion 110. In some embodiments, MCU 210 or AISP 230 is configured to recognize three or four corners of docking portion 110 image data sensed by optical flow sensor 263, for UAV 200 to fly above and align with docking portion 110.

(23) In some embodiments, when UAV 200 flies back to and approaches docking station 100 to dock, MCU 210 (FIG. 3) is configured to execute the instructions stored in memory 250 to control UAV 200 to fly above and align with docking portion 110 by recognizing the first L shape of the plurality of power-supply contacts on the docking portion. For example, when UAV 200 flies back to and approaches docking station 100 to dock, downward viewing camera 261 of UAV 200 is configured to acquire downward images. The downward images include the first L shape of the plurality of power-supply contacts on docking portion 110. MCU 210 (FIG. 3) is configured to, or controls AISP 230 (FIG. 3) to, receive one or more of the downward images acquired by downward viewing camera 261 (FIG. 3). MCU 210 or AISP 230 is configured to recognize the first L shape of the plurality of power-supply contacts on docking portion 110 in the downward images by, for example, template matching. After MCU 210 or ASIP 230 recognizes the first L shape of the plurality of power-supply contacts on docking portion 110, MCU 210 is configured to control UAV 200 to fly above and align UAV 200 with docking portion 110.

(24) In some embodiments, when UAV 200 flies back to and approaches docking station 100 to dock, MCU 210 (FIG. 3) is configured to execute the instructions stored in memory 250 to control UAV 200 to fly above and align with docking portion 110 by recognizing the plurality of power-supply contacts on docking portion 110. For example, when UAV 200 flies back and approaches docking station 100 to dock, downward viewing camera 261 of UAV 200 is configured to acquire downward images. The downward images include the plurality of power-supply contacts on the docking portion. Laser distance sensor 264 is configured to sense downward distances between UAV 200 and docking portion 110. MCU 210 (FIG. 3) is configured to, or controls AISP 230 (FIG.

3) to, receive one or more of the downward images acquired by downward viewing camera **261** (FIG. 3). MCU **210** or AISP **230** is configured to recognize the plurality of power-supply contacts on docking portion **110** in the downward images by, for example, template matching. In some embodiments, in calculating match rates between a template image of the plurality of power-supply contacts and the downward images, MCU **210** or AISP **230** is configured to adjust the size of the downward images or of the template image based on the distance data. After MCU **210** or AISP **230** recognizes the plurality of power-supply contacts on docking portion **110** based on the downward images, or based on the downward images and the distance data, MCU **210** is configured to control UAV **200** to fly above and align UAV **200** with docking portion **110**.

(25) After UAV **200** flies above and aligns with docking portion **110**, there may be an angle offset of 90, 180, or 270 degrees between the second L shape of charging contacts **221**, **222**, and **223** and the first L shape of power-supply contacts **121**, **122**, and **123** because four corners of square docking portion **110** look the same. MCU **210** or AISP **230** is configured to determine an angle offset value as 0, 90, 180, or 270 degrees based on the first L shape in the downward images and send the angle offset value to MCU **210**. MCU **210** is configured to execute the instructions stored in memory **250** to align the second L shape of charging contacts **221**, **222**, and **223** with the first L shape of power-supply contacts **121**, **122**, and **123** by rotating UAV **200** 90, 180, or 270 degrees relative to docking portion **110** if needed.

(26) After the second L shape aligns with the first L shape, MCU **210** is configured to execute the instructions stored in memory **250** to decrease a height of UAV **200** to dock with docking portion **110**, so that charging contacts **221**, **222**, and **223** of UAV **200** are electrically coupled to power-supply contacts **121**, **122**, and **123** of docking portion **110**, respectively.

(27) As shown in FIG. 4A, docking portion **110** includes three power-supply contacts **121**, **122**, and **123** arranged in the first L shape on its surface. Power-supply contact **121** is arranged at a corner of the first L shape. Power-supply contacts **122** and **123** are arranged at two ends of the first L shape. When UAV **200** docks with docking portion **110**, power-supply contact **121** is configured, by battery charging IC **130**, to supply a positive voltage, e.g., 5, 15, or 25 volts (V), to charging contact **221** of UAV **200**. Power-supply contacts **122** and/or **123** are configured, by battery charging IC **130**, to supply a negative voltage to charging contacts **222** and/or **223** of UAV **200**, respectively. The negative voltage is defined as a lower voltage level than the positive voltage, such as a ground level.

(28) Alternatively, when UAV **200** docks with docking portion **110**, power-supply contact **121** is configured, by battery charging IC **130**, to supply the negative voltage (e.g., the ground level) to charging contact **221** of UAV **200**. Power-supply contacts **122** and/or **123** are configured, by battery charging IC **130**, to supply the positive voltage, e.g., 5, 15, or 25 V, to charging contacts **222** and/or **223** of UAV **200**, respectively.

(29) As described above with reference to FIGS. 2 and 4A, when docking station **100** detects that UAV **200** docks with docking portion **110**, battery charging IC **130** of docking station **100** is configured to supply power to power-supply contacts **121**, **122**, and **123** on docking portion **110**. More particularly, the control circuit (battery charging IC **130** and docking detector circuit **140**) of docking station **100** is configured to detect whether two or more of power-supply contacts **121**, **122**, and **123** (FIGS. 1 and 4A) on docking portion **110** (FIGS. 1 and 4A) are electrically coupled to two or more of charging contacts **221**, **222**, and **223** (FIGS. 1 and 4A) of UAV **200**. For example, if UAV **200** aligns the second L shape of charging contacts with the first L shape of power-supply contacts on docking portion **110** and docks with docking station **100**, the control circuit is configured to detect power-supply contacts **121**, **122**, and **123** are electrically coupled to corresponding charging contacts **221**, **222**, and **223**. If UAV **200** does not align the second L shape with the first L shape and docks with docking station **100** with an angular rotation of, for example, 90 degrees, the control circuit is configured to detect power-supply contacts **121** and **122** are electrically coupled to charging contacts **221** and **223**, respectively, or power-supply contacts **121**

and **123** are electrically coupled to charging contacts **221** and **222**, respectively. If UAV **200** docks with docking station **100** with an angle rotation of 180 degrees, the control circuit is configured to detect only power-supply contact **121** is electrically coupled to charging contact **221**. As a result, the control circuit does not detect two or more of the power-supply contacts **121**, **122**, and **123** on docking portion **110** are electrically coupled to charging contacts **221**, **222**, and **223** of UAV **200**.

(30) In response to detecting that the two or more of the power-supply contacts on docking portion **110** are electrically coupled to the charging contacts of UAV **200**, battery charging IC **130** of the control circuit is configured to supply power to the two or more of the power-supply contacts on the docking portion. For example, when the control circuit (battery charging IC **130** and docking detector circuit **140**) detects power-supply contacts **121** and **122**; or **121** and **123**; or **121**, **122**, and **123** are electrically coupled to corresponding charging contacts **221** and **223**; or **221** and **222**; or **221**, **222**, and **223**, respectively, battery charging IC **130** is configured to supply power to the detected power-supply contacts **121** and **122**; or **121** and **123**; or **121**, **122**, and **123** on docking portion **110**. In some embodiments, battery charging IC **130** of the control circuit is configured to supply power to all power-supply contacts **121**, **122**, and **123** on docking portion **110** in response to detecting that two or three of power-supply contacts **121**, **122**, and **123** are electrically coupled to corresponding two or three of charging contacts **221**, **222**, and **223** of UAV **200**, respectively.

(31) In some embodiments, in response to detecting that two or more of power-supply contacts **121**, **122**, and **123** are electrically coupled to corresponding two or more of charging contacts **221**, **222**, and **223** of UAV **200**, battery charging IC **130** of the control circuit is configured to supply power to only two of power-supply contacts **121**, **122**, and **123** on docking portion **110** because two power-supply contacts are sufficient to provide the positive and negative voltages to charge UAV **200**. For example, when the control circuit (battery charging IC **130** and docking detector circuit **140**) detects all power-supply contacts **121**, **122**, and **123** are electrically coupled to charging contacts **221**, **222**, and **223**, respectively, battery charging IC **130** is configured to supply power to only power-supply contacts **121** and **122**, or only **121** and **123**. When the control circuit (battery charging IC **130** and docking detector circuit **140**) detects power-supply contacts **121** and **122**, or **121** and **123**, are electrically coupled to corresponding charging contacts **221** and **223**, or **221** and **222**, battery charging IC **130** is also configured to supply power to only power-supply contacts **121** and **122**, or **121** and **123**.

(32) FIG. 4B is a diagram of exemplary L-shape power-supply contacts **121-123** of exemplary docking station **100** in FIG. 1 and exemplary cross-shape charging contacts of an exemplary UAV **200X**, according to some embodiments of the present disclosure. As shown in FIG. 4B, docking portion **110** of docking station **100** has three power-supply contacts **121**, **122**, and **123** arranged in the first L shape from a top view perspective. UAV **200X** has five charging contacts **221**, **222**, **223**, **224**, and **225** arranged in a cross shape. Charging contact **221** at a center of the cross shape and charging contacts **222** and **223** at two ends of the cross shape form a second L shape from the top view perspective. Alternatively, charging contacts **221**, **223**, and **224**; or **221**, **224**, and **225**; or **221**, **225**, and **222** may form the second L shape. Dimensions of the first and second L shapes are the same. Accordingly, UAV **200X** can dock with docking portion **110** in any of the four angular orientations corresponding to the four different ways the charging contacts having the second L shape can align with power-supply contacts **121**, **122**, and **123** of docking portion **110** having the first L shape.

(33) UAV **200X** has all the components and functions described for UAV **200**, except a different number and arrangement of charging contacts. For example, a control circuit (e.g., battery charging IC **130** and docking detector circuit **140**) of UAV **200X** is configured to control UAV **200X** to fly above and align with docking portion **110** and decrease a height of UAV **200X** to dock with docking portion **110**, as described above for UAV **200** with reference to FIGS. 1-3 and 4A. The controller of UAV **200X** is configured to control UAV **200X** to fly above and align with docking portion **110**, by receiving one or more downward images and downward distance data and

recognizing two or more of the four corners of docking portion **110** based on the one or more downward images and the downward distance data, before decreasing the height of UAV **200X** to dock with docking portion **110**.

(34) Docking station **100** and UAV **200X** form a UAV system and operate with each other similar to those operations between docking station **100** and UAV **200** described above with reference to FIGS. **1-4A**.

(35) FIG. **4C** is a diagram of exemplary L-shape power-supply contacts **121-123** of exemplary docking station **100** in FIG. **1** and exemplary nine-square charging contacts of an exemplary UAV **200N**, according to some embodiments of the present disclosure. As shown in FIG. **4C**, docking portion **110** of docking station **100** has three power-supply contacts **121**, **122**, and **123** arranged in the first L shape from a top view perspective. UAV **200N** has nine charging contacts **221**, **222**, **223**, **224**, **225**, **226**, **227**, **228**, and **229** arranged in a nine-square configuration. Charging contact **221** at a center of the nine-square configuration and charging contacts **222** and **223** at centers of two adjacent sides of the nine-square configuration form a second L shape from the top view perspective. Alternatively, charging contacts **221**, **223**, and **224**; or **221**, **224**, and **225**; or **221**, **225**, and **222** may form the second L shape. Accordingly, UAV **200N** can dock with docking portion **110** in any of the four angular orientations corresponding to the four different ways the charging contacts having the second L shape can align with power supply contacts **121**, **122**, and **123** of docking portion **110** having the first L shape. Dimensions of the first and second L shapes are the same.

(36) UAV **200N** has all the components and functions described for UAV **200**, except a different number and arrangement of charging contacts. For example, a control circuit (e.g., battery charging IC **130** and docking detector circuit **140**) of UAV **200N** is configured to control UAV **200N** to fly above and align with docking portion **110** and decrease a height of UAV **200N** to dock with docking portion **110**, as described above for UAV **200** with reference to FIGS. **1-3** and **4A**. The controller of UAV **200N** is configured to control UAV **200N** to fly above and align with docking portion **110**, by receiving one or more downward images and downward distance data and recognizing two or more of the four corners of docking portion **110** based on the one or more downward images and the downward distance data, before decreasing the height of UAV **200N** to dock with docking portion **110**.

(37) Docking station **100** and UAV **200N** form a UAV system and operate with each other similar to those operations between docking station **100** and UAV **200** or **200X** (FIG. **4B**) described above with reference to FIGS. **1-4A** or FIG. **4B**.

(38) FIG. **5A** is a diagram of exemplary cross-shape power-supply contacts of an exemplary docking station **100X** (not shown) and exemplary L-shape charging contacts **221-223** of exemplary UAV **200** in FIG. **1**, according to some embodiments of the present disclosure. Docking station **100X** has all the components and functions described herein for docking station **100**, except a different number and arrangement of power-supply contacts. As shown in FIG. **5A**, a docking portion **110X** of docking station **100X** has five power-supply contacts **121**, **122**, **123**, **124**, and **125** mounted on its surface and arranged in a cross shape from a top view perspective.

(39) As shown in FIG. **5A**, power-supply contact **121** is arranged at a cross point of the cross shape. Remaining four power-supply contacts **122**, **123**, **124**, and **125** are arranged at four ends of the cross shape. Power-supply contact **121** is configured to supply a positive voltage and power-supply contacts **122**, **123**, **124**, and **125** at the four ends are configured to supply a negative voltage (e.g., a ground level). In some embodiments, power-supply contact **121** is configured to supply the negative voltage (e.g., the ground level) and power-supply contacts **122**, **123**, **124**, and **125** at the four ends are configured to supply the positive voltage.

(40) In FIG. **5A**, power-supply contact **121** at the center of the cross shape and power-supply contacts **122** and **123** at two ends of the cross shape are arranged in the first L shape from a top view perspective. Alternatively, power-supply contacts **121**, **123**, and **124**; or **121**, **124**, and **125**; or

121, **125**, and **122** may form the first L shape. Charging contacts **221**, **222**, and **223** of UAV **200** are arranged in the second L shape from the top view perspective. Dimensions of the first and second L shapes are the same. Accordingly, UAV **200** can dock with docking portion **110X** in any of the four angular orientations corresponding to the four different ways the power supply contacts having the first L shape can align with charging contacts **221**, **222**, and **223** of UAV **200** having the second L shape.

(41) Docking station **100X** and UAV **200** form a UAV system and operate with each other similar to those operations between docking station **100** and UAV **200**, **200X** (FIG. 4B), or **200N** (FIG. 4C) described above with reference to FIGS. 1-4A, or FIG. 4B, or FIG. 4C.

(42) FIG. 5B is a diagram of exemplary cross-shape power-supply contacts **121-125** of exemplary docking station **100X** (not shown) and exemplary cross-shape charging contacts **221-225** of exemplary UAV **200X**, according to some embodiments of the present disclosure. As shown in FIG. 5B, power-supply contacts **121-125** on docking portion **110X** are arranged in a first cross shape from a top view perspective. Charging contacts **221-225** of UAV **200X** are arranged in a second cross shape from the top view perspective. Dimensions of the first and second cross shapes are the same.

(43) The second cross shape of charging contacts **221-225** may be coupled to the first cross shape of power-supply contacts **121-125** in four different orientations. Power-supply contact **121** is configured to provide a positive voltage and power-supply contacts **122-125** are configured to provide a negative voltage (e.g., a ground level). Power-supply contacts **121-125** are able to supply power to charging contacts **221-225** in any of the four orientations. In some embodiments, power-supply contact **121** is configured to provide the negative (e.g., the ground level) and power-supply contacts **122-125** are configured to provide the positive voltage. Power-supply contacts **121-125** are able to supply power to charging contacts **221-225** in any of the four orientations.

(44) Docking station **100X** and UAV **200X** form a UAV system and operate with each other similar to those operations between docking station **100** and UAV **200**, or **200X** (FIG. 4B), or **200N** (FIG. 4C) described above with reference to FIGS. 1-4A, or FIG. 4B, or FIG. 4C; or between docking station **100X** and UAV **200** described above with reference to FIG. 5A.

(45) FIG. 5C is a diagram of exemplary cross-shape power-supply contacts **121-125** of exemplary docking station **100X** (not shown) and exemplary nine-square charging contacts **221-229** of exemplary UAV **200N**, according to some embodiments of the present disclosure. As shown in FIG. 5C, power-supply contacts **121-125** on docking portion **110X** are arranged in a first cross shape from a top view perspective. Charging contacts **221-229** of UAV **200N** are arranged in a nine-square configuration. Charging contact **221** at a center of the nine-square configuration and charging contacts **222-225** at centers of four sides of the nine-square configuration are arranged in a second cross shape. Dimensions of the first and second cross shapes are the same.

(46) The second cross shape of charging contacts **221-225** (FIG. 5C) may be coupled to the first cross shape of power-supply contacts **121-125** in four different directions, as described above with reference to FIG. 5B. Power-supply contact **121** and power-supply contacts **122-125** are configured to provide the positive and negative voltages, or the negative and positive voltages, as described above with reference to FIG. 5B.

(47) Docking station **100X** and UAV **200N** form a UAV system and operate with each other similar to those operations between docking station **100** and UAV **200**, or **200X** (FIG. 4B), or **200N** (FIG. 4C) described above with reference to FIGS. 1-4A, or FIG. 4B, or FIG. 4C; or between docking station **100X** and UAV **200** or **200X** described above with reference to FIG. 5A or 5B.

(48) FIG. 6A is a diagram of exemplary nine-square power-supply contacts of an exemplary docking station **100N** (not shown) and exemplary L-shape charging contacts **221-223** of exemplary UAV **200** in FIG. 1, according to some embodiments of the present disclosure. Docking station **100N** has all the components and functions described herein for docking station **100**, except difference in power-supply contacts. As shown in FIG. 6A, docking portion **110N** of docking

station **100N** has nine power-supply contacts **121, 122, 123, 124, 125, 126, 127, 128, and 129** mounted on its surface and arranged in a nine-square configuration from a top view perspective. (49) As shown in FIG. **6A**, power-supply contact **121** is arranged at a center of the nine-square configuration. Four power-supply contacts **122-125** are arranged at centers of four sides of the nine-square configuration. Four power-supply contacts **126-129** are arranged at four corners of the nine-square configuration. Power-supply contact **121** is configured to supply a positive voltage. Power-supply contacts **122-125** at the centers of the four sides are configured to supply a negative voltage. In some embodiments, power-supply contact **121** is configured to supply the negative voltage. Power-supply contacts **122-125** at the centers of the four sides are configured to supply the positive voltage.

(50) In FIG. **6A**, power-supply contact **121** at the center of the nine-square configuration and power-supply contacts **122** and **123** at centers of two adjacent sides of the nine-square configuration are arranged in a first L shape. Alternatively, power-supply contacts **121, 123, and 124**; or **121, 124, and 125**; or **121, 125, and 122** may form the first L shape. Charging contacts **221, 222, and 223** of UAV **200** are arranged in a second L shape. Dimensions of the first and second L shapes are the same. Accordingly, UAV **200** can dock with docking portion **110N** in any of the four angular orientations corresponding to the four different ways the power supply contacts having the first L shape can align with charging contacts **221, 222, and 223** of UAV **200** having the second L shape.

(51) Docking station **100N** and UAV **200** form a UAV system and operate with each other similar to those operations between docking station **100** and UAV **200**, or **200X** (FIG. **4B**), or **200N** (FIG. **4C**) described above with reference to FIGS. **1-4A**, or FIG. **4B**, or FIG. **4C**; or between docking station **100X** and UAV **200** (FIG. **5A**), or **200X** (FIG. **5B**), or **200N** (FIG. **5C**) described above with reference to FIG. **5A, 5B, or 5C**.

(52) FIG. **6B** is a diagram of exemplary nine-square power-supply contacts **121-129** of exemplary docking station **100N** (not shown) and exemplary cross-shape charging contacts **221-225** of exemplary UAV **200X**, according to some embodiments of the present disclosure. As shown in FIG. **6B**, power-supply contact **121** at a center of the nine-square configuration and power-supply contacts **122-125** at centers of four sides of the nine-square configuration are arranged in a first cross shape. Charging contacts **221-225** of UAV **200X** are arranged in a second cross shape. Dimensions of the first and second cross shapes are the same.

(53) Docking station **100N** and UAV **200X** form a UAV system and operate with each other similar to those operations between docking station **100** and UAV **200**, or **200X** (FIG. **4B**), or **200N** (FIG. **4C**) described above with reference to FIGS. **1-4A**, or FIG. **4B**, or FIG. **4C**; or between docking station **100X** and UAV **200** (FIG. **5A**), **200X** (FIG. **5B**), or **200N** (FIG. **5C**) described above with reference to FIG. **5A, 5B, or 5C**; or between docking station **100N** and UAV **200** (FIG. **6A**) described above with reference to FIG. **6A**.

(54) FIG. **6C** is a diagram of exemplary nine-square power-supply contacts **121-129** of exemplary docking station **100N** (not shown) and exemplary nine-square charging contacts **221-229** of exemplary UAV **200N**, according to some embodiments of the present disclosure. As shown in FIG. **6C**, power-supply contacts **121-129** on docking portion **110N** are arranged in a first nine-square configuration. Charging contacts **221-229** of UAV **200N** are arranged in a second nine-square configuration. Dimensions of the first and second nine-square configurations are the same.

(55) Docking station **100N** and UAV **200N** forms a UAV system and operate with each other similar to those operations between docking station **100** and UAV **200**, or **200X** (FIG. **4B**), or **200N** (FIG. **4C**) described above with reference to FIGS. **1-4A**, or FIG. **4B**, or FIG. **4C**; or between docking station **100X** and UAV **200** (FIG. **5A**), **200X** (FIG. **5B**), or **200N** (FIG. **5C**) described above with reference to FIG. **5A, 5B, or 5C**; or between docking station **100N** and UAV **200** (FIG. **6A**) or **200X** (FIG. **6B**) described above with reference to FIG. **6A or 6B**.

(56) In some embodiments, the second cross shape of charging contacts **221-225** may be coupled to

the first cross shape of power-supply contacts **121-125** in four different orientations. Power-supply contact **121-125** are configured to provide a positive voltage and power-supply contacts **126-129** are configured to provide a negative voltage (e.g., a ground level). Power-supply contacts **121-129** are able to supply power to charging contacts **221-229** in any of the four orientations. In some embodiments, power-supply contacts **121-125** are configured to provide the negative (e.g., the ground level) and power-supply contacts **126-129** are configured to provide the positive voltage. Power-supply contacts **121-129** are able to supply power to charging contacts **221-229** in any of the four orientations.

(57) FIG. 7 is a flow chart of an exemplary method **700** for providing charging power to exemplary UAV **200**, **200X**, or **200N**, according to some embodiments of the present disclosure. Method **700** may be practiced by apparatus and devices disclosed and illustrated in the present disclosure for providing charging power to a power storage device of a UAV. Method **700** includes controlling the UAV to fly above and align with a docking portion of docking apparatus (step **710**), aligning a plurality of charging contacts of the UAV with a plurality of power-supply contacts on the docking portion (step **720**), decreasing a height of the UAV to dock with the docking portion, so that two or more of the charging contacts of the UAV are electrically coupled to two or more of the power-supply contacts of the docking portion (step **730**), detecting whether two or more of the power-supply contacts on the docking portion are electrically coupled to two or more of the charging contacts of the UAV (step **740**), and supplying power to at least two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the UAV (step **750**).

(58) Step **710** includes controlling the UAV to fly above and align with a docking portion of docking apparatus. For example, as described above with reference to FIGS. **1-3** and **4A**, MCU **210** (FIG. **3**) of UAV **200** is configured to execute the instructions stored in memory **250** to control UAV **200** to fly above and align with docking portion **110** of docking station **100** by matching two corners of template corner images **110-C1** and **110-C2**, or by recognizing the first L shape of the plurality of power-supply contacts on the docking portion based on the downward image, or by recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data. As another example, MCU **210** (FIG. **3**) of UAV **200X** or **200N** is configured to execute the instructions stored in memory **250** to control UAV **200** to fly above and align with docking portion **110** of docking station **100** by recognizing the first cross shape (FIGS. **5B**, **5C**, and **6A-6C**) or the nine-square configuration (FIGS. **6A-6C**) of the plurality of power-supply contacts on the docking portion based on the downward image, or based on the downward image and the downward distance data.

(59) Step **720** includes aligning a plurality of charging contacts of the UAV with a plurality of power-supply contacts on the docking portion. For example, as described above with reference to FIGS. **1-3** and **4A**, three power-supply contacts **121-123** on docking portion **110** are arranged in the first L shape. Three charging contacts **221-223** of UAV **200** are arranged in the second L shape. The dimensions of the first and second L shapes are the same. After UAV **200** flies above and aligns with docking portion **110**, MCU **210** of UAV **200** is configured to align the second L shape of charging contacts **221-223** with the first L shape of power-supply contacts **121-123** by rotating UAV **200** 90, 180, or 270 degrees relative to docking portion **110** if needed. As another example, after UAV **200** flies above and aligns with docking portion **110X** or **110N**, MCU **210** of UAV **200** is configured to align the second L shape of charging contacts **221-223** with the first L shape of power-supply contacts **121-123**; or **121**, **123**, and **124**; or **121**, **124**, and **125**; or **121**, **125**, and **122** (FIGS. **5A** and **6A**). Yet as another example, after UAV **200X** flies above and aligns with docking portion **110X** or **110N**, MCU **210** of UAV **200X** is configured to align the second cross shape of charging contacts **221-225** with the first cross shape of power-supply contacts **121-125** in one of the four orientations.

(60) Step **730** includes decreasing a height of the UAV to dock with the docking portion, so that

two or more of the charging contacts of the UAV are electrically coupled to two or more of the power-supply contacts of the docking portion. For example, as described above with reference to FIGS. 1-3 and 4A, after the second L shape aligns with the first L shape, MCU 210 of UAV 200 is configured to decrease the height of UAV 200 to dock with docking portion 110, so that charging contacts 221-223 of UAV 200 are electrically coupled to power-supply contacts 121-123 of docking portion 110, respectively.

(61) Step 740 includes detecting whether two or more of the power-supply contacts on the docking portion are electrically coupled to two or more of the charging contacts of the UAV. For example, as described above with reference to FIGS. 1-3 and 4A, the control circuit (battery charging IC 130 and docking detector circuit 140) of docking station 100 is configured to detect whether power-supply contacts 121 and 122; or 121 and 123; or 121, 122, and 123 are electrically coupled to corresponding charging contacts 221 and 222; or 221 and 223; or 221, 222, and 223.

(62) Step 750 includes supplying power to at least two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the UAV. For example, as described above with reference to FIGS. 1-3 and 4A, when the control circuit (battery charging IC 130 and docking detector circuit 140) of docking station 100 detects power-supply contacts 121 and 122; or 121 and 123; or 121, 122, and 123 are electrically coupled to corresponding charging contacts 221 and 222; or 221 and 223; or 221, 222, and 223, battery charging IC 130 of docking station 100 is configured to supply power to the detected power-supply contacts 121 and 122; or 121 and 123; or 121, 122, and 123 on docking portion 110.

(63) In some embodiments, when the control circuit (battery charging IC 130 and docking detector circuit 140) of docking station 100 detects power-supply contacts 121 and 122; or 121 and 123; or 121, 122, and 123, are electrically coupled to corresponding charging contacts 221 and 222; or 221 and 223; or 221, 222, and 223, battery charging IC 130 of docking station 100 is configured to supply power to only power-supply contacts 121 and 122, or 121 and 123, as described above with reference to FIGS. 1-3 and 4A.

(64) In some embodiments, a method for providing charging power may include a plurality of operations of docking stations and UAVs described above with reference to FIGS. 1-3, 4A-4C, 5A-5C, and/or 6A-6C.

(65) The present disclosure is also related to features described in the following numbered embodiments (“E”). The numbered embodiments are illustrated and described according to some embodiments of the present disclosure.

(66) E1. Docking apparatus for charging a power storage device of an external device, the docking apparatus comprising: a docking portion for the external device to dock with; a plurality of power-supply contacts mounted on a surface of the docking portion and arranged in a cross shape; and a control circuit configured to: detect whether the external device docks with the docking portion; and supply power to the power-supply contacts on the docking portion in response to detecting that the external device docks with the docking portion.

(67) E2. The docking apparatus of E1, wherein the plurality of power-supply contacts on the docking portion includes five power-supply contacts arranged in the cross shape, wherein: a first of the five power-supply contacts is arranged at a cross point of the cross shape, and a remaining four of the five power-supply contacts are arranged at four ends of the cross shape.

(68) E3. The docking apparatus of E2, wherein: the first power-supply contact is configured to supply a positive voltage, and the four power-supply contacts at the four ends are configured to supply a negative voltage.

(69) E4. The docking apparatus of E2, wherein: the first power-supply contact is configured to supply a negative voltage, and the four power-supply contacts at the four ends are configured to supply a positive voltage.

(70) E5. The docking apparatus of E1, wherein the control circuit is configured to detect whether

the external device docks with the docking portion by detecting whether two or more of the power-supply contacts on the docking portion are electrically coupled to charging contacts of the external device.

(71) E6. The docking apparatus of E5, wherein the control circuit is configured to supply power to the power-supply contacts on the docking portion in response to detecting that the external device docks with the docking portion by supplying power to at least two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the external device.

(72) E7. The docking apparatus of E6, wherein the control circuit is configured to supply power to only two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the external device.

(73) E8. An unmanned aerial vehicle (UAV) system, comprising: a UAV comprising a power storage device; and a docking station comprising: a docking portion for the UAV to dock with; a plurality of power-supply contacts mounted on a surface of the docking portion and arranged in a cross shape; and a control circuit configured to: detect whether the UAV docks with the docking portion; and supply power to the power-supply contacts on the docking portion in response to detecting that the UAV docks with the docking portion.

(74) E9. The UAV system of E8, wherein the plurality of power-supply contacts on the docking portion includes five power-supply contacts arranged in the cross shape, wherein: a first of the five power-supply contacts is arranged at a cross point of the cross shape, and a remaining four of the five power-supply contacts are arranged at four ends of the cross shape.

(75) E10. The UAV system of E9, wherein: the first power-supply contact is configured to supply a positive voltage, and the four power-supply contacts at the four ends are configured to supply a negative voltage.

(76) E11. The UAV system of E9, wherein: the first power-supply contact is configured to supply a negative voltage, and the four power-supply contacts at the four ends are configured to supply a positive voltage.

(77) E12. The UAV system of E8, wherein the control circuit is configured to detect whether the UAV docks with the docking portion by detecting whether two or more of the power-supply contacts on the docking portion are electrically coupled to two or more of the charging contacts of the UAV.

(78) E13. The UAV system of E12, wherein the control circuit is configured to supply power to the power-supply contacts on the docking portion in response to detecting that the UAV docks with the docking portion by supplying power to at least two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the UAV.

(79) E14. The UAV system of E13, wherein the control circuit is configured to supply power to only two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the UAV.

(80) E15. The UAV system of E8, wherein: a first of the power-supply contacts at a center of the cross shape and a second and a third of the power-supply contacts at two ends of the cross shape are arranged in a first L shape, the plurality of charging contacts of the UAV are arranged in a second L shape, wherein dimensions of the first and second L shapes are the same; and the UAV further comprises a controller configured to: control the UAV to fly above and align with the docking portion, and decrease a height of the UAV to dock with the docking portion, so that two or more of the charging contacts of the UAV are electrically coupled to two or more of the power-supply contacts of the docking portion.

(81) E16. The UAV system of E15, wherein: the docking portion includes four corners; the UAV

further comprises a camera configured to acquire a downward image; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing two or more of the four corners of the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

(82) E17. The UAV system of E15, wherein: the UAV further comprises a camera configured to acquire a downward image, the downward image including the cross shape of the plurality of power-supply contacts on the docking portion; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and the downward distance data and recognizing the cross shape of the plurality of power-supply contacts on the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

(83) E18. The UAV system of E15, wherein: the UAV further comprises: a camera configured to acquire a downward image, and a sensor configured to sense downward distance data; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and the downward distance data and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

(84) E19. The UAV system of E8, wherein: the cross shape, in which the plurality of power-supply contacts on the docking portion are arranged, is a first cross shape; the plurality of charging contacts of the UAV are arranged in a second cross shape, where dimensions of the first and second cross shapes are the same; and the UAV further comprises a controller configured to: control the UAV to fly above and align with the docking portion, and decrease a height of the UAV to dock with the docking portion, so that two or more of the charging contacts of the UAV are electrically coupled to two or more of the power-supply contacts of the docking portion.

(85) E20. The UAV system of E19, wherein: the docking portion includes four corners; the UAV further comprises a camera configured to acquire a downward image; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing two or more of the four corners of the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

(86) E21. The UAV system of E19, wherein: the UAV further comprises a camera configured to acquire a downward image, the downward image including the cross shape of the plurality of power-supply contacts on the docking portion; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing the cross shape of the plurality of power-supply contacts on the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

(87) E22. The UAV system of E19, wherein: the UAV further comprises: a camera configured to acquire a downward image, and a sensor configured to sense downward distance data; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and the downward distance data and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

(88) E23. The UAV system of E8, wherein: the cross shape, in which the plurality of power-supply contacts on the docking portion are arranged, is a first cross shape; the plurality of charging contacts of the UAV are arranged in a nine-square configuration, a first of the nine charging contacts at a center of the nine-square configuration and four of the nine charging contacts at centers of four sides of the nine-square configuration being arranged in a second cross shape, wherein dimensions of the first and second cross shapes are the same; and the UAV further comprises a controller configured to: control the UAV to fly above and align with the docking portion, and decrease a height of the UAV to dock with the docking portion, so that two or more of

the charging contacts of the UAV are electrically coupled to two or more of the power-supply contacts of the docking portion.

(89) E24. The UAV system of E23, wherein: the docking portion includes four corners; the UAV further comprises a camera configured to acquire a downward image; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing two or more of the four corners of the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

(90) E25. The UAV system of E23, wherein: the UAV further comprises: a camera configured to acquire a downward image, the downward image including the cross shape of the plurality of power-supply contacts on the docking portion; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing the cross shape of the plurality of power-supply contacts on the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

(91) E26. The UAV system of E23, wherein: the UAV further comprises: a camera configured to acquire a downward image, and a sensor configured to sense downward distance data; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and the downward distance data and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

(92) E27. Docking apparatus for charging a power storage device of an external device, the docking apparatus comprising: a docking portion for the external device to dock with; a plurality of power-supply contacts mounted on a surface of the docking portion and arranged in a nine-square configuration; and a control circuit configured to: detect whether the external device docks with the docking portion; and supply power to the power-supply contacts on the docking portion in response to detecting that the external device docks with the docking portion.

(93) E28. The docking apparatus of E27, wherein the plurality of power-supply contacts on the docking portion includes nine power-supply contacts arranged in the nine-square configuration, wherein: a first of the nine power-supply contacts is arranged at a center of the nine-square configuration, a first four of the nine power-supply contacts are arranged at centers of four sides of the nine-square configuration, and a second four of the nine power-supply contacts are arranged at four corners of the nine-square configuration.

(94) E29. The docking apparatus of E28, wherein: the first power-supply contact is configured to supply a positive voltage, and the first four power-supply contacts at the centers of the four sides are configured to supply a negative voltage.

(95) E30. The docking apparatus of E28, wherein: the first power-supply contact is configured to supply a negative voltage, and the first four power-supply contacts at the centers of the four sides are configured to supply a positive voltage.

(96) E31. The docking apparatus of E27, wherein the control circuit is configured to detect whether the external device docks with the docking portion by detecting whether two or more of the power-supply contacts on the docking portion are electrically coupled to charging contacts of the external device.

(97) E32. The docking apparatus of E31, wherein the control circuit is configured to supply power to the power-supply contacts on the docking portion in response to detecting that the external device docks with the docking portion by supplying power to at least two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the external device.

(98) E33. The docking apparatus of E32, wherein the control circuit is configured to supply power to only two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the external device.

(99) E34. An unmanned aerial vehicle (UAV) system, comprising: a UAV comprising a power storage device; and a docking station comprising: a docking portion for the UAV to dock with; a plurality of power-supply contacts mounted on a surface of the docking portion and arranged in a nine-square configuration; and a control circuit configured to: detect whether the UAV docks with the docking portion; and supply power to the power-supply contacts on the docking portion in response to detecting that the UAV docks with the docking portion.

(100) E35. The UAV system of E34, wherein the plurality of power-supply contacts on the docking portion includes nine power-supply contacts arranged in the nine-square configuration, wherein: a first of the nine power-supply contacts is arranged at a center of the nine-square configuration, a first four of the nine power-supply contacts are arranged at centers of four sides of the nine-square configuration, and a second four of the nine power-supply contacts are arranged at four corners of the nine-square configuration.

(101) E36. The UAV system of E35, wherein: the first power-supply contact is configured to supply a positive voltage, and the first four power-supply contacts at the centers of the four sides are configured to supply a negative voltage.

(102) E37. The UAV system of E35, wherein: the first power-supply contact is configured to supply a negative voltage, and the first four power-supply contacts at the centers of the four sides are configured to supply a positive voltage.

(103) E38. The UAV system of E34, wherein the control circuit is configured to detect whether the UAV docks with the docking portion by detecting whether two or more of the power-supply contacts on the docking portion are electrically coupled to two or more of the charging contacts of the UAV.

(104) E39. The UAV system of E38, wherein the control circuit is configured to supply power to the power-supply contacts on the docking portion in response to detecting that the UAV docks with the docking portion by supplying power to at least two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the UAV.

(105) E40. The UAV system of E39, wherein the control circuit is configured to supply power to only two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the UAV.

(106) E41. The UAV system of E34, wherein: a first of the power-supply contacts at a center of the nine-square configuration and a second and a third of the power-supply contacts at centers of two adjacent sides of the nine-square configuration are arranged in a first L shape; the plurality of charging contacts of the UAV are arranged in a second L shape, wherein dimensions of the first and second L shapes are the same; and the UAV further comprises a controller configured to: control the UAV to fly above and align with the docking portion, and decrease a height of the UAV to dock with the docking portion, so that the two or more of the charging contacts of the UAV are electrically coupled to the two or more of the power-supply contacts of the docking portion.

(107) E42. The UAV system of E41, wherein: the docking portion includes four corners; the UAV further comprises: a camera configured to acquire a downward image; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing two or more of the four corners of the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

(108) E43. The UAV system of E41, wherein: the UAV further comprises: a camera configured to acquire a downward image, the downward image including the nine-square configuration of the plurality of power-supply contacts on the docking portion; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing the nine-square configuration of the plurality of power-supply contacts on the docking portion based on the downward image, before decreasing the height of the UAV to dock

with the docking portion.

(109) E44. The UAV system of E41, wherein: the UAV further comprises: a camera configured to acquire a downward image, and a sensor configured to sense downward distance data; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and the downward distance data and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

(110) E45. The UAV system of E34, wherein: a first of the nine power-supply contacts at a center of the nine-square configuration and a four of the nine power-supply contacts at centers of four sides of the nine-square configuration are arranged in a first cross shape; the plurality of charging contacts of the UAV are arranged in a second cross shape, wherein dimensions of the first and second cross shapes are the same; and the UAV further comprises a controller configured to: control the UAV to fly above and align with the docking portion, and decrease a height of the UAV to dock with the docking portion, so that the two or more of the charging contacts of the UAV are electrically coupled to the two or more of the power-supply contacts of the docking portion.

(111) E46. The UAV system of E45, wherein: the docking portion includes four corners; the UAV further comprises a camera configured to acquire a downward image; and the controller is configured to control the UAV to fly above and align with the docking portion by recognizing two or more of the four corners of the docking portion, by receiving the downward image and the downward distance data and recognizing two or more of the four corners of the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

(112) E47. The UAV system of E45, wherein: the docking portion includes four corners; the UAV further comprises: a camera configured to acquire a downward image, the downward image including the nine-square configuration of the plurality of power-supply contacts on the docking portion; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing the nine-square configuration of the plurality of power-supply contacts on the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

(113) E48. The UAV system of E45, wherein: the UAV further comprises: a camera configured to acquire a downward image, and a sensor configured to sense downward distance data; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and the downward distance data and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

(114) E49. The UAV system of E34, wherein: the nine-square configuration, in which the plurality of power-supply contacts on the docking portion are arranged, is a first nine-square configuration; the plurality of charging contacts of the UAV are arranged in a second nine-square configuration, wherein dimensions of the first and second nine-square configurations are the same; and the UAV further comprises a controller configured to: control the UAV to fly above and align with the docking portion, and decrease a height of the UAV to dock with the docking portion, so that the two or more of the charging contacts of the UAV are electrically coupled to the two or more of the power-supply contacts of the docking portion.

(115) E50. The UAV system of E49, wherein: the docking portion includes four corners; the UAV further comprises a camera configured to acquire a downward image; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing two or more of the four corners of the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

(116) E51. The UAV system of E49, wherein: the UAV further comprises a camera configured to acquire a downward image, the downward image including the nine-square configuration of the

plurality of power-supply contacts on the docking portion; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and recognizing the nine-square configuration of the plurality of power-supply contacts on the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

(117) E52. The UAV system of E49, wherein: the UAV further comprises: a camera configured to acquire a downward image, and a sensor configured to sense downward distance data; and the controller is configured to control the UAV to fly above and align with the docking portion by receiving the downward image and the downward distance data and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

(118) Another aspect of the disclosure is directed to a non-transitory computer-readable medium storing instructions which, when executed, cause one or more computers to perform the methods discussed above. The computer-readable medium may include volatile or non-volatile, magnetic, semiconductor, tape, optical, removable, non-removable, or other types of computer-readable medium or computer-readable storage devices. For example, the computer-readable medium may be the storage device or the memory module having the computer instructions stored thereon, as disclosed. In some embodiments, the computer-readable medium may be a disc or a flash drive having the computer instructions stored thereon.

(119) It will be appreciated that the present disclosure is not limited to the exact construction that has been described above and illustrated in the accompanying drawings, and that various modifications and changes can be made without departing from the scope thereof. It is intended that the scope of the application should only be limited by the appended claims.

Claims

1. Docking apparatus for charging a power storage device of an external device, which includes a plurality of charging contacts arranged in a second L shape, the docking apparatus comprising: a docking portion for the external device to dock with; a plurality of power-supply contacts mounted on a surface of the docking portion and arranged in a first L shape; and a control circuit configured to: detect whether the external device docks with the docking portion; and supply power to the power-supply contacts on the docking portion in response to detecting that the second L shape of the external device docks with the first L shape of the docking portion, wherein the external device is controlled to perform: flying above and align with the docking portion, determining an angle offset value of the first L shape and aligning the second L shape with the first L shape by rotating the external device relative to the docking portion according to the angle offset value, and decreasing a height of the external device to dock with the docking portion, so that the two or more of the charging contacts of the external device are electrically coupled to the two or more of the power-supply contacts of the docking portion.
2. The docking apparatus of claim 1, wherein the plurality of power-supply contacts on the docking portion includes three power-supply contacts arranged in the first L shape, wherein: a first of the three power-supply contacts is arranged at a corner of the first L shape, and a second and a third of the three power-supply contacts are arranged at two ends of the first L shape.
3. The docking apparatus of claim 2, wherein: the first power-supply contact is configured to supply a positive voltage, and the second and third power-supply contacts are configured to supply a negative voltage.
4. The docking apparatus of claim 2, wherein: the first power-supply contact is configured to supply a negative voltage, and the second and third power-supply contacts are configured to supply a positive voltage.
5. The docking apparatus of claim 1, wherein the control circuit is configured to detect whether the

external device docks with the docking portion by detecting whether two or more of the power-supply contacts on the docking portion are electrically coupled to charging contacts of the external device.

6. The docking apparatus of claim 5, wherein the control circuit is configured to supply power to the power-supply contacts on the docking portion in response to detecting that the external device docks with the docking portion by supplying power to at least two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the external device.

7. The docking apparatus of claim 6, wherein the control circuit is configured to supply power to only two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the external device.

8. An unmanned aerial vehicle (UAV) system, comprising: a UAV comprising a power storage device and a plurality of charging contacts; and a docking station comprising: a docking portion for the UAV to dock with; a plurality of power-supply contacts mounted on a surface of the docking portion and arranged in an L shape; and a control circuit configured to: detect whether the UAV docks with the docking portion; and supply power to the power-supply contacts on the docking portion in response to detecting that the UAV docks with the docking portion; wherein: the L shape, in which the plurality of power-supply contacts on the docking portion are arranged, is a first L shape; the plurality of charging contacts of the UAV are arranged in a second L shape, wherein dimensions of the first and second L shapes are the same; and the UAV further comprises a controller configured to: control the UAV to fly above and align with the docking portion, determine an angle offset value of the first L shape; align the second L shape with the first L shape by rotating the UAV relative to the docking portion according to the angle offset value, and decrease a height of the UAV to dock with the docking portion, so that the two or more of the charging contacts of the UAV are electrically coupled to the two or more of the power-supply contacts of the docking portion.

9. The UAV system of claim 8, wherein the plurality of power-supply contacts on the docking portion include three power-supply contacts arranged in the L shape, wherein: a first of the three power-supply contacts is arranged at a corner of the L shape, and a second and a third of the three power-supply contacts are arranged at two ends of the L shape.

10. The UAV system of claim 9, wherein: the first power-supply contact is configured to supply a positive voltage, and the second and third power-supply contacts are configured to supply a negative voltage.

11. The UAV system of claim 9, wherein: the first power-supply contact is configured to supply a negative voltage, and the second and third power-supply contacts are configured to supply a positive voltage.

12. The UAV system of claim 8, wherein the control circuit is configured to detect whether the UAV docks with the docking portion by detecting whether two or more of the power-supply contacts on the docking portion are electrically coupled to two or more of the charging contacts of the UAV.

13. The UAV system of claim 12, wherein the control circuit is configured to supply power to the power-supply contacts on the docking portion in response to detecting that the UAV docks with the docking portion by supplying power to at least two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the UAV.

14. The UAV system of claim 13, wherein the control circuit is configured to supply power to only two of the two or more of the power-supply contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the UAV.

15. The UAV system of claim 8, wherein: the docking portion includes four corners; the UAV further comprises a camera configured to acquire a downward image; and the controller is configured to control the UAV to fly above and align with the docking portion, by receiving the downward image and recognizing two or more of the four corners of the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

16. The UAV system of claim 8, wherein: the UAV further comprises a camera configured to acquire a downward image, the downward image including the first L shape of the plurality of power-supply contacts on the docking portion; and the controller is configured to control the UAV to fly above and align with the docking portion, by receiving the downward image and recognizing the first L shape of the plurality of power-supply contacts on the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

17. The UAV system of claim 8, wherein: the UAV further comprises: a camera configured to acquire a downward image, and a sensor configured to sense downward distance data; and the controller is configured to control the UAV to fly above and align with the docking portion, by receiving the downward image and the downward distance data and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

18. The UAV system of claim 8, wherein the controller is configured to align the second L shape with the first L shape by rotating the UAV 90, 180, or 270 degrees relative to the docking portion.

19. The UAV system of claim 8, wherein: the L shape, in which the plurality of power-supply contacts on the docking portion are arranged, is a first L shape; the plurality of charging contacts of the UAV are arranged in a cross shape, a first of the charging contacts at a center of the cross shape and a second and a third of the charging contacts at two ends of the cross shape forming a second L shape, wherein dimensions of the first and second L shapes are the same; and the UAV further comprising a controller configured to: control the UAV to fly above and align with the docking portion, and decrease a height of the UAV to dock with the docking portion.

20. The UAV system of claim 19, wherein: the docking portion includes four corners; the UAV further comprises a camera configured to acquire a downward image; and the controller is configured to control the UAV to fly above and align with the docking portion, by receiving the downward image and recognizing two or more of the four corners of the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

21. The UAV system of claim 19, wherein: the UAV further comprises a camera configured to acquire a downward image, the downward image including the first L shape of the plurality of power-supply contacts on the docking portion; and the controller is configured to control the UAV to fly above and align with the docking portion, by receiving the downward image and recognizing the first L shape of the plurality of power-supply contacts on the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

22. The UAV system of claim 19, wherein: the UAV further comprises: a camera configured to acquire a downward image, and a sensor configured to sense downward distance data; and the controller is configured to control the UAV to fly above and align with the docking portion, by receiving the downward image and the downward distance data and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

23. The UAV system of claim 8, wherein: the L shape, in which the plurality of power-supply contacts on the docking portion are arranged, is a first L shape; the plurality of charging contacts of the UAV are arranged in a nine-square configuration, a first of the charging contacts at a center of the nine-square configuration and a second and a third of the charging contacts at centers of two adjacent sides of the nine-square configuration forming a second L shape, wherein dimensions of the first and second L shapes are the same; and the UAV further comprises a controller configured to: control the UAV to fly above and align with the docking portion to, and decrease a height of the

UAV to dock with the docking portion.

24. The UAV system of claim 23, wherein: the docking portion includes four corners; the UAV further comprises a camera configured to acquire a downward image; and the controller is configured to control the UAV to fly above and align with the docking portion, by receiving the downward image and recognizing two or more of the four corners of the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

25. The UAV system of claim 23, wherein: the UAV further comprises a camera configured to acquire a downward image, the downward image including the first L shape of the plurality of power-supply contacts on the docking portion; and the controller is configured to control the UAV to fly above and align with the docking portion, by receiving the downward image and recognizing the first L shape of the plurality of power-supply contacts on the docking portion based on the downward image, before decreasing the height of the UAV to dock with the docking portion.

26. The UAV system of claim 23, wherein: the UAV further comprises: a camera configured to acquire a downward image, and a sensor configured to sense downward distance data; and the controller is configured to control the UAV to fly above and align with the docking portion, by receiving the downward image and the downward distance data and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data, before decreasing the height of the UAV to dock with the docking portion.

27. A method for providing charging power to an unmanned aerial vehicle (UAV), the method comprising: controlling the UAV to fly above and align with a docking portion of docking apparatus, aligning a plurality of charging contacts of the UAV with a plurality of power-supply contacts on the docking portion, and decreasing a height of the UAV to dock with the docking portion, so that two or more of the charging contacts of the UAV are electrically coupled to two or more of the power-supply contacts of the docking portion; wherein: the plurality of power-supply contacts on the docking portion are arranged in a first L shape; the plurality of charging contacts of the UAV are arranged in a second L shape, wherein dimensions of the first and second L shapes are the same; determine an angle offset value of the first L shape; rotating the UAV relative to the docking portion according to the angle offset value; and aligning the plurality of charging contacts of the UAV with the plurality of power-supply contacts on the docking portion includes aligning the second L shape with the first L shape.

28. The method of claim 27, wherein the docking portion includes four corners, the UAV comprising a camera configured to acquire a downward image, wherein controlling the UAV to fly above and align with the docking portion includes: receiving the downward image; and recognizing two or more of the four corners of the docking portion based on the downward image.

29. The method of claim 27, wherein the UAV comprising a camera configured to acquire a downward image, the downward image including the first L shape of the plurality of power-supply contacts on the docking portion, wherein controlling the UAV to fly above and align with the docking portion includes: receiving the downward image; and recognizing the first L shape of the plurality of power-supply contacts on the docking portion based on the downward image.

30. The method of claim 27, wherein the docking portion includes four corners, the UAV comprising a camera configured to acquire a downward image and a sensor configured to sense downward distance data, wherein controlling the UAV to fly above and align with the docking portion includes: receiving the downward image and the downward distance data; and recognizing the plurality of power-supply contacts on the docking portion based on the downward image and the downward distance data.

31. The method of claim 27, wherein aligning the second L shape with the first L shape includes rotating the UAV 90, 180, or 270 degrees relative to the docking portion.

32. The method of claim 27, further comprising: detecting whether two or more of the power-supply contacts on the docking portion are electrically coupled to two or more of the charging contacts of the UAV; and supplying power to at least two of the two or more of the power-supply

contacts on the docking portion in response to detecting that the two or more of the power-supply contacts are electrically coupled to the charging contacts of the UAV.

33. The method of claim 32, wherein supplying power to at least two of the two or more of the power-supply contacts on the docking portion includes supplying power to only two of the two or more of the power-supply contacts on the docking portion.
