

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406064
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Vajravel; Gokul Thiruchengode et al.

Pre-boot context-based security mitigation

Abstract

An information handling system may determine a pre-boot security posture, and update an advanced configuration and power interface mitigation table with the pre-boot security posture. The system may also update a security mitigation table based on a security mitigation policy, and determine a security mitigation based on a protection flag in the advanced configuration and power interface mitigation table and the security mitigation table.

Inventors: Vajravel; Gokul Thiruchengode (Bangalore, IN), Sayyed; Ibrahim (Georgetown, TX), Hamlin; Daniel L. (Round Rock, TX)

Applicant: Dell Products L.P. (Round Rock, TX)

Family ID: 89322963

Assignee: Dell Products L.P. (Round Rock, TX)

Appl. No.: 17/747647

Filed: May 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230418947 A1	Dec. 28, 2023

Publication Classification

Int. Cl.: G06F21/57 (20130101); G06F21/55 (20130101)

U.S. Cl.:

CPC G06F21/575 (20130101); G06F21/552 (20130101); G06F21/554 (20130101);

Field of Classification Search

CPC: G06F (21/575); G06F (21/552); G06F (21/554)

USPC: 713/164

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9251384	12/2015	Potlapally	N/A	G06F 21/82
9760730	12/2016	Vajravel	N/A	N/A
9971726	12/2017	Vajravel	N/A	N/A
11151256	12/2020	Martinez et al.	N/A	N/A
2010/0050244	12/2009	Tarkhanyan	713/2	G06F 21/57
2013/0304944	12/2012	Young	710/16	G06F 9/4415
2015/0169879	12/2014	Hagiuda	726/26	G06F 11/368
2017/0063895	12/2016	Abuelsaad	N/A	H04L 63/105
2017/0256323	12/2016	Taniuchi	N/A	G11C 29/08
2019/0294800	12/2018	Andrews	N/A	G06F 21/602
2020/0125497	12/2019	Shi	N/A	G06F 12/14
2020/0242253	12/2019	Noel	N/A	G06F 21/577
2020/0310826	12/2019	Liu	N/A	G06F 21/572
2020/0372156	12/2019	Sayyed et al.	N/A	N/A
2021/0243245	12/2020	Vajravel et al.	N/A	N/A
2022/0311792	12/2021	Nakkabi	N/A	H04L 63/0861

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2021251950	12/2020	WO	G06F 12/0875

Primary Examiner: Mai; Kevin S

Attorney, Agent or Firm: Larson Newman, LLP

Background/Summary

FIELD OF THE DISCLOSURE

(1) The present disclosure generally relates to information handling systems, and more particularly relates to pre-boot context-based security mitigation.

BACKGROUND

(2) As the value and use of information continues to increase, individuals and businesses seek additional ways to process and store information. One option is an information handling system. An information handling system generally processes, compiles, stores, or communicates information or data for business, personal, or other purposes. Technology and information handling needs and requirements can vary between different applications. Thus, information handling systems can also vary regarding what information is handled, how the information is handled, how much information is processed, stored, or communicated, and how quickly and efficiently the

information can be processed, stored, or communicated. The variations in information handling systems allow information handling systems to be general or configured for a specific user or specific use such as financial transaction processing, airline reservations, enterprise data storage, or global communications. In addition, information handling systems can include a variety of hardware and software resources that can be configured to process, store, and communicate information and can include one or more computer systems, graphics interface systems, data storage systems, networking systems, and mobile communication systems. Information handling systems can also implement various virtualized architectures. Data and voice communications among information handling systems may be via networks that are wired, wireless, or some combination.

SUMMARY

(3) An information handling system may determine a pre-boot security posture, and update an advanced configuration and power interface mitigation table with the pre-boot security posture. The system may also update a security mitigation table based on a security mitigation policy, and determine a security mitigation based on a protection flag in the advanced configuration and power interface mitigation table and the security mitigation table.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) It will be appreciated that for simplicity and clarity of illustration, elements illustrated in the Figures are not necessarily drawn to scale. For example, the dimensions of some elements may be exaggerated relative to other elements. Embodiments incorporating teachings of the present disclosure are shown and described with respect to the drawings herein, in which:

(2) FIG. 1 is a block diagram illustrating an information handling system according to an embodiment of the present disclosure;

(3) FIG. 2 is a block diagram illustrating an example of a system for pre-boot context-based security mitigation, according to an embodiment of the present disclosure;

(4) FIG. 3 is a block diagram illustrating an example of a system for pre-boot context-based security mitigation, according to an embodiment of the present disclosure;

(5) FIG. 4 is a block diagram illustrating an example of a system for pre-boot context-based security mitigation, according to an embodiment of the present disclosure;

(6) FIG. 5 is a block diagram illustrating an example of a system for pre-boot context-based security mitigation, according to an embodiment of the present disclosure; and

(7) FIGS. 6-7 are flowcharts illustrating an example of a method for pre-boot context-based security mitigation, according to an embodiment of the present disclosure.

(8) The use of the same reference symbols in different drawings indicates similar or identical items.

DETAILED DESCRIPTION OF THE DRAWINGS

(9) The following description in combination with the Figures is provided to assist in understanding the teachings disclosed herein. The description is focused on specific implementations and embodiments of the teachings and is provided to assist in describing the teachings. This focus should not be interpreted as a limitation on the scope or applicability of the teachings.

(10) FIG. 1 illustrates an embodiment of an information handling system **100** including processors **102** and **104**, a chipset **110**, a memory **120**, a graphics adapter **130** connected to a video display **134**, a non-volatile RAM (NV-RAM) **140** that includes a basic input and output system/extensible firmware interface (BIOS/EFI) module **142**, a disk controller **150**, a hard disk drive (HDD) **154**, an optical disk drive **156**, a disk emulator **160** connected to a solid-state drive (SSD) **164**, an input/output (I/O) interface **170** connected to an add-on resource **174** and a trusted platform module (TPM) **176**, a network interface **180**, and a baseboard management controller (BMC) **190**.

Processor **102** is connected to chipset **110** via processor interface **106**, and processor **104** is connected to the chipset via processor interface **108**. In a particular embodiment, processors **102** and **104** are connected together via a high-capacity coherent fabric, such as a HyperTransport link, a QuickPath Interconnect, or the like. Chipset **110** represents an integrated circuit or group of integrated circuits that manage the data flow between processors **102** and **104** and the other elements of information handling system **100**. In a particular embodiment, chipset **110** represents a pair of integrated circuits, such as a northbridge component and a southbridge component. In another embodiment, some or all of the functions and features of chipset **110** are integrated with one or more of processors **102** and **104**.

(11) Memory **120** is connected to chipset **110** via a memory interface **122**. An example of memory interface **122** includes a Double Data Rate (DDR) memory channel and memory **120** represents one or more DDR Dual In-Line Memory Modules (DIMMs). In a particular embodiment, memory interface **122** represents two or more DDR channels. In another embodiment, one or more of processors **102** and **104** include a memory interface that provides a dedicated memory for the processors. A DDR channel and the connected DDR DIMMs can be in accordance with a particular DDR standard, such as a DDR3 standard, a DDR4 standard, a DDR5 standard, or the like.

(12) Memory **120** may further represent various combinations of memory types, such as Dynamic Random Access Memory (DRAM) DIMMs, Static Random Access Memory (SRAM) DIMMs, non-volatile DIMMs (NV-DIMMs), storage class memory devices, Read-Only Memory (ROM) devices, or the like. Graphics adapter **130** is connected to chipset **110** via a graphics interface **132** and provides a video display output **136** to a video display **134**. An example of a graphics interface **132** includes a Peripheral Component Interconnect-Express (PCIe) interface and graphics adapter **130** can include a four-lane (x4) PCIe adapter, an eight-lane (x8) PCIe adapter, a 16-lane (x16) PCIe adapter, or another configuration, as needed or desired. In a particular embodiment, graphics adapter **130** is provided down on a system printed circuit board (PCB). Video display output **136** can include a Digital Video Interface (DVI), a High-Definition Multimedia Interface (HDMI), a DisplayPort interface, or the like, and video display **134** can include a monitor, a smart television, an embedded display such as a laptop computer display, or the like.

(13) NV-RAM **140**, disk controller **150**, and I/O interface **170** are connected to chipset **110** via an I/O channel **112**. An example of I/O channel **112** includes one or more point-to-point PCIe links between chipset **110** and each of NV-RAM **140**, disk controller **150**, and I/O interface **170**. Chipset **110** can also include one or more other I/O interfaces, including a PCIe interface, an Industry Standard Architecture (ISA) interface, a Small Computer Serial Interface (SCSI) interface, an Inter-Integrated Circuit (I^{sup}.2C) interface, a System Packet Interface (SPI), a Universal Serial Bus (USB), another interface, or a combination thereof. NV-RAM **140** includes BIOS/EFI module **142** that stores machine-executable code (BIOS/EFI code) that operates to detect the resources of information handling system **100**, to provide drivers for the resources, to initialize the resources, and to provide common access mechanisms for the resources. In one embodiment, BIOS/EFI module **142** includes a unified extensible firmware interface (UEFI) service **145** to capture the state of BIOS security indicators or pre-boot security indicators. The functions and features of BIOS/EFI module **142** will be further described below.

(14) Disk controller **150** includes a disk interface **152** that connects the disk controller to a hard disk drive (HDD) **154**, to an optical disk drive (ODD) **156**, and to disk emulator **160**. An example of disk interface **152** includes an Integrated Drive Electronics (IDE) interface, an Advanced Technology Attachment (ATA) such as a parallel ATA (PATA) interface or a serial ATA (SATA) interface, a SCSI interface, a USB interface, a proprietary interface, or a combination thereof. Disk emulator **160** permits SSD **164** to be connected to information handling system **100** via an external interface **162**. An example of external interface **162** includes a USB interface, an institute of electrical and electronics engineers (IEEE) **1394** (Firewire) interface, a proprietary interface, or a combination thereof. Alternatively, SSD **164** can be disposed within information handling system

100.

(15) I/O interface **170** includes a peripheral interface **172** that connects the I/O interface to add-on resource **174**, to TPM **176**, and to network interface **180**. Peripheral interface **172** can be the same type of interface as I/O channel **112** or can be a different type of interface. As such, I/O interface **170** extends the capacity of I/O channel **112** when peripheral interface **172** and the I/O channel are of the same type, and the I/O interface translates information from a format suitable to the I/O channel to a format suitable to the peripheral interface **172** when they are of a different type. Add-on resource **174** can include a data storage system, an additional graphics interface, a network interface card (NIC), a sound/video processing card, another add-on resource, or a combination thereof. Add-on resource **174** can be on a main circuit board, on a separate circuit board or add-in card disposed within information handling system **100**, a device that is external to the information handling system, or a combination thereof.

(16) Network interface **180** represents a network communication device disposed within information handling system **100**, on a main circuit board of the information handling system, integrated onto another component such as chipset **110**, in another suitable location, or a combination thereof. Network interface **180** includes a network channel **182** that provides an interface to devices that are external to information handling system **100**. In a particular embodiment, network channel **182** is of a different type than peripheral interface **172**, and network interface **180** translates information from a format suitable to the peripheral channel to a format suitable to external devices.

(17) In a particular embodiment, network interface **180** includes a NIC or host bus adapter (HBA), and an example of network channel **182** includes an InfiniBand channel, a Fibre Channel, a Gigabit Ethernet channel, a proprietary channel architecture, or a combination thereof. In another embodiment, network interface **180** includes a wireless communication interface, and network channel **182** includes a Wi-Fi channel, a near-field communication (NFC) channel, a Bluetooth® or Bluetooth-Low-Energy (BLE) channel, a cellular based interface such as a Global System for Mobile (GSM) interface, a Code-Division Multiple Access (CDMA) interface, a Universal Mobile Telecommunications System (UMTS) interface, a Long-Term Evolution (LTE) interface, or another cellular based interface, or a combination thereof. Network channel **182** can be connected to an external network resource (not illustrated). The network resource can include another information handling system, a data storage system, another network, a grid management system, another suitable resource, or a combination thereof.

(18) BMC **190** is connected to multiple elements of information handling system **100** via one or more management interface **192** to provide out-of-band monitoring, maintenance, and control of the elements of the information handling system. As such, BMC **190** represents a processing device different from processor **102** and processor **104**, which provides various management functions for information handling system **100**. For example, BMC **190** may be responsible for power management, cooling management, and the like. The term BMC is often used in the context of server systems, while in a consumer-level device a BMC may be referred to as an embedded controller (EC). A BMC included at a data storage system can be referred to as a storage enclosure processor. A BMC included at a chassis of a blade server can be referred to as a chassis management controller and embedded controllers included at the blades of the blade server can be referred to as blade management controllers. Capabilities and functions provided by BMC **190** can vary considerably based on the type of information handling system. BMC **190** can operate in accordance with an Intelligent Platform Management Interface (IPMI). Examples of BMC **190** include an Integrated Dell® Remote Access Controller (iDRAC).

(19) Management interface **192** represents one or more out-of-band communication interfaces between BMC **190** and the elements of information handling system **100**, and can include an Inter-Integrated Circuit (I2C) bus, a System Management Bus (SMBUS), a Power Management Bus (PMBUS), a Low Pin Count (LPC) interface, a serial bus such as a Universal Serial Bus (USB) or a

Serial Peripheral Interface (SPI), a network interface such as an Ethernet interface, a high-speed serial data link such as a PCIe interface, a Network Controller Sideband Interface (NC-SI), or the like. As used herein, out-of-band access refers to operations performed apart from a BIOS/operating system execution environment on information handling system **100**, that is apart from the execution of code by processors **102** and **104** and procedures that are implemented on the information handling system in response to the executed code.

(20) BMC **190** operates to monitor and maintain system firmware, such as code stored in BIOS/EFI module **142**, option ROMs for graphics adapter **130**, disk controller **150**, add-on resource **174**, network interface **180**, or other elements of information handling system **100**, as needed or desired. In particular, BMC **190** includes a network interface **194** that can be connected to a remote management system to receive firmware updates, as needed or desired. Here, BMC **190** receives the firmware updates, stores the updates to a data storage device associated with the BMC, and transfers the firmware updates to the NV-RAM of the device or system that is the subject of the firmware update, thereby replacing the currently operating firmware associated with the device or system, and reboots information handling system, whereupon the device or system utilizes the updated firmware image.

(21) BMC **190** utilizes various protocols and application programming interfaces (APIs) to direct and control the processes for monitoring and maintaining the system firmware. An example of a protocol or API for monitoring and maintaining the system firmware includes a graphical user interface (GUI) associated with BMC **190**, an interface defined by the Distributed Management Taskforce (DMTF) (such as a Web Services Management (WSMan) interface, a Management Component Transport Protocol (MCTP) or, a Redfish® interface), various vendor-defined interfaces (such as a Dell EMC Remote Access Controller Administrator (RACADM) utility, a Dell EMC OpenManage Enterprise, a Dell EMC OpenManage Server Administrator (OMSS) utility, a Dell EMC OpenManage Storage Services (OMSS) utility, or a Dell EMC OpenManage Deployment Toolkit (DTK) suite), a BIOS setup utility such as invoked by a “F2” boot option, or another protocol or API, as needed or desired.

(22) In a particular embodiment, BMC **190** is included on a main circuit board (such as a baseboard, a motherboard, or any combination thereof) of information handling system **100** or is integrated onto another element of the information handling system such as chipset **110**, or another suitable element, as needed or desired. As such, BMC **190** can be part of an integrated circuit or a chipset within information handling system **100**. An example of BMC **190** includes an iDRAC or the like. BMC **190** may operate on a separate power plane from other resources in information handling system **100**. Thus BMC **190** can communicate with the management system via network interface **194** while the resources of information handling system **100** are powered off. Here, information can be sent from the management system to BMC **190** and the information can be stored in a RAM or NV-RAM associated with the BMC. Information stored in the RAM may be lost after power-down of the power plane for BMC **190**, while information stored in the NV-RAM may be saved through a power-down/power-up cycle of the power plane for the BMC.

(23) Information handling system **100** can include additional components and additional busses, not shown for clarity. For example, information handling system **100** can include multiple processor cores, audio devices, and the like. While a particular arrangement of bus technologies and interconnections is illustrated for the purpose of example, one of skill will appreciate that the techniques disclosed herein are applicable to other system architectures. Information handling system **100** can include multiple central processing units (CPUs) and redundant bus controllers. One or more components can be integrated together. Information handling system **100** can include additional buses and bus protocols, for example, I2C and the like. Additional components of information handling system **100** can include one or more storage devices that can store machine-executable code, one or more communications ports for communicating with external devices, and various input and output (I/O) devices, such as a keyboard, a mouse, and a video display.

(24) For purpose of this disclosure information handling system **100** can include any instrumentality or aggregate of instrumentalities operable to compute, classify, process, transmit, receive, retrieve, originate, switch, store, display, manifest, detect, record, reproduce, handle, or utilize any form of information, intelligence, or data for business, scientific, control, entertainment, or other purposes. For example, information handling system **100** can be a personal computer, a laptop computer, a smartphone, a tablet device or other consumer electronic device, a network server, a network storage device, a switch, a router, or another network communication device, or any other suitable device and may vary in size, shape, performance, functionality, and price. Further, information handling system **100** can include processing resources for executing machine-executable code, such as processor **102**, a programmable logic array (PLA), an embedded device such as a System-on-a-Chip (SoC), or other control logic hardware. Information handling system **100** can also include one or more computer-readable media for storing machine-executable code, such as software or data.

(25) Threats to the security of an information handling system may require alignment between hardware security and software security techniques to keep users, data, and devices protected. The operating system alone cannot protect an information handling system from the wide range of tools and techniques used by malicious intruders. Once inside the information handling system, intruders can be difficult to detect while they are engaging in nefarious activities from stealing important data or credentials to implanting malware into low-level device firmware that becomes difficult to identify and remove. While there are multiple ways to introduce security threats during the pre-boot stage of an information handling system, there is no comprehensive mechanism to notify the operating system of the information handling systems for context-based mitigation action based on these security threats as disclosed herein. As such the present disclosure includes a system and method with threat intelligence and analytics for a rapid assessment of an attacker's behavior, eviction, and remediation which may prevent a bad actor from gaining access to an information handling system.

(26) FIG. 2 shows a system **200** of a system for pre-boot context-based security mitigation applied to a legacy client and native applications. System **200** may be configured to determine if there is a modification to a resource or a pre-boot indicator of attack (IOA) during a driver execution environment (DXE) phase of a boot process. System **200** may derive context out of IOA and translate such to security mitigations such as choosing authorization levels and application restrictions. System **200** includes an information handling system **100** and information technology device management (ITDM) **210**. Information handling system **100** includes a UEFI environment **290**, an operating system kernel environment **275**, and a user environment **270**. UEFI environment **290** includes UEFI service **145** and an advanced configuration and power interface (ACPI) mitigation table **292**. Operating system kernel environment **275** includes an operating system kernel module **285**. User environment **270** includes a logon service **225**, applications **230a-230n**, an operating system service **255**, and a legacy client security mitigation table **293**.

(27) ITDM **210** may be implemented as an enterprise-class device management solution for managing information handling system assets, whether owned by the enterprise, an employee, or an end-user. Functionality performed by ITDM **210** may include over-the-air installation, distribution, and upgrade of enterprise and personal applications, data, and configuration settings for a diverse mix of information handling system types including any suitable type of mobile device. ITDM **210** may be located locally or remotely from information handling system **100**. Examples of ITDM **210** include Microsoft Endpoint Manager®, Dell Wyse Management Suite®, or similar. In at least one embodiment, ITDM **210** includes configuration information and/or policy in handling modification to a resource and/or IOA associated with information handling system **100**. The policy may include one or more rules in determining the IOA, its corresponding security mitigation, and the application of the security mitigation. ITDM **210** may transmit the configuration information and/or security mitigation policy to operating system service **255**, a workspace service, and/or VDI

connector during an operating system phase of the information handling system.

(28) UEFI environment **290** represents an operating firmware of information handling system **100** and includes UEFI code, such as BIOS/EFI **142**. UEFI code may be operable to detect the resources of information handling system **205**, to provide drivers for, to initialize, and to access said resources. These resources may include hardware devices, components, firmware, and software applications such as applications **230a-230n**. In line with this, UEFI service **145** may be configured to load early during the boot process and determine the pre-boot security posture of the resources of information handling system **100**, such as capture the state of the BIOS security indicators which includes IOAs and update ACPI mitigation table **292** accordingly. The pre-boot security posture of information handling system **100** may be based on one or more parameters or attributes of its resources.

(29) For example, UEFI service **145** may detect whether there is a new external device attached to information handling system **100**, whether a pre-determined threshold of a number of BIOS login tries is reached, whether the chassis of information handling system **100** has been opened, whether a new internal device is attached to the information handling system **100** after its chassis was opened, etc. UEFI service **145** may communicate the pre-boot security posture to operating system service **255** via interface **280** which may use the ACPI standard. For example, UEFI service **145** may communicate the pre-boot security posture using Windows® Management Instrumentation™, Open LINUX Management Infrastructure™, etc. This communication may be performed during the boot device selection phase of the boot process.

(30) UEFI service **145** may be configured to capture the state of BIOS security indicators and update ACPI mitigation table **292**, which is an ACPI table stored in an ACPI namespace of UEFI environment **290** during the DXE phase of the boot process. ACPI mitigation table **292** includes a protection flag field, also referred to as a security flag, which may indicate the presence of IOA and/or security mitigation. The value of the protection flag field may be used to elect whether to enable and/or disable a security feature. For illustration purposes, a portion of ACPI mitigation table **292** and the associated protection flag table is shown below:

(31) TABLE-US-00001 ACPI Mitigation Table

Byte	Field	Length	Offset	Description
Signature 4 0	Signature of the ACPI mitigation table	Length 4 4	Length, in bytes, of the ACPI mitigation table.	Revision 1 8 A revision number of the ACPI mitigation table
Checksum 1 9	Checksum of the ACPI mitigation table, which may sum to zero	OEMID 6 10	Original equipment manufacturer (OEM) identifier (ID)	OEM Table ID 8 16 Manufacturer model ID
OEM Revision 4 24	OEM revision for supplied OEM table ID	Creator ID 4 28	Vendor ID of the ACPI source language (ASL) compiler utility that created the ACPI mitigation table	Creator Revision 4 32
Revision of the ASL compiler utility that created the ACPI mitigation table	Device ID 4 36	Hardware attested identification (e.g., derived device ID, device rooted ID, seeded consolidation of hardware device IDs, etc.)	Protection Flag 4 40	Container of a bitmask of the system implemented ACPI mitigation protections. Bits in this field represent that certain protections/enforcements are enabled and active for firmware executed inside BIOS
The protection flag may also indicate pre-boot security state information of the information handling system, such as an IOA detected. See the protection flag table for a detailed description of this field.				

(32) TABLE-US-00002 Protection Flag Table

Bit	Length	Offset	Description
1 0	Chassis intrusion detected	1 1	Data wipe detected
1 2	SPI probing detected	1 4	Boot interface (e.g. Thunderbolt® interface) boot path security disabled
1 8	Boot interruption detected	1 10	UEFI secure boot disabled
1 12	Information handling system booting after a restore/repair attempt . . . etc.	1 14	Secure boot key wipe detected
1 18	Windows system management mode mitigation table disabled		

(33) Operating system kernel environment **275**, also referred to as a kernel space, may include core operating system functions that provide a low-level abstraction layer for resources such as processor, memory, and peripherals. In addition, operating system kernel environment **275** may include security attributes and address spaces of an operating system that are typically hidden from

user-level applications in user environment **270**. Operating system kernel environment **275** may implement one or more operating system kernel modules such as operating system kernel module **285** for managing said resources. Accordingly, operating system kernel module **285** may include APIs, drivers, etc. to manage the interaction between resources in operating system kernel environment **275** and user environment **270** in accordance with a communication protocol. This interaction may be hidden from applications **230a-230n**, which are native applications running in user environment **270**.

(34) User environment **270**, also referred to as a user space, may include applications and non-core operating system functions. In addition, user environment **270** includes operating system service **255** which may be configured as a system startup service and may be loaded during the startup of the operating system. In addition, operating system service **255** may be configured to communicate with UEFI service **145** via interface **280** to receive and/or transmit information regarding the security posture and corresponding security mitigation. The security mitigation may be a function/method or action for the security or integrity of the resources of information handling system **100**. Operating system service **255** may be loaded at startup of the operating system prior to logon service **225** and configured to retrieve and cache ITDM configuration and store it in legacy client security mitigation table **293** which is a mapping of pre-boot IOA to one or more legacy client security mitigations. For illustration purposes, a portion of legacy client security mitigation table **293** also referred to herein as table **1** is shown below:

(35) TABLE-US-00003 TABLE 1 Client Security Mitigation Table Pre-boot Security State Information (via ACPI Recommended Actions from the Operating System Mitigation Table)

Service	Chassis intrusion	Notify ITDM	Operating system mitigation
	→	Allow only signed drivers (e.g. Windows Logo Kit™ signed drivers)	for loading; block application instrumentation (e.g. App-hooking via Load AppInit); high entropy address space layout randomization
Security of boot interface/port	is Disable the boot interface/port (e.g. Thunderbolt/USB-4 port)	disabled	If the port can't be disabled, block enumerating the devices connected to that port
Chassis intrusion	+	a new internal Disable automatic run or automatically play feature of a device is connected	program or application
Operating system mitigation	→	Allow only signed binaries; disallow system calls directly to native system services	

(36) Operating system service **255** may be configured to read data stored in ACPI mitigation table **292** via an ACPI read through interface **280**, wherein the ACPI Mitigation table may be located in the ACPI namespace of information handling system **100**. In particular, operating system service **255** may be configured to determine the status of one or more protection flags in the ACPI Mitigation table and corresponding security mitigation. Operating system service **255** may submit information associated with the security mitigation to the operating system.

(37) As part of the security mitigation, operating system service may provide logon service **225** of a particular logon type and/or credentials to be used by a user to log into information handling system **100**. Logon service **225**, such as Windows logon service may be configured to authenticate an identity of a user to determine whether the user can log into information handling system **100**. For example, logon service **225** may be configured to prompt a user to insert a smart card into a smart card reader associated with information handling system **205**. Logon service **225** may then prompt the user to enter a personal identification number instead of a username and password via a graphical user interface. In another example, operating system service **255** may prevent one or more applications **230a-230n** from running.

(38) FIG. 3 shows a system **300** of a system for pre-boot context-based security mitigation applied to a modern client and isolated native applications. System **300** may be configured to derive context out of pre-boot IOA and translate such to security mitigations such as choosing authorization levels and application restrictions. System **300** includes an information handling system **100** and ITDM) **210**. Information handling system **100** includes UEFI environment **290**, operating system kernel environment **275**, and user environment **270**. UEFI environment **290**

includes UEFI service **145** and ACPI mitigation table **292**. Operating system kernel environment **275** includes operating system kernel module **285**. User environment **270** includes logon service **225**, operating system service **255**, workspace **340**, workspace agent **350**, workspace host daemon **365**, and a modern client security mitigation table **370**. Workspace **340** includes applications **345a-345n** which are native applications running in isolation inside workspace **340**.

(39) Workspace host daemon **365** may be a persistent process that is configured to manage workspace **340**. Workspace host daemon **365** may also be configured to support security features of workspace **340** such as workspace encryption, workspace attestation, workspace-to-device anchoring, etc. Workspace host daemon **365** may control operations performed in workspace **340** through interaction with workspace agent **350**. Workspace host daemon **365** may issue commands to control the operation of workspace **340** via workspace agent **350**. For example, various commands can start or stop workspace **340**, perform configuration management, add or remove users to workspace **340**, add or remove applications that are isolated in workspace **340**, etc.

(40) Workspace **340** may be configured to provide users with secured access to applications **345a-345n**. Workspace **340** may be a sandboxed container that provides a secure isolation boundary between the host operating system and the applications **345a-345n** which are native applications running inside workspace **340**. Examples of workspace technologies include Workspace ONE Intelligent Hub™ from VMWARE, INC. and Dell® Hybrid Client™ from Dell Technologies Inc., Microsoft® HyperV® container, Windows Sandbox™, among others.

(41) Workspace agent **350** may be configured to receive information associated with the pre-boot security posture of information handling system **100** from operating system service **255**. Based on the received information, workspace agent **350** may be configured to apply the security mitigation based on a modern client security mitigation table **370** which is a mapping of pre-boot IOA mapped to corresponding security mitigation for a modern client. A modern client may be a client that includes an environment where an application can be run in isolation from the host machine. The security mitigation may also be applied to containerized isolated applications in workspace **340** such as applications **345a-345n**. For example, workspace agent **350** may prevent one or all of applications **345a-345n** from running/playing in workspace **340**. For illustration purposes, a portion of modern client security mitigation table **370** also referred to herein as table **2** is shown below:

(42) TABLE-US-00004 TABLE 2 Modern Client Security Mitigation Table Pre-boot Security State Information (via ACPI Recommended Actions from the Operating System Service to the Mitigation Table) Workspace Agent Chassis Intrusion Disable clipboard and file-sharing across workspace and local applications Security of boot interface/port is Disable mapping of the devices to the workspaces that are connected via disabled the boot interface/port (e.g. Thunderbolt/USB-4 port) Chassis intrusion + new internal Migrate workspaces from local machine (virtual machine/container) to device connected cloud Disable the clipboard and file sharing across workspace and local applications

(43) FIG. 4 shows a system **400** of a system for pre-boot context-based security mitigation applied to a thin client and cloud-based applications. System **400** may be configured to derive context out of pre-boot IOA and translate such to security mitigations such as choosing authorization levels and application restrictions. System **300** includes an information handling system **100**, ITDM **210**. Information handling system **100** includes UEFI environment **290**, operating system kernel environment **275**, and user environment **270**. UEFI environment **290** includes UEFI service **145** and ACPI mitigation table **292**. Operating system kernel environment **275** includes operating system kernel module **285**. User environment **270** includes logon service **225**, operating system service **255**, a virtual desktop infrastructure (VDI) connector **450**, and a thin client security mitigation table **440**. Server **420** includes a virtual machine **425** which further includes applications **430a-430n**.

(44) VDI environments may include any one or more information handling systems, such as server **420**. A virtual environment, such as a VDI, separates a desktop environment and its associated

software in a data center or server from the information handling system that is used to access the desktop environment. A “virtual desktop” may refer to any number of methodologies including server-based computing (SBC) where a number of users share the desktop of a server-based operating system, VDI where each user gets their own virtual machine, such as virtual machine 222 which typically runs a client operating system, and application virtualization technologies that concentrate more closely on making specific applications, such as applications 430a-430n, being hosted on a remote system or streamed to the user's local system.

(45) Server 420 may include a hypervisor which is a hardware and/or software component that creates, runs, and manages virtual machines, such as virtual machine 222. Virtual machine 222 is a virtualized instance of a computer that typically runs a client operating system and one or more applications such as applications 430a-430n. Applications 430a-430n may be software-as-a-service (SaaS) applications served to a user over network 415. SaaS can provide a user using a thin client with software and data stored at a remote location. In certain embodiments, network 415 may be a public network, such as the Internet, a physical private network, a wireless network, a virtual private network (VPN), or any combination thereof.

(46) VDI connector 450 may be configured to establish and maintain a remote session with server 420 or virtual machine 425 that hosts applications 430a-430n via network 415. While VDI connector 450 may be a VMWARE HORIZON client, a CITRIX® WORKSPACE APP, a MICROSOFT REMOTE DESKTOP client, etc. In addition, VDI connector 450 may be configured to communicate with operating system service 255 and receive information associated with the pre-boot security posture and corresponding security mitigation to information handling system 100. Operating system service 255 may determine the corresponding security mitigation based on thin client security mitigation table 440. For example, operating system service 255 may direct VDI connector 450 to put virtual machine 425 in restricted mode. For illustration purposes, thin client security mitigation table 440 may be a mapping of thin client security mitigation to pre-boot IOA. For illustration purposes, a portion of thin client security mitigation table 440, also referred to herein as table 3, is shown below:

(47) TABLE-US-00005 TABLE 3 Thin Client Security Mitigation Table Pre-boot Security State Information (via ACPI Mitigation Table) Recommended Actions from Operating System Service Chassis Intrusion Notify ITDM Move thin client to kiosk mode (restricted) and allow native VDI connector, not web-based VDI connector Enforce smartcard or two-factor authentication for the VDI login An ACPI table that allows programs to Operating system mitigation → Allow only signed drivers execute every time the information handling (e.g. Windows Logo Kit™ signed drivers) for loading; system boots, such as Windows Platform block application instrumentation (e.g. App-hooking via Binary Table™, was moved from disabled Load AppInit); high entropy address space layout to enabled randomization Allow only signed native VDI connectors and their plugins are loaded Chassis intrusion + new internal device <All recommended actions of ‘chassis intrusion’> connected Disable local drive mapping for the VDI connection/link

(48) FIG. 5 shows a system 500 of a system for pre-boot context-based security mitigation applied to various clients. In this example, system 500 includes features of systems 200, 300, and 400. As such, system 500 may be configured to derive context out of pre-boot IOA and translate such to security mitigations such as choosing authorization levels and application restrictions to legacy, modern, and thin clients accordingly. System 500 includes an information handling system 100, ITDM 210. Information handling system 100 includes UEFI environment 290, operating system kernel environment 275, and user environment 270. UEFI environment 290 includes UEFI service 145 and ACPI mitigation table 292. Operating system kernel environment 275 includes operating system kernel module 285 and a kernel driver 505. User environment 270 includes logon service 225, operating system service 255, workspace agent 350, workspace 340, workspace host daemon 365, VDI connector 450, and a thin client security mitigation table 440. Server 420 includes a virtual machine 425 which further includes applications 430a-430n.

(49) Kernel driver **505** may be installed as a boot-start driver to read and cache ACPI mitigation table **292**. Kernel driver **505** may be communicatively coupled to operating system service **255**. In one embodiment, kernel driver **505** may receive a request for information in ACPI mitigation table **292** from operating system service **255** instead of retrieving such information instead. This may free operating system service **255** to perform other functions. Kernel driver **505** may also be configured to apply the security mitigation as directed by operating system service **255**, such as blocking the Thunderbolt/USB-4 port, blocking device enumeration connected to a certain port, etc.

(50) In various embodiments, information handling system **100** may not include each of the components shown in FIG. 5. Additionally, or alternatively, information handling system **100** may include various additional components in addition to those that are shown in FIG. 5. Furthermore, some components that are represented as separate components in FIG. 5 may in certain embodiments instead be integrated with other components. For example, in certain embodiments, all or a portion of the functionality provided by the illustrated components may instead be provided by components integrated into one or more processor(s) as a system-on-a-chip.

(51) FIG. 6 shows a flowchart of a method **600** for pre-boot context-based security mitigation based on the client scenarios of an information handling system. By default, the method may apply the security mitigation based on a security mitigation table, such as table **1**. However, the method **600** may also determine whether the information handling system includes a workspace and/or a thin client and apply the security mitigation using table **2** and/or table **3** accordingly. For example, if the information handling system includes a workspace, then the method may apply security mitigation based on a security mitigation table, such as table **1** and/or table **2**. Method **600** may take place during pre-boot phase **605** and operating system phase **610**. Method **600** may be performed by a UEFI service **145**, operating system service **255**, and workspace agent **350** of FIG. 5. However, while the embodiments of the present disclosure are described in system **500** of FIG. 5, it should be recognized that other systems may be utilized to perform the described method. One of skill in the art will appreciate that this flowchart explains a typical example that can be extended to advanced applications or services in practice.

(52) Method **600** may be configured to handle IOA in a legacy client, a modern client, and a thin client. For example, a security mitigation, which is operating system agnostic, may be performed on native applications, web applications, containerized applications, and VDI client/connector based on an IOA. At block **615**, ITDM **210** may transmit configuration information and/or a security mitigation policy to information handling system. In particular, ITDM **210** may transmit the configuration information and/or a security mitigation policy to operating system service **255**, workspace agent **350**, and/or VDI connector **460** based on their presence in the system. The configuration information and/or security mitigation policy may be in various formats such as an extensible markup language™, JavaScript Object Notation™, or a similar format. The configuration information and/or a security mitigation policy for a legacy client, a modern client, and a thin client may vary. As such, ITDM **210** may transmit a first configuration information and/or a security mitigation policy to operating system service **255**, a second configuration information and/or a security mitigation policy to workspace agent **350**, and a third configuration information and/or a security mitigation policy to VDI connector **460**.

(53) At block **620**, UEFI service **145**, which may be inside the PEI/DXE module of BIOS/EFI **142**, may capture the pre-boot security posture of information handling system by determining the pre-boot security state of one or more BIOS and/or pre-boot security indicators which includes IOAs during the PEI and/or DXE phase of the boot process. At block **625**, UEFI service **145** may update an ACPI mitigation table based on the pre-boot security posture of the information handling system. For example, UEFI service may update the security state of the BIOS and/or pre-boot security indicator(s) and IOA(s). At block **630**, workspace agent **350** may receive configuration information and/or security mitigation policy from ITDM **210** and cache it in workspace client

mitigation table.

(54) At block **635**, operating system service **255** may be loaded during the operating system startup prior to a logon screen. Operating system service **255** may retrieve or receive configuration information and/or security mitigation policy **615** from ITDM **210** and cache it in the legacy client security mitigation table. The legacy client security mitigation table may include a mapping of one or more mitigation actions mapped to an IOA. The mitigation action may include using an operating system method and/or APIs.

(55) At block **640**, operating system service **255** may retrieve the information stored in the ACPI mitigation table via an ACPI read function. At block **645**, operating system service **255** may determine the pre-boot security posture of the information handling system by reading and/or parsing the retrieved information. For example, operating system service **255** may determine the value of the protection flags in the ACPI mitigation table to determine the pre-boot security posture of the information handling system. Said information may then be cached. The pre-boot security posture may relate to the security status of the external and/or internal devices associated with the information handling system at pre-boot. The pre-boot security posture may also include IOAs associated with the resources of the information handling system.

(56) In addition to the information retrieved from the ACPI mitigation table, operating system service **255** may determine additional IOA via other sources such as trusted platform module platform configuration registers, and health logs from a third party such as Microsoft health attestation, etc. An IOA may be digital or physical evidence that a security attack is likely to occur. Examples of the IOAs include chassis intrusion or disabling of a security feature.

(57) At block **650**, operating system service **255** may enumerate external and/or internal devices that are attached to the information handling system based on the value of the protection flags. The method proceeds to block **705** of FIG. 7. At block **655**, VDI connector **460** may receive configuration information/security mitigation policy from ITDM **210** and cache it in the thin client security mitigation table.

(58) FIG. 7 shows a flowchart of method **700** for the pre-boot context-based security mitigation. Method **700** is a continuation of method **600** of FIG. 6 and may be performed by a UEFI service **145**, operating system service **255**, workspace agent **350**, and VDI connector **460** of FIG. 5. At block **705**, operating system service **255**, may notify workspace agent **350** of the pre-boot security posture as applicable, such as when the information handling system includes a workspace, such as workspace **340** of FIG. 5. At block **710**, operating system service **255** may determine one or more security mitigations based on table **1** and then apply the one or more security mitigations. For example, operating system service **255** may set the logon service type such as requiring the use of a smart card or biometrics instead of a username and password for credentials. As such if there is no information received regarding an IOA, then there may not be a security mitigation to be applied.

(59) At block **715**, operating system service **255** may also determine one or more security mitigations based on table **3** as applicable. For example, the operating system service may determine if there is a thin client associated with the information handling system and then determine if there is an IOA associated with the thin client. If there is an IOA, then operating system service **255** may determine corresponding security mitigation. The security mitigation may be applied to VDI connector **460** and/or the thin client. As such if there is no IOA associated with the thin client, then there may not be the security mitigation to be applied to VDI connector **460** and/or the thin client.

(60) At block **720**, workspace agent **350** may receive the notification associated with the security posture of the information handling system that is transmitted by operating system service **255**. For example, workspace agent **350** may transmit IOAs associated with the workspace. If there is no workspace or there is no IOA associated with the workspace, then operating system agent may not transmit IOA information to workspace agent **350**. At block **725**, workspace agent **350** may determine corresponding security mitigation to the IOA based on table **2** as applicable. As such if

there is no information received regarding an IOA, then there may not be a security mitigation to be applied. At block **730**, the VDI connector **460** may receive the security mitigation from operating system service **255**. For example, VDI connector **460** may receive a command to block an application running on the thin client and/or the thin client.

(61) Although FIG. **6**, and FIG. **7** show example blocks of method **600** and method **700** in some implementations, method **600** and method **700** may include additional blocks, fewer blocks, different blocks, or differently arranged blocks than those depicted in FIG. **6** and FIG. **7**. Those skilled in the art will understand that the principles presented herein may be implemented in any suitably arranged processing system. Additionally, or alternatively, two or more of the blocks of method **600** and method **700** may be performed in parallel. For example, blocks **705** and **710** of method **700** may be performed in parallel.

(62) In accordance with various embodiments of the present disclosure, the methods described herein may be implemented by software programs executable by a computer system. Further, in an exemplary, non-limited embodiment, implementations can include distributed processing, component/object distributed processing, and parallel processing. Alternatively, virtual computer system processing can be constructed to implement one or more of the methods or functionalities as described herein.

(63) When referred to as a “device,” a “module,” a “unit,” a “controller,” or the like, the embodiments described herein can be configured as hardware. For example, a portion of an information handling system device may be hardware such as, for example, an integrated circuit (such as an Application Specific Integrated Circuit (ASIC), a Field Programmable Gate Array (FPGA), a structured ASIC, or a device embedded on a larger chip), a card (such as a Peripheral Component Interface (PCI) card, a PCI-express card, a Personal Computer Memory Card International Association (PCMCIA) card, or other such expansion card), or a system (such as a motherboard, a system-on-a-chip (SoC), or a stand-alone device).

(64) The present disclosure contemplates a computer-readable medium that includes instructions or receives and executes instructions responsive to a propagated signal; so that a device connected to a network can communicate voice, video, or data over the network. Further, the instructions may be transmitted or received over the network via the network interface device.

(65) While the computer-readable medium is shown to be a single medium, the term “computer-readable medium” includes a single medium or multiple media, such as a centralized or distributed database, and/or associated caches and servers that store one or more sets of instructions. The term “computer-readable medium” shall also include any medium that is capable of storing, encoding or carrying a set of instructions for execution by a processor or that causes a computer system to perform any one or more of the methods or operations disclosed herein.

(66) In a particular non-limiting, exemplary embodiment, the computer-readable medium can include a solid-state memory such as a memory card or other package that houses one or more non-volatile read-only memories. Further, the computer-readable medium can be a random-access memory or other volatile re-writable memory. Additionally, the computer-readable medium can include a magneto-optical or optical medium, such as a disk or tapes or another storage device to store information received via carrier wave signals such as a signal communicated over a transmission medium. A digital file attachment to an e-mail or other self-contained information archive or set of archives may be considered a distribution medium that is equivalent to a tangible storage medium. Accordingly, the disclosure is considered to include any one or more of a computer-readable medium or a distribution medium and other equivalents and successor media, in which data or instructions may be stored.

(67) Although only a few exemplary embodiments have been described in detail above, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of the embodiments of the present disclosure. Accordingly, all such modifications are intended to be

included within the scope of the embodiments of the present disclosure as defined in the following claims. In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures.

Claims

1. A method comprising: determining, by a processor, a pre-boot security posture of an information handling system by capturing state of a basic input/output system (BIOS) security indicator during a boot device selection phase of a boot process, wherein the pre-boot security posture indicates a pre-boot security status of an external device associated with the information handling system; updating an advanced configuration and power interface mitigation table based on the pre-boot security posture according to the state of the BIOS security indicator; receiving a security mitigation policy; updating a security mitigation table based on the security mitigation policy; determining a security mitigation corresponding to the pre-boot security posture captured during the boot device selection phase of the boot process, wherein the security mitigation is based on a protection flag in the advanced configuration and power interface mitigation table and the security mitigation table; and applying the security mitigation by an operating system to mitigate the pre-boot security status of the external device.
2. The method of claim 1, wherein the determining of the pre-boot security posture is performed during a driver execution environment phase.
3. The method of claim 1, wherein the security mitigation table includes a mapping of an indicator of attack to the security mitigation.
4. The method of claim 1, wherein the security mitigation policy is received from a device management solution.
5. The method of claim 1, further comprising providing a logon type to be used by a logon service of the information handling system.
6. The method of claim 1, wherein the security mitigation is applied to a modern client.
7. The method of claim 1, wherein the security mitigation is applied to a thin client.
8. An information handling system, comprising: a processor; and a memory coupled to the processor, the memory having program instructions stored thereon that, upon execution by the processor, cause the information handling system to: determine a pre-boot security posture of the information handling system by capturing state of a basic input/output system (BIOS) security indicator during a boot device selection phase of a boot process, wherein the pre-boot security posture indicates a pre-boot security status of an internal device of the information handling system; update an advanced configuration and power interface mitigation table with the pre-boot security posture according to the state of the BIOS security indicator; update a security mitigation table based on a security mitigation policy; determine a security mitigation corresponding to the pre-boot security posture captured during the boot device selection phase of the boot process, wherein the security mitigation is based on a protection flag in the advanced configuration and power interface mitigation table and the security mitigation table; and apply the security mitigation by an operating system to mitigate the pre-boot security status of the internal device.
9. The information handling system of claim 8, wherein the determination of the pre-boot security posture is performed during a driver execution environment phase.
10. The information handling system of claim 8, wherein the security mitigation table includes a mapping of the pre-boot security posture to the security mitigation.
11. The information handling system of claim 8, wherein the advanced configuration and power interface mitigation table is received from a device management solution.
12. The information handling system of claim 8, further comprising providing a credential type to be used by a logon service of the information handling system.

13. The information handling system of claim 8, wherein the security mitigation is applied to a modern client.
 14. The information handling system of claim 8, wherein the security mitigation is applied to a thin client.
 15. A non-transitory computer-readable medium to store instructions that are executable to perform operations comprising: determining a pre-boot security posture of an information handling system by capturing state of a basic input/output system (BIOS) security indicator during a boot device selection phase of a boot process, wherein the pre-boot security posture indicates a pre-boot security status of an external device associated with the information handling system; updating an advanced configuration and power interface mitigation table with the pre-boot security posture according to the state of the BIOS security indicator; updating a security mitigation table based on a security mitigation policy; determining a security mitigation corresponding to the pre-boot security posture captured during the boot device selection phase of the boot process, wherein the security mitigation is based on an indicator of attack associated with a protection flag in the advanced configuration and power interface mitigation table and the security mitigation table; and applying the security mitigation by an operating system to mitigate the pre-boot security status of the external device.
 16. The non-transitory computer-readable medium of claim 15, wherein the determining of the pre-boot security posture is performed during a driver execution environment phase.
 17. The non-transitory computer-readable medium of claim 15, wherein the security mitigation table includes a mapping of the indicator of attack to the security mitigation.
 18. The non-transitory computer-readable medium of claim 15, wherein the advanced configuration and power interface mitigation table is received from a device management solution.
 19. The non-transitory computer-readable medium of claim 15, wherein the security mitigation is applied to a modern client.
 20. The non-transitory computer-readable medium of claim 15, wherein the security mitigation is applied to a thin client.
-