

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407632
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Schuetz; Sebastian et al.

Training a bot orchestrator for chatbots

Abstract

Disclosed herein are system, method, and computer program product embodiments for training a bot orchestrator for chatbot selection. An embodiment operates by collecting a set of expressions from training data sets of a plurality of chatbots. For each pair of expressions, the embodiment calculates a mathematical distance between an expression for a first chatbot in the respective pair of expressions and an expression for a second chatbot in the respective pair of expressions. The embodiment filters the set of expressions based on the calculated mathematical distances, thereby generating a filtered set of expressions. The embodiment then trains a machine learning-based classification model of the bot orchestrator using the filtered set of expressions.

Inventors:	Schuetz; Sebastian (Mannheim, DE), Knoll; Johannes (Mannheim, DE)
Applicant:	SAP SE (Walldorf, DE)
Family ID:	89168613
Assignee:	SAP SE (Walldorf, DE)
Appl. No.:	17/845297
Filed:	June 21, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230412530 A1	Dec. 21, 2023

Publication Classification

Int. Cl.: G06F17/27 (20060101); G06F18/214 (20230101); G06F40/35 (20200101); H04L51/02 (20220101)

U.S. Cl.:

CPC H04L51/02 (20130101); G06F18/214 (20230101); G06F40/35 (20200101);

Field of Classification Search

CPC: G06F (18/214); G06F (40/35); G06F (16/90332); G10L (15/1815); H04L (51/02)

USPC: 704/9

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2019/0273701	12/2018	Basheer	N/A	H04L 51/02
2020/0342032	12/2019	Subramaniam	N/A	G06F 16/90332
2021/0012245	12/2020	Singaraju	N/A	H04L 51/04

OTHER PUBLICATIONS

Cer, D et al., "Universal Sentence Encoder," arXiv: 1803.11175v2 [cs.CL], 7 pages, Apr. 12, 2018. cited by applicant

Iyyer, M. et al., "Deep Unordered Composition Rivals Syntactic Methods for Text Classification," Proc. of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th Int'l Joint Conf. on Natural Language Processing, pp. 1681-1691, Beijing, China, 2015. cited by applicant

Lee, L.H. et al., "An enhanced Support Vector Machine classification framework by using Euclidean distance function for text document categorization," Appl Intell 37, pp. 80-99, 2012. cited by applicant

Li, B. and Han, L., "Distance Weighted Cosine Similarity Measure for Text Classification," IDEAL 2013, LNCS 8206, pp. 611-618, 2013. cited by applicant

Niwattanakul, S. et al., "Using of Jaccard Coefficient for Keywords Similarity," Proc. of the Int'l MultiConference of Engineers and Computer Scientists 2013 vol. I, 6 pages, 2013. cited by applicant

Schutz, S. and Knoll, J., "Automatic Training Data Harmonization for Bot Orchestrators in Digital Assistants," 18 pages, Feb. 2022. cited by applicant

Stucki, T. and D'Onofrio, T., "Architectural Patterns for Multi-Chatbot Environments: Bot Orchestrator and Alternatives," HMD (2020) 57, pp. 1187-1205, 2020. cited by applicant

Primary Examiner: Elahee; Md S

Attorney, Agent or Firm: Sterne, Kessler, Goldstein & Fox P.L.L.C.

Background/Summary

BACKGROUND

(1) Many dialog systems combine multiple different and isolated chatbots into one comprehensive digital assistant. A bot orchestrator may be responsible for managing all these chatbots. For example, the bot orchestrator may determine which of the chatbots is best-fitted to respond to a user's input. The bot orchestrator may make this decision using a machine learning-based

classification model (also referred to as a metabot model) which is trained using the training data sets of the individual chatbots. For example, the training data set of the metabot model may be created by aggregating the expressions for the intent classification of the individual chatbots. The resulting data set may then be labeled by the chatbot from which the expressions originated.

(2) But this approach often results in the bot orchestrator selecting the wrong chatbot in response to a user's input. This may be because the metabot model is trained with unharmonized data. This often occurs because the training data sets of the individual chatbots do not fit together very well for a digital assistant scenario. For example, the training data sets can contain doubled or similar expressions if multiple chatbots are designed to work in similar scenarios. Moreover, a training data set for a chatbot can also contain expressions which are unrelated to the main functionality of the chatbot such as small talk.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings are incorporated herein and form a part of the specification.

(2) FIG. 1 is a block diagram of a system for deciding which one of a plurality of chatbots is best-fitted to respond to a user's input, according to some embodiments.

(3) FIG. 2 is an example of aggregating training data sets for individual chatbots to create a training data set for a machine learning-based classification model, according to some embodiments.

(4) FIG. 3 is a flowchart illustrating a process for training a bot orchestrator for chatbot selection, according to some embodiments.

(5) FIG. 4 is an example computer system useful for implementing various embodiments.

(6) In the drawings, like reference numbers generally indicate identical or similar elements.

Additionally, generally, the left-most digit(s) of a reference number identifies the drawing in which the reference number first appears.

DETAILED DESCRIPTION

(7) Provided herein are system, apparatus, device, method and/or computer program product embodiments, and/or combinations and sub-combinations thereof, for training a bot orchestrator for chatbot selection.

(8) FIG. 1 is a block diagram of a system **100** that decides which one of a plurality of chatbots **106** is best-fitted to respond to a user **108**'s input, according to some embodiments. System **100** can include digital assistant **102**. Digital assistant **102** can include bot orchestrator **104** and one or more chatbots **106**. System **100** can be implemented on a desktop computer, server, laptop, tablet, smartphone, or other device as would be appreciated by a person of ordinary skill in the art. System **100** can also be implemented on a virtual machine, container, cloud computing platform, or other software platform as would be appreciated by a person of ordinary skill in the art.

(9) Bot orchestrator **104** may be responsible for managing the one or more chatbots **106**. Bot orchestrator **104** may receive an input from user **108**. User **108** may be a person. User **108** may also be another software system. In response to receiving the input from user **108**, bot orchestrator **104** may determine which of the chatbots **106** is best-fitted to respond to the input. Bot orchestrator **104** may make this decision using a machine learning-based classification model (also referred to as a metabot model) which is trained using the training data sets of the individual chatbots **106**. Bot orchestrator **104** may then route the input to the determined chatbot **106**. In response, bot orchestrator **104** may receive a response from the determined chatbot **106**. Bot orchestrator **104** may output the response to user **108**.

(10) The training data set of the machine learning-based classification model may be created from the training data sets of the individual chatbots **106**. FIG. 2 is an example of aggregating training data sets for individual chatbots to create a training data set for a machine learning-based

classification model, according to some embodiments. FIG. 2 is described with reference to FIG. 1. (11) FIG. 2 includes chatbots **106-1**, **106-2**, and **106-3**. FIG. 2 further includes training data sets **202-1**, **202-2**, and **202-3**. FIG. 2 further includes training data set **204** for a machine learning-based classification model for bot orchestrator **104**.

(12) Each chatbot **106** may be tailored to a separate problem domain. For example, chatbot **106-1** may be a lunch chatbot. Chatbot **106-1** may provide lunch related information in response to an input from user **108**. Chatbot **106-2** may be a news chatbot. Chatbot **106-2** may provide news related information in response to an input from user **108**. Chatbot **106-3** may be a carfleet chatbot. Chatbot **106-3** may provide car related information in response to an input from user **108**.

(13) Each chatbot **106** may have a separate training data set. For example, training data set **202-1** may be the training data set for chatbot **106-1**. Training data set **202-2** may be the training data set for chatbot **106-2**. And training data set **202-3** may be the training data set for chatbot **106-3**.

(14) Each training data set **202** may include one or more (expression, intent) pairs. An expression may be a possible input to the corresponding chatbot **106**. An intent may be a function or task performed by the corresponding chatbot **106**. For example, training set **106-1** may include the expression “What is for lunch today?” for chatbot **106-1**. This expression may be associated with the intent “get lunch.” Thus, chatbot **106-1** may perform the function “get lunch” in response to the input “What is for lunch today?” Similarly, training set **106-2** may include the expression “What are the top news?” for chatbot **106-2**. This expression may be associated with the intent “get news.” Thus, chatbot **106-2** may perform the function “get news” in response to the input “What are the top news?” And training set **106-3** may include the expression “My company car needs a repair” for chatbot **106-3**. This expression may be associated with the intent “request service.” Thus, chatbot **106-3** may perform the function “request service” in response to the input “My company car needs a repair.”

(15) In response to an input from user **108**, bot orchestrator **104** may select a particular chatbot **106** among a plurality of chatbots **106** based on a machine learning-based classification model trained using training data set **204**. Training data set **204** may be created by aggregating the training data sets of each of the plurality of chatbots **106**. For example, trained data set **204** may be created by aggregating the training data sets of chatbots **106-1**, **106-2**, and **106-3**.

(16) During the aggregation process, each expression from each individual training data set **202** may be added to training data set **204** along with an indication of the corresponding chatbot **106** that handles that expression. For example, the expression “What is for lunch today?” may be added to training data set **204** along with an indication that chatbot **106-1** handles that expression. Similarly, the expression “What are the top news?” may be added to training data set **204** along with an indication that chatbot **106-2** handles that expression. And the expression “My company car needs a repair” may be added to training data set **204** along with an indication that chatbot **106-3** handles that expression.

(17) This aggregation process may work well where a single developer develops digital assistant **102**. However, this aggregation process may not work well where different chatbots **106** are developed by separate and isolated developers. For example, one technological problem associated with this approach is that bot orchestrator **104** may select the wrong chatbot **106** in response to user **108**'s input. This may be because the machine learning-based classification model for bot orchestrator **104** may be trained with unharmonized data in training data set **204**.

(18) There may be unharmonized data in training data set **204** because the training data sets **202** of the individual chatbots **106** often do not fit together very well for a digital assistant scenario. The training data sets **202** may contain doubled or similar expressions where multiple chatbots **106** are designed to work in similar scenarios. For example, the expression “What is new today?” may be used by chatbot **106-1** to ask for the lunch and by chatbot **106-2** to ask for the current news. Moreover, a training data set **202** for a chatbot **106** can also contain expressions which are unrelated to the main functionality of the chatbot **106** such as small talk.

(19) To solve this technological problem, embodiments herein harmonize the data in a training data set for a machine learning-based classification model of a bot orchestrator. For example, embodiments herein harmonize the data in the training data set for the machine learning-based classification model by filtering training data sets from individual chatbots. Embodiments herein may filter the training data sets by removing double, similar, or unrelated expressions before adding the expressions to the training data set for the machine learning-based classification model. Embodiments herein then train the machine learning-based classification model of the bot orchestrator using filtered training data set.

(20) To harmonize data in training data set **204** for the machine learning-based classification model for bot orchestrator **104**, system **100** may collect a set of expressions from all (or a portion) of the training data sets associated with chatbots **106**. For example, in FIG. 2, system **100** may collect a set of expressions from training data sets **202-1**, **202-2**, and **202-3**.

(21) After collecting the set of expressions, system **100** may compare pairs of expressions with mathematical distance measures. For example, system **100** may compare each expression of a chatbot **106** to all expressions of all other chatbots **106**. In other words, system **100** may not compare the expressions of one individual chatbot **106** against other expressions of the same chatbot **106**.

(22) System **100** may compare a pair of expressions by calculating a mathematical distance between an expression of a first chatbot **106** and an expression of a second chatbot **106**. System **100** may calculate the mathematical distance between the expression of the first chatbot **106** and the expression of the second chatbot **106** using various techniques.

(23) System **100** may calculate the mathematical distance between the expression of the first chatbot **106** and the expression of the second chatbot **106** using a Jaccard distance. To compute the Jaccard distance, system **100** may first compute the Jaccard similarity of the expression of the first chatbot **106** and the expression of the second chatbot **106**. The Jaccard similarity can represent the similarity of the two expressions.

(24) The Jaccard similarity can represent the ratio between the number of elements (e.g., words) occurring identically in both expressions and the total number of elements (e.g., words) occurring in both expressions. System **100** can compute the Jaccard similarity as follows:

$$(25) J(A, B) = \frac{.Math. A .Math. B .Math.}{.Math. A .Math. B .Math.}$$

(26) In the above example, A can represent the expression of the first chatbot **106** and B can represent the expression of the second chatbot **106**. The resulting Jaccard similarity value can range from 0 and 1.

(27) To compute the Jaccard distance between the expression of the first chatbot **106** and the expression of the second chatbot **106**, system **100** can subtract the Jaccard similarity value from 1. In other words, system **100** can compute the Jaccard distance as follows:

$$d.sub.J(A, B) = 1 - J(A, B)$$

(28) In the above example, dJ(A, B) can represent the Jaccard distance between A and B, where A can represent the expression of the first chatbot **106** and B can represent the expression of the second chatbot **106**.

(29) System **100** may also calculate the mathematical distance between the expression of the first chatbot **106** and the expression of the second chatbot **106** using a Euclidean distance. To compute the Euclidean distance, system **100** may first transform both expressions into vectors using sentence embedding. For example, system **100** may transform the expression of the first chatbot **106** into a first vector and the expression of the second chatbot **106** into a second vector.

(30) System **100** may transform the expressions into vectors using various sentence embedding techniques. For example, system **100** may transform the expressions into vectors using a sentence encoder (e.g., Google LLC's Universal Sentence Encoder). The sentence encoder may represent each expression as a 512-dimensional vector of floating-point numbers.

(31) The sentence encoder may generate a vector from an expression using a 3-step process. First,

the sentence encoder may generate an embedding for each word and each bigram of the expression. Second, the sentence encoder may average the embeddings into a single vector. Finally, the sentence encoder may process the single vector using a feedforward artificial neural network, thereby obtaining the final vector for the expression. Once system **100** has transformed the expressions into vectors, system **100** can calculate the mathematical distance between the vector for the first chatbot **106** and the vector for the second chatbot **106** using a Euclidean distance. System **100** can compute the Euclidean distance between the vector for the first chatbot **106** and the vector for the second chatbot **106** as follows:

$$(32) d(y, x) = \sqrt{\sum_{i=1}^n (\text{Math. } y_i - x_i)^2}$$

(33) In the above example, $d(y, x)$ can represent the Euclidean distance between y and x , where y can represent the vector of the first chatbot **106** and x can represent the vector of the second chatbot **106**.

(34) System **100** may also calculate the mathematical distance between the expression of the first chatbot **106** and the expression of the second chatbot **106** using a cosine distance. To compute the cosine distance, system **100** may first transform both expressions into vectors using sentence embedding. For example, as discussed above, system **100** may transform the expression of the first chatbot **106** into a first vector and the expression of the second chatbot **106** into a second vector using a sentence encoder.

(35) To compute the cosine distance, system **100** may first compute the cosine similarity of the vector of the first chatbot **106** and the vector of the second chatbot **106**. The cosine similarity can represent the distance between two vectors based on the angle between them.

(36) System **100** can compute the cosine similarity as follows:

$$(37) \text{cosine}(\overset{\text{.fwdarw.}}{\underset{\text{.Math.}}{u}}, \overset{\text{.fwdarw.}}{\underset{\text{.Math.}}{v}}) = \frac{\overset{\text{.fwdarw.}}{\underset{\text{.Math.}}{u}} \cdot \overset{\text{.fwdarw.}}{\underset{\text{.Math.}}{v}}}{\sqrt{\overset{\text{.fwdarw.}}{\underset{\text{.Math.}}{u}}^2} \sqrt{\overset{\text{.fwdarw.}}{\underset{\text{.Math.}}{v}}^2}} = \frac{\sum_{i=1}^n \text{Math. } u_i \cdot \text{Math. } v_i}{\sqrt{\sum_{i=1}^n \text{Math. } u_i^2} \sqrt{\sum_{i=1}^n \text{Math. } v_i^2}}$$

(38) In the above example, u can represent the vector of the first chatbot **106** and v can represent the vector of the second chatbot **106**. The resulting cosine similarity value can range from -1 (e.g., meaning exactly opposite) to 1 (e.g., meaning exactly the same).

(39) To compute the cosine distance between the vector of the first chatbot **106** and the vector of the second chatbot **106**, system **100** can subtract the cosine similarity value from 1 . In other words, system **100** can compute the cosine distance as follows:

$$\text{cosine distance}(\overset{\text{right arrow over}}{(u)}, \overset{\text{right arrow over}}{(v)}) = 1 - \text{cosine}(\overset{\text{right arrow over}}{(u)}, \overset{\text{right arrow over}}{(v)})$$

(40) In the above example, $\text{cosine distance}(\overset{\text{right arrow over}}{(u)}, \overset{\text{right arrow over}}{(v)})$ can represent the cosine distance between u and v , where u can represent the vector of the first chatbot **106** and v can represent the vector of the second chatbot **106**.

(41) System **100** may also calculate the mathematical distance between the expression of the first chatbot **106** and the expression of the second chatbot **106** by first transforming both expressions into vectors using sentence embedding. System **100** can then calculate the mathematical distance between the vector of the first chatbot **106** and the vector of the second chatbot **106** using various similarity statistics as would be appreciated by a person of ordinary skill in the art.

(42) After comparing the pairs of expressions (e.g., by calculating mathematical distances for each pair of expressions), system **100** can filter the set of expressions based on the comparison. For example, system **100** can filter the set of expressions based on the calculated mathematical distances. System **100** can filter the set of expressions based on the calculated mathematical distances using a fully automated approach. System **100** can also filter the set of expressions based on the calculated mathematical distances using a semi-automated approach.

(43) System **100** can filter the set of expressions based on the calculated mathematical distances using a fully automated approach. System **100** can first determine whether a calculated mathematical distance for a pair of expressions is below a threshold value. The threshold value may

be set by system **100** or by an administrator of system **100**. The threshold value may be set to balance the accuracy of selection of a chatbot **106** against possible exclusions of valuable expressions. If so, system **100** can remove at least one of the expressions from the set of expressions, thereby generating a filtered set of expressions. If the goal is to have an optimal and clear separation between the expressions of chatbots **106**, system **100** can remove both expressions in the pair of expressions from the set of expressions. If the goal is that certain areas of expressions should be covered by a dedicated chatbot **106** (e.g., a dedicated chatbot to handle small talk), system **100** can remove a single expression in the pair of expressions from the set of expressions. System **100** may remove the single expression in the pair of expressions from the set of expressions based on the single expression's corresponding chatbot **106** having a lower priority (e.g., lower priority value) than the other chatbot **106** corresponding to the other expression in the pair of expressions.

(44) System **100** can also filter the set of expressions based on the calculated mathematical distances using a semi-automated approach. System **100** can first rank each pair of expressions based on their respective calculated mathematical distance. For example, system **100** can rank a pair of expressions having a lower calculated mathematical distance than another pair of expressions as having a higher priority than the other pair of expressions. System **100** can then output the ranked pairs of expressions to a user. System **100** can then filter the set of expressions based on input from the user (e.g., based on a decision from the user).

(45) System **100** can train a machine-learning-based classification model (also referred to as a metabot model) using the filtered set of expressions. System **100** may train the machine-learning-based classification model using the filtered set of expressions using various training algorithms as would be appreciated by a person of ordinary skill in the art.

(46) After system **100** trains the machine-learning-based classification model, system **100** can route, using bot orchestrator **104**, an input from user **108** to a chatbot **106** based on the trained machine learning-based classification model.

(47) FIG. 3 is a flowchart for a method **300** for training a bot orchestrator for chatbot selection, according to an embodiment. Method **300** can be performed by processing logic that can comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (e.g., instructions executing on a processing device), or a combination thereof. It is to be appreciated that not all steps may be needed to perform the disclosure provided herein. Further, some of the steps may be performed simultaneously, or in a different order than shown in FIG. 3, as will be understood by a person of ordinary skill in the art.

(48) Method **300** shall be described with reference to FIGS. 1 and 2. However, method **300** is not limited to that example embodiment.

(49) In **302**, system **100** collects a set of expressions from training data sets of a plurality of chatbots **106**. System **100** may collect the set of expressions from training data sets of all chatbots **106**. System **100** may also collect the set of expressions from training data sets of a portion of the plurality of chatbots **106**. System **100** may collect the set of expressions for a portion of the chatbots **106** where system **100** is attempting to configure bot orchestrator **104** to accurately route an input from user **108** to one chatbot **106** among the portion of chatbots **106**.

(50) In **304**, for each pair of expressions in the set of collected expressions, system **100** calculates a mathematical distance between an expression for a first chatbot in the respective pair of expressions and an expression for a second chatbot in the respective pair of expressions. System **100** may calculate the mathematical distance between the expression of the first chatbot **106** and the expression of the second chatbot **106** using various techniques.

(51) For example, system **100** may calculate the mathematical distance between the expression of the first chatbot **106** and the expression of the second chatbot **106** using a Jaccard distance. To compute the Jaccard distance, system **100** may first compute the Jaccard similarity of the expression of the first chatbot **106** and the expression of the second chatbot **106**. To compute the

Jaccard distance between the expression of the first chatbot **106** and the expression of the second chatbot **106**, system **100** can then subtract the Jaccard similarity value from 1.

(52) System **100** may also calculate the mathematical distance between the expression of the first chatbot **106** and the expression of the second chatbot **106** using a Euclidean distance. To compute the Euclidean distance, system **100** may first transform both expressions into vectors using sentence embedding. For example, system **100** may transform the expressions into vectors using a sentence encoder. Once system **100** has transformed the expressions into vectors, system **100** can calculate the mathematical distance between the vector for the first chatbot **106** and the vector of the second chatbot **106** using a Euclidean distance.

(53) System **100** may also calculate the mathematical distance between the expression of the first chatbot **106** and the expression of the second chatbot **106** using a cosine distance. To compute the cosine distance, system **100** may first transform both expressions into vectors using sentence embedding. For example, system **100** may transform the expressions into vectors using a sentence encoder. Once system **100** has transformed the expressions into vectors, system **100** may compute the cosine similarity of the vector of the first chatbot **106** and the vector of the second chatbot **106**. To compute the cosine distance between the vector of the first chatbot **106** and the vector of the second chatbot **106**, system **100** can subtract the cosine similarity value from 1.

(54) In **306**, system **100** filters the set of expressions based on the calculated mathematical distances, thereby generating a filtered set of expressions. System **100** can first determine whether a calculated mathematical distance for a pair of expressions is below a threshold value. The threshold value may be set by system **100** or by an administrator of system **100**. The threshold value may be set to balance the accuracy of selection of a chatbot **106** against possible exclusions of valuable expressions. If so, system **100** can remove at least one of the expressions from the set of expressions, thereby generating the filtered set of expressions. If the goal is to have an optimal and clear separation between the expressions of chatbots **106**, system **100** can remove both expressions in the pair of expressions from the set of expressions. If the goal is that certain areas of expressions should be covered by a dedicated chatbot **106** (e.g., a dedicated chatbot to handle small talk), system **100** can remove a single expression in the pair of expressions from the set of expressions. System **100** may remove the single expression in the pair of expressions from the set of expressions based on the single expression's corresponding chatbot **106** having a lower priority (e.g., lower priority value) than the other chatbot **106** corresponding to the other expression in the pair of expressions.

(55) System **100** may also filter the set of expressions based on the calculated mathematical distances using a semi-automated approach. System **100** can first rank each pair of expressions based on their respective calculated mathematical distance. For example, system **100** can rank a pair of expressions having a lower calculated mathematical distance than another pair of expressions as having a higher priority than the other pair of expressions. System **100** can then output the ranked pairs of expressions to a user. System **100** can then filter the set of expressions based on input from the user (e.g., based on a decision from the user).

(56) In **308**, system **100** trains a machine-learning-based classification model (also referred to as a metabot model) using the filtered set of expressions. System **100** may train the machine-learning-based classification model using the filtered set of expressions using various training algorithms as would be appreciated by a person of ordinary skill in the art.

(57) Various embodiments may be implemented, for example, using one or more well-known computer systems, such as computer system **400** shown in FIG. **4**. One or more computer systems **400** may be used, for example, to implement any of the embodiments discussed herein, as well as combinations and sub-combinations thereof

(58) Computer system **400** may include one or more processors (also called central processing units, or CPUs), such as a processor **404**. Processor **404** may be connected to a communication infrastructure or bus **406**.

- (59) Computer system **400** may also include user input/output device(s) **403**, such as monitors, keyboards, pointing devices, etc., which may communicate with communication infrastructure **406** through user input/output interface(s) **402**.
- (60) One or more of processors **404** may be a graphics processing unit (GPU). In an embodiment, a GPU may be a processor that is a specialized electronic circuit designed to process mathematically intensive applications. The GPU may have a parallel structure that is efficient for parallel processing of large blocks of data, such as mathematically intensive data common to computer graphics applications, images, videos, etc.
- (61) Computer system **400** may also include a main or primary memory **408**, such as random access memory (RAM). Main memory **408** may include one or more levels of cache. Main memory **408** may have stored therein control logic (i.e., computer software) and/or data.
- (62) Computer system **400** may also include one or more secondary storage devices or memory **410**. Secondary memory **410** may include, for example, a hard disk drive **412** and/or a removable storage device or drive **414**. Removable storage drive **414** may be a floppy disk drive, a magnetic tape drive, a compact disk drive, an optical storage device, tape backup device, and/or any other storage device/drive.
- (63) Removable storage drive **414** may interact with a removable storage unit **418**. Removable storage unit **418** may include a computer usable or readable storage device having stored thereon computer software (control logic) and/or data. Removable storage unit **418** may be a floppy disk, magnetic tape, compact disk, DVD, optical storage disk, and/ any other computer data storage device. Removable storage drive **414** may read from and/or write to removable storage unit **418**.
- (64) Secondary memory **410** may include other means, devices, components, instrumentalities or other approaches for allowing computer programs and/or other instructions and/or data to be accessed by computer system **400**. Such means, devices, components, instrumentalities or other approaches may include, for example, a removable storage unit **422** and an interface **420**. Examples of the removable storage unit **422** and the interface **420** may include a program cartridge and cartridge interface (such as that found in video game devices), a removable memory chip (such as an EPROM or PROM) and associated socket, a memory stick and USB port, a memory card and associated memory card slot, and/or any other removable storage unit and associated interface.
- (65) Computer system **400** may further include a communication or network interface **424**. Communication interface **424** may enable computer system **400** to communicate and interact with any combination of external devices, external networks, external entities, etc. (individually and collectively referenced by reference number **428**). For example, communication interface **424** may allow computer system **400** to communicate with external or remote devices **428** over communications path **426**, which may be wired and/or wireless (or a combination thereof), and which may include any combination of LANs, WANs, the Internet, etc. Control logic and/or data may be transmitted to and from computer system **400** via communication path **426**.
- (66) Computer system **400** may also be any of a personal digital assistant (PDA), desktop workstation, laptop or notebook computer, netbook, tablet, smart phone, smart watch or other wearable, appliance, part of the Internet-of-Things, and/or embedded system, to name a few non-limiting examples, or any combination thereof.
- (67) Computer system **400** may be a client or server, accessing or hosting any applications and/or data through any delivery paradigm, including but not limited to remote or distributed cloud computing solutions; local or on-premises software (“on-premise” cloud-based solutions); “as a service” models (e.g., content as a service (CaaS), digital content as a service (DCaaS), software as a service (SaaS), managed software as a service (MSaaS), platform as a service (PaaS), desktop as a service (DaaS), framework as a service (FaaS), backend as a service (BaaS), mobile backend as a service (MBaaS), infrastructure as a service (IaaS), etc.); and/or a hybrid model including any combination of the foregoing examples or other services or delivery paradigms.
- (68) Any applicable data structures, file formats, and schemas in computer system **400** may be

derived from standards including but not limited to JavaScript Object Notation (JSON), Extensible Markup Language (XML), Yet Another Markup Language (YAML), Extensible Hypertext Markup Language (XHTML), Wireless Markup Language (WML), MessagePack, XML User Interface Language (XUL), or any other functionally similar representations alone or in combination. Alternatively, proprietary data structures, formats or schemas may be used, either exclusively or in combination with known or open standards.

(69) In some embodiments, a tangible, non-transitory apparatus or article of manufacture comprising a tangible, non-transitory computer useable or readable medium having control logic (software) stored thereon may also be referred to herein as a computer program product or program storage device. This includes, but is not limited to, computer system **400**, main memory **408**, secondary memory **410**, and removable storage units **418** and **422**, as well as tangible articles of manufacture embodying any combination of the foregoing. Such control logic, when executed by one or more data processing devices (such as computer system **400**), may cause such data processing devices to operate as described herein.

(70) Based on the teachings contained in this disclosure, it will be apparent to persons skilled in the relevant art(s) how to make and use embodiments of this disclosure using data processing devices, computer systems and/or computer architectures other than that shown in FIG. **4**. In particular, embodiments can operate with software, hardware, and/or operating system implementations other than those described herein.

(71) It is to be appreciated that the Detailed Description section, and not any other section, is intended to be used to interpret the claims. Other sections can set forth one or more but not all exemplary embodiments as contemplated by the inventor(s), and thus, are not intended to limit this disclosure or the appended claims in any way.

(72) While this disclosure describes exemplary embodiments for exemplary fields and applications, it should be understood that the disclosure is not limited thereto. Other embodiments and modifications thereto are possible, and are within the scope and spirit of this disclosure. For example, and without limiting the generality of this paragraph, embodiments are not limited to the software, hardware, firmware, and/or entities illustrated in the figures and/or described herein. Further, embodiments (whether or not explicitly described herein) have significant utility to fields and applications beyond the examples described herein.

(73) Embodiments have been described herein with the aid of functional building blocks illustrating the implementation of specified functions and relationships thereof. The boundaries of these functional building blocks have been arbitrarily defined herein for the convenience of the description. Alternate boundaries can be defined as long as the specified functions and relationships (or equivalents thereof) are appropriately performed. Also, alternative embodiments can perform functional blocks, steps, operations, methods, etc. using orderings different than those described herein.

(74) References herein to “one embodiment,” “an embodiment,” “an example embodiment,” or similar phrases, indicate that the embodiment described can include a particular feature, structure, or characteristic, but every embodiment can not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it would be within the knowledge of persons skilled in the relevant art(s) to incorporate such feature, structure, or characteristic into other embodiments whether or not explicitly mentioned or described herein. Additionally, some embodiments can be described using the expression “coupled” and “connected” along with their derivatives. These terms are not necessarily intended as synonyms for each other. For example, some embodiments can be described using the terms “connected” and/or “coupled” to indicate that two or more elements are in direct physical or electrical contact with each other. The term “coupled,” however, can also mean that two or more elements are not in direct contact with each other, but yet still co-operate or

interact with each other.

(75) The breadth and scope of this disclosure should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

Claims

1. A computer implemented method for training a bot orchestrator for chatbot selection, comprising: collecting a set of expressions from a training data set of a first chatbot and a training data set of a second chatbot; for each respective pair of expressions in the set of expressions: calculating a mathematical distance between an expression for the first chatbot in the respective pair of expressions and an expression for the second chatbot in the respective pair of expressions; and filtering the set of expressions based on the calculated mathematical distance, thereby generating a filtered set of expressions; and training a machine learning-based classification model of the bot orchestrator using the filtered set of expressions, wherein the bot orchestrator is being trained to select a particular chatbot among the first and second chatbots based on the machine learning-based classification model of the bot orchestrator using the filtered set of expressions.
2. The computer implemented method of claim 1, further comprising: routing, using the bot orchestrator, an input to the first chatbot based on the trained machine learning-based classification model.
3. The computer implemented method of claim 1, wherein the calculating the mathematical distance between the expression for the first chatbot in the respective pair of expressions and the expression for the second chatbot in the respective pair of expressions further comprises: calculating the mathematical distance using a Jaccard distance.
4. The computer implemented method of claim 1, wherein the calculating the mathematical distance between the expression for the first chatbot in the respective pair of expressions and the expression for the second chatbot in the respective pair of expressions further comprises: converting the expression for the first chatbot into a first vector using sentence embedding; converting the expression for the second chatbot into a second vector using sentence embedding; and calculating the mathematical distance based on the first vector and the second vector.
5. The computer implemented method of claim 1, wherein the filtering the set of expressions further comprises: ranking each pair of expressions based on the respective calculated mathematical distance; and filtering the ranked pairs of expressions based on user input, thereby generating the filtered set of expressions.
6. The computer implemented method of claim 1, wherein the filtering the set of expressions further comprises: determining the calculated mathematical distance of a pair of expressions of the pairs of expressions is below a threshold value; and removing an expression for the first chatbot in the pair of expressions from the set of expressions, thereby generating the filtered set of expressions.
7. The computer implemented method of claim 6, wherein the removing the expression for the first chatbot in the pair of expressions from the set of expressions further comprises: removing the expression for the first chatbot in the pair of expressions from the set of expressions based on the first chatbot having a lower priority value than the second chatbot.
8. A system for training a bot orchestrator for chatbot selection, comprising: a memory; and at least one processor coupled to the memory and configured to: collect a set of expressions from a training data set of a first chatbot and a training data set of a second chatbot; for each respective pair of expressions in the set of expressions: calculate a mathematical distance between an expression for the first chatbot in the respective pair of expressions and an expression for the second chatbot in the respective pair of expressions; and filter the set of expressions based on the calculated mathematical distance, thereby generating a filtered set of expressions; and train a machine

learning-based classification model of the bot orchestrator using the filtered set of expressions, wherein the bot orchestrator is being trained to select a particular chatbot among the first and second chatbots based on the machine learning-based classification model of the bot orchestrator using the filtered set of expressions.

9. The system of claim 8, wherein the at least one processor is further configured to: route, using the bot orchestrator, an input to the first chatbot based on the trained machine learning-based classification model.

10. The system of claim 8, wherein to calculate the mathematical distance between the expression for the first chatbot in the respective pair of expressions and the expression for the second chatbot in the respective pair of expressions the at least one processor is further configured to: calculate the mathematical distance using a Jaccard distance.

11. The system of claim 8, wherein to calculate the mathematical distance between the expression for the first chatbot in the respective pair of expressions and the expression for the second chatbot in the respective pair of expressions the at least one processor is further configured to: convert the expression for the first chatbot into a first vector using sentence embedding; convert the expression for the second chatbot into a second vector using sentence embedding; and calculate the mathematical distance based on the first vector and the second vector.

12. The system of claim 8, wherein to filter the set of expressions, the at least one processor is further configured to: rank each pair of expressions based on the respective calculated mathematical distance; and filter the ranked pairs of expressions based on user input, thereby generating the filtered set of expressions.

13. The system of claim 8, wherein to filter the set of expressions, the at least one processor is further configured to: determine the calculated mathematical distance of a pair of expressions of the pairs of expressions is below a threshold value; and remove an expression for the first chatbot in the pair of expressions from the set of expressions, thereby generating the filtered set of expressions.

14. The system of claim 13, wherein to remove the expression for the first chatbot in the pair of expressions from the set of expressions, the at least one processor is further configured to: remove the expression for the first chatbot in the pair of expressions from the set of expressions based on the first chatbot having a lower priority value than the second chatbot.

15. A non-transitory computer-readable medium having instructions stored thereon that, when executed by at least one computing device, cause the at least one computing device to perform operations comprising: collecting a set of expressions from a training data set of a first chatbot and a training data set of a second chatbot; for each respective pair of expressions in the set of expressions: calculating a mathematical distance between an expression for the first chatbot in the respective pair of expressions and an expression for the second chatbot in the respective pair of expressions; and filtering the set of expressions based on the calculated mathematical distance, thereby generating a filtered set of expressions; and training a machine learning-based classification model of a bot orchestrator using the filtered set of expressions, wherein the bot orchestrator is being trained to select a particular chatbot among the first and second chatbots based on the machine learning-based classification model of the bot orchestrator using the filtered set of expressions.

16. The non-transitory computer-readable medium of claim 15, wherein the operations further comprise: routing, using the bot orchestrator, an input to the first chatbot based on the trained machine learning-based classification model.

17. The non-transitory computer-readable medium of claim 15, wherein the calculating further comprises: calculating the mathematical distance using a Jaccard distance.

18. The non-transitory computer-readable medium of claim 15, wherein the calculating further comprises: converting the expression for the first chatbot into a first vector using sentence embedding; converting the expression for the second chatbot into a second vector using sentence

embedding; and calculating the mathematical distance based on the first vector and the second vector.

19. The non-transitory computer-readable medium of claim 15, wherein the filtering further comprises: ranking each pair of expressions based on the respective calculated mathematical distance; and filtering the ranked pairs of expressions based on user input, thereby generating the filtered set of expressions.

20. The non-transitory computer-readable medium of claim 15, wherein the filtering further comprises: determining the calculated mathematical distance of a pair of expressions of the pairs of expressions is below a threshold value; and removing an expression for the first chatbot in the pair of expressions from the set of expressions, thereby generating the filtered set of expressions.
