

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407903
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Fang; Zheng et al.

Reference video quality measurement feedback

Abstract

Approaches to preventing degraded video presentation use reference video quality measurement feedback from a video decoder node that is receiving live action video streams from a video encoder across a cellular network. A reference video stream is encoded along with the live action video streams, and the video decoder node compares the decoded reference video stream with a local copy to determine video quality. The video decoder node provides video encoding parameter feedback for adjusting the encoding and/or provides cellular network feedback for adjusting a transmission parameter for data traffic through the cellular network (from the video encoder node to the video decoder node). Solutions are disclosed for implementation at the video encoder, at the video decoder, and within the cellular network. For example, different compression codecs may be specified, and bit rates, frame, rates, key frame intervals, and/or bit depth may be automatically (immediately) adjusted without requiring human intervention.

Inventors: Fang; Zheng (McLean, VA), Schnellbacher; George Jason (Leawood, KS)

Applicant: T-Mobile USA, Inc. (Bellevue, WA)

Family ID: 89662129

Assignee: T-Mobile USA, Inc. (Bellevue, WA)

Appl. No.: 18/158464

Filed: January 23, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240251138 A1	Jul. 25, 2024

Publication Classification

Int. Cl.: H04N21/234 (20110101); H04N21/2187 (20110101); H04N21/61 (20110101); H04N21/6379 (20110101)

U.S. Cl.:

CPC H04N21/6131 (20130101); H04N21/2187 (20130101); H04N21/234 (20130101); H04N21/6379 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7020093	12/2005	Sirivara	370/395.2	H04N 21/6125
9060191	12/2014	Chhaochharia	N/A	H04L 47/25
9491219	12/2015	Venkatasubramaniam	N/A	H04L 65/80
10165286	12/2017	Sze et al.	N/A	N/A
2004/0098748	12/2003	Bo	725/105	H04L 1/0002
2008/0117930	12/2007	Chakareski	370/465	H04L 1/0002
2009/0153668	12/2008	Kim	348/180	H04N 21/654
2010/0057928	12/2009	Kapoor	709/231	G06F 16/4387
2010/0215053	12/2009	Chakareski	370/465	H04L 47/10
2010/0259625	12/2009	Yamada	348/E17.005	H04N 21/4347
2012/0013748	12/2011	Stanwood	348/192	H04L 47/2408
2012/0278441	12/2011	Li	709/219	H04L 65/70
2013/0044803	12/2012	Fisher	709/231	H04N 21/8455
2013/0055331	12/2012	Karacali-Akyamac	N/A	N/A
2013/0148741	12/2012	Steinberg et al.	N/A	N/A
2013/0188060	12/2012	Steinberg et al.	N/A	N/A
2013/0286879	12/2012	ElArabawy	370/252	H04N 21/26208
2013/0298170	12/2012	ElArabawy	725/62	H04L 47/2416
2014/0294362	12/2013	Pettersson	386/264	H04N 17/004
2015/0026309	12/2014	Radcliffe	709/219	H04L 65/612
2015/0142702	12/2014	Nilsson	706/14	G06N 20/00
2015/0341646	12/2014	Sze	375/240.26	H04N 21/631
2016/0105728	12/2015	Schmidmer	725/110	H04N 21/64723
2016/0335754	12/2015	Aaron	N/A	H04N 21/4666
2016/0337680	12/2015	Kalagi	N/A	H04N 21/23439
2017/0085616	12/2016	Botsford	N/A	H04L 65/70
2018/0115475	12/2017	Broom	N/A	H04N 21/44209
2018/0270524	12/2017	Jones	N/A	H04N 21/23439

2018/0302455	12/2017	Bordoloi	N/A	H04N 19/115
2019/0020909	12/2018	Petajan	N/A	H04N 21/234363
2019/0158564	12/2018	Wang	N/A	H04L 41/5067
2020/0169736	12/2019	Petajan	N/A	H04N 19/154
2020/0314503	12/2019	Wang	N/A	H04N 21/2402
2020/0322694	12/2019	Colligan	N/A	H04N 21/8547
2022/0321892	12/2021	Liu et al.	N/A	N/A
2022/0415046	12/2021	Zhang	N/A	N/A

OTHER PUBLICATIONS

“European Search Report Application No. 24152765.4”, Mailed Date: May 27, 2024, 10 Pages.
cited by applicant

Primary Examiner: Kim; William J

Attorney, Agent or Firm: Foley IP Law, PLLC

Background/Summary

BACKGROUND

(1) The high bandwidth of fifth generation (5G) cellular networks open up new options for video production projects, such as permitting a bank of multiple cameras at a remote live action filming site, which does not support wired connectivity, to be monitored in real-time by dispersed video production team members in real-time. Under favorable conditions, a 5G air interface supports sufficient bandwidth for multiple simultaneous live action video streams, captured at the filming site, to be transmitted via a wireless modem to a base station, where it can then be carried across a wired network to a video distribution location for distribution among the video production team members.

(2) Unfortunately, cellular network performance has some degree of unpredictability. Not only may the air interface for a particular base station be congested, but since the cellular network carries other traffic for other users to/from other base stations, end-to-end data traffic performance may suffer (e.g., lost packets and packet delay) due to congestion through the cellular carrier's core network. Further, any other intervening network between the demarcation of the cellular network and the video distribution location, whether the internet or a dedicated private network, may also suffer performance degradation, outside the control of the cellular network operator. The result is a degraded video presentation to the video production team members, which may adversely impact a video production project.

SUMMARY

(3) The following summary is provided to illustrate examples disclosed herein, but is not meant to limit all examples to any particular configuration or sequence of operations.

(4) Disclosed approaches to reference video quality measurement feedback include: receiving, by a video encoder node, from a first video camera, a first live action video stream; selecting a first reference video stream; encoding each of the first live action video stream and the first reference video stream according to a first set of video encoding parameters; transmitting, to a video decoder node across a cellular network, the encoded first live action video stream and the encoded first reference video stream; receiving, from the video decoder node, video encoding parameter feedback; based on at least the video encoding parameter feedback, setting a second set of video

encoding parameters; encoding each of the first live action video stream and the first reference video stream according to the second set of video encoding parameters; and further transmitting, to the video decoder node, the encoded first live action video stream and the encoded first reference video stream.

(5) Further disclosed approaches to reference video quality measurement feedback include: receiving, by a video decoder node, from a video encoder node across a cellular network, an encoded first live action video stream and an encoded first reference video stream, the encoded second live action video stream and the encoded second reference video stream encoded according to the first set of video encoding parameters; decoding the first live action video stream and the first reference video stream; selecting a first comparison video stream; and based on at least a comparison of the first reference video stream with the first comparison video stream, transmitting, to the video encoder node, video encoding parameter feedback.

(6) Further disclosed approaches to reference video quality measurement feedback include: receiving, by a cellular network, from a video encoder node, an encoded first live action video stream and an encoded first reference video stream, the encoded first live action video stream and the encoded first reference video stream encoded according to a first set of video encoding parameters; transmitting, to a video decoder node, the encoded first live action video stream and the encoded first reference video stream; receiving, from the video decoder node, video encoding parameter feedback; transmitting, to the video encoder node, the video encoding parameter feedback; receiving, from the video decoder node, cellular network feedback; and based on at least receiving the cellular network feedback, adjusting at least one packet transmission parameter for data traffic from the video encoder node to the video decoder node.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The disclosed examples are described below with reference to the accompanying drawing figures listed below, wherein:

(2) FIG. 1 illustrates an exemplary architecture that advantageously provides reference video quality measurement feedback for automatic adjustment of video streaming encoding;

(3) FIG. 2 illustrates further detail for the video encoder node of FIG. 1;

(4) FIG. 3 illustrates further detail for the video decoder node of FIG. 1;

(5) FIG. 4 illustrates further detail for the cellular network of FIG. 1;

(6) FIGS. 5A-8 illustrate flowcharts of exemplary operations associated with examples of the architecture of FIG. 1; and

(7) FIG. 9 illustrates a block diagram of a computing device suitable for implementing various aspects of the disclosure.

(8) Corresponding reference characters indicate corresponding parts throughout the drawings, where practical. References made throughout this disclosure, relating to specific examples, are provided for illustrative purposes, and are not meant to limit all implementations or to be interpreted as excluding the existence of additional implementations that also incorporate the recited features.

DETAILED DESCRIPTION

(9) Approaches to preventing degraded video presentation use reference video quality measurement feedback from a video decoder node that is receiving live action video streams from a video encoder across a cellular network. A reference video stream is encoded along with the live action video streams, and the video decoder node compares the decoded reference video stream with a local copy to determine video quality. The video decoder node provides video encoding parameter feedback for adjusting the encoding and/or provides cellular network feedback for adjusting a

transmission parameter for data traffic through the cellular network (from the video encoder node to the video decoder node). Solutions are disclosed for implementation at the video encoder, at the video decoder, and within the cellular network. For example, different compression codecs may be specified, and bit rates, frame, rates, key frame intervals, bit depth and/or other encoding parameters may be automatically (immediately) adjusted without requiring human intervention.

(10) Aspects of the disclosure improve objectively-measured video quality metrics for video streams passing through cellular networks. This provides a useful, practical change in the operation of video distribution arrangements and is enabled, at least in part, by the video encoder receiving video encoding parameter feedback from the video decoder node and setting a new set of video encoding parameters based on at least the video encoding parameter feedback. The practical results are further enabled, at least in part, by the video encoder transmitting the video encoding parameter feedback to the video encoder node, based on at least a comparison of a reference video stream with a comparison video stream, and the cellular network receiving cellular network feedback from the video decoder node and adjusting at least one packet transmission parameter for data traffic from the video encoder node to the video decoder node based on at least receiving the cellular network feedback. With reference now to the figures, FIG. 1 illustrates an architecture **100** that advantageously provides reference video quality measurement feedback for automatic adjustment of video streaming encoding. With architecture **100**, video production that relies on a cellular network for distributing video streams to dispersed team members becomes a closed loop arrangement. This has advantages over current open loop video production, in which live streaming over a cellular network lacks a video quality value indication on the application layer from the intermediate receiver (e.g., the proxy server in the cloud or elsewhere) back to the sender or from final receivers (e.g., team member locations) back to the sender.

(11) In architecture **100**, video production, a live scene **102** is being captured by a plurality of cameras, such as camera **104a**, camera **104b**, and camera **104c**. Some examples use a different number of cameras. In the illustrated example, each camera has local storage for captured live action video and transmits a live action video stream to a video encoder **202** at a video encoder node **200**. For example, camera **104a** has a storage **108a** for its captured live action video and transmits live action video stream **106a** to video encoder node **200**; camera **104b** has a storage **108b** for its captured live action video and transmits live action video stream **106b** to video encoder node **200**; and camera **104c** has a storage **108c** for its captured live action video and transmits live action video stream **106c** to video encoder node **200**. In some examples, the live action video stored by each camera is raw video (which may be processed further at a later time), and the transmitted live action video stream is processed and/or compressed for transmission and immediate (real-time) viewing.

(12) A video encoder **202** within video encoder node **200** encodes live action video streams **106a-106c** for transmission to cloud video service **128** for further distribution to video production team members in a video distribution environment **130**. In some examples, video encoder **202** and/or other functionality described herein for video encoder node **200** is implemented using a notebook personal computer (PC). Video production team members include team member **132a** at a first geographic location **134a**, team member **132b** at a second geographic location **134b**, and team member **132c** at a third geographic location **134c**.

(13) In some examples, cloud video service **128** reduces the resolution and/or frame rate for at least some of the distributed video within video distribution environment **130**. For example, team member **132a** may be viewing the distributed video on a large monitor, whereas team member **132b** is viewing the distributed video on a standard size notebook computer monitor, and team member **132c** is viewing the distributed video on a personal device, such as a cellular telephone. As a result, each of team members **132a-132c** receives a custom-resolution video stream selected from one or more of live action video streams **106a-106c**.

(14) Geographic location **134a-134c** may be dispersed from each other and also from live scene

102. Because live scene **102** is at a remote location, in the illustrated example, such that a cabled connection is unavailable for the entirety of the path between video cameras **102a-102c** and cloud video service **128**, video encoder node **200** relies on an air interface **120** to a cellular network **400**. In some examples, cellular network **400** comprises a fifth generation (5G) cellular network. In some examples, there may also be another network, such as the internet shown as other network **122**, may be used to carry encoded live action video streams **106a-106c** from cellular network **400** to cloud video service **128**.

(15) To provide the closed loop functionality, a set of small reference video streams, shown as reference video stream **116a** and a reference video stream **116b**, from a respective one of a notional virtual camera **114a** and a notional virtual camera **114b**, are encoded by video encoder **202** and injected into the set of video streams sent by video encoder node **200**. Reference video streams **116a** and **116b** are not generally intended for viewing by team members **132a-132c**, and so may not be distributed in video distribution environment **130**, but are instead intended for video quality diagnostic purposes. Some examples may use a different number of reference video streams and live action video streams.

(16) Network latency and packet loss, either due to congestion or failures in cellular network **400** and/or other network **122** may affect video quality of streaming live action video. Thus, encoded reference video streams **116a** and **116b** travel through cellular network **400** and other network **122** along with encoded live action video streams **106a-106c** so that any degradation in the live action video streams **106a-106c**, as received by cloud video service **128**, also likely impacts reference video streams **116a** and **116b**.

(17) A video decoder **302** at video decoder node **300** decodes the received encoded reference video streams **116a** and **116b** and encoded live action video streams **106a-106c** and a video quality assessor **320** determines video quality metrics that indicate whether the received video streams are degraded. In some examples, each of reference video streams **116a** and **116b** and live action video streams **106a-106c** are encoded with the same set of video encoding parameters, which provides a direct estimate of the degradation of live action video streams **106a-106c** by assessing the quality of reference video streams **116a** and **116b**. However, in some examples, one or both of reference video streams **116a** and **116b** is encoded differently than live action video streams **106a-106c** (which, in some further examples, are encoded differently than each other).

(18) For example, reference video stream **116a** is selected in order to mimic live action video stream **106a** (e.g., similar image complexity, motion, frame rate, and other aspects), and reference video stream **116b** is selected in order to mimic live action video stream **106b**. With identical encoding for each, the video quality of live action video stream **106a** is estimated using the measured video quality of reference video stream **116a** and the video quality of live action video stream **106b** is estimated using the measured video quality of reference video stream **116b**.

(19) In another example, both reference video streams **116a** and **116b** are selected in order to mimic live action video stream **106a**, with reference video stream **116a** encoded the same as live action video stream **106a** and reference video stream **116b** encoded with different video encoding parameters. In this scenario, the video quality of live action video stream **106a** is still estimated using the measured video quality of reference video stream **116a**, however the video quality resulting from encoding live action video stream **106a** with the different video encoding parameters may be predicted by the measured video quality of reference video stream **116a**. With this second scheme, a new set of encoding parameters may be tested for suitability for given network conditions before the encoding is changed.

(20) Video decoder node **300** provides video encoding parameter feedback **112** to video encoded node **200** to use in adjusting the video encoding parameters in order to meet desired video quality metrics. In some examples, video decoder node **300** also provides cellular network feedback **118** to cellular network **400** so that cellular network **400** is alerted to adjust packet transmission (e.g., routing and/or priority) of the packets carrying reference video streams **116a** and **116b** and live

action video streams **106a-106c**. In some examples, video decoder node **300** is located separately from cloud video service **128**. In some examples, the functionality described herein for video decoder node **300** is located within cellular network **400**, within other network **122**, or is included within the functionality provided by cloud video service **128**. In some examples, the functionality described herein for video decoder node **300** is provided in multiple locations within architecture **100** (e.g., within cloud video service **128**, and separately, elsewhere).

(21) FIG. 2 illustrates further detail for video encoder node **200**. A reference video stream selector **204** receives some or all of live action video streams **106a-106c** and selects reference video streams **116a** and **116b** from a plurality of reference video streams **206** within a library of reference video streams. Plurality of reference video streams **206** has a variety of reference video streams with varying degrees of image complexity that span the demand on inter-frame compression (i.e., compression of the single image of a key frame), as well as varying degrees of motion that span the demand on intra-frame compression (i.e., compression across multiple images of a key frame interval).

(22) For example, plurality of reference video streams **206** has reference video streams **116a** and **116b**, along with a reference video stream **116c** and another reference video stream **116d**. Reference video stream selector **204** selects reference video stream **116a** due to its similarity to live action video stream **106a** and further reference video stream **116b** due to its similarity to live action video stream **106b**. Reference video stream selector **204** sends reference video streams **116a** and **116b** to video encoder **202** and sends identification **216a** of reference video stream **116a** and identification **216b** of reference video stream **116b** to a cellular modem **220** for multiplexing with encoded reference video streams **116a** and **116b** and encoded live action video streams **106a-106c**.

(23) Video encoder **202** receives reference video streams **116a** and **116b** from reference video stream selector **204** and live action video streams **106a-106c** from cameras **104a-104c**. In some examples, video encoder **202** encodes all of the received video streams with a common set of video encoding parameters, for example, set of video encoding parameters **210**. Video encoder **202** sends encoded reference video streams **116a** and **116b** and encoded live action video streams **106a-106c** to cellular modem **220** for transmission to video decoder node **300** and cloud video service **128**. Cellular modem **220** transmits encoded reference video streams **116a** and **116b** and encoded live action video streams **106a-106c**, along with identification **216a** of reference video stream **116a** and identification **216b** of reference video stream **116b**, using air interface **120** (e.g., a 5G air interface).

(24) Cellular modem **220** receives video encoding parameter feedback **112** from video decoder node **300** across cellular network **400** and through air interface **120**. Parameter adjustment **208** then adjusts the video encoding parameters used by video encoder **202** for subsequent encoding of reference video streams **116a** and **116b** and encoded live action video streams **106a-106c**. For example, parameter adjustment **208** instructs video encoder **202** to use a different set of video encoding parameters **212** in place of set of video encoding parameters **210**.

(25) Sets of video encoding parameters **212** may include specification of the bit rate, identification of a compression codec, resolution (e.g., in terms of pixels), frame rate (e.g., 30 or 60 frames per second), bit depth (e.g., specifying color depth), and a key frame interval. For some video compression algorithms, frames are categorized into three different frame types. I-frames (key frames) are sent as a complete image for a key frame interval, also known as a group of pictures (GOP) in which intra-image compression is performed using P-frames and B-frames. P-frames are predicted frames using only prior frames, and B-frames are bi-directional frames that are reconstructed using both prior and following frames within the current key frame interval.

(26) To perform the video encoding (which includes compression), video encoder **202** has multiple video codecs, shown as codec **212a** and codec **212b**. Examples include H.264 and H.265, and others. In general, H.265 may be preferred to H.264 but is more susceptible to degradation with high motion and poor network throughput.

(27) FIG. 3 illustrates further detail for video decoder node **300**. Video decoder node **300** receives encoded live action video streams **106a-106c**, reference video streams **116a** and **116b**, identification **216a** of reference video stream **116a**, and identification **216b** of reference video stream **116b** through cellular network **400**. In some examples, the video streams and identifications of the reference video streams are received through other network **122** and/or through cloud video service **128**. In some examples, the video streams are received from cloud video service **128**, whereas the identifications of the reference video streams are received through other network **122**.

(28) Video decoder **202** has its own copies of codec **212a** and **212b** to decode the encoded video streams and sends decoded reference video streams **116a** and **116b** to video quality assessor **320**. Video decoder node **300** has its own local copy of plurality of reference video streams **206**, shown as plurality of comparison video streams **306**. Comparison video stream **316a** is the same as reference video stream **116a**, comparison video stream **316b** is the same as reference video stream **116b**, comparison video stream **316c** is the same as reference video stream **116c**, and comparison video stream **316d** is the same as reference video stream **116d**.

(29) A comparison video stream selector **304** at video decoder node **300** receives identification **216a** of reference video stream **116a** and identification **216b**. Comparison video stream selector **304** selects corresponding comparison video streams **316a** and **316b** (for reference video streams **116a** and **116b**, respectively) and sends them to video quality assessor **320**.

(30) Video quality assessor **320** is then able to perform a full reference (FR) video quality assessment of received reference video streams **116a** and **116b** to determine video quality metrics **322**. FR video quality assessment computes the quality difference between a received video stream and a local clean copy of the same video stream. In some examples, video quality assessor **320** comprises a machine learning (ML) model. Video quality metrics **322** may include a set of standard metrics, such as peak signal-to-noise ratio (PSNR), structural similarity (SSIM), SSIMplus (e.g., SSIM with further ML assessment), and video multi-method assessment fusion (VMAF).

(31) A video feedback generator **324** generates video encoding parameter feedback **112** using video quality metrics **322**. In some examples, video encoding parameter feedback **112** merely represents video quality metrics **322**, whereas in some examples, video feedback generator **324** determines recommended changes to set of video encoding parameters **210**. That is, various examples may locate the logic to translate from video quality metrics **322** into new set of video encoding parameters **212** in video feedback generator **324**, parameter adjustment **208**, or across both. Video decoder node **300** transmits video encoding parameter feedback **112** to video encoder node **200** across cellular network **400**.

(32) In some examples, video encoder node **200** also has a network performance assessor **326** that determines general packet-based performance of cellular network, possibly in conjunction with other network **122**. The general packet-based performance includes metrics such as lost packets and packet delay. In real time video, packets are buffered at the receiver and sorted, in case they arrive out of order, and then sent for decoding. However, to maintain the timeliness of the video stream (e.g., live or real-time), the buffering has a time-out limit, such as 200 milliseconds (ms). If a packet arrives too late, it is dropped, and the result is the same as if the packet is lost: the reconstructed video will be blurred, jerky, or otherwise degraded. Network performance assessor **326** generates cellular network feedback **118** and transmits cellular network feedback **118** to cellular network **400**.

(33) FIG. 4 illustrates further detail for cellular network **400**. Cellular network **400** receives encoded live action video streams **106a-106c**, reference video streams **116a** and **116b**, identification **216a** of reference video stream **116a**, and identification **216b** of reference video stream **116b** from video encoder node **200** through air interface **120** and sends video encoding parameter feedback **112** to video encoder node **200** through air interface **120**. On the opposing end, cellular network **400** sends (transmits) encoded live action video streams **106a-106c**, reference video streams **116a** and **116b**, identification **216a** of reference video stream **116a**, and identification

216b of reference video stream **116b** to video decoder node **300**, possibly other network **122**, and receives video encoding parameter feedback **112** and cellular network feedback **118** from video decoder node **300**.

(34) Cellular network **400** couples with air interface **120** through a base station **402**, which may be a part of a radio access network (RAN). Cellular network **400** has a session management node **404**, which in some examples (such as 5G), comprises a session management function (SMF). Session management node **404** manages connectivity and traffic routing of user data packets through cellular network **400**, for example, using a packet transmission parameter **406**. Packet transmission parameter **406** may specify packet priority for data traffic from video encoder node **200** (specifically, from cellular modem **220**), and or routing of data traffic through the various nodes of cellular network **400**.

(35) In some examples, packet traffic through cellular network **400** is encrypted, so cellular network **400** has no visibility into video quality. In such examples, the contribution of cellular network **400** to improving the quality of the video streams received by video decoder node **300** is adjusting packet transmission parameter **406** in response to receiving cellular network feedback **118**. For example, session management node **404** may increase packet priority for packets routed from video encoder node **200** to video decoder node **300**. Even if the packets are encrypted, the packet headers, which specify origination and destination, are visible to cellular network **400**.

(36) Additionally, session management node **404** may reroute packets through cellular network **400** in response to receiving cellular network feedback **118**. For example, cellular network **400** is illustrated as having a packet routing node **410**, which may be a first user plane function (UPF) in communication with base station **402**, and a packet routing node **412** which may be another UPF in communication with base station **402**. Cellular network **400** is also illustrated as having a packet routing node **414**, which may be a first packet data network gateway (PGW) in communication with other network **122**, and a packet routing node **416** which may be another PGW in communication with other network **122**.

(37) A first path **420** traverses base station **402**, packet routing node **410**, and packet routing node **414**. A second path **422** traverses base station **402**, packet routing node **412**, and packet routing node **416**. If data traffic from video encoder node **200** to video decoder node **300** is initially using path **420**, and cellular network feedback **118** indicates to session management node **404** that there is significant packet loss and/or packet delay, session management node **404** may reroute data traffic from video encoder node **200** to video decoder node **300** through path **422**.

(38) FIGS. 5A-5D together illustrate a flowchart **500** of exemplary operations associated with end-to-end emergency call testing by architecture **100** (e.g., flowchart **500** spans FIGS. 5A, 5B, 5C, and 5D). In some examples, at least a portion of flowchart **500** is performed using one or more computing devices **900** of FIG. 9. FIGS. 5A-5D are each divided into three portions: one portion for operations performed by video encoder node **200** and video cameras **102a-102c**, one portion for operations performed by cellular network **400**, and one portion for operations performed by video decoder node **300** and cloud video service **128**. This permits easy identification of how the various components of architecture **100** interact.

(39) Flowchart **500** commences with video cameras **102a-102c** capturing and storing live action video in operation **502**. In operation **504**, video cameras **102a-102c** transmit live action video as live action video streams **106a-106c** to video encoder **202**, and video encoder node **200** receives live action video streams **106a-106c** from video cameras **102a-102c** in operation **506**. Operations **502-506** remain ongoing through the remainder of flowchart **500**.

(40) In operation **508**, video encoder node **200** selects reference video streams **116a** and **116b** from plurality of reference video streams **206**, based on at least a similarity between each of reference video streams **116a** and **116b** and a respective one of live action video streams **106a** and **106b**. In operation **510**, video encoder node **200** identifies reference video streams **116a** and **116b** to video decoder node **300** (e.g., using identifications **216a** and **216b**).

(41) Video encoder node **200**, using video encoder **202**, encodes each of live action video stream **106a** and reference video stream **116a** according to video encoding parameters **210** in operation **512**. In some examples, video encoder node **200**, also encodes each of live action video stream **106b**, live action video stream **106c**, and reference video stream **116b** according to the same video encoding parameters **210** in operation **512**. In operation **514**, video encoder node **200** transmits encoded live action video streams **106a-106c** and encoded reference video streams **116a** and **116b** to video decoder node **300** across cellular network **400**. Operations **512** and **514** remain ongoing through operation **550** of flowchart **500**, when the video encoding parameters are changed.

(42) In operation **516**, cellular network **400** receives encoded live action video streams **106a-106c**, encoded reference video streams **116a** and **116b**, and identifications **216a** and **216b** of reference video streams **116a** and **116b** from video encoder node **200**. In some examples, during the first pass of flowchart **500** through operation **516**, live action video streams **106a-106c** and reference video streams **116a** and **116b** are encoded to set of video encoding parameters **210**. In some examples, during the next pass of flowchart **500** through operation **516** (i.e., upon returning from operation **554**), live action video streams **106a-106c** and reference video streams **116a** and **116b** are encoded to set of video encoding parameters **212**.

(43) Cellular network **400** transmits encoded live action video streams **106a-106c**, encoded reference video streams **116a** and **116b**, and identifications **216a** and **216b** of reference video streams **116a** and **116b** to video decoder node **300** in operation **518**. Operations **516** and **517** remain ongoing through the remainder of flowchart **500**, although identification **216a** of reference video stream **116a** and identification **216** of reference video stream **116b** may be transmitted only a single time.

(44) Video decoder node **300** receives identification **216a** of reference video stream **116a** and identification **216b** of reference video stream **116b** in operation **520**. In operation **522**, video decoder node **300**, using comparison video stream selector **304**, selects comparison video stream **316a** and **316b**, based on at least identifications **216a** and **216b**.

(45) In operation **524**, video decoder node **300** receives encoded live action video streams **106a-106c** and encoded reference video streams **116a** and **116b** from video encoder node **200** (through cellular network **400**). Video decoder node **300**, using video decoder **302**, decodes encoded live action video streams **106a-106c** and encoded reference video streams **116a** and **116b**. Cloud video service **128** distributes live action video streams **106a-106c** among disparate locations in video distribution environment **130** in operation **528**. Operations **524-528** remain ongoing through the remainder of flowchart **500**.

(46) In operation **530**, video decoder node **300** compares reference video stream **116a** with comparison video stream **316a** and also compares reference video stream **116b** with comparison video stream **316b**, using video quality assessor **320**. Based on at least the comparisons, video decoder node **300** determines video encoding parameter feedback **112** in operation **532** and transmits video encoding parameter feedback **112** to video encoder node **200** in operation **534**.

(47) In operation **536**, video decoder node **300** determines cellular network feedback **118**, based on at least receiving encoded live action video streams **106a-106c** and encoded reference video streams **116a** and **116b**, and transmits cellular network feedback **118** to cellular network **400** in operation **538**. In some examples, cellular network feedback **118** comprises an indication of missing packets and/or an indication of packet delay.

(48) Cellular network receives video encoding parameter feedback **112** from video decoder node **300** in operation **540** and transmits video encoding parameter feedback **112** to video encoder node **200** in operation **542**. Cellular network receives cellular network feedback **118** from video decoder node **300** in operation **544**, and adjusts at least one packet transmission parameter (e.g., packet transmission parameter **406** for data traffic from video encoder node **200** to video decoder node **300**) in operation **546**, based on at least receiving cellular network feedback **118**. In some examples, adjusting at least one packet transmission parameter comprises adjusting packet priority

and/or rerouting the data traffic from video encoder node **200** to video decoder node **300** within cellular network **400**.

(49) Video encoder node **200** receives video encoding parameter feedback **112** from video decoder node **300** (through cellular network **400**) in operation **548**. In operation **550**, video encoder node **200** sets a new set of video encoding parameters (e.g., set of video encoding parameters **212**, based on at least video encoding parameter feedback **112**).

(50) Video encoder node **200** continues to receive live action video as live action video streams **106a-106c** from cameras **104a-104c**, because operations **502-506** have remained ongoing. In operation **552**, video encoder node **200** encodes each of live action video streams **106a-106c** and reference video streams **116a** and **116b** according to set of video encoding parameters **212** (the new set of parameters), and further transmits encoded live action video streams **106a-106c** and encoded reference video streams **116a** and **116b** to video decoder node **300** in operation **554**. Operations **552** and **554** remain ongoing while flowchart **500** returns to operation **516**, to encode the video streams with the new video encoding parameters.

(51) FIG. **6** illustrates a flowchart **600** of exemplary operations associated with examples of architecture **100**. In some examples, at least a portion of flowchart **600** may be performed using one or more computing devices **900** of FIG. **9**. Flowchart **600** commences with operation **602**, which includes receiving, by a video encoder node, from a first video camera, a first live action video stream. Operation **604** includes selecting a first reference video stream. Operation **606** includes encoding each of the first live action video stream and the first reference video stream according to a first set of video encoding parameters. Operation **608** includes transmitting, to a video decoder node across a cellular network, the encoded first live action video stream and the encoded first reference video stream.

(52) Operation **610** includes receiving, from the video decoder node, video encoding parameter feedback. Operation **612** includes based on at least the video encoding parameter feedback, setting a second set of video encoding parameters. Operation **614** includes encoding each of the first live action video stream and the first reference video stream according to the second set of video encoding parameters. Operation **616** includes further transmitting, to the video decoder node, the encoded first live action video stream and the encoded first reference video stream.

(53) FIG. **7** illustrates a flowchart **700** of exemplary operations associated with examples of architecture **100**. In some examples, at least a portion of flowchart **700** may be performed using one or more computing devices **900** of FIG. **9**. Flowchart **700** commences with operation **702**, which includes receiving, by a video decoder node, from a video encoder node across a cellular network, an encoded first live action video stream and an encoded first reference video stream, the encoded first live action video stream and the encoded first reference video stream encoded according to the first set of video encoding parameters.

(54) Operation **704** includes decoding the first live action video stream and the first reference video stream. Operation **706** includes selecting a first comparison video stream. Operation **708** includes based on at least a comparison of the first reference video stream with the first comparison video stream, transmitting, to the video encoder node, video encoding parameter feedback.

(55) FIG. **8** illustrates a flowchart **800** of exemplary operations associated with examples of architecture **100**. In some examples, at least a portion of flowchart **800** may be performed using one or more computing devices **900** of FIG. **9**. Flowchart **800** commences with operation **802**, which includes receiving, by a cellular network, from a video encoder node, an encoded first live action video stream and an encoded first reference video stream, the encoded first live action video stream and the encoded first reference video stream encoded according to a first set of video encoding parameters.

(56) Operation **804** includes transmitting, to a video decoder node, the encoded first live action video stream and the encoded first reference video stream. Operation **806** includes receiving, from the video decoder node, video encoding parameter feedback. Operation **808** includes transmitting,

to the video encoder node, the video encoding parameter feedback. Operation **810** includes receiving, from the video decoder node, cellular network feedback. Operation **812** includes based on at least receiving the cellular network feedback, adjusting at least one packet transmission parameter for data traffic from the video encoder node to the video decoder node.

(57) FIG. **9** illustrates a block diagram of computing device **900** that may be used as any component described herein that may require computational or storage capacity. Computing device **900** has at least a processor **902** and a memory **904** that holds program code **910**, data area **920**, and other logic and storage **930**. Memory **904** is any device allowing information, such as computer executable instructions and/or other data, to be stored and retrieved. For example, memory **904** may include one or more random access memory (RAM) modules, flash memory modules, hard disks, solid-state disks, persistent memory devices, and/or optical disks. Program code **910** comprises computer executable instructions and computer executable components including any instructions necessary to perform operations described herein. Data area **920** holds any data necessary to perform operations described herein. Memory **904** also includes other logic and storage **930** that performs or facilitates other functions disclosed herein or otherwise required of computing device **900**. An input/output (I/O) component **940** facilitates receiving input from users and other devices and generating displays for users and outputs for other devices. A network interface **950** permits communication over a network **960** with a remote node **970**, which may represent another implementation of computing device **900**. For example, a remote node **970** may represent another of the above-noted nodes within architecture **100**.

Additional Examples

(58) A method of video distribution comprises: receiving, by a video encoder node, from a first video camera, a first live action video stream; selecting a first reference video stream; encoding each of the first live action video stream and the first reference video stream according to a first set of video encoding parameters; transmitting, to a video decoder node across a cellular network, the encoded first live action video stream and the encoded first reference video stream; receiving, from the video decoder node, video encoding parameter feedback; based on at least the video encoding parameter feedback, setting a second set of video encoding parameters; encoding each of the first live action video stream and the first reference video stream according to the second set of video encoding parameters; and further transmitting, to the video decoder node, the encoded first live action video stream and the encoded first reference video stream.

(59) Another method of video distribution comprises: receiving, by a video decoder node, from a video encoder node across a cellular network, an encoded first live action video stream and an encoded first reference video stream, the encoded second live action video stream and the encoded second reference video stream encoded according to the first set of video encoding parameters; decoding the first live action video stream and the first reference video stream; selecting a first comparison video stream; and based on at least a comparison of the first reference video stream with the first comparison video stream, transmitting, to the video encoder node, video encoding parameter feedback.

(60) Another method of video distribution comprises: receiving, by a cellular network, from a video encoder node, an encoded first live action video stream and an encoded first reference video stream, the encoded first live action video stream and the encoded first reference video stream encoded according to a first set of video encoding parameters; transmitting, to a video decoder node, the encoded first live action video stream and the encoded first reference video stream; receiving, from the video decoder node, video encoding parameter feedback; transmitting, to a video decoder node, the video encoding parameter feedback; receiving, from the video decoder node, cellular network feedback; and based on at least receiving the cellular network feedback, adjusting at least one packet transmission parameter for data traffic from the video encoder node to the video decoder node.

(61) A system for video distribution comprises: a processor; and a computer-readable medium

storing instructions that are operative upon execution by the processor to: receive, by a video encoder node, from a first video camera, a first live action video stream; select a first reference video stream; encode each of the first live action video stream and the first reference video stream according to a first set of video encoding parameters; transmit, to a video decoder node across a cellular network, the encoded first live action video stream and the encoded first reference video stream; receive, from the video decoder node, video encoding parameter feedback; based on at least the video encoding parameter feedback, set a second set of video encoding parameters; encode each of the first live action video stream and the first reference video stream according to the second set of video encoding parameters; and further transmit, to the video decoder node, the encoded first live action video stream and the encoded first reference video stream.

(62) Another system for video distribution comprises: a processor; and a computer-readable medium storing instructions that are operative upon execution by the processor to: receive, by a video decoder node, from a video encoder node across a cellular network, an encoded first live action video stream and an encoded first reference video stream, the encoded second live action video stream and the encoded second reference video stream encoded according to the first set of video encoding parameters; decode the first live action video stream and the first reference video stream; select a first comparison video stream; and based on at least a comparison of the first reference video stream with the first comparison video stream, transmit, to the video encoder node, video encoding parameter feedback.

(63) Another system for video distribution comprises: a processor; and a computer-readable medium storing instructions that are operative upon execution by the processor to: receive, by a cellular network, from a video encoder node, an encoded first live action video stream and an encoded first reference video stream, the encoded first live action video stream and the encoded first reference video stream encoded according to a first set of video encoding parameters; transmit, to a video decoder node, the encoded first live action video stream and the encoded first reference video stream; receive, from the video decoder node, video encoding parameter feedback; transmit, to the video encoder node, the video encoding parameter feedback; receive, from the video decoder node, cellular network feedback; and based on at least receiving the cellular network feedback, adjust at least one packet transmission parameter for data traffic from the video encoder node to the video decoder node.

(64) One or more example computer storage devices has computer-executable instructions stored thereon, which, upon execution by a computer, cause the computer to perform operations comprising: receiving, by a video encoder node, from a first video camera, a first live action video stream; selecting a first reference video stream; encoding each of the first live action video stream and the first reference video stream according to a first set of video encoding parameters; transmitting, to a video decoder node across a cellular network, the encoded first live action video stream and the encoded first reference video stream; receiving, from the video decoder node, video encoding parameter feedback; based on at least the video encoding parameter feedback, setting a second set of video encoding parameters; encoding each of the first live action video stream and the first reference video stream according to the second set of video encoding parameters; and further transmitting, to the video decoder node, the encoded first live action video stream and the encoded first reference video stream.

(65) One or more additional example computer storage devices has computer-executable instructions stored thereon, which, upon execution by a computer, cause the computer to perform operations comprising: receiving, by a video decoder node, from a video encoder node across a cellular network, an encoded first live action video stream and an encoded first reference video stream, the encoded first live action video stream and the encoded first reference video stream encoded according to the first set of video encoding parameters; decoding the first live action video stream and the first reference video stream; selecting a first comparison video stream; and based on at least a comparison of the first reference video stream with the first comparison video stream,

transmitting, to the video encoder node, video encoding parameter feedback.

(66) One or more additional example computer storage devices has computer-executable instructions stored thereon, which, upon execution by a computer, cause the computer to perform operations comprising: receiving, by a cellular network, from a video encoder node, an encoded first live action video stream and an encoded first reference video stream, the encoded first live action video stream and the encoded first reference video stream encoded according to a first set of video encoding parameters; transmitting, to a video decoder node, the encoded first live action video stream and the encoded first reference video stream; receiving, from the video decoder node, video encoding parameter feedback; and transmitting, to a video decoder node, the video encoding parameter feedback; receiving, from the video decoder node, cellular network feedback; and based on at least receiving the cellular network feedback, adjusting at least one packet transmission parameter for data traffic from the video encoder node to the video decoder node.

(67) Alternatively, or in addition to the other examples described herein, examples include any combination of the following: the first set of video encoding parameters comprises at least two parameters selected from the list consisting of bit rate, compression codec identification, resolution, frame rate, bit depth, and key frame interval; the second set of video encoding parameters comprises at least two parameters selected from the list consisting of bit rate, compression codec identification, resolution, frame rate, bit depth, and key frame interval; receiving, from a second video camera, a second live action video stream; selecting a second reference video stream; encoding each of the second live action video stream and the second reference video stream according to the encoding of the first live action video stream; transmitting, to the video decoder node, the encoded second live action video stream and the encoded second reference video stream; identifying, by the video encoder node, to the video decoder node, the first reference video stream; the video encoding parameter feedback comprises parameter adjustments; the video encoding parameter feedback comprises video quality metrics; receiving, by the cellular network, from the video encoder node, identification of the first and second reference video streams; transmitting, by the cellular network, to the video decoder node, the identification of the first and second reference video streams; encoding each of the second live action video stream and the second reference video stream according to the second set of video encoding parameters; further transmitting, to the video decoder node, the encoded second live action video stream and the encoded second reference video stream; receiving, from the video encoder node, an encoded second live action video stream and an encoded second reference video stream from across a cellular network; decoding the second live action video stream and the second reference video stream; selecting a second comparison video stream, wherein the video encoding parameter feedback is based on at least the comparison of the first reference video stream with the first comparison video stream and a comparison of the second reference video stream with the second comparison video stream; receiving, from the video encoder node, an identification of the first reference video stream; the video encoding parameter feedback comprises parameter adjustments or video quality metrics; based on at least receiving the encoded first live action video stream and the encoded first reference video stream, determining cellular network feedback; transmitting, to the cellular network, the cellular network feedback; the cellular network feedback comprises an indication of missing packets and/or an indication of packet delay; receiving, by from the video encoder node, an encoded second live action video stream and an encoded second reference video stream, the encoded second live action video stream and the encoded second reference video stream encoded according to the first set of video encoding parameters; transmitting, to the video decoder node, the encoded second live action video stream and the encoded second reference video stream; the cellular network comprises a 5G cellular network; the cellular network feedback comprises an indication of missing packets and/or an indication of packet delay; adjusting at least one packet transmission parameter comprises adjusting packet priority; adjusting at least one packet transmission parameter comprises rerouting the data traffic from the video encoder node to the video decoder node within the cellular network;

capturing and storing, by the first video camera and the second video camera, live action video; transmitting, by the first video camera, to the video encoder, live action video as the first live action video stream; transmitting, by the second video camera, to the video encoder, live action video as the second live action video stream; selecting the first reference video stream from a plurality of reference video streams based on at least a similarity between the first reference video stream and the first live action video stream; selecting the second reference video stream from the plurality of reference video streams based on at least a similarity between the second reference video stream and the second live action video stream; identifying, by the video encoder node, to the video decoder node, the second reference video stream; receiving, by the video decoder node, from the video encoder node, an identification of the second reference video stream; selecting the first comparison video stream based on at least the identification of the first reference video stream; selecting the second comparison video stream based on at least the identification of the first reference video stream; comparing the first reference video stream with the first comparison video stream; comparing the second reference video stream with the second comparison video stream; based on at least the comparison of the first reference video stream with the first comparison video stream, determining the video encoding parameter feedback; and based on at least the comparison of the first reference video stream with the first comparison video stream and the comparison of the second reference video stream with the second comparison video stream, determining the video encoding parameter feedback.

(68) The order of execution or performance of the operations in examples of the disclosure illustrated and described herein is not essential, unless otherwise specified. That is, the operations may be performed in any order, unless otherwise specified, and examples of the disclosure may include additional or fewer operations than those disclosed herein. For example, it is contemplated that executing or performing a particular operation before, contemporaneously with, or after another operation is within the scope of aspects of the disclosure. It will be understood that the benefits and advantages described above may relate to one embodiment or may relate to several embodiments. When introducing elements of aspects of the disclosure or the examples thereof, the articles “a,” “an,” “the,” and “said” are intended to mean that there are one or more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. The term “exemplary” is intended to mean “an example of.”

(69) Having described aspects of the disclosure in detail, it will be apparent that modifications and variations are possible without departing from the scope of aspects of the disclosure as defined in the appended claims. As various changes may be made in the above constructions, products, and methods without departing from the scope of aspects of the disclosure, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

Claims

1. A method of video distribution, the method comprising: receiving, by a video encoder node, from a first video camera, a first live action video stream; selecting a first reference video stream, the first reference video stream including different content than the first live action video stream; encoding each of the first live action video stream and the first reference video stream according to a first set of video encoding parameters to obtain a first encoded first live action video stream and a first encoded first reference video stream; transmitting, to a video decoder node across a cellular network, the first encoded first live action video stream and the first encoded first reference video stream; receiving, from the video decoder node, video encoding parameter feedback corresponding to the first reference video stream, wherein the video encoding parameter feedback is generated based on a comparison of a decoded version of the first encoded first reference video stream and a

local copy of the first reference video stream; based on at least the video encoding parameter feedback, setting a second set of video encoding parameters for the first live action video stream; encoding each of the first live action video stream and the first reference video stream according to the second set of video encoding parameters to obtain a second encoded first live action video stream and a second encoded first reference video stream; and transmitting, to the video decoder node, the second encoded first live action video stream and the second encoded first reference video stream.

2. The method of claim 1, wherein the first set of video encoding parameters and the second set of video encoding parameters each comprises at least two parameters selected from the list consisting of: bit rate, compression codec identification, resolution, frame rate, bit depth, and key frame interval.

3. The method of claim 1, further comprising: receiving, from a second video camera, a second live action video stream; selecting a second reference video stream; encoding each of the second live action video stream and the second reference video stream according to the encoding of the first live action video stream to obtain a first encoded second live action video stream and a first encoded second reference video stream; and transmitting, to the video decoder node, the first encoded second live action video stream and the first encoded second reference video stream.

4. The method of claim 3, further comprising: encoding each of the second live action video stream and the second reference video stream according to the second set of video encoding parameters to obtain a second encoded second live action video stream and a second encoded second reference video stream; and further transmitting, to the video decoder node, the second encoded second live action video stream and the second encoded second reference video stream.

5. The method of claim 1, further comprising: identifying, by the video encoder node, to the video decoder node, the first reference video stream.

6. The method of claim 1, wherein the video encoding parameter feedback comprises parameter adjustments.

7. The method of claim 1, wherein the video encoding parameter feedback comprises video quality metrics.

8. A system comprising: a processor; and a computer-readable medium storing programming instructions that, when executed by the processor, cause the processor to: receive from a first video camera, a first live action video stream; select a first reference video stream, the first reference video stream including different content than the first live action video stream; encode each of the first live action video stream and the first reference video stream according to a first set of video encoding parameters to obtain a first encoded first live action video stream and a first encoded first reference video stream; transmit, to a video decoder node across a cellular network, the first encoded first live action video stream and the first encoded first reference video stream; receive, from the video decoder node, video encoding parameter feedback corresponding to the first reference video stream, wherein the video encoding parameter feedback is generated based on a comparison of a decoded version of the first encoded first reference video stream and a local copy of the first reference video stream; based on at least the video encoding parameter feedback, set a second set of video encoding parameters for the first live action video stream; encode each of the first live action video stream and the first reference video stream according to the second set of video encoding parameters to obtain a second encoded first live action video stream and a second encoded first reference video stream; and transmit, to the video decoder node, the second encoded first live action video stream and the second encoded first reference video stream.

9. The system of claim 8, wherein the first set of video encoding parameters and the second set of video encoding parameters each comprises at least two parameters selected from the list consisting of: bit rate, compression codec identification, resolution, frame rate, bit depth, and key frame interval.

10. The system of claim 8, wherein the programming instructions further cause the processor to:

identify the first reference video stream to the video decoder node.

11. The system of claim 8, wherein the video encoding parameter feedback comprises parameter adjustments.

12. The system of claim 8, wherein the video encoding parameter feedback comprises video quality metrics.

13. A computer program product that includes a computer-readable medium memory storing programming instructions that, when executed by a processor, cause the processor to: receive from a first video camera, a first live action video stream; select a first reference video stream, the first reference video stream including different content than the first live action video stream; encode each of the first live action video stream and the first reference video stream according to a first set of video encoding parameters to obtain a first encoded first live action video stream and a first encoded first reference video stream; transmit, to a video decoder node across a cellular network, the first encoded first live action video stream and the first encoded first reference video stream; receive, from the video decoder node, video encoding parameter feedback corresponding to the first reference video stream, wherein the video encoding parameter feedback is generated based on a comparison of a decoded version of the first encoded first reference video stream and a local copy of the first reference video stream; based on at least the video encoding parameter feedback, set a second set of video encoding parameters for the first live action video stream; encode each of the first live action video stream and the first reference video stream according to the second set of video encoding parameters to obtain a second encoded first live action video stream and a second encoded first reference video stream; and transmit, to the video decoder node, the second encoded first live action video stream and the second encoded first reference video stream.

14. The computer program product of claim 13, wherein the first set of video encoding parameters and the second set of video encoding parameters each comprises at least two parameters selected from the list consisting of: bit rate, compression codec identification, resolution, frame rate, bit depth, and key frame interval.

15. The computer program product of claim 13, wherein the programming instructions further cause the processor to: identify the first reference video stream to the video decoder node.

16. The computer program product of claim 13, wherein the video encoding parameter feedback comprises parameter adjustments.

17. The computer program product of claim 13, wherein the video encoding parameter feedback comprises video quality metrics.
