

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408622
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Veness; David et al.

Pet carrier

Abstract

A carrier includes a body and a cover portion. The body has a bottom portion and a top portion and an opening in the top portion. The bottom portion is configured to be placed on a surface. The opening is the only opening sized and configured to enable an animal to enter or exit the body and enables an animal to enter or exit the body in a vertical manner when the bottom portion is placed on the surface. The cover portion is sized and configured to fit within the opening of the top portion. The cover portion is hingedly attached to the top portion at a first side and includes a latching mechanism at a second side. The latching mechanism enables the cover to be disposed in a latched state to close the opening in the top portion.

Inventors:	Veness; David (Fort Worth, TX), Jackson; Jill (Fort Worth, TX)
Applicant:	PLUTO OPCO (CAYMAN), LLC (George Town, KY)
Family ID:	78220861
Assignee:	Doskocil Manufacturing Company, Inc. (Arlington, TX)
Appl. No.:	17/165122
Filed:	February 02, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210329879 A1	Oct. 28, 2021

Related U.S. Application Data

us-provisional-application US 63016383 20200428

Publication Classification

Int. Cl.: A01K1/02 (20060101)

U.S. Cl.:

CPC **A01K1/0245** (20130101);

Field of Classification Search

CPC: A01K (1/0236); A01K (1/0245); A01K (1/0254); A01K (1/0272); A01K (1/0281); A01K (1/029)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2294708	12/1941	Barnett	292/42	E05D 13/06
4010880	12/1976	Guillot-Munoz	119/28.5	A01K 1/0272
5016926	12/1990	Sharp	292/42	A01K 1/0245
6588373	12/2002	Strzempko	119/416	A01K 1/031
8584618	12/2012	Batson	119/496	A01K 1/0272
9095120	12/2014	Skaggs	N/A	A01K 1/0245
D800394	12/2016	Walter	D30/112	A01K 1/0245
10653106	12/2019	Northrop	N/A	A01K 1/0125
2005/0035166	12/2004	Kresge	224/431	B62J 9/23
2009/0114688	12/2008	Beeler	119/500	B62J 9/23
2011/0017145	12/2010	Northrop	119/497	A01K 1/0254
2011/0041774	12/2010	Northrop	119/500	A01K 1/0245
2011/0079971	12/2010	Lulevitch	280/28.12	A01K 1/0245
2011/0203528	12/2010	Northrop	119/497	A01K 1/033
2012/0037083	12/2011	Greene	119/497	A01K 1/0245
2013/0220231	12/2012	Hovsepien	119/496	B62J 9/24
2015/0144070	12/2014	Qiu	119/496	E05C 9/04
2016/0066535	12/2015	Anderson	119/473	A01K 1/0245
2017/0318774	12/2016	Taylor	N/A	A01K 1/034
2018/0153134	12/2017	Hedley	N/A	A01K 1/0236
2018/0288964	12/2017	Tamiozzo	N/A	A01K 1/0245
2019/0183088	12/2018	Yang	N/A	A01K 1/0245
2019/0230894	12/2018	Pan	N/A	A01K 1/0272
2020/0060219	12/2019	Levin	N/A	A01K 1/033
2020/0296919	12/2019	Jakubowski	N/A	A01K 1/0245
2021/0120778	12/2020	Prehogan	N/A	A01K 31/08
2021/0329881	12/2020	Paxson	N/A	A01K 1/0245
2022/0378011	12/2021	Crampton	N/A	A01K 1/0356

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2486893	12/2011	GB	A01K 1/0245

OTHER PUBLICATIONS

Top Load Plastic Kennels, prior to Mar. 6, 2020, 8 pages. cited by applicant

Primary Examiner: Truong; Katelyn T

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

RELATED APPLICATIONS (1) This application claims priority to U.S. Provisional Patent Application No. 63/016,383 filed on Apr. 28, 2020, which is hereby incorporated herein by

reference.

BACKGROUND

Field of the Invention

(1) The present disclosure relates to a pet carrier. In particular, the present invention relates to a pet carrier with a single opening in the top surface thereof.

Background Art

(2) There are many types of conventional pet carriers that are designed to transport pets or animals. Many conventional carriers are plastic molded two-piece structures. When assembled, the two piece structures form an opening in the front of the carrier that enables an animal to enter and exit. These carriers can also include a handle on the top portion that enables the carrier to be carried.

SUMMARY

(3) It has been determined that a need for an improved pet carrier exists. Many of the conventional pet carriers include an opening in the front of the carrier. As can be understood, it has been determined that many animals, in particular, cats, do not like being placed into the front of a carrier. The animal can resist, resulting in a difficult and dangerous situation. Accordingly, it has been determined that the front opening in many carriers is undesired or unused.

(4) Therefore, it has been determined that a carrier having a single top loading opening is desired. A first aspect of such a carrier includes a body and a cover portion. The body has a bottom portion and a top portion and an opening in the top portion. The bottom portion is configured to be placed on a surface. The opening is the only opening sized and configured to enable an animal to enter or exit the body and enables an animal to enter or exit the body in a vertical manner when the bottom portion is placed on the surface. The cover portion is sized and configured to fit within the opening of the top portion. The cover portion is hingedly attached to the top portion at a first side and includes a latching mechanism at a second side. The latching mechanism enables the cover to be disposed in a latched state to close the opening in the top portion.

(5) In a second aspect of the carrier according to the first aspect the cover portion has an opening therein.

(6) In a third aspect of the carrier according to the first or second aspect, a wire grating at least partial blocks the opening in the cover portion.

(7) In a fourth aspect of the carrier according to any of the previous aspects, the bottom portion is detachable from the top portion.

(8) In a fifth aspect of the carrier according to any of the previous aspects, the latching mechanism is a spring loaded push button mechanism.

(9) In a sixth aspect of the carrier according to any of the previous aspects, the latching mechanism includes at least one rod configured to enter an opening in the top portion.

(10) In a seventh aspect of the carrier according to any of the previous aspects, the body is formed from plastic.

(11) In an eighth aspect of the carrier according to any of the previous aspects, the cover portion includes a carrier handle is hingedly connected to the cover portion.

(12) In a ninth aspect of the carrier according to any of the previous aspects, the top portion includes an edge configured to overlap an outside of the bottom portion.

(13) In a tenth aspect of the carrier according to any of the previous aspects, the bottom portion is sized and configured to fit within an interior of the top portion when the bottom portion is inverted.

(14) An eleventh aspect of the disclosure includes a method of forming a carrier. In this aspect the method comprises forming a bottom portion, the bottom portion configured to be placed on a surface, forming a top portion with an opening, the opening being the only opening sized and configured to enable an animal to enter or exit the body and enables an animal to enter or exit the body in a vertical manner when the bottom portion is placed on the surface, and positioning a cover portion within the opening of the top portion, the cover being hingedly attached to the top portion

at a first side and including a latching mechanism at a second side, the latching mechanism enabling the cover to be disposed in a latched state to close the opening in the top portion.

(15) In a twelfth aspect of the present invention according to any of the previous aspects, the positioning in the cover portion includes positioning the cover portion having an opening therein.

(16) In a thirteenth aspect of the present invention according to any of the previous aspects, a wire grating at least partial blocks the opening in the cover portion.

(17) A fourteenth aspect of the present invention according to any of the previous aspects, further includes attaching the bottom portion to the top portion.

(18) In a fifteenth aspect of the present invention according to any of the previous aspects, the latching mechanism is a spring loaded push button mechanism.

(19) In a sixteenth aspect of the present invention according to any of the previous aspects, the latching mechanism includes at least one rod configured to enter an opening in the top portion.

(20) In a seventeenth aspect of the present invention according to any of the previous aspects, the forming the bottom portion and the forming the top portion include forming the bottom portion and forming the top portion from plastic.

(21) An eighteenth aspect of the present invention according to any of the previous aspects, further includes hingedly connecting a carrier handle to the cover portion.

(22) In a nineteenth aspect of the present invention according to any of the previous aspects, the top portion includes an edge configured to overlap an outside of the bottom portion.

(23) A twentieth aspect of the present invention according to any of the previous aspects, further includes inverting the bottom portion and positioning the bottom portion within an interior of the top portion.

(24) The embodiments disclosed herein provide a carrier with a single top loading opening for animals that reduces or eliminates the resistance from animals, resulting in an easier and safer situation in which an animal can be loaded.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The invention will be explained in more detail hereinafter with reference to the drawings.
- (2) FIG. 1 is a top perspective view of the a carrier according to an embodiment of the present disclosure;
- (3) FIG. 2 is a side elevational view of the carrier of FIG. 1;
- (4) FIG. 3 is a front perspective view of the carrier of FIG. 1;
- (5) FIG. 4 is a top plan view of the carrier of FIG. 1;
- (6) FIG. 5 is a bottom perspective view of the carrier of FIG. 1;
- (7) FIG. 6 is a bottom plan view of the carrier of FIG. 1;
- (8) FIG. 7 is a cross section al view taken along line 7-7 of FIG. 4;
- (9) FIG. 8 is an enlarged cross section view of the connection between the top portion and the bottom portion;
- (10) FIG. 9 is an exploded view of the carrier of FIG. 1;
- (11) FIG. 10 is a top perspective view of the cover portion removed from the top portion of the carrier of FIG. 1, and the latching mechanism illustrated in an exploded view;
- (12) FIG. 11 is a top perspective view of the carrier of FIG. 1, with the cover portion in an opened configuration; and
- (13) FIG. 12 illustrates the entry of an animal into the carrier illustrated in the opened state in FIG. 11.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (14) Selected embodiments will now be explained with reference to the drawings. It will be

apparent to those skilled in the art from this disclosure that the following descriptions of the embodiments are provided for illustration only and not for the purpose of limiting the invention as defined by the appended claims and their equivalents.

(15) Referring initially to FIGS. 1-6, a carrier **10** is illustrated in accordance with a first embodiment. The carrier **10** includes a body **12** with a bottom portion **14**, a top portion **16** with an opening **18** therein and a cover portion **20**.

(16) The bottom portion **14** is preferably a plastic molded structure with a bottom surface **22** and a wall surface **24** extending upwardly from the bottom surface **22**. The wall surface **24** is generally oval and extends from the bottom surface at an angle other than 90 degrees, such that the wall surface **24** extends radially outwardly from the bottom surface **22**. Such a configuration enables the interior I of the carrier **10** to increase in an upward direction, as shown in FIG. 7. This structure forms an increased interior area for the animal A or pet, while reducing the overall footprint of the carrier **10**. In one embodiment the bottom portion **14** can have a stepped configuration in which the bottom portion **14** has a series of rings **14a** and **14b** that increase in cross sectional area in the upward direction. The sides of each of the rings **14a** and **14b** can have an arcuate configuration.

(17) As shown in FIGS. 7 and 8, the upper edge **26** of the bottom portion **14** can include an outwardly extending portion or flange **28** that is connected to a downwardly extended lip **30**. The outwardly extending portion **28** can be configured to accept fasteners **32** that extend through the top portion **16** and into the bottom portion **14** to couple the top portion **16** to the bottom portion **14** as discussed in more detail below.

(18) The top portion **16** is preferably a plastic molded structure with a top surface **34** and a wall surface **36** extending downwardly from the top surface **34**. The wall surface **36** is generally oval and extends from the top surface **34** at an angle other than 90 degrees, such that the wall surface **36** extends radially outwardly from the top surface **34**. Such a configuration enables the interior I of the carrier **10** to increase in a downward direction, as shown in FIG. 7. This structure forms an increased interior area for the animal A, while reducing the overall top surface of the carrier **10**. In one embodiment, the top portion **16** can have a stepped configuration in which the top portion **16** has a series of rings **16a-16c** that increase in cross sectional area in the downward direction. The sides of each of these rings **16a-16c** can have an arcuate configuration. The bottom of the top portion **16** is defined by ring **16c** having an increased diameter or the largest diameter. The ring **16c** thus forms an edge **38** that extends slightly outwardly.

(19) As can be understood, the top portion **16**, when inverted has the same basic configuration as the bottom portion **14**, such that the bottom portion **14** is capable of fitting into an interior of the top portion **16** when the bottom portion **14** is inverted. Such a configuration saves space for storage and shipping purposes.

(20) The top surface **34** of the top portion **16** can include the opening **18** therein. The opening **18** is the only opening in the carrier **10** that is sized and configured to enable an animal A to enter or exit the body **12**. Furthermore, as shown in FIGS. 11 and 12, the opening **18** enables an animal A to enter or exit the body **12** in a vertical manner when the bottom portion **14** is placed on an exterior surface S. In one embodiment, the opening **18** has an inner circumference **40** such that the opening **18** has a generally oval shape or configuration. Specifically, in this embodiment the opening **18** can have a first straight edge **40a**, a second straight edge **40b**, a first curved part **40c** and a second curved part **40d**. The first straight edge **40a** can include a first hinge structure **42** that connects the top portion **16** to the cover portion **20**.

(21) As shown in FIGS. 3, 4 and 11, the cover portion **20** is sized and configured to fit within or cover the opening **18** in the top portion **16**. Thus, as can be understood, the outer circumference **44** of the cover portion **20** has the same general shape as the inner circumference **40** of the opening **18**. In one embodiment the cover portion **20** has an outer circumference such that the cover portion **20** has a generally oval shape or configuration. Specifically, in this embodiment the cover portion **20** can have a first straight edge or side **44a**, a second straight edge or side **44b**, a first curved part **44c**

and a second curved part **44d**. The first straight edge **44d** can include a second hinge structure **45** that interacts with the first hinge structure **42** to connect the top portion **16** to the cover portion **20**. (22) The cover portion **20** is preferably molded plastic and can include an opening **46** and a locking or latching mechanism **48**. As shown in FIG. **4**, the opening **46** in the cover portion **20** has an outer periphery **50** that at least partially follows the contour of the outer circumference **44** of the cover portion **20**. The opening **46**, as shown in FIG. **4**, is not centered within the cover **20**. Specifically, the opening **46** (also referred to as viewing opening) is closer to the first straight edge or side **44a** than to the second straight edge or side **44b** of the cover **20**, as shown in FIG. **4**. Further, the opening **46** can have a plurality of wires or rods **52a** and **52b** that form a wire grating **52** to block the opening **46** so as to restrict passage through the opening **46**. In one embodiment, the plurality of wires **52** include a set of vertical wires **52b** and a set of horizontal wires **52a**. The vertical wires **52b** are transverse (or perpendicular) to the horizontal wires **52a**. However, it is noted that the plurality of wires **52a** and **52b** can have any suitable configuration. The plurality of wires **52a** and **52b** restrict passage of the animal A through the opening in the cover portion **20**, while also allowing the animal A to see through the opening **46**. Seeing through the opening **46**, enables the animal A to feel more at ease and calm. It is further noted that the opening **46** in the cover portion **20** can be blocked or restricted in any suitable manner with any suitable structure and in one embodiment, the opening **46** can be completely blocked or be nonexistent.

(23) As shown in FIGS. **9** and **10**, the locking mechanism **48** is disposed at the second straight edge **44b** of the cover portion **20** and includes a first rod **54**, a second rod **56**, a first spring **58**, a second spring **60**, and an attaching structure **62**. The attaching structure **62** is a plastic molded structure that is attached to the cover portion **20**. The attaching structure **62** can be generally oval and includes a first recess **62a** and a second recess **62b** separated from the first recess **62a** by a divider **62c**. The cover portion **20** includes first and second passages **64** and **66** therein for the first and second rods **54** and **56**.

(24) The first and second rods **54** and **56** can be metal and can include longitudinal sections **54a** and **56a** and traverse sections **54b** and **56b**. The longitudinal sections **54a** and **56a** are disposed in the passages **64** and **66** in the attaching structure **62** with the transverse sections **54b** and **56b** disposed in a respective recess **62a** and **62b**. The longitudinal sections **54a** and **56a** have a sufficient length to extend out of the passages **64** and **66** in the attaching structure **62** and into an opening **71** in the inner circumference **40** of the opening **18** in the top portion **16** to lock the cover portion **20** in a closed state to restrict passage through the opening **18** in the top portion **16**. As shown in FIG. **11**, the rods **64** and **56** can be attached to at least one (or a plurality) of the plurality of wires **52a** and **52b** with a support structure **70** to support and hold the rods **54** and **56** in place.

(25) A handle **72** can be attached to at least one of the plurality of wires **52a** and **52b**. The handle **72** can be hingedly attached to a wire so that the handle **72** lays flat against some of the plurality of wires **52a** and **52b** and/or a portion of the cover portion **20**. The handle **72** can be arcuate in shape and have an ergonomic configuration to fit comfortably in the hand of a user. Further the handle and the connection to the plurality of wires is sufficiently strong to enable the carrier **10** to be carried with an animal A disposed in the interior I. As shown in FIG. **4**, the handle **72** is centered with respect to the cover portion **20**. However, because the opening **46** is not centered relative to the cover portion **20**, the handle **72** is not centered relative to the wire grating **52** within the opening **46**.

(26) The carrier **10** is a molded product, in which the top portion **16**, the bottom portion **14** and the cover portion **20** can be separately molded. The top portion **16** is formed with the opening **18**, which, in one embodiment is the only opening sized and configured to enable an animal A to enter or exit the body **12** and enables an animal A to enter or exit the body **12** in a vertical manner when the bottom portion **14** is placed on the surface S.

(27) The top portion **16** can be permanently, semi-permanently or removably attached to the bottom portion **14**. In one embodiment, the top portion **16** is attached to the bottom portion **14** such that the

edge **38** of the ring **61c** extends over the outwardly extending portion **28**. Fasteners or screws **32** can pass through recesses **74** in the ring **16c** and into the outwardly extending portion **28** to attach the top portion **16** to the bottom portion **14**.

(28) The cover portion **20** can have the plurality of wires **52a** and **52b** permanently, semi-permanently or removably attached thereto and the handle **72** can be attached to the at least one of the plurality of wires **52a** and **52b**. The locking mechanism **48** can then be attached to the cover portion **20**. The springs **58** and **60** are disposed such that they are between the transverse portions **54b** and **56b** and a surface of the attaching structure **62** to bias the rods **54** and **56** into the locked position. That is, the springs **58** and **60** are configured and arranged to bias the rods **54** and **56** outwardly such that the ends **54c** and **56c** of each of the rods **54** and **56** extends into the opening **71** in the inner circumference **40** of the opening **18** in the top portion **16**, such that the locking mechanism **48** can be considered a spring loaded push button mechanism.

(29) The cover portion **20** can be attached to the top portion **16** by connecting the first hinge structure **42** to the second hinge structure **45**. In one embodiment, the first hinge structure **42** can be a generally cylindrical plastic molded member and the second hinge structure **45** can be an arcuate molded member that has an inner diameter that is substantially the same as the outer diameter of the first hinge structure **42**. Thus, the second hinge structure **45** can be snap fit onto the first hinge structure **42**. In one embodiment, the second hinge structure **45** extends more than 180 degrees around the first hinge structure **42** and less than 360 degrees around the first hinge structure **42** such that an opening or a gap **45a** is formed in the circumference of the second hinge structure **45**. Moreover, the second hinge structure **45** has a thickness to diameter ratio that enables the opening in the circumference to be expanded when the first hinge structure **42** is pressed into the opening and elastically snap back into place around the outer circumference of the first hinge structure **42**.

(30) To use the carrier **10**, the user can place fingers (e.g., a fore finger and a thumb) into the recess **62a** and **62b** of the attaching structure **62** and simultaneously engage the transverse portions **54b** and **56b** of the first and second rods **54** and **56**. The user can then squeeze the transverse portions **54b** and **56b** together against the biasing force of the springs **58** and **60**. The ends **54c** and **56c** of the longitudinal portions **54a** and **56a** of the rods **54** and **56** will then retract out of the openings in the inner circumference **40** of the opening **18**. Thus, the cover portion **20** is free to move in a hinged manner to enable the opening **18** to be exposed.

(31) As shown in FIG. **12**, the carrier **10** is configured to be placed on a surface **S**, with the opening **18** being the only opening sized and configured to enable an animal **A** to enter or exit the body **12** and enables an animal **A** to enter or exit the body **12** in a vertical manner. Thus, the animal **A** can enter or be placed into the interior **I** of the carrier **10** through the opening **18**. Once the animal **A** is disposed in the interior **I** the cover portion **20** can be placed so as to block the opening **18** in the top portion **16** and the latching mechanism **48** can lock the cover portion **20** in the latched or locked state to prevent the animal **A** from exiting the carrier **10**.

(32) In one embodiment, the user can apply pressure to the transverse portions **54b** and **56b** to cause the ends **54c** and **56c** of the rods **54** and **56** to be withdrawn and release the pressure once the cover portion **20** is properly positioned. Alternatively, the inner circumference **40** of the opening **18** in the top portion **16** can include slanted surfaces that are capable of engaging the ends **54c** and **56c** of the rods **54** and **56** such that the ends **54c** and **56c** of the rods **54** and **56** slides there along and are biased inwardly against the springs **58** and **60**. Once the cover portion **20** is positioned in the opening **18** in the top portion **16** the ends **54c** and **56c** of the rods **54** and **56** engage and enter the openings in the inner circumference **40** of the opening **18** in the top portion **16**.

(33) The embodiments disclosed herein provide a carrier with a single top loading opening for animals that reduces or eliminates the resistance from animals, resulting in an easier and safer situation in which an animal can be loaded. The carrier further provides a safe and secure carrier for an animal.

(34) In understanding the scope of the present invention, the term “comprising” and its derivatives,

as used herein, are intended to be open ended terms that specify the presence of the stated features, elements, components, groups, integers, and/or steps, but do not exclude the presence of other unstated features, elements, components, groups, integers and/or steps. The foregoing also applies to words having similar meanings such as the terms, “including”, “having” and their derivatives. Also, the terms “part,” “section,” “portion,” “member” or “element” when used in the singular can have the dual meaning of a single part or a plurality of parts. Also as used herein to describe the above embodiment(s), the following directional terms “front”, “downward”, “vertical”, “horizontal”, and “transverse” as well as any other similar directional terms refer to those directions relative a carrier **10**. Accordingly, these terms, as utilized to describe the present invention should be interpreted relative to a carrier **10**.

(35) The term “configured” as used herein to describe a component, section or part of a device includes hardware and/or software that is constructed and/or programmed to carry out the desired function.

(36) The terms of degree such as “substantially”, as used herein mean a reasonable amount of deviation of the modified term such that the end result is not significantly changed.

(37) While only selected embodiments have been chosen to illustrate the present invention, it will be apparent to those skilled in the art from this disclosure that various changes and modifications can be made herein without departing from the scope of the invention as defined in the appended claims. For example, the size, shape, location, or orientation of the various components can be changed as needed and/or desired. Components that are shown directly connected or contacting each other can have intermediate structures disposed between them. The functions of one element can be performed by two, and vice versa. The structures and functions of one embodiment can be adopted in another embodiment. It is not necessary for all advantages to be present in a particular embodiment at the same time. Every feature which is unique from the prior art, alone or in combination with other features, also should be considered a separate description of further inventions by the applicant, including the structural and/or functional concepts embodied by such feature(s). Thus, the foregoing descriptions of the embodiments according to the present invention are provided for illustration only, and not for the purpose of limiting the invention as defined by the appended claims and their equivalents.

Claims

1. A carrier comprising: a body with a bottom portion and a top portion, the top portion defining a top opening having a first top side, the bottom portion configured to be placed on a surface, the top opening being an only opening in the top portion that (a) is sized and configured to enable an animal to enter or exit the body and (b) enables an animal to enter or exit the body in a vertical manner when the bottom portion is placed on a surface; a cover portion sized and configured to open and close the top opening, the cover portion having a first cover side, a second cover side, a viewing opening therein, an attachment opening therein, and a first passage and a second passage located on opposite sides of the attachment opening, the first passage and the second passage defining a plane, an entirety of the first passage and the second passage extending within the plane, the viewing opening extending along the plane, the first cover side of the cover portion being attached to the top portion of the body at the first top side of the top opening by a hinge, the viewing opening being off-centered within the cover portion and closer to the first cover side than to the second cover side, the viewing opening having a wire grating that restricts passage through the viewing opening with a carrier handle hingedly connected to the wire grating, the carrier handle being off-center relative to the wire grating and centered relative to the cover portion; and a latching mechanism installed to a latch supporting portion of the cover portion closer to the second cover side than to the first cover side, the latching mechanism being manually operable to retain the cover portion in a latched state to close the top opening and to release the cover portion such that

the cover portion is free to move about the hinge to provide access to the top portion via the top opening, the latching mechanism including: an attaching structure attached to the cover portion at the attachment opening so as to be spaced apart from the viewing opening, at least one recess, a first rod having a first transverse section, a first end, and a first longitudinal section extending at least between the first transverse section and the first end, the first transverse section and the first longitudinal section extending along the plane, and a second rod having a second transverse section, a second end, and a second longitudinal section extending at least between the second transverse section and the second end, the second transverse section and the second longitudinal section extending along the plane, the first longitudinal section extending through the first passage in the cover portion and the second longitudinal section extending through the second passage in the cover portion, the first transverse section and the second transverse section extending into the at least one recess such that a user can insert one or more fingers into the at least one recess to squeeze the first transverse section and the second transverse section towards each other to release the first end from the top portion as the first longitudinal section translates within the first passage and the second end from the top portion as the second longitudinal section translates within the second passage.

2. The carrier according to claim 1, wherein; the wire grating at least partially blocks the viewing opening in the cover portion.
3. The carrier according to claim 1, wherein: the bottom portion is detachable from the top portion.
4. The carrier according to claim 1, wherein: the latching mechanism includes at least one spring that biases the first rod and the second rod away from each other.
5. The carrier according to claim 1, wherein: the top portion includes an edge configured to overlap an outside periphery of the bottom portion.
6. The carrier according to claim 1, wherein: the bottom portion is sized and configured to fit within an interior of the top portion when the bottom portion is inverted.
7. The carrier according to claim 1, wherein: the first transverse section extends outwardly from a first intermediate portion of the first longitudinal section, and the second transverse section extends outwardly from a second intermediate portion of the second longitudinal section.
8. The carrier according to claim 1, wherein; the top opening has an oval shape with the first top side and a second top side being substantially straight, the first top side opposite the second top side, and the attachment opening also has an oval shape with the first cover side and the second cover side being substantially straight.
9. The carrier according to claim 1, wherein: the at least one recess includes a first recess and a second recess separated by a divider, the first transverse section translates within the first recess, and the second transverse section translates within the second recess.
10. The carrier according to claim 1, wherein the first rod includes: a third transverse section extending from the first longitudinal section, a third end, and a third longitudinal section extending from the third transverse section to the third end, the third longitudinal section and the third transverse section extending along the plane.
11. The carrier according to claim 10, wherein the second rod includes: a fourth transverse section extending from the second longitudinal section, a fourth end, and a fourth longitudinal section extending from the fourth transverse section to the fourth end, the fourth longitudinal section and the fourth transverse section extending along the plane.
12. The carrier according to claim 1, wherein the latching mechanism is not coupled to or formed by the wire grating.
13. A method of forming a carrier, the method comprising: forming a bottom portion, the bottom portion configured to be placed on a surface; forming a top portion with a top opening, the top opening having a first top side and being an only opening sized and configured to enable an animal to enter or exit the carrier and enables an animal to enter or exit the carrier in a vertical manner when the bottom portion is placed on a surface; positioning a cover portion to selectively provide

access to the top portion via the top opening, the cover portion having a first cover side, a second cover side, a viewing opening therein, an attachment opening therein, and a first passage and a second passage located on opposite sides of the attachment opening, the first passage and the second passage defining a plane, an entirety of the first passage and the second passage extending within the plane, the viewing opening extending along the plane, the cover portion being attached to the top portion by a hinge that is attached to the top portion at the first top side of the top opening, the viewing opening being off-centered within the cover portion and closer to the first cover side than to the second cover side, the viewing opening having a wire grating that restricts passage through the viewing opening with a carrier handle hingedly connected to the wire grating, the carrier handle being off-center relative to the wire grating and centered relative to the cover portion; and installing a latching mechanism to a latch supporting portion of the cover portion closer to the second cover side than to the first cover side, such that the latching mechanism is manually operable to retain the cover portion in a latched state to close the top opening in the top portion and to release the cover portion such that the cover portion is free to move about the hinge to provide access to the top portion via the top opening, the latching mechanism including: an attaching structure attached to the cover portion at the attachment opening so as to be spaced apart from the viewing opening, at least one recess, a first rod having a first transverse section, a first end, and a first longitudinal section extending at least between the first transverse section and the first end, the first transverse section and the first longitudinal section extending along the plane, and a second rod having a second transverse section, a second end, and a second longitudinal section extending at least between the second transverse section and the second end, the second transverse section and the second longitudinal section extending along the plane, the first longitudinal section extending through the first passage in the cover portion and the second longitudinal section extending through the second passage in the cover portion, the first transverse section and the second transverse section extending into the at least one recess such that a user can insert one or more fingers into the at least one recess to squeeze the first transverse section and the second transverse section towards each other to release the first end from the top portion as the first longitudinal section translates within the first passage and the second end from the top portion as the second longitudinal section translates within the second passage.

14. The method according to claim 13, wherein: the wire grating at least partially blocks the viewing opening in the cover portion.

15. The method according to claim 13, wherein: the latching mechanism includes at least one spring that biases the first rod and the second rod away from each other.

16. The method according to claim 13, wherein: the top portion includes an edge configured to overlap an outside periphery of the bottom portion.

17. The method according to claim 13, further comprising: inverting the bottom portion and positioning the bottom portion within an interior of the top portion.

18. The method according to claim 13, wherein: the first transverse section extends outwardly from a first intermediate portion of the first longitudinal section, and the second transverse section extends outwardly from a second intermediate portion of the second longitudinal section.

19. The method according to claim 13, wherein: the top opening has an oval shape with the first top side and a second top side being substantially straight, the first top side opposite the second top side, and the attachment opening also has an oval shape with the first cover side and the second cover side being substantially straight.

20. The method according to claim 13, wherein: the at least one recess includes a first recess and a second recess separated by a divider, the first transverse section translates within the first recess, and the second transverse section translates within the second recess.
