

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408696
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	He; Danchong et al.

Aerosol-forming article

Abstract

An aerosol-forming article includes: an aerosol-forming substrate; a heating layer encircling a concave portion, the aerosol-forming substrate being arranged in the concave portion; and a cover layer covering at least a part of the heating layer and an opening of the concave portion. The aerosol-forming substrate is located between the heating layer and the cover layer. A through hole is provided at a position of the cover layer corresponding to the opening. The heating layer generates eddy currents in a magnetic field to generate heat so as to heat the aerosol-forming substrate to form aerosols.

Inventors: He; Danchong (Shenzhen, CN), Wen; Zhihua (Shenzhen, CN), Shen; Pifa (Shenzhen, CN), Xing; Fenglei (Shenzhen, CN)

Applicant: SHENZHEN SMOORE TECHNOLOGY LIMITED (Guangdong, CN)

Family ID: 78338499

Assignee: SHENZHEN SMOORE TECHNOLOGY LIMITED (Shenzhen, CN)

Appl. No.: 17/866872

Filed: July 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230037042 A1	Feb. 02, 2023

Foreign Application Priority Data

CN	202110857437.7	Jul. 28, 2021
----	----------------	---------------

Publication Classification

Int. Cl.: **A24D1/20** (20200101); **A24D1/02** (20060101); **A24F40/20** (20200101); **A24F40/465** (20200101); **H05B6/10** (20060101)

U.S. Cl.:

CPC **A24D1/20** (20200101); **A24D1/02** (20130101); **A24F40/20** (20200101); **A24F40/465** (20200101); **H05B6/105** (20130101);

Field of Classification Search

CPC: A24D (1/02); A24D (1/20); A24F (40/20); A24F (40/465); H05B (6/105)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2016/0360785	12/2015	Bless et al.	N/A	N/A
2017/0055574	12/2016	Kaufman et al.	N/A	A24F 47/004
2017/0318862	12/2016	Mironov et al.	N/A	N/A
2018/0184712	12/2017	Fraser et al.	N/A	N/A
2018/0199630	12/2017	Qiu	N/A	N/A
2018/0271153	12/2017	John et al.	N/A	A24F 47/008
2018/0317555	12/2017	Blandino et al.	N/A	N/A
2018/0368475	12/2017	Smith et al.	N/A	N/A
2019/0208827	12/2018	Mironov	N/A	A24F 40/70
2019/0216135	12/2018	Guo et al.	N/A	N/A
2019/0297946	12/2018	Fu et al.	N/A	N/A
2020/0000148	12/2019	Horrod et al.	N/A	A24F 47/008
2020/0229511	12/2019	Wang et al.	N/A	N/A
2021/0153552	12/2020	Taurino	N/A	A61M 11/042
2021/0161201	12/2020	Aoun et al.	N/A	N/A
2021/0186104	12/2020	Mironov	N/A	A24F 40/42
2021/0204604	12/2020	Mironov	N/A	H05B 6/105
2024/0225100	12/2023	Qian et al.	N/A	A24F 40/42

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3047236	12/2017	CA	N/A
104068473	12/2013	CN	N/A
104135881	12/2015	CN	N/A
106659247	12/2016	CN	N/A
107373761	12/2016	CN	N/A
107427086	12/2016	CN	N/A
104470386	12/2017	CN	N/A

107846987	12/2017	CN	N/A
107920598	12/2017	CN	N/A
107920600	12/2017	CN	N/A
107949285	12/2017	CN	N/A
207355483	12/2017	CN	N/A
108366627	12/2017	CN	N/A
108430239	12/2017	CN	N/A
208160043	12/2017	CN	N/A
109068752	12/2017	CN	N/A
109275963	12/2018	CN	N/A
110178443	12/2018	CN	N/A
110213973	12/2018	CN	N/A
110352016	12/2018	CN	N/A
209749814	12/2018	CN	N/A
110771960	12/2019	CN	N/A
210169064	12/2019	CN	N/A
111011932	12/2019	CN	N/A
210642459	12/2019	CN	N/A
111372480	12/2019	CN	N/A
111387566	12/2019	CN	N/A
111466618	12/2019	CN	N/A
210960421	12/2019	CN	N/A
211746979	12/2019	CN	N/A
112135533	12/2019	CN	N/A
212279879	12/2020	CN	N/A
112584712	12/2020	CN	N/A
112638183	12/2020	CN	N/A
112822951	12/2020	CN	N/A
112841738	12/2020	CN	N/A
113100484	12/2020	CN	N/A
213719921	12/2020	CN	N/A
216135176	12/2021	CN	N/A
216135177	12/2021	CN	N/A
216135178	12/2021	CN	N/A
216135179	12/2021	CN	N/A
216293004	12/2021	CN	N/A
216315588	12/2021	CN	N/A
216453387	12/2021	CN	N/A
012883	12/2008	EA	N/A
3476230	12/2018	EP	N/A
3782491	12/2020	EP	N/A
2005516647	12/2004	JP	N/A
200935723	12/2008	JP	N/A
2017520263	12/2016	JP	N/A
2018504127	12/2017	JP	N/A
2018528767	12/2017	JP	N/A
2019520043	12/2018	JP	N/A
2020503877	12/2019	JP	N/A
2020505073	12/2019	JP	N/A
2020516306	12/2019	JP	N/A

2020529214	12/2019	JP	N/A
2021513339	12/2020	JP	N/A
1020180059916	12/2017	KR	N/A
1020200011941	12/2019	KR	N/A
1020210021069	12/2020	KR	N/A
1020210043285	12/2020	KR	N/A
1020210089736	12/2020	KR	N/A
2531890	12/2013	RU	N/A
2685029	12/2018	RU	N/A
2685285	12/2018	RU	N/A
2731860	12/2019	RU	N/A
2733243	12/2019	RU	N/A
2741921	12/2020	RU	N/A
2751032	12/2020	RU	N/A
2016026096	12/2015	WO	N/A
WO-2016120344	12/2015	WO	A24B 15/167
2016156495	12/2015	WO	N/A
2017075759	12/2016	WO	N/A
WO-2018134159	12/2017	WO	A24D 1/20
2019201031	12/2018	WO	N/A
2019234143	12/2018	WO	N/A
2019238819	12/2018	WO	N/A
2020044181	12/2019	WO	N/A
2020048513	12/2019	WO	N/A
WO-2020119011	12/2019	WO	A24B 15/10
2020245012	12/2019	WO	N/A
2020249493	12/2019	WO	N/A
2020253640	12/2019	WO	N/A
2021014388	12/2020	WO	N/A
2021043690	12/2020	WO	N/A
2021047423	12/2020	WO	N/A
2021071201	12/2020	WO	N/A
2021105462	12/2020	WO	N/A
2021105473	12/2020	WO	N/A
2021105479	12/2020	WO	N/A

OTHER PUBLICATIONS

Japanese Patent Office, Office Action in Japanese Patent Application No. 2022-118458 (Oct. 10, 2023). cited by applicant

Japanese Patent Office, Notice of Registration in Japanese Patent Application No. 2022-118499 (Nov. 14, 2023). cited by applicant

Japanese Patent Office, Notice of Registration in Japanese Patent Application No. 2022-118549 (Nov. 14, 2023). cited by applicant

Japanese Patent Office, Notice of Registration in Japanese Patent Application No. 2022-118490 (Dec. 26, 2023). cited by applicant

Russian Patent Office, Office Action in Russian Patent Application No. 2022120617 (Apr. 6, 2023). cited by applicant

Russian Patent Office, Office Action in Russian Patent Application No. 2022119623 (Dec. 8, 2022). cited by applicant

Japanese Patent Office, Office Action in Japanese Patent Application No. 2022-118458 (Jun. 13, 2023). cited by applicant

Japanese Patent Office, Notice of Registration in Japanese Patent Application No. 2022-118572 (Jun. 13, 2023). cited by applicant

Russian Patent Office, Notice of Registration in Russian Patent Application No. 2022120597 (Jun. 19, 2023). cited by applicant

Chinese Patent Office, First Office Action in Chinese Patent Application No. 202121741709.9 (Mar. 18, 2022). cited by applicant

Russian Patent Office, Office Action in Russian Patent Application No. 2022120597 (Jan. 12, 2023). cited by applicant

Japanese Patent Office, Office Action in Japanese Patent Application No. 2022-118549 (Jul. 4, 2023). cited by applicant

Japanese Patent Office, Office Action in Japanese Patent Application No. 2022-118499 (Jul. 4, 2023). cited by applicant

Japanese Patent Office, Office Action in Japanese Patent Application No. 2022-118490 (Jul. 4, 2023). cited by applicant

Japanese Patent Office, Office Action in Japanese Patent Application No. 2022-118524 (Aug. 8, 2023). cited by applicant

Japanese Patent Office, Office Action in Japanese Patent Application No. 2022-118474 (Aug. 8, 2023). cited by applicant

Japanese Patent Office, Notice of Registration in Japanese Patent Application No. 2022-115861 (Sep. 5, 2023). cited by applicant

Chinese Patent Office, Office Action in Chinese Patent Application No. 202110857412.7 (Aug. 20, 2024). cited by applicant

Chinese Patent Office, Office Action in Chinese Patent Application No. 202110859043.5 (Oct. 12, 2024). cited by applicant

Chinese Patent Office, Office Action in Chinese Patent Application No. 202110859047.3 (Oct. 11, 2024). cited by applicant

Chinese Patent Office, Office Action in Chinese Patent Application No. 202110857420.1 (Sep. 2, 2024). cited by applicant

Chinese Patent Office, Notification of grant of patent right for invention in Chinese Patent Application No. 202110859037.X (Jul. 19, 2024). cited by applicant

U.S. Patent and Trademark Office, Office Action in U.S. Appl. No. 17/815,344 (Sep. 20, 2024). cited by applicant

U.S. Patent and Trademark Office, Office Action in U.S. Appl. No. 17/814,316 (Sep. 9, 2024). cited by applicant

CN/202110859037.X, Notification of grant, Jul. 19, 2024. cited by applicant

CN/202110857412.7, Office Action, Aug. 20, 2024. cited by applicant

CN/202110857420.1, Office Action, Sep. 2, 2024. cited by applicant

CN/202110859043.5, Office Action, Oct. 12, 2024. cited by applicant

CN/202110859047.3, Office Action, Oct. 11, 2024. cited by applicant

CN/202110859047.3, Notification of grant, Nov. 29, 2024. cited by applicant

CN/202110857412.7, Notification of grant, Nov. 28, 2024. cited by applicant

CN/202110857437.7, Office Action, Oct. 17, 2024. cited by applicant

US/17814316, Office Action, Dec. 13, 2024. cited by applicant

CN/202110857437.7, Notification of grant, Dec. 26, 2024. cited by applicant

CN/202110857420.1, Notification of grant, Jan. 3, 2025. cited by applicant

CN/202110857429.2, Notification of grant, Dec. 26, 2024. cited by applicant

CN/202110857417.X, Notification of grant, Dec. 26, 2024. cited by applicant

Chinese Patent Office, Notification of grant of patent right for invention in Chinese Patent

Application No. 202110859047.3 (Nov. 29, 2024). cited by applicant
Chinese Patent Office, Notification of grant of patent right for invention in Chinese Patent Application No. 202110857412.7 (Nov. 28, 2024). cited by applicant
Chinese Patent Office, Office Action in Chinese Patent Application No. 202110857437.7 (Oct. 17, 2024). cited by applicant
U.S. Patent and Trademark Office, Office Action in U.S. Appl. No. 17/814,316 (Dec. 13, 2024). cited by applicant
Chinese Patent Office, Notification of grant of patent right for invention in Chinese Patent Application No. 202110857437.7 (Dec. 26, 2024). cited by applicant
Chinese Patent Office, Notification of grant of patent right for invention in Chinese Patent Application No. 202110857420.1 (Jan. 3, 2025). cited by applicant
Chinese Patent Office, Notification of grant of patent right for invention in Chinese Patent Application No. 202110857429.2 (Dec. 26, 2024). cited by applicant
Chinese Patent Office, Notification of grant of patent right for invention in Chinese Patent Application No. 202110857417.X (Dec. 26, 2024). cited by applicant

Primary Examiner: Wilson; Michael H.

Assistant Examiner: Jordan; Ronnie Kirby

Attorney, Agent or Firm: Leydig, Voit & Mayer, Ltd.

Background/Summary

CROSS-REFERENCE TO PRIOR APPLICATION

(1) Priority is claimed to Chinese Patent Application No. CN 202110857437.7, filed on Jul. 28, 2021, the entire disclosure of which is hereby incorporated by reference herein.

FIELD

(2) This application relates to the field of vaporization device technologies, and in particular, to an aerosol-forming article.

BACKGROUND

(3) At present, a heating body of a heat-not-burn (HNB) product on the market is independent of the HNB product, and the heating body is inserted into the HNB product or wrapped outside the HNB product during use by a user, so that the heating body is in direct contact with the HNB product, and power is supplied to the heating body to generate heat to further bake the HNB product, to cause the HNB product to generate aerosols for inhalation. Because the HNB product is in direct contact with the heating body and the heating body needs to be reused, dirt generated by the HNB product during use is continuously accumulated on and adhered to the heating body, which is hard to clean, and a burnt flavor and odor may be generated after the dirt generated by the HNB product is heated repeatedly, affecting the taste consistency.

SUMMARY

(4) In an embodiment, the present invention provides an aerosol-forming article, comprising: an aerosol-forming substrate; a heating layer encircling a concave portion, the aerosol-forming substrate being arranged in the concave portion; and a cover layer covering at least a part of the heating layer and an opening of the concave portion, wherein the aerosol-forming substrate is located between the heating layer and the cover layer, wherein a through hole is provided at a position of the cover layer corresponding to the opening, and wherein the heating layer is

configured to generate eddy currents in a magnetic field to generate heat so as to heat the aerosol-forming substrate to form aerosols.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Subject matter of the present disclosure will be described in even greater detail below based on the exemplary figures. All features described and/or illustrated herein can be used alone or combined in different combinations. The features and advantages of various embodiments will become apparent by reading the following detailed description with reference to the attached drawings, which illustrate the following:
- (2) FIG. 1 is a schematic structural diagram of an aerosol-forming device according to this application;
- (3) FIG. 2 is a schematic structural diagram of a first embodiment of an aerosol-forming article according to this application;
- (4) FIG. 3 is a schematic structural diagram of a second embodiment of an aerosol-forming article according to this application;
- (5) FIG. 4 is a schematic structural diagram of a third embodiment of an aerosol-forming article according to this application;
- (6) FIG. 5 is a schematic structural diagram of a fourth embodiment of an aerosol-forming article according to this application;
- (7) FIG. 6 is a schematic structural diagram of a fifth embodiment of an aerosol-forming article according to this application;
- (8) FIG. 7 is another schematic structural diagram of a fifth embodiment of an aerosol-forming article according to this application;
- (9) FIG. 8 is a schematic structural diagram of a sixth embodiment of an aerosol-forming article according to this application;
- (10) FIG. 9 is another schematic structural diagram of a sixth embodiment of an aerosol-forming article according to this application;
- (11) FIG. 10 is a schematic structural diagram of a vaporization main unit according to this application;
- (12) FIG. 11 is a schematic structural diagram of a mounting base in a vaporization main unit according to this application;
- (13) FIG. 12 is another schematic structural diagram of a mounting base in a vaporization main unit according to this application;
- (14) FIG. 13 is a schematic partial cross-sectional view of a first embodiment of a vaporization main unit according to this application;
- (15) FIG. 14a is a schematic cross-sectional view of an implementation of a heating element in a first embodiment of a vaporization main unit according to this application;
- (16) FIG. 14b is a schematic cross-sectional view of another implementation of a heating element in a first embodiment of a vaporization main unit according to this application;
- (17) FIG. 15 is a three-dimensional schematic structural diagram of a heating element in a first embodiment of a vaporization main unit according to this application;
- (18) FIG. 16 is a schematic structural diagram of a heating circuit layer of a heating element in a first embodiment of a vaporization main unit according to this application;
- (19) FIG. 17 is a schematic diagram of a relationship between a heating time and a temperature of an aerosol-forming article according to this application;
- (20) FIG. 18 is a schematic partial structural diagram of a second embodiment of a vaporization main unit according to this application;

- (21) FIG. 19 is a schematic partial cross-sectional view of a second embodiment of a vaporization main unit according to this application;
- (22) FIG. 20 is a schematic flowchart of an aerosol generation method according to this application;
- (23) FIG. 21 is a schematic structural diagram of an air communication component according to this application;
- (24) FIG. 22 is a schematic cross-sectional view of an air communication component according to this application;
- (25) FIG. 23 is a schematic cross-sectional view of a top cover in an air communication component according to this application;
- (26) FIG. 24 is a schematic cross-sectional view of a bottom cover in an air communication component according to this application;
- (27) FIG. 25 is a schematic partial cross-sectional view of an aerosol-forming device according to this application;
- (28) FIG. 26 is a schematic diagram of an air flowing direction in an air communication component according to this application;
- (29) FIG. 27 is a schematic structural diagram of another aerosol-forming device according to this application; and
- (30) FIG. 28 is a schematic structural diagram of still another aerosol-forming device according to this application.

DETAILED DESCRIPTION

- (31) In an embodiment, the present invention provides an aerosol-forming article, to resolve the problem that the dirt adhered to the heating body during repeated heating affects the taste in the related art.
- (32) In an embodiment, the present invention provides an aerosol-forming article, including: an aerosol-forming substrate; a heating layer, where the heating layer encircles a concave portion, and the aerosol-forming substrate is arranged in the concave portion; and a cover layer, covering at least a part of the heating layer and an opening of the concave portion, where the aerosol-forming substrate is located between the heating layer and the cover layer; a through hole is provided at a position of the cover layer corresponding to the opening; and the heating layer is configured to generate eddy currents in a magnetic field to generate heat, so that the aerosol-forming substrate is heated to form aerosols.
- (33) The concave portion includes an annular side wall and a bottom wall, and an outer side of the annular side wall includes a hanger loop. The heating layer encircles a plurality of concave portions, annular side walls of adjacent concave portions are spaced, and adjacent concave portions share a same hanger loop.
- (34) The heating layer is provided with a first partition hole on the hanger loop shared by the adjacent concave portions.
- (35) A second partition hole is provided on the cover layer, and the second partition hole and the first partition hole are correspondingly provided.
- (36) Each heating layer encircles one concave portion, adjacent concave portions are spaced, and hanger loops of adjacent concave portions are spaced.
- (37) The aerosol-forming substrate gathers to form a layered body, a bottom wall of the concave portion is attached to a bottom surface of the aerosol-forming substrate, and a distance between a side wall of the concave portion and a side surface of the aerosol-forming substrate ranges from 0.1 mm to 1.0 mm.
- (38) A thickness of the aerosol-forming substrate ranges from 0.5 mm to 3 mm, and a depth of the concave portion ranges from 0.5 mm to 3 mm.
- (39) A shape of a cross-section of the aerosol-forming substrate is a circle, and a diameter of the aerosol-forming substrate ranges from 3.0 mm to 20 mm.

(40) A thickness of the heating layer ranges from 0.05 mm to 0.3 mm. The heating layer is made of an aluminum foil.

(41) A thickness of the cover layer ranges from 0.02 mm to 0.1 mm; and the cover layer is made of an aluminum foil. Beneficial effects of this application are as follows: different from the related art, an aerosol-forming article is provided, the aerosol-forming article includes: an aerosol-forming substrate; a heating layer, where the heating layer encircles a concave portion, and the aerosol-forming substrate is arranged in the concave portion; and a cover layer, covering at least a part of the heating layer and an opening of the concave portion, where the aerosol-forming substrate is located between the heating layer and the cover layer; a through hole is provided at a position of the cover layer corresponding to the opening; and the heating layer is configured to generate eddy currents in a magnetic field to generate heat, so that the aerosol-forming substrate is heated to form aerosols. According to the aerosol-forming article provided in this application, eddy currents are generated in a magnetic current to generate heat, and the aerosol-forming substrate is further heated, thereby preventing occurrence of a burnt flavor or odor caused by heating of a heating layer that is reused and improving the taste of aerosols.

(42) This application is further described in detail below with reference to the accompanying drawings and embodiments. It should be specifically noted that, the following embodiments are merely used for describing this application rather than limiting the scope of this application. Similarly, the following embodiments are merely some rather than all of the embodiments of this application, and all other embodiments obtained by a person of ordinary skill in the art without creative efforts shall fall within the protection scope of this application.

(43) The terms “first”, “second”, and “third” in this application are merely intended for a purpose of description, and shall not be understood as indicating or implying relative significance or implicitly indicating the number of indicated technical features. Therefore, features defining “first”, “second”, and “third” can explicitly or implicitly include at least one of the features. In the description of this application, “a plurality of” means at least two, such as two and three unless it is specifically defined otherwise. All directional indications (for example, upper, lower, left, right, front, and rear) in the embodiments of this application are merely used for explaining relative position relationships, movement situations, or the like between the various components in a specific posture (as shown in the accompanying drawings). If the specific posture changes, the directional indications change accordingly. In the embodiments of this application, the terms “include”, “have”, and any variant thereof are intended to cover a non-exclusive inclusion. For example, a process, method, system, product, or device that includes a series of steps or units is not limited to the listed steps or units, but further optionally includes a step or unit that is not listed, or further optionally includes another step or component that is intrinsic to the process, method, product, or device.

(44) “Embodiment” mentioned in this specification means that particular features, structures, or characteristics described with reference to the embodiment may be included in at least one embodiment of this application. The term appearing at different positions of this specification may not refer to the same embodiment or an independent or alternative embodiment that is mutually exclusive with another embodiment. A person skilled in the art explicitly or implicitly understands that the embodiments described in this specification may be combined with other embodiments.

(45) Referring to FIG. 1, FIG. 1 is a schematic structural diagram of an aerosol-forming device according to this application. The aerosol-forming device includes an aerosol-forming article 1, an air communication component 2, and a vaporization main unit 3. The vaporization main unit 3 includes a heating element 31, the heating element 31 is arranged on an end portion of the vaporization main unit 3 close to the air communication component 2, and the aerosol-forming article 1 is arranged on an end of the vaporization main unit 3 close to the air communication component 2. Namely, the aerosol-forming article 1 is arranged between the air communication component 2 and the vaporization main unit 3, and the aerosol-forming article 1 is in contact with

the heating element **31**.

(46) The aerosol-forming article **1** is fixed through connection and fixing between the air communication component **2** and the vaporization main unit **3**.

(47) Specifically, the air communication component **2** and the vaporization main unit **3** may be fixed and connected through magnetic attraction. Namely, magnetic members are respectively arranged on the air communication component **2** and the vaporization main unit **3** to implement a magnetic attraction connection, or a magnet is arranged on one of the air communication component **2** and the vaporization main unit **3**, and a metal member is correspondingly arranged on the other to implement a magnetic attraction connection. The air communication component **2** and the vaporization main unit **3** may be fixed and connected through buckles. Namely, a protrusion is provided on the air communication component **2**, and a slot is correspondingly provided on the vaporization main unit **3** to implement a buckle connection, or a protrusion is provided on the vaporization main unit **3**, and a slot is correspondingly provided on the air communication component **2** to implement a buckle connection. A connection manner between the air communication component **2** and the vaporization main unit **3** is designed as required, which is not limited in this application.

(48) Referring to FIG. 2, FIG. 2 is a schematic structural diagram of a first embodiment of an aerosol-forming article according to this application.

(49) The aerosol-forming article **1** includes an aerosol-forming substrate **11** and an encapsulation layer **12**. The encapsulation layer **12** covers at least a part of the aerosol-forming substrate **11**, so that the encapsulation layer **12** isolates the aerosol-forming substrate **11** from the heating element **31**. The aerosol-forming article **1** is a replaceable and disposable product. An area of the aerosol-forming substrate **11** covered by the encapsulation layer **12** is selected according to a specific implementation, provided that the encapsulation layer **12** can isolate the aerosol-forming substrate **11** from the heating element **31**, namely, provided that the aerosol-forming substrate **11** and the heating element **31** cannot be in direct contact due to the area of the aerosol-forming substrate **11** covered by the encapsulation layer **12**.

(50) The heating element **31** is configured to heat the encapsulation layer **12**, and the encapsulation layer **12** conducts heat to the aerosol-forming substrate **11** in the aerosol-forming article **1** to form aerosols, namely, the aerosol-forming article **1** is heated in a resistive manner. Alternatively, the heating element **31** is an electromagnetic member such as an electromagnetic coil, and the encapsulation layer **12** generates eddy currents in a magnetic field of the electromagnetic member to generate heat, to heat the aerosol-forming substrate **11** to form aerosols, namely, the aerosol-forming article **1** is heated in an electromagnetic manner. When the aerosol-forming article **1** is heated in an electromagnetic manner, the encapsulation layer **12** is a heating layer, and the heating layer generates eddy currents in the magnetic field of the heating element **31** (electromagnetic member) to generate heat, to heat the aerosol-forming substrate **11** to form aerosols.

(51) When the aerosol-forming article **1** is heated in a resistive manner, the encapsulation layer **12** has a characteristic of uniform heat conduction and may be made of glasses, ceramics, or metals, provided that the requirement is met. Namely, the encapsulation layer **12** may be a metal layer, a ceramic layer, or a glass layer. It may be understood that, the aerosol-forming substrate **11** can be heated uniformly due to the uniform heat conduction characteristic of the encapsulation layer **12**, thereby helping improve the quality consistency, namely, taste consistency of the aerosols. When the aerosol-forming article **1** is heated in an electromagnetic manner, the encapsulation layer **12** is made of a metal such as an aluminum foil that can generate heat in a magnetic field.

(52) The aerosol-forming article **1** is set to include the aerosol-forming substrate **11** and the encapsulation layer **12**, and the encapsulation layer **12** covers at least a part of the aerosol-forming substrate **11**, so that the encapsulation layer **12** isolates the aerosol-forming substrate **11** from the heating element **31**. Therefore, the heating element **31** is prevented from being in direct contact with the aerosol-forming substrate **11**, namely, aerosol residues are prevented from being adhered

to the heating element **31** when the heating element **31** heats the aerosol-forming substrate **11** to generate aerosols, and a problem that the aerosol residues adhered to the heating element **31** are hard to clean is further prevented. No impact is caused on the taste of the aerosols even if the heating element **31** is reused, thereby improving the use experience of users. In addition, the encapsulation layer **12** covers at least a part of the aerosol-forming substrate **11**, after the aerosol-forming substrate **11** is consumed, the encapsulation layer **12** and the aerosol-forming substrate **11** are discarded together, and a new aerosol-forming article **1** is replaced, so that replacement of the aerosol-forming substrate **11** is more convenient, faster, and cleaner.

(53) During a specific implementation, the aerosol-forming substrate **11** may be in a shape of power, filamentous, or may form a block through gathering. When the aerosol-forming substrate **11** is in a shape of power or filamentous, a form of the aerosol-forming substrate cannot be fixed. In this case, a mold is required to lay the encapsulation layer **12** in the mold, and the mold is then filled by the aerosol-forming substrate **11**, to further obtain the aerosol-forming article **1** in a predetermined shape. When the aerosol-forming substrate **11** is a block, it is more convenient to assemble the aerosol-forming substrate **11** and the encapsulation layer **12** to form the aerosol-forming article **1**. In addition, the aerosol-forming substrate **11** may be designed into a columnar body, a layered body, or another shape as required, and a required shape of the aerosol-forming article **1** is further obtained. The aerosol-forming substrate **11** is described as a block in the following description.

(54) It may be understood that, at least a part of the encapsulation layer **12** covering the aerosol-forming substrate **11** is to isolate the aerosol-forming substrate **11** from the heating element **31**, to ensure relatively high heating efficiency, and the part of encapsulation layer **12** is attached to the aerosol-forming substrate **11**.

(55) In a first embodiment of the aerosol-forming article **1**, the aerosol-forming substrate **11** gathers to form a columnar body, and the encapsulation layer **12** is set to be in a shape of a hollow column and covers a side surface of the aerosol-forming substrate **11**.

(56) For example, the encapsulation layer **12** may be in a shape of a sheet to form the hollow column through wrapping; or the encapsulation layer **12** may be in a shape of a belt to form the hollow column through spirally wrapping. In this embodiment, the aerosol-forming article **1** may be heated in a resistive manner or may be heated in an electromagnetic manner, which is specifically selected as required. It may be understood that, the side surface of the aerosol-forming substrate **11** in this embodiment is a heating surface, and a bottom surface thereof is an aerosol releasing surface.

(57) For example, the columnar body formed by the aerosol-forming substrate **11** through gathering may be a cylinder, a triangular prism, or a quadrangular prism, and a structure size of the encapsulation layer **12** and a structure size of the aerosol-forming substrate **11** are arranged in an engagement manner, provided that the encapsulation layer **12** completely covers the side surface of the aerosol-forming substrate **11**.

(58) To ensure relatively high heating efficiency, the encapsulation layer **12** is attached to the side surface of the aerosol-forming substrate **11**.

(59) When the aerosol-forming article **1** is heated in an electromagnetic manner, the heating element **31** is an electromagnetic member, the encapsulation layer **12** is a heating layer, and the heating layer generates eddy currents in the magnetic field of the electromagnetic member to generate heat, to heat the aerosol-forming substrate **11** to form aerosols. The heating layer encircles a columnar structure and forms a non-closed loop, and the aerosol-forming substrate **11** is arranged in the columnar structure. Specifically, the heating layer is arranged in a curled manner and encircles an accommodating space, and the accommodating space is configured to accommodate the aerosol-forming substrate **11**. The heating layer includes a first end and a second end opposite to the first end, where the first end and the second end are provided opposite to each other. A surface of the heating layer that is in contact with the aerosol-forming substrate **11** is an inner wall

surface of the accommodating space, and a surface of the heating layer that is not in contact with the aerosol-forming substrate **11** is an outer wall surface of the accommodating space. The first end and the second end of the heating layer are both spaced apart from the inner wall surface and the outer wall surface of the accommodating space.

(60) In an implementation, the aerosol-forming substrate **11** gathers to form a columnar body, the heating layer surrounds the side surface of the aerosol-forming substrate **11** and encircles a hollow tubular body, and a notch is provided on a side wall of the hollow tubular body, so that the heating layer forms a non-closed loop. That is, the first end and the second end of the heating layer are provided opposite to each other and are spaced apart from each other. Two opposite ends of the hollow tubular body are both opening ends, and the heating layer covers the side surface of the aerosol-forming substrate **11**, where the structure is shown in FIG. **2**. The notch extends from one end of the hollow tubular body to the other end in an axial direction of the hollow tubular body.

(61) In another implementation, the heating layer is in a shape of a rectangular sheet, the heating layer is arranged in a curled manner surrounding one side thereof to form a hollow columnar body, and there is a gap between two opposite sides of the heating layer, so that the heating layer forms a non-closed loop, where the structure is shown in FIG. **2**. It may be understood that, a shape of a cross-section of the aerosol-forming substrate **11** may be a circle or a triangle. When the shape of the cross-section of the aerosol-forming substrate **11** is a circle, a diameter of the aerosol-forming substrate **11** ranges from 3.0 mm to 20 mm. The heating layer is made of an aluminum foil or a copper foil, and a thickness of the heating layer ranges from 0.05 mm to 0.3 mm.

(62) When the aerosol-forming article **1** is heated in a resistive manner, the encapsulation layer **12** in the structure of FIG. **2** may form a closed loop or a non-closed loop, which is specifically designed as required.

(63) Referring to FIG. **3**, FIG. **3** is a schematic structural diagram of a second embodiment of an aerosol-forming article according to this application.

(64) In the second embodiment of the aerosol-forming article **1**, the aerosol-forming substrate **11** gathers to form a columnar body. For example, the aerosol-forming substrate **11** may be in a shape of a cylinder, a triangular prism, or a quadrangular prism. An insertion groove **111** is provided on the aerosol-forming substrate **11**, the encapsulation layer **12** is arranged in the insertion groove **111** and covers an inner wall of the insertion groove **111**, and the heating element **31** is inserted into a cavity **120** encircled by the encapsulation layer **12**. In this embodiment, the aerosol-forming article **1** is heated in a resistive manner. It may be understood that, in this embodiment, an inner wall surface of the insertion groove **111** of the aerosol-forming substrate **11** is a heating surface, and an outer surface of the aerosol-forming substrate **11** may be used as an aerosol releasing surface, which are specifically designed as required. In an implementation, the encapsulation layer **12** may alternatively be folded into a multi-layer structure and then inserted into the aerosol-forming substrate **11**. During use, the sheet-like heating element **31** is inserted into layers of the encapsulation layer **12**, thereby preventing the heating element **31** from being in contact with the aerosol-forming substrate **11**.

(65) Referring to FIG. **4**, FIG. **4** is a schematic structural diagram of a third embodiment of an aerosol-forming article according to this application.

(66) In the third embodiment of the aerosol-forming article **1**, the aerosol-forming substrate **11** gathers to form a layered body, and the encapsulation layer **12** and the aerosol-forming substrate **11** are stacked and are curled together into a shape of a column or a shape similar to a column, such as a shape of a spring roll, so that the outer surface of the aerosol-forming substrate **11** is wrapped by the encapsulation layer **12**, and the encapsulation layer **12** is also arranged inside the aerosol-forming substrate. That is, the encapsulation layer **12** includes a first end and a second end, where the second end is curled surrounding the first end to form a shape of a roll, and the aerosol-forming substrate **11** is filled in a gap of the rolled encapsulation layer **12**. For example, a cross-section of the layered aerosol-forming substrate **11** may be a square or a rectangle, and the column formed by

the aerosol-forming substrate **11** and the encapsulation layer **12** through curling may be a cylinder, a triangular prism, or a quadrangular prism. In this embodiment, the aerosol-forming article **1** may be heated in a resistive manner or may be heated in an electromagnetic manner, which is specifically selected as required.

(67) It may be understood that, a side surface of the column formed by the aerosol-forming substrate **11** and the encapsulation layer **12** through curling is a heating surface, and a bottom surface thereof is an aerosol releasing surface. A structure size of the encapsulation layer **12** and a structure size of the layered aerosol-forming substrate **11** are arranged in an engagement manner, so that the encapsulation layer **12** and the aerosol-forming substrate **11** are curled together, and the encapsulation layer **12** isolates the aerosol-forming substrate **11** from the heating element **31**.

(68) When the aerosol-forming article **1** is heated in an electromagnetic manner, the heating element **31** is an electromagnetic member, the encapsulation layer **12** is a heating layer, and the heating layer generates eddy currents in the magnetic field of the electromagnetic member to generate heat, to heat the aerosol-forming substrate **11** to form aerosols. The heating layer encircles a columnar structure and forms a non-closed loop, and the aerosol-forming substrate **11** is arranged in the columnar structure. Specifically, the aerosol-forming substrate **11** gathers to form a columnar body, the heating layer is in a shape of a rectangular sheet, one side of the heating layer is located on a side surface of the aerosol-forming substrate **11**, the heating layer is curled, and another side of the heating layer is located inside the aerosol-forming substrate **11**, to form a non-closed loop (as shown in FIG. 4). That is, the aerosol-forming substrate **11** covers on the heating layer, the second end of the heating layer is arranged surrounding the first end thereof, the first end of the heating layer is curled and located inside the aerosol-forming substrate **11**, and the second end of the heating layer is located on an outer side of the aerosol-forming substrate **11**. The inner wall surface of the accommodating space is a first surface **127** of the heating layer, and a part of the heating layer curled to the inside of the aerosol-forming substrate **11** is a second surface **128**. The outer wall surface of the accommodating space is a part of the heating layer that is not curled to the inside of the aerosol-forming substrate **11** and is not in contact with the aerosol-forming substrate **11**. The first end of the heating layer and the inner wall surface of the accommodating space are spaced, and the second end of the heating layer and the outer wall surface of the accommodating space are spaced.

(69) Referring to FIG. 5, FIG. 5 is a schematic structural diagram of a fourth embodiment of an aerosol-forming article according to this application.

(70) In the fourth embodiment of the aerosol-forming article **1**, the aerosol-forming substrate **11** gathers to form a layered body, and the encapsulation layer **12** covers the whole outer surface of the aerosol-forming substrate **11**. In addition, a first through hole **121** is provided on the encapsulation layer **12** on one side of the aerosol-forming substrate **11** away from the heating element **31**, to release aerosols. In this embodiment, the aerosol-forming article **1** may be heated in a resistive manner or may be heated in an electromagnetic manner, which is specifically selected as required.

(71) For example, a cross-section of the layered aerosol-forming substrate **11** may be a circle, a square, or a rectangle, which is specifically designed as required. It may be understood that, in this embodiment, because the encapsulation layer **12** covers the whole outer surface of the aerosol-forming substrate **11**, surfaces of the aerosol-forming substrate **11** in contact with the encapsulation layer **12** are all heating surfaces, and a surface of the aerosol-forming substrate **11** corresponding to the first through hole **121** provided on the encapsulation layer **12** is an aerosol releasing surface.

(72) Referring to FIG. 6 and FIG. 7, FIG. 6 is a schematic structural diagram of a fifth embodiment of an aerosol-forming article according to this application, and FIG. 7 is another schematic structural diagram of a fifth embodiment of an aerosol-forming article according to this application.

(73) In the fifth embodiment of the aerosol-forming article **1**, the aerosol-forming substrate **11** gathers to form a layered body. For example, a cross-section of the layered aerosol-forming substrate **11** may be a circle, a square, or a rectangle, which is specifically designed as required.

The encapsulation layer **12** covers a surface of one side of the aerosol-forming substrate **11** close to the heating element **31**, to isolate the aerosol-forming substrate **11** from the heating element **31**. That is, the encapsulation layer **12** encircles a concave portion **122**, and the aerosol-forming substrate **11** is arranged in the concave portion **122**. The concave portion **122** includes an annular side wall and a bottom wall, and an outer side of the annular side wall includes a hanger loop **1221**, so that the aerosol-forming article **1** is connected onto the vaporization main unit **3**.

(74) It may be understood that, in this embodiment, a surface of the aerosol-forming substrate **11** in contact with the encapsulation layer **12** is a heating surface, and surfaces other than the surface in contact with the encapsulation layer **12** on the aerosol-forming substrate **11** are all aerosol releasing surfaces, which are specifically designed as required. Namely, the bottom surface of the aerosol-forming substrate **11** is attached to the bottom wall of the concave portion **122**, and the side surface of the aerosol-forming substrate **11** may be in contact or not in contact with the annular side wall of the concave portion **122**, which is specifically designed as required. In this embodiment, the aerosol-forming article **1** may be heated in a resistive manner or may be heated in an electromagnetic manner, which is specifically selected as required.

(75) In an implementation, a plurality of aerosol-forming articles **1** are independent of each other. As shown in FIG. 6, encapsulation layers **12** of the plurality of aerosol-forming articles **1** are independent of each other. Specifically, each encapsulation layer **12** encircles one concave portion **122**, the plurality of encapsulation layers **12** encircle a plurality of concave portions **122**, the aerosol-forming substrate **11** is arranged in each concave portion **122**, and adjacent concave portions **122** are spaced. For ease of assembling the aerosol-forming article **1** into an aerosol-forming device, in addition to covering the surface of the side of the aerosol-forming substrate **11** close to the heating element **31**, the encapsulation layer **12** of the aerosol-forming article **1** further bends toward the side surface of the aerosol-forming substrate **11** to form the hanger loop **1221**, so that the aerosol-forming article **1** is connected onto the vaporization main unit **3**. In this implementation, hanger loops **1221** of adjacent concave portions **122** are spaced. That is, the encapsulation layer **12** bends to form the concave portion **122**, and the aerosol-forming substrate **11** is arranged in the concave portion **122**. A distance between the annular side wall of the concave portion **122** and the side surface of the aerosol-forming substrate **11** ranges from 0.1 mm to 1.0 mm, to better release aerosols. Optionally, the distance between the annular side wall of the concave portion **122** and the side surface of the aerosol-forming substrate **11** ranges from 0.2 mm to 0.3 mm. The bottom surface of the aerosol-forming substrate **11** is attached to the bottom wall of the concave portion **122**, to improve the heating efficiency.

(76) In another implementation, for ease of assembling a plurality of aerosol-forming articles **1** into an aerosol-forming device, the plurality of aerosol-forming articles **1** are set to be an integral structure. Namely, encapsulation layers **12** of the plurality of aerosol-forming articles **1** are a whole layer structure, and as shown in FIG. 7, the plurality of aerosol-forming articles **1** form an integral structure through the encapsulation layer **12**. Specifically, there are a plurality of concave portions **122** encircled by the encapsulation layer **12**. Namely, the encapsulation layer **12** bends to form a plurality of spaced concave portions **122**, and the aerosol-forming substrate **11** is arranged in each of the plurality of concave portions **122**. Annular side walls of adjacent concave portions **122** are spaced, so that adjacent aerosol-forming substrates **11** are independent of each other. Therefore, the adjacent aerosol-forming substrates **11** can be heated independently, and the adjacent aerosol-forming substrates **11** do not affect each other during heating. Hanger loops **1221** of adjacent concave portions **122** include a common part. Further, to improve the heating efficiency, a first partition hole **123** is provided on a hanger loop **1221** serving as the common part between adjacent concave portions **122** on the encapsulation layer **12**, and heat conduction between the adjacent concave portions **122** is reduced through air heat insulation, so that mutual impact between the adjacent aerosol-forming substrates **11** during heating is reduced to the maximum extent. A distance between the annular side wall of the concave portion **122** and the side surface of the

aerosol-forming substrate **11** ranges from 0.1 mm to 1.0 mm, to better release aerosols. Optionally, the distance between the annular side wall of the concave portion **122** and the side surface of the aerosol-forming substrate **11** ranges from 0.2 mm to 0.3 mm. The bottom surface of the aerosol-forming substrate **11** is attached to the bottom wall of the concave portion **122**, to improve the heating efficiency.

(77) Referring to FIG. **8** and FIG. **9**, FIG. **8** is a schematic structural diagram of a sixth embodiment of an aerosol-forming article according to this application, and FIG. **9** is another schematic structural diagram of a sixth embodiment of an aerosol-forming article according to this application.

(78) In the sixth embodiment of the aerosol-forming article **1**, the structure of the aerosol-forming article **1** is basically the same as that in the fifth embodiment, and a difference lies in that the aerosol-forming article further includes a cover layer **13**.

(79) In the sixth embodiment of the aerosol-forming article **1**, the aerosol-forming substrate **11** gathers to form a layered body. For example, a cross-section of the layered aerosol-forming substrate **11** may be a circle, a square, or a rectangle, which is specifically designed as required. The encapsulation layer **12** covers a surface of one side of the aerosol-forming substrate **11** close to the heating element **31**, to isolate the aerosol-forming substrate **11** from the heating element **31**. That is, the encapsulation layer **12** encircles a concave portion **122**, and the aerosol-forming substrate **11** is arranged in the concave portion **122**. The concave portion **122** includes an annular side wall and a bottom wall, and an outer side of the annular side wall includes a hanger loop **1221**, so that the aerosol-forming article **1** is connected onto the vaporization main unit **3**. The cover layer **13** covers at least a part of the encapsulation layer **12** and an opening of the concave portion **122**, and the aerosol-forming substrate **11** is arranged between the encapsulation layer **12** and the cover layer **13**. A second through hole **131** is provided at a position of the cover layer **13** corresponding to the opening of the concave portion **122**, and the second through hole **131** is configured to release aerosols. Namely, the cover layer **13** is arranged on a surface of the encapsulation layer **12** and covers the concave portion **122**, and the second through hole **131** is provided at a position of the cover layer **13** corresponding to the concave portion **122**. A main function of the cover layer **13** is to fix the aerosol-forming substrate **11** in the concave portion **122**, and the cover layer **13** is fixed on the encapsulation layer **12** in a riveting or wrapping manner or using high temperature resistant glue. The cover layer **13** is made of a metal material. Optionally, the material of the cover layer **13** is an aluminum foil. A thickness of the cover layer ranges from 0.02 mm to 0.1 mm. Optionally, the thickness of the cover layer ranges from 0.02 mm to 0.05 mm.

(80) It may be understood that, in this embodiment, a surface of the aerosol-forming substrate **11** in contact with the encapsulation layer **12** is a heating surface, and all surfaces other than the surface in contact with the encapsulation layer **12** on the aerosol-forming substrate **11** are aerosol releasing surfaces, which are specifically designed as required. Namely, the bottom surface of the aerosol-forming substrate **11** is attached to the bottom wall of the concave portion **122**, and the side surface of the aerosol-forming substrate **11** may be in contact or not in contact with the annular side wall of the concave portion **122**, which is specifically designed as required. In this embodiment, the aerosol-forming article **1** may be heated in a resistive manner or may be heated in an electromagnetic manner, which is specifically selected as required.

(81) In an implementation, a plurality of aerosol-forming articles **1** are independent of each other. Namely, encapsulation layers **12** of the plurality of aerosol-forming articles **1** are independent of each other, and cover layers **13** of the plurality of aerosol-forming articles **1** are independent of each other. As shown in FIG. **8**, one encapsulation layer **12** encircles one concave portion **122**, and one cover layer **13** covers one concave portion **122**. Specifically, an arrangement manner of the encapsulation layer **12** is the same as the arrangement manner of the encapsulation layer **12** in the aerosol-forming article **1** provided in FIG. **6**, and an engagement relationship between the encapsulation layer **12** and the aerosol-forming substrate **11** is the same as the engagement

relationship between the encapsulation layer **12** and the aerosol-forming substrate **11** in the aerosol-forming article **1** provided in FIG. **6**, which are not described in detail herein.

(82) In another implementation, for ease of assembling a plurality of aerosol-forming articles **1** into an aerosol-forming device, the plurality of aerosol-forming articles **1** are set to be an integral structure. Namely, encapsulation layers **12** of the plurality of aerosol-forming articles **1** are a whole layer structure, cover layers **13** of the plurality of aerosol-forming articles **1** are a whole layer structure, and as shown in FIG. **9**, the plurality of aerosol-forming articles **1** form an integral structure through the encapsulation layer **12** and the cover layers **13**. Specifically, an arrangement manner of the encapsulation layer **12** is the same as the arrangement manner of the encapsulation layer **12** in the aerosol-forming article **1** provided in FIG. **7**, and an engagement relationship between the encapsulation layer **12** and the aerosol-forming substrate **11** is the same as the engagement relationship between the encapsulation layer **12** and the aerosol-forming substrate **11** in the aerosol-forming article **1** provided in FIG. **6**, which are not described in detail herein. Different from the aerosol-forming article **1** provided in FIG. **7**, in the aerosol-forming article **1** provided in FIG. **9**, the cover layer **13** covers the plurality of concave portions **122**, and a second through hole **131** is provided at a position of the cover layer **13** corresponding to the concave portion **122** to release aerosols. A second partition hole **132** is provided on the cover layer **13** corresponding to the first partition hole **123**, and heat conduction between adjacent concave portions **122** is reduced through air heat insulation, so that mutual impact between adjacent aerosol-forming substrates **11** during heating is reduced to the maximum extent.

(83) In the first embodiment, the second embodiment, the third embodiment, the fourth embodiment, the fifth embodiment, and the sixth embodiment of the aerosol-forming article **1**, the encapsulation layer **12** is made of a metal material. Optionally, the material of the encapsulation layer **12** is a copper foil or an aluminum foil. To achieve relatively high heating efficiency, the thickness of the encapsulation layer **12** is set to range from 0.05 mm to 0.3 mm. Optionally, the thickness of the encapsulation layer **12** ranges from 0.1 mm to 0.15 mm.

(84) In the first embodiment and the second embodiment of the aerosol-forming article **1**, a farthest distance between two points on the cross-section of the columnar aerosol-forming substrate **11** ranges from 0.5 mm to 3 mm, so that the aerosol-forming substrate **11** can be better heated, and the aerosol-forming substrate **11** can be prevented from being locally heated for a long time. In the third embodiment, the fourth embodiment, the fifth embodiment, and the sixth embodiment of the aerosol-forming article **1**, the thickness of the sheet-like aerosol-forming substrate **11** is set to range from 0.5 mm to 3 mm. A thinner thickness indicates that the surface of the aerosol-forming substrate **11** away from the encapsulation layer **12** can be better heated and a shorter time that the aerosol-forming substrate **11** is heated and consumed. Therefore, the aerosol-forming substrate **11** can be prevented from being locally heated for a long time, and occurrence of a burnt flavor can be further prevented from affecting the taste. Optionally, the thickness of the aerosol-forming substrate **11** ranges from 1.0 mm to 2.0 mm.

(85) In the fourth embodiment, the fifth embodiment, and the sixth embodiment of the aerosol-forming article **1**, the shape of the cross-section of the sheet-like aerosol-forming substrate **11** is a circle, and the diameter of the aerosol-forming substrate **11** is set to range from 3.0 mm to 20 mm. Optionally, the diameter of the aerosol-forming substrate **11** ranges from 8.0 mm to 12.0 mm.

(86) The aerosol-forming article **1** adopts the structure in the sixth embodiment shown in FIG. **9** in the following description.

(87) Referring to FIG. **10**, FIG. **10** is a schematic structural diagram of a vaporization main unit according to this application.

(88) The vaporization main unit **3** further includes a housing **30**, a mounting base **32**, a controller **33**, and a power supply **34**. The housing **30** includes a mounting space **300**. The mounting base **32** is arranged in the mounting space **300** and is exposed from one end of the housing **30**, to engage with an air communication component **2** to form a vaporization cavity **24** (referring to FIG. **25**).

The mounting base **32** is provided with at least one mounting portion **320**, the mounting portion **320** is configured to mount an aerosol-forming article **1**, and a heating element **31** is arranged corresponding to the mounting portion **320** and configured to heat the aerosol-forming article **1**. The controller **33** and the power supply **34** are arranged in the mounting space **300** and are located on one side of the mounting base **32** away from the air communication component **2**, and the controller **33** controls the power supply **34** to supply power to the heating element **31**. It may be understood that, one or more aerosol-forming articles **1** may be arranged in the mounting portion **320**. Alternatively, one aerosol-forming article **1** may be arranged in one mounting portion **320**, namely, the number of mounting portions **320** and the number of heating elements **31** are the same as the number of aerosol-forming articles **1**, which is specifically designed as required. The following description is provided by using an example in which one aerosol-forming article **1** is arranged in one mounting portion **320**.

(89) Referring to FIG. **11** and FIG. **12**, FIG. **11** is a schematic structural diagram of a mounting base in a vaporization main unit according to this application, and FIG. **12** is another schematic structural diagram of a mounting base in a vaporization main unit according to this application. During a specific implementation, that at least one mounting portion **320** is formed on the mounting base **32** may be that at least one groove **321** is formed on the mounting base **32**. One groove **321** is used as one mounting portion **320**, and an internal space formed by the groove **321** is a mounting position of the aerosol-forming article **1** (as shown in FIG. **11**). Namely, the groove **321** is used as the mounting portion **320** and configured to accommodate the aerosol-forming article **1**. Alternatively, a plurality of protrusions **322** may be provided on the mounting base **32**, a space encircled by the plurality of protrusions **322** is the mounting position of the aerosol-forming article **1**, and the space encircled by the plurality of protrusions **322** is used as one mounting portion **320** (as shown in FIG. **12**). The arrangement manner of the mounting portion **320** may be designed as required, provided that the aerosol-forming article **1** can be fixed.

(90) To improve the heating efficiency, there is a gap between a side surface of the aerosol-forming article **1** and an inner side surface of the mounting portion **320** to implement air heat insulation, and the heating element **31** and the inner side surface of the mounting portion **320** are at least partially spaced to implement air heat insulation between the heating element **31** and an inner wall surface of the groove **321**, so that heat of the heating element **31** for heating the aerosol-forming article **1** is mostly absorbed by the aerosol-forming article **1**, and only a few of the heat is conducted to the mounting base **32**, thereby reducing a heat loss.

(91) Referring to FIG. **13**, FIG. **13** is a schematic partial cross-sectional view of a first embodiment of a vaporization main unit according to this application.

(92) In the first embodiment of the vaporization main unit **3**, a groove **321** is formed on the mounting base **32** as the mounting portion **320**. Namely, the mounting portion **320** forms the groove **321**, and the aerosol-forming article **1** and the heating element **31** are arranged in the groove **321**. Specifically, the groove **321** includes an accommodating cavity, and the accommodating cavity is configured to accommodate the aerosol-forming article **1**. The heating element **31** is arranged in the groove **321**, and the heating element **31** generates heat when energized to heat the aerosol-forming article **1**. Specifically, the heating element **31** generates heat when energized to heat an encapsulation layer **12**, and the encapsulation layer **12** conducts the heat to an aerosol-forming substrate **11** to form aerosols. Namely, the aerosol-forming article **1** is heated in a resistive manner. To improve the heating efficiency, the heating element **31** is attached to the encapsulation layer **12** of the aerosol-forming article **1**. It may be understood that, one or more heating elements **31** may be arranged in the mounting portion **320**, provided that the aerosol-forming article **1** is uniformly heated, which is specifically selected as required. The following is described by using an example in which one heating element **31** is arranged in the mounting portion **320**.

(93) In an implementation, a plurality of aerosol-forming articles **1** are arranged, the mounting base **32** is provided with a plurality of mounting portions **320**, and the heating element **31** and the

aerosol-forming article **1** are arranged in each mounting portion **320**. Namely, a plurality of grooves **321** are provided on the mounting base **32**, one groove **321** is used as one mounting portion **320**, and one aerosol-forming article **1** is arranged in one groove **321**. The vaporization main unit **3** includes a plurality of heating elements **31**, and one heating element **31** is arranged corresponding to one mounting portion **320**. Namely, one heating element **31** is arranged in one groove **321**. A pin of the heating element **31** is electrically connected to the power supply **34** outside the accommodating cavity. The pin of the heating element **31** bypasses the accommodating cavity to be connected to the power supply **34**, or the pin of the heating element **31** passes through a bottom wall of the groove **321** to be connected to the power supply **34**.

(94) To heat the aerosol-forming article **1** uniformly, a projection of the aerosol-forming article **1** on the heating element **31** at least covers a part of the heating element **31**. Namely, an area of a surface of the heating element **31** in contact with the aerosol-forming article **1** is greater than an area of the surface of the heating element **31**, so that the heating element **31** heats a whole cross-section of the aerosol-forming article **1** uniformly, thereby helping maintain the taste consistency.

(95) Because the aerosol-forming article **1** and the heating element **31** are arranged in the groove **321** formed on the mounting base **32**, namely, the heating element **31** heats the aerosol-forming article **1** in the groove **321**. To improve the heating efficiency and reduce a heat loss, the mounting base **32** is made of a material with low thermal conduction and high temperature resistance such as ceramics or foams. In this embodiment, the mounting base **32** is made of a ceramic with low thermal conduction and high temperature resistance.

(96) To avoid mutual impact between adjacent grooves **321**, a third partition hole **323** is provided between adjacent grooves **321** on the mounting base **32**, to further reduce the heat loss.

(97) To further improve the heating efficiency, there is a gap between the side surface of the aerosol-forming article **1** and a side surface of the groove **321** to implement air heat insulation. The heating element **31** and an inner wall surface of the groove **321** are at least partially spaced to implement air heat insulation between the heating element **31** and the inner wall surface of the groove **321**, so that heat of the heating element **31** for heating the aerosol-forming article **1** is mostly absorbed by the aerosol-forming article **1**, and only a few of the heat is conducted to the mounting base **32**, thereby reducing the heat loss.

(98) In an implementation, the heating element **31** includes a heating body **311** and a mounting ear **312** fixedly connected to the heating body **311**. The heating body **311** is connected to the side surface of the groove **321** through the mounting ear **312**, namely, the heating body **311** is fixed to the groove **321** through the mounting ear **312**. In addition, the heating body **311** and a bottom surface of the groove **321** are spaced to implement air heat insulation. It may be understood that, a smaller contact area between the mounting ear **312** and the side surface of the groove **321** better helps reduce the heat loss, provided that the mounting ear **312** can fix the heating body **311** onto the side surface of the groove **321**. The fixing manner between the heating element **31** and the groove **321** is the same among the plurality of grooves **321**.

(99) In another implementation, a bump **3211** is provided on the bottom surface of the groove **321**, and the heating element **31** is arranged on the bump **3211**. The bump **3211** is in contact with a part of the heating element **31**, and the heating element **31** and the side surface of the groove **321** are at least partially spaced to implement air heat insulation.

(100) It may be understood that, a smaller contact area between the bump **3211** and the heating element **31** better helps reduce the heat loss, provided that the bump **3211** can fix the heating element **31** in the groove **321**. The fixing manner between the heating element **31** and the groove **321** is the same among the plurality of grooves **321**.

(101) In this embodiment, to fix the position of the heating element **31** and prevent the heating element **31** from shaking in the groove **321**, the heating element **31** includes a heating body **311** and a mounting ear **312** fixedly connected to the heating body **311**. The heating body **311** and the side surface of the groove **321** are spaced, the heating body **311** is connected to the side surface of

the groove **321** through the mounting ear **312**, and the heating body **311** and the bottom surface of the groove **321** are spaced. A bump **3211** is provided on the bottom surface of the groove **321**, and the heating body **311** is connected onto the bump **3211**. That is, the heating body **311** is fixed in the groove **321** through the mounting ear **312** and the bump **3211**. The fixing manner between the heating element **31** and the groove **321** is the same among the plurality of grooves **321**.

(102) The heating element **31** is set to be able to rise a temperature to 500° C. within 3 seconds, so that the heating element **31** can cause the aerosol-forming substrate **11** in the aerosol-forming article **1** to reach a volatilization temperature thereof quickly to release aerosols. Further, the entire heating efficiency is improved by using the high thermal conduction performance of the encapsulation layer **12** in the aerosol-forming article **1**, the feature of quick heat conduction of the aerosol-forming substrate **11** due to a thin thickness, the low thermal conduction and high temperature resistance performance of the mounting base **32**, and the air heat insulation between the mounting base **32** and the heating element **31** with the aerosol-forming article **1**. Therefore, the aerosol-forming substrate **11** in the aerosol-forming article **1** can release aerosols quickly.

(103) Referring to FIG. **14a**, FIG. **14b**, and FIG. **15**, FIG. **14a** is a schematic cross-sectional view of an implementation of a heating element in a first embodiment of a vaporization main unit according to this application, FIG. **14b** is a schematic cross-sectional view of another implementation of a heating element in a first embodiment of a vaporization main unit according to this application, and FIG. **15** is a three-dimensional schematic structural diagram of a heating element in a first embodiment of a vaporization main unit according to this application.

(104) The heating element **31** includes a heating body **311** and a mounting ear **312**. The heating body **311** includes a heat conducting base layer **319**, a heating circuit layer **315**, and an electrode **317**. Namely, the heating element **31** includes the heat conducting base layer **319**, the heating circuit layer **315**, and the electrode **317**. The heat conducting base layer **319** includes a first surface and a second surface that are opposite to each other, and the second surface of the heat conducting base layer **319** is configured to be in contact with the aerosol-forming article **1**. The heating circuit layer **315** is arranged on the first surface of the heat conducting base layer **319**. The heating circuit layer **315** is arranged on the first surface of the heat conducting base layer **319**, so that the entire surface of the heat conducting base layer **319** has uniform temperature. Namely, the entire surface of the heat conducting base layer **319** is a high temperature region. The electrode **317** is arranged on a surface of one side of the heating circuit layer **315** away from the heat conducting base layer **319** and is electrically connected to the heating circuit layer **315**.

(105) The heating element **31** further includes a pin **317a**, where one end of the pin **317a** is connected to the electrode **317**, and the other end of the pin is configured to connect to the power supply **34**.

(106) In the related art, most of the heating element is inserted in the aerosol-forming substrate, and a small part of the heating element is exposed to the outside of the aerosol-forming substrate. The part of the heating element inserted in the aerosol-forming substrate forms a high temperature region to heat the aerosol-forming substrate. The part exposed to the outside of the aerosol-forming substrate forms a low temperature region for ease of arrangement of assembly support points of leads. A lead region for arranging leads is provided in the low temperature region, to implement an electrical connection between the heating element and the controller. The heating element adopts a layout of a high temperature region, a low temperature region, and a lead region, and uses the low temperature region as assembly support points, which has poor temperature uniformity. The entire surface of the heating element **31** in this application is a high temperature region, which has uniform temperature, and the electrode **317** is assembled in the high temperature region.

(107) The heating body **311** of the heating element **31** in this application is a sheet-like structure. The heating body **311** is set to be a sheet-like structure, so that the heating element **31** and the aerosol-forming article **1** are in contact in a large-scale manner. Therefore, the aerosol-forming article **1** is heated uniformly, and the taste consistency is maintained. The heating circuit layer **315**

generates heat and conducts the heat to the heat conducting base layer **319**. To improve the heat utilization of the heating circuit layer **315**, a thickness of the heat conducting base layer **319** ranges from 0.1 mm to 1.0 mm. Optionally, the thickness of the heat conducting base layer **319** is 0.2 mm. A shape of the heat conducting base layer **319** may be manufactured into a circle or a square as required.

(108) The heat conducting base layer **319** may be made of a heat conduction ceramic material. The heating element **31** further includes a protective layer **316**, and the protective layer **316** is arranged on the surface of the side of the heating circuit layer **315** away from the heat conducting base layer **319** (as shown in FIG. **14a**). A shape of the protective layer **316** is designed according to the shape of the heat conducting base layer **319**, and a material of the protective layer **316** includes characteristics of high hardness and high temperature resistance, to protect the heating circuit layer **315** and improve the high temperature stability of the heating circuit layer **315**. Optionally, the material of the protective layer **316** is ceramic glaze.

(109) The heat conducting base layer **319** may alternatively be made of a metal material. The heating element **31** further includes an insulating layer **314** and a protective layer **316**. The insulating layer **314** is arranged between the heat conducting base layer **319** and the heating circuit layer **315**, and the protective layer **316** is arranged on a surface of one side of the heating circuit layer **315** away from the insulating layer **314**, namely, the protective layer **316** is arranged on the surface of the side of the heating circuit layer **315** away from the heat conducting base layer **319** (as shown in FIG. **14b**). Specifically, the heat conducting base layer **319** is made of a metal material with a high thermal conductivity, such as stainless steel, copper alloy, or aluminum alloy. Such a material has high strength and toughness, is hard to break, and has high reliability, so that a temperature field of the heat conducting base layer **319** has high uniformity under quick heating. Optionally, the material of the heat conducting base layer **319** is **430** stainless steel. Shapes of the insulating layer **314** and the protective layer **316** are designed according to the shape of the heat conducting base layer **319**. A material of the protective layer **316** includes characteristics of high hardness and high temperature resistance, to protect the heating circuit layer **315** and improve the high temperature stability of the heating circuit layer **315**. Optionally, the material of the protective layer **316** is ceramic glaze.

(110) Because the heating body **311** is attached to the aerosol-forming article **1**, only a surface of the heating body **311** is in contact with the aerosol-forming article **1**, namely, only the second surface of the heat conducting base layer **319** is in contact with the aerosol-forming article **1**. The insulating layer **314** does not need to be arranged on the first surface and the second surface of the heat conducting base layer **319**, and the protective layer **316** on the two surfaces does not need to be arranged further, thereby simplifying a process procedure.

(111) To further increase the contact area between the heating element **31** and the aerosol-forming article **1**, the second surface of the heat conducting base layer **319** is set to be an arc surface structure, and a corresponding surface of the aerosol-forming article **1** in contact with the second surface of the heat conducting base layer **319** is set to be an arc surface. Namely, the surface of the aerosol-forming article **1** in contact with the heating element **31** is an arc surface. In addition, a bending direction and a bending degree of the surface of the aerosol-forming article **1** in contact with the heating element **31** and a bending direction and a bending degree of the heat conducting base layer **319** are set in an engagement manner.

(112) Further, the heating circuit layer **315** generates heat and conducts the heat to the heat conducting base layer **319**. To ensure that the temperature of the entire surface of the heat conducting base layer **319** is uniform, the first surface of the heat conducting base layer **319** is also set to be an arc surface, and a bending direction and a bending degree of the first surface are the same as the bending direction and the bending degree of the second surface. Namely, the first surface of the heat conducting base layer **319** is set to be an arc surface structure corresponding to the second surface. In an implementation, a protruding direction of the first surface and the second

surface is a direction away from the electrode **317**. In another implementation, a protruding direction of the first surface and the second surface is a direction approaching the electrode **317**.

(113) It may be understood that, when the heat conducting base layer **319** is made of a metal material, and the first surface and the second surface of the heat conducting base layer **319** are both an arc surface structure, to ensure that the temperature of the entire surface of the heat conducting base layer **319** is uniform, a cross-section of the insulating layer **314** is an arc, and a bending direction and a bending degree of the arc are the same as the bending direction and the bending degree of the second surface of the heat conducting base layer **319**. The insulating layer **314** can still maintain relatively good stability and insulation performance under a high temperature.

(114) The mounting ear **312** is arranged on the heat conducting base layer **319**. Specifically, a plurality of spaced mounting ears **312** are arranged on a periphery of the heat conducting base layer **319**, and the mounting ear **312** is configured to fix the heating element **31**. A ratio of a contact length between the mounting ear **312** and the side surface of the heat conducting base layer **319** to a circumference of the side surface is less than 1:12. A smaller contact area between the mounting ear **312** and the heat conducting base layer **319** indicates fewer heat conducted by the heating body **311** to other components through the mounting ear **312**, and better helps reduce a heat loss the heating element **31**, provided that the size setting of the mounting ear **312** can fix the heating body **311**.

(115) It may be understood that, the mounting ear **312** may be formed by the periphery of the heat conducting base layer **319** through extending outward. Optionally, a thickness of the mounting ear **312** is less than the thickness of the heat conducting base layer **319**, so that heat conducted by the heating body **311** to other components through the mounting ear **312** can be reduced, which helps reduce the heat loss of the heating element **31**. The heating element **31** is mounted in the groove **321** through the mounting ear **312**, and the heat conducting base layer **319** and the side wall of the groove **321** form an air gap, to improve the energy utilization of the heating element **31** through air heat insulation.

(116) The heating circuit layer **315** in the heating element **31** includes a temperature coefficient of resistance (TCR) characteristic, and the heating circuit layer **315** is electrically connected to the controller **33** through the electrode **317**. A temperature of the heating circuit layer **315** can be increased to 500° C. within 3 seconds. The entire heating circuit layer **315** is a high temperature region. The electrode **317** arranged on the heating circuit layer **315** is assembled in the high temperature region.

(117) Referring to FIG. **16**, FIG. **16** is a schematic structural diagram of a heating circuit layer of a heating element in a first embodiment of a vaporization main unit according to this application.

(118) The heating circuit layer **315** is a heating circuit, and patterns formed through bending of the heating circuit include a first section **3151**, a second section **3152**, and a third section **3153**. The first section **3151** is arranged close to an edge of the heat conducting base layer **319** and includes two first notches **3154** provided opposite to each other. The second section **3152** and the third section **3153** are arranged in a region encircled by the first section **3151**, the second section **3152** and the third section **3153** are both connected to the first section **3151**, and patterns encircled by the second section **3152** and the third section **3153** are arranged symmetrically. Specifically, two ends of the second section **3152** are respectively connected to two end portions of one of the first notches **3154** of the first section **3151**, and two ends of the third section **3153** are respectively connected to two end portions of the other of the first notches **3154** of the first section **3151**. There are two electrodes **317**, where one electrode **317** is connected to the second section **3152**, and the other electrode **317** is connected to the third section **3153**.

(119) For example, a cross-section of the heat conducting base layer **319** is a circle. The first section **3151** of the heating circuit layer is arranged close to an edge of the insulating layer **314** to form a shape of a circular ring and includes two first notches **3154** provided opposite to each other. The second section **3152** and the third section **3153** are arranged in the circular ring encircled by the first section **3151**, the second section **3152** and the third section **3153** are respectively in a shape

of a triangle and form a second notch **3155** at a vertex angle, and the triangles encircled by the second section **3152** and the third section **3153** are arranged symmetrically. Two end portions of the second notch **3155** of the second section **3152** are respectively connected to two end portions of one of the first notches **3154** of the first section **3151**, and two end portions of the second notch **3155** of the third section **3153** are respectively connected to two end portions of the other of the first notches **3154** of the first section **3151**.

(120) In the first embodiment of the vaporization main unit **3**, the controller **33** controls the heating element **31** to work, to heat the aerosol-forming article **1** in the mounting portion **320** corresponding to the heating element **31**.

(121) Specifically, the controller **33** may control a plurality of heating elements **31** to work at the same time or control the plurality of heating elements **31** to work sequentially, which is specifically designed as required. When the controller **33** controls the plurality of heating elements **31** to work sequentially, aerosol-forming articles **1** in a plurality of mounting portions **320** are heated sequentially. Namely, after controlling one heating element **31** to heat one aerosol-forming article **1**, the controller **33** continues to control a next heating element **31** to heat a next aerosol-forming article **1**. A total working time for which the controller **33** controls each heating element **31** is a first preset duration, and the first preset duration is a time that the aerosol-forming substrate **11** in the aerosol-forming article **1** is consumed.

(122) A heating total duration of the plurality of aerosol-forming articles **1** is the same as a heating total duration of a convention heat-not-burn (HNB) product, and a total number of times that aerosols can be inhaled after the plurality of aerosol-forming articles **1** are heated is the same as a number of times that aerosols are inhaled after the conventional HNB product is heated. The conventional HNB product is replaced with the plurality of aerosol-forming articles **1**, the thickness of the aerosol-forming substrate **11** in the aerosol-forming article **1** is set to range from 0.5 mm to 3 mm to reduce a shape volume of the aerosol-forming substrate, and the plurality of aerosol-forming articles **1** are heated sequentially, so that the aerosol-forming substrate **11** can be prevented from being locally heated for a long time, and occurrence of a burnt flavor can be further prevented from affecting the taste, thereby improving the taste consistency

(123) In an embodiment, the controller **33** controls the next heating element **31** to work in advance before the total working time of the current heating element **31** reaches the first preset duration. Specifically, the controller **33** controls the next heating element **31** to work when the total working time of the current heating element **31** reaches a second preset duration, and the second preset duration is shorter than the first preset duration. A difference between the second preset duration and the first preset duration ranges from 5 seconds to 15 seconds. Optionally, the difference between the second preset duration and the first preset duration is 10 seconds.

(124) The controller **33** controls the next heating element **31** to work when the total working time of the current heating element **31** reaches the second preset duration, so that the next aerosol-forming article **1** is preheated in advance when heating of the current aerosol-forming article **1** is near the end, and a release amount of aerosols is relatively stable, thereby preventing the release amount of aerosols from being decreased suddenly and helping improve the use experience of users.

(125) In an embodiment, the controller **33** detects whether a heating process of the current heating element **31** is interrupted, and controls the next heating element **31** to work after the controller **33** detects that the heating process of the current heating element **31** is interrupted and the total working time of the interrupted heating element **31** reaches a third preset duration. When working of the heating element **31** does not reach the first preset duration, the aerosol-forming article **1** is still heated by residual heat after heating is interrupted, which may consume a small amount of aerosol-forming substrate. To prevent the heating element **31** from dry burning, the third preset duration is shorter than the second preset duration. A difference between the third preset duration and the second preset duration ranges from 1 seconds to 5 seconds. That is, when the controller **33**

controls the plurality of heating elements **31** to work, the controller first detects whether a heating element **31** is interrupted during heating. If yes, the controller causes the interrupted heating element **31** to work first, namely, first heats the aerosol-forming article **1** that is not consumed, and causes the next heating element **31** to preheat the next aerosol-forming article **1** when the total heating time of the interrupted heating element **31** reaches the third preset duration.

(126) Referring to FIG. **17**, FIG. **17** is a schematic diagram of a relationship between a heating time and a temperature of an aerosol-forming article according to this application.

(127) A continuous working time for which the controller **33** controls a first heating element **31** is a first preset duration. The first preset duration of the first heating element **31** includes: a first time period, a second time period, and a third time period. The controller **33** controls the first heating element **31** to cause the aerosol-forming substrate **11** in the aerosol-forming article **1** to rise from a first temperature to a second temperature within the first time period, cause the aerosol-forming substrate **11** in the aerosol-forming article **1** to decrease from the second temperature to a third temperature within the second time period, cause the aerosol-forming substrate **11** in the aerosol-forming article **1** to keep at the third temperature with the third time period, and stop heating at the end of the third time period.

(128) The first preset duration of the first heating element **31** further includes a fourth time period. The fourth time period is between the first time period and the second time period, and the aerosol-forming substrate **11** in the aerosol-forming article **1** is caused to keep at the second temperature within the fourth time period.

(129) The first time period ranges from 5 seconds to 7 seconds, the second time period ranges from 3 seconds to 5 seconds, the third time period ranges from 22 seconds to 25 seconds, and the fourth time period ranges from 3 seconds to 4 seconds. The first temperature ranges from 20° C. to 30° C., the second temperature ranges from 300° C. to 350° C., and third temperature ranges from 220° C. to 280° C. Optionally, the first temperature is 25° C., the second temperature is 330° C., and the third temperature is 250° C. The third temperature is a temperature that the aerosol-forming substrate **11** can release aerosols.

(130) In an implementation, a continuous working time for which the controller **33** controls a second heating element **31**, a third heating element **31**, and a fourth heating element **31** other than the first heating element **31** is a first preset duration. The first preset duration of the second heating element **31**, the third heating element **31**, and the fourth heating element **31** other than the first heating element **31** includes a fifth time period and a sixth time period. The controller **33** controls the heating element **31** to cause the aerosol-forming substrate **11** in the aerosol-forming article **1** to rise from the first temperature to the third temperature within the fifth time period, cause the aerosol-forming substrate **11** in the aerosol-forming article **1** to keep at the third temperature within the sixth time period, and stop heating at the end of the sixth time period. The fifth time period ranges from 2 seconds to 5 seconds, and the sixth time period ranges from 25 seconds to 28 seconds.

(131) The aerosol-forming substrate **11** in the first aerosol-forming article **1** is heated to the second temperature higher than the temperature (the third temperature) for releasing aerosols by the first heating element **31** within the first time period, which helps the aerosol-forming substrate **11** to release aerosols quickly. Therefore, when a user inhales an aerosol-forming device, aerosols are inhaled within a shortest possible time, thereby improving the use experience of the user. It may be understood that, because the next heating element **31** is caused to preheat the next aerosol-forming article **1** when heating of the current heating element **31** is near the end, the second heating element **31**, the third heating element **31**, and the fourth heating element **31** other than the first heating element **31** do not need to cause the aerosol-forming substrates **11** in the corresponding second aerosol-forming article **1**, third aerosol-forming article **1**, and fourth aerosol-forming article **1** to first rise to the second temperature and then decrease to the third temperature, and instead, cause the aerosol-forming substrates to direct rise to the third temperature. Because when heating of the

heating element **31** is near the end, most of the aerosol-forming substrate **11** in the corresponding aerosol-forming article **1** is consumed, and the concentration of the released aerosols is decreased. To ensure the concentration consistency of the released aerosols, the next heating element **31** is caused to heat the next aerosol-forming article **1** to release aerosols when heating of the heating element **31** is near the end, to ensure the taste consistency.

(132) It may be understood that, after controlling one heating element **31** to work for the second preset duration, the controller **33** controls a next heating element **31** to work. In this case, the next heating element **31** corresponds to an aerosol-forming article **1** that is not heated. Namely, after the controller **33** detects that the aerosol-forming substrate **11** in the aerosol-forming article **1** is heated for the first preset duration, the controller **33** no longer controls the corresponding heating element **31** to work, to prevent the heating element **31** from dry burning and power wastes. The numbers of mounting portions **320**, heating elements **31**, and aerosol-forming articles **1** are correspondingly set and are designed as required.

(133) Referring to FIG. **18** and FIG. **19**, FIG. **18** is a schematic partial structural diagram of a second embodiment of a vaporization main unit according to this application; and FIG. **19** is a schematic partial cross-sectional view of a second embodiment of a vaporization main unit according to this application.

(134) In the second embodiment of the vaporization main unit **3**, the structure of the vaporization main unit **3** is basically the same as the structure in the first embodiment, functions and a control method of the controller **33** are the same as that in the first embodiment, and differences lie in the structure of the heating element **31** and a position relationship between the heating element **31** and the mounting portion **320**. In the second embodiment, the aerosol-forming article **1** arranged on the vaporization main unit **3** may be the aerosol-forming article **1** shown in FIG. **5** to FIG. **9**.

(135) In this embodiment, the heating element **31** is an electromagnetic member, and the electromagnetic member is configured to provide a variable magnetic field.

(136) Specifically, the electromagnetic member includes an electromagnetic coil, the encapsulation layer **12** is a heating layer, and the heating layer generates eddy currents in the magnetic field of the electromagnetic member to generate heat, to heat the aerosol-forming substrate **11** to form aerosols. Namely, eddy currents are generated when the variable magnetic field generated by the electromagnetic coil penetrates the metal heating layer, so that the metal heating layer generate heat and heats the aerosol-forming substrate **11**. The electromagnetic coil is horizontally coiled to form a disc-type structure. Namely, after one end of the electromagnetic coil is fixed, the other end of the electromagnetic coil is wound along an outer side of the electromagnetic coil. The electromagnetic coil is arranged on the bottom surface of the groove **321**, a side surface of the electromagnetic coil and the side surface of the groove **321** are spaced, and the electromagnetic coil and the aerosol-forming article **1** are spaced.

(137) An aerosol generation method is provided based on the working manner in which the controller **33** controls the heating element **31**. Referring to FIG. **20**, FIG. **20** is a schematic flowchart of an aerosol generation method according to this application.

(138) Steps of the aerosol generation method are as follows:

(139) **S01**: Provide a plurality of aerosol-forming articles and a plurality of heating elements.

(140) Specifically, the aerosol-forming articles **1** and the heating elements **31** are arranged correspondingly. Namely, the number of aerosol-forming articles **1** is the same as the number of heating elements **31**, and one heating element **31** heats one aerosol-forming article **1**.

(141) The aerosol-forming article **1** includes an aerosol-forming substrate **11** and an encapsulation layer **12**. The encapsulation layer **12** covers at least a part of the aerosol-forming substrate **11**, so that the encapsulation layer **12** isolates the aerosol-forming substrate **11** from the heating element **31**.

(142) The heating element **31** includes a resistance wire, and the resistance wire heats the encapsulation layer **12**, so that the encapsulation layer **12** bakes the aerosol-forming substrate **11** to

generate aerosols. Namely, the heating element **31** heats the encapsulation layer **12**, so that the encapsulation layer **12** bakes the aerosol-forming substrate **11** to generate aerosols. Alternatively, the heating element **31** includes an electromagnetic coil, the electromagnetic coil and the encapsulation layer **12** (the encapsulation layer **12** is a heating layer) generate heat under the action of a magnetic field of the electromagnetic coil, and the encapsulation layer **12** heats the aerosol-forming substrate **11** to form aerosols. To improve the heating efficiency of the heating element **31**, the encapsulation layer **12** is attached to the heating element **31**.

(143) **S02**: A controller controls the plurality of heating elements to work sequentially.

(144) Specifically, the controller **33** controls the plurality of heating elements **31** to heat the aerosol-forming articles **1** sequentially. The plurality of heating elements **31** all work for a first preset duration, and the controller **33** is further configured to control a next heating element **31** to work when the heating element **31** works for a second preset duration. The second preset duration is shorter than the first preset duration.

(145) In this method, the manner in which the controller **33** controls the heating element **31** can implement the functions of the controller **33** described above, which is not described in detail herein.

(146) Referring to FIG. **21** to FIG. **25**, FIG. **21** is a schematic structural diagram of an air communication component according to this application, FIG. **22** is a schematic cross-sectional view of an air communication component according to this application, FIG. **23** is a schematic cross-sectional view of a top cover in an air communication component according to this application, FIG. **24** is a schematic cross-sectional view of a bottom cover in an air communication component according to this application, and FIG. **25** is a schematic partial cross-sectional view of an aerosol-forming device according to this application.

(147) The air communication component **2** includes a top cover **21** and a bottom cover **22**. The top cover **21** is provided with a first cavity **211** and a second cavity **212** that is in communication with each other. An air outlet hole **231** is provided on a cavity wall of the second cavity **212** for inhalation of a user. The bottom cover **22** includes a bottom cover body **221** and a protrusion **222** provided on the bottom cover body **221**, where the bottom cover body **221** is arranged in the first cavity **211**, and the protrusion **222** is provided in the second cavity **212**. An air outlet channel **23** is provided on the protrusion **222**.

(148) The bottom cover **22** is configured to engage with one end of the vaporization main unit **3** provided with the aerosol-forming article **1** to form a vaporization cavity **24**. Namely, the air communication component **2** engages with the vaporization main unit **3** to form the vaporization cavity **24**. The aerosol-forming article **1** is arranged on one end of the vaporization main unit **3** close to the air communication component **2**, and the aerosol-forming article **1** is located in the vaporization cavity **24**. Specifically, the bottom cover body **221** includes a first surface **2211** and a second surface **2212** arranged opposite to the first surface **2211**. The protrusion **222** is provided on the first surface **2211**, the second surface **2212** includes a recess **2213**, and the recess **2213** engages with the end of the vaporization main unit **3** provided with the aerosol-forming article **1** to form the vaporization cavity **24**.

(149) The bottom cover body **221** and a top wall of the first cavity **211** are spaced to form an air inlet channel **25**.

(150) Namely, the air inlet channel **25** is formed between the bottom cover **22** and the top cover **21**, the air inlet channel **25** communicates the vaporization cavity **24** with external air, and the air outlet channel **23** communicates the vaporization cavity **24** with the air outlet hole **231**.

(151) The air inlet channel **25** is formed between the top cover **21** and the bottom cover **22**. In this way, during inhalation of a user, external cool air continuously flows into the air inlet channel **25**, and heat in the air inlet channel **25** is carried out in a process that an airflow flows toward the vaporization cavity **24**, so that the top cover **21** is cooled down, namely, an outer wall of a suction nozzle component **2** is cooled down, and the cooling efficiency is improved, thereby preventing a

high temperature from burning the user.

(152) To cause the external air to flow from one end of a gap between the top cover **21** and the bottom cover **22** toward the other end of the gap after entering the suction nozzle component **2**, an air inlet hole **251** is provided on a side wall of the first cavity **211**.

(153) The cavity wall of the second cavity **212** includes a top wall and an annular side wall, and the air outlet hole **231** is provided on the top wall of the second cavity **212**. A top surface of the protrusion **222** abuts against the top wall of the second cavity **212**, the annular side wall of the second cavity **212** and a side surface of the protrusion **222** are spaced, and a shielding sheet **26** is arranged between the annular side wall of the second cavity **212** and the side surface of the protrusion **222**. The shielding sheet **26** divides a cavity formed by the protrusion **222** with the second cavity **212** and the first cavity **211** through engagement into a first space **261** and a second space **262**. The external air enters the first space **261** through the air inlet hole **251**, and enters the second space **262** from the first space **261** in an extending direction of the protrusion **222**. It may be understood that, the shielding sheet **26** may be arranged on the side surface of the protrusion **222** or may be arranged on the annular side wall of the second cavity **212**.

(154) Referring to FIG. 25, in this embodiment, the shielding sheet **26** is arranged on the side surface of the protrusion **222**. Specifically, the shielding sheet **26** is arranged on two sides of the protrusion **222**. Because the bottom cover body **221** and the top wall of the first cavity **211** are spaced, one end of the shielding sheet **26** extends onto the bottom cover body **221**, and a part of the shielding sheet **26** abuts against an inner wall surface of the first cavity **211**. The other end of the shielding sheet **26** extends in a direction approaching the top wall of the second cavity **212**, to divide the cavity formed by the protrusion **222** with the second cavity **212** and the first cavity **211** through engagement into the first space **261** and the second space **262**.

(155) In an implementation, one end of the shielding sheet **26** close to the second cavity **212** abuts against the top wall of the second cavity **212**, and the end of the shielding sheet **26** close to the second cavity **212** is provided with a notch **263**, to communicate the first space **261** with the second space **262**. A size of the notch **263** is designed according to requirements on inhalation resistance and an air intake.

(156) In another implementation, one end of the shielding sheet **26** close to the second cavity **212** abuts against the top wall of the second cavity **212**, and the end of the shielding sheet **26** close to the second cavity **212** is provided with a through hole, to communicate the first space **261** with the second space **262**. A size of the through hole is designed according to requirements on inhalation resistance and an air intake.

(157) In still another implementation, there is a gap between one end of the shielding sheet **26** close to the second cavity **212** and the top wall of the second cavity **212**, to communicate the first space **261** with the second space **262**. A distance (the gap) between the end of the shielding sheet **26** close to the second cavity **212** and the top wall of the second cavity **212** ranges from 4 mm to 7 mm, and a size of the gap is designed according to requirements on inhalation resistance and an air intake.

(158) In an implementation, the bottom cover **22** further includes an elastic member **223**. The elastic member **223** is arranged on the bottom cover body **221** and configured to squeeze the aerosol-forming article **1**, so that the aerosol-forming article **1** is tightly attached to the heating element **31** in the vaporization main unit **3**. A mounting hole **2214** is provided on a bottom wall of the recess **2213** of the bottom cover body **221**, and the mounting hole **2214** is configured to mount the elastic member **223**. Namely, a structure size and an arrangement manner of the mounting hole **2214** and a structure size and an arrangement manner of the elastic member **223** are set in an engagement manner.

(159) A surface of the elastic member **223** close to the aerosol-forming article **1** is provided with a recess **2231**, and an air outlet hole of the aerosol-forming article **1** is exposed in the recess **2231**, namely, aerosols vaporized by the aerosol-forming article **1** are released in the recess **2231**. A side wall of the recess **2231** includes a through hole or a notch, so that the aerosols in the recess **2231**

enters the vaporization cavity **24**.

(160) A plurality of elastic members **223** are arranged on the bottom cover body **221**, where one elastic member **223** is arranged corresponding to the protrusion **222**, and other elastic members **223** are arranged on the bottom cover body **221** in a direction away from the protrusion **221**. A first communication hole **2232** is provided on an elastic member **223** that is farthest to the protrusion **222** and configured to communicate the air inlet channel **25** with the vaporization cavity **24**. A second communication hole **2233** is provided on the elastic member **223** arranged corresponding to the protrusion **222** and configured to communicate the vaporization cavity **24** with the air outlet channel **23**.

(161) It may be understood that, an elastic member **223** is arranged on the bottom cover body **221**, at least one recess **2231** is provided on one side of the elastic member **223** close to the aerosol-forming article **1**, the recess **2231** is provided corresponding to the aerosol-forming article **1**, and a notch or a through hole is provided on a side wall of the recess **2231**, to engage with the aerosol-forming article **1** to form the vaporization cavity **24**. A second communication hole **2233** is provided at a position of the elastic member **223** corresponding to the protrusion **222**, to communicate the vaporization cavity **24** with the air outlet channel **23**. A first communication hole **2232** is provided at a position of the elastic member **223** corresponding to an aerosol-forming article **1** that is farthest to the protrusion **222**, to communicate the air inlet channel **25** with the vaporization cavity **24**.

(162) Referring to FIG. **26**, FIG. **26** is a schematic diagram of an air flowing direction in an air communication component according to this application.

(163) After entering the air communication component through the air inlet hole **251**, the external air enters the second space **262** from the first space **261** through the notch **263** on the shielding sheet **26** in the extending direction of the protrusion **222**, then enters the gap between the bottom cover body **221** and the top wall of the first cavity **211**, enters the vaporization cavity **24** through the first communication hole **2232**, and enters the air outlet channel **23** with aerosols through the second communication hole **2233**. The aerosols are then inhaled by the user from the air outlet hole **231**.

(164) To fully carry out the aerosols in the vaporization cavity **24**, an arrangement position of the through hole or notch on the side wall of the first communication hole **2232** on the elastic member **223** that is farthest to the protrusion **222** faces away from an adjacent elastic member **223**; and an arrangement position of the through hole or notch on the side wall of the second communication hole **2233** on the elastic member **223** arranged corresponding to the protrusion **222** faces away from an adjacent elastic member **223**.

(165) It may be understood that, the structures of the air communication component **2** and the vaporization main unit **3** described above are applicable to the structures of the fourth embodiment, the fifth embodiment, and the sixth embodiment of the aerosol-forming article **1** according to this application. For the structures of the first embodiment and the third embodiment of the aerosol-forming article **1** according to this application, this application further provides a vaporization main unit **3** of another structure.

(166) Referring to FIG. **27**, FIG. **27** is a schematic structural diagram of another aerosol-forming device according to this application.

(167) The aerosol-forming device includes an aerosol-forming article **1**, an air communication component **2**, and a vaporization main unit **3**. The vaporization main unit **3** includes a housing **30**, a heating element **31**, a controller **33**, and a power supply **34**. The controller **33** and the power supply **34** are arranged in a cavity formed by the housing **30**, and the controller **33** controls the power supply **34** to supply power to the heating element **31**. One end of the housing **30** forms a mounting groove **35**, and the mounting groove **35** is configured to accommodate the heating element **31** and the aerosol-forming article **1**. Specifically, the heating element **31** is arranged on a side wall of the mounting groove **35**, and the aerosol-forming article **1** is arranged in a space encircled by the

heating element **31**.

(168) The air communication component **2** includes a cooling member **28** and a filter member **27**. The cooling member **28** is arranged between the aerosol-forming article **1** and the filter member **27**. The cooling member **28** is a tubular body, and the tubular body forms a communication hole. In an embodiment, one end of the cooling member **28** is inserted into the mounting groove **35** and connected to the aerosol-forming article **1**, and the other end of the cooling member is arranged outside the mounting groove **35** and connected to the filter member **27**. An encapsulation layer **12** in the aerosol-forming article **1** heats an aerosol-forming substrate **11** to generate aerosols, and the aerosols reach the filter member **27** through the communication hole. There is a heat loss in a process that the aerosols pass through the communication hole, so that a temperature of the aerosols is reduced and then transmitted to a mouth of the user through the filter member **27**, thereby preventing the user from being burnt by an excessively high temperature of the aerosols. A material of the cooling member **28** is a heat resistant and dense material. For example, the material of the cooling member **28** may be plastics or ceramics.

(169) The filter member **27** is mounted on one end of the cooling member **28** away from the mounting groove **35**, and the filter member **27** covers an opening of one end of the communication hole away from the mounting groove **35**, so that the aerosols in the communication hole are transmitted to the mouth of the user through the filter member **27**. The filter member **27** is configured to filter out the aerosol-forming substrate **11** entering the communication hole along with an airflow of the aerosols. A material of the filter member **27** may be a porous material, such as a cotton core.

(170) The structures of the vaporization main unit **3** and the air communication component **2** in this embodiment are applicable to the structures of the first embodiment and the third embodiment of the aerosol-forming article **1** according to this application. The heating element **31** is a resistive heating body.

(171) Referring to FIG. **28**, FIG. **28** is a schematic structural diagram of still another aerosol-forming device according to this application.

(172) The aerosol-forming device includes an aerosol-forming article **1**, an air communication component **2**, and a vaporization main unit **3**. The aerosol-forming device in FIG. **28** and the aerosol-forming device in FIG. **27** are basically the same in structure, and a difference lies in that, the heating element **31** is an electromagnetic heating body, the heating element **31** includes a spiral coil, and a mounting sleeve **36** is arranged in the spiral coil and configured to accommodate the aerosol-forming article **1**.

(173) Specifically, the spiral coil and the mounting sleeve **36** are together arranged in the mounting groove **35**, the spiral coil is arranged on an outer surface of the mounting sleeve **36**, and a cavity formed by the mounting sleeve **36** is configured to accommodate the aerosol-forming article **1**. In an implementation, the spiral coil is embedded in a side wall of the mounting groove **35** (as shown in FIG. **28**). In another implementation, the spiral coil is in interference fit with the side wall of the mounting groove **35** or fixed to the mounting groove **35** through a structure such as a buckle.

(174) For a case that the heating element **31** is a resistive heating body, this application provides an aerosol generation method, and steps are as follows:

(175) S**11**: Provide an aerosol-forming article, the aerosol-forming article including an aerosol-forming substrate and an encapsulation layer.

(176) Specifically, the aerosol-forming article **1** includes an aerosol-forming substrate **11** and an encapsulation layer **12**. The encapsulation layer **12** covers at least a part of the aerosol-forming substrate **11**, so that the encapsulation layer **12** isolates the aerosol-forming substrate **11** from the heating element **31**.

(177) S**12**: A heating element heats the encapsulation layer, so that the encapsulation layer bakes the aerosol-forming substrate to generate aerosols.

(178) Specifically, the heating element **31** is configured to heat the aerosol-forming article **1**. The

heating element **31** includes a resistance wire, and the resistance wire heats the encapsulation layer **12**, so that the encapsulation layer **12** bakes the aerosol-forming substrate **11** to generate aerosols. Namely, the heating element **31** heats the encapsulation layer **12**, so that the encapsulation layer **12** bakes the aerosol-forming substrate **11** to generate aerosols. To improve the heating efficiency of the heating element **31**, the encapsulation layer **12** is attached to the heating element **31**.

(179) Any combination of the structure of the aerosol-forming article **1**, the structure of the suction nozzle component **2**, and the structure of the vaporization main unit **3** described above is applicable to implementing the method, so that the structure of a device corresponding to the method is not described in detail.

(180) For a case that the heating element **31** is an electromagnetic heating body, this application provides an aerosol generation method, and steps are as follows:

(181) **S31**: Provide an aerosol-forming article, the aerosol-forming article including an aerosol-forming substrate and an encapsulation layer.

(182) Specifically, the aerosol-forming article **1** includes an aerosol-forming substrate **11** and an encapsulation layer **12**. The encapsulation layer **12** covers at least a part of the aerosol-forming substrate **11**, so that the encapsulation layer **12** isolates the aerosol-forming substrate **11** from the heating element **31**.

(183) **S32**: Provide a variable magnetic field for the aerosol-forming article through an electromagnetic member, so that the encapsulation layer generates eddy currents to generate heat, to heat the aerosol-forming substrate.

(184) Specifically, the heating element **31** is an electromagnetic member. The electromagnetic member is energized, a variable magnetic field is generated after the electromagnetic member is energized, and eddy currents are generated when the variable magnetic field generated by the electromagnetic member penetrates the encapsulation layer **12**, so that the encapsulation layer **12** generates heat and heats the aerosol-forming substrate **11**.

(185) Any combination of the structure of the aerosol-forming article **1**, the structure of the suction nozzle component **2**, and the structure of the vaporization main unit **3** described above is applicable to implementing the method, so that the structure of a device corresponding to the method is not described in detail.

(186) The aerosol-forming article according to this application includes: an aerosol-forming substrate; a heating layer, where the heating layer encircles a concave portion, and the aerosol-forming substrate is arranged in the concave portion; and a cover layer, covering at least a part of the heating layer and an opening of the concave portion, where the aerosol-forming substrate is located between the heating layer and the cover layer; a through hole is provided at a position of the cover layer corresponding to the opening; and the heating layer is configured to generate eddy currents in a magnetic field to generate heat, so that the aerosol-forming substrate is heated to form aerosols. According to the aerosol-forming article provided in this application, eddy currents are generated in a magnetic current to generate heat, and the aerosol-forming substrate is further heated, thereby preventing occurrence of a burnt flavor or odor caused by heating of a heating layer that is reused and improving the taste of aerosols.

(187) The foregoing descriptions are implementations of this application, and the protection scope of this application is not limited thereto. All equivalent structure or process changes made according to the content of this specification and accompanying drawings in this application or by directly or indirectly applying this application in other related technical fields shall fall within the protection scope of this application.

(188) While the invention has been illustrated and described in detail in the drawings and foregoing description, such illustration and description are to be considered illustrative or exemplary and not restrictive. It will be understood that changes and modifications may be made by those of ordinary skill within the scope of the following claims. In particular, the present invention covers further embodiments with any combination of features from different embodiments described above and

below. Additionally, statements made herein characterizing the invention refer to an embodiment of the invention and not necessarily all embodiments.

(189) The terms used in the claims should be construed to have the broadest reasonable interpretation consistent with the foregoing description. For example, the use of the article “a” or “the” in introducing an element should not be interpreted as being exclusive of a plurality of elements. Likewise, the recitation of “or” should be interpreted as being inclusive, such that the recitation of “A or B” is not exclusive of “A and B,” unless it is clear from the context or the foregoing description that only one of A and B is intended. Further, the recitation of “at least one of A, B and C” should be interpreted as one or more of a group of elements consisting of A, B and C, and should not be interpreted as requiring at least one of each of the listed elements A, B and C, regardless of whether A, B and C are related as categories or otherwise. Moreover, the recitation of “A, B and/or C” or “at least one of A, B or C” should be interpreted as including any singular entity from the listed elements, e.g., A, any subset from the listed elements, e.g., A and B, or the entire list of elements A, B and C.

Claims

1. An aerosol-forming article, comprising: an aerosol-forming substrate; a heating layer encircling at least one concave portion, the aerosol-forming substrate being arranged in the at least one concave portion; and a cover layer covering at least a part of the heating layer and an opening of the at least one concave portion, wherein the aerosol-forming substrate is located between the heating layer and the cover layer, wherein a through hole is provided at a position of the cover layer corresponding to the opening, wherein the heating layer is configured to generate eddy currents in a magnetic field to generate heat so as to heat the aerosol-forming substrate to form aerosols, wherein the aerosol-forming substrate gathers to form a layered body, wherein a bottom wall of the at least one concave portion is attached to a bottom surface of the aerosol-forming substrate, and wherein a distance between a side wall of the at least one concave portion and a side surface of the aerosol-forming substrate ranges from 0.1 mm to 1.0 mm.
2. The aerosol-forming article of claim 1, wherein the at least one concave portion comprises an annular side wall and a bottom wall, and wherein an outer side of the annular side wall comprises a hanger loop.
3. The aerosol-forming article of claim 2, wherein the at least one concave portion comprises a plurality of concave portions, wherein the heating layer encircles the plurality of concave portions, wherein annular side walls of adjacent concave portions are spaced, and wherein adjacent concave portions of the plurality of concave portions share a same hanger loop.
4. The aerosol-forming article of claim 3, wherein the first partition hole is provided on a hanger loop shared by the adjacent concave portions.
5. The aerosol-forming article of claim 2, wherein the heating layer encircles the at least one concave portion, wherein the at least one concave portion comprises a plurality of concave portions, wherein adjacent concave portions of the plurality of concave portions are spaced, and wherein hanger loops of adjacent concave portions are spaced.
6. The aerosol-forming article of claim 1, wherein a thickness of the heating layer ranges from 0.05 mm to 0.3 mm.
7. The aerosol-forming article of claim 1, wherein the heating layer comprises an aluminum foil.
8. The aerosol-forming article of claim 1, wherein a thickness of the cover layer ranges from 0.02 mm to 0.1 mm, and wherein the cover layer comprises an aluminum foil.
9. The aerosol-forming article of claim 1, wherein a thickness of the aerosol-forming substrate ranges from 0.5 mm to 3 mm, and wherein a depth of the at least one concave portion ranges from 0.5 mm to 3 mm.
10. The aerosol-forming article of claim 1, wherein a shape of a cross-section of the aerosol-

forming substrate is a circle, and wherein a diameter of the aerosol-forming substrate ranges from 3.0 mm to 20 mm.
