

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12409997
B2
September 09, 2025
Abdelhamid; Alla Hussein et al.

Container for storing perishable contents and method of making same

Abstract

A container for storing perishable contents comprising an inner storage chamber defining top and bottom ends and comprising a floor at the bottom end thereof and an inner wall extending from the floor towards an opening at the top end thereof. The floor and the inner wall defining a storage cavity therebetween. An outer wall covers the inner wall and downwardly extends from a junction therewith at or near the top end of the storage chamber towards a bottom edge thereof at or near the bottom end of the storage chamber. The outer wall and the inner wall are spaced apart to define an air channel therebetween for receiving air. The bottom edge of the outer wall and the floor of the storage chamber define an opening therebetween leading to the air channel. The air channel provides for allowing a layer of air between the outer wall and inner wall to act as insulation for the perishable contents.

Inventors:	Abdelhamid; Alla Hussein (Longueuil, CA), Roberge-Fortin; Samuel (Longueuil, CA)
Applicant:	GROUPE CANAPA (Longueuil, CA)
Family ID:	78467849
Assignee:	Abdelhamid; Alla Hussein (Longueuil, CA); VERTLIME TECHNOLOGIES INC. (Richelieu, CA)
Appl. No.:	17/923770
Filed (or PCT Filed):	May 05, 2021
PCT No.:	PCT/CA2021/000041
PCT Pub. No.:	WO2021/223009
PCT Pub. Date:	November 11, 2021

Prior Publication Data

Related U.S. Application Data

us-provisional-application US 63020253 20200505

Publication Classification

Int. Cl.: A24F15/12 (20060101); A24F23/00 (20060101); B65D1/40 (20060101); B65D6/10 (20060101); B65D8/00 (20060101); B65D43/02 (20060101); B65D81/24 (20060101); B65D81/38 (20060101); B65D85/08 (20060101)

U.S. Cl.:

CPC B65D81/24 (20130101); A24F15/12 (20130101); A24F23/00 (20130101); B65D1/40 (20130101); B65D11/04 (20130101); B65D11/16 (20130101); B65D43/0231 (20130101); B65D81/3841 (20130101); B65D85/08 (20130101);

Field of Classification Search

CPC: B65D (81/3841)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2493633	12/1949	Mart	206/519	B65D 1/265
4367820	12/1982	Yoshino	220/634	B65D 23/001
5036998	12/1990	Dunn	D34/1	A47G 19/30
7243812	12/2006	Mansfield	206/219	B65D 1/265
2004/0084346	12/2003	Candy	206/505	B65D 21/0213
2007/0209331	12/2006	Killinger	53/474	B65D 11/16
2017/0367509	12/2016	Achan, Jr.	N/A	A47G 19/2261
2019/0300228	12/2018	Tsukatani	N/A	B29C 49/48

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2903672	12/2007	FR	A45D 40/0068
2000335543	12/1999	JP	N/A

Primary Examiner: Impink; Mollie

Attorney, Agent or Firm: PRAXIS

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application claims priority on U.S. Provisional Application Ser. No. 63/020,253 filed on May 5, 2020 and incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) The present disclosure generally relates to storing perishable contents such as herbs. More particularly, but not exclusively, the present disclosure relates to a container for storing perishable contents, a method of making this container and a method of storing perishable contents.

BACKGROUND

(2) Containers for perishable goods including herbs such as cannabis are well known and widely available. Currently, these containers are produced by blow molding thermoplastic materials such as High-density polyethylene (HDPE), Polyethylene terephthalate (PET), Polyvinyl chloride type I (PVC-1) and the like. Blow molding is used to make discontinuous hollow bodies such as bottles, containers, and vials. This technology allows to unmold parts with angles that would not otherwise be possible to unmold with art injection molding process. The walls of the containers provided by this technology are relatively thick. Cracks and small holes in the container walls allow for airborne moisture to enter the container. Water vapor may also enter the container walls through diffusion. Water vapor decreases the life cycle of perishable goods such as herbs including cannabis thereby decreasing the freshness period thereof.

OBJECTS

(3) An object of the present disclosure is to provide a container for storing perishable contents such as herbs.

(4) An object of the present disclosure is to provide a method of making a container for storing perishable contents such as herbs.

(5) An object of the present disclosure is to provide a method of storing perishable contents such as herbs.

(6) An object of the present disclosure is to provide a container assembly.

SUMMARY

(7) In accordance with an aspect of the present disclosure, there is provided a container for storing perishable contents comprising an inner storage chamber for receiving the perishable contents therein, the inner storage chamber defining top and bottom ends and comprising a floor at the bottom end thereof, an inner wall extending from the floor towards an opening at the top end thereof, the floor and the inner wall defining a storage cavity therebetween; and an outer wall covering the inner wall and downwardly extending from a junction therewith at or near the top end of the storage chamber towards a bottom edge thereof at or near the bottom end of the storage chamber, the outer wall and the inner wall being spaced apart so as to define an air channel therebetween for receiving air, the bottom edge of the outer wall and the floor of the storage chamber defining an opening therebetween leading to the air channel; wherein the air channel provides for allowing a layer of air between the outer wall and inner wall to act as insulation for the perishable contents. In an embodiment, the container further comprises interconnectors between the outer wall and inner wall. In an embodiment, the container further comprises a spout at the top end of storage defining the opening leading to the storage cavity.

(8) In an embodiment, the container further comprises interconnectors between the outer wall and inner wall. In an embodiment, each interconnector extends along a length of the outer wall and comprises an upper part thereof connected to the inner wall and a lower part thereof that is not connected to the inner wall. In an embodiment, the interconnectors are spaced apart.

(9) In an embodiment, the container further comprises a spout at the top end of storage defining the opening leading to the storage cavity. In an embodiment, the opening is releasably sealable by a closure cover.

(10) In an embodiment, the air channel size expands along the length of the inner storage chamber

from a position near or at the junction to a position near or at the bottom edge thereof at or near the bottom end of the storage chamber. In an embodiment, the air channel size retracts along the length of the inner storage chamber from a position near or at the junction to a position near or at the bottom edge thereof at or near the bottom end of the storage chamber. In an embodiment, the air channel size is similar along the length of the inner storage chamber from a position near or at the junction to a position near or at the bottom edge thereof at or near the bottom end of the storage chamber.

(11) In accordance with an aspect of the present disclosure, there is provided a method of making a container for perishable contents, the method comprising: providing an inner storage chamber for receiving the perishable contents therein, the inner storage chamber defining top and bottom ends and comprising a floor at the bottom end thereof, an inner wall extending from the floor towards an opening at the top end thereof, the floor and the inner wall defining a storage cavity therebetween; and providing an outer wall covering the inner wall and downwardly extending from a junction therewith at or near the top end of the storage chamber towards a bottom edge thereof at or near the bottom end of the storage chamber, the outer wall and the inner wall being spaced apart so as to define an air channel therebetween for receiving air, the bottom edge of the outer wall and the floor of the storage chamber defining an opening therebetween leading to the air channel.

(12) In accordance with an aspect of the present disclosure, there is provided a method of storing perishable contents, the method comprising: storing the perishable contents within an inner storage chamber comprising an inner wall extending from a floor and defining a storage cavity therebetween; and providing a layer of air between the inner wall and an outer wall covering the inner wall and being spaced therefrom to provide an air channel therebetween for receiving air, the air acting as insulation for the perishable contents; and allowing air to enter the air channel via an opening defined between a bottom edge of the outer wall and the floor.

(13) The layer of air between the outer and inner wall of the container provides for a layer of air insulation for the perishable contents within the storage chamber thereby reducing the water vapor transmission ratio and increasing the freshness time period of the perishable contents. The double spaced walls structure with air channel therebetween provides for reducing costs and manufacturing time of the containers herein.

(14) In accordance with an aspect of the present disclosure, there is provided a container assembly for perishable contents including rolled smokable cylinders of burnable material, the assembly comprising: at least one pair of a first and second containers being adjacent to each other, each of the first and the second containers comprising respective closed ends and respective open ends and defining respective and separate storage chambers for storing therein the perishable contents; and a connector interposed and connected to the first and second connectors for connecting the first and second containers; wherein the closed end of the first container is adjacent to the open end of the second container and the open end of the first container is adjacent the closed end of the second container; wherein the first and second containers are offset relative to each other providing for the open end of the first container to be positioned outwardly relative to the closed end of the second container and for the open end of the second container to be positioned outwardly relative to the closed end of the first container.

(15) In an embodiment, each of the first and second containers comprises a removable enclosure cover for sealing thereof, wherein the relative offset provides a clearance for the removable enclosure cover.

(16) In an embodiment, the connector between the at least one pair of first and second containers is made of rigid material. In an embodiment, the connector between the at least one pair of first and second containers is made of flexible material. In an embodiment, the connector between the at least one pair of first and second containers is integral to the first and second containers. In an embodiment, the connector between the at least one pair of first and second containers is removably mountable to the first and second containers. In an embodiment, the connector between

the at least one pair of first and second containers comprises an air channel therethrough.

(17) In an embodiment, the container assembly comprises a plurality of the pair of first and second containers.

(18) In accordance with an aspect of the present disclosure, there is provided a container kit comprising the container of hereinabove described and the container assembly hereinabove described.

(19) In an embodiment, the perishable contents comprise herbs. In an embodiment, the herbs comprise cannabis.

(20) Other objects, advantages and features of the present disclosure will become more apparent upon reading of the following non-restrictive description of illustrative embodiments thereof, given by way of example only with reference to the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the appended drawings:

(2) FIG. 1 is a front side view of the container for storing perishable contents in accordance with a non-restrictive illustrative embodiment of the present disclosure, the rear, and lateral sides thereof being the same as the front side view shown;

(3) FIG. 2 is a perspective view of the top and side view of the container of FIG. 1;

(4) FIG. 3 is a perspective view of the bottom and side of the container of FIG. 1;

(5) FIG. 4 is a partially transparent front view of the container of FIG. 1;

(6) FIG. 5 is sectional view of the container for storing perishable contents in accordance with a non-restrictive illustrative embodiment of the present disclosure taken along line 5-5 of FIG. 1;

(7) FIG. 6 is sectional view of the container for storing perishable contents in accordance with a non-restrictive illustrative embodiment of the present disclosure taken along line 6-6 of FIG. 1;

(8) FIG. 7 is a top plan view of the container of FIG. 1;

(9) FIG. 8 is a bottom view of the container of FIG. 1;

(10) FIG. 9 is a perspective top view of a container of FIG. 1 with an enclosure cover in accordance with a non-restrictive illustrative embodiment of the present disclosure;

(11) FIG. 10 is a top perspective view of the cover of the container shown in FIG. 10;

(12) FIG. 11 is a bottom perspective view of the cover of FIG. 10;

(13) FIG. 12 is a top perspective view of a container for storing perishable contents in accordance with another non-restrictive illustrative embodiment of the present disclosure;

(14) FIG. 13 is a top perspective view of a container for storing perishable contents in accordance with a further non-restrictive illustrative embodiment of the present disclosure;

(15) FIG. 14 is a top perspective view of a container for storing perishable contents in accordance with yet another non-restrictive illustrative embodiment of the present disclosure;

(16) FIG. 15 is a perspective view of a container for storing a rolled smokable cylinder of burnable material in accordance with a non-restrictive illustrative embodiment of the present disclosure;

(17) FIG. 16 is a perspective view of a container assembly for storing a pair of rolled smokable cylinders of burnable material in accordance with a non-restrictive illustrative embodiment of the present disclosure; and

(18) FIG. 17 is a perspective view of a container assembly for storing a plurality of rolled smokable cylinders of burnable material in accordance with a non-restrictive illustrative embodiment of the present disclosure.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

(19) Generally stated and in accordance with an aspect of the present disclosure, there is provided a container for storing perishable contents such as herbs including cannabis. The container comprises

an inner storage chamber for receiving the perishable contents therein. The inner storage chamber defines top and bottom ends thereof. The inner storage chamber comprises a floor at the bottom end thereof and an inner wall extending from the floor towards an opening at the top end thereof. The floor and the inner wall define a storage cavity therebetween. An outer wall covers the inner wall and downwardly extends from a junction therewith at or near the top end of the storage chamber towards its bottom edge at or near the bottom end of the storage chamber. The outer wall and the inner wall are spaced apart and define an air channel therebetween for receiving air. The bottom edge of the outer wall and the floor of the storage chamber define an opening therebetween leading to the air channel. The air channel provides for allowing a layer of air between the outer wall and inner wall to act as insulation for the perishable contents. In an embodiment, the container further comprises interconnectors between the outer wall and inner wall. In an embodiment, the container further comprises a spout at the top end of storage defining the opening leading to the storage cavity.

(20) With reference to FIGS. 1 to 7, non-restrictive illustrative embodiments will be described to further exemplify the disclosure only and by no means limit the scope thereof.

(21) The container **10** a main container section **12** and a spout **14**. The main container section **12** upwardly extends from the bottom end **16** of the container **10** which engages a surface and is contiguous with spout **14** forming a shoulder **18** at a junction **20** thereof. The spout **14** circumscribes an opening **22** at the top end **24** of the container. The opening **22** leads to the internal storage cavity **26** of the container **10** for storing perishable contents such as herbs including cannabis for example. The spout **14** includes external threads **27** for releasable mutual interference engagement with covers including complementary threads (as discussed further below).

(22) The main container section **12** comprises a pair of concentric and spaced apart inner and outer walls, **28** and **30**, defining an air channel **32** therebetween. The walls **28** and **30** merge at a top end **20** thereof defined by the shoulder **18** and define an opening **34** therebetween at the bottom end **16** of the container **12**. A plurality of spaced apart interconnectors or ribs **36** positioned within the air channel adjoin the inner and outer walls **28** and **30** at spaced apart respective contact points **37'** and **37''** therebetween.

(23) The inner wall **28** upwardly extends from a floor **38** which together form the inner storage chamber **40** that defines the internal storage cavity **26**. The storage chamber **40** has a top end that is contiguous with the spout **14** and thus the top end **14** of the container **10** is the end thereof. The floor **38** of the storage chamber **40** defines the bottom end **16** thereof. The inner wall **28** and the floor **38** define contiguous inner surface **42** which forms the boundary of the storage cavity **26**. The inner wall **28** defines an outer surface **44** and the floor **38** defines an outer floor wall surface **46**. Surfaces **44** and **46** merge at junction edge **48**. The floor wall surface **46** engages the surfaces on which the container **10** is positioned.

(24) The outer wall **30** defines a bottom edge **50** that also engages the surfaces on which the container **10** is positioned. The opening **34** leading to the air channel **32** is defined between the edges **48** and **50** or generally between the floor **38** and the edge **50**. The outer wall **30** defines an inner surface **52** which interfaces with the outer surface **44** of the inner wall **28**. Surfaces **44** and **52** merge at junction **20** and define the boundary of the air channel **32**. The outer wall **30** defines an outer surface **54** which is the outer surface of the main container section **12**.

(25) The ribs **36** are wing like structures with larger upper parts **36A** which extend between the surfaces **44** and **52** including at the junction **20** thereof and receding lower parts **36B** which are not connected to surface **44** but only along surface **52** defining a free vertically extending edge **55** that recedes further away (in a diagonal fashion) from surface **44** as part **36B** extend towards bottom edge **50**. Likewise, the wall **28** is tapered as it extends from the extension towards the floor **38**. Each wing like rib **36** defines opposite faces **56A** and **56B**. Thus, the air channel **32** has empty section **58** between the ribs **36** and a contiguous pathway **60** beneath the upper parts **36B**. The ribs **36** also define respective bottom rib edge **51** at or near bottom edge **50**.

(26) The foregoing structure provides for a pair of thinner walls **28** and **30** which are provided with additional sturdiness by the interconnecting ribs **36**. The foregoing structure allows for a cleaner, faster, and more stable injection moulding process. Thus, a higher number of containers can be produced at a higher rate. structure injection molding process in order to make the present container **10**.

(27) Moreover, the air channel **32** provided by the spaced apart walls **28** and **30** improves the freshness and shelf life of herbs contained within the storage chamber **40**. Indeed, the air channel **32** protects the contents inside the container **10** from external environment factors. Although several external factors can affect the freshness of the contents in the container **10** and thereby the maximum lifespan of these contents, water vapour is usually the main source that can affect the life and freshness of the herbs. Water vapour infiltration is usually caused by airborne moisture and diffusion. Indeed, air passing through each small hole or crack within the wall of a container contains moisture (i.e. water vapour) that seeps into the container and cannot escape coming into contact with the herbs.

(28) Diffusion is caused by a difference in moisture on either side of the container (external or internal); water vapour simply passes through the container wall. Some materials may have more airtight properties than others, but no material is 100% water-vapour tight.

(29) The air channel **32** defined by the spaced apart walls **28** and **30** having an opening **34** at one end and being closed at the junction **20** limits airborne moisture from entering the storage chamber and diffusion between the storage cavity **26** and the air channel **32** or the ambient environment. The present structure adds a layer of air to the container **10**. Indeed, the air channel **32** is usually partially (but not hermetically) sealed when the container is on a surface and the opening **34** is closed. This added layer acts as an insulator between the inner and outer walls **28** and **30** thus reducing the water vapor transmission ratio and lengthening the life cycle of the herbs which increases the freshness time period.

(30) Turning now to FIGS. **9**, **10** and **11**, the container **10** is enclosed via an enclosure cover **62** such as a cap. The cover **62** defines inner and outer sides, **64** and **66**, respectively and includes inner threads **67** which are complementary to external threads **27** of the spout **14** for releasable mutual interference engagement therewith.

(31) The containers for perishable goods herein can be provided in a variety of different sizes, configurations and dimensions as can be contemplated by the skilled artisan. For example, FIGS. **12**, **13** and **14** show container **10A**, **10B** and **10C** having different heights and widths. Moreover, container **10B** and **10C** are shown with respective storage chambers, **40B** and **40C**, with respective acutely tapered and subtly tapered shapes in the direction of their respective bottom surfaces **46B** and **46C**. The configuration of chamber **40B** provides an air channel **32B** is a relatively wider openings **34B** and the configuration of chamber **40C** provides for an air channel **32C** with a relatively narrower opening **34C**. In an embodiment, the air channels **32B** and **32C** become narrower in the direction leading to junction **20** (as discussed for container **10** and as shown in FIGS. **4** and **5**). Of course, the air channels may have the same width along their length about the storage chamber.

(32) FIG. **15** shows a container **70** for a rolled smokable cylinder of burnable material such as a cigarette with tobacco and/or cannabis also colloquially referred to as a joint, a spliff etc.

(33) The container **70** is a narrow longitudinal cylinder body **72** having a closed end **74** and open opposite end **76** defining an opening **78** (see FIG. **16**) closable by a closure cover **80**. The opening **78** leads to a tubular chamber **82** for receiving therein the closed smokable cylinder **84** of burnable material. The cylinder body **72** is tapered from its open end **76** to its closed end **74**, this the open end **76** is larger than the closed end **74**.

(34) FIG. **16** shows a container assembly **86** for smokable cylinders such as cigarettes, joints etc. The container **86** comprises a pair of containers **70'** and **70''**, joined together along their respective cylinder bodies **72'** and **72''** by way of a connector **88** therebetween. It is to be understood, that

containers **70'** and **70''** are substantially similar to container **70** and thus the description of container **70** applies to containers **70'** and **70''** mutatis mutandis and is not repeated here for concision purposes only. The end containers **70'** and **70''** are oppositely positioned with respect to each other such that the closed end **74'** of container **70'** is adjacent the open end **76''** of container **70''** and the closed end of **76'** of container **70'** is adjacent the open end **74''** of container **70''**. The containers **70'** and **70''** are offset relative to each other along their longitudinal length such that the closed end **74'** of container **70'** is recessed relative the open end **76''** of container **70''** adjacent thereto which extends beyond the position of the closed end **74'**. Similarly, the closed end **74''** of container **70''** is recessed relative to the open end **76'** of container **70'** adjacent thereto which extends beyond the position of the closed end **74''**. This foregoing offset and alternating end arrangement between a pair of containers **70'** and **70''** is shown to be a repeated pattern in the container assembly **96** of FIG. **17** which will be discussed further below. Indeed, the arrangement between containers **70'** and **70''** along with the space between the containers **70'** and **70''** provided by the connector **88** therebetween allows for clearance space **S** for a closure cover **80** to be fitted onto the open ends **76'** or **76''**. As shown, the spout **90** of the open end **76''** includes threads **92** for a mutual interference fit with the complementary inner threads **94** of the cover **80**.

(35) Providing separate chambers **82'** and **82''** sealed from each other allow to maintain greater freshness of the material therein. Moreover, a partially smoked cigarette can be re-inserted in its chamber to be smoked later without contacting other cigarettes.

(36) As shown in FIG. **17**, a container assembly **96** includes a plurality of containers **70A**, **70B**, **70C**, **70D**, **70E** all of which are similar to constructed to container **70** and define respective separate chambers **82A**, **82B**, **82C**, **82D**, **82E**. Each pair of adjacent pair of containers: **70A** and **70B**; **70B** and **70C**; **70C** and **70D**; and **70D** and **70E** are respectively interconnected by connectors: **88i**; **881i**; **88iii**; and **881v**, interposed between each of the container pairs. Each of the container pairs are arranged in the same alternating side by side and offset position, with each open end being adjacent a closed end of the adjacent container and vice versa and with each containers of an adjacent pair being offset so as to provide the clearance space **S**.

(37) In an embodiment, the connectors **88**, **88i**, **88ii**, **88iii**, and **88iv** are solid bodies integrated to the containers they join together. In another embodiment, the connectors comprise air channels. In yet another embodiment, these connectors are malleable or flexible to allow the user to bend the area defined by a connector. In another embodiment, the connectors are separate body portions for selectively and releasably interconnecting a pair of containers together.

(38) The various features described herein can be combined in a variety of ways within the context of the present disclosure so as to provide still other embodiments. As such, the embodiments are not mutually exclusive. Moreover, the embodiments discussed herein need not include all of the features and elements illustrated and/or described and thus partial combinations of features can also be contemplated. Furthermore, embodiments with less features than those described can also be contemplated. It is to be understood that the present disclosure is not limited in its application to the details of construction and parts illustrated in the accompanying drawings and described hereinabove. The disclosure is capable of other embodiments and of being practiced in various ways. It is also to be understood that the phraseology or terminology used herein is for the purpose of description and not limitation. Hence, although the present disclosure has been provided hereinabove by way of non-restrictive illustrative embodiments thereof, it can be modified, without departing from the scope, spirit and nature thereof and of the appended claims.

Claims

1. A container for storing perishable contents comprising: an inner storage chamber for receiving the perishable contents therein, the inner storage chamber defining top and bottom ends and comprising a floor at the bottom end thereof, an inner wall extending from the floor towards an

opening at the top end thereof, the floor and the inner wall defining a storage cavity therebetween; an outer wall covering the inner wall and downwardly extending from a junction therewith at the top end of the storage chamber towards a bottom edge thereof at the bottom end of the storage chamber, the outer wall and the inner wall being spaced apart so as to define an air channel therebetween for receiving air, the bottom edge of the outer wall and the floor of the storage chamber being horizontally aligned and defining an opening therebetween leading to the air channel; and a plurality of equally spaced apart wing-like interconnectors vertically extending between the outer wall and inner wall and along a full length of the outer and inner walls defining opposite flat faces and comprising an upper part thereof connected to the inner wall and a lower part thereof that is not connected to the inner wall, the lower part being longer than the upper part, the lower part extending from the upper part and defining a free vertical edge thereof interfacing with the inner wall and progressively and diagonally receding away from the inner wall towards a free bottom edge thereof at the bottom edge of the outer wall, the inner and outer walls comprising relatively thin and flexible material, the interconnectors providing additional sturdiness to the inner and outer walls, the upper part being fully connected to the inner wall providing greater sturdiness between the outer and inner walls than the lower part, wherein the air channel is defined by empty sections between the interconnectors and a contiguous pathway beneath the upper parts thereby providing for allowing a layer of air between the outer wall and inner wall to act as insulation for the perishable contents, wherein insulation is further provided by heat on the outer wall being absorbed by the lower parts of the interconnectors which are not connected to the inner wall thereby avoiding direct heat transfer thereto.

2. A container according to claim 1, further comprising a spout at the top end of storage defining the opening leading to the storage cavity.
 3. A container according to claim 2, wherein the opening is releasably sealable by a closure cover.
 4. A container according to claim 1 wherein the air channel size expands along the length of the inner storage chamber from a position near or at the junction to a position near or at the bottom edge thereof at or near the bottom end of the storage chamber.
 5. A container according to claim 1, wherein the air channel size is similar along the length of the inner storage chamber from a position at the junction to a position at the bottom edge thereof at the bottom end of the storage chamber.
-