

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410575
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lipscomb; Chad

Erosion control securing apparatus and method

Abstract

An erosion control securing apparatus and method is disclosed. For example, an erosion control securing device is provided that includes a main shaft with a hexagonal-shaped head portion at its proximal end and a coil portion at its distal end. In one example, the coil portion of the erosion control securing device includes three turns. Further, a method of using the presently disclosed erosion control securing device for securing erosion control products is provided.

Inventors:	Lipscomb; Chad (Evansville, IN)
Applicant:	WESTERN GREEN, LLC (Evansville, IN)
Family ID:	78722831
Assignee:	Western Green, LLC (Evansville, IN)
Appl. No.:	17/767320
Filed (or PCT Filed):	May 28, 2021
PCT No.:	PCT/US2021/034727
PCT Pub. No.:	WO2021/243131
PCT Pub. Date:	December 02, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220372723 A1	Nov. 24, 2022

Related U.S. Application Data

us-provisional-application US 63031768 20200529

Publication Classification

Int. Cl.: E02D17/20 (20060101); E02D5/80 (20060101)

U.S. Cl.:

CPC E02D5/801 (20130101); E02D17/202 (20130101); E02D2200/1671 (20130101); E02D2600/30 (20130101)

Field of Classification Search

CPC: E02D (5/801); E02D (17/202); E02D (2200/1671); E02D (5/80); A01G (13/0293)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2603319	12/1951	Dyche	52/157	E21B 10/44
4543972	12/1984	Bennett et al.	N/A	N/A
6715384	12/2003	Kozak	N/A	N/A
7044031	12/2005	Mullen	N/A	N/A
2004/0148877	12/2003	Roberts	52/155	E02D 5/80
2012/0217709	12/2011	Christofius et al.	N/A	N/A
2017/0218593	12/2016	Butterworth et al.	N/A	N/A
2021/0048055	12/2020	Brown	N/A	E02D 5/801
2022/0098815	12/2021	Zhou	N/A	E04B 1/34347

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102011014880	12/2011	DE	N/A
2016020631	12/2015	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion issued in counterpart PCT Application No. PCT/US2021/034727 dated Aug. 25, 2021 (fourteen (14) pages). cited by applicant

Primary Examiner: Andrish; Sean D

Attorney, Agent or Firm: Maynard Nexsen PC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The presently disclosed subject matter is a 35 U.S.C. § 371 U.S. national phase entry of International Application No. PCT/US2021/034727 having an international filing date of May 28, 2021, which is related to and claims priority to U.S. Provisional Patent Application No. 63/031,768 entitled “Erosion Control Securing Apparatus and Method” filed on May 29, 2020; the entire disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The presently disclosed subject matter relates generally to the installation and performance of erosion control products and more particularly to an erosion control securing apparatus and method.

BACKGROUND

(2) Erosion control is important to the environment and its inhabitants. Not only does severe erosion threaten plant and animal life, economic concerns are triggered when commercial and infrastructure facilities are disrupted or harmed.

(3) On land areas that are susceptible to erosion, therefore, it may be necessary to provide some kind of erosion control system. In one example, erosion control matting or blankets may be laid out over the land area. One issue is keeping this material in place in areas having slopes and channels. The erosion control matting or blankets may be secured in place by the use of securing devices, such as pins, pegs, or staples. However, a drawback of such devices is that they can be easily removed, may not be reliable and/or may not be able to be easily installed, which can lead to failure of the erosion control system.

(4) Accordingly, there remains a need for improved erosion protection that is reliable and convenient.

SUMMARY

(5) The following presents a simplified summary of the invention in order to provide a basic understanding of some aspects of the invention. This summary is not an extensive overview of the invention. It is not intended to identify key or critical elements of the invention or to delineate the scope of the invention; its sole purpose is to present concepts of the invention in a simplified form as a prelude to the more detailed description that is subsequently presented.

(6) In some embodiments, the presently disclosed subject matter may provide an erosion control securing apparatus and method. For example, an erosion control securing device may be provided that includes a main shaft with a hexagonal-shaped head portion at its proximal end and a coil portion at its distal end. In one example, the coil portion of the erosion control securing device may include three turns. Further, a main feature of the presently disclosed erosion control securing device may be that the hexagonal-shaped head portion is sized and shaped to engage with a standard hexagonal shaped drive tool, such as a standard hex socket that may be driven by a drill and/or socket wrench.

(7) In some embodiments, the presently disclosed erosion control securing apparatus and method provide a coil portion that may include three turns and wherein the beginning of the coil portion (i.e., beginning of the first turn) may have a starting radius, then the radius of the coil portion may symmetrically increase to a maximum radius at the second turn, and then the radius may symmetrically decrease back to the starting radius at the ending of the coil portion (i.e., ending of the third turn).

(8) In some embodiments, the presently disclosed erosion control securing apparatus may include a main shaft having a main shaft proximal end and a main shaft distal end; a head portion at the main shaft proximal end, the head portion being substantially hexagonal in shape; and a coil portion at the main shaft distal end.

(9) In one example, the erosion control securing apparatus may include a coil portion having three turns, with the first of the three turns having a first radius, the second of the three turns having a radius larger than the first radius, and the third of the three turns having a radius about the same as the first radius.

(10) In one example, the main shaft, the head portion, and the coil portion of the erosion control securing apparatus may be connected in a substantially continuous matter. Further, the main shaft, the head portion, and the coil portion may be substantially tubular or rod-like.

(11) In one example, a head transition segment may be between the head portion and the main shaft

proximal end, and the main shaft may be arranged substantially normal to the plane of the head portion.

(12) In one example, a coil transition segment may be between the main shaft distal end and the proximal end of the coil portion, a tip may be at the distal end of the coil portion, and a tip transition segment may be between the distal end of the coil portion and the proximal end of the tip.

(13) In one example, the head portion may be formed by adjoining segments, the adjoining segments may include a terminal end segment next to four central segments next to a head transition segment, the head transition segment may be connected to the main shaft, wherein the head transition segment may be spaced apart from the terminal end segment.

(14) In one example, the head transition segment may include three adjoining segments, the first of the three adjoining segments may be connected to one of the four central segments, the second of the three adjoining segments may be about the same length as the first of the three adjoining segments, and the last of the three adjoining segments may be connected to the main shaft.

(15) In some embodiments, the presently disclosed erosion control securing system and kit may include an erosion control securing kit may include a securing device having a main shaft having a main shaft proximal end and a main shaft distal end; a head portion at the main shaft proximal end, the head portion being substantially hexagonal in shape; and a coil portion at the main shaft distal end; and a rotational drive mechanism for installing the securing device.

(16) In one example, the rotational drive mechanism may include a socket with a body having a recess on one side, and the recess may be substantially hexagonal in shape and dimensioned to receive the head portion. In one example, the body has a socket wrench receiver on the side opposing the one side

(17) In one example, the substantially hexagonal recess may include a central recess that is substantially circular. In one example, an arrangement of engaging features may be provided within the substantially hexagonal recess and surrounding the central recess. In one example, a magnet may be provided within the central recess.

(18) In some embodiments, the presently disclosed method for using an erosion control securing system may include the steps of: providing a securing device comprising: a main shaft having a main shaft proximal end and a main shaft distal end; a head portion at the main shaft proximal end, the head portion being substantially hexagonal in shape; and a coil portion at the main shaft distal end; providing a matting material; laying out the matting material over an area; and installing the securing device into the matting material to secure the matting material to the area, wherein the head portion is on one side of the matting material and the main shaft and coil portion are on the opposing side of the matting material.

(19) Other features will be readily apparent to those skilled in the arts, techniques and equipment relevant to the present invention from a review of the Drawings and Detailed Description.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) Having thus described the presently disclosed subject matter in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

(2) FIG. 1 illustrates a perspective view of an example of the presently disclosed erosion control securing device;

(3) FIGS. 2A-2C illustrate a side view (FIG. 2A) and top views (FIGS. 2B and 2C) of the erosion control securing device shown in FIG. 1;

(4) FIG. 3 illustrates a side view of the erosion control securing device shown in FIG. 1;

- (5) FIGS. 4A and 4B illustrate top views of the erosion control securing device shown in FIG. 1 with various measures in accordance with various embodiments;
- (6) FIGS. 5A and 5B illustrate additional top views of the erosion control securing device shown in FIG. 1 with various measures in accordance with various embodiments;
- (7) FIG. 6 illustrates a perspective view of an example of the erosion control securing device shown in FIG. 1 though FIG. 5B installed in erosion control matting;
- (8) FIG. 7 illustrates a flow diagram of an example of a method of using the presently disclosed erosion control securing device for securing erosion control products; and
- (9) FIG. 8A and FIG. 8B show an example of a hex-shaped head portion and a rectangular-shaped head portion, respectively, of the erosion control securing device in relation to the hexagonal shape of a hex socket drive mechanism;
- (10) FIG. 9A and FIG. 9B show perspective views of an example of a drive mechanism that may be used for installing the erosion control securing device shown in FIG. 1;
- (11) FIG. 10, FIG. 11, and FIG. 12 show perspective views of another example of a drive mechanism that may be used for installing the erosion control securing device shown in FIG. 1;
- (12) FIG. 13 shows a plan view of the drive mechanism shown in FIG. 10, FIG. 11, and FIG. 12 in relation to the hex-shaped head portion of the erosion control securing device shown in FIG. 1; and
- (13) FIG. 14, FIG. 15, and FIG. 16 show a top view, a bottom view, and a side view, respectively, of the drive mechanism shown in FIG. 10, FIG. 11, and FIG. 12 and showing more details thereof.

DETAILED DESCRIPTION

- (14) The presently disclosed subject matter now will be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all embodiments of the presently disclosed subject matter are shown. Like numbers refer to like elements throughout. The presently disclosed subject matter may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Indeed, many modifications and other embodiments of the presently disclosed subject matter set forth herein will come to mind to one skilled in the art to which the presently disclosed subject matter pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the presently disclosed subject matter is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the present subject matter.
- (15) In some embodiments, the presently disclosed subject matter provides an erosion control securing apparatus and method. For example, an erosion control securing device is provided that includes a main shaft with a hexagonal-shaped head portion at its proximal end and a coil portion at its distal end. In one example, the coil portion of the erosion control securing device includes three turns. Further, a main feature of the presently disclosed erosion control securing device is that the hexagonal-shaped head portion may be sized and shaped to engage with a standard hexagonal shaped drive tool, such as a standard hex socket that may be driven by a drill and/or socket wrench.
- (16) In some embodiments, the presently disclosed erosion control securing apparatus and method provide a coil portion that includes three turns and wherein the beginning of the coil portion (i.e., beginning of the first turn) has a starting radius, then the radius of the coil portion symmetrically increases to a maximum radius at the second turn, and then the radius symmetrically decreases back to the starting radius at the ending of the coil portion (i.e., ending of the third turn).
- (17) In some embodiments, the presently disclosed erosion control securing apparatus and method provide a head portion of any shape that may be engaged with a standard hexagonal shaped drive tool, such as a standard hex socket. For example, the head portion may be hexagonal-shaped, rectangular-shaped, or bowtie-shaped as long as it is sized to engage in driving fashion to a standard hexagonal shaped drive tool, such as a standard hex socket.
- (18) In some embodiments, the presently disclosed erosion control securing apparatus and method

provide a custom drive mechanism, such as a custom hex socket that may be designed to receive the hexagonal-shaped head portion of the erosion control securing device and that may include a magnet for holding the hexagonal-shaped head portion of the erosion control securing device within the drive mechanism by magnet forces.

(19) Referring now to FIG. 1 is a perspective view of an example of the presently disclosed erosion control securing device **100**. Erosion control securing device **100** may include a main shaft **110**. A head portion **112** is provided on the proximal end of a main shaft **110**. Head portion **112** is substantially hexagonal in shape (see FIG. 8) and is hereafter called HEX head portion **112**. HEX head portion **112** has a head transition segment **114** for transitioning to main shaft **110**. Main shaft **110** is arranged substantially normal to the plane of HEX head portion **112**. A coil portion **116** is provided at the distal end of a main shaft **110**. A coil transition segment **120** is provided between the distal end of main shaft **110** and the proximal end of coil portion **116**. Further, a tip **122** is provided at the distal end of coil portion **116**. A tip transition segment **121** may be provided between the distal end of the coil portion **116** and the proximal end of the tip **122**.

(20) In one example, shown in FIG. 2A-2C, coil portion **116** may include three turns **118**, starting with a beginning sized turn **118a**, then transitioning to a larger sized turn **118b**, then transitioning back to a beginning sized turn **118c**. Additionally, FIG. 2A-2C shows a side view, a top view, and a simplified top view of erosion control securing device **100** shown in FIG. 1. In FIG. 2C, coil portion **116** is omitted.

(21) The members forming erosion control securing device **100** connect one to another in a substantially continuous manner. Further, the members forming erosion control securing device **100** may be substantially tubular or rod-like members having a radius, for example, of about 0.156 inches. Erosion control securing device **100** may be formed of any rigid, strong, and durable material that is able to withstand installation in the soil for an extended period of time. Erosion control securing device **100** may be formed, for example, of metal; galvanized metal; plastic; and biodegradable materials.

(22) Referring now to FIGS. 3, 4A-4B, and 5A-5B are various views of erosion control securing device **100** shown in FIG. 1 and showing more details thereof. Namely, FIGS. 3, 4A-4B, and 5A-5B show example dimensions and/or angles of erosion control securing device **100**. In FIGS. 3, 4A-4B, and 5A-5B all dimensions are in inches. Again, in one example shown in FIG. 3, coil portion **116** may include three turns **118** with a starting radius at turn **118a** of about 0.156 inches, then symmetrically increasing to a radius at turn **118b** of about 0.625 inches, then symmetrically decreasing back to a radius at turn **118c** of about 0.156 inches. Coil transition segment **120** may be, for example, about 0.16 inches long to provide a transition length from the center of main shaft **110** and the center of coil portion **116**. Tip transition segment **121** may also be, for example, about 0.16 inches long to provide a transition length from the center of coil portion **116** to the center of tip **122**. Tip **122** may be about 0.44 inches long.

(23) In one example, the dimensions of HEX head portion **112** are shown in FIGS. 4A-4B and 5A-5B. The HEX head portion **112** includes adjoining segments that are arranged to form a hexagonal shape with internal angles of about 120° between one segment and the adjacent segment. A terminal end segment of the HEX head portion **112** may be about 0.33 inches long. Adjacent to the end segment are four central segments that are each approximately the same length of about 0.85 inches at the outer periphery of the segment and about 0.67 inches at the inner periphery of the segment. The length of the widest part of the HEX head portion, or the length between the opposing tips of three adjoining central segments is about 1.70 inches. The length between opposing tips of two adjoining central segments is about 1.47 inches. Head transition segment **114** between the central segments and the main shaft **110** may include approximately three adjoining segments, shorter than the central segments, that include internal angles of about 120°. The first two of the head transition segments are adjacent to a central segment, and are each approximately 0.52 inches in length. The last of the three head transition segments adjacent to the main shaft **110**

is approximately 0.43 inches. The HEX head portion **112** in this example does not form a closed hexagonal shape, and includes an opening between the terminal end segment and the head transitional segment **114**. That opening is about 0.13 inches in length.

(24) The overall dimensions of erosion control securing device **100** may vary. For example, the 4.25-inch length of main shaft **110** and/or the 3-inch length of coil portion **116** may vary.

Accordingly, the overall 8.156-inch length of erosion control securing device **100** may vary. A main feature of erosion control securing device **100** is that HEX head portion **112** is sized and shaped to engage with a standard hexagonal shaped drive tool, such as a “HEX socket” (see FIG. 9A through FIG. 16).

(25) However, the configuration of erosion control securing device **100** shown in FIGS. 3, 4A-4B, and 5A-5B is exemplary only. For example, the overall length of erosion control securing device **100** may range from about 6 inches to about 12 inches. Further, coil portion **116** of erosion control securing device **100** may include from about one to about three turns **118**. Further, the radius of turns **118** may range from about 0.125 inches to about 1.25 inches.

(26) Referring now to FIG. 6 is a perspective view of an example of an erosion control securing system including an erosion control securing device **100** shown in FIG. 1 though FIG. 5B installed in an erosion control matting **200** such as by an erosion control drive mechanism (see FIG. 10).

(27) Referring now to FIG. 7 is a flow diagram of an example of a method **300** of using the presently disclosed erosion control securing device **100** for securing erosion control products. Method **300** may include, but is not limited to, the following steps.

(28) At a step **310**, certain erosion control products along with a plurality of the presently disclosed erosion control securing devices are provided. For example, one or more erosion control mattings **200** (see FIG. 6) and a plurality of erosion control securing devices **100** as shown in FIG. 1 though FIG. 5B are provided at an installation job site.

(29) At a step **315**, one or more erosion control products are laid out at an installation job site. For example, one or more erosion control mattings **200** (see FIG. 6) are laid out at the installation job site.

(30) At a step **320**, a plurality of the presently disclosed erosion control securing devices are installed into the erosion control products. For example, a plurality of erosion control securing devices **100** as shown in FIG. 1 though FIG. 5B are installed into one or more erosion control mattings **200**, as shown in FIG. 6.

(31) Referring now to FIG. 8A and FIG. 8B is an example of a hex-shaped head portion **112** and a rectangular-shaped head portion **112**, respectively, of the erosion control securing device **100** in relation to the hexagonal shape of a hex socket drive mechanism. For example, FIG. 8A shows an example of another variation of the hex-shaped head portion **112** of erosion control securing device **100** in relation of a hexagonal shape **350**. Hexagonal shape **350** may be representative of the shape of a standard hex socket that may be used to drive erosion control securing device **100**.

(32) Further, head portion **112** of drive erosion control securing device **100** is not limited to hexagonal shape only and still be driven by a standard hex socket. For example, FIG. 8B shows an example of a rectangular-shaped head portion **112** in relation of hexagonal shape **350**. In this example, the rectangular-shaped head portion **112** may be sized for fitting into and engaging in driving fashion with a hex socket drive mechanism, such as those described hereinbelow with reference to FIG. 9A through FIG. 16. In another example, head portion **112** may have a “bowtie” shape (not shown) that may be sized for fitting into a hex socket drive mechanism.

(33) Referring now to FIG. 9A and FIG. 9B that are perspective views of an example of a drive mechanism that may be used for installing erosion control securing device **100** shown in FIG. 1. In one example the drive mechanism can be incorporated into an erosion control securing kit. In this example, the drive mechanism may be a HEX socket **400**. HEX socket **400** may be used to rotationally drive erosion control securing device **100**. In one example, HEX socket **400** may be a standard 1.5-inch HEX socket that can be installed in the chuck of a hand tool or of a power tool,

such as a standard drill. Once engaged, HEX socket **400** may be driven manually by hand or with the power tool to install erosion control securing device **100**.

(34) Referring now to FIG. **10**, FIG. **11**, and FIG. **12** is perspective views of another example of a drive mechanism that may be used for installing erosion control securing device **100** shown in FIG. **1**. In this example, the drive mechanism may be a HEX socket **500**. In one example, HEX socket **500** may be a custom ½-inch drive or ⅜-inch drive socket that may be used with a standard ½-inch drive or ⅜-inch drive socket wrench. In this example, HEX socket **500** may be designed to receive the hex-shaped head portion **112** of erosion control securing device **100**.

(35) HEX socket **500** may include, for example, a body **510** that has a hex-shaped recess **512** in one, top side (see FIG. **10**) and a socket wrench receiver **520** on the opposite, bottom side (see FIG. **11**). Another substantially circular recess **514** is provided at about the center portion of hex-shaped recess **512**. Further, an arrangement (e.g., six) of engaging features **516** are provided within hex-shaped recess **512** and around circular recess **514**. Hex-shaped recess **512** with engaging features **516** may be designed to receive hex-shaped head portion **112** of erosion control securing device **100**. Further, a magnet **518** may be installed in circular recess **514** of hex-shaped recess **512** (see FIG. **12**).

(36) Referring now to FIG. **13** is a plan view of HEX socket **500** shown in FIG. **10**, FIG. **11**, and FIG. **12** in relation to hex-shaped head portion **112** of erosion control securing device **100** shown in FIG. **1**. In addition to being engaged and secured within the six sides of the hex-shaped recess **512** and the engaging features **516**, the center portion of hex-shaped head portion **112** may be held within HEX socket **500** by the magnetic forces of magnet **518**. The arrangement of HEX socket **500** allows gripping of the outer portion of hex-shaped head portion **112** during driving, which is more stable and allows for more torque transfer than prior art driving device and anchoring systems. The engaging features **516** of the socket are not used to drive the securing device **100**, rather, they serve to reduce wobble in installation, minimizing the rotation of the securing device **100** in the socket **500**, a further improvement on the prior art.

(37) Further, FIG. **14**, FIG. **15**, and FIG. **16** show a top view, a bottom view, and a side view, respectively, of HEX socket **500** shown in FIG. **10**, FIG. **11**, and FIG. **12** and showing more details thereof. For example, FIG. **14**, FIG. **15**, and FIG. **16** show example dimensions (in inches) of HEX socket **500**. In one example, the radius of the center portion of HEX socket **500** may be about 0.80 inches. The distance between each engaging feature **516** may be about 0.25 inches. Each engaging feature may be angled, and approximately pentagonal in shape, with four substantially flat sides, and one curved side that is adjacent to the central portion. The two outer most, flat sides in relation to the curved side may each be about 0.18 inches in length. The length of two adjoining sides of the hex-shaped recess **512** may be about 1.50 inches. The outer walls of the top side of the body **510** may include an arrangement of grooves. Each groove may have a depth of about 0.04 inches. The overall length of the body **510** may be about 1.10 inches, the overall width of the top side of the body is about 2.00 inches, and the overall width of the bottom side of the body **510** is about 0.89 inches. The length and width of the socket wrench receiver **520** are about 0.51 inches, respectively. However, the configuration and dimensions of HEX socket **500** shown in FIGS. **10-16** are exemplary only.

(38) Referring now again to FIG. **1** through FIG. **16**, the presently disclosed erosion control securing device **100** and method **300** is not limited to use with erosion control products. This is exemplary only. The presently disclosed erosion control securing device **100** and method **300** may be used in any application for securing an item into the ground. For example, erosion control securing device **100** may be used as a tent stake; canopy stake; hunting blind stake; any stake to which a rope, cord, or strap may be tied; and the like.

(39) Following long-standing patent law convention, the terms “a,” “an,” and “the” refer to “one or more” when used in this application, including the claims. Thus, for example, reference to “a subject” includes a plurality of subjects, unless the context clearly is to the contrary (e.g., a

plurality of subjects), and so forth.

(40) Throughout this specification and the claims, the terms “comprise,” “comprises,” and “comprising” are used in a non-exclusive sense, except where the context requires otherwise. Likewise, the term “include” and its grammatical variants are intended to be non-limiting, such that recitation of items in a list is not to the exclusion of other like items that can be substituted or added to the listed items.

(41) For the purposes of this specification and appended claims, unless otherwise indicated, all numbers expressing amounts, sizes, dimensions, proportions, shapes, formulations, parameters, percentages, quantities, characteristics, and other numerical values used in the specification and claims, are to be understood as being modified in all instances by the term “about” even though the term “about” may not expressly appear with the value, amount or range. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the following specification and attached claims are not and need not be exact, but may be approximate and/or larger or smaller as desired, reflecting tolerances, conversion factors, rounding off, measurement error and the like, and other factors known to those of skill in the art depending on the desired properties sought to be obtained by the presently disclosed subject matter. For example, the term “about,” when referring to a value can be meant to encompass variations of, in some embodiments $\pm 100\%$, in some embodiments $\pm 50\%$, in some embodiments $\pm 20\%$, in some embodiments $\pm 10\%$, in some embodiments $\pm 5\%$, in some embodiments $\pm 1\%$, in some embodiments $\pm 0.5\%$, and in some embodiments $\pm 0.1\%$ from the specified amount, as such variations are appropriate to perform the disclosed methods or employ the disclosed compositions.

(42) Further, the term “about” when used in connection with one or more numbers or numerical ranges, should be understood to refer to all such numbers, including all numbers in a range and modifies that range by extending the boundaries above and below the numerical values set forth. The recitation of numerical ranges by endpoints includes all numbers, e.g., whole integers, including fractions thereof, subsumed within that range (for example, the recitation of 1 to 5 includes 1, 2, 3, 4, and 5, as well as fractions thereof, e.g., 1.5, 2.25, 3.75, 4.1, and the like) and any range within that range.

(43) Although the foregoing subject matter has been described in some detail by way of illustration and example for purposes of clarity of understanding, it will be understood by those skilled in the art that certain changes and modifications can be practiced within the scope of the present subject matter.

Claims

1. An erosion control securing system kit, comprising: an erosion control securing device comprising: a main shaft having a main shaft proximal end and a main shaft distal end; a head portion at the main shaft proximal end, the head portion being substantially hexagonal in shape; and a coil portion at the main shaft distal end; and a rotational drive mechanism for installing the securing device, wherein the rotational drive mechanism comprises: a socket with a body having a recess on one side, the recess being substantially hexagonal in shape and dimensioned to receive the head portion, wherein the substantially hexagonal recess includes a central recess that is substantially circular; a magnet within the central recess; and an arrangement of engaging features within the substantially hexagonal recess and surrounding the central recess, wherein the arrangement of engaging features each extend from the central recess to the head portion in an instance in which the head portion is received by the recess.
2. The securing system kit of claim 1, wherein the body has a socket wrench receiver on a side opposing the one side.
3. The securing system kit of claim 1, wherein the coil portion has three turns, with a first turn of the three turns having a first radius, a second turn of the three turns having a radius larger than the

first radius, and a third turn of the three turns having a radius the same as the first radius.

4. The securing system kit of claim 3, wherein the first radius is about 0.156 inches and the second radius is about 0.675 inches.

5. The securing system kit of claim 4, wherein the three turns each has a radius ranging from about 0.125 inches to about 1.25 inches.

6. The securing system kit of claim 1, wherein the main shaft, the head portion, and the coil portion are connected in a substantially continuous matter.

7. The securing system kit of claim 6, wherein the main shaft, the head portion, and the coil portion are substantially tubular with a radius of about 0.156 inches.

8. The securing system kit of claim 1, further comprising a head transition segment between the head portion and the main shaft proximal end, wherein the main shaft is arranged substantially normal to a plane of the head portion.

9. The securing system kit of claim 8, further comprising a coil transition segment between the main shaft distal end and the proximal end of the coil portion, a tip at the distal end of the coil portion, and a tip transition segment between the distal end of the coil portion and the proximal end of the tip.

10. The securing system kit of claim 9, wherein the tip is about 0.44 inches long, wherein the coil transition segment is about 0.16 inches long, and wherein the tip transition segment is about 0.16 inches long.

11. The securing system kit of claim 9, wherein an overall length of the securing device is about 8.156 inches, wherein the main shaft is about 4.25 inches long, and wherein the coil portion is about 3.00 inches long, and wherein a width of the head portion is about 1.47 inches.

12. The securing system kit of claim 9, wherein the head portion is formed by adjoining segments, the adjoining segments including a terminal end segment next to four central segments next to a head transition segment, the head transition segment connected to the main shaft, wherein the head transition segment is spaced apart from the terminal end segment.

13. The securing system kit of claim 12, wherein the terminal end segment is about 0.33 inches long, and wherein the four central segments are each about 0.85 inches long.

14. The securing system kit of claim 12, wherein the head transition segment includes three adjoining segments, a first segment of the three adjoining segments being connected to one of the four central segments, a second segment of the three adjoining segments, wherein a length of the second segment being about the same length as a length of the first segment of the three adjoining segments, and a third segment of the three adjoining segments being connected to the main shaft.

15. A method for using an erosional control securing system, comprising: providing an erosion control securing device comprising: a main shaft having a main shaft proximal end and a main shaft distal end; a head portion at the main shaft proximal end, the head portion being substantially hexagonal in shape; and a coil portion at the main shaft distal end; providing a matting material; laying out the matting material over an area; installing the securing device into the matting material to secure the matting material to the area, wherein the head portion is on one side of the matting material and the main shaft and coil portion are on an opposing side of the matting material, wherein the securing device is installed into the matting material by a rotational drive mechanism for installing the securing device, wherein the rotational drive mechanism comprises: a socket with a body having a recess on one side, the recess being substantially hexagonal in shape and dimensioned to receive the head portion, wherein the substantially hexagonal recess includes a central recess that is substantially circular; a magnet within the central recess; and an arrangement of engaging features within the substantially hexagonal recess and surrounding the central recess, wherein the arrangement of engaging features each extend from the central recess to the head portion in an instance in which the head portion is received by the recess.

16. The method of claim 15, wherein the body has a socket wrench receiver on a side opposing the one side.

17. The method of claim 15, wherein the coil portion has three turns, with a first turn of the three turns having a first radius, a second turn of the three turns having a radius larger than the first radius, and a third turn of the three turns having a radius the same as the first radius.
