

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410849
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	McGrew, Jr.; Arthur L. et al.

Output gearing for a dual motor mixed-speed continuous power transmission

Abstract

An electric powertrain includes a first electric motor that has an uninterrupted connection with a drive shaft of a vehicle. The electric powertrain further includes a second electric motor that has an interruptible connection with the drive shaft. In one form, this interruptible connection includes a clutch. The electric powertrain further includes a first gear train in the form of a first planetary gear and a second gear train in the form of a second planetary gear. The first gear train, second gear train, and clutch are arranged downstream from the first electric motor and second electric motor.

Inventors: McGrew, Jr.; Arthur L. (Indianapolis, IN), Mock; Isaac (Martinsville, IN), Pelton; George S. (Indianapolis, IN), Raszkowski; James Allen (Indianapolis, IN)

Applicant: Allison Transmission, Inc. (Indianapolis, IN)

Family ID: 78705768

Assignee: Allison Transmission, Inc. (Indianapolis, IN)

Appl. No.: 18/815104

Filed: August 26, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240418245 A1	Dec. 19, 2024

Related U.S. Application Data

continuation parent-doc WO PCT/US2021/070650 20210601 PENDING child-doc US 17815419
continuation parent-doc US 15929993 20200602 US 11421759 20220823 child-doc US 17815419
division parent-doc US 18470766 20230920 US 12085155 20240910 child-doc US 18815104
division parent-doc US 17815419 20220727 US 11796038 20231024 child-doc US 18470766

Publication Classification

Int. Cl.: F16H3/66 (20060101); F16H3/72 (20060101)

U.S. Cl.:

CPC F16H3/725 (20130101); F16H2200/2007 (20130101); F16H2200/201 (20130101); F16H2200/2064 (20130101); F16H2200/2066 (20130101); F16H2200/2082 (20130101); F16H2200/2094 (20130101)

Field of Classification Search

CPC: F16H (3/725); F16H (2200/2007); F16H (2200/201); F16H (2200/2064); F16H (2200/2066); F16H (2200/2082); F16H (2200/2094)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5931757	12/1998	Schmidt	N/A	N/A
6524215	12/2002	Schmidt	N/A	N/A
7273435	12/2006	Raghavan	475/5	F16H 3/728
7367910	12/2007	Schmidt	N/A	N/A
7686723	12/2009	Schondorf	475/5	B60L 50/61
7846051	12/2009	Holmes et al.	N/A	N/A
8135526	12/2011	Minarcin et al.	N/A	N/A
8196687	12/2011	Swales et al.	N/A	N/A
8465386	12/2012	Kersting	N/A	N/A
9566852	12/2016	Knoblauch et al.	N/A	N/A
9840140	12/2016	Holmes et al.	N/A	N/A
10144309	12/2017	Leng et al.	N/A	N/A
10465779	12/2018	Nilsson	N/A	N/A
11040607	12/2020	McGrew et al.	N/A	N/A
11173781	12/2020	Mock et al.	N/A	N/A
11193562	12/2020	McGrew, Jr. et al.	N/A	N/A
11448298	12/2021	Schlittenbauer et al.	N/A	N/A
2006/0276288	12/2005	Iwanaka et al.	N/A	N/A
2009/0084653	12/2008	Holmes	N/A	N/A
2010/0227722	12/2009	Conlon	475/5	F16H 3/728
2011/0070992	12/2010	Si	N/A	N/A
2013/0095970	12/2012	Conlon et al.	N/A	N/A
2013/0267378	12/2012	Hiraiwa	N/A	N/A
2016/0369873	12/2015	Chae	N/A	N/A
2017/0182995	12/2016	Endo et al.	N/A	N/A
2017/0182997	12/2016	Hata et al.	N/A	N/A
2019/0077255	12/2018	Misu et al.	N/A	N/A

2020/0062101	12/2019	Choi et al.	N/A	N/A
2021/0188066	12/2020	McGrew et al.	N/A	N/A
2021/0341036	12/2020	McGrew et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1936362	12/2006	CN	N/A
100591950	12/2009	CN	B60K 6/365
106347112	12/2016	CN	N/A
107244234	12/2016	CN	N/A
107428234	12/2016	CN	N/A
107914564	12/2017	CN	N/A
207510212	12/2017	CN	N/A
108528188	12/2017	CN	N/A
108603572	12/2017	CN	N/A
102006041160	12/2007	DE	N/A
102008022797	12/2007	DE	N/A
2762747	12/2013	EP	N/A
3230106	12/2017	EP	B60K 6/387
20080027638	12/2019	KR	N/A
2018224742	12/2017	WO	N/A
2019125279	12/2018	WO	N/A
2019214995	12/2018	WO	N/A
2020093301	12/2019	WO	N/A

OTHER PUBLICATIONS

PCT, Intl. App. No. PCT/US2021/070650 Written Opinion of the International Searching Authority, 6 pages, Sep. 8, 2021. cited by applicant

PCT, Intl. App. No. PCT/US2021/070650 International Search Report, 3 pages, Sep. 8, 2021. cited by applicant

GB, App. No. 2218621.7 Examination Report, 4 pages, Oct. 17, 2023. cited by applicant

Primary Examiner: Holmes; Justin

Attorney, Agent or Firm: Woodard, Emhardt, Henry, Reeves & Wagner LLP

Background/Summary

REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional of U.S. patent application Ser. No. 18/470,766, filed Sep. 20, 2023, which is hereby incorporated by reference. U.S. patent application Ser. No. 18/470,766, filed Sep. 20, 2023, is a divisional of U.S. patent application Ser. No. 17/815,419, filed Jul. 27, 2022, which are hereby incorporated by reference. U.S. patent application Ser. No. 17/815,419, filed Jul. 27, 2022, is a continuation of International Patent Application Number PCT/US2021/070650, filed Jun. 1, 2021, which are hereby incorporated by reference. U.S. patent application Ser. No. 17/815,419, filed Jul. 27, 2022, is a

BACKGROUND

(1) There has been a recent push to develop hybrid and fully electric consumer passenger vehicles. This in turn has created an explosion in the development of various electric motor designs. However, even with these enhancements, current electric motors in consumer vehicles are not generally able to produce enough torque for large commercial vehicles. To reach these torque values would require larger and heavier electric motors which would tend to increase energy consumption.

(2) Thus, there is a need for improvement in this field.

SUMMARY

(3) A powertrain system includes two or more electric motors that provide power to an output such as a driveshaft of a vehicle. One of the electric motors (“A”), which will be referred to as the “first motor” for our purposes, is always connected to the output drive shaft in order to continuously provide power for propelling the vehicle. In other words, the first electric motor (A) has an uninterrupted connection with the output. The system further includes a second electric motor (“B”) that intermittently applies torque to the output shaft. In one variation, this intermittent connection between the second electric motor (B) and the output includes at least one clutch. The clutch engages and disengages the second electric motor (B) with the output shaft.

(4) In some cases, two speed or three speed gearing arrangements and planetary gear arrangements are used. In one design option, all of the gearing and clutches are located downstream or near the output end of the system such that all of the gearing is positioned between the motors and the output of the system. Among other things, this downstream arrangement of the gearing and clutches reduces noise inside the cabin of the vehicle. Different clutch arrangements and approaches can be used for the system as well. For example, the second electric motor (B) can have its own gearing for speed reduction. Likewise, the first electric motor (A), such as when it is a high-speed electric motor, can include gearing such as a planetary gears to reduce the rotational speed of its output. In another variation, a two-clutch arrangement can be used in which an actuator actuates one clutch that is used to connect the second electric motor (B) to the motor gearing of the second motor and a selectable one-way clutch (SOWC) can be used as well.

(5) Aspect 1 generally concerns a system that includes a first electric motor connected to an output and a second electric motor connected to the output.

(6) Aspect 2 generally concerns the system of any previous aspect in which the first electric motor has an uninterrupted connection to the output and the second electric motor has an interruptible connection to the output.

(7) Aspect 3 generally concerns the system of any previous aspect in which the second electric motor is configured to supply power to the output via at least two planetary gears and a clutch.

(8) Aspect 4 generally concerns the system of any previous aspect in which the two planetary gears and the clutch are located downstream from the first electric motor and the second electric motor.

(9) Aspect 5 generally concerns the system of any previous aspect in which the second electric motor is connected to the output via a two-speed gear train arrangement.

(10) Aspect 6 generally concerns the system of any previous aspect in which the first electric motor and the second electric motor are connected to the output via a three-speed gear train arrangement.

(11) Aspect 7 generally concerns the system of any previous aspect in which the first gear train is connected to the output.

(12) Aspect 8 generally concerns the system of any previous aspect in which the first gear train includes a first planetary gear.

(13) Aspect 9 generally concerns the system of any previous aspect in which the second gear train connects the second electric motor to the output.

- (14) Aspect 10 generally concerns the system of any previous aspect in which the second gear train includes a second planetary gear.
 - (15) Aspect 11 generally concerns the system of any previous aspect in which the second gear train includes a clutch configured to shift gears in the second gear train.
 - (16) Aspect 12 generally concerns the system of any previous aspect in which the clutch includes a positive clutch.
 - (17) Aspect 13 generally concerns the system of any previous aspect in which the positive clutch includes a dog clutch.
 - (18) Aspect 14 generally concerns the system of any previous aspect in which the clutch includes a one-way clutch.
 - (19) Aspect 15 generally concerns the system of any previous aspect in which the one-way clutch includes a Selectable One-Way Clutch (SOWC).
 - (20) Aspect 16 generally concerns the system of any previous aspect in which the first gear train, the second gear train, and the clutch are all located between the second electric motor and the output.
 - (21) Aspect 17 generally concerns the system of any previous aspect in which the clutch is located between the first gear train and the second gear train.
 - (22) Aspect 18 generally concerns the system of any previous aspect in which the clutch is located between the second electric motor and the second gear train.
 - (23) Aspect 19 generally concerns the system of any previous aspect in which the third gear train connects the first electric motor to the output.
 - (24) Aspect 20 generally concerns the system of any previous aspect in which the third gear train includes a third planetary gear.
 - (25) Aspect 21 generally concerns the system of any previous aspect in which the third planetary gear includes a sun gear, an inner planet gear engaged with the sun gear, and an outer planet gear engaged to the inner planet gear.
 - (26) Aspect 22 generally concerns the system of any previous aspect in which the third gear train includes a clutch configured to shift gears in the third gear train.
 - (27) Aspect 23 generally concerns the system of any previous aspect in which the at least one of the clutch of the second gear train and the clutch of the third gear train remain engaged to always provide an uninterrupted connection to the output.
 - (28) Aspect 24 generally concerns the system of any previous aspect in which the third gear train is positioned upstream from the first electric motor.
 - (29) Aspect 25 generally concerns the system of any previous aspect in which the intermediate gear train connects the second gear train to the second electric motor.
 - (30) Aspect 26 generally concerns the system of any previous aspect in which the interruptible connection includes a clutch and a single planetary gear.
 - (31) Aspect 27 generally concerns a method of operating the system of any previous aspect.
 - (32) Further forms, objects, features, aspects, benefits, advantages, and embodiments of the present invention will become apparent from a detailed description and drawings provided herewith.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagrammatic view of a vehicle.
- (2) FIG. 2 is a diagrammatic view of another example of an electric powertrain that can be used in the vehicle of FIG. 1.
- (3) FIG. 3 is a cross-sectional view of the electric powertrain shown in FIG. 2.
- (4) FIG. 4 is a diagrammatic view of a further example of an electric powertrain that can be used in

the vehicle of FIG. 1.

(5) FIG. 5 is a diagrammatic view of still yet another example of an electric powertrain that can be used in the vehicle of FIG. 1.

(6) FIG. 6 is a diagrammatic view of another example of an electric powertrain that can be used in the vehicle of FIG. 1.

(7) FIG. 7 is a cross-sectional view of the electric powertrain shown in FIG. 6.

(8) FIG. 8 is a diagrammatic view of a further example of an electric powertrain that can be used in the vehicle of FIG. 1.

(9) FIG. 9 is a diagrammatic view of still yet another example of an electric powertrain that can be used in the vehicle of FIG. 1.

DETAILED DESCRIPTION OF SELECTED EMBODIMENTS

(10) For the purpose of promoting an understanding of the principles of the invention, reference will now be made to the embodiments illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended. Any alterations and further modifications in the described embodiments, and any further applications of the principles of the invention as described herein, are contemplated as would normally occur to one skilled in the art to which the invention relates. One embodiment of the invention is shown in great detail, although it will be apparent to those skilled in the relevant art that some features that are not relevant to the present invention may not be shown for the sake of clarity.

(11) The reference numerals in the following description have been organized to aid the reader in quickly identifying the drawings where various components are first shown. In particular, the drawing in which an element first appears is typically indicated by the left-most digit(s) in the corresponding reference number. For example, an element identified by a “100” series reference numeral will likely first appear in FIG. 1, an element identified by a “200” series reference numeral will likely first appear in FIG. 2, and so on.

(12) A vehicle **100** according to one example is illustrated in FIG. 1. As shown, the vehicle **100** includes at least one powertrain system **105**, at least one controller **110**, and at least one Energy Storage System (“ESS”) **115** configured to supply power to the powertrain system **105**. The powertrain system **105**, controller **110**, and ESS **115** are operatively connected together so as to communicate with one another via at least one Controller Area Network (“CAN”) **120**. The controller **110** is configured to control the operation of one or more systems and/or other components of the vehicle **100** such as the powertrain system **105** and ESS **115**. The powertrain system **105** has an output or drive shaft **125** that transfers mechanical power from the powertrain system **105** to a propulsion system **130**. In the illustrated example, the propulsion system **130** includes one or more wheels **135**, but the propulsion system **130** in further examples can include other types of propulsion devices like continuous track systems. One or more power cables **140** transfer electrical power between the powertrain system **105** and the ESS **115**.

(13) The powertrain system **105** is designed to electrically propel the vehicle **100** in an efficient manner. As will be explained in greater detail below, the powertrain system **105** is designed to power heavy-duty commercial and/or military grade vehicles such as buses, garbage trucks, delivery trucks, fire trucks, and semi-trailers. The powertrain system **105** is designed to electrically power vehicles **100** with a class group rating of at least four (4) according to the US Department of Transportation Federal Highway Administration (FHWA) classification rule set. In one form, the powertrain system **105** is configured to move at least 40,000 pound (18,144 Kg) passenger vehicles like buses. The powertrain system **105** has a unique, compact centerline design that allows the powertrain system **105** to be easily retrofitted into pre-existing vehicle chassis designs and/or conventional drivetrains with minimal changes to the other parts of the vehicle **100** like the braking and suspension systems. This in turn allows existing internal combustion type vehicles to be readily reconfigured as fully electric vehicles. Moreover, the centerline design of the powertrain system

105 reduces gear loss and other power losses so as to make the vehicle **100** more power efficient which in turn can improve driving range and/or reduce weight of other components such as the ESS **115**.

(14) FIG. 2 shows a diagram of another example of an electric powertrain **200** that can be used in the powertrain system **105** of FIG. 1. FIG. 3 shows a cross-sectional view of the electric powertrain **200**. The electric powertrain **200** shares a number of components and functions in common with the ones described before (see e.g., FIGS. 2 and 3). For the sake of brevity as well as clarity, these common features will not be described in great detail below, but please refer to the previous discussion.

(15) As depicted, the electric powertrain **200** includes a multiple motor continuous power transmission **205**. The transmission **205** of the electric powertrain **200** includes a first electric motor **210** with a first inverter **212** and a second electric motor **215** with a second inverter **217**. The first inverter **212** is electrically connected between the ESS **115** and the first electric motor **210**, and the second inverter **217** is electrically connected between the ESS **115** and the second electric motor **215**. The first inverter **212** and second inverter **217** convert the direct current (DC) from the ESS **115** to alternating current (AC) in order to power the first electric motor **210** and second electric motor **215**, respectively. The first electric motor **210** and second electric motor **215** can also act as generators such as during regenerative braking. In such a situation, the first inverter **212** and second inverter **217** act as rectifiers by converting the AC electrical power from the first electric motor **210** and second electric motor **215**, respectively, to DC power that is supplied to the ESS **115**. In the illustrated example, the first inverter **212** and second inverter **217** include combined inverter-rectifiers that at least convert DC to AC and AC to DC. In one example, the first electric motor **210** and second electric motor **215** are the same type of electric motor such that both motors generally provide the same speed and torque output within normal manufacturing tolerances. In other words, the first electric motor **210** and second electric motor **215** are interchangeable with one another. The first electric motor **210** and second electric motor **215** in one form are both high speed electric motors, and in another form, the first electric motor **210** and second electric motor **215** are both low speed electric motors. In alternative variations, the first electric motor **210** and second electric motor **215** can be different such that one for example is a high speed motor and the other is a low speed motor.

(16) The first electric motor **210** and second electric motor **215** in one form are interchangeable with one another. In one specific example, the first electric motor **210** and second electric motor **215** are the same type of high speed electric motor having rated speeds of at least 5,000 revolutions per minute (rpm), and more particularly, the first electric motor **210** and second electric motor **215** each has a rated speed of at least 10,600 rpm, a rated peak power of at least 250 horsepower (hp), a rated continuous power of at least 150 hp, a rated continuous torque of at least 240 pound-feet (lb-ft), and a rated peak torque of at least 310 lb-ft.

(17) The transmission **205** of the electric powertrain **200** further includes a first gear train **220** and a second gear train **225** both located at an output end of the first electric motor **210** and the second electric motor **215**. As can be seen, the first gear train **220** is located at the output end of the entire transmission **205** that is proximal to the drive shaft **125**. The second gear train **225** is sandwiched or located between the second electric motor **215** and the first gear train **220**. This configuration helps to dampen noise and vibrations created by the first gear train **220** and second gear train **225**. Typically, higher pitch line (or circle) velocities produce higher noise levels. Noise levels can be lowered by enhancing gear mesh contact and selecting appropriate materials as well as lubrication. The illustrated design moves the first gear train **220** and second carrier **255** downstream so as to be closer to the drive shaft **125**. This in turn typically moves any resulting noise away from the passenger cabin of the vehicle **100**.

(18) In the illustrated example, the first gear train **220** is in the form of a first planetary gear **230**. The first planetary gear **230** includes a first sun gear **231**, one or more first planet gears **232** that

engage the first sun gear **231** in an orbital manner, and a first ring gear **233** that surrounds and engages the first planet gears **232**. The second gear train **225** in the depicted example is in the form of a second planetary gear **235**. The second planetary gear **235** includes a second sun gear **236**, one or more second planet gears **237** that engage the second sun gear **236** in an orbital manner, and a second ring gear **238** that surrounds and engages the second sun gear **236**. The first electric motor **210** and second electric motor **215** respectively have a first output shaft **240** and a second output shaft **245** for providing rotational mechanical power. In the illustrated example, the second output shaft **245** is hollow such that the first output shaft **240** is able to extend through the second output shaft **245** in a concentric manner. The first planetary gear **230** has a first carrier **250** that is connected to the drive shaft **125**, and the second planetary gear **235** has a second carrier **255**. The first planet gears **232** and second planet gears **237** are respectively mounted or connected to the first carrier **250** and second carrier **255**. In one form, the first sun gear **231** and second sun gear **236** are respectively integrally formed with the first output shaft **240** and second output shaft **245**, respectively. In other examples, the first sun gear **231** and second sun gear **236** can be separate gears that are attached to the first output shaft **240** and second output shaft **245**.

(19) As shown in FIGS. **2** and **5**, the electric powertrain **200** includes at least one clutch **260** with a clutch actuator **262** that engages and disengages the second electric motor **215** from the first electric motor **210**. Through the clutch **260**, the transmission **205** of the electric powertrain **200** is further able to shift gears such that the speed and/or torque from second electric motor **215** can be changed. The first electric motor **210** is permanently connected to the drive shaft **125** (i.e., there is no clutch) such that the first electric motor **210** is able to provide continuous power to the drive shaft **125** and propulsion system **130**. In other words, the first electric motor **210** has an uninterrupted connection to the drive shaft **125**, and the second electric motor **215** has an interruptible connection to the drive shaft **125**. This configuration of the electric powertrain **200** facilitates power shifting in which power is always able to be provided to the wheels **135** even when shifting of the clutch **260** occurs. With power being continuously provided, any shifting can be made generally imperceptible to the driver and/or passengers.

(20) In the illustrated example, the electric powertrain **200** includes a single clutch **260**, but the electric powertrain **200** in other examples can include more than one clutch. In one variation, the clutch **260** is a dog clutch **261**, and in another, the clutch **260** is a Selectable One-Way Clutch (SOWC). In further variations, the clutch **260** includes a wet disc type clutch or a dry disc type clutch. As should be appreciated, replacing the dog clutch with a SOWC, a wet disk type clutch, and/or a dry disk type clutch requires the use of more than one clutch. For example, the dog clutch may be replaced by two wet or dry disk type clutches. The first output shaft **240** for the first electric motor **210** has a clutch engagement member **265** where the clutch **260** is able to selectively engage different range members on the second output shaft **245** and the second carrier **255**. The second carrier **255** of the second planetary gear **235** has a first range member **270** where the clutch **260** engages when in a first range position. When in the first range position, the clutch **260** connects the first range member **270** to the clutch engagement member **265** such that the speed (i.e., rpm) provided by the second electric motor **215** is reduced through the second gear train **225**, and the torque provided by the second electric motor **215** to the first output shaft **240** is increased through the second planetary gear **235**. The second output shaft **245** of the second electric motor **215** has a second range member **275** where the clutch **260** engages when in a second range position. When in the second range position, the clutch **260** connects the second range member **275** to the clutch engagement member **265** such that the speed and torque of the second electric motor **215** is directly provided to the first output shaft **240** of the first electric motor **210**. As compared to the first range position, the speed of the second electric motor **215** provided to the first output shaft **240** of the first electric motor **210** is faster, and the torque is less. The clutch **260** can further be positioned at a neutral position where the second electric motor **215** is not mechanically coupled to the first electric motor **210**. In the neutral shift position, the first electric motor **210** can provide the sole

mechanical power to propel the vehicle **100**.

(21) By using more than one electric motor, the powertrain system **105** is configured to allow smaller, consumer automotive electric motors to be used to power larger, commercial-grade vehicles such as those with a FHWA class rating of four (4) or higher and/or those that are able to move 20,000 pounds (18,144 Kg) or more. Typically, but not always, consumer-grade automotive electric motors are less expensive, lighter, and are capable of providing higher speeds as compared to the higher torque commercial-grade electric motors. Moreover, these consumer-grade motors tend to be more power dense and energy efficient such that the coverage range of the vehicle **100** between charging of the ESS **115** can be enlarged.

(22) The electric powertrain **200** operates in a similar fashion as described before. Again, this multiple motor design also can use energy more efficiently. The power, speed, and/or torque provided by the first electric motor **210** and the second electric motor **215** can be adjusted so that the motors operate in a more efficient manner for differing operational conditions. For example, the clutch **260** can change the gear ratios of the second gear train **225** so as to adjust the output speed and/or torque provided by the second electric motor **215**. The dog clutch **261** can further be used to disconnect the second electric motor **215** from the first electric motor **210** such that the first electric motor **210** provides all of the propulsive mechanical power to the drive shaft **125**. At the same time, the second electric motor **215** can be shut down to conserve power and allow the first electric motor **210** to operate within an efficient power band, or the speed of the second electric motor **215** can be changed for shifting purposes. Having the first gear train **220** reduce the output speed, the first electric motor **210** and second electric motor **215** can be high speed motors that are commonly developed for passenger vehicles.

(23) Once more, with the first electric motor **210** permanently connected to the drive shaft **125** power can be always applied to the propulsion system **130** such that any shifting of the second gear train **225** via the clutch **260** can be imperceptible to the driver and/or passengers of the vehicle **100**. Given the first electric motor **210** continuously provides power to the wheels **135**, the powertrain system **105** can take the proper time during shifting so as to enhance efficiency and performance of the vehicle **100**. The powertrain system **105** is able to provide more than adequate time to deal with timing and synchronization issues between the first electric motor **210**, second electric motor **215**, second gear train **225**, and/or clutch **260**.

(24) With the first electric motor **210** and second electric motor **215** being electric motors, there is no need for hydraulic controls because the electric powertrain **200** can be electronically controlled. The first electric motor **210** and second electric motor **215** again in one specific example are the same type of high speed electric motor having rated speeds of at least 5,000 rpm, and more particularly, the first electric motor **210** and second electric motor **215** each has a rated speed of at least 10,600 rpm, a rated peak power of at least 250 hp, a rated continuous power of at least 150 hp, a rated continuous torque of at least 240 lb-ft, and a rated peak torque of at least 310 lb-ft. The first planetary gear **230** of the first gear train **220** reduces the output speed from both the first electric motor **210** and second electric motor **215** such that the maximum output speed at the drive shaft **125** is about 3,500 rpm and the maximum output torque at the drive shaft **125** is about 3,600 lb-ft in one example.

(25) FIG. 4 shows an electric powertrain **400** that is a variation of the electric powertrain **200** shown in FIG. 2. As can be seen, the electric powertrain **400** contains a number of the same components and is constructed in a similar manner as the electric powertrain **200** shown in FIG. 2. For example, the electric powertrain **400** includes the second gear train **225**, second planetary gear **235**, first output shaft **240**, second output shaft **245**, second carrier **255**, clutch **260**, and clutch actuator **262** of the type described above for the electric powertrain **200** in FIG. 2, and the electric powertrain **400** includes the first electric motor **210** with the first inverter **212** and the second electric motor **215** with the second inverter **217**. Once more, the clutch **260** is a dog clutch **261** to reduce power loss during shifting. For the sake of brevity and clarity, these common features will

not be again discussed below, so please refer to the previous discussion of these features. Unlike the electric powertrain **200** in FIG. 2, the electric powertrain **400** has a transmission **405** in which the first gear train **220** (i.e., first planetary gear **230**) has been eliminated. In the illustrated example, both the first electric motor **210** and second electric motor **215** are low speed motors with a rated speed of less than 5,000 rpm. This configuration of the electric powertrain **400** is conducive in situations where the first electric motor **210** and second electric motor **215** are both low speed motors such that the first gear train **220** is not required to reduce the speed of the output from the electric powertrain **400**.

(26) With the first electric motor **210** and second electric motor **215** being electric motors, there is no need for hydraulic controls because the electric powertrain **400** can be electronically controlled. The first electric motor **210** and second electric motor **215** again in one specific example are the same type of low speed electric motor having rated speeds of less than 5,000 rpm. In one form, the first electric motor **210** and second electric motor **215** are interchangeable parts with the same part or SKU number. More particularly, the first electric motor **210** and second electric motor **215** each has a rated speed of at most 2,500 rpm, a rated peak power of at least 250 hp (600 Volts DC), a rated continuous power of at least 133 hp (600 Volts DC), a rated continuous torque of at least 320 lb-ft, and a rated peak torque of at least 735 lb-ft. Without the first gear train **220**, the output at the drive shaft **125** from the electric powertrain **400** has a maximum output speed of about 3,500 rpm and a maximum output torque of about 3,200 lb-ft in one example.

(27) The second gear train **225** and clutch **260** in the electric powertrain **400** operate in a similar fashion as described before. The controller **110** via the clutch actuator **262** shifts the dog clutch **261** between neutral, first range, and second range positions so that the second electric motor **215** is able to provide different torques (or not) to the clutch engagement member **265** that are combined with the torque from the first electric motor **210** at the drive shaft **125**. When the dog clutch **261** is in a neutral position, the second electric motor **215** does not supply power to the drive shaft **125**. In such a case, the first electric motor **210** can supply all of the power to the drive shaft **125**. Once more, the first electric motor **210** can also act as a generator during regenerative braking so as to recharge the ESS **115**. The dog clutch **261** engages the first range member **270** to place the clutch **260** in the first range position where the second electric motor **215** is able to provide higher torques to the drive shaft **125**. The dog clutch **261** shifts to the second range position by engaging the second range member **275**. At the second range position, the second electric motor **215** provides a torque that is lower than when at the first range position, but the speed is higher. Once more, both the first electric motor **210** and second electric motor **215** are low speed motors such that the first gear train **220** is not required to reduce the speed of the output from the electric powertrain **400**.

(28) FIG. 5 shows an electric powertrain **500** that is a variation of the electric powertrain **200** and the electric powertrain **500** shown in FIGS. 2 and 4, respectively. As can be seen, the electric powertrain **500** contains a number of the same components and is constructed in a similar manner as the electric powertrain **200** shown in FIG. 2. For example, the electric powertrain **500** includes the second gear train **225**, second planetary gear **235**, first output shaft **240**, second carrier **255**, clutch **260**, and clutch actuator **262** of the type described above for the electric powertrain **200** in FIG. 2, and the electric powertrain **500** includes the first electric motor **210** with the first inverter **212** and the second electric motor **215** with the second inverter **217**. The second gear train **225** in the illustrated example includes the second planetary gear **235**. Like before, the second planetary gear **235** has the second sun gear **236**, second planet gears **237**, and second ring gear **238**. Once more, the clutch **260** is a positive clutch, like the dog clutch **261**, to reduce power loss during shifting. For the sake of brevity and clarity, these common features will not be again discussed below, so please refer to the previous discussion of these features. Unlike the electric powertrain **200** in FIG. 2, the electric powertrain **500** has a transmission **405** in which the first gear train **220** (i.e., first planetary gear **230**) has been eliminated. In the illustrated example, the first electric motor **210** is a low speed motor with a rated speed of less than 5,000 rpm, and the second electric

motor **215** is a high speed motor with a rated speed greater than 5,000 rpm.

(29) With the first electric motor **210** and second electric motor **215** being electric motors, there is no need for hydraulic controls because the electric powertrain **500** can be electronically controlled. The first electric motor **210** and second electric motor **215** again in one specific example are the same type of low speed electric motor having rated speeds of less than 5,000 rpm. In one form, the first electric motor **210** and second electric motor **215** are interchangeable parts with the same part or SKU number. More particularly, the first electric motor **210** and second electric motor **215** each has a rated speed of at least 10,600 rpm, a rated peak power of at least 250 hp (600 Volts DC), a rated continuous power of at least 150 hp (600 Volts DC), a rated continuous torque of at least 240 lb-ft, and a rated peak torque of at least 310 lb-ft. The first electric motor **210** and second electric motor **215** in other examples can be different types of motors. For instance, the first electric motor **210** is a low speed motor and the second electric motor **215** is a high speed motor in another variation.

(30) As illustrated, the transmission **505** includes a second output shaft **510** that is connected to the second electric motor **215** and an intermediate output shaft **515** that is connected to the second gear train **225**. In one form, the second sun gear **236** of the second planetary gear **235** is integrally formed with the intermediate output shaft **515**, and in other forms, the second sun gear **236** is a separate component. Connected between the second output shaft **510** and intermediate output shaft **515**, the transmission **505** has an intermediate gear train **520**. In the illustrated example, the intermediate gear train **520** includes an intermediate planetary gear **525**. The intermediate planetary gear **525** includes an intermediate sun gear **530**, one or more intermediate planet gear **535** that engage the intermediate sun gear **530** in an orbital manner, and an intermediate ring gear **540** that surrounds and engages the intermediate planet gear **535**. The intermediate ring gear **540** is secured to the housing **239**. The intermediate gear train **520** includes an intermediate carrier **545** on which the intermediate planet gear **535** is rotationally mounted. The intermediate planetary gear **525** connects the intermediate planetary gear **525** to the intermediate output shaft **515**. In one form, the intermediate sun gear **530** is integrally formed on the second output shaft **510**, and in other forms, the intermediate sun gear **530** is a separate component connected to the second output shaft **510**. In the illustrated example, the second output shaft **510** and intermediate output shaft **515** are hollow such that the first output shaft **240** is able to extend through the second output shaft **510** and intermediate output shaft **515** in a concentric manner. The intermediate planetary gear **525** is configured to reduce the speed and increase the torque output from the second electric motor **215** supplied to the second gear train **225**.

(31) The second gear train **225** and clutch **260** in the electric powertrain **500** operate in a similar fashion as described before. The controller **110** via the clutch actuator **262** shifts the dog clutch **261** between neutral, first range, and second range positions so that the second electric motor **215** is able to provide different torques (or not) to the clutch engagement member **265** that are combined with the torque from the first electric motor **210** at the drive shaft **125**. When the dog clutch **261** is in a neutral position, the second electric motor **215** does not supply power to the drive shaft **125**. In such a case, the first electric motor **210** can supply all of the power to the drive shaft **125**. Once more, the first electric motor **210** can also act as a generator during regenerative braking so as to recharge the ESS **115**. The dog clutch **261** engages the first range member **270** to place the clutch **260** in the first range position where the second electric motor **215** is able to provide higher torques to the drive shaft **125**. The dog clutch **261** shifts to the second range position by engaging the second range member **275**. At the second range position, the second electric motor **215** provides a torque that is lower than when at the first range position, but the speed is higher.

(32) FIG. 6 shows a diagram of another example of an electric powertrain **600** that can be used in the powertrain system **105** of FIG. 1, and FIG. 7 shows a cross-sectional view of the electric powertrain **600**. FIG. 6 shows an electric powertrain **600** that is another variation of the electric powertrain **200** shown in FIG. 2. The electric powertrain **600** contains a number of the same

components and is constructed in a similar manner as the electric powertrain **200** shown in FIG. 2. For example, the electric powertrain **600** includes the first gear train **220**, second planetary gear **235**, first output shaft **240**, second carrier **255**, clutch **260**, and clutch actuator **262** of the type described above for the electric powertrain **200** in FIG. 2, and the electric powertrain **600** includes the first electric motor **210** with the first inverter **212** and the second electric motor **215** with the second inverter **217**. The first gear train **220** in the illustrated example includes the first planetary gear **230**. Like before, the first planetary gear **230** has the first sun gear **231**, first planet gears **232**, and first ring gear **233**. Once more, the clutch **260** is a positive clutch, like the dog clutch **261**, to reduce power loss during shifting. For the sake of brevity and clarity, these common features will not be again discussed below, so please refer to the previous discussion of these features.

(33) With the first electric motor **210** and second electric motor **215** being electric motors, there is no need for hydraulic controls because the electric powertrain **600** can be electronically controlled. The first inverter **212** is electrically connected between the ESS **115** and the first electric motor **210**, and the second inverter **217** is electrically connected between the ESS **115** and the second electric motor **215**. The first inverter **212** and second inverter **217** convert the direct current (DC) from the ESS **115** to alternating current (AC) in order to power the first electric motor **210** and second electric motor **215**, respectively. The first electric motor **210** and second electric motor **215** can also act as generators such as during regenerative braking. In such a situation, the first inverter **212** and second inverter **217** convert the AC electrical power from the first electric motor **210** and second electric motor **215**, respectively, to DC power that is supplied to the ESS **115**. In one example, the first electric motor **210** and second electric motor **215** are the same type of electric motor such that both motors generally provide the same speed and torque output within normal manufacturing tolerances. The first electric motor **210** and second electric motor **215** in one form are both high speed electric motors, and in another form, the first electric motor **210** and second electric motor **215** are both low speed electric motors. In alternative variations, the first electric motor **210** and second electric motor **215** can be different such that one for example is a high speed motor and the other is a low speed motor.

(34) As can be seen, the electric powertrain **600** in FIG. 6 has a second gear train **625** that is configured differently from the second gear train **225** of FIG. 2. The second gear train **625** is sandwiched or located between the second electric motor **215** and the first gear train **220**. This configuration helps to dampen noise created by the second gear train **625**. In the illustrated example, the second gear train **625** includes a second planetary gear **635**. The second planetary gear **635** includes a second sun gear **636**, one or more second planet gears **637** that engage the second sun gear **636** in an orbital manner, and a second ring gear **638** that surrounds and engages the second planet gears **637**. The first electric motor **210** and second electric motor **215** respectively have the first output shaft **240** and a second output shaft **645** for providing rotational mechanical power. In the illustrated example, the second output shaft **645** is hollow such that the first output shaft **240** is able to extend through the second output shaft **645** in a concentric manner. The second planetary gear **635** has a second carrier **655** that is coupled to the first gear train **220**, and the second ring gear **638** generally surrounds the second carrier **655**.

(35) As shown in FIGS. 6 and 7, the electric powertrain **600** includes at least one Selectable One-Way Clutch (“SOWC”) **660** with a clutch actuator **662** that engages and disengages the SOWC **660** with the second ring gear **638**. Through the SOWC **660**, the transmission **605** of the electric powertrain **600** is able to shift gears such that the speed and/or torque from second electric motor **215** can be changed. The second gear train **625** further includes a clutch **665** with a clutch actuator **670** that actuates the clutch **665**. In one example, the clutch **665** includes a dog clutch **675**, and in one particular version, the dog clutch **675** is a two-position dog clutch. The second carrier **655** has a clutch engagement member **680**, and the second output shaft **645** has a range member **685**. When actuated by the clutch actuator **670**, the clutch **665** is able to operatively connect the range member **685** to the clutch engagement member **680** such that torque from the second output shaft **645** is

transferred to the second carrier **655**. The torque from the second carrier **655** is in turn transferred to the drive shaft **125** via the first planetary gear **230**. Different gear ranges from the second electric motor **215** can be achieved by engaging and disengaging the SOWC **660** and dog clutch **675** in various combinations. In further variations, the clutch **665** includes a wet disc type clutch or a dry disc type clutch.

(36) The first electric motor **210** is permanently connected to the drive shaft **125** (i.e., there is no clutch) such that the first electric motor **210** is able to provide continuous power to the drive shaft **125** and propulsion system **130**. In other words, the first electric motor **210** has an uninterrupted connection to the drive shaft **125**, and the second electric motor **215** is connected to the drive shaft **125** via the SOWC **660** or clutch **665**. This configuration of the electric powertrain **600** facilitates power shifting in which power is always able to be provided to the drive shaft **125** even when shifting of the SOWC **660** occurs. With power being continuously provided, any shifting can be made generally imperceptible to the driver and/or passengers.

(37) By using more than one electric motor, the powertrain system **105** is configured to allow smaller, consumer automotive electric motors to be used to power larger, commercial-grade vehicles such as those with a FHWA class rating of four (4) or higher and/or those that are able to move 40,000 pounds (18,144 Kg) or more. Typically, but not always, consumer-grade automotive electric motors are less expensive, lighter, and are capable of providing higher speeds as compared to the higher torque commercial-grade electric motors. Moreover, these consumer-grade motors tend to be more power dense and energy efficient such that the coverage range of the vehicle **100** between charging of the ESS **115** can be enlarged.

(38) Again, this multiple motor design also can use energy more efficiently. The power, speed, and/or torque provide by the first electric motor **210** and the second electric motor **215** can be adjusted so that the motors operate in a more efficient manner for differing operational conditions. For example, the SOWC **660** and/or clutch **665** can change the gear ratios of the second gear train **625** so as to adjust the output speed and/or torque provided by the second electric motor **215**. The SOWC **660** can further be used to disconnect the second electric motor **215** from the first electric motor **210** such that the first electric motor **210** provides all of the propulsive mechanical power to the drive shaft **125**. At the same time, the second electric motor **215** can be shut down to conserve power and allow the first electric motor **210** to operate within an efficient power band, or the speed of the second electric motor **215** can be changed for shifting purposes. Once more, with the first electric motor **210** permanently connected to the drive shaft **125** power can be always applied to the propulsion system **130** such that any shifting of the second gear train **625** via the SOWC **660** and clutch **665** can be imperceptible to the driver and/or passengers of the vehicle **100**. Given the first electric motor **210** continuously provides power to the drive shaft **125**, the powertrain system **105** can take the proper time during shifting so as to enhance efficiency and performance of the vehicle **100**. The powertrain system **105** is able to provide more than adequate time to deal with timing and synchronization issues between the first electric motor **210**, second electric motor **215**, second gear train **625**, SOWC **660**, and/or dog clutch **675**.

(39) FIG. 8 shows an electric powertrain **800** that is a variation of the electric powertrain **600** shown in FIGS. 6 and 7. As can be seen, the electric powertrain **800** contains a number of the same components and is constructed in a similar manner as the electric powertrain **200** shown in FIG. 2. For example, the electric powertrain **800** includes the first output shaft **240**, second gear train **625**, second planetary gear **635**, second output shaft **645**, second carrier **655**, SOWC **660**, clutch actuator **662**, clutch **665**, clutch actuator **670**, dog clutch **675**, clutch engagement member **680**, and range member **685** of the type described above for the electric powertrain **600** in FIG. 6, and the electric powertrain **800** includes the first electric motor **210** with the first inverter **212** and the second electric motor **215** with the second inverter **217**. Once more, the second planetary gear **635** of the second gear train **625** includes the second sun gear **636**, second planet gears **637**, and second ring gear **638**. For the sake of brevity and clarity, these common features will not be again

discussed below, so please refer to the previous discussion of these features. Unlike the electric powertrain **600** in FIG. **6**, the electric powertrain **800** has a transmission **805** in which the first gear train **220** (i.e., first planetary gear **230**) has been eliminated. In the illustrated example, both the first electric motor **210** and second electric motor **215** are low speed motors with a rated speed of less than 5,000 rpm. This configuration of the electric powertrain **800** is conducive in situations where the first electric motor **210** and second electric motor **215** are both low speed motors such that the first gear train **220** is not required to reduce the speed of the output from the electric powertrain **800**.

(40) With the first electric motor **210** and second electric motor **215** being electric motors, there is no need for hydraulic controls because the electric powertrain **800** can be electronically controlled. The first electric motor **210** and second electric motor **215** again in one specific example are the same type of low speed electric motor having rated speeds of less than 5,000 rpm. In one form, the first electric motor **210** and second electric motor **215** are interchangeable parts with the same part or SKU number. More particularly, the first electric motor **210** and second electric motor **215** each has a rated speed of at most 2,500 rpm, a rated peak power of at least 250 hp (600 Volts DC), a rated continuous power of at least 133 hp (600 Volts DC), a rated continuous torque of at least 320 lb-ft, and a rated peak torque of at least 735 lb-ft. Without the first gear train **220**, the output at the drive shaft **125** from the electric powertrain **800** has a maximum output speed of about 3,500 rpm and a maximum output torque of about 3,200 lb-ft in one example.

(41) The second gear train **225**, SOWC **660**, and clutch **665** in the electric powertrain **800** operate in a similar fashion as described before. The power, speed, and/or torque provide by the first electric motor **210** and the second electric motor **215** can be adjusted so that the motors operate in a more efficient manner for differing operational conditions. For example, the SOWC **660** and/or clutch **665** can change the gear ratios of the second gear train **625** so as to adjust the output speed and/or torque provided by the second electric motor **215**. The SOWC **660** can further be used to disconnect the second electric motor **215** from the first electric motor **210** such that the first electric motor **210** provides all of the propulsive mechanical power to the drive shaft **125**. At the same time, the second electric motor **215** can be shut down to conserve power and allow the first electric motor **210** to operate within an efficient power band, or the speed of the second electric motor **215** can be changed for shifting purposes. Once more, with the first electric motor **210** permanently connected to the drive shaft **125** power can be always applied to the propulsion system **130** such that any shifting of the second gear train **625** via the SOWC **660** and clutch **665** can be imperceptible to the driver and/or passengers of the vehicle **100**. Given the first electric motor **210** continuously provides power to the drive shaft **125**, the powertrain system **105** can take the proper time during shifting so as to enhance efficiency and performance of the vehicle **100**. The powertrain system **105** is able to provide more than adequate time to deal with timing and synchronization issues between the first electric motor **210**, second electric motor **215**, second gear train **625**, SOWC **660**, and/or dog clutch **675**.

(42) FIG. **9** shows a diagram of another example of an electric powertrain **900** with a multiple motor continuous power transmission **905** that can be used in the powertrain system **105** of FIG. **1**. The electric powertrain **900** shares a number of components and functions in common with the ones described before (see e.g., FIGS. **2** and **3**). For the sake of brevity as well as clarity, these common features will not be described in great detail below, but please refer to the previous discussion.

(43) The front end of the transmission **905** is generally constructed in a similar fashion as the transmission **205** in FIGS. **2** and **3**, but the transmission **905** in FIG. **9** further includes an add-on module **907** configured to provide additional shifting ranges. For example, the transmission **905** in FIG. **9** includes the first electric motor **210** with the first inverter **212** and the second electric motor **215** with the second inverter **217**. The first inverter **212** is electrically connected between the ESS **115** and the first electric motor **210**, and the second inverter **217** is electrically connected between

the ESS **115** and the second electric motor **215**. The first inverter **212** and second inverter **217** convert the direct current (DC) from the ESS **115** to alternating current (AC) in order to power the first electric motor **210** and second electric motor **215**, respectively. The first electric motor **210** and second electric motor **215** can also act as generators such as during regenerative braking. In such a situation, the first inverter **212** and second inverter **217** convert the AC electrical power from the first electric motor **210** and second electric motor **215**, respectively, to DC power that is supplied to the ESS **115**. In one example, the first electric motor **210** and second electric motor **215** are the same type of electric motor such that both motors generally provide the same speed and torque output within normal manufacturing tolerances. The first electric motor **210** and second electric motor **215** in one form are both high speed electric motors, and in another form, the first electric motor **210** and second electric motor **215** are both low speed electric motors. In alternative variations, the first electric motor **210** and second electric motor **215** can be different such that one for example is a high speed motor and the other is a low speed motor.

(44) Like before, the transmission **905** has the first gear train **220** and the second gear train **225** both located at an output end of the first electric motor **210** and the second electric motor **215**. The first gear train **220** is located at the output end of the entire transmission **205** that is proximal to the drive shaft **125**. The second gear train **225** is sandwiched or located between the second electric motor **215** and the first gear train **220**. This configuration helps to dampen noise created by the second gear train **225**. Higher pitch line (or circle) velocities produce higher noise levels. Noise levels can be lowered by enhancing gear mesh contact and selecting appropriate materials as well as lubrication. The illustrated design moves the first gear train **220** and second carrier **255** downstream so as to be closer to the drive shaft **125**. This in turn typically moves any resulting noise away from the passenger cabin of the vehicle **100**.

(45) In the illustrated example, the first gear train **220** is in the form of the first planetary gear **230**. The first planetary gear **230** includes the first sun gear **231**, one or more first planet gears **232** that engage the first sun gear **231** in an orbital manner, and the first ring gear **233** that surrounds and engages the first planet gears **232**. The second gear train **225** in the depicted example is in the form of the second planetary gear **235**. The second planetary gear **235** includes the second sun gear **236**, one or more second planet gears **237** that engage the first sun gear **231** in an orbital manner, and the first ring gear **233** that surrounds and engages the first planet gears **232**. The first electric motor **210** and second electric motor **215** respectively have the first output shaft **240** and the second output shaft **245** for providing rotational mechanical power. In the illustrated example, the second output shaft **245** is hollow such that the first output shaft **240** is able to extend through the second output shaft **245** in a concentric manner. The first planetary gear **230** again has the first carrier **250** that is connected to the drive shaft **125**, and the second planetary gear **235** has the second carrier **255**. The first planet gears **232** and second planet gears **237** are respectively mounted or connected to the first carrier **250** and second carrier **255**. In one form, the first sun gear **231** and second sun gear **236** are respectively integrally formed with the first output shaft **240** and second output shaft **245**, respectively. In other examples, the first sun gear **231** and second sun gear **236** can be separate gears that are attached to the first output shaft **240** and second output shaft **245**.

(46) As shown in FIG. **9**, the transmission **905** includes at least one clutch **260** in the form of the dog clutch **261**. Like in the earlier examples, the dog clutch **261** has the clutch actuator **262** that engages and disengages the second electric motor **215** from the first electric motor **210**. Through the clutch **260**, the transmission **205** of the electric powertrain **200** is further able to shift gears such that the speed and/or torque from second electric motor **215** can be changed. In the illustrated example, the transmission **905** includes a single clutch **260**, but the transmission **905** in other examples can include more than one clutch. The first output shaft **240** for the first electric motor **210** has the clutch engagement member **265** where the clutch **260** is able to engage the first output shaft **240**. The second carrier **255** of the second planetary gear **235** has the first range member **270** where the clutch **260** engages when in a first range position. When in the first range position, the

clutch **260** connects the first range member **270** to the clutch engagement member **265** such that the speed (i.e., rpm) provided by the second electric motor **215** is reduced through the second gear train **225**, and the torque provided by the second electric motor **215** to the first gear train **220** is increased through the second planetary gear **235**. The second output shaft **245** of the second electric motor **215** has the second range member **275** where the clutch **260** engages when in a second range position. When in the second range position, the clutch **260** connects the second range member **275** to the clutch engagement member **265** such that the speed and torque of the second electric motor **215** is directly provided to the first gear train **220**. As compared to the first range position, the speed of the second electric motor **215** provided to the first output shaft **240** of the first electric motor **210** is faster, and the torque is less. The clutch **260** can further be positioned at a neutral position where the second electric motor **215** is not mechanically coupled to the drive shaft **125**. In the neutral shift position, the first electric motor **210** can provide the sole mechanical power to propel the vehicle **100**, if desired.

(47) As noted before, the module **907** in FIG. **9** is configured to readily convert the transmission **205** of FIG. **2** from a two-speed to a three-speed type design. As shown, the module **907** includes a third gear train **910** that is located upstream from the first electric motor **210**, that is, on a side of the transmission **905** opposite the first gear train **220** and second gear train **225**. The transmission **905** has a first output shaft **915** and a first connector shaft **920**. The first connector shaft **920** connects the first electric motor **210** to the third gear train **910**, and the first output shaft **915** extends in a longitudinal direction inside the transmission **905** to connect the third gear train **910** to the first gear train **220** and second gear train **225**. The second output shaft **245** and first connector shaft **920** are hollow such that the first output shaft **915** is able to extend through the second output shaft **245** and first connector shaft **920** in a concentric manner. Through the third gear train **910** and first output shaft **915**, the first electric motor **210** is able to provide power to the drive shaft **125**.

(48) The third gear train **910** in the illustrated example includes a third planetary gear **922**. As shown, the transmission **905** further includes a second clutch **925** that selectively engages and disengages with the third planetary gear **922** through a second clutch actuator **927**. In the illustrated form, the second clutch **925** is a dog clutch. The second clutch actuator **927** is operatively coupled or connected to the controller **110** through the CAN **120** such that the controller **110** is able to control the operation of the second clutch **925**. The third planetary gear **922** in the depicted example has a third sun gear **928**, one or more inner planet gears **930** that engage the third sun gear **928**, one or more outer planet gears **935** that engage the inner planet gears **930**, and a third ring gear **938** that surrounds and engages with the outer planet gears **935**. The third sun gear **928**, inner planet gears **930**, outer planet gears **935**, and third ring gear **938** in the third planetary gear **922** are generally arranged in a concentric manner. The inner planet gears **930** and outer planet gears **935** are each rotationally mounted to a third carrier **940** that is fixed to the housing **239**. Relative to the housing **239**, the inner planet gears **930** and outer planet gears **935** are stationary, and the third sun gear **928** and third ring gear **938** rotate or move in relation to the housing **239**. With this gearing arrangement, the third planetary gear **922** of the third gear train **910** is able to increase the torque supplied by the first electric motor **210** and reduce the output speed of the first electric motor **210**.

(49) As shown in FIG. **9**, the first output shaft **915** at the third gear train **910** has a second clutch engagement member **945** that engages the second clutch **925**. The third ring gear **938** of the third planetary gear **922** has a first-second range member **950** that is engageable by the second clutch **925**. The first connector shaft **920** has a third range member **955** that is likewise engageable by the second clutch **925**. The controller **110** via the second clutch actuator **927** is able to change the torque and speed from the first electric motor **210** supplied to the drive shaft **125** by shifting the second clutch **925** to alternatively engage the first-second range member **950** or third range member **955**. In one variation, the first gear train **220** has a gear ratio of about 3.00, the second gear train **225** has a gear ratio of about 3.50, and the third gear train **910** has a gear ratio of about 2.50. It should be recognized that these gear trains in other variations can have different ratios.

(50) One technique for operating the transmission **905** will now be described with reference to FIG. **9**. Once more, the transmission **905** has a three speed design. With this technique, at least one of the motors is always supplying power to the drive shaft **125** such that no power interrupt occurs such as during shifting. Having this uninterrupted power, any shifting will occur smoothly such that a driver and/or passenger of the vehicle **100** will generally not feel any significant power loss or jerking motion.

(51) In the first range, both the first electric motor **210** and second electric motor **215** supply mechanical power to the drive shaft **125**. The controller **110** via the second clutch actuator **927** positions the second clutch **925** so that the second clutch **925** mechanically connects the first-second range member **950** of the third planetary gear **922** to the second clutch engagement member **945**. At this first range position, the third planetary gear **922** of the third gear train **910** is able to increase the torque supplied by the first electric motor **210** to the first gear train **220** and reduce the output speed of the first electric motor **210**. At the same time in the first range position, the controller **110** via the clutch actuator **262** positions the clutch **260** so that the clutch **260** connects the first range member **270** to the clutch engagement member **265**. When in this first range position, the second electric motor **215** through the second planet gears **237** of the second gear train **225** supplies higher torque at a lower speed to the first gear train **220**. The output from both the first electric motor **210** and second electric motor **215** is directed through the first planetary gear **230** so as to increase the torque and reduce the speed supplied to the drive shaft **125**. This allows higher speed electric motors, such as those designed for passenger vehicles, to be used in heavy duty vehicles. Typically, but not always, the first range position is used when the vehicle **100** is travelling at low speeds and/or under high torque requirement conditions.

(52) From the first range position, the transmission **905** is able to shift to a second range position. During this first shifting position (i.e., from the first range position to the second range position), the first electric motor **210** supplies all of the mechanical power to the drive shaft **125** so that the transmission **905** maintains an uninterrupted power connection. With this uninterrupted connection, the shifting will occur smoothly such that a driver and/or passenger of the vehicle **100** will generally not feel any significant power loss or jerking motion. When in this first shifting position, power supplied by the first electric motor **210** is increased to compensate for the power loss of the second electric motor **215**. The second clutch actuator **927** maintains the engagement of the second clutch **925** between the second clutch engagement member **945** and third range member **955**. The clutch actuator **262** moves the clutch **260** to a neutral position where the clutch **260** is disengaged from both the first range member **270** and second range member **275**. With the clutch **260** in this neutral position at the first shifting position, no mechanical power from the second electric motor **215** is transferred to the drive shaft **125** of the vehicle **100** such that the first electric motor **210** supplies all of the power to the drive shaft **125**.

(53) To shift to the second range position, the controller **110** via the clutch actuator **262** moves the clutch **260** to a position where the clutch **260** mechanically connects the second range member **275** to the clutch engagement member **265** such that the second electric motor **215** again supplies power to the drive shaft **125**. As compared to the first range position, the output from the second electric motor **215** has a generally higher speed and lower torque because the power from the second electric motor **215** does not pass through the second planet gears **237**. At the same time, the second clutch actuator **927** maintains the engagement of the second clutch **925** between the second clutch engagement member **945** and third range member **955** at the second range position. The power supplied by the first electric motor **210** can be reduced once the second electric motor **215** is engaged in the second range position. At the second range position, both the first electric motor **210** and second electric motor **215** supply power to the drive shaft **125** via the first gear train **220**.

(54) From the second range position, the transmission **905** is able to shift to a third range position. During this second shifting position (i.e., from the second range position to the third range position), the second electric motor **215** supplies all of the mechanical power to the drive shaft **125**

so that the transmission **905** maintains an uninterrupted power connection. With this uninterrupted connection, the shifting will occur smoothly such that a driver and/or passenger of the vehicle **100** will generally not feel any significant power loss or jerking motion. When in this second shifting position, power supplied by the second electric motor **215** is increased to compensate for the power loss of the first electric motor **210**. The clutch actuator **262** maintains the engagement of the clutch **260** between the clutch engagement member **265** and second range member **275**. At the same time, the second clutch actuator **927** moves the second clutch **925** to a neutral position where the second clutch **925** is disengaged from both the first-second range member **950** and third range member **955**. With the second clutch **925** in this neutral position at the second shifting position, no mechanical power from the first electric motor **210** is transferred to the drive shaft **125** of the vehicle **100** such that the second electric motor **215** supplies all of the power to the drive shaft **125**. (55) To shift to the third range position, the controller **110** via the second clutch actuator **927** moves the second clutch **925** to a position where the second clutch **925** mechanically connects the third range member **955** to the second clutch engagement member **945** such that the first electric motor **210** again supplies power to the drive shaft **125**. As compared to the first and second range positions, the output from the first electric motor **210** has a generally higher speed and lower torque because the power from the first electric motor **210** does not pass through the third planetary gear **922**. At the same time, the clutch actuator **262** maintains the engagement of the clutch **260** between the clutch engagement member **265** and second range member **275** at the third range position. The power supplied by the second electric motor **215** can be reduced once the first electric motor **210** is engaged in the third range position. At the third range position, both the first electric motor **210** and second electric motor **215** again supply power to the drive shaft **125** via the first gear train **220**. Typically, but not always, the third range position is used when the vehicle **100** is travelling at high speeds and/or under low torque requirement conditions.

(56) Using the above-described technique and transmission **905**, at least one of the motors is always supplying power to the drive shaft **125** such that no power interrupt occurs such as during shifting. Having this uninterrupted power, any shifting will occur smoothly such that a driver and/or passenger of the vehicle **100** will generally not feel any significant power loss or jerking motion. Moreover, this technique and system allows higher speed electric motors, such as those designed for passenger vehicles, to be used in heavy duty vehicles.

Glossary of Terms

(57) The language used in the claims and specification is to only have its plain and ordinary meaning, except as explicitly defined below. The words in these definitions are to only have their plain and ordinary meaning. Such plain and ordinary meaning is inclusive of all consistent dictionary definitions from the most recently published Webster's dictionaries and Random House dictionaries. As used in the specification and claims, the following definitions apply to these terms and common variations thereof identified below.

(58) "About" with reference to numerical values generally refers to plus or minus 10% of the stated value. For example if the stated value is 4.375, then use of the term "about 4.375" generally means a range between 3.9375 and 4.8125.

(59) "And/Or" generally refers to a grammatical conjunction indicating that one or more of the cases it connects may occur. For instance, it can indicate that either or both of two stated cases can occur. In general, "and/or" includes any combination of the listed collection. For example, "X, Y, and/or Z" encompasses: any one letter individually (e.g., {X}, {Y}, {Z}); any combination of two of the letters (e.g., {X, Y}, {X, Z}, {Y, Z}); and all three letters (e.g., {X, Y, Z}). Such combinations may include other unlisted elements as well.

(60) "Axis" generally refers to a straight line about which a body, object, and/or a geometric figure rotates or may be conceived to rotate.

(61) "Bearing" generally refers to a machine element that constrains relative motion and reduces friction between moving parts to only the desired motion, such as a rotational movement. The

bearing for example can be in the form of loose ball bearings found in a cup and cone style hub. The bearing can also be in the form of a cartridge bearing where ball bearings are contained in a cartridge that is shaped like a hollow cylinder where the inner surface rotates with respect to the outer surface by the use of ball or other types of bearings.

(62) “Brake” generally refers to a device for arresting and/or preventing the motion of a mechanism usually via friction, electromagnetic, and/or other forces. Brakes for example can include equipment in automobiles, bicycles, or other vehicles that are used to slow down and/or stop the vehicle. In other words, a brake is a mechanical device that inhibits motion by absorbing energy from a moving system. The brake can be for example used for slowing or stopping a moving vehicle, wheel, and/or axle, or to prevent its motion. Most often, this is accomplished by friction. Types of brakes include frictional, pressure, and/or electromagnetic type braking systems. Frictional brakes for instance can include caliper, drum, and/or disc brakes. Electromagnetic braking systems for example can include electrical motor/generators found in regenerative braking systems.

(63) “Clutch” generally refers to a device that engages and disengages mechanical power transmission between two or more rotating shafts or other moving components. In one example, one shaft is typically attached to an engine, motor, or other power source, which acts as the driving member, while the other shaft (i.e., the driven member) provides output power for work. While the motions involved are usually rotary motions, linear clutches are also used to engage and disengage components moving with a linear or near linear motion. The clutch components can for instance be engaged and disengaged through mechanical, hydraulic, and/or electrical actuation. The clutches can include positive type clutches and friction type clutches. Wet type clutches are typically immersed in a cooling lubrication liquid or other fluid, and dry clutches are not bathed in such liquids. Some non-limiting examples of clutches include cone clutches, centrifugal clutches, torque limiter clutches, axial clutches, disc clutches, dog clutches, and rim clutches, to name just a few.

(64) “Contact” generally refers to a condition and/or state where at least two objects are physically touching. For example, contact requires at least one location where objects are directly or indirectly touching, with or without any other member(s) material in between.

(65) “Controller” generally refers to a device, using mechanical, hydraulic, pneumatic electronic techniques, and/or a microprocessor or computer, which monitors and physically alters the operating conditions of a given dynamical system. In one non-limiting example, the controller can include an Allen Bradley brand Programmable Logic Controller (PLC). A controller may include a processor for performing calculations to process input or output. A controller may include a memory for storing values to be processed by the processor or for storing the results of previous processing. A controller may also be configured to accept input and output from a wide array of input and output devices for receiving or sending values. Such devices include other computers, keyboards, mice, visual displays, printers, industrial equipment, and systems or machinery of all types and sizes. For example, a controller can control a network or network interface to perform various network communications upon request. The network interface may be part of the controller, or characterized as separate and remote from the controller. A controller may be a single, physical, computing device such as a desktop computer or a laptop computer, or may be composed of multiple devices of the same type such as a group of servers operating as one device in a networked cluster, or a heterogeneous combination of different computing devices operating as one controller and linked together by a communication network. The communication network connected to the controller may also be connected to a wider network such as the Internet. Thus a controller may include one or more physical processors or other computing devices or circuitry and may also include any suitable type of memory. A controller may also be a virtual computing platform having an unknown or fluctuating number of physical processors and memories or memory devices. A controller may thus be physically located in one geographical location or physically spread across several widely scattered locations with multiple processors linked together by a communication

network to operate as a single controller. Multiple controllers or computing devices may be configured to communicate with one another or with other devices over wired or wireless communication links to form a network. Network communications may pass through various controllers operating as network appliances such as switches, routers, firewalls or other network devices or interfaces before passing over other larger computer networks such as the Internet. Communications can also be passed over the network as wireless data transmissions carried over electromagnetic waves through transmission lines or free space. Such communications include using WiFi or other Wireless Local Area Network (WLAN) or a cellular transmitter/receiver to transfer data.

(66) “Controller Area Network” or “CAN” generally refers to a vehicle bus standard designed to allow microcontrollers, sensors, and/or other devices to communicate with each other in applications without necessarily a host computer. CAN systems include a message-based protocol, designed originally for multiplex electrical wiring within automobiles, but is also used in many other contexts. A vehicle with a CAN system may normally, but not always, include multiple Electronic Control Units (ECUs) which can be also called nodes. These ECUs can include Engine Control Modules (ECMs) and Transmission Control Modules (TCMs) as well as other control units such as for airbags, antilock braking/ABS, cruise control, electric power steering, audio systems, power windows, doors, mirror adjustment, battery and/or hybrid/electric recharging systems, to name just a few. A CAN includes a multi-master serial bus standard for connecting ECUs. The complexity of the ECU or node can range from a simple Input/Output (I/O) device up to an embedded computer with a CAN interface and software. The ECU or node can also act as a gateway allowing a general purpose computer to communicate over an interface, such as via a USB and/or Ethernet port, to the devices on the CAN network. Each ECU usually, but not always, includes a central processing unit, a CAN controller, and transceiver. The CAN systems can for example include low speed CAN (128 Kbps) under the ISO 11898-3 standard, high speed CAN (512 Kbps) under the ISO 11898-2 standard, CAN FD under the ISO 11898-1 standard, and single wire CAN under the SAE J2411 standard.

(67) “Dog Clutch” generally refers to a type of positive clutch that couples and decouples at least two rotating shafts or other rotating mechanical components by an interference type connection. The two parts of the clutch are designed such that one will push the other, thereby causing both to rotate at the same speed with no (or very minimal) slippage. Typically, but not always, one part of the dog clutch includes a series of teeth or other protrusions that are configured to mate with another part of the dog clutch that includes corresponding recesses for receiving the teeth or protrusions. Unlike friction clutches that allow slippage, dog clutches are used where slip is undesirable and/or the clutch is not used to control torque. Without slippage, dog clutches are not affected by wear in the same manner as friction clutches.

(68) “Downstream” generally refers to a direction or relative location that is the same as where power flows in a system.

(69) “Eccentric” generally refers to having an axis located elsewhere than at the geometric center of an object or relative an axis of another object. As one non-limiting example, when oriented in an eccentric manner, the object has an axis of revolution displaced from the center of the object (or relative to another object) so that the object is capable of imparting reciprocating motion. In other words, something is considered eccentric when it is not placed centrally or does not have its axis or other part placed centrally.

(70) “Electric Motor” generally refers to an electrical machine that converts electrical energy into mechanical energy. Normally, but not always, electric motors operate through the interaction between one or more magnetic fields in the motor and winding currents to generate force in the form of rotation. Electric motors can be powered by direct current (DC) sources, such as from batteries, motor vehicles, and/or rectifiers, or by alternating current (AC) sources, such as a power grid, inverters, and/or electrical generators. An electric generator can (but not always) be

mechanically identical to an electric motor, but operate in the reverse direction, accepting mechanical energy and converting the mechanical energy into electrical energy.

(71) “Electronic Control Unit (ECU)” or “Electronic Control Module (ECM)” generally refers to an embedded system in electronics of a vehicle that controls one or more electrical systems and/or subsystems of the vehicle. Usually, but not always, ECUs communicate over a Controller Area Network (CAN) and can act as nodes over the CAN. The complexity of the ECU or node can range from a simple Input/Output (I/O) device up to an embedded computer with a CAN interface and software. The ECU or node can also act as a gateway allowing a general purpose computer to communicate over an interface, such as via a USB and/or Ethernet port, to the devices on the CAN network. Each ECU usually, but not always, includes a central processing unit, a CAN controller, and a transceiver. These ECUs can for instance include Engine Control Modules (ECMs) and Transmission Control Modules (TCMs) as well as other control units such as for airbags, antilock braking/ABS, cruise control, electric power steering, audio systems, power windows, doors, mirror adjustment, battery and/or hybrid/electric recharging systems, to name just a few. By way of nonlimiting examples, types of ECUs can include ECMs, TCMs, Powertrain Control Module (PCMs), Brake Control Modules (BCMs or EBCMs), Central Control Modules (CCMs), Central Timing Modules (CTMs), General Electronic Modules (GEMs), Body Control Modules (BCMs), and/or Suspension Control Modules (SCMs), to name just a few.

(72) “Energy Storage System” (ESS) or “Energy Storage Unit” generally refers to a device that captures energy produced at one time for use at a later time. The energy can be supplied to the ESS in one or more forms, for example including radiation, chemical, gravitational potential, electrical potential, electricity, elevated temperature, latent heat, and kinetic types of energy. The ESS converts the energy from forms that are difficult to store to more conveniently and/or economically storable forms. By way of non-limiting examples, techniques for accumulating the energy in the ESS can include: mechanical capturing techniques, such as compressed air storage, flywheels, gravitational potential energy devices, springs, and hydraulic accumulators; electrical and/or electromagnetic capturing techniques, such as using capacitors, super capacitors, and superconducting magnetic energy storage coils; biological techniques, such as using glycogen, biofuel, and starch storage mediums; electrochemical capturing techniques, such as using flow batteries, rechargeable batteries, and ultra batteries; thermal capture techniques, such as using cutectic systems, molten salt storage, phase-change materials, and steam accumulators; and/or chemical capture techniques, such as using hydrated salts, hydrogen, and hydrogen peroxide. Common ESS examples include lithium-ion batteries and super capacitors.

(73) “Fastener” generally refers to a hardware device that mechanically joins or otherwise affixes two or more objects together. By way of nonlimiting examples, the fastener can include bolts, dowels, nails, nuts, pegs, pins, rivets, screws, and snap fasteners, to just name a few.

(74) “Gear Train” generally refers to a system of gears that transmit power from one mechanical component to another. For example, a gear train can include a combination of two or more gears, mounted on rotating shafts, to transmit torque and/or power. As one non-limiting example, the gear train for instance can include a planetary gearset.

(75) “High Speed Motor” generally refers to a motor that has a maximum output speed of at least 5,000 rpm (rotations per minute) without the use of gear trains or other similar equipment for boosting speed.

(76) “Interchangeable” generally refers to two or more things that are capable of being put and/or used in place of each other. In other words, one thing is capable of replacing and/or changing places with something else. For example, interchangeable parts typically, but not always, are manufactured to have nearly the same structural size as well as shape within normal manufacturing tolerances and have nearly the same operational characteristics so that one part can be replaced by another interchangeable part. In some cases, the interchangeable parts can be manufactured and/or sold by a specific company under the same part or Stock Keeping Unit (SKU) identifier, and in

other cases, different companies can manufacture and/or sell the same interchangeable parts.

(77) “Interruptible Connection” generally refers to a mechanical linkage between two mechanical components that has the ability to break continuity during normal operation such that the components can be mechanically disconnected and reconnected if so desired. When disconnected, the components are unable to provide mechanical power to one another. The interruptible connection can include multiple components such as multiple shafts and gears that engage with one another. The interruptible connection includes at least one mechanism, such as a clutch, that is designed to disconnect and reconnect the mechanical linkage between the components during normal operation.

(78) “Inverter” or “Power Inverter” generally refers to an electronic device and/or circuitry that at least converts direct current (DC) to alternating current (AC). Certain types of inverters can further include a rectifier that converts AC to DC such that the inverter and rectifier functions are combined together to form a single unit that is sometimes referred to as an inverter. The inverter can be entirely electronic or may be a combination of mechanical devices, like a rotary apparatus, and electronic circuitry. The inverter can further include static type inverters that do not use moving parts to convert DC to AC.

(79) “Lateral” generally refers to being situated on, directed toward, or coming from the side.

(80) “Longitudinal” generally relates to length or lengthwise dimension of an object, rather than across.

(81) “Low Speed Motor” generally refers to a motor that has a maximum output speed of less than 5,000 rpm (rotations per minute) without the use of gear trains or other similar equipment for boosting speed.

(82) “Means For” in a claim invokes 35 U.S.C. 112 (f), literally encompassing the recited function and corresponding structure and equivalents thereto. Its absence does not, unless there otherwise is insufficient structure recited for that claim element. Nothing herein or elsewhere restricts the doctrine of equivalents available to the patentee.

(83) “Motor” generally refers to a machine that supplies motive power for a device with moving parts. The motor can include rotor and linear type motors. The motor can be powered in any number of ways, such as via electricity, internal combustion, pneumatics, and/or hydraulic power sources. By way of non-limiting examples, the motor can include a servomotor, a pneumatic motor, a hydraulic motor, a steam engine, pneumatic piston, hydraulic piston, and/or an internal combustion engine.

(84) “Optionally” means discretionary; not required; possible, but not compulsory; left to personal choice.

(85) “Original Equipment Manufacturer” or “OEM” generally refers to an organization that makes finished devices from component parts bought from other organizations that are usually sold under their own brand in a consumer or commercial market.

(86) “Planetary Gear” or “Planetary Gearset” generally refers to a system of at least two gears mounted so that the center of at least one gear revolves around the center of the other. In other words, the planetary gear includes a system of epicyclic gears in which at least one gear axis revolves about the axis of another gear. In one example, a carrier connects the centers of the two gears and rotates to carry one gear, which is called a planet gear, around the other, which is commonly called a sun gear. Typically, but not always, the planet and sun gears mesh so that their pitch circles roll without slip. A point on the pitch circle of the planet gear normally traces an epicycloid curve. In one simplified case, the sun gear is fixed and the one or more planet gears roll around the sun gear. In other examples, an epicyclic gear train can be assembled so the planet gear rolls on the inside of the pitch circle of a fixed, outer gear ring, or ring gear, that is sometimes called an annular gear. In this case, the curve traced by a point on the pitch circle of the planet gear is a hypocycloid. A planetary gear is typically used to transfer large torque loads in a compact form.

(87) “Positive Clutch” generally refers to a type of clutch that is designed to transmit torque

without slippage such as through a mechanical interference type connection. Some examples of positive clutches include jaw clutches (e.g., square or spiral jaw clutches) and dog clutches.

(88) “Powertrain” generally refers to devices and/or systems used to transform stored energy into kinetic energy for propulsion purposes. The powertrain can include multiple power sources and can be used in non-wheel-based vehicles. By way of non-limiting examples, the stored energy sources can include chemical, solar, nuclear, electrical, electrochemical, kinetic, and/or other potential energy sources. For example, the powertrain in a motor vehicle includes the devices that generate power and deliver the power to the road surface, water, and/or air. These devices in the powertrain include engines, motors, transmissions, drive shafts, differentials, and/or final drive components (e.g., drive wheels, continuous tracks, propeller, thrusters, etc.).

(89) “Rated Continuous Power” or “Continuous Rated Power” generally refer to an amount of energy or work provided per unit of time (i.e., power) an electric motor will produce without interruption for a rated speed, at a rated torque, and at a rated voltage for the electric motor. In other words, the rated continuous power is usually the power that the electric motor can produce for a long period of time at the rated speed and the rated torque without damaging the electric motor.

(90) “Rated Operating Speed” or “Rated Speed” generally refers to a velocity (i.e., speed) an electric motor will rotate when producing a rated continuous power at a supplied rated voltage for the electric motor. Typically, but not always, the rated operating speed is measured in terms of Revolutions Per Minute (rpm). Generally speaking, the rated operating speed is the prescribed rpm at which the motor operates, keeping the mechanical stability and efficiency of the electric motor in mind. The rated voltage and rated horsepower respectively refer to the maximum voltage and horsepower (hp) where the motor can operate efficiently without being damaged. The value for the rated operating speed will be slightly less than a synchronous speed of the electric motor due to a decrease in speed caused by adding a load (i.e., slip or speed loss). For instance, most alternating current (AC) induction motors with synchronous speeds of 1800 RPM will have normally have rated speeds ranging between about 1720 and about 1770 RPM depending on the amount of slip. Some newer high or energy-efficient electric motors will tend to have rated operating speeds towards a higher end of the range.

(91) “Rated Continuous Torque” or “Continuous Rated Torque” generally refer to a magnitude of twisting force, or torque, an electric motor will produce without interruption for a rated speed and at a rated voltage for the electric motor. In other words, the rated continuous torque is usually a torque that the electric motor can output for a long period of time at the rated speed without damaging the electric motor. Typically, this value is generated close to the maximum speed of the motor.

(92) “Resolver” generally refers to a type of rotary sensor for measuring the degree of rotation, velocity, and/or acceleration of a rotary type device. In one example, the resolver includes a rotary electrical transformer used for measuring degrees of rotation such as in an electric motor, an electric generator, and/or a transmission. The resolver can include analog or digital type electrical devices. The resolver can be in the form of a two-pole type resolver or a multi-pole type resolver. Some other types of resolvers include receiver type resolvers and differential type resolvers.

(93) “Rotor” generally refers to a part or portion in a machine that rotates in or around a stationary part, which is commonly referred to as a stator. The rotor is the moving or rotating part of a rotary system, such as found in electric generators, electric motors, sirens, mud motors, turbines, and/or biological rotors. In one particular non-limiting example, the rotor includes the rotating portion of an electric generator and/or motor, especially of an induction motor.

(94) “Selectable One-Way Clutch” (SOWC) generally refers to a type of clutch that is able to be controlled to lock in at least one rotational direction. One-way clutches are usually (but not always) designed to transfer torque or lock when rotated in one direction and to allow rotational movement or free-wheel when rotated in the opposite direction. The SOWC is a type of one-way clutch that can be used to control when and/or in which direction the rotational motion is locked or able to

rotate freely. By way of a non-limiting example, the SOWC can be activated to lock so as to transfer torque when torque is applied in one rotational direction and facilitate free-wheel or slipping movement in the opposite rotational direction. In other variations, the SOWC can be controlled at times to facilitate free-wheel motion in both rotational directions or locked to allow torque transfer in both rotational directions. Alternatively or additionally, the SOWC can be controlled to switch or change the locked and freewheel rotational directions. For example, the SOWC under one operating condition can be locked when rotated in a counterclockwise and free-wheel spin in the clockwise direction, and under other conditions, the SOWC can be switched so that the SOWC is locked in the clockwise direction and freewheel spin in the counterclockwise direction. Some non-limiting examples of SOWC designs include roller, sprag, spiral, and mechanical diode type designs. The SOWC can be controlled or actuated in a number of ways such as through mechanical and/or electrical actuation. For instance, the SOWC can be actuated with hydraulic, pneumatic, and/or electrical type actuators to name just a few.

(95) “Sensor” generally refers to an object whose purpose is to detect events and/or changes in the environment of the sensor, and then provide a corresponding output. Sensors include transducers that provide various types of output, such as electrical and/or optical signals. By way of nonlimiting examples, the sensors can include pressure sensors, ultrasonic sensors, humidity sensors, gas sensors, motion sensors, acceleration sensors, displacement sensors, force sensors, optical sensors, and/or electromagnetic sensors. In some examples, the sensors include barcode readers, RFID readers, and/or vision systems.

(96) “Stator” generally refers to a stationary part or portion in a machine in or about which a rotating part revolves, which is commonly referred to as a rotor. The stator is the stationary part of a rotary system, such as found in electric generators, electric motors, sirens, mud motors, turbines, and/or biological rotors. In one particular non-limiting example, the stator includes the stationary portion of an electric generator and/or motor, especially of an induction motor.

(97) “Substantially” generally refers to the degree by which a quantitative representation may vary from a stated reference without resulting in an essential change of the basic function of the subject matter at issue. The term “substantially” is utilized herein to represent the inherent degree of uncertainty that may be attributed to any quantitative comparison, value, measurement, and/or other representation.

(98) “Symmetric” or “Symmetrical” generally refer to a property of something having two sides or halves that are the same relative to one another, such as in shape, size, and/or style. In other words, symmetric describes something as having a mirror-image quality.

(99) “Synchronizer” or “Synchronizer Mechanism” (“Synchromesh”) generally refer to a device that includes a cone clutch and a blocking ring which brings the speeds of a gear and a gear selector to the same speed using friction. In one example, before the teeth of the gear and gear selector can engage, the cone clutch engages first which in turn brings the gear selector and gear to the same speed using friction. Until synchronization occurs, the teeth of the gear and the gear selector are prevented from making contact by the blocking ring. When synchronization occurs, the friction on the blocking ring is relieved and the blocking ring twists slightly. With this twisting motion, grooves or notches are aligned that allow further passage of the gear selector which brings the teeth together.

(100) “Synchronous Speed” generally refers to a theoretical speed where an electrical motor can be operated based on the electrical parameters of the motor. Generally speaking, the synchronous speed is not achieved in reality. For an alternating current (AC) motor, the synchronous speed is dependent on the number of poles in the motor and the line frequency of the power supply to the motor. The synchronous speed for an AC motor can be represented by the following equation: Synchronous Speed = $120 \times \text{power supply line frequency (Hertz)} / \text{number of poles in the AC motor}$.

(101) “Transmission” generally refers to a power system that provides controlled application of mechanical power. The transmission uses gears and/or gear trains to provide speed, direction,

and/or torque conversions from a rotating power source to another device.

(102) “Transverse” generally refers to things, axes, straight lines, planes, or geometric shapes extending in a non-parallel and/or crosswise manner relative to one another. For example, when in a transverse arrangement, lines can extend at right angles or perpendicular relative to one another, but the lines can extend at other non-straight angles as well such as at acute, obtuse, or reflex angles. For instance, transverse lines can also form angles greater than zero (0) degrees such that the lines are not parallel. When extending in a transverse manner, the lines or other things do not necessarily have to intersect one another, but they can.

(103) “Uninterrupted Connection” generally refers to a mechanical linkage between two mechanical components without any break in continuity such that mechanical force can be transmitted on a continuous basis if so desired. The uninterrupted connection does not require a unitary connection such that the uninterrupted connection can include multiple components such as multiple shafts and gears that engage with one another. The uninterrupted connection lacks mechanisms or other structures, such as clutches, that are designed to disconnect and reconnect the mechanical linkage between the components during normal operation. It should be recognized that the uninterrupted connection can occasionally have accidental breakages that disconnect the components, but the design of the uninterrupted connection is not designed to facilitate such breakages and resulting disconnections.

(104) “Upstream” generally refers to a direction or relative location that is opposite from where power flows in a system.

(105) “Vehicle” generally refers to a machine that transports people and/or cargo. Common vehicle types can include land based vehicles, amphibious vehicles, watercraft, aircraft, and space craft. By way of non-limiting examples, land based vehicles can include wagons, carts, scooters, bicycles, motorcycles, automobiles, buses, trucks, semi-trailers, trains, trolleys, and trams. Amphibious vehicles can for example include hovercraft and duck boats, and watercraft can include ships, boats, and submarines, to name just a few examples. Common forms of aircraft include airplanes, helicopters, autogiros, and balloons, and spacecraft for instance can include rockets and rocket-powered aircraft. The vehicle can have numerous types of power sources. For instance, the vehicle can be powered via human propulsion, electrically powered, powered via chemical combustion, nuclear powered, and/or solar powered. The direction, velocity, and operation of the vehicle can be human controlled, autonomously controlled, and/or semi-autonomously controlled. Examples of autonomously or semi-autonomously controlled vehicles include Automated Guided Vehicles (AGVs) and drones.

(106) The term “or” is inclusive, meaning “and/or”.

(107) It should be noted that the singular forms “a,” “an,” “the,” and the like as used in the description and/or the claims include the plural forms unless expressly discussed otherwise. For example, if the specification and/or claims refer to “a device” or “the device”, it includes one or more of such devices.

(108) It should be noted that directional terms, such as “up,” “down,” “top,” “bottom,” “lateral,” “longitudinal,” “radial,” “circumferential,” “horizontal,” “vertical,” etc., are used herein solely for the convenience of the reader in order to aid in the reader's understanding of the illustrated embodiments, and it is not the intent that the use of these directional terms in any manner limit the described, illustrated, and/or claimed features to a specific direction and/or orientation.

(109) While the invention has been illustrated and described in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character, it being understood that only the preferred embodiment has been shown and described and that all changes, equivalents, and modifications that come within the spirit of the inventions defined by the following claims are desired to be protected. All publications, patents, and patent applications cited in this specification are herein incorporated by reference as if each individual publication, patent, or patent application were specifically and individually indicated to be incorporated by reference and

set forth in its entirety herein.

REFERENCE NUMBERS

(110) **100** vehicle **105** powertrain system **110** controller **115** ESS **120** CAN **125** drive shaft **130** propulsion system **135** wheels **140** power cables **200** electric powertrain **205** transmission **210** first electric motor **212** first inverter **215** second electric motor **217** second inverter **220** first gear train **225** second gear train **230** first planetary gear **231** first sun gear **232** first planet gears **233** first ring gear **235** second planetary gear **236** second sun gear **237** second planet gears **238** second ring gear **239** housing **240** first output shaft **245** second output shaft **250** first carrier **255** second carrier **260** clutch **261** dog clutch **262** clutch actuator **265** clutch engagement member **270** first range member **275** second range member **400** electric powertrain **500** electric powertrain **505** transmission **510** second output shaft **515** intermediate output shaft **520** intermediate gear train **525** intermediate planetary gear **530** intermediate sun gear **535** intermediate planet gear **540** intermediate ring gear **545** intermediate carrier **600** electric powertrain **605** transmission **625** second gear train **635** second planetary gear **636** second sun gear **637** second planet gears **638** second ring gear **645** second output shaft **655** second carrier **660** SOWC **662** clutch actuator **665** clutch **670** clutch actuator **675** dog clutch **680** clutch engagement member **685** range member **800** electric powertrain **805** transmission **900** electric powertrain **905** transmission **907** module **910** third gear train **915** first output shaft **920** first connector shaft **922** third planetary gear **925** second clutch **927** second clutch actuator **928** third sun gear **930** inner planet gears **935** outer planet gears **938** third ring gear **940** third carrier **945** second clutch engagement member **950** first-second range member **955** third range member

Claims

1. A powertrain system, comprising: an output; a first electric motor connected to the output; a second electric motor; an intermediate gear train connected to the second electric motor; a second gear train connected to the intermediate gear train; wherein the second gear train has a clutch configured to selectively connect the second gear train to the output; and wherein the first electric motor has an uninterrupted direct connection to the output and the second electric motor has an interruptible connection to the output.
2. The powertrain system of claim 1, further comprising: a first output shaft connected to the first electric motor; wherein the first output shaft is connected to the output; wherein the first output shaft extends through the second electric motor; wherein the first output shaft extends through the intermediate gear train; and wherein the first output shaft extends through the second gear train.
3. The powertrain system of claim 2, wherein: the first output shaft has a clutch engagement member; and the clutch is configured to selectively engage the clutch engagement member.
4. The powertrain system of claim 3, further comprising: a second output shaft connected between the second electric motor and the intermediate gear train; an intermediate output shaft connected between the intermediate gear train and the second gear train; and wherein the first output shaft extends through the second output shaft in a concentric manner.
5. The powertrain system of claim 2, wherein the first electric motor is located upstream relative to the second electric motor.
6. The powertrain system of claim 1, wherein the intermediate gear train includes an intermediate planetary gear.
7. The powertrain system of claim 6, wherein: the intermediate planetary gear includes an intermediate sun gear; the intermediate planetary gear includes one or more intermediate planet gears that engage the intermediate sun gear in an orbital manner; and the intermediate planetary gear includes an intermediate ring gear that surrounds and engages the intermediate planet gears.
8. The powertrain system of claim 6, wherein the second gear train includes a second planetary gear.

9. The powertrain system of claim 8, wherein the second planetary gear includes a sun gear, a ring gear, and one or more planet gears engaged between the sun gear and the ring gear.
 10. The powertrain system of claim 9, further comprising: a first output shaft connected to the first electric motor; wherein the first output shaft is connected to the output; wherein the first output shaft has a clutch engagement member; a second output shaft connected between the second electric motor and the intermediate gear train; wherein the second gear train includes a first range member connected to the planet gears of the second planetary gear; an intermediate output shaft having a second range member; and wherein the clutch is configured to selectively engage the first range member, the second range member, and the clutch engagement member.
 11. The powertrain system of claim 10, wherein the clutch includes a positive clutch.
 12. The powertrain system of claim 11, wherein the positive clutch includes a dog clutch.
 13. A powertrain system, comprising: an output; a first electric motor connected to the output; a first output shaft connected to the first electric motor; wherein the first output shaft is directly connected to the output; a second electric motor; an intermediate gear train connected to the second electric motor; a second gear train connected to the intermediate gear train; wherein the second gear train has a clutch configured to selectively connect the second gear train to the output; and wherein the first output shaft extends through the intermediate gear train.
 14. The powertrain system of claim 13, wherein: the first output shaft has a clutch engagement member; and the clutch is configured to selectively engage the clutch engagement member.
 15. The powertrain system of claim 14, further comprising: a second output shaft connected between the second electric motor and the intermediate gear train; an intermediate output shaft connected between the intermediate gear train and the second gear train; and wherein the first output shaft extends through the second output shaft in a concentric manner.
 16. The powertrain system of claim 13, wherein the first electric motor is located upstream relative to the second electric motor.
 17. A powertrain system, comprising: an output; a first electric motor connected to the output; a first output shaft connected to the first electric motor; wherein the first output shaft is connected to the output; a second electric motor; an intermediate gear train connected to the second electric motor; a second gear train connected to the intermediate gear train; wherein the second gear train has a clutch configured to selectively connect the second gear train to the output; wherein the first output shaft has a clutch engagement member; a second output shaft connected between the second electric motor and the intermediate gear train; wherein the second gear train has a first range member; an intermediate output shaft having a second range member; and a clutch configured to selectively engage the first range member, the second range member, and the clutch engagement member.
 18. The powertrain system of claim 17, wherein the clutch includes a positive clutch.
 19. The powertrain system of claim 18, wherein the positive clutch includes a dog clutch.
 20. A powertrain system, comprising: an output; a first electric motor connected to the output; a second electric motor; wherein the second electric motor is located between the first electric motor and the output; an intermediate gear train connected to the second electric motor; a second gear train connected to the intermediate gear train; wherein the intermediate gear train and the second gear train are located between the second electric motor and the output; and wherein the second gear train has a clutch configured to selectively connect the second gear train to the output.
-