

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411471
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Funaki; Masataka

Cutting tool, tool system and communication control method

Abstract

A cutting tool for turning includes a cutting insert having a cutting edge, a holder for holding the cutting insert, a wireless communication unit for transmitting information based on a measurement result of a sensor attached to the cutting tool, an acceleration sensor installed in the holder, and a control unit for performing first control for controlling activation of the wireless communication unit based on the measurement result of the acceleration sensor.

Inventors:	Funaki; Masataka (Osaka, JP)
Applicant:	Sumitomo Electric Industries, Ltd. (Osaka, JP)
Family ID:	78847209
Assignee:	SUMITOMO ELECTRIC INDUSTRIES, LTD. (Osaka, JP)
Appl. No.:	18/008456
Filed (or PCT Filed):	May 18, 2021
PCT No.:	PCT/JP2021/018760
PCT Pub. No.:	WO2021/251072
PCT Pub. Date:	December 16, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230205166 A1	Jun. 29, 2023

Foreign Application Priority Data

JP	2020-099186	Jun. 08, 2020
----	-------------	---------------

Publication Classification

Int. Cl.: G05B19/402 (20060101); B23B27/16 (20060101)

U.S. Cl.:

CPC G05B19/402 (20130101); B23B27/16 (20130101); B23B2270/32 (20130101); B23B2270/48 (20130101); G05B2219/33192 (20130101); G05B2219/37027 (20130101); G05B2219/37236 (20130101); G05B2219/37388 (20130101)

Field of Classification Search

CPC: B32B (2260/128); B32B (2270/32); B32B (2270/48); B32B (27/14); B32B (27/16); B32B (29/323); B23Q (17/0966); B23Q (17/0971); B23Q (17/0985); G05B (19/402); G05B (19/4065); G05B (2219/33192); G05B (2219/37027); G05B (2219/37236); G05B (2219/37274); G05B (2219/37337); G05B (2219/37388); G05B (2219/37428); G05B (2219/50009)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4927300	12/1989	Ramalingam et al.	N/A	N/A
2002/0067968	12/2001	Lapikas	269/317	B23Q 16/001
2006/0085092	12/2005	Redecker	700/174	B23Q 17/098
2009/0234490	12/2008	Suprock	408/116	B23B 31/02
2011/0305534	12/2010	Park	407/100	B23B 51/02
2015/0027723	12/2014	Fripp	166/373	G01V 11/002
2015/0122098	12/2014	Scherhag	83/367	B26D 5/00
2018/0311779	12/2017	Ziegltrum	N/A	B23Q 17/0985
2019/0001456	12/2018	Kalhuri	N/A	B23Q 17/0952
2019/0232377	12/2018	Ostling	N/A	B23Q 17/2233
2020/0156200	12/2019	Nakaya	N/A	G05B 19/19
2021/0100417	12/2020	Tauber et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102007036002	12/2008	DE	N/A
57-079431	12/1981	JP	N/A
61-013242	12/1985	JP	N/A
2-503171	12/1989	JP	N/A
2018-043339	12/2017	JP	N/A
2018-054611	12/2017	JP	N/A
2018-103286	12/2017	JP	N/A
2020-062746	12/2019	JP	N/A
2018/177623	12/2017	WO	N/A
2019/130659	12/2018	WO	N/A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application is based on PCT/JP2021/018760, filed on May 18, 2021, which claims priority to JP 2020-099186, filed Jun. 8, 2020, the entire contents of each are incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to a cutting tool, a tool system and a communication control method.

BACKGROUND ART

(3) PTL 1 (Japanese Unexamined Patent Application Publication No. 2018-43339) discloses a cutting head provided with a current path as described below. That is, the cutting head with a current path is a cutting tool for cutting an object or a holder for holding the cutting tool, and a current path for measuring a change in a member of the cutting tool or the holder is directly or indirectly formed in the whole or a part of the member of the cutting tool or the holder.

PRIOR ART DOCUMENT

Patent Literature

(4) PTL 1: Japanese Unexamined Patent Application Publication No. 2018-43339

SUMMARY OF INVENTION

(5) A cutting tool of the present disclosure is a cutting tool for turning including a cutting insert having a cutting edge, a holder to hold the cutting insert, a wireless communication unit configured to transmit information based on a measurement result of a sensor attached to the cutting tool, an acceleration sensor disposed at the holder, and a control unit configured to perform first control of controlling activation of the wireless communication unit, based on a measurement result of the acceleration sensor.

(6) A tool system of the present disclosure includes a first cutting tool for turning, and a second cutting tool for turning. Each of the first cutting tool and the second cutting tool includes a cutting insert having a cutting edge, a holder to hold the cutting insert, a wireless communication unit configured to transmit measurement information based on a measurement result of a sensor attached to a corresponding cutting tool among the first cutting tool and the second cutting tool, an acceleration sensor disposed at the holder, and a control unit configured to perform activation control of controlling activation of the wireless communication unit, based on a measurement result of the acceleration sensor. The control unit of the first cutting tool and the control unit of the second cutting tool are configured to perform the activation control at a timing of a change in the positions of the first cutting tool and the second cutting tool with respect to a workpiece, details of the activation control performed by the control unit of the first cutting tool and details of the activation control performed by the control unit of the second cutting tool being different from each other.

(7) A communication control method of the present disclosure is a communication control method in a tool system including a first cutting tool for turning and a second cutting tool for turning, each of the first cutting tool and the second cutting tool including a cutting insert having a cutting edge, a holder to hold the cutting insert, a wireless communication unit configured to transmit information based on a measurement result of a sensor attached to a corresponding cutting tool among the first cutting tool and the second cutting tool, an acceleration sensor disposed at the holder, and a control unit configured to perform activation control of controlling activation of the wireless communication unit, based on a measurement result of the acceleration sensor, the

communication control method includes acquiring, by the control unit of the first cutting tool, the measurement result of the corresponding acceleration sensor, acquiring, by the control unit of the second cutting tool, the measurement result of the corresponding acceleration sensor and performing, by the control unit of the first cutting tool and the control unit of the second cutting tool, the activation control, details of the activation control performed by the control unit of the first cutting tool and details of the activation control performed by the control unit of the second cutting tool being different from each other.

(8) An aspect of the present disclosure can be implemented as a semiconductor integrated circuit that implements a part or all of a cutting tool. In addition, one aspect of the present disclosure can be realized as a semiconductor integrated circuit that realizes a part or all of the tool system. Further, one aspect of the present disclosure can be realized as a program for causing a computer to execute the steps of the processing in the communication control method.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a diagram showing a configuration of a tool system according to an embodiment of the present disclosure.
- (2) FIG. 2 is a diagram showing an example of a state in which a cutting tool in a tool system according to the embodiment of the present disclosure is attached to machining equipment.
- (3) FIG. 3 is a diagram showing a configuration of a sensor module according to the embodiment of the present disclosure.
- (4) FIG. 4 is a diagram showing a change in position of a cutting tool when a tool system according to the embodiment of the present disclosure includes one cutting tool.
- (5) FIG. 5 is a diagram showing an example of a correspondence table stored in a storage unit of a cutting tool according to the embodiment of the present disclosure.
- (6) FIG. 6 is a diagram showing a change in position of each cutting tool when the tool system according to the embodiment of the present disclosure includes three cutting tools.
- (7) FIG. 7 is a diagram showing an example of a correspondence table stored in a storage unit of a cutting tool according to the embodiment of the present disclosure.
- (8) FIG. 8 is a diagram for explaining the details of the first activation control and the second activation control by the control unit in each cutting tool in step 1 shown in FIG. 6.
- (9) FIG. 9 is a diagram for explaining the details of the first activation control and the second activation control by the control unit in each cutting tool in step 2 shown in FIG. 6.
- (10) FIG. 10 is a diagram for explaining the details of the first activation control and the second activation control by the control unit in each cutting tool in step 3 shown in FIG. 6.
- (11) FIG. 11 is a flowchart defining an operation procedure of the first activation control and the second activation control by the control unit in the case of the specific example 1 shown in FIG. 4.
- (12) FIG. 12 is a sequence diagram defining an operation procedure of the first activation control and the second activation control by each control unit in the case of the specific example 2 shown in FIG. 6.
- (13) FIG. 13 is a sequence diagram defining an operation procedure of the first activation control and the second activation control by each control unit in the case of the specific example 2 shown in FIG. 6.

DESCRIPTION OF EMBODIMENTS

(14) Conventionally, a technique for monitoring a state of a cutting tool is known.

Problems to be Solved by Present Disclosure

(15) There is a demand for a technique capable of realizing more excellent functions in a system capable of monitoring the state of a cutting tool beyond the technique described in PTL 1.

(16) The present disclosure has been made to solve the above-described problems, and an object thereof is to provide a cutting tool, a tool system, and a communication control method capable of realizing more excellent functions in a system capable of monitoring a state of a cutting tool.

Advantageous Effects of Present Disclosure

(17) According to the present disclosure, a better function can be realized in a system capable of monitoring the state of a cutting tool.

Description of Embodiments of Present Disclosure

(18) First, the contents of the embodiments of the present disclosure will be listed and explained.

(19) (1) A cutting tool according to an embodiment of the present disclosure is a cutting tool for turning including a cutting insert having a cutting edge, a holder to hold the cutting insert, a wireless communication unit configured to transmit information based on a measurement result of a sensor attached to the cutting tool, an acceleration sensor disposed at the holder, and a control unit configured to perform first control of controlling activation of the wireless communication unit, based on a measurement result of the acceleration sensor.

(20) For example, in order to suppress consumption of electric power necessary for wireless transmission of information based on a measurement result (hereinafter, also referred to as “measurement information”), a technique of activating a wireless communication unit at a timing of starting machining is desired. On the other hand, in order to control the activation of the wireless communication unit at the timing of starting the machining, an input operation by an operator, installation of an external device for detecting the timing of starting the machining, or the like is required.

(21) In contrast, with the above-described configuration, the state of the cutting tool can be determined using the acceleration sensor mounted on the cutting tool. Accordingly, since it is possible to grasp the timing suitable for activation of the wireless communication unit in the cutting tool, it is possible to perform activation of the wireless communication unit at an appropriate timing without requiring an input operation by an operator or installation of an external device.

(22) In addition, by performing activation of the wireless communication unit at an appropriate timing, it is possible to suppress consumption of power necessary for wireless transmission of measurement information and to suppress an increase in wireless traffic. Therefore, it is possible to realize more excellent functions in the system capable of monitoring the state of the cutting tool.

(23) (2) The cutting tool may be configured to include a plurality of acceleration sensors each being the acceleration sensor and each configured to measure an acceleration in a single direction, or a single acceleration sensor being the acceleration sensor and configured to measure accelerations in a plurality of directions.

(24) For example, in a system in which a cutting tool is attached to a turret of machining equipment and the cutting tool used for machining is automatically replaced by rotating the turret for each machining process, gravitational acceleration in the vertical direction that the cutting tool experiences has the same value at two locations that are line-symmetric with respect to a straight line passing through the center of the turret and extending in the vertical direction.

(25) In contrast, with the configuration as described above, it is possible to measure gravitational acceleration in a plurality of directions, and thus it is possible to more accurately determine the position of the cutting tool and to perform activation of the wireless communication unit at a more appropriate timing.

(26) (3) The control unit may be configured to determine a position of the cutting tool with respect to a workpiece, and perform the first control of which details correspond to the determined position.

(27) With such a configuration, for example, since the timing at which the cutting tool reaches the machining position can be grasped, the activation of the wireless communication unit in the cutting tool can be performed at a more appropriate timing.

(28) (4) The position may include a machining position in which machining with the cutting tool is

performed, a stop position in which machining with the cutting tool is not performed, and a preparation position between the machining position and the stop position. The control unit may be configured to activate the wireless communication unit as the first control in a case where the cutting tool is in the preparation position with respect to the workpiece.

(29) With such a configuration, before starting machining by the cutting tool, it is possible to secure a time for establishing a communication connection between the cutting tool and the management device that is a transmission destination of the measurement information. Therefore, it is possible for the management device to more reliably acquire the measurement information at the timing of starting the machining.

(30) (5) The cutting tool may further include a measurement sensor of a type different from the acceleration sensor. The wireless communication unit may be configured to transmit information based on a measurement result of the measurement sensor. The control unit may be configured to further perform second control of controlling activation of the measurement sensor, based on the measurement result of the acceleration sensor.

(31) In this manner, by performing the second control in addition to the first control, the power consumption can be further suppressed.

(32) (6) A tool system according to an embodiment of the present disclosure includes a first cutting tool for turning, and a second cutting tool for turning. Each of the first cutting tool and the second cutting tool includes a cutting insert having a cutting edge, a holder to hold the cutting insert, a wireless communication unit configured to transmit measurement information based on a measurement result of a sensor attached to a corresponding cutting tool among the first cutting tool and the second cutting tool, an acceleration sensor disposed at the holder, and a control unit configured to perform activation control of controlling activation of the wireless communication unit, based on a measurement result of the acceleration sensor. The control unit of the first cutting tool and the control unit of the second cutting tool are configured to perform the activation control at a timing of a change in the positions of the first cutting tool and the second cutting tool with respect to a workpiece, details of the activation control performed by the control unit of the first cutting tool and details of the activation control performed by the control unit of the second cutting tool being different from each other.

(33) For example, in order to suppress consumption of power necessary for wireless transmission of measurement information, a technique of activating a wireless communication unit at a timing of starting machining is desired. On the other hand, in order to control the activation of the wireless communication unit at the timing of starting the machining, an input operation by an operator, installation of an external device for detecting the timing of starting the machining, or the like is required.

(34) In contrast, with the above-described configuration, the state of the cutting tool can be determined using the acceleration sensor mounted on the cutting tool. Accordingly, since it is possible to grasp the timing suitable for activation of the wireless communication unit in the cutting tool, it is possible to perform activation of the wireless communication unit at an appropriate timing without requiring an input operation by an operator or installation of an external device.

(35) In addition, by performing activation of the wireless communication unit at an appropriate timing, it is possible to suppress consumption of power necessary for wireless transmission of measurement information and to suppress an increase in wireless traffic particularly effectively in a tool system including a plurality of cutting tools.

(36) Further, according to the above-described configuration, for example, at the timing at which machining is performed by the first cutting tool, the wireless communication unit in the first cutting tool can be activated, and the wireless communication unit in the second cutting tool can be stopped. That is, the control unit in each cutting tool can perform the first control with appropriate details according to the state of each cutting tool. Therefore, it is possible to realize more excellent functions in the system capable of monitoring the state of the cutting tool.

(37) (7) The tool system may further include a management device. The control unit may be configured to determine a position of the first cutting tool or the second cutting tool with respect to the workpiece and create position information indicating a determined result. The wireless communication unit may be configured to transmit the measurement information including the position information created by the control unit. The management device may be configured to display details based on the position information included in the measurement information received from the wireless communication unit.

(38) With such a configuration, in the management device, since the position of each cutting tool can be further grasped in addition to the measurement result of the sensor, it is possible to easily confirm whether or not the measurement of the sensor in the cutting tool during machining is appropriately performed.

(39) (8) A communication control method according to an embodiment of the present disclosure is a communication control method in a tool system including a first cutting tool for turning and a second cutting tool for turning, each of the first cutting tool and the second cutting tool including a cutting insert having a cutting edge, a holder to hold the cutting insert, a wireless communication unit configured to transmit information based on a measurement result of a sensor attached to a corresponding cutting tool among the first cutting tool and the second cutting tool, an acceleration sensor disposed at the holder, and a control unit configured to perform activation control of controlling activation of the wireless communication unit, based on a measurement result of the acceleration sensor. The communication control method includes, acquiring, by the control unit of the first cutting tool, the measurement result of the corresponding acceleration sensor, acquiring, by the control unit of the second cutting tool, the measurement result of the corresponding acceleration sensor, and performing, by the control unit of the first cutting tool and the control unit of the second cutting tool, the activation control, details of the activation control performed by the control unit of the first cutting tool and details of the activation control performed by the control unit of the second cutting tool being different from each other.

(40) For example, in order to suppress consumption of power necessary for wireless transmission of measurement information, a technique of activating a wireless communication unit at a timing of starting machining is desired. On the other hand, in order to control the activation of the wireless communication unit at the timing of starting the machining, an input operation by an operator, installation of an external device for detecting the timing of starting the machining, or the like is required.

(41) In contrast, the state of the cutting tool can be determined using an acceleration sensor mounted on the cutting tool. Accordingly, since it is possible to grasp the timing suitable for activation of the wireless communication unit in the cutting tool, it is possible to perform activation of the wireless communication unit at an appropriate timing without requiring an input operation by an operator or installation of an external device.

(42) In addition, by performing activation of the wireless communication unit at an appropriate timing, it is possible to suppress consumption of power necessary for wireless transmission of measurement information and to suppress an increase in wireless traffic particularly effectively in a tool system including a plurality of cutting tools.

(43) Further, according to the above-described method, for example, at the timing at which machining is performed by the first cutting tool, the wireless communication unit in the first cutting tool can be activated, and the wireless communication unit in the second cutting tool can be stopped. That is, the control unit in each cutting tool can perform the first control with appropriate details according to the state of each cutting tool. Therefore, it is possible to realize more excellent functions in the system capable of monitoring the state of the cutting tool.

(44) Hereinafter, embodiments of the present disclosure will be described with reference to the drawings. In the drawings, the same or corresponding portions are denoted by the same reference numerals, and description thereof will not be repeated. Further, at least a part of the embodiments

described below may be arbitrarily combined.

(45) [Configuration and Basic Operation]

(46) (Tool System)

(47) FIG. 1 is a diagram showing a configuration of a tool system according to an embodiment of the present disclosure.

(48) Referring to FIG. 1, a tool system **300** includes a plurality of cutting tools **100** for turning, a management device **200**, and a wireless base unit **201**. Cutting tool **100** includes a cutting tool holder **2** and a sensor module **110**. Sensor module **110** includes a measurement sensor. Hereinafter, cutting tool holder **2** is also simply referred to as holder **2**. The plurality of cutting tools **100** are attached to, for example, machining equipment.

(49) Wireless base unit **201** is connected to management device **200** in a wired manner, for example. Wireless base unit **201** is, for example, an access point.

(50) Holder **2** holds a cutting insert **1** having a cutting edge. Sensor module **110** is provided in holder **2**.

(51) Holder **2** includes fixing members **3A** and **3B**. Fixing members **3A** and **3B** hold cutting insert **1**.

(52) Cutting insert **1** has, for example, a polygonal shape such as a triangle, a square, a rhombus, and a pentagon in a top view. Cutting insert **1** has, for example, a through hole formed in the center of the upper surface thereof, and is fixed to holder **2** by fixing members **3A** and **3B**.

(53) Tool system **300** is not limited to a configuration including a plurality of cutting tools **100**, and may be a configuration including one cutting tool **100**. Further, tool system **300** is not limited to a configuration including one management device **200**, and may be a configuration including a plurality of management devices **200**.

(54) Cutting tool **100** wirelessly transmits information based on the measurement result of the sensor in sensor module **110** to wireless base unit **201**. For example, cutting tool **100** wirelessly transmits a sensor packet including measurement information based on the measurement result of the measurement sensor in sensor module **110** to wireless base unit **201**.

(55) Cutting tool **100** and wireless base unit **201** perform wireless communication using a communication protocol such as ZigBee® compliant with IEEE 802.15.4, Bluetooth® compliant with IEEE 802.15.1, or UWB (Ultra Wide Band) compliant with IEEE 802.15.3a. A communication protocol other than the above may be used between cutting tool **100** and wireless base unit **201**.

(56) Wireless base unit **201** relays the sensor packet received from cutting tool **100** to management device **200**.

(57) Management device **200** receives the sensor packet relayed by wireless base unit **201** and analyzes the measurement information included in the received sensor packet to monitor, for example, the state of cutting tool **100**.

(58) Specifically, based on the measurement information included in the received sensor packet, management device **200** predicts the lifetime of cutting insert **1** in cutting tool **100** that is the transmission source of the measurement information. Then, management device **200** performs, for example, notification for prompting the user to replace cutting insert **1** based on the prediction result.

(59) (Specific Example of Tool System)

(60) FIG. 2 is a diagram showing an example of a state in which a cutting tool in a tool system according to the embodiment of the present disclosure is attached to machining equipment.

(61) Referring to FIG. 2, a machining equipment **120** includes a motor holder **51**, a motor (not shown) built in motor holder **51**, and a turret **52** rotated by driving of the motor.

(62) Turret **52** has, for example, a disk shape, and rotates in a circumferential direction indicated by an arrow R at a timing when cutting tool **100** used for machining is replaced. Further, turret **52** includes one tool holder **53** or a plurality of tool holders **53** on an outer peripheral portion thereof.

Cutting tool **100** is attached to tool holder **53**. In FIG. **2**, as an example, turret **52** includes six tool holders **53**, and six cutting tools **100** are attached to six tool holders **53** respectively.

(63) Here, six cutting tools **100** shown in FIG. **2** are referred to as cutting tools **100A**, **100B**, **100C**, **100D**, **100E**, and **100F**. Further, in FIG. **2**, cutting insert **1** in cutting tool **100A** is located at a location in contact with a workpiece P (hereinafter, also referred to as “machining location”), and machining is performed on workpiece P by cutting tool **100A**.

(64) When the machining by cutting tool **100A** is finished, turret **52** is rotated in the circumferential direction, and for example, cutting tool **100B** is moved to the machining location. Then, machining is performed on workpiece P by cutting tool **100B**.

(65) When the machining by cutting tool **100B** is finished, turret **52** is rotated again in the circumferential direction, and for example, cutting tool **100C** is moved to the machining location. Then, machining is performed on workpiece P by cutting tool **100C**.

(66) In this way, by rotating turret **52**, it is possible to exchange cutting tool **100** used for machining without carrying cutting tool **100** or workpiece P.

(67) (Sensor Module)

(68) FIG. **3** is a diagram showing a configuration of a sensor module according to the embodiment of the present disclosure.

(69) Referring to FIG. **3**, sensor module **110** includes a measurement sensor **10**, a data generation unit **20**, a wireless communication unit **30**, a control unit **40**, an acceleration sensor **50**, a battery **60**, and a storage unit **70**. Storage unit **70** is, for example, a nonvolatile memory. Wireless communication unit **30** is provided with a communication circuit such as a communication IC (Integrated Circuit).

(70) Battery **60** is a power storage device including, for example, a primary battery, a secondary battery, a solar battery, or a capacitor. Battery **60** stores energy and supplies electric power to each circuit of wireless communication unit **30** and the like in sensor module **110** using the stored energy.

(71) For example, acceleration sensor **50** regularly or irregularly measures gravitational acceleration, and outputs an analog signal indicating a measurement result to control unit **40**. Acceleration sensor **50** is always driven by electric power supplied from battery **60** during operation of tool system **300**, for example.

(72) Measurement sensor **10** includes, for example, at least one of a strain sensor, a pressure sensor, a sound sensor, and a temperature sensor. Measurement sensor **10** is provided, for example, in the vicinity of cutting insert **1** in holder **2**.

(73) Measurement sensor **10** measures at least one of physical quantities such as strain, pressure, sound, and temperature, and outputs an analog signal indicating the measured physical quantity to data generation unit **20**. Measurement sensor **10** is driven by electric power supplied from battery **60**, for example.

(74) Measurement sensor **10** switches between a measurement state, which is an activated state, and a non-measurement state, which is a non-activated state. Measurement sensor **10** performs measurement in the measurement state, outputs an analog signal indicating the measured physical quantity to data generation unit **20**, and stops in the non-measurement state.

(75) Data generation unit **20** creates measurement information including a measurement result of measurement sensor **10** or information based on the measurement result. More specifically, data generation unit **20** receives an analog signal from measurement sensor **10**, and creates measurement information including a measurement result acquired by performing AD (Analog Digital) conversion on the received analog signal or measurement information including a value acquired by performing calculation such as averaging on the measurement result.

(76) Data generation unit **20** creates a sensor packet in which the created measurement information, the sensor ID of measurement sensor **10**, and the like are stored, and outputs the created sensor packet to wireless communication unit **30**.

(77) Wireless communication unit **30** transmits measurement information based on a measurement result of the sensor attached to cutting tool **100** to wireless base unit **201** outside cutting tool **100**. More specifically, wireless communication unit **30** wirelessly transmits the sensor packet in which the measurement information, the sensor ID of measurement sensor **10**, and the like received from data generation unit **20** are stored to wireless base unit **201**. Wireless communication unit **30** is driven by electric power supplied from the battery.

(78) Wireless communication unit **30** switches between a reporting state, which is an activated state, and a non-reporting state, which is a non-activated state. Wireless communication unit **30** wirelessly transmits the sensor packet to wireless base unit **201** in the reporting state, and does not wirelessly transmit the sensor packet to wireless base unit **201** in the non-reporting state.

(79) Control unit **40** is provided with a processor such as CPU (Central Processing Unit) and MPU (Micro Processing Unit). Control unit **40** performs a first activation control for controlling activation of wireless communication unit **30** and a second activation control for controlling activation of measurement sensor **10** based on the measurement result of acceleration sensor **50**.

(80) That is, control unit **40** performs a switching process for switching between the reporting state and the non-reporting state of wireless communication unit **30** as first activation control. In addition, control unit **40** performs the switching process of switching between the measurement state and the non-measurement state of measurement sensor **10** as the second activation control.

(81) More specifically, storage unit **70** stores, for example, a correspondence table T indicating a correspondence relationship among the measurement result of acceleration sensor **50**, the position of cutting tool **100** with respect to workpiece P, the state of wireless communication unit **30**, and the state of measurement sensor **10**.

(82) The position of cutting tool **100** relative to workpiece P is determined by the angle of the rake face of cutting tool **100** relative to workpiece P, i.e., the angle of the chip delivery surface, and the location of cutting tool **100** relative to workpiece P. Hereinafter, the position of cutting tool **100** with respect to workpiece P may be simply referred to as a “position of cutting tool **100**”.

(83) Control unit **40** determines the position of each cutting tool **100** based on the measurement result of acceleration sensor **50** with reference to correspondence table T stored in storage unit **70**. That is, control unit **40** determines the position of cutting tool **100** including sensor module **110** including control unit **40**. Then, control unit **40** refers to correspondence table T and performs a switching process between the reporting state and the non-reporting state of wireless communication unit **30** and between the measurement state and the non-measurement state of measurement sensor **10** based on the determined position of cutting tool **100**.

(84) (Specific Example 1 of Switching Process)

(85) FIG. 4 is a diagram showing a change in position of a cutting tool when a tool system according to the embodiment of the present disclosure includes one cutting tool. FIG. 5 is a diagram showing an example of a correspondence table stored in a storage unit of a cutting tool according to the embodiment of the present disclosure.

(86) Referring to FIGS. 3 to 5, a position of cutting tool **100** in a state where machining by cutting tool **100** is not performed is referred to as “position 1”, and a position of cutting tool **100** in a state where machining by cutting tool **100** is performed is referred to as “position 2”.

(87) Here, acceleration sensor **50** in cutting tool **100** measures the gravitational acceleration of cutting tool **100** in the radial direction (hereinafter also referred to as “Y-direction”) of turret **52**. According to a change in the position of cutting tool **100** due to rotation of turret **52**, the gravitational acceleration in the Y direction that cutting tool **100** experiences changes.

(88) Storage unit **70** stores a correspondence table T1, which is correspondence table T. Correspondence table T1 indicates that the position of cutting tool **100** is “position 1” when the measurement result of acceleration sensor **50** is other than 1 G. In addition, correspondence table T1 indicates that the position of cutting tool **100** is “position 2” when the measurement result of acceleration sensor **50** is 1 G.

(89) In addition, correspondence table T1 indicates that when the position of cutting tool 100 is “position 1”, wireless communication unit 30 is set to the non-reporting state and measurement sensor 10 is set to the non-measurement state. In addition, correspondence table T1 indicates that when the position of cutting tool 100 is “position 2”, wireless communication unit 30 is set to the reporting state and measurement sensor 10 is set to the measurement state.

(90) Further, correspondence table T1 indicates that acceleration sensor 50 is always driven.

(91) Control unit 40 determines the position of cutting tool 100 based on the measurement result indicated by the analog signal received from acceleration sensor 50 and correspondence table T1. Then, control unit 40 performs the first activation control and the second activation control of which details correspond to the determined positions.

(92) Specifically, control unit 40 determines that the position of cutting tool 100 is “position 2” when wireless communication unit 30 is in the non-reporting state and measurement sensor 10 is in the non-measurement state, and in this case, control unit 40 switches wireless communication unit 30 from the non-reporting state to the reporting state as the first activation control. Further, control unit 40 switches measurement sensor 10 from the non-measurement state to the measurement state as the second activation control.

(93) In addition, control unit 40 determines that the position of cutting tool 100 is “position 2” when wireless communication unit 30 is in the reporting state and measurement sensor 10 is in the measurement state, and in this case, control unit 40 continues the reporting state of wireless communication unit 30 and the measurement state of measurement sensor 10 as the first activation control and the second activation control.

(94) In addition, control unit 40 determines that the position of cutting tool 100 is “position 1” when wireless communication unit 30 is in the reporting state and measurement sensor 10 is in the measurement state, and in this case, control unit 40 switches wireless communication unit 30 from the reporting state to the non-reporting state as the first activation control. In addition, control unit 40 switches measurement sensor 10 from the measurement state to the non-measurement state as second activation control.

(95) In addition, control unit 40 determines that the position of cutting tool 100 is “position 1” when wireless communication unit 30 is in the non-reporting state and measurement sensor 10 is in the non-measurement state, and in this case, control unit 40 continues the non-reporting state of wireless communication unit 30 and the non-measurement state of measurement sensor 10 as the first activation control and the second activation control.

(96) Hereinafter, both the switching process of wireless communication unit 30 from the non-reporting state to the reporting state and the process of continuing the reporting state of wireless communication unit 30 are also referred to as “a switching process of wireless communication unit 30 to the reporting state”. In addition, both the switching process of wireless communication unit 30 from the reporting state to the non-reporting state and the process of continuing the non-reporting state of wireless communication unit 30 are also referred to as “a switching process of wireless communication unit 30 to the non-reporting state”.

(97) In addition, both the switching process of measurement sensor 10 from the non-measurement state to the measurement state and the process of continuing the measurement state of measurement sensor 10 are also referred to as “a switching process of measurement sensor 10 to the measurement state”. In addition, both the switching process of measurement sensor 10 from the measurement state to the non-measurement state and the process of continuing the non-measurement state of measurement sensor 10 are also referred to as “a switching process of measurement sensor 10 to the non-measurement state”.

(98) (Specific Example 2 of Switching Process)

(99) FIG. 6 is a diagram showing a change in position of each cutting tool when the tool system according to the embodiment of the present disclosure includes three cutting tools.

(100) Referring to FIG. 6, here, three cutting tools 100A, 100B and 100C, which correspond to

cutting tool **100**, are mounted on turret **52** at 45° intervals. Further, a step in which machining is performed by cutting tool **100A** is referred to as “step 1”, a step in which machining is performed by cutting tool **100B** is referred to as “step 2”, and a step in which machining is performed by cutting tool **100C** is referred to as “step 3”.

(101) Further, here, acceleration sensor **50** in each cutting tool **100** measures acceleration in two directions. More specifically, acceleration sensor **50** measures the gravitational acceleration of corresponding cutting tool **100** in a direction tangential to turret **52** and along a rotational direction of turret **52** as indicated by arrow R (hereinafter referred to as “X-direction”), and the gravitational acceleration of corresponding cutting tool **100** in a radial direction, that is “Y-direction”, of turret **52**.

(102) Hereinafter, the gravitational acceleration in the X direction may be referred to as an “X value”, and the gravitational acceleration in the Y direction may be referred to as a “Y value”. The X value and the Y value change according to a change in the position of cutting tool **100** caused by the rotation of turret **52**.

(103) In addition, control unit **40** in each cutting tool **100** determines the three positions of each cutting tool **100**, and performs the first activation control and the second activation control of which details correspond to the determined positions. The three positions include a “machining position” in which machining is performed by cutting tool **100**, a “stop position” in which cutting tool **100** is not in contact with workpiece P, and a “preparation position” just before machining is performed by cutting tool **100**.

(104) The “stop position” is a position in a state in which machining by cutting tool **100** is not performed, and is, for example, a position of cutting tool **100** at a stop location before the machining position. The position of cutting tool **100** at a location away from the gravity direction by an angle of 90 degrees or more in the counter-rotation direction of turret **52** may be defined as the “stop position”.

(105) The “preparation position” is a position during the change of the position of cutting tool **100** from the stop position to the machining position, and is, for example, the position of cutting tool **100** at the stop location between the stop position and the machining position. The “preparation position” may be a position of cutting tool **100** at an angle greater than 0 degrees and less than 90 degrees from the gravity direction in the counter-rotation direction of turret **52**. Further, the position of cutting tool **100** at a location between a stop location Ps1, which is the machining position, and a stop location Ps2 just before stop location Ps1 in the rotational direction of turret **52** may be defined as the “preparation position”.

(106) FIG. 7 is a diagram showing an example of a correspondence table stored in a storage unit of a cutting tool according to the embodiment of the present disclosure.

(107) Referring to FIG. 7, a correspondence table T2, which is correspondence table T, is stored in storage unit **70** of each of cutting tools **100A**, **100B**, and **100C**. Correspondence table T2 indicates that the position of cutting tool **100** is the “machining position” when the X value and the Y value are (0 G, 1 G).

(108) In addition, correspondence table T2 indicates that the position of cutting tool **100** is the “preparation position” when the X value and the Y value are (0.5 G, 0.5 G) or (−1 G, 0 G).

(109) In addition, correspondence table T2 indicates that the position of cutting tool **100** is “stop position” when the X value and the Y value are (1 G, 0 G) or (−0.5 G, 0.5 G).

(110) In addition, correspondence table T2 indicates that when the position of cutting tool **100** is the “machining position”, wireless communication unit **30** is set to the reporting state and measurement sensor **10** is set to the measurement state.

(111) In addition, correspondence table T2 indicates that when the position of cutting tool **100** is “preparation position”, wireless communication unit **30** is set to the reporting state and measurement sensor **10** is set to the non-measurement state.

(112) In addition, correspondence table T2 indicates that when the position of cutting tool **100** is

“stop position”, wireless communication unit **30** is set to the non-reporting state and measurement sensor **10** is set to the non-measurement state.

(113) In addition, correspondence table T2 indicates that acceleration sensor **50** is always driven.

(114) (a) Step 1

(115) FIG. **8** is a diagram for explaining the details of the first activation control and the second activation control by the control unit in each cutting tool in step **1** shown in FIG. **6**.

(116) Referring to FIGS. **3** and **6** to **8**, control unit **40** in each of cutting tools **100A**, **100B**, and **100C** performs the first activation control and the second activation control based on the X value and the Y value indicated by the analog signal received from acceleration sensor **50** and correspondence table T2.

(117) More specifically, for example, each time control unit **40** receives an analog signal from acceleration sensor **50**, control unit **40** checks a combination of the X value and the Y value indicated by the analog signal. Then, when the newly acquired combination of the X value and the Y value matches any one of the plurality of combinations of the X value and the Y value indicated in correspondence table T2, control unit **40** determines the corresponding position of cutting tool **100**.

(118) For example, at timings when cutting tools **100A**, **100B**, and **100C** change positions with respect to workpiece P, the determined results of the positions by respective control units **40** are different from each other. Thus, each control unit **40** performs the first activation control and the second activation control having different details from each other based on the determined result.

(119) To be specific, in step **1**, the X value and the Y value by acceleration sensor **50** in cutting tool **100A** are (0 G, 1 G). Control unit **40** in cutting tool **100A** determines that the position of cutting tool **100A** is the “machining position” with reference to correspondence table T2, and performs the switching process of wireless communication unit **30** to the reporting state and the switching process of measurement sensor **10** to the measurement state based on the determined result.

(120) In step **1**, the X value and the Y value by acceleration sensor **50** in cutting tool **100B** are (0.5 G, 0.5 G). Control unit **40** in cutting tool **100B** determines that the position of cutting tool **100B** is the “preparation position” with reference to correspondence table T2, and performs the switching process of wireless communication unit **30** to the reporting state and the switching process of measurement sensor **10** to the non-measurement state based on the determined result.

(121) In step **1**, the X value and the Y value by acceleration sensor **50** in cutting tool **100C** are (1 G, 0 G). Control unit **40** in cutting tool **100C** determines that the position of cutting tool **100C** is the “stop position” with reference to correspondence table T2, and performs the switching process of wireless communication unit **30** to the non-reporting state and the switching process of measurement sensor **10** to the non-measurement state based on the determined result.

(122) (b) Step 2

(123) FIG. **9** is a diagram for explaining the details of the first activation control and the second activation control by the control unit in each cutting tool in step **2** shown in FIG. **6**.

(124) Referring to FIGS. **3**, **6**, **7** and **9**, in step **2**, the X value and the Y value by acceleration sensor **50** at cutting tool **100A** are (−0.5 G, 0.5 G). Control unit **40** in cutting tool **100A** determines the position of cutting tool **100A** is the “stop position”, and performs the switching process of wireless communication unit **30** to the non-reporting state and the switching process of measurement sensor **10** to the non-measurement state based on the determined result.

(125) In step **2**, the X value and the Y value by acceleration sensor **50** in cutting tool **100B** are (0 G, 1 G). Control unit **40** in cutting tool **100B** determines the position of cutting tool **100B** is the “machining position”, and performs the switching process of wireless communication unit **30** to the reporting state and the switching process of measurement sensor **10** to the measurement state based on the determined result.

(126) In step **2**, the X value and the Y value by acceleration sensor **50** in cutting tool **100C** are (0.5 G, 0.5 G). Control unit **40** in cutting tool **100C** determines that the position of cutting tool **100C** is

the “preparation position”, and performs switching process of wireless communication unit **30** to the reporting state and switching process of measurement sensor **10** to the non-measurement state based on the determined result.

(127) (c) Step **3**

(128) FIG. **10** is a diagram for explaining the details of the first activation control and the second activation control by the control unit in each cutting tool in step **3** shown in FIG. **6**.

(129) Referring to FIGS. **3**, **6**, **7**, and **10**, in step **3**, the X value and the Y value from acceleration sensor **50** at cutting tool **100A** are (−1 G, 0 G). Control unit **40** in cutting tool **100A** determines that the position of cutting tool **100A** is the “preparation position”, and performs switching process of wireless communication unit **30** to the reporting state and switching process of measurement sensor **10** to the non-measurement state based on the determined result.

(130) In step **3**, the X value and the Y value by acceleration sensor **50** in cutting tool **100B** are (−0.5 G, 0.5 G). Control unit **40** in cutting tool **100B** determines the position of cutting tool **100B** is the “stop position”, and performs the switching process of wireless communication unit **30** to the non-reporting state and the switching process of measurement sensor **10** to the non-measurement state based on the determined result.

(131) In step **3**, the X value and the Y value by acceleration sensor **50** in cutting tool **100C** are (0 G, 1 G). Control unit **40** in cutting tool **100C** determines the position of cutting tool **100C** is the “machining position”, and performs the switching process of wireless communication unit **30** to the reporting state and the switching process of measurement sensor **10** to the measurement state based on the determined result.

(132) Cutting tool **100** is not limited to the configuration including acceleration sensor **50** that measures gravitational acceleration in two directions. For example, cutting tool **100** may include acceleration sensor **50** that measures gravitational acceleration in three or more directions, or may include a plurality of acceleration sensors **50** each of which measures gravitational acceleration in a single direction. In addition, cutting tool **100** may include single acceleration sensor **50** that measures gravitational acceleration in a single direction.

(133) Cutting tool **100** may further transmit information based on the measurement result by acceleration sensor **50** to management device **200** in addition to the information based on the measurement result by measurement sensor **10**.

(134) In this case, acceleration sensor **50** outputs an analog signal indicating the measurement result to data generation unit **20**. Data generation unit **20** creates measurement information including information based on the measurement result of measurement sensor **10** and information based on the measurement result of acceleration sensor **50**, and outputs the created measurement information to wireless communication unit **30**. Wireless communication unit **30** transmits the measurement information received from data generation unit **20** to wireless base unit **201**.

(135) Further, cutting tool **100** may not include measurement sensor **10**. In this case, wireless communication unit **30** transmits, for example, measurement information including information based on the measurement result by acceleration sensor **50** to wireless base unit **201**. In this case, control unit **40** does not perform the second activation control.

(136) Also in the case where tool system **300** includes two cutting tools **100**, the configuration and operation are similar to those in the case where tool system **300** includes three cutting tools **100** described above.

(137) In addition, control unit **40** is not limited to be configured to determine the position of cutting tool **100**, and may be configured to determine any state of cutting tool **100** and perform the first activation control using the determined result.

(138) [Operation]

(139) Next, an operation procedure when cutting tool **100** in tool system **300** according to the embodiment of the present disclosure performs the first activation control and the second activation control will be described with reference to the drawings.

(140) Each device in the tool system according to the embodiment of the present disclosure is provided with a computer including a memory, and an arithmetic processing unit such as a CPU in the computer reads a program including a part or all of each step of the following flowcharts and sequences from the memory and executes the program. The respective programs of the plurality of devices can be installed from the outside. The respective programs of the plurality of devices are distributed in a state of being stored in recording media.

(141) (Operation Procedure of First Activation Control and Second Activation Control in Case of Specific Example 1)

(142) FIG. 11 is a flowchart defining an operation procedure of the first activation control and the second activation control by the control unit in the case of the specific example 1 shown in FIG. 4.

(143) Referring to FIGS. 4, 5 and 11, first, acceleration sensor 50 measures the gravitational acceleration of cutting tool 100 and outputs an analog signal indicating the measurement result to control unit 40 (step S101).

(144) Next, control unit 40 receives the analog signal output from acceleration sensor 50, and determines the position of cutting tool 100 based on the measurement result indicated by the analog signal and correspondence table T1 stored in storage unit 70 (step S102).

(145) Next, when control unit 40 determines that the position of cutting tool 100 is "Position 2" ("YES" in step S103), control unit 40 performs a switching process of wireless communication unit 30 to the reporting state as the first activation control. That is, control unit 40 activates wireless communication unit 30. In addition, control unit 40 performs a switching process of measurement sensor 10 to the measurement state as the second activation control. That is, control unit 40 activates measurement sensor 10 (step S104).

(146) Next, wireless communication unit 30 establishes a communication connection between cutting tool 100 and management device 200 (step S105). When the communication connection between cutting tool 100 and management device 200 is established, wireless communication unit 30 maintains the connection state.

(147) Next, measurement sensor 10 measures at least one of physical quantities such as accelerations, strains, pressures, sounds, and temperatures, and outputs an analog signal indicating the measured physical quantity to data generation unit 20 (step S106).

(148) Next, data generation unit 20 creates measurement information including the measurement result of measurement sensor 10 or information based on the measurement result, and outputs the created measurement information to wireless communication unit 30. Then, wireless communication unit 30 transmits the measurement information received from data generation unit 20 to management device 200 via wireless base unit 201 (step S107).

(149) Next, acceleration sensor 50 measures the gravitational acceleration of cutting tool 100 again and outputs an analog signal indicating the measurement result to control unit 40 (step S101).

(150) Next, control unit 40 receives the analog signal output from acceleration sensor 50 and determines the position of cutting tool 100 again based on the measurement result indicated by the analog signal and correspondence table T1 stored in storage unit 70 (step S102).

(151) Next, when control unit 40 determines that the position of cutting tool 100 is "Position 1" ("NO" in step S103), control unit 40 performs a switching process of wireless communication unit 30 to the non-reporting state as the first activation control. That is, control unit 40 stops wireless communication unit 30. In addition, control unit 40 performs a switching process of measurement sensor 10 to the non-measurement state as the second activation control. That is, control unit 40 stops measurement sensor 10 (step S108).

(152) The measurement by measurement sensor 10 (step S106) and the transmission of the measurement information by wireless communication unit 30 (step S107) described above are repeated regularly or irregularly until the switching process of wireless communication unit 30 to the non-reporting state and the switching process of measurement sensor 10 to the non-measurement state (step S108) are performed.

(153) (Operation Procedure of First Activation Control and Second Activation Control in Case of Specific Example 2)

(154) FIG. 12 and FIG. 13 are sequence diagrams defining operation procedures of the first activation control and the second activation control by each control unit in the case of the specific example 2 shown in FIG. 6.

(155) Referring to FIGS. 6 to 9, 12, and 13, first, acceleration sensor 50 in each of cutting tools 100A, 100B, and 100C measures the X value and the Y value that are gravitational accelerations of corresponding cutting tool 100, and outputs an analog signal indicating a measurement result to corresponding control unit 40 (step S201).

(156) Next, control unit 40 in each of cutting tools 100A, 100B, and 100C receives the analog signal output from corresponding acceleration sensor 50, and determines the position of corresponding cutting tool 100 based on the measurement result indicated by the analog signal and correspondence table T2 stored in corresponding storage unit 70.

(157) Here, control unit 40 in cutting tool 100A determines the position of cutting tool 100A as the “machining position”. Control unit 40 in cutting tool 100B determines the position of cutting tool 100B as the “preparation position”. Control unit 40 in cutting tool 100C determines that the position of cutting tool 100C is “stop position” (step S202).

(158) Next, control unit 40 in cutting tool 100A performs a switching process of wireless communication unit 30 to the reporting state and a switching process of measurement sensor 10 to the measurement state (step S203).

(159) Next, control unit 40 in cutting tool 100B performs a switching process of wireless communication unit 30 to the reporting state and a switching process of measurement sensor 10 to the non-measurement state (step S204).

(160) Next, control unit 40 in cutting tool 100C performs a switching process of wireless communication unit 30 to the non-reporting state and a switching process of measurement sensor 10 to the non-measurement state (step S205).

(161) Next, wireless communication unit 30 in cutting tool 100A establishes a communication connection between cutting tool 100A and management device 200 (step S206). When the communication connection between cutting tool 100A and management device 200 is established, wireless communication unit 30 maintains the connection state.

(162) Next, wireless communication unit 30 in cutting tool 100B establishes a communication connection between cutting tool 100B and management device 200 (step S207). When the communication connection between cutting tool 100B and management device 200 is established, wireless communication unit 30 maintains the connection state.

(163) Next, measurement sensor 10 in cutting tool 100A measures at least one of physical quantities such as accelerations, strains, pressures, sounds, and temperatures, and outputs an analog signal indicating the measured physical quantity to corresponding data generation unit 20 (step S208).

(164) Next, data generation unit 20 in cutting tool 100A creates measurement information including the measurement result of measurement sensor 10 or information based on the measurement result, and outputs the created measurement information to corresponding wireless communication unit 30. Then, wireless communication unit 30 transmits the measurement information received from data generation unit 20 to management device 200 via wireless base unit 201 (step S209).

(165) Next, acceleration sensor 50 in each of cutting tools 100A, 100B, and 100C measures the X value and the Y value that are the gravitational accelerations of corresponding cutting tool 100 again, and outputs an analog signal indicating the measurement result to corresponding control unit 40 (step S211).

(166) Next, control unit 40 in each of cutting tools 100A, 100B, and 100C receives the analog signal output from corresponding acceleration sensor 50, and determines the position of

corresponding cutting tool **100** based on the measurement result indicated by the analog signal and correspondence table T2 stored in corresponding storage unit **70**.

(167) Here, control unit **40** in cutting tool **100A** determines that the position of cutting tool **100A** as the “stop position”. Further, control unit **40** in cutting tool **100B** determines the position of cutting tool **100B** as the “machining position”. Control unit **40** in cutting tool **100C** determines that the position of cutting tool **100C** as the “preparation position” (step S212).

(168) Next, control unit **40** in cutting tool **100A** performs a switching process of wireless communication unit **30** to the non-reporting state and a switching process of measurement sensor **10** to the non-measurement state (step S213).

(169) The measurement by measurement sensor **10** (step S208) and the transmission of the measurement information by wireless communication unit **30** (step S209) in cutting tool **100A** described above are repeated regularly or irregularly until the switching process of wireless communication unit **30** to the non-reporting state and the switching process of measurement sensor **10** to the non-measurement state (step S213) are performed.

(170) Next, control unit **40** in cutting tool **100B** performs a switching process of wireless communication unit **30** to the reporting state and a switching process of measurement sensor **10** to the measurement state (step S214).

(171) Next, control unit **40** in cutting tool **100C** performs a switching process of wireless communication unit **30** to the reporting state and a switching process of measurement sensor **10** to the non-measurement state (step S215).

(172) Next, wireless communication unit **30** in cutting tool **100C** establishes a communication connection between cutting tool **100C** and management device **200** (step S216). Here, the communication connection between cutting tool **100A** and management device **200** is disconnected, and the communication connection between cutting tool **100B** and management device **200** is maintained.

(173) Next, measurement sensor **10** in cutting tool **100B** measures at least one of physical quantities such as accelerations, strains, pressures, sounds, and temperatures, and outputs an analog signal indicating the measured physical quantity to corresponding data generation unit **20** (step S217).

(174) Next, data generation unit **20** in cutting tool **100B** creates measurement information including the measurement result of measurement sensor **10** or information based on the measurement result, and outputs the created measurement information to corresponding wireless communication unit **30**. Then, wireless communication unit **30** transmits the measurement information received from data generation unit **20** to management device **200** via wireless base unit **201** (step S218).

(175) Next, acceleration sensor **50** in each of cutting tools **100A**, **100B**, and **100C** measures the X value and the Y value that are the gravitational accelerations of corresponding cutting tool **100** again, and outputs an analog signal indicating the measurement result to corresponding control unit **40** (step S221).

(176) Next, control unit **40** in each of cutting tools **100A**, **100B**, and **100C** receives the analog signal output from corresponding acceleration sensor **50**, and determines the position of corresponding cutting tool **100** based on the measurement result indicated by the analog signal and correspondence table T2 stored in corresponding storage unit **70**.

(177) Here, control unit **40** in cutting tool **100A** determines the position of cutting tool **100A** as the “preparation position”. In addition, control unit **40** in cutting tool **100B** determines the position of cutting tool **100B** as the “stop position”. Control unit **40** in cutting tool **100C** determines the position of cutting tool **100C** as the “machining position” (step S222).

(178) Next, control unit **40** in cutting tool **100A** performs a switching process of wireless communication unit **30** to the reporting state and a switching process of measurement sensor **10** to the non-measurement state (step S223).

(179) Next, control unit **40** in cutting tool **100B** performs a switching process of wireless communication unit **30** to the non-reporting state and a switching process of measurement sensor **10** to the non-measurement state (step **S224**).

(180) The measurement by measurement sensor **10** (step **S217**) and the transmission of the measurement information by wireless communication unit **30** (step **S218**) in cutting tool **100B** described above are repeated regularly or irregularly until the switching process of wireless communication unit **30** to the non-reporting state and the switching process of measurement sensor **10** to the non-measurement state (step **S224**) are performed.

(181) Next, control unit **40** in cutting tool **100C** performs a switching process of wireless communication unit **30** to the reporting state and a switching process of measurement sensor **10** to the measurement state (step **S225**).

(182) Next, wireless communication unit **30** in cutting tool **100A** establishes a communication connection between cutting tool **100A** and management device **200** (step **S226**). Here, the communication connection between cutting tool **100B** and management device **200** is disconnected, and the communication connection between cutting tool **100C** and management device **200** is maintained.

(183) Next, measurement sensor **10** in cutting tool **100C** measures at least one of physical quantities such as accelerations, strains, pressures, sounds, and temperatures, and outputs an analog signal indicating the measured physical quantity to corresponding data generation unit **20** (step **S227**).

(184) Next, data generation unit **20** in cutting tool **100C** creates measurement information including the measurement result of measurement sensor **10** or information based on the measurement result, and outputs the created measurement information to corresponding wireless communication unit **30**. Then, wireless communication unit **30** transmits the measurement information received from data generation unit **20** to management device **200** via wireless base unit **201** (step **S228**).

Modification

(185) Wireless communication unit **30** in cutting tool **100** may transmit information indicating the determined result of the position of cutting tool **100** by control unit **40** to management device **200** via wireless base unit **201**.

(186) More specifically, control unit **40** determines the position of cutting tool **100** and creates position information indicating the determined result. Then, control unit **40** outputs the created position information to data generation unit **20**.

(187) Data generation unit **20** creates measurement information including information based on the measurement result of measurement sensor **10** and the position information received from control unit **40**, and outputs the created measurement information to wireless communication unit **30**.

(188) Wireless communication unit **30** transmits the measurement information received from data generation unit **20** to management device **200** via wireless base unit **201**.

(189) Management device **200** displays the detail based on the position information included in the measurement information received from wireless communication unit **30**. For example, management device **200** displays the ID of cutting tool **100** corresponding to wireless communication unit **30**, the position of cutting tool **100** indicated by the position information, and the measurement result of measurement sensor **10** included in the measurement information on a monitor or a display device included in management device **200**.

(190) To be specific, tool system **300** includes three cutting tools **100A**, **100B**, and **100C**.

(191) As described above, when the position of cutting tool **100A** is the machining position, wireless communication unit **30** of cutting tool **100A** is in the reporting state, and measurement sensor **10** of cutting tool **100A** is in the measurement state. Therefore, on the screen **G** displayed by management device **200**, for example, the ID of cutting tool **100A**, the fact that the position of cutting tool **100A** is “machining position”, and the measurement results of measurement sensor **10**

of cutting tool **100A** are displayed.

(192) When the position of cutting tool **100B** is the preparation position, wireless communication unit **30** of cutting tool **100B** is in the reporting state, and measurement sensor **10** of cutting tool **100B** is in the non-measurement state. Therefore, on the screen G, for example, the ID of cutting tool **100B** and the fact that the position of cutting tool **100B** is “preparation position” are displayed, and the measurement result of measurement sensor **10** of cutting tool **100B** is not displayed.

(193) Further, when the position of cutting tool **100C** is the stop position, wireless communication unit **30** of cutting tool **100C** is in the non-reporting state, and measurement sensor **10** of cutting tool **100C** is in the non-measurement state. Therefore, the measurement information from cutting tool **100C** is not transmitted, and on the screen G, for example, the ID of cutting tool **100C** is displayed, and the position of cutting tool **100C** and the measurement result of measurement sensor **10** of cutting tool **100C** are not displayed.

(194) In a system capable of monitoring a state of a cutting tool, a technique capable of realizing a more excellent function is desired.

(195) In contrast, in cutting tool **100** according to the embodiment of the present disclosure, cutting insert **1** has a cutting edge. Holder **2** holds cutting insert **1**. Wireless communication unit **30** transmits information based on a measurement result of a sensor attached to cutting tool **100**. Acceleration sensor **50** is disposed at holder **2**. Control unit **40** performs first activation control for controlling activation of wireless communication unit **30** based on the measurement result of acceleration sensor **50**.

(196) For example, in order to suppress consumption of electric power necessary for wireless transmission of measurement information that is information based on a measurement result, a technique of activating wireless communication unit **30** at a timing of starting machining is desired. On the other hand, in order to control the activation of wireless communication unit **30** at the timing of starting the machining, an input operation by an operator, installation of an external device for detecting the timing of starting the machining, or the like is required.

(197) In contrast, with the above-described configuration, the state of cutting tool **100** can be determined using acceleration sensor **50** mounted on cutting tool **100**. Accordingly, since it is possible to grasp the timing suitable for activation of wireless communication unit **30** in cutting tool **100**, it is possible to perform activation of wireless communication unit **30** at an appropriate timing without requiring an input operation by an operator or installation of an external device.

(198) In addition, by performing activation of wireless communication unit **30** at an appropriate timing, it is possible to suppress consumption of power necessary for wireless transmission of measurement information and to suppress an increase in wireless traffic.

(199) Therefore, in cutting tool **100** according to the embodiment of the present disclosure, it is possible to realize more excellent functions in a system capable of monitoring the state of cutting tool **100**.

(200) In addition, cutting tool **100** according to the embodiment of the present disclosure includes a plurality of acceleration sensors **50** each being acceleration sensor **50** and each configured to measure an acceleration in a single direction, or a single acceleration sensor **50** being acceleration sensor **50** and configured to measure accelerations in a plurality of directions.

(201) For example, in a system in which cutting tool **100** is attached to turret **52** of machining equipment **120** and cutting tool **100** used for machining is automatically replaced by rotating turret **52** for each machining process, gravitational acceleration in the vertical direction that cutting tool **100** experiences has the same value at two locations that are line-symmetric with respect to a straight line passing through the center of turret **52** and extending in the vertical direction.

(202) In contrast, with the configuration as described above, it is possible to measure gravitational acceleration in a plurality of directions, and thus it is possible to more accurately determine the position of cutting tool **100** and to perform activation of wireless communication unit **30** at more appropriate timing.

(203) In addition, in cutting tool **100** according to the embodiment of the present disclosure, control unit **40** is configured to determine the position of cutting tool **100**, and performs the first activation control of which details correspond to the determined position.

(204) With such a configuration, for example, since the timing at which cutting tool **100** reaches the machining position can be grasped, the activation of wireless communication unit **30** in cutting tool **100** can be performed at a more appropriate timing.

(205) In addition, in cutting tool **100** according to the embodiment of the present disclosure, the position includes a machining position in which machining with cutting tool **100** is performed, a stop position in which machining with cutting tool **100** is not performed, and a preparation position between the machining position and the stop position. Control unit **40** is configured to activate wireless communication unit **30** as the first control in a case where cutting tool **100** is in the preparation position.

(206) With such a configuration, before starting machining by cutting tool **100**, it is possible to secure a time for establishing communication connection between cutting tool **100** and management device **200** that is a transmission destination of measurement information. Therefore, it is possible for management device **200** to more reliably acquire the measurement information at the timing of starting the machining.

(207) Further, cutting tool **100** according to the embodiment of the present disclosure further includes measurement sensor **10** of a type different from acceleration sensor **50**. Wireless communication unit **30** is configured to transmit information based on a measurement result of measurement sensor **10**. Control unit **40** is configured to further perform a second activation control of controlling activation of measurement sensor **10** based on the measurement result of acceleration sensor **50**.

(208) In this manner, by performing the second activation control in addition to the first activation control, it is possible to further suppress power consumption.

(209) In addition, in tool system **300** according to the embodiment of the present disclosure, each of first cutting tool **100** and second cutting tool **100** includes cutting insert **1** having a cutting edge, holder **2** to hold cutting insert **1**, wireless communication unit **30** configured to transmit measurement information based on a measurement result of a sensor attached to corresponding cutting tool **100**, acceleration sensor **50** disposed at holder **2**, and control unit **40** configured to perform activation control of controlling activation of wireless communication unit **30** based on a measurement result of acceleration sensor **50**. In addition, control unit **40** of first cutting tool **100** and control unit **40** of second cutting tool **100** are configured to perform the activation control at a timing of a change in the positions of first cutting tool **100** and second cutting tool **100** with respect to workpiece **P**, details of the activation control performed by control unit **40** of first cutting tool **100** and details of the activation control performed by control unit **40** of second cutting tool **100** being different from each other.

(210) For example, in order to suppress consumption of power necessary for wireless transmission of measurement information, a technique of activating wireless communication unit **30** at a timing of starting machining is desired. On the other hand, in order to control the activation of wireless communication unit **30** at the timing of starting the machining, an input operation by an operator, installation of an external device for detecting the timing of starting the machining, or the like is required.

(211) In contrast, with the above-described configuration, the state of cutting tool **100** can be determined using acceleration sensor **50** mounted on cutting tool **100**. Accordingly, since it is possible to grasp the timing suitable for activation of wireless communication unit **30** in cutting tool **100**, it is possible to perform activation of wireless communication unit **30** at an appropriate timing without requiring an input operation by an operator or installation of an external device.

(212) In addition, by performing activation of wireless communication unit **30** at an appropriate timing, it is possible to suppress consumption of power necessary for wireless transmission of

measurement information and to suppress an increase in wireless traffic particularly effectively in tool system **300** including a plurality of cutting tools **100**.

(213) Further, according to the above-described configuration, for example, at the timing at which machining is performed by the first cutting tool, the wireless communication unit in the first cutting tool can be activated, and the wireless communication unit in the second cutting tool can be stopped. That is, the control unit in each cutting tool can perform the first activation control with appropriate details according to the state of each cutting tool.

(214) Therefore, in tool system **300** according to the embodiment of the present disclosure, a more excellent function can be realized in a system capable of monitoring the state of cutting tool **100**.

(215) In tool system **300** according to the embodiment of the present disclosure, control unit **40** determines the position of cutting tool **100** with respect to workpiece P, and creates position information indicating the determined result. Wireless communication unit **30** transmits measurement information including the position information created by control unit **40**. Management device **200** displays the detail based on the position information included in the measurement information received from wireless communication unit **30**.

(216) With such a configuration, in management device **200**, since the position of each cutting tool **100** can be further grasped in addition to the measurement result of the sensor, it is possible to easily confirm whether or not the measurement of the sensor in cutting tool **100** during machining is appropriately performed.

(217) A communication control method according to the embodiment of the present disclosure is a communication control method in tool system **300** including first cutting tool **100** for turning and second cutting tool **100** for turning. Each of first cutting tool **100** and second cutting tool **100** includes cutting insert **1** having a cutting edge, holder **2** holding cutting insert **1**, wireless communication unit **30** configured to transmit information based on a measurement result of a sensor attached to corresponding cutting tool **100** among first cutting tool **100** and second cutting tool **100**, acceleration sensor **50** disposed at holder **2**, and control unit **40** configured to perform activation control of controlling activation of wireless communication unit **30**, based on a measurement result of acceleration sensor **50**. In this communication control method, first, control unit **40** of first cutting tool **100** acquires the measurement result of corresponding acceleration sensor **50**. Next, control unit **40** of second cutting tool **100** acquires the measurement result of corresponding acceleration sensor **50**. Then, control unit **40** in first cutting tool **100** and control unit **40** in second cutting tool **100** perform activation control, details of the activation control performed by control unit **40** of first cutting tool **100** and details of the activation control performed by control unit **40** of second cutting tool **100** being different from each other.

(218) For example, in order to suppress consumption of power necessary for wireless transmission of measurement information, a technique of activating wireless communication unit **30** at a timing of starting machining is desired. On the other hand, in order to control the activation of wireless communication unit **30** at the timing of starting the machining, an input operation by an operator, installation of an external device for detecting the timing of starting the machining, or the like is required.

(219) In contrast, according to the method described above, the state of cutting tool **100** can be determined by using acceleration sensor **50** mounted on cutting tool **100**. Accordingly, since it is possible to grasp the timing suitable for activation of wireless communication unit **30** in cutting tool **100**, it is possible to perform activation of wireless communication unit **30** at an appropriate timing without requiring an input operation by an operator or installation of an external device.

(220) In addition, by performing activation of wireless communication unit **30** at an appropriate timing, it is possible to suppress consumption of power necessary for wireless transmission of measurement information and to suppress an increase in wireless traffic particularly effectively in tool system **300** including a plurality of cutting tools **100**.

(221) Further, according to the above-described method, for example, at the timing at which

machining is performed by the first cutting tool, the wireless communication unit in the first cutting tool can be activated, and the wireless communication unit in the second cutting tool can be stopped. That is, the control unit in each cutting tool can perform the first activation control with appropriate details according to the state of each cutting tool.

(222) Therefore, in the communication control method according to the embodiment of the present disclosure, it is possible to realize more excellent functions in a system capable of monitoring the state of cutting tool **100**.

(223) The above-described embodiments are to be considered in all respects as illustrative and not restrictive. The scope of the present invention is defined not by the above description but by the claims, and is intended to include meanings equivalent to the claims and all modifications within the scope.

(224) The foregoing description includes the following additional features.

Supplementary Note 1

(225) A cutting tool for turning, comprising: a cutting insert having a cutting edge; a holder to hold the cutting insert; a wireless communication unit configured to transmit information based on a measurement result of a sensor attached to the cutting tool; an acceleration sensor disposed at the holder; and a control unit configured to perform first control of controlling activation of the wireless communication unit, based on a measurement result of the acceleration sensor, and wherein the acceleration sensor is configured to measure gravitational acceleration that the cutting tool experiences, and wherein the gravitational acceleration changes according to a position of the cutting tool.

Supplementary Note 2

(226) A tool system comprising: a first cutting tool for turning; and a second cutting tool for turning, wherein each of the first cutting tool and the second cutting tool includes a cutting insert having a cutting edge, a holder to hold the cutting insert, a wireless communication unit configured to transmit measurement information based on a measurement result of a sensor attached to a corresponding cutting tool among the first cutting tool and the second cutting tool, an acceleration sensor disposed at the holder, and a control unit configured to perform activation control of controlling activation of the wireless communication unit, based on a measurement result of the acceleration sensor, and wherein the first cutting tool and the second cutting tool are attached to a turret of machining equipment, the turret rotates for each machining process, and the positions of the first cutting tool and the second cutting tool change due to rotation of the turret.

REFERENCE SIGNS LIST

(227) **1** cutting insert **3A**, **3B** fixing member **2** holder **10** measurement sensor **20** data generation unit **30** wireless communication unit **40** control unit **50** acceleration sensor **51** motor holder **52** turret **53** tool holder **60** battery **70** storage unit **100** cutting tool **110** sensor module **120** machining equipment **200** management device **201** wireless base unit **300** tool system

Claims

1. A cutting tool for turning, comprising: a cutting insert having a cutting edge; a holder to hold the cutting insert; a wireless transmitter configured to transmit information based on a measurement result of a sensor attached to the holder; an acceleration sensor disposed at the holder; and a processor configured to perform first control of controlling activation of the wireless transmitter, based on a measurement result of the acceleration sensor, wherein the acceleration sensor is configured to determine a state of the cutting tool with respect to a workpiece, and wherein the first control includes selectively activating the wireless transmitter based on the state of the cutting tool with respect to the workpiece.
2. The cutting tool according to claim 1, wherein the cutting tool includes a plurality of acceleration sensors each being the acceleration sensor and each configured to measure an acceleration in a

single direction, or a single acceleration sensor being the acceleration sensor and configured to measure accelerations in a plurality of directions.

3. The cutting tool according to claim 1, wherein the processor is configured to determine a position of the cutting tool with respect to the workpiece, and perform the first control of which details correspond to the determined position.

4. The cutting tool according to claim 3, wherein the position includes a machining position in which machining with the cutting tool is performed, a stop position in which machining with the cutting tool is not performed, and a preparation position between the machining position and the stop position, and wherein the processor is configured to activate the wireless transmitter as the first control in a case where the cutting tool is in the preparation position with respect to the workpiece.

5. The cutting tool according to claim 1, further comprising: a measurement sensor of a type different from the acceleration sensor, wherein the wireless transmitter is configured to transmit information based on a measurement result of the measurement sensor, and wherein the processor is configured to further perform second control of controlling activation of the measurement sensor, based on the measurement result of the acceleration sensor.

6. A tool system comprising: a first cutting tool for turning; and a second cutting tool for turning, wherein each of the first cutting tool and the second cutting tool includes a cutting insert having a cutting edge, a holder to hold the cutting insert, a wireless transmitter configured to transmit measurement information based on a measurement result of a sensor attached to the holder, an acceleration sensor disposed at the holder, and a processor configured to perform activation control of controlling activation of the wireless transmitter, based on a measurement result of the acceleration sensor, wherein the processor of the first cutting tool and the processor of the second cutting tool are configured to perform the activation control at a timing of a change in the positions of the first cutting tool and the second cutting tool with respect to a workpiece, details of the activation control performed by the processor of the first cutting tool and details of the activation control performed by the processor of the second cutting tool being different from each other, wherein when the wireless transmitter of the first cutting tool is active, the wireless transmitter of the second cutting tool is inactive, and wherein when the wireless transmitter of the second cutting tool is active, the wireless transmitter of the first cutting tool is inactive.

7. The tool system according to claim 6, further comprising: a management device, wherein the processor is configured to determine a position of the first cutting tool or the second cutting tool with respect to the workpiece and create position information indicating a determined result, wherein the wireless transmitter is configured to transmit the measurement information including the position information created by the processor, and wherein the management device is configured to display details based on the position information included in the measurement information received from the wireless transmitter.

8. A communication control method in a tool system including a first cutting tool for turning and a second cutting tool for turning, each of the first cutting tool and the second cutting tool including a cutting insert having a cutting edge, a holder to hold the cutting insert, a wireless transmitter configured to transmit information based on a measurement result of a sensor attached to the holder, an acceleration sensor disposed at the holder, and a processor configured to perform activation control of controlling activation of the wireless transmitter, based on a measurement result of the acceleration sensor, the communication control method comprising: acquiring, by the processor of the first cutting tool, the measurement result of the corresponding acceleration sensor; acquiring, by the processor of the second cutting tool, the measurement result of the corresponding acceleration sensor; and performing, by the processor of the first cutting tool and the processor of the second cutting tool, the activation control, details of the activation control performed by the processor of the first cutting tool and details of the activation control performed by the processor of the second cutting tool being different from each other, wherein when the wireless transmitter of

the first cutting tool is active, the wireless transmitter of the second cutting tool is inactive, and wherein when the wireless transmitter of the second cutting tool is active, the wireless transmitter of the first cutting tool is inactive.
