

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414445
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Huang; Kuanta et al.

Display device, display panel and manufacturing method thereof

Abstract

A display device, a display panel, and a manufacturing method thereof are proposed. The display panel includes a substrate, a first insulation layer, a first electrode layer, a pixel definition layer, a light-emitting function layer and a second electrode.

Inventors: Huang; Kuanta (Beijing, CN), Lee; Yuhao (Beijing, CN), Zhang; Dacheng (Beijing, CN), Tong; Hui (Beijing, CN), Shen; Xiaobin (Beijing, CN), Li; Shipeng (Beijing, CN), Yang; Chao (Beijing, CN), Li; Dongsheng (Beijing, CN)

Applicant: BOE TECHNOLOGY GROUP CO., LTD. (Beijing, CN)

Family ID: 78270268

Assignee: BOE TECHNOLOGY GROUP CO., LTD. (Beijing, CN)

Appl. No.: 18/336196

Filed: June 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230329044 A1	Oct. 12, 2023

Related U.S. Application Data

continuation parent-doc US 17428326 PENDING WO PCT/CN2021/088701 20210421 child-doc US 18336196
continuation parent-doc WO PCT/CN2020/085955 20200421 PENDING child-doc US 17428326

Publication Classification

Int. Cl.: H10K59/122 (20230101); H10K50/844 (20230101); H10K59/80 (20230101); H10K71/00 (20230101)

U.S. Cl.:

CPC H10K59/122 (20230201); H10K50/844 (20230201); H10K59/80521 (20230201); H10K59/873 (20230201); H10K71/00 (20230201);

Field of Classification Search

CPC: H10K (59/122)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8816339	12/2013	Kawamura et al.	N/A	N/A
9324947	12/2015	Sato et al.	N/A	N/A
9515132	12/2015	Sato et al.	N/A	N/A
9666650	12/2016	Zhang	N/A	N/A
10446633	12/2018	Liu et al.	N/A	N/A
10504976	12/2018	Hanashima et al.	N/A	N/A
2008/0122347	12/2007	Lee	445/24	H10K 59/80521
2012/0049175	12/2011	Ono et al.	N/A	N/A
2012/0208311	12/2011	Bang et al.	N/A	N/A
2012/0228603	12/2011	Nakamura	N/A	N/A
2013/0069085	12/2012	Kang et al.	N/A	N/A
2013/0099221	12/2012	Kawamura et al.	N/A	N/A
2014/0353599	12/2013	Kang	N/A	N/A
2015/0014636	12/2014	Kang	438/26	H10K 50/844
2015/0060815	12/2014	Sato	N/A	N/A
2015/0069361	12/2014	Sato	438/34	H10K 59/1315
2015/0144902	12/2014	Do	257/40	H10K 50/805
2015/0179719	12/2014	Nam	438/4	H10K 50/814
2016/0013438	12/2015	Im et al.	N/A	N/A
2016/0079325	12/2015	Lee et al.	N/A	N/A
2016/0190508	12/2015	Nakamura	N/A	N/A
2016/0204187	12/2015	Sato et al.	N/A	N/A
2016/0260787	12/2015	Kim	N/A	N/A
2016/0284774	12/2015	Zhang	N/A	H10K 77/111
2016/0322437	12/2015	Sakamoto et al.	N/A	N/A
2017/0005286	12/2016	Yun	N/A	H10K 59/35
2017/0062770	12/2016	Jang et al.	N/A	N/A
2017/0084676	12/2016	Jang et al.	N/A	N/A

2017/0117337	12/2016	Kimura	N/A	H10K 71/00
2017/0125738	12/2016	Kim	N/A	H10K 59/879
2017/0317154	12/2016	Heo	N/A	N/A
2018/0062106	12/2017	Heo	N/A	H10K 50/805
2018/0120620	12/2017	Shim	N/A	H10K 59/1315
2018/0123081	12/2017	Baik et al.	N/A	N/A
2018/0190737	12/2017	Yang et al.	N/A	N/A
2018/0366524	12/2017	Bang	N/A	H10K 71/60
2019/0006443	12/2018	Hanashima et al.	N/A	N/A
2019/0006557	12/2018	Kim	N/A	H10K 99/00
2019/0096971	12/2018	Ukigaya	N/A	H10K 59/12
2019/0115403	12/2018	Kang	N/A	N/A
2019/0123121	12/2018	Liu et al.	N/A	N/A
2019/0386248	12/2018	Itonaga	N/A	N/A
2020/0043998	12/2019	Choi et al.	N/A	N/A
2020/0058708	12/2019	Jang et al.	N/A	N/A
2020/0152717	12/2019	Hwang	N/A	N/A
2020/0212146	12/2019	Shin et al.	N/A	N/A
2020/0251541	12/2019	Kim et al.	N/A	N/A
2020/0279896	12/2019	Cao	N/A	N/A
2020/0295300	12/2019	Chung et al.	N/A	N/A
2020/0328264	12/2019	Wu	N/A	H10K 59/12
2021/0091158	12/2020	Kasahara	N/A	N/A
2022/0052136	12/2021	Wang	N/A	H10K 59/38
2022/0344419	12/2021	Wang	N/A	H10K 59/122
2024/0365602	12/2023	Yamazaki et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102405686	12/2011	CN	N/A
103137652	12/2012	CN	N/A
103311265	12/2012	CN	N/A
103887261	12/2013	CN	N/A
104517997	12/2014	CN	N/A
103311265	12/2015	CN	H01L 51/5228
107808895	12/2017	CN	N/A
109216413	12/2018	CN	N/A
110808340	12/2019	CN	N/A
212342660	12/2020	CN	N/A
113451524	12/2020	CN	N/A
4131454	12/2022	EP	N/A
2011044271	12/2010	JP	N/A
2011249089	12/2010	JP	N/A
2019012684	12/2018	JP	N/A
2019067525	12/2018	JP	N/A
2012017498	12/2011	WO	N/A

OTHER PUBLICATIONS

International Search Report from PCT/CN2020/085955 dated Jan. 27, 2021. cited by applicant
Written Opinion from PCT/CN2020/085955 dated Jan. 27, 2021. cited by applicant
Office action from Chinese Application No. 202180000830.2 dated Aug. 4, 2022. cited by applicant
Office action from Chinese Application No. 202080000564.9 dated Sep. 15, 2022. cited by applicant
International Search Report from PCT/CN2021/088701 dated Aug. 2, 2021. cited by applicant
Written Opinion from PCT/CN2021/088701 dated Aug. 2, 2021. cited by applicant
Yokoyama, et al. "Ultra-high-resolution 1058-ppi OLED displays with 2.78-in size using CAAC-IGZO FETs with tandem OLED device and single OLED device", J. of the SID 24/3, 9 pgs., 2016. cited by applicant
Extended European Search Report of EP application No. 21726546.1 dated May 8, 2024. cited by applicant
Notice of Allowance from U.S. Appl. No. 17/264,446 dated Oct. 18, 2023. cited by applicant
Office Action from U.S. Appl. No. 17/428,326 dated Aug. 23, 2024. cited by applicant
Office Action from U.S. Appl. No. 18/336,892 dated Oct. 7, 2024. cited by applicant
Non-final Office of Action of U.S. Appl. No. 18/336,892 dated Jun. 25, 2025. cited by applicant
Non-final Office of Action of U.S. Appl. No. 18/641,532 dated Jul. 17, 2025. cited by applicant

Primary Examiner: Wall; Incent

Attorney, Agent or Firm: Calfee, Halter & Griswold LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION(S) (1) The present application is a Continuation application of U.S. patent application Ser. No. 17/428,326, which is a 35 U.S.C. 371 national phase application of PCT International Application No. PCT/CN2021/088701, which claims the priority of PCT application No. PCT/CN2020/085955, the entire contents of which are all incorporated herein by reference in their entireties.

TECHNICAL FIELD

(1) The present disclosure relates to the field of display technology, and in particular, to a display device, a display panel, and a manufacturing method of the display panel.

BACKGROUND

(2) Currently, Organic Light-Emitting Diode (OLED) display panels are more and more widely used. In an OLED display panel, the light-emitting device usually includes a plurality of OLED light-emitting units distributed in an array, and each light-emitting unit can emit light independently in order to display an image. However, due to reasons in the manufacturing process, the luminescence stability of the OLED light-emitting device still needs to be improved.

(3) It should be noted that the information disclosed in the background section above is only used to enhance understanding the background of the present disclosure, and therefore may include information that does not constitute the prior art known to those of ordinary skill in the art.

SUMMARY

(4) The purpose of the present disclosure is to overcome the above-mentioned shortcomings of the prior art and to provide a display device, a display panel, and a manufacturing method of the display panel.

(5) According to an aspect of the present disclosure, there is provided a display panel, including: a substrate; a first insulation layer, provided on a side of the substrate, wherein the first insulation layer has a plurality of pixel regions distributed in an array and a separation region separating the pixel regions; a first electrode layer, provided on a surface of the first insulation layer away from the substrate and including a plurality of first electrodes, wherein the orthographic projection of each of the first electrodes on the first insulation layer is located in a respective pixel region; a pixel definition layer, provided on the surface of the first insulation layer away from the substrate and exposing each of the first electrodes, wherein the pixel definition layer is formed with a pixel definition groove in a region corresponding to the separation region, a middle part of the pixel definition groove has a first protrusion protruding in a direction away from the substrate, and a sub-groove is formed between the sidewall of the first protrusion and the sidewall of the pixel definition groove; a light-emitting functional layer, covering the pixel definition layer and the first electrodes exposed by the pixel definition layer; and a second electrode, covering the light-emitting function layer.

(6) In an exemplary embodiment of the present disclosure, the two sidewalls of the first protrusion are inclined surfaces that expand toward the substrate, and the two sidewalls of the pixel definition groove are inclined surfaces that contract toward the substrate.

(7) In an exemplary embodiment of the present disclosure, the slope of the sidewall of the first protrusion is different from the slope of the sidewall of the pixel definition groove.

(8) In an exemplary embodiment of the present disclosure, the thickness of the first protrusion is smaller than the depth of the pixel definition groove.

(9) In an exemplary embodiment of the present disclosure, the orthographic projection of the middle part of the pixel definition groove on the first insulation layer is located in the separation region.

(10) In an exemplary embodiment of the present disclosure, the pixel definition layer includes a spacing part and an extension part, wherein the spacing part is located in an area other than the first electrodes, and the pixel definition groove is at least partially provided in the spacing part. Besides, the extension part is connected to the spacing part, extends to the surface of the first electrodes away from the substrate, and covers the first electrodes partially.

(11) In an exemplary embodiment of the present disclosure, the width of the extension part covering any one of the first electrodes is smaller than the width of the spacing part between two adjacent ones of the first electrodes.

(12) In an exemplary embodiment of the present disclosure, at least two of the first electrodes have different thicknesses.

(13) In an exemplary embodiment of the present disclosure, the maximum depth of the pixel definition groove is not more than 60% of the sum of the thicknesses of the light-emitting function layer and the first electrodes.

(14) According to an aspect of the present disclosure, there is provided a display panel including: a substrate; a first insulation layer, provided on a side of the substrate; a first electrode layer, provided on a surface of the first insulation layer away from the substrate and including a plurality of first electrodes; a pixel definition layer, arranged on the surface of the first insulation layer away from the substrate, and exposing each of the first electrodes; a light-emitting functional layer, covering the pixel definition layer and the first electrodes exposed by the pixel definition layer; and a second electrode, covering the light-emitting functional layer, and including a recessed part and a plurality of smooth parts separated by the recessed part, wherein the orthographic projection of each smooth part on the first insulation layer is located in a respective first electrode, at least part of the recessed part is recessed toward the side of the smooth parts close to the substrate, and the orthographic projection of the recessed part on the first insulation layer is at least partially located outside the first electrodes. Besides, a second protrusion is provided in the middle part of the recessed part, and a sub-recess is formed between the side surface of the second protrusion and the

side surface of the recessed part.

(15) In an exemplary embodiment of the present disclosure, the first insulation layer has a plurality of pixel regions distributed in an array and a separation region separating the pixel regions, wherein the orthographic projection of each of the first electrodes on the first insulation layer is located in a respective first electrode.

(16) Besides, the pixel definition layer exposes each of the first electrodes, and a pixel definition groove is formed in a region corresponding to the separation region, wherein the middle part of the pixel definition groove has a first protrusion protruding in a direction away from the substrate, and a sub-groove is formed between the sidewall of the first protrusion and the sidewall of the pixel definition groove.

(17) Further, the orthographic projection of the recessed part on the first insulation layer is at least partially located in the pixel definition groove.

(18) In an exemplary embodiment of the present disclosure, the orthographic projection on the first insulation layer of a point of the sub-recess closest to the substrate is located in the sub-groove.

(19) In an exemplary embodiment of the present disclosure, the recessed part includes a first side surface and a second side surface, wherein the first side surface and the second side surface are respectively connected to two sides of the second protrusion, and the first side surface and the second side surface contract toward the substrate.

(20) In an exemplary embodiment of the present disclosure, the second protrusion includes a first sloped surface, a second sloped surface, and a connection face connected between the first sloped surface and the second sloped surface. The connection face is located on a side of the bottom sides of the first side surface and the second side surface away from the substrate, the first sloped surface is connected to the bottom side of the first side surface, and the second sloped surface is connected to the bottom side of the second side surface.

(21) In an exemplary embodiment of the present disclosure, the minimum thickness of an area of the second electrode corresponding to the first side surface and the second side surface is larger than the minimum thickness of an area corresponding to the first sloped surface and the second sloped surface.

(22) In an exemplary embodiment of the present disclosure, the pixel definition layer includes a spacing part and an extension part, wherein the spacing part is located in an area other than the first electrodes, and the pixel definition groove is provided in the spacing part. Further, the extension part is connected to the spacing part, extends to the surface of the first electrodes away from the substrate, and covers the first electrode partially.

(23) Besides, the second electrode further has a protrusion part that protrudes in a direction away from the substrate, and the smooth parts are connected to the recessed part through the protrusion part, wherein the orthographic projection of the protrusion part on the substrate at least partially overlaps with the orthographic projection of the extension part on the substrate.

(24) In an exemplary embodiment of the present disclosure, of the two protrusion parts connected to two sides of the recessed part, the distance between the substrate and a point of one protrusion part farthest from the substrate is different from the distance between the substrate and a point of the other protrusion part farthest from the substrate.

(25) In an exemplary embodiment of the present disclosure, the display panel further includes: a first encapsulation layer, covering the second electrode and forming a pit in a region corresponding to the recessed part.

(26) In an exemplary embodiment of the present disclosure, the two sidewalls of the pit are narrowed and connected in a direction approaching the substrate.

(27) According to an aspect of the present disclosure, there is provided a method for manufacturing a display panel, including: forming a first insulation layer on a side of a substrate, wherein the first insulation layer has a plurality of pixel regions distributed in an array and a separation region separating the pixel regions; forming a first electrode layer including a plurality of first electrodes

on a surface of the first insulation layer away from the substrate, wherein the orthographic projection of each of the first electrodes on the first insulation layer is located in a respective pixel region; forming a pixel definition layer on the surface of the first insulation layer away from the substrate, and exposing each of the first electrodes, wherein the pixel definition layer is formed with a pixel definition groove in a region corresponding to the separation region, a middle part of the pixel definition groove has a first protrusion protruding in a direction away from the substrate, and a sub-groove is formed between the sidewall of the first protrusion and the sidewall of the pixel definition groove; forming a light-emitting functional layer, the light-emitting functional layer covering the pixel definition layer and the first electrodes exposed by the pixel definition layer; and forming a second electrode covering the light-emitting function layer.

(28) According to an aspect of the present disclosure, there is provided a method for manufacturing a display panel, including: forming a first insulation layer on a side of a substrate; forming a first electrode layer on a surface of the first insulation layer away from the substrate, the first electrode layer including a plurality of first electrodes; forming a pixel definition layer on the surface of the first insulation layer away from the substrate, the pixel definition exposing each of the first electrodes; forming a light-emitting functional layer, the light-emitting functional layer covering the pixel definition layer and the first electrodes exposed by the pixel definition layer; and forming a second electrode covering the light-emitting function layer, wherein the second electrode includes a recessed part and a plurality of smooth parts separated by the recessed part, the orthographic projection of each smooth part on the first insulation layer is located in a respective first electrode, at least part of the recessed part is recessed toward a side of the smooth parts close to the substrate, and the orthographic projection of the recessed part on the first insulation layer is at least partially located in an area other than the first electrodes. Besides, a second protrusion is provided in the middle part of the recessed part, and a sub-recess is formed between the side surface of the second protrusion and the side surface of the recessed part.

(29) According to an aspect of the present disclosure, there is provided a display device including the display panel as described in any one of the above embodiments.

(30) It should be understood that the above general description and the following detailed description are only exemplary and explanatory, and cannot limit the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The drawings herein are incorporated into the specification and constitute a part of the specification, show embodiments in accordance with the present disclosure, and are used together with the specification to explain the principle of the present disclosure. Obviously, the drawings in the following description are only some embodiments of the present disclosure. For those of ordinary skill in the art, other drawings can be obtained based on these drawings without creative work.

(2) FIG. 1 is a schematic diagram of a first display panel according to an embodiment of the present disclosure.

(3) FIG. 2 is a partial electron microscope diagram of a first display panel according to an embodiment of the present disclosure.

(4) FIG. 3 is a schematic diagram of a first display panel according to another embodiment of the present disclosure.

(5) FIG. 4 is a schematic diagram of a first display panel according to still another embodiment of the present disclosure.

(6) FIG. 5 is a top view of a pixel definition layer in a first display panel according to an embodiment of the present disclosure.

- (7) FIG. 6 is a top view of the pixel definition layer and the first electrode in a first display panel according to an embodiment of the present disclosure.
- (8) FIG. 7 is a schematic diagram of a second display panel according to an embodiment of the present disclosure.
- (9) FIG. 8 is an enlarged view of part A in FIG. 7.
- (10) FIG. 9 is a partial electron micrograph of a second display panel according to an embodiment of the present disclosure.
- (11) FIG. 10 is a schematic diagram of a third display panel according to an embodiment of the present disclosure.
- (12) FIG. 11 is a schematic diagram of a third display panel according to another embodiment of the present disclosure.
- (13) FIG. 12 is a schematic diagram of a fourth display panel according to another embodiment of the present disclosure.
- (14) FIG. 13 is an enlarged view of part B in FIG. 12.
- (15) FIG. 14 is a schematic diagram of a method for manufacturing a first display panel according to an embodiment of the present disclosure.
- (16) FIG. 15 is a schematic diagram of a method for manufacturing a first display panel according to another embodiment of the present disclosure.
- (17) FIG. 16 is a schematic diagram of a method for manufacturing a second display panel according to an embodiment of the present disclosure.
- (18) FIG. 17 is a schematic diagram of a method for manufacturing a third display panel according to an embodiment of the present disclosure.
- (19) FIG. 18 is a schematic diagram of a method for manufacturing a fourth display panel according to an embodiment of the present disclosure.

LIST OF REFERENCE NUMERALS

(20) **1**. substrate; **101**. active area; **1011**. source; **1012**. drain; **2**. flat layer; **201**. separation groove; **2011**. sidewall; **2012**. bottom wall; **202**. pixel region; **3**. first electrode layer; **31**, first electrode; **310**, middle part; **311**, edge part; **3110**, flat part; **3111**, sloped part **3111**; **320**, first conductive layer; **321**, second conductive layer; **322**, third conductive layer; **4**. pixel definition layer; **401**, opening; **41**, pixel definition groove; **42**, first protrusion; **40**, sub groove; **400**, spacing part; **410**, extension part; **5**. light-emitting function layer; **501**, light-emitting unit layer; **502**, charge generation layer; **6**, second electrode; **61**, recessed part; **611**, first side surface; **612**, second side surface; **613**, bottom surface; **6131**, first sloped surface; **6132**, second sloped surface; **6133**, connection face; **600**, the second protrusion; **62**, smooth part; **63**, protrusion part; **7**, gate insulation layer; **8**, gate; **9**, second insulation layer; **10**, first wiring layer; **11**. third insulation layer; **12**. second wiring layer; **13**. first encapsulation layer; **1301**; pit; **14**. color film layer; **15**. second encapsulation layer; **16**. transparent cover plate; **17**. light extraction layer.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(21) Example embodiments will now be described more fully with reference to the accompanying drawings. However, the example embodiments can be implemented in various forms, and should not be construed as being limited to the embodiments set forth herein. On the contrary, these embodiments are provided so that the present disclosure will be comprehensive and complete, and fully convey the concept of the example embodiments to those skilled in the art. The same reference numerals in the figures indicate the same or similar structures, and thus their detailed descriptions will be omitted. In addition, the drawings are only schematic illustrations of the present disclosure, and are not necessarily drawn to scale.

(22) The terms “a”, “an”, “the”, “said” and “at least one” are used to indicate the presence of one or more elements/components/etc. The terms “including” and “have” are used to indicate open-ended inclusion, and means that in addition to the listed elements/components/etc., there may be other elements/components/etc. The terms “first”, “second” and “third” etc. are only used as a marker,

not a limit on the number of objects.

(23) In the related art, the OLED display panel includes a driving backplane, a plurality of first electrodes, a pixel definition layer, a light-emitting function layer, a second electrode, and a color filter layer. The array of first electrodes is distributed on the driving backplane. The pixel definition layer is provided on the surface of the driving backplane where the first electrodes are provided, and each first electrode is exposed. The light-emitting function layer covers the pixel definition layer and the surface of the first electrodes away from the driving backplane. The second electrode covers the surface of the light-emitting function layer facing away from the driving backplane. In this way, a plurality of light-emitting units can be defined by the pixel definition layer. When driven by the driving signal, the holes injected by the first electrodes and the electrons injected by the second electrode enter the light-emitting function layer and form excitons, thus the excitons radiating and transitioning to emit photons to form electroluminescence. The color filter layer is arranged on the side of the second electrode away from the driving backplane, and has a plurality of filter regions each corresponding to a respective light-emitting unit, wherein each filter region and the respective light-emitting unit can be used as a sub-pixel.

(24) Since the thickness of the pixel definition layer is greater than that of the first electrode, when the light-emitting function layer is formed by the evaporation process, the light-emitting function layer will appear recessed at a junction part between the first electrode and the pixel definition layer, that is, at the edge of the light-emitting device. Accordingly, the second electrode forms a recessed area, and the distance between the recessed area of the second electrode and the first electrode is relatively short, which is prone to tip discharge or even short circuit, thus affecting the stability of the light-emitting device and making it difficult for the display panel to emit light stably. In the meanwhile, the recessed area of the second electrode corresponds to the first electrode, and therefore also emits light. However, because the recessed area is having a structure recessed toward the driving backplane, rather than a planar structure, light will be emitted in a scattered state across the recessed area, and at least part of the light is skewed toward adjacent sub-pixels. Thus, the light emission of the adjacent sub-pixels interferes with each other, which affects the display effect.

(25) The light-emitting function layer is recessed in a junction part of the second electrode between the first electrode and the pixel definition layer, so that the second electrode forms a recessed area in the area corresponding to the recessed area. The recessed area is directly opposite to the first electrode. That is, the orthographic projection of the recessed area on driving backplane is located in the first electrode, so that a sharp discharge or even a short circuit may occur between the two. At the same time, the recessed area emits light, and because the recessed area is curved in shape, the light will be emitted by the recessed area in a scattered state, which interferes with the light emission of adjacent sub-pixels.

(26) In addition, since the light-emitting functional layer is a continuous film layer so that the sub-pixels are connected to each other, at least a part of the film layer (including but not limited to the hole injection layer) in the light-emitting functional layer will cause crosstalk between adjacent sub-pixels. In particular, for a tandem OLED display panel, the light-emitting function layer includes a plurality of light-emitting unit layers, and two adjacent light-emitting unit layers are connected in series through a charge generation layer. However, the charge generation layer has good charge conduction characteristics, which will cause crosstalk between adjacent sub-pixels and affect the light-emitting effect.

(27) In order to solve at least one of the technical problems in the above-mentioned related art, embodiments of the present disclosure provide various display panels.

(28) A First Display Panel

(29) As shown in FIGS. 1 and 2, the display panel may include a substrate 1, a first insulation layer 2, a first electrode layer 3, a pixel definition layer 4, a light-emitting function layer 5, and a second electrode 6.

(30) The first insulation layer **2** is provided on a side of the substrate **1**, and the surface of the first insulation layer **2** facing away from the substrate **1** is provided with a plurality of separation grooves **201** so as to divide a plurality of pixel regions **202** on the first insulation layer **2**, wherein the pixel regions **202** are arranged in an array.

(31) The first electrode layer **3** is provided on the surface of the first insulation layer **2** away from the substrate **1**, and includes a plurality of first electrodes **31** distributed in an array, wherein the orthographic projection of each first electrode **31** on the first insulation layer **2** is located by a one-to-one correspondence in a respective pixel region **202**. The first electrode **31** includes a flat middle part **310** and an edge part **311** surrounding the middle part **310**. The edge part **311** includes a flat part **3110** surrounding the middle part **310** and a sloped part **3111** connected between the middle part **310** and the flat part **3110**, wherein the thickness of the flat part **3110** is smaller than that of the middle part **310**.

(32) The pixel definition layer **4** is disposed on the surface of the first insulation layer **2** away from the substrate **1** and exposes at least part of the middle part **310**.

(33) The light-emitting function layer **5** covers the pixel definition layer **4** and the middle part **310** and the first insulation layer **2** exposed by the pixel definition layer **4**.

(34) The second electrode **6** covers the light-emitting function layer **5**.

(35) In the display panel according to an embodiment of the present disclosure, the area of the middle part **310** of each first electrode **31** exposed by the pixel definition layer **4** and the corresponding light-emitting function layer **5** and second electrode **6** can constitute a light-emitting device to emit light.

(36) The orthographic projection of the first electrode **31** on the first insulation layer **2** is located in a respective pixel region **202** by a one-to-one correspondence, so that the separation groove **201** is located outside the first electrode **31**. In this case, when the light-emitting functional layer **5** is formed, the light-emitting functional layer **5** can be recessed toward the substrate **1** at the position of the separation groove **201**, so that the second electrode **6** forms a recessed part **61** in this recessed area, and the orthographic projection of the recessed part **61** on the first insulation layer **2** is at least partially located outside the middle part **310** of the first electrode **31**, that is, located outside the light-emitting device. Therefore, the position of the recessed part **61** of the second electrode **6** can be restricted by the separation groove **201**, so as to prevent the tip discharge or even short circuit between the recessed part **61** and the middle part **310**. This helps to ensure that the light-emitting device emits light stably. At the same time, light emission across the recessed part **61** can be reduced or even avoided, thereby reducing the mutual interference of the light emission between adjacent light-emitting devices.

(37) As shown in FIG. 2, FIG. 2 is a partial electron micrograph of a first display panel according to an embodiment of the present disclosure. It can be seen that the orthographic projection of the recessed part **61** on the first insulation layer **2** is at least partially located outside the first electrode **31**, which helps to reduce the risk of sharp discharge with the first electrode **31**. At the same time, this can reduce or even prevent the recessed part **61** from emitting light, and prevent interference with adjacent sub-pixels.

(38) Each part of the first display panel according to an embodiment of the present disclosure will be described in detail below.

(39) As shown in FIG. 1, the material of the substrate **1** can be a semiconductor material such as single crystal silicon or polysilicon, or other hard or soft materials such as glass.

(40) In some embodiments of the present disclosure, a plurality of driving transistors may be provided on the substrate **1**, so as to drive each light-emitting device to emit light for image display. Taking a driving transistor with a top gate structure as an example, the display panel further includes a gate insulation layer **7**, a gate electrode **8**, a second insulation layer **9** and a first wiring layer **10**. The material of the substrate **1** can be semiconductor materials such as monocrystalline silicon or polysilicon, and the substrate **1** includes an active region **101** and a source **1011** and a

drain **1012** located at both ends of the active region **101**. The gate insulation layer **7** covers the active region **101**. The gate **8** is provided on the surface of the gate insulation layer **7** away from the substrate **1**, and the material of the gate **8** may include polysilicon material. The second insulation layer **9** covers the gate **8** and the substrate **1**, and the material of the second insulation layer **9** may include at least one of silicon oxide and silicon nitride. The first wiring layer **10** is provided on the surface of the second insulation layer **9** away from the substrate **1**, and the gate **8**, the source **1011** and the drain **1012** are all connected to the first wiring layer **10** through via holes filled with tungsten or other metals.

(41) In addition, the display panel may further include a third insulation layer **11** and a second wiring layer **12**. The third insulation layer **11** covers the first wiring layer **10** and the second insulation layer **9**, and the second wiring layer **12** is provided on the surface of the third insulation layer **11** away from the substrate **1**. The specific pattern of the second wiring layer **12** is not particularly limited here, and it can be connected to the first wiring layer **10** through via holes filled with tungsten or other metals.

(42) As shown in FIG. 1, the first insulation layer **2** is provided on a side of the substrate **1**. In some embodiments of the present disclosure, the first insulation layer **2** can cover the second wiring layer **12**, and the first electrode **31** can be connected to the second wiring layer **12** through via holes filled with tungsten or other metals. The material of the first insulation layer **2** may include at least one of silicon nitride and silicon oxide, and of course, may also include other insulation materials. For example, the first insulation layer **2** can be planarized by a polishing process.

(43) The surface of the first insulation layer **2** facing away from the substrate **1** can be provided with a plurality of separation grooves **201**. The depth of the separation grooves **201** is smaller than the thickness of the first insulation layer **2**. That is, the separation grooves **201** do not penetrate the first insulation layer **2** in the depth direction. A plurality of pixel regions **202** can be divided on the first insulation layer **2** by the separation grooves **201**, and the pixel regions **202** are arranged in an array.

(44) The shape of the orthographic projection of the pixel region **202** on the substrate **1** can be a rectangle, a pentagon, a hexagon or other polygons. Of course, it can also be a circle or other shapes, which is not specifically limited here. At the same time, the shape and size of different pixel regions **202** may be different.

(45) In some embodiments of the present disclosure, for example, the separation groove **201** may include a first separation groove and a second separation groove, wherein the number of the first separation groove is plural, and each first separation groove extends linearly along the first direction, and distributed along the second direction at intervals. Besides, the number of the second separation grooves is plural, and each second separation groove extends linearly along the second direction, and is spaced apart along the first direction. The first direction and the second direction cross each other. For example, the first direction and the second direction are mutually perpendicular directions. In this way, a plurality of pixel regions **202** distributed in an array can be divided on the first insulation layer **2** by the staggered first separation grooves and second separation grooves.

(46) In other embodiments of the present disclosure, the first separation groove and the second separation groove may also extend along a curved or broken track line, thereby dividing the pixel region **202** of other shapes.

(47) Each separation groove **201** may include two opposite sidewalls **2011** and a bottom wall **2012** connected between the two sidewalls **2011**. To be specific, the two sidewalls **2011** may be arranged in parallel, that is, in the direction perpendicular to the substrate **1**, and the two sidewalls **2011** and their extension surfaces do not intersect. Alternatively, the two sidewalls **2011** may also be arranged at a certain angle.

(48) As shown in FIG. 3, the bottom wall **2012** may be approximately parallel to the surface of the first insulation layer **2** facing away from the substrate **1**. Alternatively, as shown in FIG. 1, the

bottom wall **2012** may also be a curved surface being convex in a direction away from the substrate **1**. The curvature and shape of the curved surface are not particularly limited here. In the cross section perpendicular to the substrate **1**, the contour of the bottom wall **2012** can be roughly arc-shaped, parabolic or wavy. Of course, it can also be other regular or irregular shapes, as long as they are convex in the direction away from the substrate **1**.

(49) In some embodiments of the present disclosure, the two sidewalls **2011** contract toward the bottom wall **2012**. That is, the distance between the two sidewalls **2011** gradually decreases toward the bottom wall **2012**, so that the sidewalls **2011** have a slope with relative to the surface of the first insulation layer **2** away from the substrate **1**, which slope is the angle between the sidewall **2011** and the surface of the first insulation layer **2** away from the substrate **1**. Further, the slope is not less than 70° and not more than 90°. For example, the slope may be 70°, 80°, 90°, and so on.

(50) In some embodiments of the present disclosure, the maximum distance S between the two sidewalls **2011** of the separation groove **201** may be 0.2 μm-0.7 μm, such as 0.2 μm, 0.3 μm, 0.5 μm, or 0.7 μm.

(51) As shown in FIG. **1**, the first electrode layer **3** is provided on the surface of the first insulation layer **2** away from the substrate **1**, and includes a plurality of first electrodes **31** distributed in an array, wherein the orthographic projection of each first electrode **31** on the first insulation layer **2** is located in a respective pixel region **202** by one-to-one correspondence. That is, the boundary of the orthographic projection of each first electrode **31** on the substrate **1** is located in the boundary of the orthographic projection of a respective pixel region **202** on the substrate **1** by a one-to-one correspondence. Only one first electrode **31** is provided in each pixel region **202**. Since the pixel region **202** is separated by the separation groove **201** and the first electrode **31** is located in the pixel region **202**, the separation groove **201** is located outside the first electrode **31**. The shape of the orthographic projection of each first electrode **31** on the first insulation layer **2** may be the same as the shape of the pixel region **202** where it is located, and the boundary of the first electrode **31** is located in the pixel region **202** where it is located.

(52) In a direction parallel to the substrate **1**, at least one first electrode **31** may include a middle part **310** and an edge part **311** surrounding the middle part **310**, wherein the middle part **310** is a flat structure. That is, the middle part **310** is approximately parallel to the surface of the first insulation layer **2** away from the substrate **1**.

(53) In some embodiments of the present disclosure, the boundary of the orthographic projection of the middle part **310** of each first electrode **31** on the substrate **1** may be located within the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1**. That is, the distance L between the boundary of the orthographic projection of the middle part **310** on the substrate **1** and the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1** is not zero. Further, the distance L is not less than 0.15 μm. For example, the distance may be 0.15 μm, 0.2 μm, 0.25 μm, or the like.

(54) The edge part **311** may include a flat part **3110** and a sloped part **3111**, wherein the flat part **3110** is located on the surface of the first insulation layer **2** facing away from the substrate **1** and arranged around the middle part **310**. Besides, the flat part **3110** is approximately parallel to the surface of the first insulation layer **2** away from the substrate **1**. At the same time, the thickness of the flat part **3110** is smaller than the thickness of the middle part **310**. In some embodiments of the present disclosure, the distance between the boundary of the orthographic projection of the flat part **3110** on the substrate **1** and the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1** is not zero. Of course, the boundary of the orthographic projection of the flat part **3110** on the substrate **1** overlaps with the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1**.

(55) The sloped part **3111** is connected between the middle part **310** and the flat part **3110**. That is, the sloped part **3111** surrounds the middle part **310**, and the flat part **3110** is arranged around the sloped part **3111**. In some embodiments of the present disclosure, the slope of the sloped part **3111**

relative to the surface of the first insulation layer **2** away from the substrate **1** is not less than 30°, where the slope is an angle between the surface of the sloped part **3111** and the surface of the first insulation layer **2** away from the substrate **1**.

(56) The first electrode **31** includes a first conductive layer **320**, a second conductive layer **321**, and a third conductive layer **322**. The first conductive layer **320** is provided on the surface of the first insulation layer **2** facing away from the substrate **1**, and the second conductive layer **321** is provided on the surface of the first conductive layer **320** away from the substrate **1**. The third conductive layer **322** is provided on the surface of the second conductive layer **321** away from the substrate **1**, and extends to the first insulation layer **2** at a certain slope, thereby cladding the first conductive layer **320** and the second conductive layer **321** to protect the first conductive layer **320** and the second conductive layer **321**.

(57) The middle part **310** of the first electrode **31** includes an area of the third conductive layer **322** that is located in the surface of the second conductive layer **321** facing away from the substrate **1** and also includes the first conductive layer **320** and the second conductive layer **321**. The edge part **311** includes an area of the third conductive layer **322** cladding the edges of the first conductive layer **320** and the second conductive layer **321**, i.e., an area extending toward the first insulation layer **2**. Exemplarily, the material of the first conductive layer **320** may include titanium (Ti), the material of the second conductive layer **321** includes silver (Ag), and the material of the third conductive layer **322** includes indium tin oxide (ITO). Of course, it may also be other materials.

(58) As shown in FIG. **1**, the pixel definition layer **4** is made of insulation material, and is provided on the surface of the first insulation layer **2** away from the substrate **1** along with the first electrode layer **3**. At the same time, the pixel definition layer **4** exposes at least a portion of the middle part **310** of the first electrode **31**, and the middle part **310** exposed by the pixel definition layer **4** can form, together with the corresponding light-emitting function layer **5** and second electrode **6**, a light-emitting device.

(59) In some embodiments of the present disclosure, each first electrode **31** does not completely cover the pixel region **202** where it is located, and a certain distance exists between the boundary of the orthographic projection of the flat part **3110** of the first electrode **31** on the substrate **1** and the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1**. The pixel definition layer **4** extends at most to the sidewalls **2011** and the bottom wall **2012** of the separation groove **201**. That is, the pixel definition layer **4** is conformally attached to the pixel region **202** not covered by the first electrode **31**, so that the pixel definition layer **4** is recessed in an area corresponding to the separation groove **201**. The pixel definition layer **4** is provided with a plurality of openings **401**, each exposing at least a portion of a respective middle part **310** in a one-to-one correspondence, so that the light-emitting range of the light-emitting device can be defined by the pixel definition layer **4**.

(60) As shown in FIGS. **5** and **6**, in some embodiments of the present disclosure, the opening **401** of the pixel definition layer **4** may have a hexagonal or other polygonal structure. Besides, the first electrode **31** may also have a polygonal structure, and has the same shape as the opening **401**. Of course, the first electrode **31** may also have other shapes.

(61) As shown in FIG. **1**, the light-emitting function layer **5** can be a continuous film layer, and at least partially covers the middle part **310** of each first electrode **31**, that is, covers the area exposed by the opening **401**. At the same time, the light-emitting function layer **5** also covers the pixel definition layer **4** and the area of the first insulation layer **2** that is not covered by the pixel definition layer **4** and the first electrode **31**. When the light-emitting functional layer **5** is formed by evaporation or other processes, the light-emitting functional layer **5** is recessed in a direction approaching toward the substrate **1** in the area corresponding to the separation groove **201**.

(62) In an embodiment of the present disclosure, as shown in FIG. **4**, the light-emitting function layer **5** includes a multilayer light-emitting unit layer **501**, and the hole injection layer, the hole transport layer, the light-emitting layer, the electron transport layer, and the electron injection layer

of each light-emitting unit layer **501** have the same distribution. At the same time, a charge generation layer **502** is provided between two adjacent light-emitting unit layers **501**, so that the light-emitting unit layers **501** are connected in series through the charge generation layer **502**, so as to form a series-type OLED light-emitting device.

(63) In some other embodiments of the present disclosure, the light-emitting function layer **5** includes a light-emitting unit layer, and the light-emitting unit layer includes a hole injection layer, a hole transport layer, a light-emitting layer, an electron transport layer and an electron injection layer, which are sequentially stacked from the first electrode **31** in a direction away from the substrate **1**.

(64) The charge generation layer **502** cannot cover the sidewall **2011** of the separation groove **201**, so that the charge generation layer **502** of the light-emitting device can be cut off by the separation groove **201**, so as to avoid crosstalk between two adjacent light-emitting devices. Of course, the separation groove **201** can also cut off the hole injection layer or other film layers, which can also prevent crosstalk.

(65) As shown in FIG. **1**, the second electrode **6** covers the light-emitting functional layer **5**, and can apply driving signals to the first electrode **31** and the second electrode **6**, so that a portion of the light-emitting functional layer **5** located between the first electrode **31** and the second electrode **6** emits light.

(66) The morphology of the second electrode **6** matches with that of the light-emitting functional layer **5**, which is recessed in the recessed area of the light-emitting functional layer **5** to form a recessed part **61**. Besides, a smooth part **62** is formed in the region corresponding to the middle part **310** of the first electrode **31**, such that the orthographic projection of the recessed part **61** on the first insulation layer **2** is at least partially located outside the middle part **310** of the first electrode **31**, so as to reduce or avoid the tip discharge between the recessed part **61** of the second electrode **6** and the first electrode **31**. The material of the second electrode **6** may be an alloy material. For example, the material of the second electrode **6** may include Mg and Ag. Alternatively, the second electrode **6** may also be an alloy of Al and Li. Of course, the second electrode **6** can also use other alloys or elemental metals, which will not be listed here.

(67) It should be noted that if the pixel definition layer **4** covers the edge of the middle part **310**, the smooth part **62** can be protruding in the direction away from the substrate **1** in the area corresponding to the pixel definition layer **4** covering the middle part **310**, but the height of the protrusion is smaller than the thickness of the first middle part **310** so that the smooth part **62** is generally smooth.

(68) Further, as shown in FIGS. **1** and **2**, in some embodiments of the present disclosure, the lowest point of the recessed part **61** of the second electrode **6** in the cross section perpendicular to the substrate **1** has an orthographic projection on the first insulation layer **2**, which orthographic projection is located completely in the separation groove **201**, that is, completely outside the middle part **310**.

(69) In order to ensure that the separation groove **201** can cut off the hole injection layer, the charge generation layer **502** or other film layers, the separation groove **201** should be made to have a certain depth. But, the separation groove **201** should also be prevented from being too deep to penetrate the first insulation layer **2** and affect the driving device. Therefore, in some embodiments of the present disclosure, in the direction perpendicular to the substrate **1**, the maximum depth **H** of the separation groove **201** is not less than 30% of the sum of the thicknesses of the light-emitting function layer **5** and the first electrode **31**. At the same time, the maximum depth **H** of the separation groove **201** is not more than 60% of the sum of the thickness of the light-emitting function layer **5** and the first electrode **31**. To be specific, the maximum depth of the separation groove **201** refers to a distance, in the direction perpendicular to the substrate **1**, between a point on the bottom wall **2012** of the separation groove **201**, which point is farthest from the surface of the first insulation layer **2** away from the substrate **1**, and the surface of the first insulation layer **2** away

from the substrate **1**. For example, in some embodiments of the present disclosure, the maximum depth **H** of the separation groove **201** is 1000 Å to 3000 Å.

(70) In addition, in some embodiments of the present disclosure, as shown in FIG. **1**, the first type of display panel may further include a first encapsulation layer **13**, a color filter layer **14**, a second encapsulation layer **15**, and a transparent cover plate **16**.

(71) The first encapsulation layer **13** may cover the second electrode **6**. For example, the first encapsulation layer **13** may include two inorganic layers and an organic layer between the two inorganic layers.

(72) In some embodiments of the present disclosure, the first encapsulation layer **13** may be recessed to form a pit **1301** in the region corresponding to the recessed part **61**. Of course, if the thickness of the first encapsulation layer **13** is large, the surface of the first encapsulation layer **13** away from the substrate **1** can also be roughly flat.

(73) The color filter layer **14** is disposed on a side of the first encapsulation layer **13** away from the second electrode **6**, and the color filter layer **14** includes filter regions corresponding to each first electrode **31** one by one. The color filter regions have multiple colors, such as red, blue and green.

(74) The second encapsulation layer **15** may cover the color filter layer **14**, and its structure may be the same as that of the first encapsulation layer **13**.

(75) The transparent cover plate **16** can cover the second encapsulation layer **15**, and its material can be glass or other material.

(76) In addition, in some embodiments of the present disclosure, as shown in FIG. **1**, the first type of display panel may further include a light extraction layer **17**, which covers the surface of the second electrode **6** away from the substrate **1**, and is recessed in an area corresponding to the recessed part **61**. Besides, the first encapsulation layer **13** is provided on the side of the light extraction layer **17** away from the substrate **1**. The refractive index of the light extraction layer **17** is greater than that of the second electrode **6**, which can improve the light extraction efficiency. Besides, the higher the refractive index is, the higher the light extraction efficiency will be.

(77) A Second Display Panel

(78) As shown in FIGS. **7-9**, a second display panel of the present disclosure may include a substrate **1**, a first insulation layer **2**, a first electrode layer **3**, a light-emitting function layer **5**, and a second electrode **6**.

(79) The first insulation layer **2** is provided on a side of the substrate **1**.

(80) The first electrode layer **3** is provided on the surface of the first insulation layer **2** facing away from the substrate **1** and includes a plurality of first electrodes **31**. The first electrode **31** includes a flat middle part **310** and an edge part **311** surrounding the middle part **310**. The edge part **311** includes a flat part **3110** surrounding the middle part **310** and a sloped part **3111** connected between the middle part **310** and the flat part **3110**. The thickness of the flat part **3110** is smaller than that of the middle part **310**.

(81) The light-emitting function layer **5** covers at least a portion of the middle part **310**.

(82) The second electrode **6** covers the light-emitting functional layer **5**, and includes a recessed part **61** and a plurality of smooth parts **62** separated by the recessed part **61**. The orthographic projection of each smooth part **62** on the first insulation layer **2** is located in a respective first electrode **31** by a one-to-one correspondence. The recessed part **61** is recessed toward the side of the smooth part **62** close to the substrate **1**, and the orthographic projection of the recessed part **61** on the first insulation layer **2** is at least partially located outside the middle part **310**.

(83) In the display panel according to an embodiment of the present disclosure, each first electrode **31** and its corresponding light-emitting function layer **5** and second electrode **6** can constitute a light-emitting device, which can emit light. By making the orthographic projection of the recessed part **61** of the second electrode **6** on the first insulation layer **2** at least partially located outside the thicker middle part **310** and not directly facing the middle part **310**, the risk of sharp discharge between the recessed part **61** and the first electrode **31** can be reduced, which helps to ensure that

the light-emitting device emits light stably. At the same time, the light emission across the recessed part **61** can be reduced, thereby reducing the mutual interference of the light emission between adjacent light-emitting devices.

(84) Each part of a second display panel according to an embodiment of the present disclosure will be described in detail below.

(85) In some embodiments of the present disclosure, as shown in FIG. 7, a plurality of driving transistors may be provided on the substrate **1** for driving each light-emitting device to emit light for image display. Taking a driving transistor with a top gate structure as an example, the display panel further includes a gate insulation layer **7**, a gate **8**, a second insulation layer **9**, and a first wiring layer **10**. The material of the substrate **1** can be semiconductor materials such as monocrystalline silicon or polysilicon, and the substrate **1** may include an active region **101** and a source **1011** and a drain **1012** located at both ends of the active region **101**. The gate insulation layer **7** covers the active region **101**. The gate **8** is provided on the surface of the gate insulation layer **7** away from the substrate **1**. The second insulation layer **9** covers the gate **8** and the substrate **1**, and its material may include at least one of silicon oxide and silicon nitride. The first wiring layer **10** is provided on the surface of the second insulation layer **9** away from the substrate **1**, and the gate **8**, the source **1011** and the drain **1012** are all connected to the first wiring layer **10** through via holes filled with tungsten or other metals.

(86) In addition, the display panel may further include a third insulation layer **11** and a second wiring layer **12**. The third insulation layer **11** covers the first wiring layer **10** and the second insulation layer **9**, and the second wiring layer **12** is provided on the surface of the third insulation layer **11** away from the substrate **1**. The specific pattern of the second wiring layer **12** is not particularly limited here, and it can be connected to the first wiring layer **10** through via holes filled with tungsten or other metals.

(87) As shown in FIG. 7, the first insulation layer **2** is provided on a side of the substrate **1**. In some embodiments of the present disclosure, the first insulation layer **2** can cover the second wiring layer **12**, and the first electrode **31** can be connected to the second wiring layer **12** through via holes filled with tungsten or other metals. The material of the first insulation layer **2** may include at least one of silicon nitride and silicon oxide. Of course, it may also include other insulation materials.

(88) As shown in FIG. 7, the first electrode layer **3** is provided on the side of the first insulation layer **2** facing away from the substrate **1**, and includes a plurality of first electrodes **31**. The first electrodes **31** are arranged in an array, and adjacent first electrodes **31** are arranged at intervals.

(89) In a direction parallel to the substrate **1**, each first electrode **31** may include a middle part **310** and an edge part **311** surrounding the middle part **310**, wherein the middle part **310** is a flat structure. That is, the middle part **310** is approximately parallel to the surface the first insulation layer **2** away from the substrate **1**.

(90) The edge part **311** may include a flat part **3110** and a sloped part **3111**, wherein the flat part **3110** is located on the surface of the first insulation layer **2** facing away from the substrate **1** and arranged around the middle part **310**, and the flat part **3110** is approximately parallel to the surface of the first insulation layer **2** away from the substrate **1**. At the same time, the thickness of the flat part **3110** is smaller than the thickness of the middle part **310**. In some embodiments of the present disclosure, there is a non-zero distance between the flat part **3110** and the boundary of the pixel region **202** where it is located. Of course, the boundary of the flat part **3110** may also overlap with the boundary of the pixel region **202**.

(91) The sloped part **3111** is connected between the middle part **310** and the flat part **3110**. That is, the sloped part **3111** surrounds the middle part **310**, and the flat part **3110** is arranged around the sloped part **3111**. In some embodiments of the present disclosure, the slope of the sloped part **3111** with relative to the surface of the first insulation layer **2** away from the substrate **1** is not less than 30°, and the slope refers to the angle between the surface of the sloped part **3111** and the surface of the first insulation layer **2** away from the substrate **1**.

(92) The first electrode **31** includes a first conductive layer **320**, a second conductive layer **321**, and a third conductive layer **322**. The first conductive layer **320** is provided on the surface of the first insulation layer **2** facing away from the substrate **1**, and the second conductive layer **321** is provided on the surface of the first conductive layer **320** away from the substrate **1**. The third conductive layer **322** is provided on the surface of the second conductive layer **321** away from the substrate **1**, and extends at a certain slope to the surface of the pixel region **202** (where it is located) away from the substrate **1**, thereby cladding the first conductive layer **320** and the second conductive layer **321** to protect the first conductive layer **320** and the second conductive layer **321**.

(93) The middle part **310** of the first electrode **31** includes an area of the third conductive layer **322** located in the surface of the second conductive layer **321** facing away from the substrate **1**, and also includes the first conductive layer **320** and the second conductive layer **321**. The edge part **311** includes an area of the third conductive layer **322** cladding the edges of the first conductive layer **320** and the second conductive layer **321**, i.e., an area extending toward the first insulation layer **2**. Exemplarily, the material of the first conductive layer **320** may include titanium (Ti), the material of the second conductive layer **321** includes silver (Ag), and the material of the third conductive layer **322** includes indium tin oxide (ITO). Of course, it may also be other materials.

(94) As shown in FIG. 7, the light-emitting function layer **5** may be a continuous film layer, and covers simultaneously at least part of the area in each first electrode **31**. In some embodiments of the present disclosure, the light-emitting functional layer **5** includes a light-emitting unit layer, and the light-emitting unit layer includes a hole injection layer, a hole transport layer, a light-emitting layer, an electron transport layer, and an electron injection layer that are sequentially stacked from the first electrode **31** in a direction away from the substrate **1**.

(95) In another embodiment of the present disclosure, the light-emitting functional layer **5** includes multiple light-emitting unit layers, and the hole injection layer, the hole transport layer, the light-emitting layer, the electron transport layer, and the electron injection layer of each light-emitting unit layer are distributed in the same arrangement. At the same time, a charge generation layer is provided between two adjacent light-emitting unit layers, so that the light-emitting unit layers are connected in series through the charge generation layer, so as to form a series-type OLED light-emitting device.

(96) As shown in FIG. 7, the second electrode **6** covers the light-emitting functional layer **5**, and a driving signal can be applied to the first electrode **31** and the second electrode **6**, so that a portion of the light-emitting functional layer **5** located between the first electrode **31** and the second electrode **6** emits light. The second electrode **6** includes a plurality of recessed parts **61** and a plurality of smooth parts **62**.

(97) The smooth parts **62** are arranged in an array and are arranged in a one-to-one correspondence with the middle part **310** of a respective first electrode **31**. That is, the orthographic projection of each smooth part **62** on the first insulation layer **2** is located in a respective first electrode **31** by a one-to-one correspondence. The smooth part **62** is parallel or substantially parallel to the middle part **310**.

(98) The recessed part **61** corresponds to the area of the first insulation layer **2** that is not covered by the middle part **310**, and is used to separate the smooth parts **62**, wherein the recessed part **61** is recessed toward the side of the smooth part **62** close to the substrate **1**. The recessed part **61** has a ring structure, and the number is plural, wherein each recessed part **61** surrounds a respective smooth part **62** in a one-to-one correspondence. That is, the recessed part **61** acts as a transition area between two adjacent smooth parts **62**.

(99) The orthographic projection of the recessed part **61** on the substrate **1** is at least partially located outside the middle part **310** of the first electrode **31**, so as to directly face the area other than the first electrode **31** or the edge part **311** with a smaller thickness, but not directly facing the edge part **311** with a larger thickness. This can reduce the risk of tip discharge and short circuit between the recessed part **61** and the first electrode **31**, thereby improving the stability in light

emission of the light-emitting device.

(100) In some embodiments of the present disclosure, in a cross-section perpendicular to the substrate **1**, the orthographic projection on the first insulation layer **2** of the lowest point of the recessed part **61** is located outside the middle part **310**. For example, the lowest point corresponds to one of the sloped part **3111** and the flat part **3110**, so as to avoid the occurrence of tip discharge with the middle part **310**. The lowest point of the recessed part **61** in the cross section perpendicular to the substrate **1** refers to a point, in the cross section perpendicular to the substrate **1**, of the recessed part **61** that is closest to the first electrode **31**, that is, farthest from the smooth part **62**.

(101) It should be noted that the number of the recessed parts **61** in the cross section perpendicular to the substrate **1** may be plural, and the lowest point in different cross sections may be different. For example, the lowest point may be a point in the depth direction that is nearest to the middle part **310** of the first electrode **31**, or some other point in the depth direction, depending on the position of the cross section perpendicular to the substrate **1**.

(102) As shown in FIGS. 7-9, in some embodiments of the present disclosure, the recessed part **61** has two side surfaces, including a first side surface **611**, a second side surface **612**, and a bottom surface **613**, wherein the first side surface **611** and the second side surface **612** are arranged oppositely and connected to both sides of the bottom surface **613**. At the same time, the first side surface **611** and the second side surface **612** may contract in a direction close to the substrate **1**. The first side surface **611** and the second side surface **612** may be curved or flat, and are not specifically limited here.

(103) The bottom surface **613** may be a curved surface that is convex in a direction away from the substrate **1**. In some embodiments of the present disclosure, the bottom surface **613** of the recessed part **61** includes a first sloped surface **6131**, a second sloped surface **6132**, and a connection face **6133**. The first sloped surface **6131** and the second sloped surface **6132** can both be curved or flat. The connection face **6133** is located on a side of the bottom sides of the first side surface **611** and the second side surface **612** facing away from the substrate **1**, and the connection face **6133** is connected between the first sloped surface **6131** and the second sloped surface **6132**. The first sloped surface **6131** is connected to the bottom side of the first side surface **611**, and the second sloped surface **6132** is connected to the bottom side of the second side surface **612**.

(104) In some embodiments of the present disclosure, the slope of the first sloped surface **6131** with relative to the middle part **310** is not less than the slope of the first side surface **611** with relative to the middle part **310**. At the same time, the slope of the second sloped surface **6132** with relative to the middle part **310** is not less than the slope of the second side surface **612** with relative to the middle part **310**.

(105) Furthermore, in the cross section perpendicular to the substrate **1**, the first sloped surface **6131** and the second sloped surface **6132** are symmetrical about the connection face **6133**. That is, the cross section of the first sloped surface **6131** perpendicular to the substrate **1** and the cross section of the second sloped surface **6132** perpendicular to the substrate **1** are symmetrical with respect to the cross section of the connection face **6133** perpendicular to the substrate **1**. At the same time, in the cross section perpendicular to the substrate **1**, the first side surface **611** and the second side surface **612** are symmetrical with respect to the bottom surface **613**. That is, the cross section of the first side surface **611** perpendicular to the substrate **1** and the cross section of the second side surface **612** perpendicular to the substrate **1** are symmetrical with respect to the cross section of the bottom surface **613** perpendicular to the substrate **1**.

(106) In some embodiments of the present disclosure, the minimum thickness of an area of the second electrode **6** corresponding to the first side surface **611** and the second side surface **612** is larger than the minimum thickness of an area of the second electrode **6** corresponding to the first sloped surface **6131** and the second sloped surface **6132**.

(107) Further, as shown in FIG. 7, in some embodiments of the present disclosure, the depth of the recessed part **61** is less than twice the maximum thickness of the second electrode **6**. For example,

the maximum thickness of the second electrode **6** is 90 nm, and the depth of the recessed part **61** is less than 180 nm, such as being 120 nm, 100 nm, 80 nm, 70 nm, 60 nm, 50 nm, 40 nm, etc. The depth of the recessed part **61** refers to the maximum depth of the recessed part **61**, that is, in the direction perpendicular to the substrate **1**, the distance between a point of the recessed part **61** closest to the substrate **1** and the surface of the smooth part **62** away from the substrate **1**.

(108) In some embodiments of the present disclosure, as shown in FIGS. 7 and 8, the orthographic projection of each recessed part **61** on the first insulation layer **2** surrounds the middle part **310** of a first electrode **31**, and the minimum value of the distance between the bottom surface **613** of the recessed part **61** and the middle part **310** of the adjacent first electrode **31** (in the direction perpendicular to the substrate **1**, the distance between the middle part **310** and a point of the recessed part **61** closest to the middle part **310**) is not less than 70% of the total thickness of the smooth part **62** and the light-emitting functional layer **5**. The total thickness of the smooth part **62** and the light-emitting functional layer **5** refers to the sum of the thicknesses of the smooth part **62** and the light-emitting functional layer **5**. For example, if the total thickness of the smooth part **62** and the light-emitting functional layer **5** is about 365 nm, the minimum value of the distance between the bottom of the recessed part **61** in the direction perpendicular to the substrate **1** and the middle part **310** of the adjacent first electrode **31** is about 255 nm.

(109) Further, the maximum value of the distance between the bottom of the recessed part **61** and the middle part **310** of the adjacent first electrode **31** (in the direction perpendicular to the substrate **1**, the maximum value of the distance between the middle part **310** and a point of the recessed part **61** closest to the middle part **310**) is not less than 400 nm, and the maximum value is not greater than 450 nm.

(110) As shown in FIG. 7, in order to facilitate formation of the second electrode **6** above, in some embodiments of the present disclosure, a plurality of separation grooves **201** may be provided on the surface of the first insulation layer **2** away from the substrate **1**, and the depth of the separation groove **201** is smaller than the thickness of the first insulation layer **2**. That is, the separation groove **201** does not penetrate the first insulation layer **2** in the depth direction. A plurality of pixel regions **202** can be divided on the first insulation layer **2** by the separation grooves **201**, and the pixel regions **202** are arranged in an array. The specific structure of the separation groove **201** can refer to the above-mentioned first implementation of the display panel, which will not be described in detail here. At the same time, the second display panel according to an embodiment of the present disclosure further includes a pixel definition layer **4**, which is made of insulation material, and is provided on the surface of the first insulation layer **2** away from the substrate **1** along with the first electrode layer **3**. At the same time, the pixel definition layer **4** exposes at least part of the area of the middle part **310** of the first electrode **31** and is recessed in the area corresponding to the separation groove **201**. The middle part **310** exposed by the pixel definition layer **4**, together with the corresponding light-emitting function layer **5** and the second electrode **6**, can constitute a light-emitting device. The structure of the pixel definition layer **4** can refer to the above-mentioned first implementation of the display panel, which will not be described in detail here.

(111) The light-emitting functional layer **5** also covers the pixel definition layer **4** and the area of the first insulation layer **2** not covered by the pixel definition layer **4** and the first electrode **31**. When the light-emitting functional layer **5** is formed by evaporation or other processes, an area of the light-emitting functional layer **5** corresponding to the separation groove **201** is recessed in a direction close to the substrate **1**. The orthographic projection on the first insulation layer **2** of the recessed part **61** of the second electrode **6** is at least partially located in the range of the separation groove **201**.

(112) In addition, as shown in FIG. 7, the first display panel according to an embodiment of the present disclosure may further include a first encapsulation layer **13**. The first encapsulation layer **13** may cover the second electrode **6**. For example, the first encapsulation layer **13** may include two inorganic layers and an organic layer between the two inorganic layers. The first encapsulation

layer **13** forms a pit **1301** in a region corresponding to the recessed part **61**, the two sidewalls of the pit **1301** are narrowed in the direction toward the substrate **1**, and the two sidewalls are connected.

(113) In addition, the display panel may further include a color filter layer **14**, a second encapsulation layer **15**, and a transparent cover plate **16**.

(114) The color filter layer **14** is disposed on the side of the first encapsulation layer **13** away from the second electrode **6**, and the color filter layer **14** includes filter regions corresponding to each first electrode **31** one by one. The color filter regions have multiple colors, such as red, blue and green.

(115) The second encapsulation layer **15** may cover the color filter layer **14**, and its structure may be the same as that of the first encapsulation layer **13**.

(116) The transparent cover plate **16** can cover the second encapsulation layer **15**, and its material can be glass or other material.

(117) In addition, in some embodiments of the present disclosure, as shown in FIG. 7, the second type of display panel may further include a light extraction layer **17**, which covers the surface of the second electrode **6** facing away from the substrate **1** and is recessed in the area corresponding to the recessed part **61**. The first encapsulation layer **13** is provided on the side of the light extraction layer **17** away from the substrate **1**. The refractive index of the light extraction layer **17** is greater than that of the second electrode **6**, which can improve the light extraction efficiency. The higher the refractive index is, the higher the light extraction efficiency will be.

(118) A Third Display Panel

(119) As shown in FIGS. 10 and 11, the display panel may include a substrate **1**, a first insulation layer **2**, a first electrode layer **3**, a pixel definition layer **4**, a light-emitting function layer **5**, and a second electrode **6**.

(120) The first insulation layer **2** is disposed on a side of the substrate **1**, and the first insulation layer **2** has a plurality of pixel regions **202** distributed in an array and a separation region **201** that separates the pixel regions **202**.

(121) The first electrode layer **3** is provided on the surface of the first insulation layer **2** away from the substrate **1** and includes a plurality of first electrodes **31** distributed in an array. The orthographic projection of each first electrode **31** on the first insulation layer **2** is located in a respective pixel region **202**.

(122) The pixel definition layer **4** is provided on the surface of the first insulation layer **2** away from the substrate **1** and exposes the first electrodes **31**. The pixel definition layer **4** is formed with a pixel definition groove **41** in an area corresponding to the separation region **201**, a middle part of the pixel definition groove **41** has a first protrusion **42** protruding in a direction away from the substrate **1**, and a sub-groove **40** is formed between the sidewall of the first protrusion **42** and the sidewall of the pixel definition groove **41**.

(123) The light-emitting function layer **5** covers the pixel definition layer **4** and the first electrodes **31** exposed by the pixel definition layer **4**.

(124) The second electrode **6** covers the light-emitting function layer **5**.

(125) It should be noted that the middle part of the pixel definition groove **41** in this article refers to any area of the bottom surface between the two sidewalls of the pixel definition groove **41**, and is not limited to an area between the two sidewalls of the pixel definition groove **41** that is equally distanced to the two sidewalls.

(126) In the display panel according to an embodiment of the present disclosure, the area of each first electrode **31** exposed by the pixel definition layer **4** and the corresponding light-emitting function layer **5** and second electrode **6** can be used to form a light-emitting device for light emission.

(127) Since the orthographic projection of the first electrode **31** on the first insulation layer **2** is located in a respective pixel region **202**, the pixel definition groove **41** is located outside the first electrode **31**. When the light-emitting function layer **5** is formed, the light-emitting function layer **5**

can be recessed toward the substrate at the position of the pixel definition groove, so that the recessed part **61** is formed by the second electrode **6** in such recessed area, and the orthographic projection of the recessed part **61** on the first insulation layer **2** is at least partially within the range of the pixel definition layer **4**, at least partly located outside the light-emitting device. Therefore, the position of the recessed part **61** of the second electrode **6** can be restricted by the pixel definition groove **41**, so as to prevent tip discharge or even short circuit between the recessed part **61** and the first electrode **31**, which is beneficial to ensure a stable light emission from the light-emitting device. At the same time, light emission within the range of the recessed part **61** can be reduced or even avoided, thereby reducing the mutual interference of the light emission between adjacent light-emitting devices.

(128) In addition, since a sub-groove **40** is formed between the first protrusion **42** in the middle part of the pixel definition groove **41** and the sidewall of the pixel definition groove **41**, the topography of the middle part of the pixel definition groove **41** is uneven. If the light-emitting function layer **5** contains a charge generation layer, it is difficult for the charge generation layer to be formed on the sidewalls of the two sub-grooves **40**, which facilitates to cut off the charge generation layer in the pixel definition groove **41** and avoids crosstalk between two adjacent light-emitting devices. Of course, the sub-groove **40** of the pixel definition groove **41** can also cut off the hole injection layer or other film layers, which can also prevent crosstalk.

(129) Hereinafter, each part of the third display panel according to an embodiment of the present disclosure will be described in detail.

(130) As shown in FIG. **10**, the material of the substrate **1** may be a semiconductor material such as monocrystalline silicon or polycrystalline silicon, or other hard or soft materials such as glass.

(131) In some embodiments of the present disclosure, a plurality of driving transistors may be provided on the substrate **1**, so as to drive each light-emitting device to emit light to display an image. Taking a driving transistor with a top gate structure as an example, the display panel further includes a gate insulation layer **7**, a gate electrode **8**, a second insulation layer **9**, and a first wiring layer **10**. The material of the substrate **1** can be semiconductor materials such as monocrystalline silicon or polysilicon, and the substrate **1** includes an active region **101** and a source **1011** and a drain **1012** located at both ends of the active region **101**. The gate insulation layer **7** covers the active region **101**. The gate **8** is provided on the surface of the gate insulation layer **7** away from the substrate **1**, and the material of the gate **8** may include polysilicon material. The second insulation layer **9** covers the gate **8** and the substrate **1**, and its material may include at least one of silicon oxide and silicon nitride. The first wiring layer **10** is provided on the surface of the second insulation layer **9** away from the substrate **1**, and the gate **8**, the source **1011** and the drain **1012** are all connected to the first wiring layer **10** through via holes filled with tungsten or other metals.

(132) In addition, the display panel may further include a third insulation layer **11** and a second wiring layer **12**. The third insulation layer **11** covers the first wiring layer **10** and the second insulation layer **9**, and the second wiring layer **12** is provided on the surface of the third insulation layer **11** away from the substrate **1**. The specific pattern of the second wiring layer **12** is not particularly limited here, and it can be connected to the first wiring layer **10** through via holes filled with tungsten or other metals.

(133) As shown in FIG. **10**, the first insulation layer **2** is provided on a side of the substrate **1**. In some embodiments of the present disclosure, the first insulation layer **2** can cover the second wiring layer **12**, and the first electrode **31** can be connected to the second wiring layer **12** through the via holes filled with tungsten or other metals. The material of the first insulation layer **2** may include at least one of silicon nitride and silicon oxide, and of course, may also include other insulation materials. For example, the first insulation layer **2** can be planarized by a polishing process.

(134) The first insulation layer **2** can be divided into a plurality of pixel regions **202**, which pixel regions **202** are arranged in an array and arranged at intervals. The area other than the driving area

201 is the separation region **201**, so that the pixel regions **202** are separated by the separation region **201**.

(135) The shape of the orthographic projection of the pixel region **202** on the substrate **1** can be a rectangle, a pentagon, a hexagon or other polygons. Of course, it can also be a circle or other shapes, which is not specifically limited here. At the same time, the shape and size of different pixel regions **202** may be different.

(136) In some embodiments of the present disclosure, for example, the separation region **201** may include a first separation region and a second separation region. The number of the first separation regions is plural, and each first separation region extends linearly along the first direction, but is distributed along the second direction at intervals. The number of the second separation regions is plural, and each second separation region extends linearly along the second direction, but is distributed at intervals along the first direction. The first direction and the second direction intersect each other. For example, the first direction and the second direction are mutually perpendicular directions. In this way, a plurality of pixel regions **202** distributed in an array can be divided on the first insulation layer **2** by the staggered first separation region and the second separation region.

(137) In other embodiments of the present disclosure, the first separation region and the second separation region may also extend along a curved or broken track line, thereby dividing the pixel regions **202** of other shapes.

(138) As shown in FIG. **10**, the first electrode layer **3** is provided on the surface of the first insulation layer **2** facing away from the substrate **1**, and includes a plurality of first electrodes **31** distributed in an array. The orthographic projections of each first electrode **31** on the first insulation layer **2** are located within a respective pixel region **202** in one-to-one correspondence. That is, the boundary of the orthographic projection of each first electrode **31** on the substrate **1** is located within the boundary of the orthographic projection of a respective pixel region **202** on the substrate **1** in a one-to-one correspondence. Only one first electrode **31** is provided in each pixel region **202**. Since the pixel regions **202** are separated by the separation region **201** and the first electrode **31** is located in the pixel region **202**, the separation region **201** is located outside the first electrode **31**. The shape of the orthographic projection of each first electrode **31** on the first insulation layer **2** may be the same as the shape of the pixel region **202** where it is located, and the boundary of the first electrode **31** is located within the pixel region **202** where it is located.

(139) In a direction parallel to the substrate **1**, at least one first electrode **31** may include a middle part **310** and an edge part **311** surrounding the middle part **310**, wherein the middle part **310** is a flat structure. That is, the middle part **310** is approximately parallel to the surface of the first insulation layer **2** away from the substrate **1**.

(140) In some embodiments of the present disclosure, the boundary of the orthographic projection of the middle part **310** of each first electrode **31** on the substrate **1** may be located within the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1**. That is, the distance L between the boundary of the orthographic projection of the middle part **310** on the substrate **1** and the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1** is not zero. Further, the distance L is not less than $0.15\text{ }\mu\text{m}$. For example, the distance L may be $0.15\text{ }\mu\text{m}$, $0.2\text{ }\mu\text{m}$, $0.25\text{ }\mu\text{m}$, or the like.

(141) The edge part **311** may include a flat part **3110** and a sloped part **3111**, wherein the flat part **3110** is located on the surface of the first insulation layer **2** facing away from the substrate **1** and arranged around the middle part **310**. The flat part **3110** is approximately parallel to the surface of the first insulation layer **2** away from the substrate **1**. At the same time, the thickness of the flat part **3110** is smaller than the thickness of the middle part **310**. In some embodiments of the present disclosure, a non-zero distance exists between the boundary of the orthographic projection of the flat part **3110** on the substrate **1** and the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1**. Of course, the boundary of the orthographic projection of the flat part **3110** on the substrate **1** overlaps with the boundary of the orthographic projection of

the pixel region **202** (where it is located) on the substrate **1**.

(142) The sloped part **3111** is connected between the middle part **310** and the flat part **3110**. That is, the sloped part **3111** surrounds the middle part **310**, and the flat part **3110** is arranged around the sloped part **3111**. In some embodiments of the present disclosure, the slope of the sloped part **3111** with relative to the surface of the first insulation layer **2** away from the substrate **1** is not less than 30° , and the slope refers to the angle between the surface of the sloped part **3111** and the surface of the first insulation layer **2** away from the substrate **1**.

(143) The first electrode **31** may include a first conductive layer **320**, a second conductive layer **321**, and a third conductive layer **322**. The first conductive layer **320** is provided on the surface of the first insulation layer **2** away from the substrate **1**, and the second conductive layer **321** is provided on the surface of the first conductive layer **320** away from the substrate **1**. The third conductive layer **322** is provided on the surface of the second conductive layer **321** away from the substrate **1**, and extends to the first insulation layer **2** at a certain slope, thereby cladding the first conductive layer **320** and the second conductive layer **321** to protect the first conductive layer **320** and the second conductive layer **321**.

(144) The middle part **310** of the first electrode **31** includes an area of the third conductive layer **322** located in the surface of the second conductive layer **321** facing away from the substrate **1**, and also includes the first conductive layer **320** and the second conductive layer **321**. The edge part **311** includes an area of the third conductive layer **322** cladding the edges of the first conductive layer **320** and the second conductive layer **321**, i.e., an area extending toward the first insulation layer **2**. Exemplarily, the material of the first conductive layer **320** may include titanium (Ti), the material of the second conductive layer **321** includes silver (Ag), and the material of the third conductive layer **322** includes indium tin oxide (ITO). Of course, it may also be other materials.

(145) As shown in FIG. **10**, the pixel definition layer **4** is made of insulation material, and is provided on the surface of the first insulation layer **2** away from the substrate **1** along with the first electrode layer **3**, and exposes at least part of the first electrode **31**.

(146) For example, the pixel definition layer **4** is provided with a plurality of openings **401** each exposing at least a portion of a respective middle part **310** in a one-to-one correspondence. The first electrode **31** exposed by the pixel definition layer **4**, together with the corresponding light-emitting function layer **5** and the second electrode **6**, can form a light-emitting device. In some embodiments of the present disclosure, the opening **401** of the pixel definition layer **4** may have a hexagonal or other polygonal structure. The first electrode **31** may also have a polygonal structure, and has the same shape as the opening **401**. Of course, the first electrode **31** can also be other shapes. For details, reference may be made to the implementations of the first display panel in FIG. **5** and FIG. **6**.

(147) As shown in FIG. **10**, the pixel definition layer **4** is formed with a pixel definition groove **41** in a region corresponding to the separation region **201**, and the pixel definition groove **41** can be formed by a photolithography process when the pixel definition layer **4** is formed. Of course, the pixel definition layer **4** can be recessed at the separation groove by providing a separation groove in the separation region **201** of the first insulation layer **2**, so as to form the pixel definition groove **41**.

(148) In some embodiments of the present disclosure, the pixel definition layer **4** may include a spacing part **400** and an extension part **410**, wherein the spacing part **400** is located in an area of the first insulation layer **2** not covered by the first electrode **31**, that is, located in an area other than the first electrode **31**. The pixel definition groove **41** is provided in the spacing part **400**. The extension part **410** is connected to the spacing part **400**, extends to the surface of the first electrode **31** facing away from the substrate **1**, and does not completely cover the first electrode **31**. For example, the extension part **410** extends along the circumferential direction of the first electrode **31** to the surface of the circumferential direction of the middle part **310** away from the substrate **1**, and does not completely cover the middle part **310**, so as to form an opening **401**.

(149) Further, the width of the extension part **410** covering any one of the first electrodes **31** is

smaller than the width of the spacing part **400** between two adjacent first electrodes **31**. That is to say, for any first electrode **31**, the area of the extension part **410** located on the surface of the first electrode **31** facing away from the substrate **1** has a ring structure, and the width of the ring structure is smaller than the width of the spacing part **400** adjacent to the first electrode **31**, wherein the width of the ring structure refers to the distance between the two sidewalls of the ring structure. (150) Based on the above-mentioned pixel definition layer **4**, the middle part of the pixel definition groove **41** may have a first protrusion **42** protruding in a direction away from the substrate **1**, and a sub-groove **40** is formed between the sidewall of the first protrusion **42** and the sidewall of the pixel definition groove **41**. Compared with the case where the middle part of the pixel definition groove **41** is flat, the first protrusion **42** can provide the middle part of the pixel definition groove **41** with a more complicated topography, which is beneficial to cut off the charge generation layer or other film layers of the upper light-emitting functional layer **5**, preventing crosstalk between adjacent light-emitting devices.

(151) It should be noted that the middle part of the sub-groove **40** herein refers to any area of the bottom surface between the two sidewalls of the sub-groove **40**, and is not limited to an area between the two sidewalls of the sub-slot **40** that has an equal distance to the two sidewalls.

(152) In some embodiments of the present disclosure, the two sidewalls of the first protrusion **42** are inclined surfaces that expand toward the substrate **1**, and the two sidewalls of the pixel definition groove **41** are inclined surfaces that contract toward the substrate **1**. That is, the distance between the two sidewalls of the first protrusion **42** gradually increases toward the substrate **1**, and the distance between the two sidewalls of the pixel definition groove **41** gradually decreases toward the substrate **1**. Thus, the sub-groove **40** is a groove whose two sidewalls contract toward the substrate **1**.

(153) Further, the slope of the sidewall of the first protrusion **42** is different from the slope of the sidewall of the pixel definition groove **41**. The slope of the sidewall of the first protrusion **42** is the angle between the sidewall of the first protrusion **42** and the surface of the first insulation layer **2** away from the substrate **1**, and the slope of the sidewall of the pixel definition groove **41** is the angle between the sidewall of the pixel definition groove **41** and the surface of the first insulation layer **2** away from the substrate **1**. If the sidewall of the first protrusion **42** and the sidewall of the pixel definition groove **41** are arc surfaces, the slope for each of the two is a maximum or average value of the angle between the section of the respective arc surface and the surface of the first insulation layer **2** away from the substrate **1**.

(154) Further, the thickness of the first protrusion **42** may be less than the depth of the pixel definition groove **41**, so that the first protrusion **42** does not protrude from the surface of the first insulation layer **2** away from the substrate **1**, but is completely located within the pixel definition groove **41**.

(155) As shown in FIG. **10**, the light-emitting functional layer **5** may be a continuous film layer, and at least partially covers the middle part **310** of each first electrode **31**, that is, covers the area exposed by the opening **401**. At the same time, the light-emitting functional layer **5** may also cover at least part of the pixel definition layer **4**. When the light-emitting functional layer **5** is formed by evaporation or other processes, and the light-emitting functional layer **5** is recessed along a direction toward the substrate **1** in the area corresponding to the pixel definition groove **41**.

(156) In an embodiment of the present disclosure, as shown in FIG. **11**, the light-emitting function layer **5** includes a multi-layer light-emitting unit layer **501**, and the hole injection layer, the hole transport layer, the light-emitting layer, the electron transport layer and the electron injection layer of each light-emitting unit layer **501** have the same way of distribution. At the same time, a charge generation layer **502** is provided between two adjacent light-emitting unit layers **501**, so that the light-emitting unit layers **501** are connected in series through the charge generation layer **502**, so as to form a series-type OLED light-emitting device.

(157) In some other embodiments of the present disclosure, the light-emitting function layer **5**

includes a light-emitting unit layer, and the light-emitting unit layer includes a hole injection layer, a hole transport layer, a light-emitting layer, an electron transport layer, and an electron injection layer which are sequentially stacked from the first electrode **31** in a direction away from the substrate **1**.

(158) The charge generation layer **502** is difficult to cover the sidewalls of the sub-groove **40** of the pixel definition groove **41**, so that the charge generation layer **502** of the light-emitting device can be cut off by the pixel definition groove **41**, so as to avoid crosstalk between two adjacent light-emitting devices. Of course, the pixel definition groove **41** can also cut off the hole injection layer or other film layers, which can also prevent crosstalk.

(159) It should be noted that the light-emitting functional layer **5** is a continuous film layer, but not every film layer is a continuous film layer. For example, in some embodiments of the present disclosure, the light-emitting layer of the light-emitting function layer **5** may include a plurality of light-emitting parts distributed at intervals, and each light-emitting part is located in an opening **401**, so that each light-emitting device has an independent light-emitting part. The materials of different light-emitting parts can be different, so that the light-emitting colors of different light-emitting devices can be different. The other film layers of the light-emitting function layer **5** can be the aforementioned continuous film layers, meaning that each light-emitting device can share these continuous film layers.

(160) As shown in FIG. **10**, the second electrode **6** covers the light-emitting functional layer **5**, and a driving signal can be applied to the first electrode **31** and the second electrode **6**, so that the portion of the light-emitting functional layer **5** located between the first electrode **31** and the second electrode **6** emits light.

(161) There is a certain distance between the second electrode **6** and the first electrode **31**, so that a microcavity can be formed. The light emitted by the light-emitting function layer **5** will be reflected to a certain extent at the first electrode **31** and the second electrode **6**. When the light wavelength and the depth of the microcavity meet the resonance condition, the light is strengthened according to the principle of constructive interference, which is beneficial to improve the brightness of the light-emitting device. However, due to the different wavelengths of light of different colors, the depth of the microcavity of light-emitting devices with different light-emitting colors may be different.

(162) In some embodiments of the present disclosure, the light-emitting colors of the light-emitting layers in different light-emitting devices may be different. In order for the microcavity to have the same enhancement effect on light of different colors, the thickness of the first electrode **31** in the light-emitting devices of different light-emitting colors may be different, so that the depth of the microcavity matches with the wavelength of the light, meaning that the longer the wavelength of light emission is, the greater the depth of the microcavity will be. Further, the first electrode **31** includes a first conductive layer **320**, a second conductive layer **321**, and a third conductive layer **322**. The first conductive layer **320** may be a reflective material, and the depth of the microcavity may be the distance between the first conductive layer **320** and the electrodes **6**. The thickness of the first conductive layer **320** of the two first electrodes **31** can be different, while the thickness of the second conductive layer **321** is the same, and the thickness of the third conductive layer **322** is also the same, so that the thicknesses of the two first electrodes **31** are different.

(163) The morphology of the second electrode **6** matches with that of the light-emitting functional layer **5**, which is recessed in the recessed area of the light-emitting functional layer **5** to form a recessed part **61**, and a smooth part **62** is formed in the region corresponding to the middle part **310** of the first electrode **31**. The orthographic projection of the recessed part **61** on the first insulation layer **2** is at least partially located outside the middle part **310** of the first electrode **31**, so as to reduce or avoid the tip discharge between the first electrode **31** and the recessed part **61** of the second electrode **6**. The material of the second electrode **6** may be an alloy material. For example, the material of the second electrode **6** may include Mg and Ag. Alternatively, the second electrode

6 may also be an alloy of Al and Li. Of course, the second electrode **6** can also use other alloys or elemental metals, which will not be listed here.

(164) In some embodiments of the present disclosure, the extension part **410** of the pixel definition layer **4** covers the edge of the middle part **310**, and the second electrode **6** may protrude in a direction away from the substrate **1** in the region corresponding to the extension part **410**, but is protruding to a height that is smaller than the thickness of the middle part **310**, so that the junction part between the smooth part **62** and the recessed part **61** is generally smooth.

(165) Further, as shown in FIGS. **10** and **11**, in some embodiments of the present disclosure, the lowest point of the recessed part **61** of the second electrode **6** in the cross section perpendicular to the substrate **1** has an orthographic projection on the first insulation layer **2**, which orthographic projection is completely located inside the pixel definition groove **41**, that is, completely located outside the middle part **310**.

(166) In addition, in some embodiments of the present disclosure, as shown in FIGS. **10** and **11**, the third type of display panel may further include a first encapsulation layer **13**, a color filter layer **14**, a second encapsulation layer **15**, and a transparent cover plate **16**.

(167) The first encapsulation layer **13** may cover the second electrode **6**. For example, the first encapsulation layer **13** may include two inorganic layers and an organic layer between the two inorganic layers.

(168) In some embodiments of the present disclosure, the first encapsulation layer **13** may be recessed to form a pit **1301** in the region corresponding to the recessed part **61**. Of course, if the thickness of the first encapsulation layer **13** is large, the surface of the first encapsulation layer **13** away from the substrate **1** can also remain substantially flat.

(169) Further, the color filter layer **14** is disposed on the side of the first encapsulation layer **13** away from the second electrode **6**, and the color filter layer **14** includes filter regions corresponding to each first electrode **31** one by one. The color filter regions have multiple colors, such as red, blue and green.

(170) The second encapsulation layer **15** may cover the color filter layer **14**, and its structure may be the same as that of the first encapsulation layer **13**.

(171) The transparent cover plate **16** can cover the second encapsulation layer **15**, and its material can be glass or other material.

(172) In addition, in some embodiments of the present disclosure, as shown in FIGS. **10** and **11**, the third display panel may further include a light extraction layer **17**, which covers the surface of the second electrode **6** facing away from the substrate **1** and is recessed in the area corresponding to the recessed part **61**. The first encapsulation layer **13** is provided on the side of the light extraction layer **17** away from the substrate **1**. The refractive index of the light extraction layer **17** is greater than that of the second electrode **6**, which can improve the light extraction efficiency. The higher the refractive index is, the higher the light extraction efficiency will be.

(173) A Fourth Display Panel

(174) As shown in FIGS. **12** and **13**, the display panel may include a substrate **1**, a first insulation layer **2**, a first electrode layer **3**, a pixel definition layer **4**, a light-emitting function layer **5**, and a second electrode **6**.

(175) The first insulation layer **2** is provided on a side of the substrate **1**.

(176) The first electrode layer **3** is disposed on the surface of the first insulation layer **2** away from the substrate **1** and includes a plurality of first electrodes **31** distributed in an array.

(177) The pixel definition layer **4** is disposed on the surface of the first insulation layer **2** away from the substrate **1** and exposes the first electrodes **31**.

(178) The light-emitting function layer **5** covers the pixel definition layer **4** and the first electrode **31** and the first insulation layer **2** exposed by the pixel definition layer **4**.

(179) The second electrode **6** covers the light-emitting functional layer **5**, and includes a recessed part **61** and a plurality of smooth parts **62** separated by the recessed part **61**. The orthographic

projection of each smooth part **62** on the first insulation layer **2** is located in a respective first electrode **31**. At least a portion of the recessed part **61** is recessed toward the side of the smooth part **62** close to the substrate **1**. The orthographic projection of the recessed part **61** on the first insulation layer **2** is at least partially located in the pixel definition groove **41**. A second protrusion **600** is provided at a position, corresponding to the first protrusion **42**, of the middle part of the recessed part **61**, and a sub-recess **610** is formed between the side surface of the second protrusion **600** and the side surface of the recessed part **61**.

(180) It should be noted that the middle part of the recessed part **61** in this text refers to any area of the bottom surface between the two sidewalls of the recessed part **61**, and is not limited to an area between the two sidewalls of the recessed part **61** that has an equal distance to the two sidewalls.

(181) In the display panel according to an embodiment of the present disclosure, the area of each first electrode **31** exposed by the pixel definition layer **4** and the corresponding light-emitting function layer **5** and second electrode **6** can constitute a light-emitting device to emit light. Since the orthographic projection of the recessed part **61** of the second electrode **6** on the first insulation layer **2** is at least partially located outside the first electrode, it can prevent a sharp discharge or even a short circuit generated between the recessed part **61** and the first electrode **31**, which is beneficial to ensure a stable light emission by the light-emitting device. At the same time, light emission within the range of the recessed part **61** can be reduced or even avoided, thereby reducing the mutual interference of the light emission between adjacent light-emitting devices.

(182) Hereinafter, each part of the fourth display panel according to an embodiment of the present disclosure will be described in detail.

(183) As shown in FIG. **12** and FIG. **13**, in some embodiments of the present disclosure, a plurality of driving transistors may be provided on the substrate **1**, for driving each light-emitting device to emit light for image display. Taking a driving transistor with a top gate structure as an example, the display panel further includes a gate insulation layer **7**, a gate **8**, a second insulation layer **9** and a first wiring layer **10**. The material of the substrate **1** can be semiconductor materials such as monocrystalline silicon or polysilicon, and the substrate **1** includes an active area **101** and a source **1011** and a drain **1012** located at both ends of the active area **101**. The gate insulation layer **7** covers the active area **101**. The gate **8** is provided on the surface of the gate insulation layer **7** away from the substrate **1**, and the material of the gate **8** may include polysilicon material. The second insulation layer **9** covers the gate **8** and the substrate **1**, and its material may include at least one of silicon oxide and silicon nitride. The first wiring layer **10** is provided on the surface of the second insulation layer **9** away from the substrate **1**, and the gate **8**, the source **1011** and the drain **1012** are all connected to the first wiring layer **10** through via holes filled with tungsten or other metals.

(184) In addition, the display panel may further include a third insulation layer **11** and a second wiring layer **12**. The third insulation layer **11** covers the first wiring layer **10** and the second insulation layer **9**, and the second wiring layer **12** is provided on the surface of the third insulation layer **11** away from the substrate **1**. The specific pattern of the second wiring layer **12** is not particularly limited here, and it can be connected to the first wiring layer **10** through via holes filled with tungsten or other metals.

(185) As shown in FIGS. **12** and **13**, the first insulation layer **2** is provided on a side of the substrate **1**. In some embodiments of the present disclosure, the first insulation layer **2** can cover the second wiring layer **12**, and the first electrode **31** may be connected to the second wiring layer **12** through vias filled with tungsten or other metals. The material of the first insulation layer **2** may include at least one of silicon nitride and silicon oxide, and of course, may also include other insulation materials. For example, the first insulation layer **2** can be planarized by a polishing process.

(186) The first insulation layer **2** has a separation region **201** through which a plurality of pixel regions **202** can be separated on the first insulation layer **2**, and the pixel regions **202** are arranged in an array.

(187) As shown in FIGS. **12** and **13**, the first electrode layer **3** is provided on the surface of the first

insulation layer **2** away from the substrate **1** and includes a plurality of first electrodes **31** distributed in an array.

(188) In some embodiments of the present disclosure, the orthographic projection of each first electrode **31** on the first insulation layer **2** is located within a respective pixel region **202** in a one-to-one correspondence. That is, the boundary of the orthographic projection of each first electrode **31** on the substrate **1** is located within the boundary of the orthographic projection of a respective pixel region **202** on the substrate **1** in a one-to-one correspondence. Only one first electrode **31** is provided in each pixel region **202**. Since the pixel regions **202** are separated by the separation region **201** and the first electrode **31** is located in the pixel region **202**, the separation region **201** is located outside the first electrode **31**. The shape of the orthographic projection of each first electrode **31** on the first insulation layer **2** may be the same as the shape of the pixel region **202** where it is located, and the boundary of the first electrode **31** is located within the pixel region **202** where it is located.

(189) In a direction parallel to the substrate **1**, at least one first electrode **31** may include a middle part **310** and an edge part **311** surrounding the middle part **310**, wherein the middle part **310** is a flat structure. That is, the middle part **310** is approximately parallel to the surface of the first insulation layer **2** away from the substrate **1**.

(190) In some embodiments of the present disclosure, the boundary of the orthographic projection of the middle part **310** of each first electrode **31** on the substrate **1** may be located within the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1**. That is, the boundary of the orthographic projection of the middle part **310** on the substrate **1** and the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1** have a distance L that is not zero. Further, the distance L is not less than $0.15\text{ }\mu\text{m}$. For example, the distance L may be $0.15\text{ }\mu\text{m}$, $0.2\text{ }\mu\text{m}$, $0.25\text{ }\mu\text{m}$, or the like.

(191) The edge part **311** may include a flat part **3110** and a sloped part **3111**, wherein the flat part **3110** is located on the surface of the first insulation layer **2** facing away from the substrate **1** and arranged around the middle part **310**. The flat part **3110** is approximately parallel to the surface of the first insulation layer **2** away from the substrate **1**. At the same time, the thickness of the flat part **3110** is smaller than the thickness of the middle part **310**. In some embodiments of the present disclosure, there is a non-zero distance between the boundary of the orthographic projection of the flat part **3110** on the substrate **1** and the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1**. Of course, the boundary of the orthographic projection of the flat part **3110** on the substrate **1** overlaps with the boundary of the orthographic projection of the pixel region **202** (where it is located) on the substrate **1**.

(192) The sloped part **3111** is connected between the middle part **310** and the flat part **3110**. That is, the sloped part **3111** surrounds the middle part **310**, and the flat part **3110** is arranged around the sloped part **3111**. In some embodiments of the present disclosure, the slope of the sloped part **3111** with relative to the surface of the first insulation layer **2** away from the substrate **1** is not less than 30° , and the slope refers to the angle between the surface of the sloped part **3111** and the surface of the first insulation layer **2** away from the substrate **1**.

(193) As shown in FIGS. **12** and **13**, the first electrode **31** may include a first conductive layer **320**, a second conductive layer **321**, and a third conductive layer **322**. The first conductive layer **320** is disposed on the surface of the first insulation layer **2** away from the substrate **1**. The second conductive layer **321** is provided on the surface of the first conductive layer **320** away from the substrate **1**. The third conductive layer **322** is provided on the surface of the second conductive layer **321** away from the substrate **1**, extends to the first insulation layer at a certain slope, and clades the first conductive layer **320** and the second conductive layer **321** to protect the first conductive layer **320** and the second conductive layer **321**.

(194) The middle part **310** of the first electrode **31** includes an area of the third conductive layer **322** located on the surface of the second conductive layer **321** facing away from the substrate **1**,

and also includes the first conductive layer **320** and the second conductive layer **321**. The edge part **311** includes an area of the third conductive layer **322** cladding the edges of the first conductive layer **320** and the second conductive layer **321**, i.e., an area extending toward the first insulation layer **2**. Exemplarily, the material of the first conductive layer **320** may include titanium (Ti), the material of the second conductive layer **321** includes silver (Ag), and the material of the third conductive layer **322** includes indium tin oxide (ITO). Of course, it may also be other materials. (195) As shown in FIG. **12** and FIG. **13**, the pixel definition layer **4** is made of insulation material, and is provided on the surface of the first insulation layer **2** away from the substrate **1** along with the first electrode layer **3**, and exposes at least a part of the first electrode **31**.

(196) For example, the pixel definition layer **4** is provided with a plurality of openings **401**, each opening exposing at least a part of a respective middle part **310** in a one-to-one correspondence. The first electrode **31** exposed by the pixel definition layer **4** can form a light-emitting device along with the corresponding light-emitting function layer **5** and second electrode **6**. In some embodiments of the present disclosure, the opening **401** of the pixel definition layer **4** may have a hexagonal or other polygonal structure, and the first electrode **31** may also have a polygonal structure and have the same shape as the opening **401**. Of course, the first electrode **31** may also have other shapes. For details, please refer to the first type of display panel shown in FIG. **5** and FIG. **6**.

(197) As shown in FIGS. **12** and **13**, the pixel definition layer **4** is formed with a pixel definition groove **41** in an area corresponding to the separation region **201**.

(198) Based on the above-mentioned pixel definition layer **4**, the middle part of the pixel definition groove **41** may have a first protrusion **42** protruding in a direction away from the substrate **1**, and a sub-groove **40** is formed between the sidewall of the first protrusion **42** and the sidewall of the pixel definition groove **41**. Compared with the case where the middle part of the pixel definition groove **41** is flat, the first protrusion **42** can provide the middle part of the pixel definition groove **41** with a more complicated topography, which is beneficial to cut off the charge generation layer or other film layers of the upper light-emitting functional layer **5** and prevent crosstalk between adjacent light-emitting devices. Further, in order to ensure that the pixel definition groove **41** has a sufficient depth to cut off some of the upper film layers, the middle part of the pixel definition groove **41** can be located in the separation region **201**. That is, one or more point of the pixel definition groove **41** closest to the substrate **1** is located on the side of the first insulation layer **2** facing away from the substrate **1**. Correspondingly, the middle part of the sub-groove **40** is located in the separation region **201**.

(199) The detailed structure of the pixel definition layer **4** and the pixel definition groove **41** can refer to the above-mentioned implementation of the third display panel, which will not be described in detail here.

(200) As shown in FIGS. **12** and **13**, the light-emitting functional layer **5** can be a continuous film layer, and at least partially covers the middle part **310** of each first electrode **31**, that is, covers the area exposed by the opening **401**. At the same time, the light-emitting functional layer **5** also covers the pixel definition layer **4** and the area of the first insulation layer **2** not covered by the pixel definition layer **4** and the first electrode **31**. When the light-emitting function layer **5** is formed by evaporation or other processes, the light-emitting function layer **5** is recessed toward the substrate **1** in an area corresponding to the pixel definition groove **41**.

(201) In an embodiment of the present disclosure, referring to the light-emitting functional layer **5** of the third display panel, as shown in FIG. **10**, the light-emitting functional layer **5** includes a multilayer light-emitting unit layer **501**, wherein the hole injection layer, the hole transport layer, the light-emitting layer, the electron transport layer, and the electron injection layer of each light-emitting unit layer **501** are the same in distribution. At the same time, a charge generation layer **502** is provided between two adjacent light-emitting unit layers **501**, so that the light-emitting unit layers **501** are connected in series through the charge generation layer **502**, so as to form a series-

type OLED light-emitting device.

(202) In some other embodiments of the present disclosure, the light-emitting function layer **5** includes a light-emitting unit layer, wherein the light-emitting unit layer includes a hole injection layer, a hole transport layer, a light-emitting layer, an electron transport layer, and an electron injection layer which are sequentially stacked from the first electrode **31** in a direction away from the substrate **1**.

(203) The charge generation layer **502** is difficult to cover the sidewalls of the sub-groove **40** of the pixel definition groove **41**, so that the charge generation layer **502** of the light-emitting device can be cut off by the pixel definition groove **41**, so as to avoid crosstalk between two adjacent light-emitting devices. Of course, the pixel definition groove **41** can also cut off the hole injection layer or other film layers, which can also prevent crosstalk.

(204) As shown in FIGS. **12** and **13**, the second electrode **6** covers the light-emitting function layer **5**, and includes a recessed part **61** and a plurality of smooth parts **62** separated by the recessed part **61**. The orthographic projection of each smooth part **62** on the first insulation layer **2** is positioned in a respective first electrode **31** in a one-to-one correspondence. The recessed part **61** is recessed toward the side of the smooth part **62** close to the substrate **1**, and the orthographic projection of the recessed part **61** on the first insulation layer **2** is at least partially located outside the first electrode **31**. A second protrusion **600** is provided in the middle part of the recessed part **61**, and a sub-recess **610** is formed between the side surface of the second protrusion **600** and the side surface of the recessed part **61**.

(205) In some embodiments of the present disclosure, the orthographic projection of the recessed part **61** on the first insulation layer **2** is at least partially located in the pixel definition groove **41**. Further, a second protrusion **600** is provided at a position in the middle part of the recessed part **61** corresponding to the first protrusion **42**, and a sub-recess **610** is formed between the side surface of the second protrusion **600** and the side surface of the recessed part **61**. The orthographic projection on the first insulation layer **2** of a point of the sub-recess **610** closest to the substrate **1** is located in the sub-groove **40**.

(206) The smooth parts **62** are arranged in an array and are arranged in a one-to-one correspondence to the middle part **310** of a respective first electrode **31**. That is, the orthographic projection of each smooth part **62** on the first insulation layer **2** is located within a respective first electrode **31** in a one-to-one correspondence. The smooth part **62** is parallel or substantially parallel to the middle part **310**.

(207) The recessed part **61** corresponds to the area of the first insulation layer **2** that is not covered by the middle part **310**, and is used to separate the smooth parts **62**. The recessed part **61** is recessed toward the side of the smooth part **62** close to the substrate **1**. The recessed part **61** has a ring structure, and the number is plural. Each recessed part **61** surrounds a respective smooth part **62** in a one-to-one correspondence. That is, the recessed part **61** is a transition area between two adjacent smooth parts **62**.

(208) The orthographic projection of the recessed part **61** on the substrate **1** is at least partially located outside the middle part **310** of the first electrode **31**, so as to directly face the area other than the first electrode **31** or the edge part **311** with a smaller thickness, but not directly face the edge part **311** with a larger thickness. This can reduce the risk of tip discharge and short circuit between the recessed part **61** and the first electrode **31**, thereby improving the stability of the light-emitting device.

(209) In some embodiments of the present disclosure, on a cross section perpendicular to the substrate **1**, the orthographic projection of the lowest point of the recessed part **61** on the first insulation layer **2** is located outside the middle part **310**. For example, the lowest point corresponds to one of the sloped part **3111** and the flat part **3110**, so as to avoid the occurrence of tip discharge between the flat part **310** and the lowest point. The lowest point of the recessed part **61** on the cross section perpendicular to the substrate **1** refers to a point of the recessed part **61** which point is, on

the cross section perpendicular to the substrate **1**, closest to the first electrode **31**, that is, farthest from the smooth part **62**.

(210) It should be noted that the number of recessed part **61** in the section perpendicular to the substrate **1** may be plural, and the lowest point on different sections may be different. For example, the lowest point may be a point that is closest to the middle part of the first electrode **31** in the depth direction, or another point in the depth direction, depending on the position of the cross section perpendicular to the substrate **1**.

(211) As shown in FIGS. **12** and **13**, in some embodiments of the present disclosure, the recessed part **61** has two side surfaces, including a first side surface **611**, a second side surface **612**, and a second protrusion **600**, wherein the first side surface **611** and the second side surface **612** are oppositely disposed and connected to both sides of the second protrusion **600**. At the same time, the first side surface **611** and the second side surface **612** may contract in a direction approaching the substrate **1**. The first side surface **611** and the second side surface **612** may be curved or flat, and are not specifically limited here.

(212) The second protrusion **600** may be a curved surface that is convex in a direction away from the substrate **1**. In some embodiments of the present disclosure, the second protrusion **600** includes a first sloped surface **6131**, a second sloped surface **6132**, and a connection face **6133**. The first sloped surface **6131** and the second sloped surface **6132** can both be curved or flat. The connection face **6133** is located on the side of the bottom sides of the first side surface **611** and the second side surface **612** facing away from the substrate **1**, and the connection face **6133** is connected to between the first sloped surface **6131** and the second sloped surface **6132**. The first sloped surface **6131** is connected to the bottom side of the first side surface **611** to form a sub-recess **610**, and the second sloped surface **6132** is connected to the bottom side of the second side surface **612** to form another sub-recess **610**.

(213) In some embodiments of the present disclosure, the slope of the first sloped surface **6131** with relative to the middle part **310** is not less than the slope of the first side surface **611** with relative to the middle part **310**. At the same time, the slope of the second sloped surface **6132** with relative to the middle part **310** is not less than the slope of the second side surface **612** with relative to the middle part **310**.

(214) In some embodiments of the present disclosure, the minimum thickness of the area of the second electrode **6** corresponding to the first side surface **611** and the second side surface **612** is larger than the minimum thickness of the area of the second electrode **6** corresponding to the first sloped surface **6131** and the second sloped surface **6132**.

(215) Further, as shown in FIGS. **12** and **13**, in some embodiments of the present disclosure, the depth of the recessed part **61** is less than twice the maximum thickness of the second electrode **6**. For example, the maximum thickness of the second electrode **6** is 90 nm. The depth of the recessed part **61** is less than 180 nm, such as being 120 nm, 100 nm, 80 nm, 70 nm, 60 nm, 50 nm, 40 nm, etc. The depth of the recessed part **61** refers to the maximum depth of the recessed part **61**, that is, a distance, in the direction perpendicular to the substrate **1**, between the point of the recessed part **61** closest to the substrate **1** and the surface of the smooth part **62** away from the substrate **1**.

(216) In some embodiments of the present disclosure, as shown in FIGS. **12** and **13**, the orthographic projection of each recessed part **61** on the first insulation layer **2** surrounds the middle part **310** of a respective first electrode **31**. The minimum value of the distance between the second protrusion **600** of the recessed part **61** and the middle part **310** of the adjacent first electrode **31** (in the direction perpendicular to the substrate **1**, the distance between the middle part **310** and the point of the recessed part **61** nearest to the middle part **310**) is not less than 70% of the total thickness of the smooth part **62** and the light-emitting functional layer **5**, wherein the total thickness of the smooth part **62** and the light-emitting functional layer **5** is the sum of the thicknesses of the smooth part **62** and the light-emitting functional layer **5**. For example, the total thickness of the smooth part **62** and the light-emitting functional layer **5** is about 365 nm. In this

case, the minimum value of the distance between the middle part of the recessed part **61** in the direction perpendicular to the substrate **1** and the middle part **310** of the adjacent first electrode **31** is about 255 nm.

(217) Further, the maximum value of the distance between the middle part of the recessed part **61** and the middle part **310** of the adjacent first electrode **31** (in the direction perpendicular to the substrate **1**, the maximum value of the distance between the middle part **310** and the point closest to the middle part **310** of the recessed part **61**) is not less than 400 nm, and the maximum value is not greater than 450 nm.

(218) As shown in FIGS. **12** and **13**, in some embodiments of the present disclosure, the pixel definition layer **4** may include a spacing part **400** and an extension part **410**, wherein the spacing part **400** is located in an area of the first insulation layer **2** which is not covered by the first electrode **31**, i.e., outside the first electrode **31**, and the pixel definition groove **41** is provided in the spacing part **400**. The extension part **410** is connected to the spacing part **400**, extends to the surface of the first electrode **31** facing away from the substrate **1**, and does not completely cover the first electrode **31**. For example, the extension part **410** extends along the circumferential direction of the first electrode **31** to the surface of the circumferential direction of the middle part **310** away from the substrate **1**, and does not completely cover the middle part **310**.

(219) Since the extension part **410** covers the boundary of the first electrode **31**, such that the second electrode **6** corresponding to the area of the extension part **410** also has a protrusion part **63** that protrudes in a direction away from the substrate **1**, the smooth part **62** is connected to the recessed part **61** through the protrusion part **63**. The orthographic projection of the protrusion part **63** on the substrate **1** at least partially overlaps with the orthographic projection of the extension part **410** on the substrate **1**.

(220) If the thicknesses of two adjacent first electrodes **31** are different, and the distances between the substrate **1** and the surfaces of the extension parts **410** of the two first electrodes **31** facing away from the substrate **1** are different, such that among the two protrusions **63** connected to the two sides of a respective recessed part **61**, the distance between the substrate **1** and the point of one protrusion **63** furthest from the substrate **1** is different from the distance between the substrate **1** and the point of the other protrusion **63** furthest from the substrate **1**.

(221) In addition, as shown in FIGS. **12** and **13**, the display panel may further include a first encapsulation layer **13**, a color filter layer **14**, a second encapsulation layer **15**, and a transparent cover plate **16**.

(222) The first encapsulation layer **13** may cover the second electrode **6**. For example, the first encapsulation layer **13** may include two inorganic layers and an organic layer between the two inorganic layers.

(223) In some embodiments of the present disclosure, the first encapsulation layer **13** may be recessed to form a pit **1301** in the region corresponding to the recessed part **61**. Of course, if the thickness of the first encapsulation layer **13** is large, the surface of the first encapsulation layer **13** away from the substrate **1** can also remain substantially flat.

(224) The color filter layer **14** is disposed on the side of the first encapsulation layer **13** away from the second electrode **6**, and the color filter layer **14** includes filter regions corresponding to each first electrode **31** one by one. The color filter regions have multiple colors, such as red, blue and green.

(225) The second encapsulation layer **15** may cover the color filter layer **14**, and its structure may be the same as that of the first encapsulation layer **13**.

(226) The transparent cover plate **16** can cover the second encapsulation layer **15**, and its material can be glass or other material.

(227) In addition, in some embodiments of the present disclosure, as shown in FIGS. **12** and **13**, the fourth display panel may further include a light extraction layer **17**, which covers the surface of the second electrode **6** away from the substrate **1**, and is recessed in the area corresponding to the

recessed part **61**. The first encapsulation layer **13** is provided on the side of the light extraction layer **17** away from the substrate **1**. The refractive index of the light extraction layer **17** is greater than that of the second electrode **6**, which can improve the light extraction efficiency. The higher the refractive index is, the higher the light extraction efficiency will be. In the display panel according to any one of the above embodiments, the two sidewalls of the pit are narrowed and connected in a direction approaching the substrate.

(228) Embodiments of the present disclosure also provide a method for manufacturing a display panel, which display panel may be the first type of display panel described above. As shown in FIG. **14**, the manufacturing method includes steps **S110** to **S160**.

(229) Step **S110**, a first insulation layer is formed on a side of a substrate.

(230) Step **S120**, a plurality of separation grooves is formed on the surface of the first insulation layer away from the substrate, so as to separate a plurality of pixel regions distributed in an array.

(231) Step **S130**, a first electrode layer including a plurality of first electrodes is formed on the surface of the first insulation layer away from the substrate. The orthographic projection of each first electrode on the first insulation layer is located in a respective pixel region in a one-to-one correspondence. The first electrode includes a flat middle part and an edge part surrounding the middle part. The edge part includes a flat part surrounding the middle part and a sloped part connected between the middle part and the flat part, wherein the thickness of the flat part is smaller than that of the middle part.

(232) Step **S140**, a pixel definition layer is formed on the surface of the first insulation layer away from the substrate, the pixel definition layer exposing at least a portion of the middle part.

(233) Step **S150**: a light-emitting function layer is formed covering the pixel definition layer and the middle part and the first insulation layer exposed by the pixel definition layer.

(234) Step **S160**, a second electrode is formed covering the light-emitting function layer.

(235) The details and beneficial effects of each layer structure during the manufacturing method according to an embodiment of the present disclosure have been described in the above embodiments of the first display panel, and will not be repeated here.

(236) Embodiments of the present disclosure also provide a method for manufacturing a display panel, which display panel may be the first display panel described above. As shown in FIG. **15**, the manufacturing method includes step **S210** to step **S250**.

(237) Step **S210**, a first insulation layer is formed on a side of a substrate.

(238) Step **S220**, a first electrode layer including a plurality of first electrodes and a separation groove are formed on the surface of the first insulation layer away from the substrate. The first electrode includes a flat middle part and an edge part surrounding the middle part. The edge part includes a flat part surrounding the middle part and a sloped part connected between the middle part and the flat part, wherein the thickness of the flat part is smaller than that of the middle part. The separation groove separates a plurality of pixel regions distributed in an array on the first insulation layer. The orthographic projection of each first electrode on the first insulation layer is located within a respective pixel region in a one-to-one correspondence.

(239) Step **S230**, a pixel definition layer is formed on the surface of the first insulation layer away from the substrate, the pixel definition layer exposing at least a portion of the middle part.

(240) Step **S240**, a light-emitting functional layer is formed, the light-emitting functional layer covering the pixel definition layer as well as the middle part and the first insulation layer exposed by the pixel definition layer.

(241) Step **S250**, a second electrode is formed covering the light-emitting function layer.

(242) In the manufacturing method according to this embodiment, a conductive layer may be formed first on the surface of the first insulation layer away from the substrate, and the conductive layer may be patterned by a gray-scale mask process to obtain the first electrode layer. In the meantime, the gray-scale mask process can be used to form the separation grooves. Compared with the method for forming the first electrode layer and the separation groove separately by two mask

processes, the manufacturing process of the display panel can be simplified.

(243) Embodiments of the present disclosure also provide a method for manufacturing a display panel, which display panel can be the above-mentioned second display panel. As shown in FIG. 16, the manufacturing method includes steps **S310** to **S340**.

(244) Step **S310**, a first insulation layer is formed on a side of a substrate.

(245) Step **S320**, a first electrode layer including a plurality of first electrodes is formed on the surface of the first insulation layer facing away from the substrate.

(246) The first electrode includes a flat middle part and an edge part surrounding the middle part. The edge part includes a flat part surrounding the middle part and a sloped part connected between the middle part and the flat part, wherein the thickness of the flat part is smaller than that of the middle part.

(247) Step **S330**: a light-emitting function layer is formed covering at least a portion of the middle part.

(248) Step **S340**, a second electrode is formed covering the light-emitting function layer. The second electrode includes a recessed part and a plurality of smooth parts separated by the recessed part, and the orthographic projection of each smooth part on the first insulation layer is located within a respective first electrode in a one-to-one correspondence. The recessed part is recessed toward the side of the smooth part close to the substrate, and the orthographic projection of the recessed part on the first insulation layer is at least partially located outside the middle part.

(249) The details and beneficial effects of each layer structure during the manufacturing method according to an embodiment of the present disclosure have been described in the above embodiments of the second display panel, and will not be repeated here.

(250) Embodiments of the present disclosure also provide a method for manufacturing a display panel. The display panel may be the above-mentioned third display panel. As shown in FIG. 17, a method for manufacturing a display panel includes steps **S410** to **S450**.

(251) Step **S410**, a first insulation layer is formed on a side of a substrate. The first insulation layer has a plurality of pixel regions distributed in an array and a separation region separating the pixel regions; Step **S420**, a first electrode layer including a plurality of first electrodes is formed on the surface of the first insulation layer away from the substrate. The orthographic projection of each first electrode on the first insulation layer is located within a respective pixel region.

(252) Step **S430**, a pixel definition layer is formed on the surface of the first insulation layer away from the substrate, and exposing each of the first electrodes.

(253) The pixel definition layer is formed with a pixel definition groove in a region corresponding to the separation region. The middle part of the pixel definition groove has a first protrusion protruding in a direction away from the substrate, and a sub-groove is formed between the sidewall of the first protrusion and the sidewall of the pixel definition groove.

(254) Step **S440**, a light-emitting functional layer is formed, the light-emitting functional layer covering the pixel definition layer and the first electrode exposed by the pixel definition layer.

(255) Step **S450**, a second electrode is formed covering the light-emitting function layer.

(256) The details and beneficial effects of each layer structure during the manufacturing method according to an embodiment of the present disclosure have been described in the above embodiment of the third display panel, and will not be repeated here.

(257) Embodiments of the present disclosure also provide a method for manufacturing a display panel, which display panel may be the fourth display panel described above. As shown in FIG. 18, a method for manufacturing a display panel includes steps **S510** to **S540**.

(258) Step **S510**, a first insulation layer is formed on a side of a substrate.

(259) Step **S520**, a first electrode layer is formed on the surface of the first insulation layer facing away from the substrate, the first electrode layer including a plurality of first electrodes.

(260) Step **S530**: a pixel definition layer is formed on the surface of the first insulation layer away from the substrate, and the pixel definition exposes each of the first electrodes.

(261) Step S540, a light-emitting functional layer is formed, the light-emitting functional layer covering the pixel definition layer and the first electrode exposed by the pixel definition layer.

(262) Step S550, a second electrode is formed covering the light-emitting function layer. The second electrode includes a recessed part and a plurality of smooth parts separated by the recessed part, and the orthographic projection of each smooth part on the first insulation layer is located within a respective first electrodes. At least a part of the recessed part is recessed toward the side of the smooth part close to the substrate, and the orthographic projection of the recessed part on the first insulation layer is at least partially located outside the first electrode. A second protrusion is provided in the middle part of the recessed part, and a sub-recess is formed between the side surface of the second protrusion and the side surface of the recessed part.

(263) The details and beneficial effects of each layer structure during the manufacturing method according to an embodiment of the present disclosure have been described in the above embodiment of the fourth display panel, and will not be repeated here.

(264) It should be noted that although the various steps of the manufacturing method in the present disclosure are described in a specific order in the drawings, this does not require or imply that these steps must be performed in the specific order, or that all the steps shown must be performed in order to achieve the desired result. Additionally or alternatively, some steps may be omitted, multiple steps may be combined into one step for execution, and/or one step may be decomposed into multiple steps for execution, etc.

(265) Embodiments of the present disclosure also provide a display device, which may include any one of the above-mentioned first display panel, second display panel, third display panel, and fourth display panel. For the specific structure and beneficial effects, reference may be made to the above embodiments, which will not be repeated here. The display device of the present disclosure can be used in electronic devices such as mobile phones, tablet computers, televisions, etc., which will not be listed here.

(266) Those skilled in the art will easily think of other embodiments of the present disclosure after considering the specification and practicing the invention disclosed herein. The present application is intended to cover any variations, uses, or adaptive changes of the present disclosure. These variations, uses, or adaptive changes follow the general principles of the present disclosure and include common knowledge or conventional technical means in the technical field that are not disclosed in the present disclosure. The description and the embodiments are only regarded as exemplary, and the true scope and spirit of the present disclosure are defined by the appended claims.

Claims

1. A display panel, comprising: a substrate; a first insulation layer, located on a side of the substrate, wherein a plurality of separation grooves are provided on a surface of the first insulation layer away from the substrate for separating a plurality of pixel regions on the first insulation layer, the plurality of pixel regions are distributed in an array, each separation groove comprises two sidewalls opposite to each other and a bottom wall connected between the two sidewalls, and a contour of the bottom wall is a curved surface being convex in a direction away from the substrate, wherein the maximum distance between the curved surface and the substrate is smaller than the maximum distance between the substrate and the surface of the first insulation layer away from the substrate; a first electrode layer, located on the surface of the first insulation layer away from the substrate and comprising a plurality of first electrodes, wherein an orthographic projection on the first insulation layer of each of the first electrodes is located in a respective pixel region; a pixel definition layer, located on the surface of the first insulation layer away from the substrate and exposing each of the first electrodes; a light-emitting functional layer, covering the pixel definition layer and the first electrodes exposed by the pixel definition layer; and a second electrode, covering

the light-emitting function layer, wherein each pixel region is surrounded by a respective separation groove.

2. The display panel according to claim 1, wherein the contour of the bottom wall is arc-shaped, parabolic, or wavy.

3. The display panel according to claim 1, wherein the light-emitting functional layer is recessed in a direction toward the substrate in an area corresponding to the separation grooves, and the second electrode is recessed in a recessed area of the light-emitting functional layer to form a recessed part; the recessed part comprises a first side surface, a second side surface, and a bottom surface, wherein the first side surface and the second side surface are arranged oppositely and connected to both sides of the bottom surface; and the bottom surface is a curved surface being convex in a direction away from the substrate.

4. The display panel according to claim 3, wherein a contour of the bottom surface of the recessed part is arc-shaped, parabolic, or wavy.

5. The display panel according to claim 3, wherein a convex height of the bottom wall is smaller than a convex height of the bottom surface.

6. The display panel according to claim 3, wherein a curvature of the bottom surface is larger than a curvature of the bottom wall.

7. The display panel according to claim 1, wherein a plurality of driving transistors are provided on the substrate, and an area, corresponding to one of the driving transistors, of the substrate comprises an active region and a source and a drain located at both ends of the active region; and an orthographic projection on the substrate of the bottom wall or the bottom surface overlaps with an orthographic projection on the substrate of the source.

8. The display panel according to claim 1, wherein a maximum depth of the separation groove is not less than 30% of a sum of thicknesses of the light-emitting functional layer and the first electrode.

9. The display panel according to claim 1, wherein a maximum depth of the separation groove is not more than 60% of a sum of thicknesses of the light-emitting functional layer and the first electrode.

10. The display panel according to claim 1, wherein a maximum distance between the two sidewalls is from 0.2 μm to 0.7 μm .

11. The display panel according to claim 3, wherein a distance between the two sidewalls decreases in a direction towards the bottom surface.

12. The display panel according to claim 10, wherein slopes of the two sidewalls are not less than 70°.

13. The display panel according to claim 1, wherein a maximum depth of the separation groove is from 1000 Å to 3000 Å.

14. The display panel according to claim 1, wherein a convex height of the bottom wall is larger than a thickness of the pixel definition layer.

15. The display panel according to claim 1, wherein a depth of the separation groove is smaller than a thickness of the first electrode.

16. The display panel according to claim 3, wherein the recessed part is located on a side of the first electrode away from the substrate.

17. A display device, comprising a display panel, wherein the display panel comprises: a substrate; a first insulation layer, located on a side of the substrate, wherein a plurality of separation grooves are provided on a surface of the first insulation layer away from the substrate for separating a plurality of pixel regions on the first insulation layer, the plurality of pixel regions are distributed in an array, each separation groove comprises two sidewalls opposite to each other and a bottom wall connected between the two sidewalls, and a contour of the bottom wall is a curved surface being convex in a direction away from the substrate, wherein the maximum distance between the curved surface and the substrate is smaller than the maximum distance between the substrate and the

surface of the first insulation layer away from the substrate; a first electrode layer, located on the surface of the first insulation layer away from the substrate and comprising a plurality of first electrodes, wherein an orthographic projection on the first insulation layer of each of the first electrodes is located in a respective pixel region; a pixel definition layer, located on the surface of the first insulation layer away from the substrate and exposing each of the first electrodes; a light-emitting functional layer, covering the pixel definition layer and the first electrodes exposed by the pixel definition layer; and a second electrode, covering the light-emitting functional layer, wherein each pixel region is surrounded by a respective separation groove.

18. The display device according to claim 17, wherein the contour of the bottom wall is arc-shaped, parabolic, or wavy.

19. The display device according to claim 17, wherein the light-emitting functional layer is recessed in a direction toward the substrate in an area corresponding to the separation grooves, and the second electrode is recessed in a recessed area of the light-emitting functional layer to form a recessed part; the recessed part comprises a first side surface, a second side surface, and a bottom surface, wherein the first side surface and the second side surface are arranged oppositely and connected to both sides of the bottom surface; and the bottom surface is a curved surface being convex in a direction away from the substrate.

20. The display device according to claim 17, wherein a plurality of driving transistors are provided on the substrate, and an area, corresponding to one of the driving transistors, of the substrate comprises an active region and a source and a drain located at both ends of the active region; and an orthographic projection on the substrate of the bottom wall or the bottom surface overlaps with an orthographic projection on the substrate of the source.
