

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280758

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

ZHAO; Fengli et al.

SELF-MOVING DEVICE AND AUTOMATIC WORKING SYSTEM THEREOF

Abstract

A self-moving device, moving and working in a working area, includes: a housing; a moving module, mounted to the housing, and configured to drive the housing to move; a main working module, mounted to the housing, and configured to perform a main working task; an auxiliary working module, mounted to the housing, and configured to perform an auxiliary working task; a control module, configured to control the moving module, the main working module, and the auxiliary working module. The self-moving device includes a wireless communication module, configured to receive a control signal generated by user operation. The self-moving device includes an automatic working mode and an auxiliary working mode, in the auxiliary working mode, the control module controls the auxiliary working module at least based on the control signal to work; the control module controls the auxiliary working module based on an interruption of the control signal to stop working.

Inventors: ZHAO; Fengli (Jiangsu, CN), ZHA; Xiahong (Jiangsu, CN), Zhou; Xiaoqing (Jiangsu, CN)

Applicant: Positec Power Tools (Suzhou) Co., Ltd (Jiangsu, CN)

Family ID: 1000008630980

Appl. No.: 19/218025

Filed: May 23, 2025

Foreign Application Priority Data

CN 201811064195.0

Sep. 12, 2018

CN 201910591030.7

Jul. 02, 2019

Related U.S. Application Data

Publication Classification

Int. Cl.: A01D34/00 (20060101); A01D101/00 (20060101)

U.S. Cl.:

CPC A01D34/008 (20130101); A01D2101/00 (20130101)

Background/Summary

[0001] This application is a continuation-in-part of and claims priority to U.S. patent application Ser. No. 17/275,159, filed on Apr. 21, 2021 which is a National Stage Application of International Application No. PCT/CN2019/105563, filed on Sep. 12, 2019, which claims benefit of and priority to Chinese Patent Application No. 201811064195.0, filed on Sep. 12, 2018 and Chinese Patent Application No. 201910591030.7, filed on Jul. 2, 2019, all of which are hereby incorporated by reference in their entirety for all purposes as if fully set forth herein.

BACKGROUND

Technical Field

[0002] The present invention relates to a self-moving device and an automatic working system thereof.

Related Art

[0003] With the development of science and technology, intelligent self-moving devices become popular. Self-moving devices can automatically perform preset related tasks through preset programs without manual operation and intervention, and are therefore widely applied to industrial applications and household products. The industrial applications include a robot that performs various functions, and the applications in household products include, for example, a lawn mower and a vacuum cleaner. These intelligent self-moving devices greatly save people's time, and bring significant convenience to industrial production and household life.

[0004] A robotic mower is used as an example. The robotic mower usually performs autonomous movement and cutting in a specified working area. The working area may be an area defined by a boundary line, or may be a working area defined by a beacon, or may be a working area defined in a map manner or the like without setting an actual physical boundary. The robotic mower includes a cutting system. A protective cover is disposed on a periphery of the cutting system to prevent the cutting system from injuring an operator. The cutting system includes a cutting member. The cutting member is usually a blade. To prevent a user from injury, in one case, the protective cover is disposed on a periphery of a metal blade, and there is a particular distance between the protective cover and a periphery of the robotic mower. In this way, there is a relatively large distance between an end of the metal blade and a profile of the periphery of the robotic mower. In another case, the distance between the metal blade and the profile of the periphery of the robotic mower can prevent the user from touching the metal blade. In this way, the distance between the end of the metal blade and the profile of the periphery of the robotic mower is larger. That is, during cutting work, there may be uncuttable areas between the end of the metal blade and a boundary of a working area or obstacles such as a wall corner, a fence, and a step.

SUMMARY

[0005] To overcome the deficiency in the prior art, a problem to be resolved by the present

invention is to provide a self-moving device that has an auxiliary working capability and works safely.

[0006] A technical solution used in the present invention to resolve the problem in the prior art is: a self-moving device, moving and working in a working area, and comprising: a housing; a moving module, mounted to the housing, and configured to drive the housing to move; a main working module, mounted to the housing, and configured to perform a main working task; an auxiliary working module, mounted to the housing, and configured to perform an auxiliary working task; and a control module, configured to control the moving module, the main working module, and the auxiliary working module; the self-moving device comprises a wireless communication module, configured to receive a control signal generated from an operation of a user; and the self-moving device comprises an automatic working mode and an auxiliary working mode, wherein in the auxiliary working mode, the control module controls the auxiliary working module at least based on the control signal to work; and the control module controls the auxiliary working module based on an interruption of the control signal to stop working.

[0007] In one of embodiments, the interruption of the control signal comprises that a time that the wireless communication module stops receiving the control signal is greater than a preset interruption time.

[0008] In one of embodiments, the preset interruption time is less than or equal to 3 seconds.

[0009] In one of embodiments, in the auxiliary working mode, if determining that a distance between a signal source of the control signal and the wireless communication module is greater than or equal to a first preset distance, the control module controls the auxiliary working module to stop working.

[0010] In one of embodiments, the first preset distance is less than or equal to 20 meters.

[0011] In one of embodiments, in the auxiliary working mode, if the distance between the signal source and the wireless communication module is greater than a second preset distance, the control module controls the auxiliary working module to reduce a working speed, to enable working energy of the auxiliary working module to be less than preset energy; and the second preset distance is less than the first preset distance.

[0012] In one of embodiments, the second preset distance is less than or equal to 6 meters.

[0013] In one of embodiments, if determining that the strength of the control signal is less than or equal to preset strength, the control module controls the auxiliary working module to stop working.

[0014] In one of embodiments, the control module controls the self-moving device based on at least two preset signals to switch to the auxiliary working mode.

[0015] In one of embodiments, if the at least two preset signals received by the control module satisfy a preset condition, the control module controls the self-moving device to switch to the auxiliary working mode.

[0016] In one of embodiments, the preset condition comprises a preset time and/or a preset order.

[0017] In one of embodiments, the at least one preset signal is received by the wireless communication module.

[0018] In one of embodiments, the at least one preset signal comprises the control signal.

[0019] In one of embodiments, the self-moving device comprises an interaction module, and the at least one preset signal is generated by operating the interaction module by the user.

[0020] In one of embodiments, in the auxiliary working mode, the control module controls the auxiliary working module based on a stop signal to stop working.

[0021] In one of embodiments, the stop signal is received by the wireless communication module.

[0022] In one of embodiments, in the auxiliary working mode, the control module controls the moving module to move along a preset path.

[0023] In one of embodiments, the self-moving device comprises a path detection module, configured to detect the preset path, and the control module automatically controls a moving direction of the moving module according to an output of the path detection module.

[0024] In one of embodiments, the control module determines, according to the output of the path detection module, whether the self-moving device is on the preset path, and if the self-moving device is not on the preset path, controls the auxiliary working module to stop working.

[0025] In one of embodiments, the preset path comprises an inner boundary and/or an outer boundary of the working area.

[0026] In one of embodiments, in the auxiliary working mode, working energy of the auxiliary working module is less than 5 J.

[0027] In one of embodiments, in the auxiliary working mode, working energy of the auxiliary working module less than 2 J.

[0028] In one of embodiments, in the auxiliary working mode, a maximum moving speed of the moving module is less than 25 m/min.

[0029] In one of embodiments, in the auxiliary working mode, the maximum moving speed of the moving module is greater than 5 m/min.

[0030] In one of embodiments, the auxiliary working module comprises a trimmer head, the trimmer head is mounted with a trimmerline, and the trimmer head drives the trimmerline to rotate to cut grass.

[0031] In one of embodiments, the wireless communication module comprises a Bluetooth communication module.

[0032] In one of embodiments, if the auxiliary working module stops working, the control module controls the self-moving device to switch to the automatic working mode.

[0033] In one of embodiments, in the automatic working mode, the control module autonomously controls the moving module and the main working module.

[0034] In one of embodiments, in the automatic working mode, the control module controls the auxiliary working module not to work.

[0035] Another technical solution used in the present invention to resolve the problem in the prior art is:

[0036] An automatic working system, comprising a self-moving device and a user terminal, [0037] the self-moving device, moving and working in a working area, and comprising: a housing; a moving module, mounted to the housing, and configured to drive the housing to move; a main working module, mounted to the housing, and configured to perform a main working task; an auxiliary working module, mounted to the housing, and configured to perform an auxiliary working task; a control module, configured to control the moving module, the main working module, and the auxiliary working module; and a wireless communication module, configured to receive a signal sent by the user terminal; and [0038] the user terminal, comprising: an input module, for a user to operate to generate a signal; a processing module, configured to process the signal; and a remote communication module, configured to send the signal; the input module comprising a first input unit, configured to generate a control signal, the signal comprising the control signal; [0039] the self-moving device comprises an automatic working mode and an auxiliary working mode, wherein in the auxiliary working mode, the control module controls the auxiliary working module at least based on the control signal to work; and the control module controls the auxiliary working module based on an interruption of the control signal to stop working.

[0040] In one of embodiments, the interruption of the control signal comprises that a time that the wireless communication module stops receiving the control signal is greater than a preset interruption time.

[0041] In one of embodiments, the preset interruption time is less than or equal to 3 seconds.

[0042] In one of embodiments, in the auxiliary working mode, if a distance between the wireless communication module and the remote communication module is less than or equal to a first preset distance, the control module controls the auxiliary working module to stop working.

[0043] In one of embodiments, the first preset distance is less than or equal to 20 meters.

[0044] In one of embodiments, in the auxiliary working mode, if the distance is greater than a

second preset distance, the control module controls the auxiliary working module to reduce a working speed, to enable working energy of the auxiliary working module to be less than preset energy.

[0045] In one of embodiments, the second preset distance is less than or equal to 6 meters.

[0046] In one of embodiments, the input module comprises a second input unit, configured to generate a start signal.

[0047] In one of embodiments, the processing module controls the remote communication module based on the start signal to send the control signal.

[0048] In one of embodiments, if the control signal and the start signal received by the processing module satisfy a preset condition, the remote communication module is controlled to send the control signal.

[0049] In one of embodiments, the preset condition comprises a preset time and/or a preset order.

[0050] In one of embodiments, the control module controls the self-moving device based on the control signal to switch to the auxiliary working mode.

[0051] In one of embodiments, the processing module controls the remote communication module to send a start signal and a control signal.

[0052] In one of embodiments, the self-moving device comprises an interaction module, configured to generate a start signal.

[0053] In one of embodiments, the control module controls the self-moving device based on the start signal and the control signal to switch to the auxiliary working mode.

[0054] In one of embodiments, if the start signal and the control signal received by the control module satisfy a preset condition, the control module controls the self-moving device to switch to the auxiliary working mode.

[0055] In one of embodiments, the first input unit comprises a touch sensing button, touched by the user to generate the control signal.

[0056] In one of embodiments, the first input unit is connected to the processing module by a first connection circuit or a second connection circuit, and the first connection circuit is connected in parallel to the second connection circuit.

[0057] In one of embodiments, the input module comprises a third input unit, configured to generate a stop signal; and the control module controls the auxiliary working module based on the stop signal to stop working.

[0058] Compared with the prior art, the beneficial effects of this solution are as follows:

[0059] An auxiliary working module is mounted on a self-moving device, so that work such as trimming and pruning that originally requires holding of a device in hand by a user can be completed by the self-moving device, so that the user only needs to operate a user terminal, so that a working process is easier and more convenient. The user needs to operate the user terminal to perform the work of the auxiliary working module, to ensure that the work is performed in a supervised state of the user, so that it can be ensured that the user responds to an emergency that may occur, to improve the safety of operation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0060] The foregoing objects, technical solutions, and beneficial effects of the present invention can be implemented with reference to the accompanying drawings below:

[0061] FIG. 1 is a schematic diagram of an automatic working system in an embodiment.

[0062] FIG. 2 is a schematic structural diagram of a self-moving device in an embodiment.

[0063] FIG. 3 is a schematic structural diagram of a robotic mower in an embodiment.

[0064] FIG. 4 is a schematic diagram of working areas of modules of a robotic mower in an

embodiment.

[0065] FIG. 5 is a schematic diagram of working areas of modules of a robotic mower in another embodiment.

[0066] FIG. 6 is a schematic diagram of working areas of modules of a robotic mower in still another embodiment.

[0067] FIG. 7 is a schematic diagram of a moving direction of a robotic mower in an embodiment.

[0068] FIG. 8 is a schematic diagram of a moving direction of a robotic mower in still another embodiment.

[0069] FIG. 9 is a schematic structural diagram of a user terminal in an embodiment.

[0070] FIG. 10 is a schematic diagram of a height adjustment structure in an embodiment.

[0071] FIG. 11 is a schematic diagram of a position relationship between a robotic mower and an obstacle in an embodiment.

[0072] FIG. 12 is a schematic diagram of an automatic mowing system in an embodiment.

[0073] FIG. 13 is a schematic structural diagram of a user terminal in an embodiment.

[0074] FIG. 14 is a schematic structural diagram of a user terminal in another embodiment.

[0075] FIG. 15 is a schematic structural diagram of a robotic mower in an embodiment.

DETAILED DESCRIPTION

[0076] Specific implementations of the present invention are described below in detail with reference to the accompanying drawings.

[0077] FIG. 1 shows an automatic working system. As shown in FIG. 1, in this implementation, the automatic working system includes a self-moving device 1, a boundary 3, and a parking station 5. The boundary 3 is configured to define a working area 7 of the automatic working system. The self-moving device 1 moves and works within the boundary 3. The parking station 5 is used for parking the self-moving device 1, especially, for the self-moving device to return to replenish energy when there is insufficient energy.

[0078] The boundary 3 may be an outer boundary of the working area 7. The outer boundary is a periphery of the entire working area 7, and is usually connected head to tail, to close the working area 7. The boundary 3 may be physical or may be electrical. That is, a wall, a fence, a handrail, or the like may form the boundary 3. A boundary signal generation apparatus may send an electromagnetic signal, an optical signal, or the like, and may be a passive magnetic apparatus that can generate a magnetic field. The boundary may be alternatively absolute coordinates or relative coordinates learned or recorded by the self-moving device 1, other environmental information that can be used for determining a position, or the like. The boundary 3 may be alternatively a general name of the outer boundary and an inner boundary of the working area 7. The inner boundary includes an obstacle in a working range or another area unsuitable for the self-moving device 1 to enter. The obstacle is a part or an area on which the self-moving device cannot move in the working range, and is, for example, an indoor couch or nightstand or an outdoor pond or flowerbed.

[0079] In this embodiment, the self-moving device 1 is a robotic mower. In other embodiments, the self-moving device 1 may be an unsupervised device such as an automatic vacuum cleaner, an automatic sprinkle device, or an automatic monitoring device. The device automatically moves on the ground or surface of the working area 7, to complete corresponding work. The self-moving device 1 includes a moving module, a main working module, a boundary detection module, an energy module, and a control module.

[0080] As shown in FIG. 2, a moving module 23 is configured to drive the self-moving device 1 to move in the working area 7, and is usually formed by a wheel group mounted to the self-moving device 1 and a moving motor configured to drive the wheel group. The wheel group includes a drive wheel connected to the moving motor and an auxiliary wheel mainly used for auxiliary support. In this embodiment, there are two drive wheels, located at the rear portion of the self-moving device 1. Each drive wheel is connected to the moving motor. There is one or two auxiliary wheels, located at the front portion of the self-moving device 1.

[0081] The main working module **25** is configured to perform a main working task of the self-moving device **1**. If the self-moving device **1** is a robotic mower, the main working module includes a mowing blade, a cutting motor, and the like, or may include a part such as a mowing height adjustment mechanism that optimizes or adjusts the mowing effect. If the self-moving device **1** is an automatic vacuum cleaner, the main working module includes working parts such as a dust suction motor, a dust suction opening, a dust suction tube, a vacuum chamber, and a dust collection apparatus that are configured to perform a dust suction task.

[0082] The boundary detection module is configured to detect a relative position relationship between the self-moving device **1** and the boundary **3**. The relative position relationship may specifically include one or more of a distance, an angle, and the inside and outside of the boundary **3**. The boundary detection module may have various structures and principles, and may be, for example, of an infrared type, an ultrasound type, a collision detection type, a magnetic sensing type. A sensor and a corresponding signal generation apparatus of the boundary detection module also have various arrangement positions and quantities, and are related to a path planning manner.

[0083] The energy module is configured to supply energy for various work of the self-moving device **1**, and includes a rechargeable battery and a charging connection structure. The charging connection structure is usually a charging electrode.

[0084] A control module **31** is configured to control the self-moving device **1** to automatically move and work, and is the core part of the self-moving device **1**. The functions performed by the control module include: controlling the main working module to start working or stop, controlling the moving module to start or stop, controlling a moving direction, determining the energy of the energy module and instructing in time the self-moving device **1** to return to a charging station for automatic docking and charging, and the like. The control module usually includes a microcontroller, a memory, and another peripheral circuit.

[0085] In addition to the foregoing modules, the self-moving device **1** further includes a housing **21** for accommodating and mounting various modules, a control panel for operations by a user, and the like. The self-moving device **1** may further include various environmental sensors, for example, a humidity sensor, a temperature sensor, an acceleration sensor, and an optical sensor. These sensors may assist the self-moving device in determining a working environment, to execute a corresponding program.

[0086] In an embodiment, the self-moving device **1** includes an auxiliary working module **33**, configured to perform an auxiliary working task of the self-moving device **1**. Optionally, if the self-moving device **1** is a robotic mower. The auxiliary working module includes an auxiliary cutting module, a fertilization module, a fallen leaves collection module, or the like. If the self-moving device **1** is a cleaning robot, the auxiliary working module includes a watering module, a mopping module, or the like.

[0087] The parking station **5** is usually located in a working range, for example, near or on the boundary **3**, and is connected to mains electricity or another electric power supply system, for the self-moving device **1** to return for charging. The charging electrode is disposed on the parking station **5**, and is configured to be docked to a corresponding electrode of the self-moving device **1**. Optionally, a wireless charging module instead of the charging electrode is disposed in the parking station **5**, and the wireless charging module and a wireless charging module of the self-moving device **1** perform induction to implement wireless charging.

[0088] In an embodiment, the self-moving device **1** includes a main working mode and an auxiliary working mode. In the main working mode, the control module **31** autonomously controls the moving module **23** and the main working module **25**. In the auxiliary working mode, the control module **31** controls the auxiliary working module **33** based on a preset signal generated from an operation of a user to work.

[0089] FIG. **9** is a schematic structural diagram of a user terminal **9** in an embodiment. As shown in FIG. **9**, the automatic working system includes the user terminal **9**. The user terminal **9** may

establish a communication connection with the self-moving device **1**. The user terminal **9** includes a remote communication module **10**, a processing module **12**, and an input module **14**. The input module **14** and the remote communication module **10** are respectively connected to the processing module **12**. Optionally, the user terminal **9** further includes an indicator lamp **16**, connected to the processing module, and configured to indicate a communication connection state. According to an actual requirement, several buttons may be disposed on the input module **14**. The buttons correspond to different functions. The self-moving device **1** includes a wireless communication module, which may establish a communication connection with the user terminal **9** to receive a signal. The user terminal **9** may be an independent controller, or may be a control apparatus detachably connected to the self-moving device **1**, or is a user terminal such as a mobile phone or a computer. A user operates the user terminal **9** to at least partially control the self-moving device **1** to work.

[0090] In an embodiment, the input module **14** includes: a first input unit, configured to generate a control signal; and a second input unit, configured to generate a start signal. Continuing to refer to FIG. **9**, in an embodiment, the first input unit includes a button **141**, and the second input unit includes a button **143**. The button **141** is a start button for a user to operate to generate the start signal. The button **143** is a control button configured for the user to operate to generate the control signal. Optionally, the button **143** is a contact sensor, and detects the contact of the user on the user terminal **9** and generates the control signal, so that when holding the user terminal in hand in a normal gesture, the user can contact the contact sensor **143** to send the control signal. In this embodiment, the contact sensor is a capacitive sensor.

[0091] In an embodiment, the input module **14** includes a third input unit, in this embodiment, the third input unit includes a stop button **145**, and generates a stop signal. The control module **31** stops the moving module **23** and the auxiliary working module **33** based on the stop signal.

[0092] In an embodiment, to prevent the button **143** and a signal transmission circuit or control circuit connected to a button from failing in a working process, the button **143** is connected to circuits of two independent channels. If the circuit of one channel fails, the circuit of the other channel can ensure normal control of the user. In another embodiment, the button **143** includes a button **1** and a button **2**. If either of the button **1** and the button **2** fails, the other can still work normally, to ensure normal control of the user.

[0093] In an embodiment, if the user terminal **9** is in a working state, when the user presses the button **141** and the button **143**, the start signal and the control signal are generated. The processing module **12** controls the remote communication module **10** to respectively send the start signal and the control signal. In a communication state, the wireless communication module receives the start signal and the control signal. The control module **31** controls the auxiliary working module **33** based on the start signal and the control signal to work.

[0094] In an embodiment, if the user terminal **9** is in a working state, when the user presses the button **141** and the button **143**, the processing module **12** respectively receives the start signal and the control signal, and a preset condition is satisfied, the processing module **12** controls the remote communication module **10** to send the control signal. In this embodiment, the preset condition includes that the processing module **12** receives the start signal and the control signal within a preset time. The preset time may be 10 seconds, 20 seconds, or the like, and is set according to an actual requirement. In other embodiments, the preset condition includes the processing module **12** to receive the start signal and the control signal in a preset order. The control module **31** controls the auxiliary working module **33** based on the control signal to work. The preset order may be receiving the start signal first and then receiving the control signal; or may be receiving the control signal first and then receiving the start signal; or may be set to simultaneously receiving the start signal and the control signal.

[0095] In an embodiment, the self-moving device **1** includes an interaction module, for the user to operate to generate a signal. In this embodiment, the interaction module includes a start button

disposed on the housing **21**, and a control button is disposed on the user terminal **9**. When the user operates the start button, the control module **31** receives the start signal, and when the user operates the control button, the user terminal **9** sends the control signal. The control module **31** receives the control signal by using the wireless communication module. If the start signal and the control signal received by the control module **31** satisfy the preset condition, the control module **31** controls the auxiliary working module **33** to work.

[0096] The wireless communication module includes an antenna. The antenna of the wireless communication module is disposed at an upper portion of the self-moving device **1**, and optionally, is disposed at an upper portion of the auxiliary working module **33** to prevent interference from metal in a robotic mower **11**, to avoid the impact on the sending and receiving of a signal by the wireless communication module.

[0097] In an embodiment, in the auxiliary working mode, the control module **31** at least controls the auxiliary working module **33** based on the control signal to work. If the control signal received by the control module **31** is interrupted, the control module **31** controls the auxiliary working module **33** to stop working.

[0098] In an embodiment, the interruption of the control signal is specifically that a time that the wireless communication module cannot receive the control signal is greater than a preset interruption time. In this embodiment, the preset interruption time is less than or equal to 3 seconds. According to an actual requirement, the preset interruption time may be 4 seconds, 5 seconds, or the like. Herein, a case that the wireless communication module cannot receive the control signal includes that the user releases a button of the user terminal **9**, the user terminal **9** is disconnected from the self-moving device **1**, the user terminal **9** is out of power, there is the blockage of an obstacle between the user terminal **9** and the self-moving device **1**, or the like.

[0099] If the user continuously holds the user terminal **9** in hand and contacts the button **143**, the user terminal **9** continuously sends the control signal, indicating that the user is in a control state. The control module **31** controls the auxiliary working module **33** according to the received control signal to work. If the control module **31** determines that the user terminal **9** has been started, the control module **31** controls the auxiliary working module **33** through an interruption of the control signal received by the wireless communication module to stop working. Optionally, the auxiliary working module **33** and the moving module **23** are controlled to stop working.

[0100] In an embodiment, if the control module **31** receives the stop signal, that is, the user presses the stop button **145**, the control module **31** controls the auxiliary working module **33** to stop working. Optionally, the control module **31** controls both the auxiliary working module **33** and the moving module **23** to stop working.

[0101] In an embodiment, to ensure that the user performs control in a valid control range of the self-moving device **1**, the control module **31** determines a distance between the user terminal **9** and the self-moving device **1** according to the received control signal, and if the distance between the user terminal **9** and the self-moving device **1** is greater than or equal to a preset distance, controls the auxiliary working module **33** to stop working. In this embodiment, the preset distance is less than or equal to 20 meters. That is, when a valid distance between the user terminal **9** and the self-moving device **1** is less than 20 meters, the user terminal **9** may control the self-moving device **1**. When the valid distance between the user terminal **9** and the self-moving device **1** is greater than 20 meters, the control signal sent by the user terminal **9** cannot control the auxiliary working module **33** to work.

[0102] FIG. **12** is a schematic diagram of an automatic mowing system in an embodiment. As shown in FIG. **12**, the automatic mowing system includes: a robotic mower **11**; a parking station **105**, for the robotic mower **11** to perform parking and charging; a boundary signal generator, located on the parking station **105**, and generating a boundary signal; and a boundary line **103**, connected to the boundary signal generator, where the boundary line **103** and the boundary signal generator form a closed ring, the boundary signal is provided on the boundary line **103**, and a

working area **107** of the robotic mower **11** is formed in the boundary line **103**. The robotic mower **11** includes a housing **61**, a moving module **51** mounted to the housing **61**, a main cutting module **53**, a boundary detection module, an energy module **57**, and a control module **59**.

[0103] The main cutting module **53** is a cutting deck, including a bottom disk rotating around an axis of a rotating shaft, where the bottom disk forms a plane perpendicular to the axis of the rotating shaft, an opening hole is provided at the center of the bottom disk, the opening hole is sleeved on the rotating shaft, and the rotating shaft is located at the center of the bottom disk; and further including a main cutting element disposed at a circumferential edge of the bottom disk, where the main cutting element rotates around the axis of the rotating shaft together along with the rotation of the bottom disk, and the bottom disk and the main cutting element rotate to form a main cutting area with the center of a coil disk as a first rotating axis.

[0104] A traveling direction of the robotic mower **11** is a longitudinal direction of the housing **61**, a direction perpendicular to the ground is a vertical direction of the housing **61**, and a direction perpendicular to both the longitudinal direction and the vertical direction is a transverse direction of the housing **61**. The housing **61** includes a vertical axis **111** in the longitudinal direction, and the main cutting module **53** is mounted to the vertical axis **111** of the housing **61**, so that there is a sufficient distance between a circumferential edge of the housing **61** and the main cutting module **53**, to ensure the use safety of a user. If the robotic mower **11** moves along the boundary line **103** on an inner side of the boundary line **103**, the main cutting area formed by the working of the main cutting module **53** may fail to cover a boundary of the working area **107**.

[0105] In an embodiment, a boundary detection module includes a first boundary signal sensor and a second boundary signal sensor, symmetrically disposed at the front portion of the housing **61**, and detecting a boundary signal to determine whether the sensor is located inside or outside the boundary line **103**. If a detection result of the first boundary signal sensor shows that the sensor is outside the boundary line **103**, it indicates that the robotic mower **11** has left the boundary line **103** on a side in which the first boundary signal sensor is located. In this case, the control module **59** controls the robotic mower **11** to steer. That is, the robotic mower **11** partially leaves the boundary line **103** and then steers. Generally, to prevent the robotic mower **11** from frequently colliding with an obstacle such as a wall, a fence, or a step or entering an area that does not requires working, a distance between the boundary line **103** disposed at an edge of the obstacle and the obstacle or another boundary is approximately 30 centimeters. If the robotic mower **11** is partially located inside the boundary line **103** and partially located outside the boundary line **103** when returning to the parking station **105**, that is, returns across a line, the main cutting module **53** can only cut an area of approximately 10 mm outside the boundary line **103**. Therefore, a to-be-trimmed area of approximately 20 mm left between the boundary line **103** and the obstacle is not processable by the robotic mower **11**. In consideration of an extreme case, the robotic mower **11** can completely move along an obstacle such as a wall, a fence, or the like, and for the presence of the distance between the circumferential edge of the housing **61** and the main cutting area, the to-be-trimmed area cannot be completely processed. Therefore, if only the main cutting module **53** is mounted, the robotic mower **11** cannot implement cutting to edge.

[0106] FIG. 3 is a schematic structural diagram of a robotic mower. As shown in FIG. 12 and FIG. 3, to resolve a problem that the main cutting module **53** cannot cut to edge, the robotic mower **11** further includes an auxiliary cutting module **63**. In this embodiment, the auxiliary cutting module **63** includes a trimmer head, including a coil disk wound with a trimmerline, an accommodating base for accommodating the coil disk. When the trimmer head is working, the accommodating base is driven to rotate to drive the coil disk and the trimmerline to synchronously rotate, to form an auxiliary cutting area with the center of circle of the coil disk as a second rotating axis.

[0107] Grass cuttings generated from the working of the auxiliary cutting module **63** tend to be stuck on the housing **61**, and water washing is an important manner to resolve this problem. Therefore, to prevent water from contacting the inside of the auxiliary cutting module in a water

washing process to cause damage, a waterproof design needs to be applied to the auxiliary cutting module **63**. Continuing to refer to FIG. **3**, in an embodiment, the auxiliary cutting module **63** includes an auxiliary cutting motor, configured to drive the trimmer head to rotate. The auxiliary cutting motor is disposed in a motor protective cover. The motor protective cover prevents dust, rain, snow, or the like from causing damage to the operation of an electric motor, to ensure normal and continuous working of the electric motor. In this embodiment, the motor protective cover includes an outlet for an output shaft of the auxiliary cutting motor to extend out. Apart from the outlet, the motor protective cover is a sealed structure, that is, does not include a heat dissipation hole for the heat dissipation of the motor. Therefore, the material of the motor protective cover includes a thermal conduction material such as an aluminum shell. In this embodiment, there is a gap between the motor protective cover and the shell of the auxiliary cutting motor in the height direction for an air outlet of the auxiliary cutting motor to discharge an airflow, to implement airflow circulation in the motor protective cover. In an embodiment, the auxiliary cutting module **63** includes a heat dissipation fan, mounted below the motor protective cover, and used for auxiliary heat dissipation. In an embodiment, one side of the motor protective cover faces the main cutting module **53**, and the other side faces the robotic mower **11**. Therefore, the foregoing other side of the motor protective cover is provided with the heat dissipation hole, to assist the auxiliary cutting motor in heat dissipation. The foregoing side facing the main cutting module **53** is provided with no heat dissipation hole, to prevent grass cuttings generated during the working of the main cutting module **53** from entering the auxiliary cutting motor.

[0108] In an embodiment, a sealing member is disposed between the outlet of the motor protective cover and the output shaft of the auxiliary cutting motor, to further isolate the internal environment and the external environment of the motor protective cover while keeping that the output shaft of the auxiliary cutting motor normally rotate. In an embodiment, an electrically charged body in the auxiliary cutting module **63** is encapsulated for isolation from the external environment, including potting waterproof, for example, an epoxy resin potting compound; or surface coating waterproof, for example, conformal coating or nano-coating, and the like.

[0109] FIG. **4** is a schematic diagram of working areas of modules of a robotic mower in an embodiment. As shown in FIG. **4**, to implement that the robotic mower **11** can cut a to-be-trimmed area outside the boundary line **103** when moving along the boundary line **103**, and the auxiliary cutting area formed by the working of the auxiliary cutting module **63** is tangent to the housing **61** or extends beyond the housing **61**. If the moving module **51** is located in the housing **61** in the transverse direction, a distance between the second rotating axis and an outer edge of the housing **61** in the transverse direction is less than or equal to the radius of the auxiliary cutting area. If the moving module **51** is located outside the housing **61** in the transverse direction, a distance between the second rotating axis and an outer edge of the moving module **51** in the transverse direction is less than or equal to the radius of the auxiliary cutting area. In this way, the auxiliary cutting area extends beyond or is tangent to the housing **61** or the moving module **51**. In this way, if the robotic mower **11** can move along an obstacle, the auxiliary cutting area can completely cover the surrounding of the obstacle. When the robotic mower **11** moves along the boundary line **103**, provided that the auxiliary cutting area can cover the boundary line **103** or the to-be-trimmed area outside the boundary line **103** in the transverse direction, it can be implemented that the robotic mower **11** completely cuts to edge, and the user does not need to perform processing again. A side on which the auxiliary cutting module **63** is mounted on a left side or a right side of a moving direction of the robotic mower **11**. If the auxiliary cutting module **63** includes two trimmer heads, the trimmer heads may be respectively mounted on the left side and right side of the moving direction of the automatic lawn mower **11**, and the control module **59** may control one of the trimmer heads to work or both the trimmer heads to work. In other embodiments, cutting to edge can also be implemented with the auxiliary cutting area extending beyond the housing **61** in the longitudinal direction. In particular, for a case in which there is an obstacle in the working area

107, when the robotic mower **11** encounters an obstacle during travel, the robotic mower **11** does not need to change a movement manner, and the auxiliary cutting area extending beyond the housing **61** may cover an edge of the obstacle.

[0110] FIG. 5 is a schematic diagram of working areas of modules of a robotic mower in another embodiment. As shown in FIG. 5, the main cutting module **53** is mounted to a side of the vertical axis **111** of the housing **61**, so that the main cutting area can be closer to an obstacle, to cut an area that cannot be cut when the main cutting module **53** is mounted to the vertical axis **111**. However, to avoid accidental injury, a protective cover is usually disposed on a side on which the user may contact the main cutting element, to ensure that the user cannot reach in and contact the main cutting element. As a result, there is still a distance between the main cutting module **53** and the protective cover, and even if the robotic mower **11** cuts along an obstacle, cutting to edge cannot be implemented. Therefore, the auxiliary cutting module **63** is also mounted to the same side of the vertical axis **111** of the housing **61**. For example, the main cutting module **53** and the auxiliary cutting module **63** are both mounted to the right side of the moving direction of the robotic mower **11**. The main cutting module **53** and the auxiliary cutting module **63** are mounted to the housing **61** in this manner, so that the main cutting module **53** can maximally cut to the proximity of the boundary of the working area **107**, thereby reducing the workload of the auxiliary cutting module **63**. Because the main cutting module **53** and the auxiliary cutting module **63** are mounted to the same side, to enable the main cutting module **53** and the auxiliary cutting module **63** to face the outer side of the working area **107**, when the main cutting module **53** is working or the auxiliary cutting module **63** is working, the robotic mower **11** has a consistent moving direction when moving along the boundary line **103**, does not need to change the direction.

[0111] FIG. 6 is a schematic diagram of working areas of modules of a robotic mower in still another embodiment. As shown in FIG. 6, the main cutting module **53** is mounted to a side of the vertical axis **111** of the housing **61**, and the auxiliary cutting module **63** is mounted to the other side of the vertical axis **111** of the housing **61**. Because the main cutting module **53** and the auxiliary cutting module **63** are mounted to different sides of the vertical axis **111**, the space of the housing **61** can be fully used, so that the modules of the robotic mower **11** have a more compact structural layout. To implement cutting to edge, when the main cutting module **53** is working, the direction in which the robotic mower **11** moves along the boundary line **103**, and when the auxiliary cutting module **63** is working, the direction in which the robotic mower **11** moves along the boundary line **103** is opposite.

[0112] In an embodiment, an auxiliary cutting element of the auxiliary cutting module **63** is a trimmerline. When the trimmer head is working, working energy of the trimmerline is less than or equal to full energy, safe energy is less than or equal to 5 J, to prevent a human or an animal from injury in the case of contact. In this embodiment, the trimmerline is made of nylon. The working energy of the trimmerline is controlled within a safe range by limiting the material and shape of the trimmerline, a working speed of the trimmer head, and the like. In other embodiments, the trimmerline may be another flexible material, for example, made of resin or fiber. The auxiliary cutting module **63** may be a cutting apparatus other than the trimmer head, and may be alternatively a metal element, a plastic blade, or the like without a cutting edge, provided that it can be satisfied that the working energy of the auxiliary cutting element is less than the safe energy. In an embodiment, the safe energy is less than or equal to 2 J.

[0113] In an embodiment, when the auxiliary cutting module **63** is working, the maximum moving speed of the robotic mower **11** does not exceed a preset speed range. The moving speed of the robotic mower **11** is related to the working energy of the auxiliary cutting module **63**. If the moving speed of the robotic mower **11** is excessively large, to reduce the possibility of cutting miss, the auxiliary cutting module **63** needs to work with relatively high working energy, and as a result the working safety is affected. In this embodiment, the preset speed range is less than or equal to 25 m/min.

[0114] If the moving speed of the robotic mower **11** is small, the working energy of the auxiliary cutting module **63** may be correspondingly reduced to improve the safety. However, an excessively low moving speed affects the working efficiency of the robotic mower **11**, causes an increase in working time, and affects user experience. In an embodiment, the preset speed range is greater than or equal to 5 m/min.

[0115] In an embodiment, the drive wheel includes a wheel hub cap. The wheel hub cap has an approximately smooth surface and a groove depth of less than or equal to 5 mm. When the groove depth of the wheel hub cap is larger, grass cuttings are more prone to adhesion and need to be cleaned by the user. Therefore, the approximately smooth surface of the wheel hub cap can reduce the adhesion rate of grass cuttings. It may be understood that the surface, close to the auxiliary cutting module **63**, of the housing **61** is approximately smooth.

[0116] In an embodiment, the housing **61** includes a bottom base and an upper cap mounted to the bottom base. Because a working area of the auxiliary cutting module **63** and an edge portion of the upper cap are overlapped in the height direction, to prevent the housing **61** from interfering with the working of the auxiliary cutting module **63**, a height difference between the auxiliary cutting module **63** the housing **61** of the overlapped portion in the height direction and the plane in which the working area of the auxiliary cutting module **63** is located is greater than or equal to 5 mm.

[0117] In an embodiment, as shown in FIG. 6, the main cutting module **53** and the auxiliary cutting module **63** are respectively located on two sides of the vertical axis of the housing **61**. A distance between the housing **61** on a side where the auxiliary cutting module **63** is located and the main cutting module **53** in the horizontal direction is greater than or equal to 180 mm, to prevent the user from putting a finger in to cause injury during the working of the main cutting module **53**.

[0118] In an embodiment, the housing **61** includes a movable guard, mounted to the bottom base or the upper cap, and located on a side where the auxiliary cutting module **63** is located. When the auxiliary cutting module **63** is mounted to the housing **61**, the movable guard moves upward, to prevent the working of the auxiliary cutting module from impact. When the auxiliary cutting module **63** is not mounted to the housing **61**, the movable guard moves downward, to prevent the user from putting a hand or a foot in to contact the main cutting module **53**. In other embodiments, when the auxiliary cutting module **63** is mounted to the housing **61**, the part of the upper cap is detached from the housing **61**. When the auxiliary cutting module **63** is not mounted to the housing **61**, the part of the upper cap is mounted to the housing **61**. In an embodiment, a maximum radius of the auxiliary cutting area is set. This maximum radius is less than or equal to a distance between the second rotating axis and another structure of the robotic mower **11**. Continuing to refer to FIG. 4, a limiting element **37** is mounted at an edge of the auxiliary cutting area, and is configured to limit the length of the trimmerline, thereby limiting the maximum radius of the auxiliary cutting area. The auxiliary cutting module **63** is mounted to a side of the vertical axis **111** of the housing **61**. Because the trimmerline is subject to relatively severe wear in a working process, the trimmer head is frequently uncoiled in the working process. That is, a segment of the trimmerline is uncoiled. Generally, the uncoiled trimmerline has a relatively fixed length. However, a conventional trimmer head uncoiling structure inevitably uncoils the trimmerline by a length greater than a normal length. In this case, during the working of the trimmer head, the trimmerline hits another structure such as the moving module **51** or the main cutting module **53** of the robotic mower **11**, resulting in damage to a particular degree. In this embodiment, the limiting element **37** is mounted to the housing **61**, and the limiting element **37** includes a blade, configured to cut off a trimmerline part exceeding a set length. The limiting element **37** limits the length of the trimmerline, to ensure the working areas of the auxiliary cutting module **63** and other modules do not interfere with each other.

[0119] In an embodiment, in the moving direction of the robotic mower **11**, the auxiliary wheel is located on the front side, and the drive wheel is located on the rear side. The rear side of the auxiliary wheel and the rear side of the auxiliary cutting module **63** form an area A. A mounting

height of the limiting element **37** is approximately parallel to the cutting area of the auxiliary cutting module **63**, and the limiting element is located in the area A. In this embodiment, the limiting element **37** is mounted to the area A, and is close to the auxiliary wheel. When the robotic mower **11** encounters an obstacle, the auxiliary wheel encounters and moves over the obstacle before the limiting element **37**, and the limiting element **37** located on the rear side of the auxiliary wheel can also move over the obstacle along with the auxiliary wheel. In other embodiments, the limiting element **37** is mounted to the area A and is close to the drive wheel. When the obstacle is located on the rear side of the robotic mower **11**, the drive wheel is more likely to contact and move over the obstacle. The limiting element **37** can move over the obstacle accordingly, to avoid a collision. In other embodiments, the moving module **51** includes two drive wheels on the front side and two drive wheels on the rear side, but does not include an auxiliary wheel. The limiting element **37** is also located in the area A.

[0120] In an embodiment, the limiting element **37** is mounted to a movable structure, for example, an elastic structure. When the lawn mower encounters an obstacle, the limiting element **37** can be driven by the movable structure to avoid the obstacle. After the lawn mower leaves the obstacle, the limiting element **37** can automatically restore the original position. In an embodiment, the height of the limiting element **37** is greater than 30 millimeters. That is, a distance between the limiting element **37** and the horizontal ground is greater than 30 millimeters. In an embodiment, the auxiliary cutting module **63** includes a trimmer head, and the control module **59** controls the trimmer head to rotate backward. If the trimmer head is located on the left side of the housing **61**, the control module **59** controls the trimmer head to rotate counterclockwise. If the trimmer head is located on the right side of the housing **61**, the control module **59** controls the trimmer head to rotate clockwise. When the trimmer head rotates to perform cutting, grass cuttings moving in a corresponding rotating direction are generated. Therefore, if the trimmer head rotates forward, grass cuttings tend to accumulate on the front side of the robotic mower **11**. After the robotic mower **11** moves forward, the trimmer head acts on the accumulated grass cuttings again, causing an increase in the workload of the trimmer head. Therefore, when the trimmer head rotates backward, the workload of the trimmer head can be reduced. Further, for the auxiliary wheel mounted below the housing **61**, if grass cuttings accumulate on the auxiliary wheel, it is very difficult to discharge the grass cuttings. If the drive wheel is not covered by the housing **61**, it is relatively easy to discharge grass cuttings. Therefore, when the trimmer head rotates backward, the moving module can be assisted in discharging grass cuttings, to prevent the movement of the robotic mower **11** from impact.

[0121] In an embodiment, an isolation cover is disposed between the main cutting module **53** and the auxiliary cutting module **63**. The isolation cover at least partially covers the main cutting module **53**, or at least partially covers the auxiliary cutting module **63**, thereby preventing grass cuttings from entering the auxiliary cutting module **63** during the working of the main cutting module **53** or grass cuttings from entering the main cutting module **53** during the working of the auxiliary cutting module **63**.

[0122] In an embodiment, the main cutting module **53** includes a blade disposed obliquely. The auxiliary cutting module **63** includes an obliquely disposed trimmer head or an obliquely disposed trimmerline, so that a tilt angle of the trimmerline during working is consistent with a tilt angle of the blade of the main cutting module **53**, thereby keeping a cutting section surface after cutting by the auxiliary cutting module **63** consistent with a cutting section surface after cutting by the main cutting module **53**, to obtain a better cutting effect. In an embodiment, the tilt angle is 3 degrees.

[0123] In an embodiment, the trimmer head is mounted with two trimmerlines, and there is a height difference between the trimmerlines in the vertical direction. When the trimmer head is working, the two trimmerlines respectively form a first cutting plane and a second cutting plane. If a lawn has a relatively large height, the first cutting plane and the second cutting plane may separately cut grass. Because the working frequency of the auxiliary cutting module **63** is lower than that of the

main cutting module **53**, the height of grass in a to-be-trimmed area is greater than grass in the working area **107**. If the trimmer head is mounted with one trimmerline, grass cuttings after cutting by the trimmer head are relatively long. If the two trimmerlines are mounted to cut grass in the to-be-trimmed area, grass cuttings can be further reduced in size, to prevent scattered grass cuttings from affecting the beauty of a lawn or even affecting growth of the lawn.

[0124] In an embodiment, the control module **59** determines, by detecting a working parameter of the trimmer head, a length by which the trimmerline protrudes from the trimmer head. If it is determined that the length is less than a threshold, the trimmer head is controlled to automatically uncoil, that is, the trimmerline is automatically uncoiled by a particular length, so that the auxiliary cutting area restores the original working area. Specifically, parameters such as a working voltage of the trimmer head may be detected, and the control module **59** determines a relationship between the working voltage and the threshold, thereby controlling the trimmer head to uncoil.

[0125] In an embodiment, the trimmerline is wound around the coil disk mounted to the trimmer head. When the trimmerline on the coil disk is used up, the coil disk needs to be replaced with a new coil disk for use by the working of the trimmer head. The control module **59** detects the working parameter of the trimmer head to determine whether the trimmerline is used up, and if the trimmerline is used up, prompts a user to make a replacement. Specifically, the trimmer head includes a drive motor. A sensor is used to detect the rotational speed, current, power, or the like of the motor. When a measured signal of the drive motor of the trimmer head is less than a preset value, it is determined that the trimmerline is used up. When the control module **59** determines that the trimmerline is used up, a prompting apparatus such as a photoelectric module or the like mounted to the housing **61** may be used to make a prompt, or a wireless signal transmission manner may be used to transmit a line replacement prompt signal to a terminal device such as a mobile phone or a computer.

[0126] In an embodiment, the moving module **51** may move along the boundary line **103** in two directions, namely, a first direction for ensuring that the auxiliary cutting module **63** can cut to edge and a second direction opposite the first direction. The control module **59** controls the moving module **51** to move along the boundary line **103** in the first direction. When the robotic mower **11** moves in the first direction, the other side relative to the vertical axis **111** of one side on which the auxiliary cutting module **63** is mounted faces the outside of the working area **107**, to enable the auxiliary cutting area to extend outside the boundary line **103** or the boundary line **103**, thereby cutting an area that the main cutting module **53** cannot cut.

[0127] FIG. **7** is a schematic diagram of a moving direction of a robotic mower in an embodiment. As shown in FIG. **7**, the auxiliary cutting module **63** is mounted to the left side of the vertical axis **111**. The control module **59** needs to control the moving module **51** to move along the boundary line **103** in a clockwise direction. That is, along the boundary line **103**, the clockwise direction is the first direction, and the counterclockwise direction is the second direction.

[0128] FIG. **8** is a schematic diagram of a moving direction of a robotic mower in still another embodiment. As shown in FIG. **8**, the auxiliary cutting module **63** is mounted to the right side of the vertical axis **111**. The control module **59** needs to control the moving module **51** to move along the boundary line **103** in a counterclockwise direction. That is, along the boundary line **103**, the counterclockwise direction is the first direction, and the clockwise direction is the second direction.

[0129] Continuing to refer to FIG. **12**, in an embodiment, the boundary detection module includes a first magnetic field sensor and a second magnetic field sensor. The first magnetic field sensor and the second magnetic field sensor detect magnetic field signals generated from currents in the boundary line **103**, to determine whether the sensor is located inside the boundary line **103** or outside the boundary line **103**. The first magnetic field sensor is mounted to the left side of the vertical axis **111**, and the second magnetic field sensor is mounted to the right side of the vertical axis **111**. To control the direction in which the robotic mower **11** moves along the boundary line **103** to be the clockwise direction, the control module **59** needs to control the first magnetic field

sensor to be located outside the boundary line **103** and the second magnetic field sensor to be located inside the boundary line **103**. To control the direction in which the self-moving lawn mower **11** moves along the boundary line **103** to be the counterclockwise direction, the control module **59** needs to control the first magnetic field sensor to be located inside the boundary line **103** and the second magnetic field sensor to be located outside the boundary line **103**. In other embodiments, the control module **59** may determine, by using the magnetic field signal detected by the first magnetic field sensor and the second magnetic field sensor, whether the sensor is located inside or outside the boundary line **103**, and may further control the robotic mower **11** by using the strength of the magnetic field signal to move along a side of the boundary line **103** and control the moving direction. Details are not described herein again.

[0130] Continuing to refer to FIG. 4, FIG. 5, and FIG. 6, in an embodiment, a distance between a first rotating axis and the vertical axis **111** is a first distance, and a distance from the second rotating axis to the vertical axis **111** is a second distance. A difference value between the second distance and the first distance is less than or equal to a sum of the radii of the main cutting area and the auxiliary cutting area. As the robotic mower **11** moves along the boundary line **103**, an area after the main cutting module **53** works on a lawn is approximately an area a with a width equal to the diameter of the main cutting area, and an area after the auxiliary cutting module **63** works on the lawn is approximately an area b with a width equal to the diameter of the auxiliary cutting area. If the difference value between the second distance and the first distance is greater than the sum of the radii of the main cutting area and the auxiliary cutting area, there is a gap between the area a and the area b in the transverse direction. As a result, there is still an uncut area around the obstacle after the main cutting module **53** and the auxiliary cutting module **63** work. In this way, when the robotic mower **11** moves along the boundary line **103** in a specific manner and completes cutting, the control module **59** further needs to control a relative distance between the moving module **51** and the boundary line **103** according to the detection of the signal strength of the boundary line **103** by the boundary detection module, thereby implementing cutting in the uncut area. This working manner increases the load of the control module **59** and also reduces the working efficiency of the robotic mower **11**. Therefore, when the difference value between the second distance and the first distance is less than or equal to the sum of the radii of the main cutting area and the auxiliary cutting area, the area a and the area b are tangent or intersect in the transverse direction, to ensure that after the main cutting module **53** and the auxiliary cutting module **63** work, complete cutting is implemented around the obstacle.

[0131] In an embodiment, to prevent the auxiliary cutting module **63** from contacting an uneven ground, the free movement of the robotic mower **11** is affected. The height of the auxiliary cutting module **63** is greater than or equal to 30 mm. That is, a distance between the auxiliary cutting module **63** and the horizontal ground is greater than or equal to 30 mm. FIG. 10 is a schematic diagram of a height adjustment structure in an embodiment. As shown in FIG. 10, the main cutting module **53** includes a main height adjustment module, configured to adjust the height of the main cutting module **53**. Generally, the cutting height of the main cutting module **53** is between 20 millimeters and 100 millimeters. Users in different districts such as Europe and America have different requirements. To ensure the passability of the robotic mower **11** and adapt to the main cutting module **53**, the cutting height of the auxiliary cutting module **63** is greater than or equal to 20 millimeters. In an embodiment, to obtain a cutting effect, the cutting height of the auxiliary cutting module **63** also cannot be excessively high, and to adapt to the main cutting module **53**, the cutting height of the auxiliary cutting module **63** is less than or equal to 100 millimeters. If the maximum cutting height of the main cutting module **53** is 80 millimeters, the cutting height of the auxiliary cutting module **63** is less than or equal to 80 millimeters. In an embodiment, to ensure a visual effect, it is necessary to keep the cutting height of the auxiliary cutting module **63** and the cutting height of the main cutting module **53** within a particular range. Optionally, the cutting height of the auxiliary cutting module **63** is set to an average value of the minimum cutting height

and the maximum cutting height of the main cutting module.

[0132] Continuing to refer to FIG. **10**, in an embodiment, the auxiliary cutting module **63** includes an auxiliary height adjustment module, configured to adjust the height of the auxiliary cutting module **63**. A height adjustment range of the auxiliary cutting module **63** is the same as that of the main cutting module **53**. In an embodiment, the main height adjustment module and the auxiliary height adjustment module are in transmission connection by a transmission module, so that when the main height adjustment module adjusts the height of the main cutting module **53**, the auxiliary height adjustment module can be driven to adjust the height of the auxiliary cutting module **63**.

[0133] In an embodiment, during the working of the auxiliary cutting module **63**, the main cutting module **53** is started in a preset manner, to prevent grass cuttings generated during the working of the auxiliary cutting module **63** from accumulating on the main cutting module **53**. Therefore, the main cutting module **53** may be periodically started to rotate to make grass cuttings fall off.

Alternatively, the main cutting module **53** may be started when it is detected that the weight is greater than a preset value or is started when a distance between the auxiliary cutting module **63** and the user terminal **9** satisfies a preset distance. In this embodiment, the control module **59** may control the main cutting module to be started at a normal working speed, or the main cutting module may be started at a higher or lower speed, provided that grass cuttings can fall off.

[0134] In an embodiment, the housing **61** is mounted with an alarm module. The alarm module may include an alarm lamp, a buzzer, or the like. During the working of the auxiliary cutting module **63**, the control module **59** controls the alarm module to be started, thereby prompting a user, to avoid accidental contact with the auxiliary cutting module **63**. The alarm module includes a sound alarm, a light alarm, or the like.

[0135] In an embodiment, during the working of the auxiliary cutting module **63**, the strength of noise generated by the auxiliary cutting module **63** is greater than a preset noise strength, and the preset noise strength is greater than the strength of noise generated during the working of the main cutting module **53**. In this embodiment, at a position one meter away from the auxiliary cutting module **63**, the strength of the noise generated by the auxiliary cutting module **63** is greater than or equal to 60 dB.

[0136] In an embodiment, the robotic mower **11** may pass the parking station **105** when moving along the boundary line **103**, leading to the contact between the auxiliary cutting element and the parking station **105**, to damage the parking station **105** or damage the auxiliary cutting element. A trimmerline is used as an example. To reduce the wear of the trimmerline and damage to the parking station **105**, a rounded corner design may be used for a partial surface of the parking station **105**, to prevent the trimmerline from contacting an edge or a corner of the parking station **105**.

[0137] In an embodiment, the height of the parking station **105** is lower than the height of the auxiliary cutting area during the working of the auxiliary cutting module **63**. In an embodiment, for a plane in which the auxiliary cutting area is located, a distance between the parking station **105** and the second rotating axis is greater than the radius of the auxiliary cutting area, so that the auxiliary cutting element cannot contact the parking station **105**.

[0138] In an embodiment, an automatic mowing system has at least two working modes: a main cutting mode and an auxiliary cutting mode. In the main cutting mode, the control module **59** automatically controls the robotic mower **11** to move and work in the boundary line **103**, or move and work along the boundary line **103**. In the auxiliary cutting mode, if continuously receiving a preset signal, the control module **59** controls the auxiliary cutting module **63** at least based on the preset signal to work. If the preset signal received by the control module **59** is interrupted, the control module **59** controls the auxiliary cutting module **63** to stop working. A user operates a user terminal **30** to indirectly control whether the auxiliary cutting module **63** works, to ensure that the user monitors and decides whether the auxiliary cutting module **63** works, so that the user can make a fast response to an abnormal case. In this way, even if the auxiliary cutting module **63** may accidentally contact a human or an animal in a working process, the user can perform monitoring to

avoid an emergency.

[0139] FIG. 13 is a schematic structural diagram of a user terminal in an embodiment. As shown in FIG. 13, the user terminal 30 includes a remote communication module 36, a processing module 32, and a button 34. The button 34 includes a button 341 and a button 343. If the user respectively presses the button 341 and the button 343, a start signal and a control signal are generated. The processing module 32 sends the start signal and the control signal by using the remote communication module 36. The robotic mower 11 further includes a wireless communication module. If a connection is established between the remote communication module 36 and the wireless communication module, when receiving the start signal and the control signal by using the wireless communication module, the control module 59 controls the robotic mower 11 to start the auxiliary cutting mode. In this embodiment, a misoperation of the user can be avoided when two or two more buttons need to be pressed to start the auxiliary cutting mode. The auxiliary cutting mode may further be started in various manners such as voice input or password input.

[0140] In an embodiment, if the start signal and the control signal received by the control module 59 satisfy a preset condition, the robotic mower is controlled to switch to the auxiliary cutting mode. In this embodiment, the preset condition includes that the processing module 32 receives the start signal and the control signal within a preset time. In other embodiments, the preset condition includes that the processing module 32 receives the start signal and the control signal in a preset order.

[0141] In an embodiment, if the user terminal 30 is in a working state, when the user presses the button 141 and the button 143, the processing module 32 respectively receives the start signal and the control signal and the preset condition is satisfied, the processing module 32 controls the remote communication module 36 to send the control signal. When receiving the control signal, the control module 59 controls the robotic mower to switch to the auxiliary cutting mode.

[0142] In an embodiment, a start button is disposed in the housing 21, and a control button is disposed in the user terminal 30. When the user operates the start button, the control module 59 receives the start signal, and when the user operates the control button, the user terminal 30 sends the control signal. The control module 59 receives the control signal by using the wireless communication module. If the start signal and the control signal received by the control module 59 satisfy the preset condition, the control module 59 controls the robotic mower to switch to the auxiliary cutting mode.

[0143] If a communication connection is established between the user terminal 30 and the robotic mower 11, when the user continuously presses the button 343, the processing module 32 sends the control signal by using the remote communication module 36. In the auxiliary cutting mode, if the control module 59 continuously receives the control signal by using the wireless communication module, the control module 59 controls the auxiliary cutting module 63 to work. In the auxiliary cutting mode, the control module 59 continuously determines whether the control signal is received. If the control signal received by the control module 59 is interrupted, the control module 59 controls the auxiliary cutting module 63 to stop working.

[0144] Continuing to refer to FIG. 13, in an embodiment, the user terminal 30 includes a button 341 and a button 343, and further includes a button 345. When the user presses the button 345, the user terminal 30 sends a stop signal, and the control module 59 controls the auxiliary cutting module 63 according to the received stop signal to stop working.

[0145] In an embodiment, the button 343 is a contact sensor. The user may continuously contact the button 343 to implement the continuous operation of the button 343, so that the user terminal 30 continuously sends the control signal. When the user no longer contacts the button 343, the user terminal 30 no longer sends the control signal. Optionally, the button 341 and/or the button 345 may be alternatively a contact sensor. The contact sensor may be specifically a capacitive sensor, a piezoelectric sensor, or the like. In other embodiments, the user terminal 30 is completely or partially mounted with a capacitive sensor, so that when the user contacts a corresponding position

of the user terminal **30**, the capacitive sensor can detect an operation of the user. The user terminal **30** correspondingly sends a preset signal. When intending to stop the working of the auxiliary cutting module **63**, the user may press the button **345** to enable the user terminal **30** to send the stop signal or may directly release the user terminal **30**. In this embodiment, the contact sensor is used in place of a conventional button, so that it becomes more convenient for the user to continuously operate the user terminal **30**. Optionally, the button **341** and/or the button **345** may be alternatively another inductive sensor, for example, an infrared sensor, or an acceleration sensor.

[0146] In an embodiment, the user terminal **30** includes a direction control button. The user operates the direction control button of the user terminal **30** to send a direction signal, and control a moving direction of the robotic mower **11**. In this embodiment, when a distance between the user terminal **30** and the robotic mower **11** is less than a direction control distance, the user is allowed to control the moving direction of the robotic mower **11** by using the direction control button. In an embodiment, when the distance between the user terminal **30** and the robotic mower **11** is greater than the direction control distance, the control module **59** ignores the direction signal sent by the user terminal **30**, that is, does not allow the user to control the moving direction of the robotic mower **11** by using the direction control button. In this embodiment, the direction control distance is 6 meters. Optionally, when receiving the direction signal sent by the user terminal **30**, the control module **59** controls the auxiliary cutting module **63** to stop working.

[0147] In an embodiment, the user terminal **30** is a movement terminal. The user terminal **30** may be a terminal device that can be connected to a communication network based on the Internet Protocol and having a data sending function. Specifically, for example, a client may be a mobile smart phone, a computer (including a notebook computer, or a desktop computer), a tablet electronic device, a personal digital assistant (PDA), an intelligent wearable device, or the like.

[0148] FIG. **14** is a schematic structural diagram of a user terminal in another embodiment. As shown in FIG. **14**, in an embodiment, the user terminal **30** is a movement terminal. The user may send a signal by operating a virtual button or a physical button by using the user terminal **30**, and operates a specific button to send a signal to control the auxiliary cutting module **63** to work or stop working. In other embodiments, the user may send a signal by not operating a specific button to control the auxiliary cutting module **63**. When the user holds the user terminal **30** in hand, the user terminal **30** uses an existing sensor to detect a state in which the user terminal is kept is not a stationary state. For example, the posture of the user terminal **30** is determined by using a compass or a gyroscope. If the posture continuously changes, the user terminal **30** sends the control signal, and the control module **59** controls the working of the auxiliary cutting module **63**. If the posture remains unchanged, the user terminal **30** no longer sends the control signal, and the auxiliary cutting module **63** stops working. In another example, a camera is used to capture an image. If the image changes relatively frequently, the user terminal **30** sends the control signal, and the control module **59** controls the auxiliary cutting module **63** to work. If the image nearly does not change, the auxiliary cutting module **63** stops working. Provided that an existing sensor of the user terminal **30** can be used to detect a handheld state of the user to ensure that the robotic mower **11** works under the supervision of the user, the user terminal **30** can output the control signal by using the sensor to enable the control module **59** to control the auxiliary cutting module **63** to work.

[0149] In an embodiment, the user terminal **30** is the movement terminal, the user terminal **30** includes a pressure sensing module. When the pressure sensing module detects the pressing of a user, it is considered that the user is in a state of supervising the working of the robotic mower **11**, and the user terminal **30** can send the control signal by using an output of a pressure sensor, so that the control module **59** controls the working of the auxiliary cutting module **63**.

[0150] In an embodiment, the user terminal **30** is a movement terminal. The user terminal **30** includes an interface, configured to implement an electrical connection to an external device. The user terminal **30** may be connected to the external device by an interface. The external device may include an accelerator, a gyroscope, or the like. A user of the external device detects a supervised

state of the user. The user terminal **30** sends the control signal by using a detection signal outputted by the external device, so that the control module **59** controls the auxiliary cutting module **63** to work.

[0151] In an embodiment, the user terminal **30** may further include an APP that is run on any foregoing listed device and has the function of sending a function instruction to the robotic mower **11**. When the APP is switched to run in the background, the control signal sent by the user terminal **30** is stopped, and the control module **59** controls the auxiliary cutting module **63** to stop working. Alternatively, when the APP is switched to run in the background, the user terminal **30** sends a stop signal, and the control module **59** controls the auxiliary cutting module **63** to stop working. Alternatively, when the APP is switched to run in the background, the user terminal **30** sends a stop signal, and the control module **59** controls the auxiliary cutting module **63** and the moving module **51** to stop working. The APP being switched to run in the background includes the user terminal being in a call answering state, a short message reading state, or the like. In an embodiment, if a call is connected and the user hangs up within a particular time, the user terminal **30** is not affected by the operation. If the user does not hang up within a particular time, the user terminal **30** sends a stop signal to control the auxiliary cutting module **63** and/or the moving module **51** to stop working.

[0152] In an embodiment, the control module **59** determines a relationship between the strength of a signal sent by the user terminal **30** and a preset strength. If the strength of a signal received by the wireless communication module is less than a preset strength, the control module **59** controls the auxiliary cutting module **63** to stop working. In this case, the user continues to operate the user terminal **30**. Although the user terminal **30** can send the control signal, the wireless communication module cannot receive the control signal, or even if the wireless communication module can receive the control signal, the control module **59** determines a state that the control signal is not received, that is, the control module **59** controls the auxiliary cutting module **63** to stop working. Herein, the strength of the signal is compared with the preset strength to keep the user terminal **30** and the robotic mower **11** within a particular distance, or parameters other than the strength of the signal may be used to determine a distance relationship. In other embodiments, the control module **59** determines the distance relationship between the user terminal **30** and the robotic mower **11** by using the control signal received by the wireless communication module. If a distance between the user terminal **30** and the robotic mower **11** is greater than a first preset distance, the auxiliary cutting module **63** is controlled to stop working.

[0153] In an embodiment, when the distance between the user terminal **30** and the robotic mower **11** is within different distance ranges, the auxiliary cutting module **63** has different working energy. When the working energy of the auxiliary cutting module **63** is relatively high, to ensure that the user can recognize an abnormal case in time and perform control by using the user terminal **30**, the user terminal **30** and the robotic mower **11** need to be constrained within the first preset distance. If the distance between the robotic mower **11** and the user terminal **30** is less than the second preset distance, the control module **59** controls the auxiliary cutting module **63**, to enable the working energy of the auxiliary cutting module **63** to be less than first preset energy. If the distance between the robotic mower **11** and the user terminal **30** is greater than the second preset distance and less than a first preset distance, the control module **59** controls the auxiliary cutting module **63** to reduce working energy, to enable the working energy of the auxiliary cutting module **63** to be less than second preset energy, and the second preset energy is less than the first preset energy. The first preset energy is 0.5 J, and the second preset energy is 0.25 J.

[0154] For a specific auxiliary cutting module, the working energy of the auxiliary cutting module is mainly affected by a working speed. In an embodiment, the auxiliary cutting module **63** has different working speeds in different cases. When the distance between the user terminal **30** and the robotic mower **11** is greater than the second preset distance, the working speed of the auxiliary cutting module **63** is low. When the distance between the user terminal **30** and the robotic mower

11 is less than the second preset distance, the working speed of the auxiliary cutting module **63** is high. In an embodiment, the working speed of the auxiliary cutting module **63** include at least two speeds: a first working speed and a second working speed. The first working speed is a high speed, and the second working speed is a low speed. The control module **59** determines a relationship between the distance between the user terminal **30** that sends the control signal and the remote communication module **36** and the second preset distance and the first preset distance, if the distance between the user terminal **30** and the robotic mower **11** is greater than the first preset distance, the user terminal **30** and the robotic mower **11** cannot establish a valid communication connection, and the control module **59** controls the auxiliary cutting module **63** to stop working. If the distance between the user terminal **30** and the robotic mower **11** is less than the second preset distance, the auxiliary cutting module **63** is controlled to work at the first working speed. If the distance is greater than the second preset distance and less than the first preset distance, the auxiliary cutting module **63** is controlled to work at the second working speed. If the distance is greater than the first preset distance, the auxiliary cutting module **63** is controlled to stop working. Because the auxiliary cutting module **63** works at the first working speed, the generated energy is relatively high, and a human or an animal may be injured. Therefore, when the user is relatively far away from the self-moving device **1**, the auxiliary cutting module **63** works at the second working speed, and the generated energy is relatively low, to reduce or avoid injury. In this way, if the area of the working area **107** is relatively large, during the movement of the robotic mower **11**, if the user does not move, the distance between the user and the robotic mower **11** exceeds the second preset distance. Through the switching between working speeds, it can be avoided that the auxiliary cutting module **63** frequently switches between a working state and a non-working state, and the user can further be prompted to adjust the position. In this embodiment, the first preset distance is 20 meters, and the second preset distance is 6 meters. In other embodiments, the values of the first preset distance and the second preset distance may be adjusted according to a safety requirement, the area of a working area, and the like.

[0155] In an embodiment, in the auxiliary cutting mode, if the user does not operate the user terminal **30** within a specified time or the distance between the user terminal **30** and the robotic mower **11** exceeds a preset distance, when the user terminal **30** returns to a valid distance of the robotic mower **11** or the user operates the user terminal **30** again to send the control signal, the control module **59** receives a valid control signal, so that the control module **59** controls the auxiliary cutting module **63** to continue working. If a time that the control module **59** cannot receive the valid control signal exceeds a specified time, the auxiliary cutting mode is switched to the main cutting mode. After the auxiliary cutting mode is interrupted, the user needs to operate the user terminal **30** to send a start signal to restart the auxiliary cutting mode.

[0156] In an embodiment, the robotic mower **11** includes a path detection module **67** that can detect a preset path set by the user. The control module **59** controls the robotic mower **11** by using an output signal of the path detection module **67** to move along the preset path. The so-called moving along the preset path may be that the moving module **51** is partially located on one side of the preset path and partially located on the other side of the preset path or may be that the moving module **51** is completely located on a side of the preset path. This is not specifically limited herein. The object of setting the preset path is to enable the auxiliary cutting module **63** to complete a corresponding working task in a corresponding area when the robotic mower **11** moves along the preset path. The control module **59** automatically controls the self-moving device by using an output of a sensor to move, and the user does not need to control the moving direction of the robotic mower **11**. In this way, errors caused by the control of the user can be reduced, the degree of complexity of operations of the user can be reduced, and the degree of automation of the robotic mower **11** is maximized while the supervision of the user is ensured. In other embodiments, the preset path set by the user may be a part of the boundary line **103** or the boundary line **103**, so that the control module **59** may control the moving module **51** by using an output of the boundary

detection module to move along the preset path. The preset path may be a specific path set by the user in the working area **107** or may be a part of the boundary line **103** or the boundary line **103**. If the preset path is a part of the boundary line **103** or the boundary line **103**, the control module **59** may control the moving module **51** by using an output of the boundary detection module to move along the preset path. That is, the boundary detection module may be used as the path detection module **67** to output a detection result for determination by the control module **59**. Specifically, the boundary line **103** includes an outer boundary line disposed on an outer side boundary of the working area **107** and an inner boundary line disposed on an inner side boundary of the working area **107**.

[0157] In an embodiment, the controlling the moving module **51** to move along the preset path is specifically controlling the robotic mower **11** to move on the preset path. In the auxiliary cutting mode, the control module **59** determines whether the robotic mower **11** is on the preset path. If the robotic mower is not on the preset path, the control module **59** controls the moving module **51** to move, and controls the robotic mower **11** by using an output of the path detection module **67** to approach the preset path. If the robotic mower **11** is on the preset path, the control module **59** controls the moving module **51** to move along the preset path.

[0158] In an embodiment, the preset path may include any one or more combinations of a physical path or an electrical path, and may be specifically a signal generation apparatus that generates a virtual signal, relative coordinates or absolute coordinates stored in the control module **59**, and the like. For example, the preset path is set by using a magnetic material, and may be a magnetic nail or a magnetic strip. The shape of the magnetic strip may be adjusted according to a requirement of the user, to adapt to a working requirement of the auxiliary cutting module **63**. Correspondingly, the path detection module **67** includes a sensor that detects a magnetic field generated by a magnetic material, and detects parameters such as the strength and direction of the magnetic field to enable the robotic mower **11** to move along the preset path.

[0159] In an embodiment, in the auxiliary cutting mode, if the control module **59** continuously receives the control signal, and the control module **59** determines that the robotic mower **11** is on the preset path, the auxiliary cutting module **63** is controlled to work. If the control module **59** continuously receives the control signal, and the control module **59** determines that the robotic mower **11** is not on the preset path, the auxiliary cutting module **63** is controlled to stop working. If the control signal received by the control module **59** is stopped, regardless of whether the robotic mower **11** is on the preset path, the control module **59** controls the auxiliary cutting module **63** to stop working. A position relationship between the robotic mower **11** and the preset path is determined to control the auxiliary cutting module **63**, so that the invalid working time of the auxiliary cutting module **63** can be reduced, thereby saving the energy of the energy module **57** and improving the working efficiency. Moreover, the auxiliary cutting module **63** is restricted to work on the preset path only, thereby reducing a working range of the auxiliary cutting module **63**, so that the possibility of causing accidental injury the auxiliary cutting module **63** can be reduced.

[0160] In an embodiment, in the auxiliary working mode, the control module **59** is configured to control the auxiliary working module to work as the self-moving device moving along a preset path, wherein the preset path comprises at least a part of a boundary; and the control module **59** is further configured to control the auxiliary working module to stop working at least in response to the self-moving device deviating from the preset path.

[0161] In an embodiment, the control module **59** is configured to control the auxiliary working module to stop working at least in response to the self-moving device deviating from the preset path by a distance greater than a preset distance threshold.

[0162] In an embodiment, the preset distance threshold may be selected from a range of 3 mm to 10 mm. Further, the preset distance threshold may be selected from a subrange of 3 mm to 7 mm. In an example, the preset distance threshold may be set to 3 mm. For instance, the control module **59** controls the auxiliary working module to stop working in response to the self-moving device

deviating from the preset path by a distance greater than 3 mm. In another example, the preset distance threshold may be set to 4 mm.

[0163] In an embodiment, the control module **59** is configured to control the auxiliary working module to stop working at least in response to the self-moving device deviating from the preset path for a time period greater than a preset time period threshold.

[0164] In an embodiment, the preset time period threshold may be selected from a range of 2 s to 5 s. Further, the preset time period threshold may be selected from a subrange of 2 s to 4 s. For example, the preset time period threshold may be set to 2 s. In other words, the control module **59** controls the auxiliary working module to stop working in response to the self-moving device deviating from the preset path for a time period greater than 2 s. In another example, the preset time period threshold may be set to 3 s. FIG. **15** is a schematic structural diagram of a robotic mower in an embodiment. As shown in FIG. **15**, the auxiliary cutting module **63** includes a pruning module. When the robotic mower **11** moves along the preset path, the auxiliary cutting module **63** faces a to-be-pruned area, so that after moving along the preset path, the robotic mower **11** can complete pruning work of the to-be-pruned area. Therefore, the user can use the auxiliary cutting mode of the robotic mower **11** to complete with ease work that originally needs to be completed by the user holding pruning scissors in hand.

[0165] In an embodiment, the robotic mower **11** includes a prompting module. The prompting module stores an additional condition for starting the auxiliary cutting mode, and may include a working schedule of the robotic mower **11**, the remaining energy of the energy module **57**, and the like. If the prompting module determines that the additional condition is satisfied, a prompt signal is sent to the user terminal **30**. The user may learn about the working state of the robotic mower **11** according to the prompt signal, to ensure more efficient manual control. The wireless communication module includes Bluetooth communication, Wi-Fi communication, cellular network communication, or the like.

[0166] In an embodiment, the robotic mower **11** includes a trimming mode. FIG. **11** is a schematic diagram of a position relationship between a robotic mower and an obstacle in an embodiment. As shown in FIG. **11**, the to-be-trimmed area includes at least a start point **100** and at least one end point **200**. The user sets a first mark **101** corresponding to the start point **100** and a second mark **201** corresponding to the end point **200** on a boundary line **13** or within a particular range of the boundary line **13**. The mark may be specifically a passive magnetic apparatus, a metal member, or the like. The robotic mower **11** is mounted with a mark detection module, and is configured to detect the first mark **101** and the second mark **201**. When the robotic mower **11** starts from a parking station **105** to move along the boundary line **13** in the first direction, if the mark detection module detects the first mark **101**, the auxiliary cutting module **33** is controlled to work. If the mark detection module detects the second mark **201**, the auxiliary cutting module **33** is controlled to stop working, so that the auxiliary cutting module **33** only works in the to-be-trimmed area. When the robotic mower **11** starts from the parking station **105** to move along the boundary line **13** in the first direction, a mark detected by the mark detection module first is the first mark **101**, and a mark detected subsequently is the second mark **201**. Because the to-be-trimmed area has a small range, a human or an animal is less likely to enter the to-be-trimmed area during the working of the robotic mower **11**, and is less likely to injure a human or an animal during the working of the auxiliary cutting module **33**.

[0167] Continuing to refer to FIG. **11**, in an embodiment, the robotic mower **11** is mounted with a boundary detection module **27**, and includes a distance detection module. A main direction detected by the distance detection module is the same as a facing direction of the auxiliary cutting module **33**, that is, the auxiliary cutting module faces the outer side of a working area **107**. In this embodiment, the to-be-trimmed area is an area between the boundary line **13** and an obstacle outside the boundary line **13**. When the robotic mower **11** moves along the boundary line **13** and approaches the obstacle, the distance detection module may detect a distance between the robotic

mower and the obstacle. When the robotic mower **11** moves along the boundary line **13** in the first direction, if the distance detected by the distance detection module is less than a preset distance, the control module **31** controls the auxiliary cutting module **33** to work. If the detected distance is greater than the preset distance, the control module **31** controls the auxiliary cutting module **33** to stop working.

[0168] Continuing to refer to FIG. **11**, in an embodiment, the robotic mower **11** includes a boundary learning mode. In the boundary learning mode, the robotic mower **11** moves along the boundary line **13** in the first direction. The user performs an operation to enable the control module **31** to record a first point **101** and a second point **201** on a boundary line and a start point **100** and an end point **200** corresponding to the to-be-trimmed area. The robotic mower **11** includes a communication module, which is mounted to the housing **21** and may communicate with user equipment **9** and receive a signal. When the robotic mower **11** moves along the boundary line **13** in the first direction, if the robotic mower **11** passes the start point **100** of the to-be-trimmed area, the user operates the user equipment **9** to send a learning signal, to enable the control module **31** to record the first point **101** on the boundary line **13**. If the robotic mower **11** passes the end point **200** of the to-be-trimmed area, and the user operates the user equipment **9** again to send a learning signal, to enable the control module **31** to record the second point **201** on the boundary line **13**. In the trimming mode, when the robotic mower **11** moves along the boundary line **13** in the first direction, the control module **31** controls the auxiliary cutting module **33** to start working from the first point **101** and stops working when passing the second point **201**. In other embodiments, to prevent a misoperation from changing the first point **101** and the second point **201** recorded by the control module **31**, the user needs to input a password or use another manner to release the locking of the record before the user can change the record.

[0169] It is apparent to a person skilled in the art the present invention may further have other implementations. However, provided that the technical essence used in the implementations are the same as or similar to that in the present invention, any change or replacement made based on the present invention falls within the protection scope of the present invention.

Claims

1. A self-moving device comprising: a housing; a moving module, configured to drive the housing to move; a main working module, configured to perform a main working task; an auxiliary working module, configured to perform an auxiliary working task; and a controller, configured to control the moving module, the main working module, and the auxiliary working module; the self-moving device is configured to operate in at least one of an automatic working mode or an auxiliary working mode, and wherein in the auxiliary working mode, the controller is further configured to: control the auxiliary working module to work as the self-moving device moves along a preset path, wherein the preset path comprises at least a part of a boundary; and control the auxiliary working module to stop working at least in response to the self-moving device deviating from the preset path.
2. The self-moving device according to claim 1, wherein in the auxiliary working mode, the controller is further configured to automatically control a moving direction of the moving module according to an output of a sensor.
3. The self-moving device according to claim 1, wherein the controller is further configured to control the auxiliary working module to stop working at least in response to the self-moving device deviating from the preset path by a distance greater than a preset distance threshold or for a time period greater than a preset time period threshold.
4. The self-moving device according to claim 1, wherein in the auxiliary working mode, the controller is further configured to: control a part of the auxiliary working module that faces outside a working area to rotate backward.

5. The self-moving device according to claim 1, further comprising: an isolation cover, disposed between the main working module and the auxiliary working module, at least partially covers the auxiliary working module.
6. The self-moving device according to claim 1, wherein the auxiliary working module comprises a trimmer head, a trimmerline is mounted on the trimmer head, and the trimmer head is configured to drive the trimmerline to rotate to cut grass.
7. The self-moving device according to claim 1, wherein in the auxiliary working mode, the controller controls the auxiliary working module based on a stop signal to stop working.
8. The self-moving device according to claim 7, wherein the self-moving device further comprises a wireless communication module, configured to receive the stop signal generated from an operation of a user.
9. The self-moving device according to claim 1, wherein the auxiliary working module is detachably connected to the self-moving device; the housing comprising: a chassis, an upper cover, mounted to the chassis, comprising: a removable section, covering a mounting location of the auxiliary working module, wherein: the removable section is separately detachable from the housing to provide access for attaching and detaching the auxiliary working module.
10. The self-moving device according to claim 1, wherein a distance between the auxiliary working module and a horizontal ground is greater than or equal to 30 mm.
11. The self-moving device according to claim 1, wherein a cutting height of the auxiliary working module is greater than or equal to 20 mm, less than or equal to 100 mm.
12. The self-moving device according to claim 3, wherein the auxiliary working module comprises an auxiliary height adjustment module, configured to adjust a height of the auxiliary working module.
13. The self-moving device according to claim 1, wherein in the auxiliary working mode, a working energy of the auxiliary working module is less than 5 J.
14. The self-moving device according to claim 1, wherein a cutting section surface after cutting by the auxiliary working module is consistent with a cutting section surface after cutting by the main cutting module.
15. The self-moving device according to claim 1, wherein the auxiliary working module comprises an auxiliary cutting motor, disposed in a motor protective cover, configured to drive a trimmer head to rotate, wherein the motor protective cover comprises an outlet for an output shaft of the auxiliary cutting motor to extend out, and apart from the outlet, the motor protective cover is a sealed structure.
16. The self-moving device according to claim 15, wherein there is a gap between the motor protective cover and a shell of the auxiliary cutting motor in a height direction for an air outlet of the auxiliary cutting motor to discharge an airflow, to implement airflow circulation in the motor protective cover.
17. The self-moving device according to claim 15, wherein a sealing member is disposed between the outlet of the motor protective cover and the output shaft of the auxiliary cutting motor.
18. An automatic working system, comprising: a self-moving device comprising: a housing; a moving module, configured to drive the housing to move; a main working module, configured to perform a main working task; an auxiliary working module, configured to perform an auxiliary working task; a controller, configured to control the moving module, the main working module, and the auxiliary working module; and the self-moving device is configured to operate in an automatic working mode or an auxiliary working mode, and wherein in the auxiliary working mode, the controller is configured to: obtain a preset path, wherein the preset path comprises at least a part of a boundary; control the auxiliary working module to work as the self-moving device moves along the preset path; and control the auxiliary working module to stop working at least in response to the self-moving device deviating from the preset path.
19. The automatic working system according to claim 18, wherein further comprising a station,

configured to dock and charge the self-moving device, the station comprises a wireless power transmitter, configured to establish inductive coupling with a corresponding receiver in the self-moving device for contactless energy transfer.

20. The automatic working system according to claim 18, wherein the auxiliary working module comprising a coil disk wound with a trimmerline and configured such that the trimmerline is rotated about a center of the coil disk to form an auxiliary cutting area, in a plane in which the auxiliary cutting area is located, a distance between the station and the center of the coil disk is greater than a radius of the auxiliary cutting area.
