

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284342

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

WAKUDA; Hiroshi

STYLUS PEN AND INPUT SYSTEM

Abstract

A stylus pen includes: a pen part; a vibrator provided in the pen part; and a controller configured to generate a drive signal for driving the vibrator. The controller is configured to generate the drive signal such that the vibrator, when driven by the drive signal, causes the pen part to vibrate based on an impulse response of a spring-mass-damper system.

Inventors: WAKUDA; Hiroshi (Miyagi, JP)

Applicant: ALPS ALPINE CO., LTD. (Tokyo, JP)

Family ID: 91484798

Appl. No.: 19/220607

Filed: May 28, 2025

Foreign Application Priority Data

JP	2022-197695	Dec. 12, 2022
----	-------------	---------------

Related U.S. Application Data

parent WO continuation PCT/JP2023/036509 20231006 PENDING child US 19220607

Publication Classification

Int. Cl.: G06F3/01 (20060101); G06F3/0354 (20130101); G06F3/038 (20130101)

U.S. Cl.:

CPC G06F3/016 (20130101); G06F3/03545 (20130101); G06F3/0383 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of International Application No. PCT/JP2023/036509, filed on Oct. 6, 2023, and designated in the U.S., which is based upon and claims priority to Japanese Patent Application No. 2022-197695, filed on Dec. 12, 2022. The entire contents of these applications are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present disclosure relates to a stylus pen and an input system.

2. Description of the Related Art

[0003] An existing vibration system includes, for example, a linear vibration motor and a controller that controls the drive current waveform of the vibration motor. The drive current waveform is composed of large unit waves that are identical to each other and arranged in a consecutive manner in the time domain. Each large unit wave has: a first region having a waveform with a low amplitude in one period T , which is the width of the large unit wave in the time domain; and a second region having a waveform with a larger amplitude than the first region. The first region and the second region appear alternately in the time domain. The vibration system produces vibrations in a stylus pen (see, for example, patent document 1).

CITATION LIST

[Patent Document]

[0004] [Patent Document 1] Unexamined Japanese Patent Application Publication No. 2019-066960

SUMMARY OF THE INVENTION

[0005] Now, assuming that the above vibration system is incorporated in a stylus pen, the vibration system does not drive the vibration motor (vibrator) based on vibrations that transmit to the user's hand while the user is really writing with the stylus pen (that is, does not rely on vibrations produced when the user writes or draws something on a sheet of paper with an ink ballpoint pen), but drives the vibration motor simply in vibration patterns that mimic the vibrations that are produced while writing is in progress. A stylus pen incorporating the above vibration system therefore has difficulty providing a realistic tactile experience that feels as if really writing with a pen.

[0006] The present disclosure therefore aims to provide a stylus pen and an input system that can provide a realistic tactile experience that feels as if really writing with a pen.

[0007] According to an embodiment of the present disclosure, a stylus pen includes: a pen part; a vibrator provided in the pen part; and a controller configured to generate a drive signal for driving the vibrator. The controller is configured to generate the drive signal such that the vibrator, when driven by the drive signal, causes the pen part to vibrate based on an impulse response of a spring-mass-damper system.

[0008] According to an embodiment of the present disclosure, an input system includes: a stylus pen; a detector configured to detect contact of the stylus pen with an operation surface; a vibrator; and a controller configured to generate a drive signal for driving the vibrator. The controller is configured to generate the drive signal such that the vibrator, when driven by the drive signal, causes the stylus pen to vibrate based on an impulse response of a spring-mass-damper system.

[0009] It is thus possible to provide a stylus pen and an input system that can provide a realistic tactile experience that feels as if really writing with a pen.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1A is a diagram showing an example state in which a stylus pen according to an embodiment of the present disclosure is used;

[0011] FIG. 1B is a diagram showing an example mechanical model combining fingers and a pen;

[0012] FIG. 2A is a diagram showing an example of how to measure a vibration waveform;

[0013] FIG. 2B is a diagram showing an example result of measuring vibration waveforms representing vibrations produced in a ballpoint pen by the act of writing;

[0014] FIG. 2C is a diagram showing an example result of measuring vibration waveforms representing vibrations produced in a ballpoint pen by the act of writing;

[0015] FIG. 3 is a diagram showing example results of measuring the rate of acceleration, writing angular velocity, and writing pressure that are produced in a ballpoint pen and change over time;

[0016] FIG. 4A is a diagram showing examples of how an internal model's rate of acceleration behaves in the time domain and the frequency domain, estimated based on an AR model;

[0017] FIG. 4B is a diagram showing examples of how an internal model's rate of acceleration behaves in the time domain and the frequency domain, estimated based on an ARMA (Prony) model;

[0018] FIG. 4C is a diagram showing examples of how vibration's acceleration behaves in the time domain and the frequency domain, estimated based on an ARMA (Steiglitz-Mcbride) model;

[0019] FIG. 5A is a diagram showing examples of how the average frequency and normalized standard deviation of vibrations behave with respect to the pen's writing angular velocity;

[0020] FIG. 5B is a diagram showing examples of how the average wave height of vibration's acceleration and the ratio "standard deviation/average wave height" behave with respect to the pen's writing angular velocity;

[0021] FIG. 5C is a histogram showing an example distribution of rates of vibration's acceleration;

[0022] FIG. 6 is a diagram showing examples of how the pen's writing angular velocity and the rate of acceleration of vibration change over time; and

[0023] FIG. 7 is a block diagram showing an inner structure of a stylus pen according to an embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0024] A stylus pen and an input system according to an embodiment of the present disclosure will be described below.

[0025] The XYZ coordinate system will be used in the following description. Directions that run parallel to the X axis ($\pm X$ directions), directions that run parallel to the Y axis ($\pm Y$ directions), and directions that run parallel to the Z axis ($\pm Z$ directions) are orthogonal to each other. Also, in the following description and the accompanying drawings, the $-Z$ direction may be referred to as the "lower side", "bottom", etc. and the $+Z$ direction may be referred to as the "upper side", "top", etc. for ease of explanation. Nevertheless, these terms do not necessarily represent the common idea of up and down. Also, "plan view" as used herein refers to a view on an XY plane.

[0026] In the following description, the length, width, thickness, etc. of each component/part may be exaggerated to make the structure(s) easier to understand. In addition, terms such as "parallel", "up", "down", etc. as used herein may allow inaccuracies insofar as they do not impair the advantages the present disclosure brings about.

Embodiment

[0027] FIG. 1A is a diagram showing an example state in which a stylus pen **100** according to an embodiment of the present disclosure is used. FIG. 1A shows a tablet computer **200** that can be operated using the stylus pen **100**. The tablet computer **200** has an operation surface **200A**. In one example, the operation surface **200A** is a top-panel surface placed on top of an LCD display. An

electrostatic sensor that can detect the coordinates of positions on the operation surface **200A** where operations are made may be provided between the LCD display and the top panel.

[0028] A user holds the stylus pen **100** in his/her hand H, and operates the tablet computer **200** by touching the operation surface **200A** of the tablet computer **200** with the tip of the stylus pen **100**.

[0029] The stylus pen **100** has a pen part **100A**. The pen part **100A** is the part of the stylus pen **100** that can be seen from outside, and includes a tip **100A1**, a cap **100A2**, etc. The stylus pen **100** includes, inside the pen part **100A**, a vibrator, a driver, a controller, a gyrosensor, a writing-pressure sensor, a battery, etc., but these are omitted in FIG. 1A.

[0030] Assuming that the system from the stylus pen **100** to the user's hand H can be represented as a mechanical model, a mechanical model that has a spring and a damper between fingers F of the user's hand H and the pen part **100A** and that is therefore elastic, that is, a mass-spring-damper system, may be provided.

[0031] FIG. 1B is a diagram showing an example mechanical model combining fingers F and the pen part **100A**. As shown in FIG. 1B, the mechanical model of fingers F and the pen part **100A** can be represented as a mass-spring-damper system including an object with a mass "m" (kg), a spring with a spring constant "k" (N/m), and a damper with a viscous resistance "d" (N/sec/m). The mass m is an equivalent mass of the stylus pen **100** and fingers F.

[0032] In the following description, the tip **100A1** of the pen part **100A** will be described as one that is very hard, like that of a ballpoint pen. In the event the tip **100A1** of the pen part **100A** is less hard like that of a felt-tip pen, a fountain pen, or a writing brush, a spring and a damper must be provided at the tip **100A1**; this provides, for example, a mechanical model in which two mechanical models such as the one shown in FIG. 1B are connected in series. The waveform of an impulse response in a mass-spring-damper system mechanical model does not change even if the pen's writing speed or load changes. In other words, when a pulse with an infinitesimal time-width and infinite displacement (i.e., impulse) is input to the mass-spring-damper system mechanical model, the waveform of the response in the time domain does not change even if the pen's writing speed or load changes.

<Measurement of Vibration Waveform>

[0033] FIG. 2A shows an example of how to measure a vibration waveform. As shown in FIG. 2A, a sheet of paper **2** (hereinafter simply "sheet") is placed on the upper surface of a flat plate **1** having an uneven part **1A** on its upper surface, and the tip of a ballpoint pen **10** is brought into contact with the surface of the sheet **2**. In this state, the person who takes measurements draws a straight line in the X-axis direction with the ballpoint pen **10**, and measures the waveform of vibrations produced then in the ballpoint pen **10**.

[0034] The rate of acceleration of vibrations produced in the ballpoint pen **10** changes over time while writing is in progress, and is measured as a vibration waveform. That is, the vibration waveform that occurs in the ballpoint pen **10** while writing is in progress can be represented as changes in the rate of acceleration of vibrations produced in the ballpoint pen **10** over time while writing is in progress.

[0035] An acceleration sensor is attached to the tip of the ballpoint pen **10**, and the rate of acceleration of vibrations produced in the ballpoint pen **10** while writing is in progress is measured using the acceleration sensor, thereby measuring the waveform of vibrations. Note that drawing a diagram or the like with the ballpoint pen **10** is the same as writing. The same is true for a stylus pen.

[0036] FIG. 2B and FIG. 2C are diagrams that each show example results of measuring vibration waveforms representing the vibrations produced in the ballpoint pen **10** by the act of writing, and the multiple lines show normalized results obtained by changing the writing speed, load, etc. of the ballpoint pen **10**. In FIG. 2B and FIG. 2C, the horizontal axis is time (seconds or "[sec]") and the vertical axis is the rate of acceleration of vibration (G). FIG. 2B shows the rate of acceleration in the X direction, and FIG. 2C shows the rate of acceleration in the Y direction. The X direction is a

direction in which the ballpoint pen **10** draws a straight line.

[0037] As shown in FIG. 2B and FIG. 2C, the rate of acceleration of the ballpoint pen **10** shows a pulse-like surge from approximately 0.008 seconds to 0.011 seconds, from the beginning, when the tip of the ballpoint pen **10** passes over the uneven part **1A**, and the shape of the vibration waveform in the time domain stays approximately the same even if the writing speed of the ballpoint pen **10** changes. This shows that the vibration of the ballpoint pen **10** and the impulse response of the mass-spring-damper system mechanical model are alike, and that the shape of the vibration waveform in the time domain stays unchanged even when the writing speed of the ballpoint pen **10** changes. The same is likely to hold true for a stylus pen with a very hard tip **100A1**. Furthermore, the same is likely to hold true for felt-tip pens, fountain pens, or writing brushes with less hard tips. The constants in the mass-spring-damper system mechanical model are likely to vary for every one of these writing instruments; it then follows that each of these writing instruments gives a vibration waveform having a shape that is determined by the frequency of vibration, which is unique to each writing instrument.

<Internal Model Estimation to Achieve Impulse Response>

[0038] FIG. 3 is a diagram showing example results of measuring changes in the rate of acceleration, writing angular velocity, and writing pressure that the ballpoint pen **10** undergoes when drawing a straight line on a normal sheet of paper with few uneven parts. The rate of acceleration, writing angular velocity, and writing pressure shown in FIG. 3 are actual measured values. The writing angular velocity of the ballpoint pen **10** is an example of its writing speed.

[0039] “The rate of acceleration” as used herein refers to the rate of acceleration of the vibration of the ballpoint pen **10** when writing with the ballpoint pen **10**, and the vibration waveform is measured by using an acceleration sensor attached to the tip of the ballpoint pen **10**. The pen's “writing angular velocity” as used herein refers to the angular velocity that is produced in the ballpoint pen **10** when writing with the ballpoint pen **10**, and is measured by a gyrosensor attached to the ballpoint pen **10**. It is preferable to place the gyrosensor in a position where it does not come into contact with the user's hand holding the ballpoint pen **10**. In the present example, the gyrosensor is attached to the cap end of the ballpoint pen **10**.

[0040] The pen's “writing pressure” as used herein refers to the force with which the tip of the ballpoint pen **10** is pressed against the sheet **2** while writing is in progress, and is measured in a state in which the flat plate **1** is mounted over a load cell (load sensor).

[0041] Based on the measured values of rates of acceleration, writing angular velocity, and writing pressure of the ballpoint pen **10**, an impulse response of the stylus pen **100**, that is, an internal model with a time-domain waveform that is unaffected by changes in the pen's writing angular velocity and writing pressure, is estimated. In FIG. 3, the pen starts off still at 0 seconds and writes linearly for 1.2 seconds; the results are as illustrated. In this example, model estimation is performed using the accelerating period from 0.4 seconds to 0.8 seconds, in which the pen's writing angular velocity peaks, as an evaluation period.

[0042] In this model estimation, the force that acts between the sheet **2** and the ballpoint pen **10** and that varies over time while writing is in progress is used as an input, and the varying force's median is set to 0. In addition, the rate of acceleration of the ballpoint pen **10** while writing is in progress is the output of the present model estimation. In the present model estimation, the parameters of the spring and damper in the mechanical model of the ballpoint pen **10** and fingers **F** are fixed values that do not change while writing is in progress.

[0043] Internal model estimation is performed using an auto regressive (AR) model or auto regressive moving average (ARMA) models. To be more specific, an AR model, an ARMA (Prony) model and an ARMA (Steiglitz-Mcbride) model are adjusted such that an input-output relationship fits each model.

[0044] FIG. 4A is a diagram showing examples of how an internal model's rate of acceleration behaves in the time domain and the frequency domain, estimated based on the AR model. FIG. 4B

is a diagram showing examples of how an internal model's rate of acceleration behaves in the time domain and the frequency domain, estimated based on the ARMA (Prony) model. FIG. 4C is a diagram showing examples of how an internal model's rate of acceleration behaves in the time domain and the frequency domain, estimated based on the ARMA (Steiglitz-Mcbride) model. Note that each illustrated behavior in the frequency domain is a result of calculating the behavior of frequency response from the system's behavior determined by internal model estimation.

[0045] Referring to the rates of acceleration of vibration in the time domain shown in FIG. 4A to FIG. 4C, the way vibration behaves does not differ substantially among the AR model, the ARMA (Prony) model, and the ARMA (Steiglitz-Mcbride) model, assuring that the rate of vibration's acceleration in the time domain can be estimated reliably. Comparing the results of estimating what behavior the rate acceleration exhibits in the time domain from the vibrations produced while writing is in progress based on the AR model, the ARMA (Prony) model, and the ARMA (Steiglitz-Mcbride) model with the result of taking measurements based on the method shown in FIG. 2A, or, to be more specific, comparing the rates of acceleration of vibration shown in FIG. 4A, FIG. 4B, and FIG. 4C with those shown of FIG. 2B and FIG. 2C, makes it clear that the time response (waveform in the time domain) is roughly the same whatever measurement/estimation method is used. These results assure that internal models obtained by a variety of internal model estimation methods such as the AR model can be used to estimate the vibration waveform of the ballpoint pen **10** while writing is in progress.

[0046] Furthermore, the rates of acceleration of vibration in the frequency domain illustrated in FIG. 4A to FIG. 4C all show that the vibration decelerates as the frequency increases. From this, it is confirmed that the system including the ballpoint pen **10** and fingers F can be represented by a mechanical model such as that shown in FIG. 1B.

[0047] Furthermore, the rates of acceleration of vibration in the frequency domain shown in FIG. 4A to FIG. 4C have one peak near 206 Hz, thus having one resonant frequency in a confirmable manner. The fact that the above behaviors of vibration's acceleration in the frequency domain have one peak indicates that the mechanical model of the system from the stylus pen **100** to the user's hand H shown in FIG. 1A provides one resonant system. This indicates that the mechanical model of the system including the ballpoint pen **10** and fingers F can be represented by a single mechanical model such as the one shown in FIG. 1B.

[0048] Provided that some writing instruments have a tip that is not hard, such as felt-tip pens, fountain pens, or writing brushes, a system combining a felt-tip pen, a fountain pen, or a writing brush with fingers F is a mechanical model in which at least two mechanical models such as the one shown in FIG. 1B are connected in series, so that there will be at least two resonant frequencies. It then follows that the rates of acceleration of vibration in the frequency domain shown in FIG. 4A to FIG. 4C should have at least two peaks.

[0049] FIG. 5A is a diagram showing examples of how the average frequency and normalized standard deviation behave with respect to the pen's writing angular velocity. The behaviors of the average frequency and normalized standard deviation versus the pen's writing angular velocity shown in FIG. 5A are determined from the actual measurement values of the pen's writing angular velocity shown in FIG. 3.

[0050] A "frequency" in this example is determined by converting the interval between adjacent pulses into a frequency. Assuming that time is divided every 100 milliseconds, the average frequency is, for example, the average value of frequencies occurring in each divided period. The normalized standard deviation is one of average frequencies. Also, for example, the behavior of the average frequency and normalized standard deviation versus the pen's writing angular velocity shown in FIG. 5A is determined from the actual measurement value of the pen's writing angular velocity in the period from 0 seconds to 0.4 seconds in FIG. 3.

[0051] As shown in FIG. 5A, the average frequency tends to increase as the pen's writing angular velocity increases. That is, the greater the pen's writing angular velocity, the higher the average

frequency tends to be, that is, the interval between adjacent pulses tends to become narrower. To be more specific, when the pen's writing angular velocity is 10 degrees per second, the average frequency is approximately 166 Hz. Likewise, when the pen's writing angular velocity is 45.8 degrees per second, the average frequency is approximately 345 Hz. In other words, the average frequency increases approximately linearly following the dashed line. The increase of the average frequency indicates that the pulses of the waveform in the time domain do not change, and that the time interval at which pulses occur becomes shorter.

[0052] Furthermore, as shown in FIG. 5A, the normalized standard deviation of average frequencies remains substantially constant at approximately 0.42 even when the pen's writing angular velocity increases.

[0053] This shows the tendency in which, when the pen's writing angular velocity increases, pulses occur at shorter intervals, and the average frequency increases accordingly. When every interval between pulses is converted into a frequency, the resulting frequencies vary in a range of approximately ± 40 Hz to ± 80 Hz from the average frequency. Consequently, the drive signal has only to be generated such that the time interval between pulses becomes shorter in response to an increase in the pen's writing angular velocity, without changing the waveform of pulses in the time domain.

[0054] FIG. 5B is a diagram showing examples of how the average wave height of vibration's acceleration and the ratio "standard deviation/average wave height" behave with respect to the pen's writing angular velocity. Where the average wave height of vibration's acceleration is determined from the actual measurement values of vibration's acceleration and the pen's writing angular velocity in FIG. 3, FIG. 5B shows how the average wave height of vibration's acceleration and the ratio "standard deviation/average wave height" behave with respect to the pen's writing angular velocity. Note that "wave height" as used herein refers to the amplitude of vibration's acceleration; the unit of measurement for the average wave height is "G." Assuming that time is divided every 100 milliseconds, the average wave height of vibration's acceleration is, for example, the average value of the wave heights of vibration's acceleration in each divided period. The standard deviation here is one of average wave heights of vibration's acceleration. The ratio "standard deviation/average wave height" is determined by dividing the standard deviation of average wave heights of vibration's acceleration by the average wave height of vibration's acceleration.

[0055] FIG. 5C is a histogram showing an example distribution of rates of vibration's acceleration. FIG. 5C shows a distribution of peak values of vibration's acceleration obtained from a part of the vibration acceleration evaluation period shown in FIG. 3. Referring to the horizontal axis in FIG. 5C, the beginning of a part taken from the evaluation period is labeled "0" [sec].

[0056] FIG. 5C makes it clear that the acceleration of vibration have varying peak values. In other words, it is confirmed that vibration's acceleration is random in that it changes over time.

[0057] FIG. 6 is a diagram showing an example in which the pen's writing angular velocity and the rate of acceleration of vibration change over time. The changes in the pen's writing angular velocity and vibration's acceleration over time shown in FIG. 6 are calculated from the vibration's acceleration and pen's angular velocity shown in FIG. 3.

[0058] As shown in FIG. 6, the waveform of the pen's writing angular velocity and the waveform of vibration's acceleration are substantially the same, making it clear that vibration's acceleration increases as the pen's writing angular velocity increases. Furthermore, vibration's acceleration increases as the pen's writing pressure becomes stronger, making it clear that vibration's acceleration increases as the pen's writing angular velocity and writing pressure increase.

Accordingly, the drive signal has only to be generated such that vibration's acceleration increases as the pen's writing angular velocity and writing pressure increase, without changing the waveform of pulses in the time domain.

<Inner Structure of Stylus Pen 100>

[0059] FIG. 7 is a block diagram showing an inner structure of the stylus pen **100**. The stylus pen **100** includes a gyrosensor **110**, a writing-pressure sensor **120**, a controller **130**, a driver **140**, and a vibrator **150**. These are housed inside the pen part **100A**. The gyrosensor **110** is an example of a speed detector. The writing-pressure sensor **20** is an example of a pen-pressure detector.

[0060] The gyrosensor **110** detects the angular velocity that is produced when writing with the stylus pen **100**. The gyrosensor **110** detects the angular velocity while writing with the stylus pen **100** is in progress (also referred to as “writing angular velocity”). The gyrosensor **110** is connected to the controller **130** and outputs the pen's writing angular velocity to the controller **130**.

Furthermore, in addition to the pen's writing angular velocity, the gyrosensor **110** may detect the three-dimensional posture of the stylus pen **100** and output it to the controller **130**.

[0061] The gyrosensor **110** may be located inside the pen part **100A**, either near the tip **100A1**, near the cap **100A2**, or between the tip **100A1** and the cap **100A2**. This is because the angular velocity that is produced in the pen part **100A** while writing is in progress is the same in all parts of the pen part **100A**.

[0062] The writing-pressure sensor **120** detects the force with which the user holding the stylus pen **100** with his/her fingers **F** presses the stylus pen **100** against the sheet **2**. The writing-pressure sensor **120** is connected to the controller **130** and outputs the pen's writing pressure to the controller **130**. For example, the writing-pressure sensor **120** may be located near the tip **100A1** of the pen part **100A** and sandwiched between the tip **100A1** and the internal structure of the pen part **100A**. It suffices if the writing-pressure sensor **120** can detect the pressure that acts on the pen's tip (the pen's writing pressure).

[0063] The controller **130** includes a data input part **131**, a waveform generator **132**, a drive signal generator **133**, and a memory **134**. The controller **130** is, for example, formed with a micro controller unit (MCU). The controller **130** is a computer including a central processing unit (CPU), a random access memory (RAM), a read-only memory (ROM), an input/output interface, and an internal bus. The data input part **131**, the waveform generator **132**, and the drive signal generator **133** are functional blocks that implement the functions of programs executed by the controller **130**. The memory **134** is a functional representation of the memory of the controller **130**. The controller **130** is not limited to a computer, and may be formed with, for example, a field programmable gate array (FPGA). An FPGA may be incorporated in a part of the controller **130** (for example, the drive signal generator **133**).

[0064] The data input part **131** receives the pen's writing angular velocity and three-dimensional posture as inputs from the gyrosensor **110** as well as the pen's writing pressure from the writing-pressure sensor **120**. The data input part **131** also integrates the pen's writing angular velocity received as an input from the gyrosensor **110** and calculates the pen's writing distance. The data input part **131** outputs the pen's writing angular velocity, writing distance, writing pressure, and three-dimensional posture, to the waveform generator **132**. The unit of measurement for the writing distance is degrees. The writing distance refers to the distance over which something is written or drawn with the stylus pen **100**, expressed in degrees.

[0065] The waveform generator **132** generates a pulse wave height (acceleration of vibration) and a pulse interval for generating a drive signal based on the pen's writing angular velocity and writing pressure received as inputs from the data input part **131**, generates the drive signal by changing the pulses that are set in advance depending on the writing instrument used, to pulses that match the generated pulse wave height and pulse interval, or by changing the time intervals at which pulses occur, and outputs the thus-generated drive signal to the drive signal generator **133**. The waveform of pulses set in advance in the time domain depending on the writing instrument used, the pulse wave height (magnitude of acceleration), and the pulse interval provide data that serves as the basis of the drive signal's waveform.

[0066] To be more specific, the waveform generator **132** multiplies the pen's writing angular velocity and a normal random number together, and multiplies the resulting value by the pen's

writing pressure, thereby determining the pulse wave height (acceleration of vibration). The pulse wave height is generated such that the greater the pen's writing angular velocity, the higher the pulse wave height (acceleration of vibration), and the higher the pen's writing pressure, the higher the pulse wave height. Note that random numbers other than normal random numbers may be used. [0067] In addition, the waveform generator **132** generates the interval between pulses (frequency) based on the value obtained by multiplying the pen's writing angular velocity and a normal random number together. The waveform generator **132** generates the interval between pulses (frequency) such that pulses occur at shorter intervals as the pen's writing angular velocity increases. By this means, vibrations occur at timings in accordance with the normal random number. Note that random numbers other than normal random numbers may also be used.

[0068] The waveform generator **132** may also correct the pen's writing pressure based on the pen's three-dimensional posture. The waveform generator **132** may also determine the interval of pulses from the previous waveform output request up to the next waveform output request, as the time elapsed, from the pen's writing speed and normal random number used at present. Using the writing position at which the previous waveform output request was sent and the pulse interval determined from the pen's writing speed and normal random number used at present, the waveform generator **132** may calculate the required writing distance by multiplying the pulse interval by the pen's writing speed at present, and use the result in making decisions.

[0069] The drive signal that matches the pulse wave height and pulse interval (frequency) generated thus is output from the waveform generator **132** to the drive signal generator **133**.

[0070] The drive signal generator **133** is implemented, for example, using a finite impulse response (FIR) filter or an infinite impulse response (IIR) filter. When the drive signal generator **133** receives as an input the drive signal that matches the pulse wave height and pulse interval (frequency) from the waveform generator **132**, the drive signal generator **133** generates the drive signal by weighting and superimposing the currently input signal (current sample signal) over past sample signals (from the previous sample signal to the N-th past sample signal, where N is an integer of 2 or more), and outputs the thus-generated drive signal to the driver **140**. The drive signal is one in which the wave height of pulses (acceleration of vibration) and the interval of pulses (frequency) change on a random basis.

[0071] The memory **134** stores the programs and data that the waveform generator **132** and the drive signal generator **133** use to perform processes. As for the data, the memory **134** stores, for example, data that represents the normal random numbers that the waveform generator **132** uses, data that represents the relationship between the pen's writing angular velocity and the rate of acceleration of vibration, data that represents the relationship between the pen's writing pressure and the rate of acceleration of vibration, data that represents the relationship between the pen's writing angular velocity and the interval of occurrences (frequency), and so forth.

[0072] The driver **140** is a drive circuit for the vibrator **150**, and drives the vibrator **150** based on the drive signal input from the drive signal generator **133**.

[0073] For example, a vibration actuator such as a linear resonant actuator (LRA) can be used for the vibrator **150**. The vibrator **150**, placed inside the pen part **100A** and driven by the drive signal, causes the pen part **100A** to vibrate. As a result of this, the pen part **100A** vibrates based on impulse responses, thereby providing vibrations that feel like really writing with the ballpoint pen **10**.

[0074] An example has been illustrated in the above description in which the stylus pen **100** includes a controller **130** and a vibrator **150**. Nevertheless, it is equally possible to include at least one of a controller **130** and a vibrator **150** in the tablet computer **200**, and, provided that the pen's writing speed can be determined based on how the position on the operation surface **200A** where the user operates the tablet computer **200** using the stylus pen **100** changes over time, drive the vibrator **150** based the pen's writing speed and writing pressure, thus causing the operation surface **200A** to vibrate.

[0075] In such a case, a system including the stylus pen **100** and the tablet computer **200** can be

regarded as one input system. In this input system, the tablet computer **200** is an example of a detector. An electrostatic sensor in the tablet computer **200** may be used to detect the positions where the user performs operations with the stylus pen **100**. The electrostatic sensor can detect the coordinates of such operation positions on the operation surface **200A**. In addition, in one example, a sensor that can detect the operational load that acts on the operation surface **200A** may be provided in the tablet computer **200** and used to detect the pen's writing pressure. In this case, the stylus pen **100** may be equipped with a gyrosensor **110** and a writing-pressure sensor **120**, and the pen's writing angular velocity and writing pressure may be sent to the controller **130** of the tablet computer **200** through wired communication or wireless communication between the stylus pen **100** and the tablet computer **200**.

[0076] Furthermore, in this input system, the stylus pen **100** may include a controller **130** and the tablet computer **200** may include a vibrator **150**, providing a structure in which the controller **130** of the tablet computer **200** generates the drive signal and sends it to the stylus pen **100** through wired communication or wireless communication between the stylus pen **100** and the tablet computer **200**, thus driving the vibrator **150**. In this case, either the stylus pen **100** or the tablet computer **200** may detect the pen's writing angular velocity and writing pressure.

Advantages

[0077] According to the present disclosure, a stylus pen **100** includes: a pen part **100A**; a vibrator **150** provided in the pen part **100A**; and a controller **130** configured to generate a drive signal for driving the vibrator **150**. The controller **130** generates the drive signal such that the vibrator **150**, when driven by the drive signal, causes the pen part **100A** to vibrate based on an impulse response of a spring-mass-damper system. When something is written or drawn on a sheet of paper **2** with a pen such as a ballpoint pen **10**, the vibrations produced in the pen then can be represented by impulse responses in a spring-mass-damper system. By thus causing the pen part **100A** to vibrate based on an impulse response of a spring-mass-damper system, it is possible to provide a realistic tactile experience that feels as if really writing with the ballpoint pen **10**.

[0078] Therefore, it is possible to provide a stylus pen **100** that can provide a realistic tactile experience of writing.

[0079] In addition to the foregoing, the stylus pen **100** may further include a gyrosensor **110** that is configured to detect the writing speed of the pen part **100A**, and the controller **130** may generate the drive signal such that the pen part **100A** vibrates at shorter intervals when the writing speed of the pen part **100A** detected by the gyrosensor **110** (speed detector) increases. Consequently, the pen part **100A** vibrates at varying timings depending on the writing speed of the pen part **100A**, thus replicating changes in the timing to have the tactile experience of writing depending on the writing speed of the pen part **100A**.

[0080] In addition to the foregoing, the controller **130** may generate the drive signal such that the pen part **100A** vibrates at timings in accordance with a normal random number. Consequently, it is possible to provide a stylus pen **100** that can produce vibrations that change randomly over time, and that can therefore provide a more realistic tactile experience of writing.

[0081] In addition to the foregoing, the stylus pen **100** may further include a gyrosensor **110** (speed detector) that is configured to detect the writing speed of the pen part **100A**. The controller **130** may generate the drive signal such that the pen part **100A** vibrates at a higher rate of acceleration when the gyrosensor **110** detects a higher writing speed of the pen part **100A**. Consequently, the pen part **100A** vibrates at varying rates of acceleration depending on the writing speed of the pen part **100A**, thus replicating changes in the power of the tactile experience of writing depending on the writing speed of the pen part **100A**.

[0082] In addition to the foregoing, the stylus pen **100** may further include a writing-pressure sensor **120** configured to detect the pressure that acts on the pen part **100A**. The controller **130** may generate the drive signal such that the pen part **100A** vibrates at a higher rate of acceleration when the writing-pressure sensor **120** (pen-pressure detector) detects a higher writing pressure.

Consequently, the pen part **100A** vibrates at varying rates of acceleration depending on the writing speed of the pen part **100A**, thus replicating changes in the power of the tactile experience of writing depending on the writing pressure of the pen part **100A**.

[0083] Furthermore, since an internal model for achieving impulse responses of a spring-mass-damper system is one that is designed based on model estimation using an auto regressive model or an auto regressive moving average model, so that it is possible to replicate a realistic tactile experience that feels as if really writing with the ballpoint pen **10**. Consequently, the present disclosure can provide a stylus pen **100** that allows the user to have a more realistic tactile experience of writing.

[0084] In addition, the resonant frequency of the vibrator **150** is 200 Hz or less. By allowing the pen part **100A** to vibrate at such frequencies that the sensory organs on the human skin can sense the vibrations easily, it is possible to replicate a realistic tactile experience that feels as if really writing on the sheet **2** with the ballpoint pen **10**. Consequently, the present disclosure can provide a stylus pen **100** that allows the user to have a more realistic tactile experience of writing.

[0085] Furthermore, according to the present disclosure, an input system includes: a stylus pen **100**; a detector configured to detect contact of the stylus pen **100** with an operation surface; a vibrator **150**; and a controller **130** configured to generate a drive signal for driving the vibrator **150**. The controller **130** generates the drive signal such that the vibrator **150**, when driven by the drive signal, causes the pen part **100A** to vibrate based on an impulse response of a spring-mass-damper system. When something is written or drawn on a sheet of paper **2** with a pen such as a ballpoint pen **10**, the vibrations produced in the pen then can be represented by impulse responses in a spring-mass-damper system. By thus causing the pen part **100A** to vibrate based on an impulse response of a spring-mass-damper system, it is possible to provide a realistic tactile experience that feels as if really writing with the ballpoint pen **10**.

[0086] It is therefore possible to provide an input system that allows the user to have a more realistic tactile experience of writing.

[0087] Although a stylus pen and an input system according to an embodiment of the present disclosure have been described above, the present disclosure is by no means limited to this embodiment, and various modifications and changes can be made without departing from the scope of the accompanying claims.

Claims

1. A stylus pen comprising: a pen part; a vibrator provided in the pen part; and a controller configured to generate a drive signal for driving the vibrator, wherein the controller is configured to generate the drive signal such that the vibrator, when driven by the drive signal, causes the pen part to vibrate based on an impulse response of a spring-mass-damper system.
2. The stylus pen according to claim 1, further comprising a speed detector configured to detect a writing speed of the pen part, wherein the controller is configured to generate the drive signal such that the pen part vibrates at shorter intervals when the speed detector detects a higher writing speed of the pen part.
3. The stylus pen according to claim 1, wherein the controller is configured to generate the drive signal such that the pen part vibrates at timings determined by a normal random number.
4. The stylus pen according to claim 1, further comprising a speed detector configured to detect a writing speed of the pen part, wherein the controller is configured to generate the drive signal such that the pen part vibrates at a higher rate of acceleration when the speed detector detects a higher writing speed of the pen part.
5. The stylus pen according to claim 1, further comprising a writing pressure detector configured to detect a writing pressure that acts on the pen part, wherein the controller is configured to generate the drive signal such that pen part vibrates at a higher rate of acceleration when the writing pressure

detector detects a higher writing pressure.

6. The stylus pen according to claim 1, wherein the impulse response is provided based on model estimation using an auto regressive model or an auto regressive moving average model.

7. The stylus pen according to claim 1, wherein a resonant frequency of the vibrator is 200 Hz or less.

8. An input system comprising: a stylus pen; a detector configured to detect contact of the stylus pen with an operation surface; a vibrator; and a controller configured to generate a drive signal for driving the vibrator, wherein the controller is configured to generate the drive signal such that the vibrator, when driven by the drive signal, causes the stylus pen to vibrate based on an impulse response of a spring-mass-damper system.
