

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287260

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

LEE; Hyunchul

ELECTRONIC DEVICE FOR SWITCHING CELLULAR COMMUNICATION ON BASIS OF STATE OF ELECTRONIC DEVICE, AND OPERATION METHOD FOR ELECTRONIC DEVICE

Abstract

An electronic device is provided. The electronic device includes a first communication circuit for supporting at least one of first cellular communication or second cellular communication, a second communication circuit for supporting short-range wireless communication, memory, comprising one or more storage media, storing instructions; an application processor coupled to the memory, and a communication processor coupled to the memory, wherein the instructions, when executed by the application processor, cause the electronic device to check whether the electronic device satisfies, in a state in which the electronic device is connected to a cellular network through the first cellular communication in a call connection status through voice over (Vo) wireless fidelity (Wi-Fi), a first condition related to disconnection of the first cellular communication, and transmit, to the communication processor, in a state in which the electronic device satisfies the first condition related to the disconnection of the first cellular communication, on the basis that the electronic device satisfies a second condition related to the disconnection of the first cellular communication, a signal indicating that the electronic device satisfies the second condition related to the disconnection of the first cellular communication, wherein instructions, when executed by the communication processor, cause the electronic device to prepare to disconnect the first cellular communication and connect the second cellular communication on the basis of reception of the signal indicating that the first condition related to the disconnection of the first cellular communication is satisfied, and perform the disconnection of the first cellular communication and the connection of the second cellular communication based on reception of the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied.

Inventors: LEE; Hyunchul (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008629830

Appl. No.: 19/219611
Filed: May 27, 2025

Foreign Application Priority Data

KR	10-2022-0169764	Dec. 07, 2022
KR	10-2023-0000118	Jan. 02, 2023

Related U.S. Application Data

parent WO continuation PCT/KR2023/014981 20230927 PENDING child US 19219611

Publication Classification

Int. Cl.: H04W28/08 (20230101); H04W28/02 (20090101); H04W76/10 (20180101);
H04W88/06 (20090101)

U.S. Cl.:

CPC H04W28/0846 (20200501); H04W28/0236 (20130101); H04W76/10 (20180201);
H04W88/06 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) [0001] This application is a continuation application, claiming priority under 35 U.S.C. § 365(c), of an International application No. PCT/KR2023/014981, filed on Sep. 27, 2023, which is based on and claims the benefit of a Korean patent application number 10-2022-0169764, filed on Dec. 7, 2022, in the Korean Intellectual Property Office, and of a Korean patent application number 10-2023-0000118, filed on Jan. 2, 2023, in the Korean Intellectual Property Office, the disclosure of each of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

[0002] The disclosure relates to an electronic device and an operation method for an electronic device. More particularly, the disclosure relates to an electronic device that switches a connected cellular communication based on a state of the electronic device.

2. Description of Related Art

[0003] In order to meet the growing demand for wireless data traffic since the fourth generation (4G) communication system came to the market, there are ongoing efforts to develop enhanced fifth generation (5G) communication systems or pre-5G communication systems. For this reason, the 5G communication system or pre-5G communication system is called the beyond 4G network communication system or post long-term evolution (LTE) system. In order to achieve a high data transmission rate, the 5G communication system is also being considered for implementation in an ultra-high frequency (millimeter wave (mmWave)) band (for example, a band above 6 GHz) in addition to a band (band below 6 GHz) used by LTE. In the 5G communication system, beamforming, massive multiple-input and multiple-out-put (MIMO), and full dimensional MIMO (FD-MIMO), an array antenna, analog beam-forming, and large-scale antenna technologies are

being discussed.

[0004] As for the frequency bands supported by 5th generation cellular communication, higher frequency bands compared to existing communication schemes may also be used. When the electronic device uses a frequency band communication scheme supported by the 5th generation cellular communication, a data transmission speed may be faster than using the existing communication method.

[0005] Access traffic steering, switching, splitting (ATSSS) refers to a technology that manages traffic transmitted through third-generation partnership project (3GPP) networks (e.g., new radio (NR) and LTE) and non-3GPP networks (e.g., wireless Fidelity (Wi-Fi)). Access traffic steering refers to a technology that selects one network among GPP networks (e.g., NR and LTE) and non-3GPP networks (e.g., Wi-Fi) and transmits data through the selected network. Access traffic switching refers to a technology that transmits data to another network while transmitting data to one network. Access traffic splitting refers to a technology that distributes and transmits a single data flow using multiple networks.

[0006] The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

SUMMARY

[0007] When a voice service request is made via WI-FI when using a 5th generation cellular communication scheme that does not support voice service, the electronic device may switch from 5th generation cellular communication to 4th generation cellular communication that supports voice service.

[0008] However, since the electronic device should switch back to the 5th generation cellular communication after the voice service is terminated, the number of signal exchanges due to network movement increases and a data speed may decrease. In addition, the electronic device may have difficulties in supporting network aggregation between Wi-Fi and 5th generation cellular communication under access traffic steering, switching, splitting (ATSSS) that is being developed by the 3GPP. The network aggregation refers to a technology that increases a signal transmission speed by combining multiple networks into one.

[0009] Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide an electronic device for switching cellular communication on bases of state of electronic device, and operation method for electronic device.

[0010] Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

[0011] In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes a first communication circuit that supports at least one of first cellular communication or second cellular communication, a second communication circuit that supports short-range wireless communication, memory, comprising one or more storage media, storing instructions, an application processor coupled to the memory, and a communication processor coupled to the memory, wherein the instructions, when executed by the application processor, cause the electronic device to check whether the electronic device satisfies a first condition related to a disconnection of the first cellular communication, in a state in which the electronic device is connected to a cellular network through the first cellular communication, in a call connection status through voice over (Vo) wireless fidelity (Wi-Fi), transmit, to the communication processor, a signal indicating that the electronic device satisfies the first condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication, check whether the electronic device satisfies a second condition related to the disconnection of the first cellular communication, in the state where the electronic device satisfies the first condition related to the disconnection of

the first cellular communication, and transmit, to the communication processor, a signal indicating that the electronic device satisfies the second condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the second condition related to the disconnection of the first cellular communication, wherein the instructions, when executed by the communication processor, cause the electronic device to prepare to disconnect the first cellular communication and connect the second cellular communication based on reception of the signal indicating that the first condition related to the disconnection of the first cellular communication is satisfied, and disconnect the first cellular communication and connect the second cellular communication based on reception of a signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied.

[0012] In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes a first communication circuit that supports at least one of first cellular communication or second cellular communication, a second communication circuit that supports short-range wireless communication, memory, comprising one or more storage media, storing instructions, an application processor coupled to the memory, and a communication processor coupled to the memory, wherein instructions, when executed by the application processor, cause the electronic device to check whether the electronic device supports access traffic steering, switching, splitting (ATSSS), in a call connection status through voice over (Vo) wireless fidelity (Wi-Fi), determine whether a base station supporting the first cellular communication exists within a preset distance from the electronic device based on that the electronic device supports the ATSSS, determine whether a signal strength of the Vo Wi-Fi is greater than or equal to a pre-specified level based on that the base station supporting the first cellular communication exists within the preset distance from the electronic device, and transmit, to the communication processor, a signal related to a disconnection of the second cellular communication based on that the signal strength of the Vo Wi-Fi is greater than or equal to the pre-specified level, and wherein instructions, when executed by the communication processor, cause the electronic device to perform the disconnection of the second cellular communication and a connection of the first cellular communication based on a signal related to the disconnection of the second cellular communication received from the application processor.

[0013] In accordance with another aspect of the disclosure, a method performed by an electronic device for switching an operation mode of cellular communication is provided. The method includes checking whether a first condition related to a disconnection of a first cellular communication is satisfied in a call connection status through voice over (Vo) wireless fidelity (Wi-Fi), transmitting, to a communication processor, a signal indicating that the electronic device satisfies the first condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication, checking whether the electronic device satisfies a second condition related to the disconnection of the first cellular communication, in a state where the electronic device satisfies the first condition related to the disconnection of the first cellular communication, transmitting, to the communication processor, a signal indicating that the electronic device satisfies the second condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the second condition related to the disconnection of the first cellular communication, preparing to disconnect the first cellular communication and connect the second cellular communication based on reception of a signal indicating that the first condition related to the disconnection of the first cellular communication is satisfied, and disconnecting the first cellular communication and connecting the second cellular communication based on reception of a signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied.

[0014] According to an embodiment, the electronic device may increase the data transmission speed by selecting the optimal technology between the 5th generation cellular communication and

the 4th generation cellular communication.

[0015] According to an embodiment, the electronic device can improve the data performance by supporting the traffic management technology of the access traffic steering, switching, splitting (ATSSS) even when the 5th generation cellular communication does not support the voice over new radio (VoNR) voice service.

[0016] Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

[0018] FIG. 1 is a block diagram illustrating an electronic device in a network environment according to an embodiment of the disclosure;

[0019] FIG. 2 is a block diagram of an electronic device for supporting legacy network communication and 5G network communication according to an embodiment of the disclosure;

[0020] FIG. 3 is a diagram illustrating a protocol stack structure of a network of the legacy communication and/or the 5G communication according to an embodiment of the disclosure;

[0021] FIGS. 4A, 4B, and 4C are diagrams illustrating wireless communication systems providing a network of the legacy communication and/or the 5G communication according to various embodiments of the disclosure;

[0022] FIG. 5 is a diagram illustrating an electronic device and a cellular network according to an embodiment of the disclosure;

[0023] FIG. 6 is a block diagram of the electronic device according to an embodiment of the disclosure;

[0024] FIG. 7 is a flowchart illustrating an operation method for an electronic device according to an embodiment of the disclosure;

[0025] FIG. 8 is a diagram illustrating an embodiment in which the electronic device changes from a connection combination of Wi-Fi and a first cellular communication to a connection combination of Wi-Fi and a second cellular communication according to an embodiment of the disclosure; and

[0026] FIG. 9 is a diagram illustrating an embodiment in which the electronic device changes from the connection combination of the Wi-Fi and the second cellular communication to the connection combination of the Wi-Fi and the first cellular communication according to an embodiment of the disclosure.

[0027] The same reference numerals are used to represent the same elements throughout the drawings.

DETAILED DESCRIPTION

[0028] The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

[0029] The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent

understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

[0030] It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

[0031] It should be appreciated that the blocks in each flowchart and combinations of the flowcharts may be performed by one or more computer programs which include instructions. The entirety of the one or more computer programs may be stored in a single memory device or the one or more computer programs may be divided with different portions stored in different multiple memory devices.

[0032] Any of the functions or operations described herein can be processed by one processor or a combination of processors. The one processor or the combination of processors is circuitry performing processing and includes circuitry like an application processor (AP, e.g. a central processing unit (CPU)), a communication processor (CP, e.g., a modem), a graphics processing unit (GPU), a neural processing unit (NPU) (e.g., an artificial intelligence (AI) chip), a wireless fidelity (Wi-Fi) chip, a Bluetooth® chip, a global positioning system (GPS) chip, a near field communication (NFC) chip, connectivity chips, a sensor controller, a touch controller, a fingerprint sensor controller, a display driver integrated circuit (IC), an audio CODEC chip, a universal serial bus (USB) controller, a camera controller, an image processing IC, a microprocessor unit (MPU), a system on chip (SoC), an IC, or the like.

[0033] FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to an embodiment of the disclosure.

[0034] Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

[0035] The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation.

According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes

the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

[0036] The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

[0037] The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

[0038] The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

[0039] The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

[0040] The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

[0041] The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

[0042] The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

[0043] The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

[0044] The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

[0045] A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

[0046] The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

[0047] The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

[0048] The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

[0049] The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

[0050] The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the

first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

[0051] The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

[0052] The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

[0053] According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

[0054] At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

[0055] According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or

the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

[0056] The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

[0057] It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

[0058] As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

[0059] Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium

and where the data is temporarily stored in the storage medium.

[0060] According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

[0061] According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

[0062] FIG. 2 is a block diagram **200** of the electronic device **101** for supporting legacy network communication and 5G network communication according to an embodiment of the disclosure.

[0063] Referring to FIG. 2, the electronic device **101** may include a first communication processor **212**, a second communication processor **214**, a first radio frequency integrated circuit (RFIC) **222**, a second RFIC **224**, a third RFIC **226**, a fourth RFIC **228**, a first radio frequency front end (RFFE) **232**, a second RFFE **234**, a first antenna module **242**, a second antenna module **244**, and an antenna **248**. The electronic device **101** may further include the processor **120** and the memory **130**. The network **199** may include a first network **292** and a second network **294**. According to another embodiment, the electronic device **101** may further include at least one of the components described in FIG. 1, and the network **199** may further include at least one other network. According to an embodiment, the first communication processor **212**, the second communication processor **214**, the first RFIC **222**, the second RFIC **224**, the fourth RFIC **228**, the first RFFE **232**, and the second RFFE **234** may form at least part of the wireless communication module **192**. According to another embodiment, the fourth RFIC **228** may be omitted or included as part of the third RFIC **226**.

[0064] The first communication processor **212** may support establishment of a communication channel in a band to be used for wireless communication with the first network **292**, and legacy network communication through the established communication channel. According to various embodiments, the first network may be a legacy network including a second generation (2G), third generation (3G), 4G, or long-term evolution (LTE) network. The second communication processor **214** may support establishment of a communication channel corresponding to a specified band (e.g., about 6 GHz to about 60 GHz) among the bands to be used for the wireless communication with the second network **294**, and 5G network communication through the established communication channel. According to various embodiments, the second network **294** may be the 5G network defined by 3GPP. Additionally, according to an embodiment, the first communication processor **212** or the second communication processor **214** may support establishment of communication channel corresponding to another specified band (e.g., about 6 GHz or less) among the bands to be used for the wireless communication with the second network **294**, and the 5G

network communication through the established communication channel. According to an embodiment, the first communication processor **212** and the second communication processor **214** may be implemented in a single chip or a single package. According to various embodiments, the first communication processor **212** or the second communication processor **214** may be formed within the single chip or the single package with the processor **120**, the auxiliary processor **123**, or the communication module **190**.

[0065] Upon transmission, the first RFIC **222** may convert a baseband signal generated by the first communication processor **212** into a radio frequency (RF) signal of about 700 MHz to about 3 GHz used in the first network **292** (e.g., a legacy network). Upon reception, the RF signal may be acquired from the first network **292** (e.g., the legacy network) via an antenna (e.g., the first antenna module **242**) and preprocessed via an RFFE (e.g., the first RFFE **232**). The first RFIC **222** may convert the preprocessed RF signal into the baseband signal so that the preprocessed RF signal may be processed by the first communication processor **212**.

[0066] Upon transmission, the second RFIC **224** may convert the baseband signal generated by the first communication processor **212** or the second communication processor **214** into the RF signal (hereinafter, a 5G Sub6 RF signal) of a Sub6 band (e.g., about 6 GHz or less) used in the second network **294** (e.g., the 5G network). Upon reception, the 5G Sub6 RF signal may be acquired from the second network **294** (e.g., the 5G network) via the antenna (e.g., the second antenna module **244**) and preprocessed through the RFFE (e.g., the second RFFE **234**). The second RFIC **224** may convert the preprocessed 5G Sub6 RF signal into the baseband signal so that the preprocessed 5G Sub6 RF signal may be processed by the corresponding communication processor of the first communication processor **212** or the second communication processor **214**.

[0067] The third RFIC **226** may convert the baseband signal generated by the second communication processor **214** into an RF signal (hereinafter, a 5G Above6 RF signal) of a 5G Above6 band (e.g., about 6 GHz to about 60 GHz) to be used in the second network **294** (e.g., the 5G network). Upon reception, the 5G Above6 RF signal may be acquired from the second network **294** (e.g., the 5G network) via the antenna (e.g., antenna **248**) and preprocessed through the third RFFE **236**. The third RFIC **226** may convert the preprocessed 5G Above6 RF signal into the baseband signal so that the preprocessed 5G Above6 RF signal may be processed by the second communication processor **214**. According to an embodiment, the third RFFE **236** may be formed as a part of the third RFIC **226**.

[0068] According to an embodiment, the electronic device **101** may include the fourth RFIC **228** separately from or at least as a part of the third RFIC **226**. In this case, the fourth RFIC **228** may convert the baseband signal generated by the second communication processor **214** into an RF signal (hereinafter, referred to as an IF signal) of an intermediate frequency band (e.g., about 9 GHz to about 11 GHz) and then transmit the IF signal to the third RFIC **226**. The third RFIC **226** may convert the IF signal into the 5G Above6 RF signal. Upon reception, the 5G Above6 RF signal may be received from the second network **294** (e.g., the 5G network) via the antenna (e.g., antenna **248**) and converted into the IF signal by the third RFIC **226**. The fourth RFIC **228** may convert the IF signal into the baseband signal for processing by the second communication processor **214**.

[0069] According to an embodiment, the first RFIC **222** and the second RFIC **224** may be implemented as at least part of a single chip or a single package. According to an embodiment, the first RFFE **232** and the second RFFE **234** may be implemented as at least part of a single chip or a single package. According to an embodiment, at least one antenna module of the first antenna module **242** or the second antenna module **244** may be omitted or combined with another antenna module to process RF signals of multiple corresponding bands.

[0070] According to an embodiment, the third RFIC **226** and the antenna **248** may be arranged on the same substrate to form the third antenna module **246**. For example, the wireless communication module **192** or the processor **120** may be arranged on a first substrate (e.g., main PCB). In this case, the third RFIC **226** may be arranged on a partial area (e.g., bottom) of a second substrate (e.g., sub

PCB) separate from the first substrate, and the antenna **248** may be arranged on another partial area (e.g., top) to form the third antenna module **246**. By arranging the third RFIC **226** and the antenna **248** on the same substrate, it is possible to reduce a length of a transmission line therebetween. This may reduce, for example, a loss (e.g., attenuation) of a signal in a high-frequency band (e.g., about 6 GHz to about 60 GHz) used for the 5G network communication by the transmission line. As a result, the electronic device **101** may improve the quality or speed of communication with the second network **294** (e.g., the 5G network).

[0071] According to an embodiment, the antenna **248** may be formed as an antenna array including a plurality of antenna elements that may be used for beamforming. In such a case, the third RFIC **226** may include a plurality of phase shifters **238** corresponding to the plurality of antenna elements, for example, as part of the third RFFE **236**. Upon transmission, each of the plurality of phase shifters **238** may shift a phase of the 5G Above6 RF signal to be transmitted to an outside (e.g., a base station of the 5G network) of the electronic device **101** via the corresponding antenna element. Upon reception, each of the plurality of phase shifters **238** may shift the phase of the 5G Above6 RF signal received from the outside via the corresponding antenna element to the same phase or substantially the same phase. This enables transmission or reception via the beamforming between the electronic device **101** and the outside.

[0072] The second network **294** (e.g., the 5G network) may operate independently (e.g., stand-alone (SA)) or connected (e.g., non-standalone (NSA)) from the first network **292** (e.g., the legacy network). For example, the 5G network may only have an access network (e.g., a 5G radio access network (RAN) or a next generation RAN (NG RAN)) and have no core network (e.g., a next generation core (NGC)). In such a case, the electronic device **101** may access an external network (e.g., the Internet) under the control of the core network (e.g., an evolved packet core (EPC)) of the legacy network after accessing the access network of the 5G network. Protocol information (e.g., LTE protocol information) for communicating with the legacy network or protocol information (e.g., new radio (NR) protocol information) for communicating with the 5G network may be stored in the memory **130** and accessed by other components (e.g., the processor **120**, the first communication processor **212**, or the second communication processor **214**).

[0073] FIG. **3** is a diagram illustrating a protocol stack structure of the network **100** of the legacy communication and/or the 5G communication according to an embodiment of the disclosure.

[0074] Referring to FIG. **3**, the network **100** according to the illustrated embodiment may include the electronic device **101**, a legacy network **392**, a 5G network **394**, and the server **108**.

[0075] The electronic device **101** may include an Internet protocol **312**, a first communication protocol stack **314**, and a second communication protocol stack **316**. The electronic device **101** may communicate with the server **108** via the legacy network **392** and/or the 5G network **394**.

[0076] According to an embodiment, the electronic device **101** may perform Internet communication associated with the server **108** using the Internet protocol **312** (e.g., TCP, UDP, and IP). The Internet protocol **312** may be executed, for example, in a main processor (e.g., the main processor **121** of FIG. **1**) included in the electronic device **101**.

[0077] In another embodiment, the electronic device **101** may wirelessly communicate with the legacy network **392** using the first communication protocol stack **314**. According to another embodiment, the electronic device **101** may wirelessly communicate with the 5G network **394** using the second communication protocol stack **316**. The first communication protocol stack **314** and the second communication protocol stack **316** may be executed, for example, in one or more communication processors (e.g., the wireless communication module **192** of FIG. **1**) included in the electronic device **101**.

[0078] The server **108** may include an Internet protocol **322**. The server **108** may transmit and receive data related to the electronic device **101** and the Internet protocol **322** via the legacy network **392** and/or the 5G network **394**. According to an embodiment, the server **108** may include a cloud computing server that exists outside the legacy network **392** or the 5G network **394**. In

another embodiment, the server **108** may include an edge computing server (or, a mobile edge computing (MEC) server) located inside at least one of the legacy network or the 5G network **394**. [0079] The legacy network **392** may include an LTE base station **340** and an EPC **342**. The LTE base station **340** may include an LTE communication protocol stack **344**. The EPC **342** may include a legacy NAS protocol **346**. The legacy network **392** may perform LTE wireless communication with the electronic device **101** using the LTE communication protocol stack **344** and the legacy NAS protocol **346**.

[0080] The 5G network **394** may include an NR base station **350** and a 5GC **352**. The NR base station **350** may include an NR communication protocol stack **354**. The 5GC **352** may include a 5G NAS protocol **356**. The 5G network **394** may perform NR wireless communication with the electronic device **101** using the NR communication protocol stack **354** and the 5G NAS protocol **356**.

[0081] According to an embodiment, the first communication protocol stack **314**, the second communication protocol stack **316**, the LTE communication protocol stack **344**, and the NR communication protocol stack **354** may include a control plane protocol for transmitting and receiving a control message and a user plane protocol for transmitting and receiving user data. The control message may include, for example, a message related to at least one of security control, bearer setup, authentication, registration, or mobility management. The user data may include, for example, the remaining data except for the control message.

[0082] According to an embodiment, a control plane protocol and a user plane protocol may include physical (PHY), medium access control (MAC), radio link control (RLC), or packet data convergence protocol (PDCP) layers. The PHY layer may, for example, channel code and modulate data received from a higher layer (e.g., the MAC layer) and transmit the channel-coded and modulated data through a wireless channel, and demodulate and decode data received through the wireless channel and deliver the demodulated and decode data to the higher layer. The PHY layer included in the second communication protocol stack **316** and the NR communication protocol stack **354** may further perform operations related to the beamforming. The MAC layer may be logically/physically mapped, for example, to the wireless channel through which data is to be transmitted and received, and perform hybrid automatic repeat request (HARQ) for error correction. The RLC layer may perform, for example, concatenation, segmentation, or reassembly of data, and perform data ordering, reordering, or duplication checking of data. The PDCP layer may perform, for example, operations related to ciphering and data integrity of the control message and the user data. The second communication protocol stack **316** and the NR communication protocol stack **354** may further include a service data adaptation protocol (SDAP). The SDAP may, for example, manage radio bearer allocation based on quality of service (QoS) of user data.

[0083] According to various embodiments, the control plane protocol may include a radio resource control (RRC) layer and a non-access stratum (NAS) layer. The RRC layer may, for example, process control data related to radio bearer setup, paging, or mobility management. The NAS may, for example, process control messages related to authentication, registration, and mobility management.

[0084] FIGS. **4A**, **4B**, and **4C** are diagrams illustrating wireless communication systems providing a network of the legacy communication and/or the 5G communication according to various embodiments of the disclosure.

[0085] Referring to FIGS. **4A**, **4B**, and **4C**, a network environment **100A** to **100C** may include at least one of the legacy network and the 5G network. The legacy network may include, for example, a 4G or LTE base station **440** (e.g., an eNodeB (eNB)) of the 3GPP standard that supports the wireless connection with the electronic device **101** and an evolved packet core (EPC) **451** that manages the 4G communication. The 5G network may include, for example, a new radio (NR) base station **450** (e.g., a gNodeB (gNB)) that supports radio access with the electronic device **101** and a 5th generation core (5GC) **452** that manages the 5G communication of the electronic device **101**.

[0086] According to various embodiments, the electronic device **101** may transmit and receive the control messages and the user data via the legacy communication and/or the 5G communication. The control message may include, for example, a message related to at least one of security control, bearer setup, authentication, registration, or mobility management of the electronic device **101**. The user data may mean, for example, user data excluding the control message transmitted and received between the electronic device **101** and the core network **430** (e.g., EPC **442**).

[0087] Referring to FIG. **4A**, the electronic device **101** according to an embodiment may transmit and receive at least one of the control message or the user data to and from at least part of the 5G network (e.g., the NR base station **450** and the 5GC **452**) using at least part of the legacy network (e.g., the LTE base station **440** and the EPC **442**).

[0088] According to various embodiments, the network environment **100A** may include a network environment that provides wireless communication dual connectivity (multi-radio access technology (multi-RAT) dual connectivity (MR-DC)) to the LTE base station **440** and the NR base station **450**, and transmits and receives the control message to and from the electronic device **101** through the core network **430** of one of the EPC **442** or the 5GC **452**.

[0089] According to various embodiments, in the MR-DC environment, one of the LTE base station **440** or the NR base station **450** may operate as a master node (MN) **410** and the other may operate as a secondary node (SN) **420**. The MN **410** may be connected to the core network **430** to transmit and receive the control message. The MN **410** and the SN **420** may be connected through a network interface to transmit and receive messages related to management of radio resources (e.g., communication channels) to and from each other.

[0090] According to various embodiments, the MN **410** may be composed of the LTE base station **440**, the SN **420** may be composed of the NR base station **450**, and the core network **430** may be composed of the EPC **442**. For example, the control message may be transmitted and received through the LTE base station **440** and the EPC **442**, and the user data may be transmitted and received through the LTE base station **440** and the NR base station **450**.

[0091] Referring to FIG. **4B**, according to various embodiments, the 5G network may independently transmit and receive the control message and the user data to and from the electronic device **101**.

[0092] Referring to FIG. **4C**, according to various embodiments, the legacy network and the 5G network may independently transmit and receive data. For example, the electronic device **101** and the EPC **442** may transmit and receive the control message and the user data through the LTE base station **440**. For another example, the electronic device **101** and the 5GC **452** may transmit and receive the control message and the user data through the NR base station **450**.

[0093] According to various embodiments, the electronic device **101** may be registered with at least one of the EPC **442** or the 5GC **452** to transmit and receive the control message.

[0094] According to various embodiments, the EPC **442** or the 5GC **452** may interwork to manage the communication of the electronic device **101**. For example, the movement information of the electronic device **101** may be transmitted and received through an interface between the EPC **442** and the 5GC **452**.

[0095] FIG. **5** is a diagram illustrating an electronic device and a cellular network according to an embodiment of the disclosure.

[0096] According to various embodiments of the disclosure, a cellular network **500** may include a first node (e.g., the NR base station **450** of FIG. **4B**) and/or a second node (e.g., the master node **410** of FIG. **4A**).

[0097] According to various embodiments of the disclosure, the first node **450** may be a base station supporting first cellular communication. The first cellular communication may refer to any one of various cellular communication schemes that the electronic device **101** can support, for example, a communication scheme on the second network **294** of FIG. **2**. For example, the first cellular communication may be a communication scheme that uses a 5th generation mobile

communication scheme (e.g., new radio). According to an embodiment, the first node **450** may be a base station that supports a standalone mode supported by the first cellular communication. The standalone mode may be a mode in which the electronic device **101** transmits or receives data using a base station that supports the first cellular communication. The electronic device **101** may be connected to the first node **450** to transmit or receive data. Alternatively, the first node **450** may be a base station that supports a non-standalone mode supported by the first cellular communication. The non-standalone mode may be a mode in which the electronic device **101** transmits or receives the data using the base station supporting the first cellular communication and the base station supporting the second cellular communication. The electronic device **101** may be connected to the first node **450** and/or the second node **460** to transmit or receive the data.

[0098] According to various embodiments of the disclosure, the second node **410** may be the base station supporting the second cellular communication. The second cellular communication may refer to any one of various cellular communication schemes that the electronic device (e.g., the electronic device **101** of FIG. 1) can support, for example, a communication scheme on the first network **292** of FIG. 2. For example, the second cellular communication may be a communication scheme that uses a 4th generation mobile communication scheme (e.g., long term evolution).

[0099] According to various embodiments of the disclosure, the first cellular communication may be a cellular communication that performs data communication using a relatively high frequency band compared to the second cellular communication. A frequency band of the first cellular communication may have a higher frequency band compared to that of the second cellular communication. The first node **450** supporting the first cellular communication may implement a relatively high speed compared to the second node **410** supporting the second cellular communication due to the characteristics of the high frequency band.

[0100] The electronic device **101** may perform a fallback to support a voice service when performing voice over wi-fi (VoWi-Fi) to establish a communication connection with the second node **410** supporting the second cellular communication. When the voice service is terminated, the electronic device **101** may establish a communication connection again with the first node **450** supporting the first cellular communication. The electronic device **101** may perform the fallback regardless of a service state of the first cellular communication, thereby increasing signaling and decrease a data speed.

[0101] Hereinafter, in order to alleviate (or resolve) the phenomenon, an embodiment is described in which an electronic device **101** performs a fallback based on the service state (e.g., load balancing ratio) of the first cellular communication, depending on conditions. Even if the first cellular communication does not support the VoNR, the electronic device **101** may maintain the connection with the first cellular communication to prevent the signaling from unnecessarily increasing and quickly control the data speed when the voice service of the lower 3GPP network (e.g., the second cellular communication) is not in use.

[0102] FIG. 6 is a diagram illustrating the electronic device according to an embodiment of the disclosure.

[0103] Referring to FIG. 6, an electronic device (e.g., the electronic device **101** of FIG. 1) may include a first communication circuit **611**, a second communication circuit **612**, a communication processor (e.g., the first communication processor **212** of FIG. 2 and/or the second communication processor **214** of FIG. 2) **620**, and/or an application processor (e.g., the processor **120** of FIG. 1) **630**.

[0104] The application processor **630** may control various components of the electronic device **101**. Specific operations will be described later.

[0105] The communication processor **620** may perform data transmission and/or reception via the first cellular communication and/or the second cellular communication. The communication processor **640** may be connected to a first node (e.g., the first node **450** of FIG. 4B) via the first cellular communication, or connected to a second node (e.g., the second node **410** of FIG. 4A) via

the second cellular communication. The communication processor **620** may transmit user data received from the application processor **630** via the first cellular communication and/or the second cellular communication, and transmit user data received via the first cellular communication and/or the second cellular communication to the application processor **630**.

[0106] The first cellular communication may refer to any one of various cellular communication schemes that the electronic device **101** can support, for example, a communication scheme on the second network **294** of FIG. **2**. For example, the first cellular communication may be a communication scheme that uses a 5th generation mobile communication scheme (e.g., new radio).

[0107] The second cellular communication may refer to any one of various cellular communication schemes that the electronic device (e.g., the electronic device **101** of FIG. **1**) can support, for example, the communication scheme on the first network **292** of FIG. **2**. For example, the second cellular communication may be a communication scheme that uses a 4th generation mobile communication scheme (e.g., long term evolution).

[0108] The first communication circuit **611** is a communication circuit that supports the first cellular communication and/or the second cellular communication, and may provide communication with an external electronic device (e.g., the external electronic device **104** of FIG. **1**) to the electronic device **101** through the first cellular communication and/or the second cellular communication.

[0109] The second communication circuit **612** is a communication circuit that supports short-range wireless communication (e.g., Wi-Fi), and may provide the communication with the external electronic device (e.g., the external electronic device **104** of FIG. **1**) to the electronic device **101** through the short-range wireless communication (e.g., Wi-Fi).

[0110] The electronic device **101** may perform the disconnection of the first cellular communication and the connection of the second cellular communication in order to provide the voice service, while being in the connected state of the first cellular communication. Hereinafter, a specific embodiment of the disconnection of the first cellular communication will be described.

[0111] The application processor **630** may check whether the electronic device **101** satisfies the conditions related to the disconnection of the first cellular communication while being in the connected state through the first cellular communication.

[0112] The conditions related to the disconnection of the first cellular communication may include conditions in which the load balancing rate of the Wi-Fi is relatively higher than the load balancing rate of the NR. The load balancing refers to an operation of balancing a load being processed by using one communication scheme (e.g., NR or LTE) into multiple communication schemes (Wi-Fi+NR or Wi-Fi+LTE).

[0113] The conditions related to the disconnection of the first cellular communication may include a case in which an active standby mode corresponds to the Wi-Fi. The active standby mode refers to a mode in which one communication scheme operates in an active state and the remaining communication schemes operate in a standby state.

[0114] The conditions related to the disconnection of the first cellular communication may include a case where the priority of the communication scheme for performing the data transmission/reception is higher for the Wi-Fi than for the cellular network (LTE and NR). Since the Wi-Fi is preferentially used for the data transmission in the case where the priority of the communication scheme for performing the data transmission/reception is higher for the Wi-Fi than for the cellular network (LTE and NR), the amount of data transmission using the NR is relatively small, so the need to use the Wi-Fi and the NR together using the ATSSS technology may be reduced. Therefore, the electronic device **101** may prepare the fallback to the LTE that may support the voice service instead of maintaining the use of the NR. This will be described with reference to FIG. **7**.

[0115] FIG. **7** is a flowchart illustrating an operation method for an electronic device according to an embodiment of the disclosure.

[0116] The operations described with reference to FIG. 7 may be implemented based on instructions that may be stored in the computer recording medium or the memory (e.g., the memory **130** of FIG. 1). An illustrated method **700** may be executed by the electronic device (e.g., the electronic device **101** of FIG. 6) described with reference to FIGS. 1 to 3, 4A to 4C, 5, and 6 above, and the technical features described above will be omitted below. The order of each operation of FIG. 7 may be changed, some operations may be omitted, and some operations may be performed simultaneously.

[0117] In operation **710**, the application processor (e.g., the application processor **630** of FIG. 6) may check whether a first condition related to the disconnection of the first cellular communication is satisfied, and transmit a signal indicating that the first condition is satisfied to the communication processor (e.g., the communication processor **620** of FIG. 6).

[0118] According to an embodiment, the first cellular communication may include new radio (NR). The second cellular communication may include long-term evolution (LTE). According to an embodiment, a first condition related to the disconnection of the first cellular communication may include a condition in which the load balancing rate of the Wi-Fi is relatively higher than the load balancing rate of the NR. The load balancing refers to an operation of balancing a load being processed by using one communication scheme (e.g., the NR or LTE) into multiple communication schemes (Wi-Fi+NR or Wi-Fi+LTE). When the load balancing rate of the Wi-Fi is relatively higher than the load balancing rate of the NR, the electronic device may determine that a signal transmission ratio using the Wi-Fi is relatively higher. In this case, since the amount of data transmission using the NR is relatively small, the need to use the Wi-Fi and the NR together using the access traffic steering, switching, splitting (ATSSS) technology may be reduced. Therefore, the electronic device **101** may prepare the fallback to the LTE that may support the voice service instead of maintaining the use of the NR. The ATSSS refers to a technology that manages traffic transmitted through the 3GPP networks (e.g., the NR and LTE) and the non-3GPP networks (e.g., the Wi-Fi). The access traffic steering refers to a technology that selects one network among the GPP networks (e.g., the NR and LTE) and the non-3GPP networks (e.g., the Wi-Fi) and transmits data through the selected network. The access traffic switching refers to a technology that transmits data to another network while transmitting data to one network. The access traffic splitting refers to a technology that distributes and transmits a single data flow using multiple networks. The application processor **630** may transmit, to the communication processor **620**, a signal indicating that the first condition is satisfied based on that the load balancing rate of the Wi-Fi is relatively higher than the load balancing rate of the NR.

[0119] According to an embodiment, the first condition related to the disconnection of the first cellular communication may include a case where the active standby mode corresponds to the Wi-Fi. The active standby mode refers to a mode in which one communication scheme operates in an active state and the remaining communication schemes operate in a standby state. The electronic device may control to execute a service on a server with a highest score or priority among the standby servers when a failure occurs in the active server. When the active standby mode corresponds to the Wi-Fi, the electronic device may preferentially transmit data using the Wi-Fi, and since the amount of data transmission using the NR is relatively small, the need to use the Wi-Fi and the NR together using the ATSSS technology may be reduced. Therefore, the electronic device **101** may prepare the fallback to the LTE that may support the voice service instead of maintaining the use of the NR. The application processor **630** may transmit, to the communication processor **620**, the signal indicating that the first condition is satisfied based on that the active standby mode corresponds to the Wi-Fi.

[0120] The conditions related to the disconnection of the first cellular communication may include a case where the priority of the communication scheme for performing the data transmission/reception is higher for the Wi-Fi than for the cellular network (LTE and NR). Since the Wi-Fi is preferentially used for the data transmission in the case where the priority of the

communication scheme for performing the data transmission/reception is higher for the Wi-Fi than for the cellular network (LTE and NR), the amount of data transmission using the NR is relatively small, so the need to use the Wi-Fi and the NR together using the ATSSS technology may be reduced. Therefore, the electronic device **101** may prepare the fallback to the LTE that may support the voice service instead of maintaining the use of the NR. The application processor **630** may transmit, to the communication processor **620**, the signal indicating that the first condition is satisfied based on that the priority-based corresponds to the Wi-Fi.

[0121] In operation **720**, the application processor **630** may check whether a second condition related to the disconnection of the first cellular communication is satisfied, and transmit a signal indicating that the second condition is satisfied to the communication processor **620**.

[0122] According to an embodiment, the second condition may include a condition in which the load balancing of the first cellular communication is less than (or less than or equal to) a pre-specified level (e.g., about 10%). The first cellular communication may include the new radio (NR). When the load balancing of the NR is less than the specified level, the load balancing of the NR may be lowered because the signal strength of the NR is relatively poor compared to the signal strength of the Wi-Fi, so the electronic device **101** may perform the fallback to the LTE that may support a voice service instead of maintaining the use of the NR. The application processor **630** may transmit, to the communication processor **620**, the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied based on that the load balancing of the first cellular communication is less than (or less than or equal to) the pre-specified level.

[0123] In operation **730**, the communication processor **620** may prepare to disconnect the first cellular communication and connect the second cellular communication based on the reception of the signal indicating that the first condition is satisfied. The communication processor **620** may prepare to disconnect the communication via the NR, and at the same time, connect the communication with the LTE based on the reception of the signal indicating that the first condition is satisfied.

[0124] In operation **740**, the communication processor **620** may perform the disconnection of the first cellular communication and the connection of the second cellular communication based on the reception of the signal indicating that the second condition is satisfied.

[0125] FIG. **8** is a diagram illustrating an embodiment in which the electronic device change from a connection combination of the Wi-Fi and the first cellular communication to a connection combination of the Wi-Fi and the second cellular communication according to an embodiment of the disclosure.

[0126] The operations described with reference to FIG. **8** may be implemented based on instructions that may be stored in the computer recording medium or the memory (e.g., the memory **130** of FIG. **1**). An illustrated method **800** may be executed by the electronic device (e.g., the electronic device **101** of FIG. **6**) described with reference to FIGS. **1** to **3**, **4A** to **4C**, **5**, and **6** above, and the technical features described above will be omitted below. The order of each operation of FIG. **8** may be changed, some operations may be omitted, and some operations may be performed simultaneously.

[0127] In operation **805**, the electronic device **101** may be registered with a 5G network (NW) and may be in a state capable of supporting VoWi-Fi.

[0128] In operation **810**, the electronic device **101** may determine whether the access traffic steering, switching, splitting (ATSSS) is in an active state. The ATSSS refers to a technology that manages traffic transmitted through the 3GPP networks (e.g., the NR and LTE) and the non-3GPP networks (e.g., the Wi-Fi). The access traffic steering refers to a technology that selects one network among the GPP networks (e.g., the NR and LTE) and the non-3GPP networks (e.g., the Wi-Fi) and transmits data through the selected network. The access traffic switching refers to a technology that transmits data to another network while transmitting data to one network. The

access traffic splitting refers to a technology that distributes and transmits a single data flow using multiple networks. The electronic device **101** may determine whether to support the ATSSS through an ATSSS support indicator (ATS-IND) during a network registration process. For example, when the electronic device **101** can support the ATSSS, the ATS-IND may be displayed as 1, and when the electronic device **101** cannot support the ATSSS, the ATS-IND may be displayed as 0. This is not fixed, and the electronic device **101** may display the ATS-IND as 0 to display that the ATSSS support is possible, and the electronic device **101** may display the ATS-IND as 1 to display that the ATSSS support is not possible.

[0129] According to an embodiment, the electronic device **101** may check whether a network node supports the ATSSS through a register procedure. When the electronic device **101** is registered with the network that supports the ATSSS, the electronic device **101** may request multi access protocol data unit (MA PDU) session establishment. The multi access (MA) refers to a multiple access technology in which multiple terminals share the same communication channel. A protocol data unit (PDU) refers to a unit of data used in a protocol. The electronic device **101** may request the MA PDU session establishment by establishing a request type to a “MA PDU request” in a UL NAS transport message. The electronic device **101** may establish the MA PDU session between the electronic device **101** and the network through a PDU session establishment request (request type: MA PDU request) and a PDU session establishment accept (ATSSS container IE), and acquire at least one ATSSS parameter. The ATSSS parameter for utilizing resources of the 3GPP and non-3GPP in the 5G core of TS 24.193 may include, for example, one of data traffic, active-standby, load-balancing, and priority-based.

[0130] The electronic device **101** may perform routing through the corresponding network (e.g., active network) until one network (e.g., the 5G or Wi-Fi) may not use data traffic. The routing refers to a process of selecting a data transmission path on the network. The electronic device **101** may switch to another network (e.g., standby network) when that the corresponding network may not use the data traffic. The electronic device **101** may switch traffic back to a previously used network (e.g., the active network) when the previously used network becomes available again. The load balancing may refer to a parameter that adjusts the ratio of the data traffic to be transmitted through the 3GPP (e.g., the 5G NW) and the data traffic to be transmitted through the non-3GPP (e.g., the Wi-Fi NW). The priority-based may refer to a parameter that preferentially transmits the data traffic through a network with a specified higher priority. The electronic device **101** may transmit data traffic by switching to a network with a lower priority when a network with a higher priority may not be used.

[0131] In operation **815**, the electronic device **101** may transmit data using a combination of the Wi-Fi and the new radio (NR) based on that the ATSSS is activated. The Wi-Fi may correspond to the non-3GPP network, and the NR may correspond to the 3GPP network.

[0132] In operation **820**, the electronic device **101** may determine whether the first condition related to the disconnection of the first cellular communication is satisfied. According to an embodiment, the first cellular communication may include the new radio (NR). The second cellular communication may include the long-term evolution (LTE). The application processor (e.g., the application processor **630** of FIG. **6**) may check whether the first condition related to the disconnection of the first cellular communication is satisfied, and transmit the signal indicating that the first condition is satisfied to the communication processor (e.g., the communication processor **620** of FIG. **6**).

[0133] According to an embodiment, the first condition related to the disconnection of the first cellular communication may include the condition in which the load balancing rate of the Wi-Fi is relatively higher than the load balancing rate of the NR. The load balancing refers to the operation of balancing the load being processed by using one communication scheme (e.g., the NR or LTE) into multiple communication schemes (Wi-Fi+NR or Wi-Fi+LTE). The electronic device **101** may acquire the ATSSS parameter including the load balancing while establishing the MA PDU session

between the networks. When the load balancing rate of the Wi-Fi is relatively higher than the load balancing rate of the NR, the electronic device **101** may determine that the signal transmission ratio using the Wi-Fi is relatively higher. In this case, since the amount of data transmission using the NR is relatively small, the need to use the Wi-Fi and the NR together using the access traffic steering, switching, splitting (ATSSS) technology may be reduced. Therefore, the electronic device **101** may prepare the fallback to the LTE that may support the voice service instead of maintaining the use of the NR.

[0134] According to an embodiment, the first condition related to the disconnection of the first cellular communication may include the case where the active standby mode corresponds to the Wi-Fi. The active standby mode refers to a mode in which one server operates in an active state and the remaining servers operate in a standby state. The electronic device may control to execute a service on a server with a highest score or priority among the standby servers when the failure occurs in the active server. The electronic device **101** may acquire the ATSSS parameter including the active standby mode while establishing the MA PDU session between the networks. When the active standby mode corresponds to the Wi-Fi, the electronic device may preferentially transmit data using the Wi-Fi, and since the amount of data transmission using the NR is relatively small, the need to use the Wi-Fi and the NR together using the ATSSS technology may be reduced. Therefore, the electronic device **101** may prepare the fallback to the LTE that may support the voice service instead of maintaining the use of the NR. The application processor **630** may transmit, to the communication processor **620**, the signal indicating that the first condition is satisfied based on that the active standby mode corresponds to the Wi-Fi.

[0135] According to an embodiment, the first condition related to the disconnection of the first cellular communication may include the case where the priority-based corresponds to the Wi-Fi. In the case where the priority-based corresponds to the Wi-Fi, since the Wi-Fi is preferentially used for the data transmission, the amount of data transmission using the NR is relatively small, so the need to use the Wi-Fi and the NR together using the ATSSS technology may be reduced. Therefore, the electronic device **101** may prepare the fallback to the LTE that may support the voice service instead of maintaining the use of the NR. The electronic device **101** may acquire the ATSSS parameter including the priority-based while establishing the MA PDU session between the networks. The application processor **630** may transmit, to the communication processor **620**, the signal indicating that the first condition is satisfied based on that the priority-based corresponds to the Wi-Fi.

[0136] In operation **825**, the communication processor **620** may prepare the fallback from the combination of the Wi-Fi and the NR to the combination of the Wi-Fi and the LTE based on receiving the signal indicating that the first condition is satisfied.

[0137] In operation **830**, the electronic device **101** may determine whether the second condition related to the disconnection of the first cellular communication is satisfied. According to an embodiment, the second condition may include the condition in which the load balancing of the first cellular communication is less than (or less than or equal to) a pre-specified level (e.g., about 10%). The electronic device **101** may acquire the ATSSS parameter including the load balancing while establishing the MA PDU session between the networks. The first cellular communication may include the new radio (NR). When the load balancing of the NR is less than the specified level, the load balancing of the NR may be lowered because the signal strength of the NR is relatively poor compared to the signal strength of the Wi-Fi, so the electronic device **101** may perform the fallback to the LTE that may support the voice service instead of maintaining the use of the NR. The application processor **630** may transmit, to the communication processor **620**, the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied based on that the load balancing of the first cellular communication is less than (or less than or equal to) the pre-specified level.

[0138] In operation **832**, the electronic device **101** may deactivate the ATSSS based on that the

second condition is satisfied.

[0139] In operation **834**, the communication processor **620** may perform the disconnection of the first cellular communication and the connection of the second cellular communication based on the reception of the signal indicating that the second condition is satisfied. The communication processor **620** may fallback from the combination of the Wi-Fi and the NR to the combination of the Wi-Fi and the LTE. The electronic device **101** may transmit data in a combination of the Wi-Fi and the LTE.

[0140] FIG. **9** is a diagram illustrating an embodiment in which the electronic device changes from the connection combination of the Wi-Fi and the second cellular communication to the connection combination of the Wi-Fi and the first cellular communication according to an embodiment of the disclosure.

[0141] The operations described with reference to FIG. **9** may be implemented based on instructions that may be stored in a computer recording medium or memory (e.g., the memory **130** of FIG. **1**). An illustrated method **900** may be executed by the electronic device (e.g., the electronic device **101** of FIG. **6**) described with reference to FIGS. **1** to **3**, **4A** to **4C**, **5**, and **6** above, and the technical features described above will be omitted below. The order of each operation of FIG. **9** may be changed, some operations may be omitted, and some operations may be performed simultaneously.

[0142] In operation **902**, the electronic device **101** may transmit data in the combination of the Wi-Fi and the LTE.

[0143] In operation **904**, the electronic device **101** may be registered with the LTE network (NW) and may be in the state capable of supporting the VoWi-Fi.

[0144] In operation **910**, the electronic device **101** may determine whether the access traffic steering, switching, splitting (ATSSS) is supported. The ATSSS refers to a technology that manages traffic transmitted through the 3GPP networks (e.g., the NR and LTE) and the non-3GPP networks (e.g., the Wi-Fi). The access traffic steering refers to a technology that selects one network among the GPP networks (e.g., the NR and LTE) and the non-3GPP networks (e.g., the Wi-Fi) and transmits data through the selected network. The access traffic switching refers to a technology that transmits data to another network while transmitting data to one network. The access traffic splitting refers to a technology that distributes and transmits a single data flow using multiple networks. The electronic device **101** may determine whether to support the ATSSS through the ATSSS support indicator (ATS-IND) during the network registration process. For example, when the electronic device **101** can support the ATSSS, the ATS-IND may be displayed as 1, and when the electronic device **101** cannot support the ATSSS, the ATS-IND may be displayed as 0. This is not fixed, and the electronic device **101** may display the ATS-IND as 0 to display that the ATSSS support is possible, and the electronic device **101** may display the ATS-IND as 1 to display that the ATSSS support is not possible.

[0145] In operation **920**, the electronic device **101** may check whether the NR base station is searched within a certain distance from the electronic device **101** based on that the ATSSS is supported. When the NR base station is not searched within a certain distance, the electronic device **101** may transmit data using the combination of the Wi-Fi and the LTE, and terminate the switching operation of the connected cellular communication. The electronic device **101** may display a guide screen (e.g., a user interface) that may select whether to use the data of the 3GPP and the non-3GPP simultaneously based on that the ATSSS is supported.

[0146] In operation **930**, the electronic device **101** may determine whether the signal strength of the VoWi-Fi exceeds a pre-specified level based on that the NR base station is searched within a certain distance. The pre-specified level may be determined differently depending on a threshold for handover to the VoLTE. The electronic device **101** may transmit data using the combination of the Wi-Fi and the LTE based on that the measured signal strength of the VoWi-Fi is less than the threshold for the handover to the VoLTE, and terminate the switching operation of the connected

cellular communication.

[0147] In operation **932**, the electronic device **101** may replace the LTE with the NR based on that the measured signal strength of the VoWi-Fi exceeds the threshold for the handover to the VoLTE. In operation **934**, the electronic device **101** may transmit data using the combination of the Wi-Fi and the new radio (NR). The Wi-Fi may correspond to the non-3GPP network, and the NR may correspond to the 3GPP network. The electronic device **101** may attempt cell reselection to the NR base station existing within a specified distance from the electronic device **101** by local releasing while being connected (RRC connected) to the LTE network, and may be registered with the NR network.

[0148] The electronic device may include the first communication circuit for supporting the first cellular communication and/or the second cellular communication, the second communication circuit for supporting the short-range wireless communication, the application processor, and the communication processor. The application processor may check whether the electronic device satisfies the first condition related to the disconnection of the first cellular communication in the state in which the electronic device is connected to the cellular network through the first cellular communication in a call connection status through the voice over (Vo) Wi-Fi, and transmit, to the communication processor, the signal indicating that the first condition related to the disconnection of the first cellular communication is satisfied based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication, check whether the electronic device satisfies the second condition related to the disconnection of the first cellular communication in the state in which the electronic device satisfies the first condition related to the disconnection of the first cellular communication, and transmit, to the communication processor, the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied based on that the electronic device satisfies the second condition related to the disconnection of the first cellular communication. The communication processor may prepare to disconnect the first cellular communication and connect the second cellular communication based on the reception of the signal indicating that the first condition related to the disconnection of the first cellular communication is satisfied, and may perform the disconnection of the first cellular communication and the connection of the second cellular communication based on the reception of the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied.

[0149] The first condition related to the disconnection of the first cellular communication includes the condition that the load balancing rate of the short-range wireless communication is relatively higher than the load balancing rate of the first cellular communication, and the application processor may transmit, to the communication processor, the signal indicating that the first condition is satisfied based on that the load balancing rate of the short-range wireless communication is greater than or equal to (or exceeds) the load balancing rate of the first cellular communication.

[0150] The first condition related to the disconnection of the first cellular communication includes a case where the short-range wireless communication operates in the active state and the remaining first cellular communication and/or second cellular communications operate in the standby state, and the application processor may transmit, to the communication processor, the signal indicating that the first condition is satisfied based on that the short-range wireless communication operates in the active state and the remaining first cellular communication and/or second cellular communications operate in the standby state.

[0151] The first condition related to the disconnection of the first cellular communication includes a case where the priority of the communication scheme for performing the data transmission/reception is higher for the short-range wireless communication than for the first cellular communication, and the application processor may transmit the signal to the communication processor indicating that the first condition is satisfied based on that the priority of

the communication scheme for performing the data transmission/reception is higher for the short-range wireless communication than for the first cellular communication.

[0152] The second condition includes the condition that the load balancing of the first cellular communication is less than (or less than or equal to) the pre-specified level, and the application processor may transmit, to the communication processor, the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied based on that the load balancing of the first cellular communication is less than (or less than or equal to) the pre-specified level.

[0153] The first cellular communication may include the new radio (NR).

[0154] The second cellular communication may include the long-term evolution (LTE).

[0155] The electronic device may include the first communication circuit for supporting the first cellular communication and/or the second cellular communication, the second communication circuit for supporting the short-range wireless communication, the application processor, and the communication processor. The application processor may check whether the electronic device supports the access traffic steering, switching, splitting (ATSSS) in the call connection status through the voice over (Vo) Wi-Fi, determine whether the base station supporting the first cellular communication exists within a preset distance from the electronic device based on that the electronic device supports the ATSSS, determine whether the signal strength of the voice over (Vo) Wi-Fi is greater than or equal to (or exceeds) a pre-specified level based on that the base station supporting the first cellular communication exists within the preset distance from the electronic device, and transmit the signal related to the disconnection of the second cellular communication to the communication processor based on that the signal strength of the voice over (Vo) Wi-Fi is greater than or equal to (or exceeds) the pre-specified level. The communication processor may perform the disconnection of the second cellular communication and the connection of the first cellular communication based on that the signal related to the disconnection of the second cellular communication is received from the application processor.

[0156] The application processor may transmit the signal related to the disconnection of the second cellular communication to the communication processor based on that the call connection through the voice over (Vo) Wi-Fi is terminated, and the communication processor may perform the disconnection of the second cellular communication and the connection of the first cellular communication based on that the signal related to the disconnection of the second cellular communication is received from the application processor.

[0157] An operation method for an electronic device for switching an operation mode of cellular communication includes checking whether a first condition related to a disconnection of a first cellular communication is satisfied in a call connection status through voice over (Vo) Wi-Fi, transmitting, to a communication processor, a signal indicating that the electronic device satisfies the first condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication, checking whether the electronic device satisfies a second condition related to the disconnection of the first cellular communication, in the state where the electronic device satisfies the first condition related to the disconnection of the first cellular communication, transmitting, to the communication processor, a signal indicating that the electronic device satisfies the second condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the second condition related to the disconnection of the first cellular communication, preparing to disconnect the first cellular communication and connect the second cellular communication based on reception of a signal indicating that the first condition related to the disconnection of the first cellular communication is satisfied, and performing the disconnection of the first cellular communication and the connection of the second cellular communication based on reception of a signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied.

[0158] It will be appreciated that various embodiments of the disclosure according to the claims and description in the specification can be realized in the form of hardware, software or a combination of hardware and software.

[0159] Any such software may be stored in non-transitory computer readable storage media. The non-transitory computer readable storage media store one or more computer programs (software modules), the one or more computer programs include computer-executable instructions that, when executed by one or more processors of an electronic device individually or collectively, cause the electronic device to perform a method of the disclosure.

[0160] Any such software may be stored in the form of volatile or non-volatile storage such as, for example, a storage device like read only memory (ROM), whether erasable or rewritable or not, or in the form of memory such as, for example, random access memory (RAM), memory chips, device or integrated circuits or on an optically or magnetically readable medium such as, for example, a compact disk (CD), digital versatile disc (DVD), magnetic disk or magnetic tape or the like. It will be appreciated that the storage devices and storage media are various embodiments of non-transitory machine-readable storage that are suitable for storing a computer program or computer programs comprising instructions that, when executed, implement various embodiments of the disclosure. Accordingly, various embodiments provide a program comprising code for implementing apparatus or a method as claimed in any one of the claims of this specification and a non-transitory machine-readable storage storing such a program.

[0161] While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. An electronic device, comprising: a first communication circuit that supports at least one of first cellular communication or second cellular communication; a second communication circuit that supports short-range wireless communication; memory, comprising one or more storage media, storing instructions; at least one application processor coupled to the memory; and at least one communication processor coupled to the memory, wherein the instructions, when executed by the at least one application processor, cause the electronic device to: check whether the electronic device satisfies a first condition related to a disconnection of the first cellular communication, in a state in which the electronic device is connected to a cellular network through the first cellular communication, in a call connection status through voice over (Vo) wireless fidelity (Wi-Fi), transmit, to the at least one communication processor, a signal indicating that the electronic device satisfies the first condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication, check whether the electronic device satisfies a second condition related to the disconnection of the first cellular communication, in the state where the electronic device satisfies the first condition related to the disconnection of the first cellular communication, and transmit, to the at least one communication processor, a signal indicating that the electronic device satisfies the second condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the second condition related to the disconnection of the first cellular communication, and wherein the instructions, when executed by the at least one communication processor, cause the electronic device to: prepare to disconnect the first cellular communication and connect the second cellular communication based on reception of the signal indicating that the first condition related to the disconnection of the first cellular communication is satisfied, and disconnect the first cellular communication and connect the second cellular communication based on reception of the signal indicating that the second condition related to the disconnection of the

first cellular communication is satisfied.

2. The electronic device of claim 1, wherein the first condition related to the disconnection of the first cellular communication includes a condition that a load balancing rate of the short-range wireless communication is relatively higher than a load balancing rate of the first cellular communication, and wherein the instructions, when executed by at least one the application processor, further cause the electronic device to: transmit, to the at least one communication processor, the signal indicating that the first condition is satisfied based on that the load balancing rate of the short-range wireless communication is greater than or equal to the load balancing rate of the first cellular communication.

3. The electronic device of claim 2, wherein the first condition related to the disconnection of the first cellular communication includes a case where the short-range wireless communication operates in an active state and at least one of remaining first cellular communications or second cellular communications operate in a standby state, and wherein the instructions, when executed by at least one the application processor, further cause the electronic device to: transmit, to the at least one communication processor, the signal indicating that the first condition is satisfied based on that the short-range wireless communication operates in the active state and the at least one of remaining first cellular communications or second cellular communications operate in the standby state.

4. The electronic device of claim 3, wherein the first condition related to the disconnection of the first cellular communication includes a case where a priority of a communication scheme for performing data transmission/reception is higher for the short-range wireless communication than for the first cellular communication, and wherein the instructions, when executed by at least one the application processor, further cause the electronic device to: transmit, to the at least one communication processor, the signal indicating that the first condition is satisfied based on that the priority of the communication scheme for performing the data transmission/reception is higher for the short-range wireless communication than for the first cellular communication.

5. The electronic device of claim 1, wherein the second condition includes a condition that load balancing of the first cellular communication is less than or equal to a pre-specified level, and wherein the instructions, when executed by the at least one application processor, further cause the electronic device to: transmit, to the at least one communication processor, the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied based on that the load balancing of the first cellular communication is less than or equal to the pre-specified level.

6. The electronic device of claim 1, wherein the first cellular communication includes new radio (NR).

7. The electronic device of claim 1, wherein the second cellular communication includes long-term evolution (LTE).

8. An electronic device, comprising: a first communication circuit that supports at least one of first cellular communication or second cellular communication; a second communication circuit that supports short-range wireless communication; memory, comprising one or more storage media, storing instructions; at least one application processor coupled to the memory; and at least one communication processor coupled to the memory, wherein the instructions, when executed by the at least one application processor, cause the electronic device to: check whether the electronic device supports access traffic steering, switching, splitting (ATSSS), in a call connection status through voice over (Vo) wireless fidelity (Wi-Fi), determine whether a base station supporting the first cellular communication exists within a preset distance from the electronic device based on that the electronic device supports the ATSSS, determine whether a signal strength of the Vo Wi-Fi is greater than or equal to a pre-specified level based on that the base station supporting the first cellular communication exists within the preset distance from the electronic device, and transmit, to the at least one communication processor, a signal related to a disconnection of the second cellular

- communication based on that the signal strength of the Vo Wi-Fi is greater than or equal to the pre-specified level, and wherein the instructions, when executed by the at least one communication processor, cause the electronic device to: disconnect the second cellular communication and connect the first cellular communication based on a signal related to the disconnection of the second cellular communication received from the application processor.
- 9.** The electronic device of claim 8, wherein the instructions, when executed by the at least one application processor, further cause the electronic device to transmit, to the at least one communication processor, the signal related to the disconnection of the second cellular communication based on that a call connection through the Vo Wi-Fi is terminated, and wherein the instructions, when executed by the at least one communication processor, further cause the electronic device to disconnect the second cellular communication and connect the first cellular communication based on that the signal related to the disconnection of the second cellular communication is received from the application processor.
- 10.** The electronic device of claim 8, wherein the first cellular communication includes new radio (NR).
- 11.** The electronic device of claim 8, wherein the second cellular communication includes long-term evolution (LTE).
- 12.** A method performed by an electronic device for switching an operation mode of cellular communication, the method comprising: checking whether a first condition related to a disconnection of a first cellular communication is satisfied in a call connection status through voice over (Vo) wireless fidelity (Wi-Fi); transmitting, to at least one communication processor, a signal indicating that the electronic device satisfies the first condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication; checking whether the electronic device satisfies a second condition related to the disconnection of the first cellular communication, in a state where the electronic device satisfies the first condition related to the disconnection of the first cellular communication; transmitting, to the at least one communication processor, a signal indicating that the electronic device satisfies the second condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the second condition related to the disconnection of the first cellular communication; preparing to disconnect the first cellular communication and connect a second cellular communication based on reception of the signal indicating that the first condition related to the disconnection of the first cellular communication is satisfied; and disconnecting the first cellular communication and connecting the second cellular communication based on reception of the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied.
- 13.** The method of claim 12, wherein the first condition related to disconnection of the first cellular communication includes a condition that a load balancing rate of a short-range wireless communication is relatively higher than a load balancing rate of the first cellular communication, and wherein the transmitting of, to the at least one communication processor, the signal indicating that the electronic device satisfies the first condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication further includes transmitting, to the at least one communication processor, the signal indicating that the first condition is satisfied based on that the load balancing rate of the short-range wireless communication is greater than or equal to the load balancing rate of the first cellular communication.
- 14.** The method of claim 13, wherein the first condition related to the disconnection of the first cellular communication includes a case where the short-range wireless communication operates in an active state and at least one of remaining first cellular communications or second cellular communications operate in a standby state, and wherein the transmitting of, to the at least one communication processor, the signal indicating that the electronic device satisfies the first

condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication further includes transmitting, to the at least one communication processor, the signal indicating that the first condition is satisfied based on that the short-range wireless communication operates in the active state and the at least one of remaining first cellular communications or second cellular communications operate in the standby state.

15. The method of claim 14, wherein the first condition related to the disconnection of the first cellular communication includes a case where a priority of a communication scheme for performing data transmission/reception is higher for the short-range wireless communication than for the first cellular communication, and wherein the transmitting of, to the at least one communication processor, the signal indicating that the electronic device satisfies the first condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication further includes transmitting, to the at least one communication processor, the signal indicating that the first condition is satisfied based on that the priority of the communication scheme for performing the data transmission/reception is higher for the short-range wireless communication than for the first cellular communication.

16. The method of claim 12, wherein the second condition includes a condition that load balancing of the first cellular communication is less than or equal to a pre-specified level, and wherein the transmitting of, to the at least one communication processor, the signal indicating that the electronic device satisfies the second condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the second condition related to the disconnection of the first cellular communication further includes transmitting, to the at least one communication processor, the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied based on that the load balancing of the first cellular communication is less than or equal to the pre-specified level.

17. The method of claim 12, wherein the first cellular communication includes new radio (NR).

18. The method of claim 12, wherein the second cellular communication includes long-term evolution (LTE).

19. One or more non-transitory computer-readable storage media storing one or more computer programs including computer-executable instructions that, when executed by one or more processors of an electronic device individually or collectively, cause the electronic device to perform operations, the operations comprising: checking whether a first condition related to a disconnection of a first cellular communication is satisfied in a call connection status through voice over (Vo) wireless fidelity (Wi-Fi); transmitting, to at least one communication processor, a signal indicating that the electronic device satisfies the first condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the first condition related to the disconnection of the first cellular communication; checking whether the electronic device satisfies a second condition related to the disconnection of the first cellular communication, in a state where the electronic device satisfies the first condition related to the disconnection of the first cellular communication; transmitting, to the at least one communication processor, a signal indicating that the electronic device satisfies the second condition related to the disconnection of the first cellular communication based on that the electronic device satisfies the second condition related to the disconnection of the first cellular communication; preparing to disconnect the first cellular communication and connect a second cellular communication based on reception of the signal indicating that the first condition related to the disconnection of the first cellular communication is satisfied; and disconnecting the first cellular communication and connecting the second cellular communication based on reception of the signal indicating that the second condition related to the disconnection of the first cellular communication is satisfied.

20. The one or more non-transitory computer-readable storage media of claim 19, the operations

further comprising: transmitting, to the at least one communication processor, the signal indicating that the first condition is satisfied based on that a load balancing rate of a short-range wireless communication is greater than or equal to a load balancing rate of the first cellular communication.
