

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409375
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Silcock; Ryan et al.

Systems and methods for haptic simulation in incline exercise devices

Abstract

A haptic simulation exercise device includes a frame, a base supporting the frame, and an incline motor. The incline motor is configured to move the frame relative to the base to provide haptic simulation during a workout routine. An actuator moves the frame faster than the incline motor to simulate outdoor conditions during a workout routine.

Inventors:	Silcock; Ryan (Logan, UT), Olsen; Tyson (Logan, UT)
Applicant:	iFIT Inc. (Logan, UT)
Family ID:	88066241
Assignee:	iFIT Inc. (Logan, UT)
Appl. No.:	18/123026
Filed:	March 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230293963 A1	Sep. 21, 2023

Related U.S. Application Data

us-provisional-application US 63321303 20220318

Publication Classification

Int. Cl.: A63B71/06 (20060101); A63B24/00 (20060101)

U.S. Cl.:

CPC **A63B71/0619** (20130101); **A63B24/0087** (20130101); A63B2024/009 (20130101);
A63B2071/0655 (20130101); A63B2225/093 (20130101); A63B2225/66 (20130101)

Field of Classification Search

CPC: A63B (22/0015); A63B (22/0023); A63B (22/0046); A63B (22/02); A63B (22/0605);
A63B (24/0087); A63B (2225/09); A63B (2225/093); A63B (2225/66)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3123646	12/1963	Easton	N/A	N/A
3579339	12/1970	Chang et al.	N/A	N/A
4023795	12/1976	Pauls	N/A	N/A
4300760	12/1980	Bobroff	N/A	N/A
D286311	12/1985	Martinell	N/A	N/A
4630839	12/1985	Seol	N/A	N/A
4681318	12/1986	Lay	N/A	N/A
4684126	12/1986	Dalebout et al.	N/A	N/A
4728102	12/1987	Pauls	N/A	N/A
4750736	12/1987	Watterson	N/A	N/A
4796881	12/1988	Watterson	N/A	N/A
4813667	12/1988	Watterson	N/A	N/A
4830371	12/1988	Lay	N/A	N/A
4844451	12/1988	Bersonnet et al.	N/A	N/A
4850585	12/1988	Dalebout et al.	N/A	N/A
D304849	12/1988	Watterson	N/A	N/A
4880225	12/1988	Lucas et al.	N/A	N/A
4883272	12/1988	Lay	N/A	N/A
D306468	12/1989	Watterson	N/A	N/A
D306891	12/1989	Watterson	N/A	N/A
4913396	12/1989	Dalebout et al.	N/A	N/A
D307614	12/1989	Bingham	N/A	N/A
D307615	12/1989	Bingham	N/A	N/A
4921242	12/1989	Watterson	N/A	N/A
4932650	12/1989	Bingham et al.	N/A	N/A
D309167	12/1989	Griffin	N/A	N/A
D309485	12/1989	Bingham	N/A	N/A
4938478	12/1989	Lay	N/A	N/A
D310253	12/1989	Bersonnet	N/A	N/A
4955599	12/1989	Bersonnet et al.	N/A	N/A
4971316	12/1989	Dalebout et al.	N/A	N/A
D313055	12/1989	Watterson	N/A	N/A
4974832	12/1989	Dalebout	N/A	N/A
4979737	12/1989	Kock	N/A	N/A
4981294	12/1990	Dalebout et al.	N/A	N/A
D315765	12/1990	Measom	N/A	N/A
4998725	12/1990	Watterson et al.	N/A	N/A

5000442	12/1990	Dalebout et al.	N/A	N/A
5000443	12/1990	Dalebout et al.	N/A	N/A
5000444	12/1990	Dalebout et al.	N/A	N/A
D316124	12/1990	Dalebout	N/A	N/A
5013033	12/1990	Watterson et al.	N/A	N/A
5014980	12/1990	Bersonnet et al.	N/A	N/A
5016871	12/1990	Dalebout et al.	N/A	N/A
D318085	12/1990	Jacobson	N/A	N/A
D318086	12/1990	Bingham	N/A	N/A
D318699	12/1990	Jacobson	N/A	N/A
5029801	12/1990	Dalebout et al.	N/A	N/A
5034576	12/1990	Dalebout et al.	N/A	N/A
5058881	12/1990	Measom	N/A	N/A
5058882	12/1990	Dalebout et al.	N/A	N/A
D321388	12/1990	Dalebout	N/A	N/A
5062626	12/1990	Dalebout et al.	N/A	N/A
5062627	12/1990	Bingham	N/A	N/A
5062632	12/1990	Dalebout et al.	N/A	N/A
5062633	12/1990	Engel et al.	N/A	N/A
5067710	12/1990	Watterson et al.	N/A	N/A
5072929	12/1990	Peterson et al.	N/A	N/A
D323009	12/1991	Dalebout	N/A	N/A
D323198	12/1991	Dalebout	N/A	N/A
D323199	12/1991	Dalebout	N/A	N/A
D323863	12/1991	Watterson	N/A	N/A
5085426	12/1991	Wanzer	482/54	A63B 22/02
5088729	12/1991	Dalebout	N/A	N/A
5090694	12/1991	Pauls et al.	N/A	N/A
5102380	12/1991	Jacobson et al.	N/A	N/A
5104120	12/1991	Watterson et al.	N/A	N/A
5108093	12/1991	Watterson	N/A	N/A
D326491	12/1991	Dalebout	N/A	N/A
5122105	12/1991	Engel et al.	N/A	N/A
5135216	12/1991	Bingham et al.	N/A	N/A
5147265	12/1991	Pauls et al.	N/A	N/A
5149084	12/1991	Dalebout et al.	N/A	N/A
5149312	12/1991	Croft et al.	N/A	N/A
5163885	12/1991	Wanzer	482/54	A63B 22/02
5171196	12/1991	Lynch	N/A	N/A
D332347	12/1992	Raadt	N/A	N/A
5190505	12/1992	Dalebout et al.	N/A	N/A
5192255	12/1992	Dalebout et al.	N/A	N/A
5195937	12/1992	Engel et al.	N/A	N/A
5203826	12/1992	Dalebout	N/A	N/A
D335511	12/1992	Engel	N/A	N/A
D335905	12/1992	Cutter	N/A	N/A
D336498	12/1992	Engel	N/A	N/A
5217487	12/1992	Engel et al.	N/A	N/A
D337361	12/1992	Engel	N/A	N/A
D337666	12/1992	Peterson	N/A	N/A

D337799	12/1992	Cutter	N/A	N/A
5226866	12/1992	Engel et al.	N/A	N/A
5244446	12/1992	Engel et al.	N/A	N/A
5247853	12/1992	Dalebout	N/A	N/A
5256115	12/1992	Scholder	601/36	A63B 22/0605
5259611	12/1992	Dalebout et al.	N/A	N/A
D342106	12/1992	Campbell	N/A	N/A
5279528	12/1993	Dalebout et al.	N/A	N/A
D344112	12/1993	Smith	N/A	N/A
D344557	12/1993	Ashby	N/A	N/A
5282776	12/1993	Dalebout	N/A	N/A
5295931	12/1993	Dreibelbis et al.	N/A	N/A
5302161	12/1993	Loubert et al.	N/A	N/A
D347251	12/1993	Dreibelbis	N/A	N/A
5316534	12/1993	Dalebout et al.	N/A	N/A
D348493	12/1993	Ashby	N/A	N/A
D348494	12/1993	Ashby	N/A	N/A
5328164	12/1993	Soga	N/A	N/A
D349931	12/1993	Bostic	N/A	N/A
5336142	12/1993	Dalebout et al.	N/A	N/A
5344376	12/1993	Bostic et al.	N/A	N/A
D351202	12/1993	Bingham	N/A	N/A
D351435	12/1993	Peterson	N/A	N/A
D351633	12/1993	Bingham	N/A	N/A
D352534	12/1993	Dreibelbis	N/A	N/A
D353422	12/1993	Bostic	N/A	N/A
5372559	12/1993	Dalebout et al.	N/A	N/A
5374228	12/1993	Buisman et al.	N/A	N/A
5382221	12/1994	Hsu et al.	N/A	N/A
5387168	12/1994	Bostic	N/A	N/A
5393690	12/1994	Fu et al.	N/A	N/A
D356128	12/1994	Smith	N/A	N/A
5409435	12/1994	Daniels	N/A	N/A
5429563	12/1994	Engel	N/A	N/A
5431612	12/1994	Holden	N/A	N/A
D360915	12/1994	Bostic	N/A	N/A
5468205	12/1994	McFall	N/A	N/A
5489249	12/1995	Brewer	N/A	N/A
5492517	12/1995	Bostic	N/A	N/A
D367689	12/1995	Wilkinson	N/A	N/A
5511740	12/1995	Loubert	N/A	N/A
5512025	12/1995	Dalebout	N/A	N/A
D370949	12/1995	Furner	N/A	N/A
D371176	12/1995	Furner	N/A	N/A
5527245	12/1995	Dalebout	N/A	N/A
5529553	12/1995	Finlayson	N/A	N/A
5540429	12/1995	Dalebout	N/A	N/A
5549533	12/1995	Olson	N/A	N/A
5554085	12/1995	Dalebout	N/A	N/A
5569128	12/1995	Dalebout	N/A	N/A

5591105	12/1996	Dalebout	N/A	N/A
5591106	12/1996	Dalebout	N/A	N/A
5595556	12/1996	Dalebout	N/A	N/A
5607375	12/1996	Dalebout	N/A	N/A
5611539	12/1996	Watterson	N/A	N/A
5622527	12/1996	Watterson	N/A	N/A
5626538	12/1996	Dalebout	N/A	N/A
5626542	12/1996	Dalebout	N/A	N/A
D380024	12/1996	Novak	N/A	N/A
5637059	12/1996	Dalebout	N/A	N/A
D380509	12/1996	Wilkinson	N/A	N/A
5643153	12/1996	Nylen	N/A	N/A
5645509	12/1996	Brewer	N/A	N/A
D384118	12/1996	Deblauw	N/A	N/A
5662557	12/1996	Watterson	N/A	N/A
5669857	12/1996	Watterson	N/A	N/A
5672140	12/1996	Watterson	N/A	N/A
5674156	12/1996	Watterson	N/A	N/A
5674453	12/1996	Watterson	N/A	N/A
5676624	12/1996	Watterson	N/A	N/A
5683331	12/1996	Dalebout	N/A	N/A
5683332	12/1996	Watterson	N/A	N/A
D387825	12/1996	Fleck	N/A	N/A
5695433	12/1996	Buisman	N/A	N/A
5695434	12/1996	Dalebout	N/A	N/A
5695435	12/1996	Dalebout	N/A	N/A
5702325	12/1996	Watterson	N/A	N/A
5704879	12/1997	Watterson	N/A	N/A
5718657	12/1997	Dalebout et al.	N/A	N/A
5720200	12/1997	Anderson	N/A	N/A
5720698	12/1997	Dalebout	N/A	N/A
D392006	12/1997	Dalebout	N/A	N/A
5722922	12/1997	Watterson	N/A	N/A
5733229	12/1997	Dalebout	N/A	N/A
5743833	12/1997	Watterson	N/A	N/A
5762584	12/1997	Daniels	N/A	N/A
5762587	12/1997	Dalebout	N/A	N/A
5772560	12/1997	Watterson	N/A	N/A
5810698	12/1997	Hullett	N/A	N/A
5827155	12/1997	Jensen	N/A	N/A
5830114	12/1997	Halfen	N/A	N/A
5860893	12/1998	Watterson	N/A	N/A
5860894	12/1998	Dalebout	N/A	N/A
5899834	12/1998	Dalebout	N/A	N/A
D412953	12/1998	Armstrong	N/A	N/A
D413948	12/1998	Dalebout	N/A	N/A
5951441	12/1998	Dalebout	N/A	N/A
5951448	12/1998	Bolland	N/A	N/A
5961424	12/1998	Warner et al.	N/A	N/A
D416596	12/1998	Armstrong	N/A	N/A

6003166	12/1998	Hald	N/A	N/A
6019710	12/1999	Dalebout	N/A	N/A
6027429	12/1999	Daniels	N/A	N/A
6033347	12/1999	Dalebout et al.	N/A	N/A
D425940	12/1999	Halfen	N/A	N/A
6059692	12/1999	Hickman	N/A	N/A
D428949	12/1999	Simonson	N/A	N/A
6123646	12/1999	Colassi	N/A	N/A
6171217	12/2000	Cutler	N/A	N/A
6171219	12/2000	Simonson	N/A	N/A
6174267	12/2000	Dalebout	N/A	N/A
6193631	12/2000	Hickman	N/A	N/A
6228003	12/2000	Hald	N/A	N/A
6238323	12/2000	Simonson	N/A	N/A
6251052	12/2000	Simonson	N/A	N/A
6261022	12/2000	Dalebout et al.	N/A	N/A
6280362	12/2000	Dalebout et al.	N/A	N/A
6296594	12/2000	Simonson	N/A	N/A
D450872	12/2000	Dalebout	N/A	N/A
6312363	12/2000	Watterson	N/A	N/A
D452338	12/2000	Dalebout	N/A	N/A
D453543	12/2001	Cutler	N/A	N/A
D453948	12/2001	Cutler	N/A	N/A
6350218	12/2001	Dalebout et al.	N/A	N/A
6387020	12/2001	Simonson	N/A	N/A
6413191	12/2001	Harris	N/A	N/A
6422980	12/2001	Simonson	N/A	N/A
6447424	12/2001	Ashby et al.	N/A	N/A
6458060	12/2001	Watterson	N/A	N/A
6458061	12/2001	Simonson	N/A	N/A
6471622	12/2001	Hammer	N/A	N/A
6563225	12/2002	Soga	N/A	N/A
6572512	12/2002	Anderson	482/54	A63B 22/0207
6601016	12/2002	Brown	N/A	N/A
6623140	12/2002	Watterson	N/A	N/A
6626799	12/2002	Watterson	N/A	N/A
6652424	12/2002	Dalebout	N/A	N/A
6685607	12/2003	Olson	N/A	N/A
6695581	12/2003	Wasson	N/A	N/A
6701271	12/2003	Willner	N/A	N/A
6702719	12/2003	Brown	N/A	N/A
6712740	12/2003	Simonson	N/A	N/A
6730002	12/2003	Hald	N/A	N/A
6743153	12/2003	Watterson	N/A	N/A
6746371	12/2003	Brown	N/A	N/A
6749537	12/2003	Hickman	N/A	N/A
6761667	12/2003	Cutler et al.	N/A	N/A
6770015	12/2003	Simonson	N/A	N/A
6786852	12/2003	Watterson	N/A	N/A
6808472	12/2003	Hickman	N/A	N/A

6821230	12/2003	Dalebout	N/A	N/A
6830540	12/2003	Watterson	N/A	N/A
6863641	12/2004	Brown	N/A	N/A
6866613	12/2004	Brown	N/A	N/A
6875160	12/2004	Watterson	N/A	N/A
D507311	12/2004	Butler	N/A	N/A
6918858	12/2004	Watterson	N/A	N/A
6921351	12/2004	Hickman	N/A	N/A
6974404	12/2004	Watterson	N/A	N/A
6997852	12/2005	Watterson	N/A	N/A
7025713	12/2005	Dalebout	N/A	N/A
D520085	12/2005	Willardson	N/A	N/A
7044897	12/2005	Myers	N/A	N/A
7052442	12/2005	Watterson	N/A	N/A
7060006	12/2005	Watterson	N/A	N/A
7060008	12/2005	Watterson et al.	N/A	N/A
7070539	12/2005	Brown	N/A	N/A
7097588	12/2005	Watterson	N/A	N/A
D527776	12/2005	Willardson	N/A	N/A
7112168	12/2005	Dalebout et al.	N/A	N/A
7128693	12/2005	Brown	N/A	N/A
7166062	12/2006	Watterson	N/A	N/A
7166064	12/2006	Watterson	N/A	N/A
7169087	12/2006	Ercanbrack	N/A	N/A
7169093	12/2006	Simonson	N/A	N/A
7192388	12/2006	Dalebout	N/A	N/A
7250022	12/2006	Dalebout	N/A	N/A
7282016	12/2006	Simonson	N/A	N/A
7285075	12/2006	Cutler	N/A	N/A
7344481	12/2007	Watterson	N/A	N/A
7377882	12/2007	Watterson	N/A	N/A
7425188	12/2007	Ercanbrack	N/A	N/A
7429236	12/2007	Dalebout	N/A	N/A
7455622	12/2007	Watterson	N/A	N/A
7482050	12/2008	Olson	N/A	N/A
D588655	12/2008	Utykanski	N/A	N/A
7510509	12/2008	Hickman	N/A	N/A
7537546	12/2008	Watterson	N/A	N/A
7537549	12/2008	Nelson	N/A	N/A
7537552	12/2008	Dalebout	N/A	N/A
7540828	12/2008	Watterson	N/A	N/A
7549947	12/2008	Hickman	N/A	N/A
7556590	12/2008	Watterson et al.	N/A	N/A
7563203	12/2008	Dalebout	N/A	N/A
7575536	12/2008	Hickman	N/A	N/A
7601105	12/2008	Gipson, III	N/A	N/A
7604573	12/2008	Dalebout	N/A	N/A
D604373	12/2008	Dalebout	N/A	N/A
7618350	12/2008	Dalebout	N/A	N/A
7618357	12/2008	Dalebout	N/A	N/A

7625315	12/2008	Hickman	N/A	N/A
7625321	12/2008	Simonson	N/A	N/A
7628730	12/2008	Watterson	N/A	N/A
7628737	12/2008	Kowallis	N/A	N/A
7637847	12/2008	Hickman	N/A	N/A
7645212	12/2009	Ashby et al.	N/A	N/A
7645213	12/2009	Watterson	N/A	N/A
7658698	12/2009	Pacheco	N/A	N/A
7674205	12/2009	Dalebout	N/A	N/A
7713171	12/2009	Hickman	N/A	N/A
7713172	12/2009	Watterson	N/A	N/A
7713180	12/2009	Wickens	N/A	N/A
7717828	12/2009	Simonson	N/A	N/A
7736279	12/2009	Dalebout	N/A	N/A
7740563	12/2009	Dalebout	N/A	N/A
7749144	12/2009	Hammer	N/A	N/A
7766797	12/2009	Dalebout	N/A	N/A
7771329	12/2009	Dalebout	N/A	N/A
7775940	12/2009	Dalebout	N/A	N/A
7789800	12/2009	Watterson	N/A	N/A
7798946	12/2009	Dalebout	N/A	N/A
7815550	12/2009	Watterson	N/A	N/A
7857731	12/2009	Hickman	N/A	N/A
7862475	12/2010	Watterson	N/A	N/A
7862478	12/2010	Watterson	N/A	N/A
7862483	12/2010	Hendrickson	N/A	N/A
D635207	12/2010	Dalebout	N/A	N/A
7901330	12/2010	Dalebout	N/A	N/A
7909740	12/2010	Dalebout	N/A	N/A
7914420	12/2010	Daly	482/901	A63B 24/00
7980996	12/2010	Hickman	N/A	N/A
7981000	12/2010	Watterson	N/A	N/A
7985164	12/2010	Ashby	N/A	N/A
8029415	12/2010	Ashby et al.	N/A	N/A
8033960	12/2010	Dalebout	N/A	N/A
D650451	12/2010	Olson	N/A	N/A
D652877	12/2011	Dalebout	N/A	N/A
8152702	12/2011	Pacheco	N/A	N/A
D659775	12/2011	Olson	N/A	N/A
D659777	12/2011	Watterson	N/A	N/A
D660383	12/2011	Watterson	N/A	N/A
D664613	12/2011	Dalebout	N/A	N/A
8251874	12/2011	Ashby	N/A	N/A
8298123	12/2011	Hickman	N/A	N/A
8298125	12/2011	Colledge	N/A	N/A
D671177	12/2011	Sip	N/A	N/A
D671178	12/2011	Sip	N/A	N/A
D673626	12/2012	Olson	N/A	N/A
8690735	12/2013	Watterson	N/A	N/A
D707763	12/2013	Cutler	N/A	N/A

8740753	12/2013	Olson	N/A	N/A
8758201	12/2013	Ashby	N/A	N/A
8771153	12/2013	Dalebout	N/A	N/A
8784270	12/2013	Watterson	N/A	N/A
8808148	12/2013	Watterson	N/A	N/A
8814762	12/2013	Butler	N/A	N/A
D712493	12/2013	Ercanbrack	N/A	N/A
8840075	12/2013	Olson	N/A	N/A
8845493	12/2013	Watterson	N/A	N/A
8870726	12/2013	Watterson	N/A	N/A
8876668	12/2013	Hendrickson	N/A	N/A
8894549	12/2013	Colledge	N/A	N/A
8894555	12/2013	Olson	N/A	N/A
8911330	12/2013	Watterson	N/A	N/A
8920288	12/2013	Dalebout	N/A	N/A
8986165	12/2014	Ashby	N/A	N/A
8992364	12/2014	Law	N/A	N/A
8992387	12/2014	Watterson	N/A	N/A
D726476	12/2014	Ercanbrack	N/A	N/A
9028368	12/2014	Ashby	N/A	N/A
9028370	12/2014	Watterson	N/A	N/A
9039578	12/2014	Dalebout	N/A	N/A
D731011	12/2014	Buchanan	N/A	N/A
9072930	12/2014	Ashby	N/A	N/A
9119983	12/2014	Rhea	N/A	N/A
9123317	12/2014	Watterson	N/A	N/A
9126071	12/2014	Smith	N/A	N/A
9126072	12/2014	Watterson	N/A	N/A
9138615	12/2014	Olson	N/A	N/A
9142139	12/2014	Watterson	N/A	N/A
9144703	12/2014	Dalebout	N/A	N/A
9149683	12/2014	Watterson et al.	N/A	N/A
9186535	12/2014	Ercanbrack	N/A	N/A
9186549	12/2014	Watterson	N/A	N/A
9254409	12/2015	Dalebout	N/A	N/A
9254416	12/2015	Ashby	N/A	N/A
9278248	12/2015	Tyger	N/A	N/A
9278249	12/2015	Watterson	N/A	N/A
9278250	12/2015	Buchanan	N/A	N/A
9289648	12/2015	Watterson	N/A	N/A
9339691	12/2015	Brammer	N/A	N/A
9352185	12/2015	Hendrickson	N/A	N/A
9352186	12/2015	Watterson	N/A	N/A
9375605	12/2015	Tyger	N/A	N/A
9381394	12/2015	Mortensen	N/A	N/A
9387387	12/2015	Dalebout	N/A	N/A
9393453	12/2015	Watterson	N/A	N/A
9403047	12/2015	Olson	N/A	N/A
9403051	12/2015	Cutler	N/A	N/A
9421416	12/2015	Mortensen	N/A	N/A

9457219	12/2015	Smith	N/A	N/A
9457220	12/2015	Olson	N/A	N/A
9457222	12/2015	Dalebout	N/A	N/A
9460632	12/2015	Watterson	N/A	N/A
9463356	12/2015	Rhea	N/A	N/A
9468794	12/2015	Barton	N/A	N/A
9468798	12/2015	Dalebout	N/A	N/A
9480874	12/2015	Cutler	N/A	N/A
9492704	12/2015	Mortensen	N/A	N/A
9498668	12/2015	Smith	N/A	N/A
9517378	12/2015	Ashby	N/A	N/A
9521901	12/2015	Dalebout	N/A	N/A
9533187	12/2016	Dalebout	N/A	N/A
9539461	12/2016	Ercanbrack	N/A	N/A
9579544	12/2016	Watterson	N/A	N/A
9586086	12/2016	Dalebout	N/A	N/A
9586090	12/2016	Watterson	N/A	N/A
9604099	12/2016	Taylor	N/A	N/A
9616276	12/2016	Dalebout	N/A	N/A
9616278	12/2016	Olson	N/A	N/A
9623281	12/2016	Hendrickson	N/A	N/A
9636567	12/2016	Brammer	N/A	N/A
9675839	12/2016	Dalebout	N/A	N/A
9682307	12/2016	Dalebout	N/A	N/A
9694234	12/2016	Dalebout	N/A	N/A
9694242	12/2016	Ashby	N/A	N/A
9707443	12/2016	Warren	N/A	N/A
9737755	12/2016	Dalebout	N/A	N/A
9757605	12/2016	Olson	N/A	N/A
9764186	12/2016	Dalebout	N/A	N/A
9767785	12/2016	Ashby	N/A	N/A
9795822	12/2016	Smith	N/A	N/A
9808672	12/2016	Dalebout	N/A	N/A
9849326	12/2016	Smith	N/A	N/A
9878210	12/2017	Watterson	N/A	N/A
9889334	12/2017	Ashby	N/A	N/A
9889339	12/2017	Douglass	N/A	N/A
9937376	12/2017	McInelly	N/A	N/A
9937377	12/2017	McInelly	N/A	N/A
9937378	12/2017	Dalebout	N/A	N/A
9937379	12/2017	Mortensen	N/A	N/A
9943719	12/2017	Smith	N/A	N/A
9943722	12/2017	Dalebout	N/A	N/A
9948037	12/2017	Ashby	N/A	N/A
9968816	12/2017	Olson	N/A	N/A
9968821	12/2017	Finlayson	N/A	N/A
9968823	12/2017	Cutler	N/A	N/A
10010755	12/2017	Watterson	N/A	N/A
10010756	12/2017	Watterson	N/A	N/A
10029145	12/2017	Douglass	N/A	N/A

D826350	12/2017	Hochstrasser	N/A	N/A
10046196	12/2017	Ercanbrack	N/A	N/A
D827733	12/2017	Hochstrasser	N/A	N/A
10065064	12/2017	Smith	N/A	N/A
10071285	12/2017	Smith	N/A	N/A
10085586	12/2017	Smith	N/A	N/A
10086254	12/2017	Watterson	N/A	N/A
10136842	12/2017	Ashby	N/A	N/A
10186161	12/2018	Watterson	N/A	N/A
10188890	12/2018	Olson	N/A	N/A
10207143	12/2018	Dalebout	N/A	N/A
10207145	12/2018	Tyger	N/A	N/A
10207147	12/2018	Ercanbrack	N/A	N/A
10207148	12/2018	Powell	N/A	N/A
10212994	12/2018	Watterson	N/A	N/A
10220259	12/2018	Brammer	N/A	N/A
10226396	12/2018	Ashby	N/A	N/A
10226664	12/2018	Dalebout	N/A	N/A
10252109	12/2018	Watterson	N/A	N/A
10258828	12/2018	Dalebout	N/A	N/A
10272317	12/2018	Watterson	N/A	N/A
10279212	12/2018	Dalebout	N/A	N/A
10293211	12/2018	Watterson	N/A	N/A
D852292	12/2018	Cutler	N/A	N/A
10343017	12/2018	Jackson	N/A	N/A
10376736	12/2018	Powell	N/A	N/A
10388183	12/2018	Watterson	N/A	N/A
10391361	12/2018	Watterson	N/A	N/A
D864320	12/2018	Weston	N/A	N/A
D864321	12/2018	Weston	N/A	N/A
10426989	12/2018	Dalebout	N/A	N/A
10433612	12/2018	Ashby	N/A	N/A
10441840	12/2018	Dalebout	N/A	N/A
10441844	12/2018	Powell	N/A	N/A
10449416	12/2018	Dalebout	N/A	N/A
10471299	12/2018	Powell	N/A	N/A
D868909	12/2018	Cutler	N/A	N/A
10492519	12/2018	Capell	N/A	N/A
10493349	12/2018	Watterson	N/A	N/A
10500473	12/2018	Watterson	N/A	N/A
10543395	12/2019	Powell et al.	N/A	N/A
10561877	12/2019	Workman	N/A	N/A
10561893	12/2019	Chatterton	N/A	N/A
10561894	12/2019	Dalebout	N/A	N/A
10569121	12/2019	Watterson	N/A	N/A
10569123	12/2019	Hochstrasser	N/A	N/A
10625114	12/2019	Ercanbrack	N/A	N/A
10625137	12/2019	Dalebout	N/A	N/A
10661114	12/2019	Watterson et al.	N/A	N/A
10668320	12/2019	Watterson	N/A	N/A

10671705	12/2019	Capell et al.	N/A	N/A
10688346	12/2019	Brammer	N/A	N/A
10702736	12/2019	Weston et al.	N/A	N/A
10709925	12/2019	Dalebout et al.	N/A	N/A
10726730	12/2019	Watterson	N/A	N/A
10729965	12/2019	Powell	N/A	N/A
10758767	12/2019	Olson	N/A	N/A
10786706	12/2019	Smith	N/A	N/A
10864407	12/2019	Watterson	N/A	N/A
10918905	12/2020	Powell et al.	N/A	N/A
10932517	12/2020	Ashby et al.	N/A	N/A
10940360	12/2020	Dalebout et al.	N/A	N/A
10953268	12/2020	Dalebout et al.	N/A	N/A
10953305	12/2020	Dalebout et al.	N/A	N/A
10967214	12/2020	Olson	N/A	N/A
10994173	12/2020	Watterson	N/A	N/A
11000730	12/2020	Dalebout et al.	N/A	N/A
11013960	12/2020	Watterson	N/A	N/A
11033777	12/2020	Watterson et al.	N/A	N/A
11058913	12/2020	Dalebout et al.	N/A	N/A
11058914	12/2020	Powell	N/A	N/A
11187285	12/2020	Wrobel	N/A	N/A
11517781	12/2021	Whalen	N/A	A61G 10/023
11534654	12/2021	Silcock	N/A	A63B 71/0622
2004/0002406	12/2003	Lopez-Santillana	482/54	A63B 22/0235
2006/0199704	12/2005	Lo	482/54	A63B 22/0023
2012/0088634	12/2011	Heidecke	482/92	A63B 22/0005
2012/0178592	12/2011	Chieh et al.	N/A	N/A
2013/0334001	12/2012	Albrecht et al.	N/A	N/A
2014/0221167	12/2013	Wu	482/54	A63B 22/0235
2014/0251709	12/2013	Ruffieux	N/A	N/A
2016/0287930	12/2015	Moser	N/A	A63B 24/0087
2017/0124912	12/2016	Ashby et al.	N/A	N/A
2017/0193578	12/2016	Watterson	N/A	N/A
2017/0266489	12/2016	Douglass et al.	N/A	N/A
2017/0270820	12/2016	Ashby et al.	N/A	N/A
2018/0043207	12/2017	Moser	N/A	A63B 71/0622
2018/0085630	12/2017	Capell et al.	N/A	N/A
2018/0099116	12/2017	Ashby	N/A	N/A
2018/0099180	12/2017	Wilkinson	N/A	N/A
2018/0111034	12/2017	Watterson	N/A	N/A
2019/0058370	12/2018	Tinney	N/A	N/A
2019/0223612	12/2018	Watterson et al.	N/A	N/A
2019/0269971	12/2018	Capell et al.	N/A	N/A
2019/0376585	12/2018	Buchanan	N/A	N/A
2020/0009417	12/2019	Dalebout	N/A	N/A
2020/0222751	12/2019	Dalebout et al.	N/A	N/A
2020/0238130	12/2019	Silcock	N/A	A63B 71/0622
2020/0254295	12/2019	Watterson	N/A	N/A
2020/0254309	12/2019	Watterson	N/A	N/A

2020/0254311	12/2019	Watterson et al.	N/A	N/A
2020/0338389	12/2019	Dalebout et al.	N/A	N/A
2020/0368575	12/2019	Hays et al.	N/A	N/A
2020/0391069	12/2019	Olson et al.	N/A	N/A
2021/0046351	12/2020	Ercanbrack et al.	N/A	N/A
2021/0046352	12/2020	Lopez Babodilla	N/A	A63B 22/0023
2021/0046353	12/2020	Dalebout et al.	N/A	N/A
2021/0106899	12/2020	Willardson et al.	N/A	N/A
2021/0110910	12/2020	Ostler et al.	N/A	N/A
2021/0138332	12/2020	Dalebout et al.	N/A	N/A
2021/0146191	12/2020	Dalebout et al.	N/A	N/A
2021/0146221	12/2020	Dalebout et al.	N/A	N/A
2021/0153463	12/2020	Yoo	N/A	A01K 29/005
2021/0153464	12/2020	Yoo	N/A	A63B 22/025
2021/0153465	12/2020	Yoo	N/A	A61L 9/122
2021/0153466	12/2020	Yoo	N/A	A63B 24/0087
2021/0153467	12/2020	Yoo	N/A	A01K 5/02
2021/0153468	12/2020	Yoo	N/A	A61L 2/10
2021/0153469	12/2020	Yoo	N/A	A63B 21/4035
2021/0153470	12/2020	Yoo	N/A	A63B 22/02
2021/0153471	12/2020	Yoo	N/A	A63B 22/0292
2021/0153472	12/2020	Yoo	N/A	A63B 24/0087
2021/0153473	12/2020	Yoo	N/A	A61M 21/02
2021/0153474	12/2020	Yoo	N/A	A63B 22/025
2021/0154524	12/2020	Yoo	N/A	A63B 22/0023
2021/0154525	12/2020	Yoo	N/A	A01K 15/027
2021/0154526	12/2020	Yoo	N/A	A01K 15/027
2021/0161245	12/2020	Ashby et al.	N/A	N/A
2021/0213331	12/2020	Watterson	N/A	N/A
2021/0213332	12/2020	Watterson et al.	N/A	N/A
2021/0220698	12/2020	Dalebout et al.	N/A	N/A
2021/0252334	12/2020	Lu	N/A	A63B 21/00069
2021/0268336	12/2020	Watterson et al.	N/A	N/A
2021/0283465	12/2020	Arceta	N/A	A63B 71/0622
2021/0291013	12/2020	Nascimento	N/A	N/A
2021/0299518	12/2020	Brammer et al.	N/A	N/A
2021/0299542	12/2020	Brammer et al.	N/A	N/A
2021/0339079	12/2020	Dalebout et al.	N/A	N/A
2022/0023702	12/2021	Watterson	N/A	N/A
2022/0062685	12/2021	Ashby et al.	N/A	N/A
2022/0074455	12/2021	Wrobel	N/A	N/A
2023/0191189	12/2022	Taylor	482/54	A63B 22/02

OTHER PUBLICATIONS

U.S. Appl. No. 29/702,127, filed Sep. 16, 2019, Cutler et al. cited by applicant
U.S. Appl. No. 63/079,697, filed Sep. 7, 2020, Willardson et al. cited by applicant
U.S. Appl. No. 17/066,485, filed Oct. 9, 2020, Weston et al. cited by applicant
U.S. Appl. No. 63/086,793, filed Oct. 20, 2020, Ashby. cited by applicant
U.S. Appl. No. 63/134,036, filed Jan. 5, 2021, Ercanbrack et al. cited by applicant
U.S. Appl. No. 63/150,066, filed Feb. 16, 2021, Smith. cited by applicant

U.S. Appl. No. 63/156,801, filed Mar. 4, 2021, Watterson. cited by applicant
U.S. Appl. No. 63/165,498, filed Mar. 24, 2021, Archer. cited by applicant
U.S. Appl. No. 63/200,903, filed Apr. 2, 2021, Watterson et al. cited by applicant
U.S. Appl. No. 63/179,094, filed Apr. 23, 2021, Watterson et al. cited by applicant
U.S. Appl. No. 63/180,521, filed Apr. 27, 2021, Watterson et al. cited by applicant
U.S. Appl. No. 63/187,348, filed May 11, 2021, Dalebout et al. cited by applicant
U.S. Appl. No. 63/188,431, filed May 13, 2021, Plummer. cited by applicant
U.S. Appl. No. 63/211,870, filed Jun. 17, 2021, Watterson et al. cited by applicant
U.S. Appl. No. 63/216,313, filed Jun. 29, 2021, Watterson et al. cited by applicant
U.S. Appl. No. 63/229,794, filed Aug. 12, 2021, Brammer. cited by applicant
U.S. Appl. No. 63/235,002, filed Aug. 19, 2021, Smith. cited by applicant
U.S. Appl. No. 17/462,687, filed Aug. 31, 2021, Ashby et al. cited by applicant
U.S. Appl. No. 63/073,081, filed Sep. 1, 2021, Ashby et al. cited by applicant
U.S. Appl. No. 17/476,899, filed Sep. 16, 2021, Willardson et al. cited by applicant
U.S. Appl. No. 17/492,104, filed Oct. 1, 2021, Ashby. cited by applicant
U.S. Appl. No. 63/254,470, filed Oct. 11, 2021, Powell. cited by applicant
U.S. Appl. No. 63/278,714, filed Nov. 12, 2021, Taylor. cited by applicant
U.S. Appl. No. 63/289,997, filed Dec. 15, 2021, Taylor et al. cited by applicant
U.S. Appl. No. 63/290,455, filed Dec. 16, 2021, Taylor et al. cited by applicant
U.S. Appl. No. 63/290,557, filed Dec. 16, 2021, Ashby. cited by applicant
U.S. Appl. No. 17/568,882, filed Jan. 5, 2022, Ercanbrack et al. cited by applicant
U.S. Appl. No. 63/298,170, filed Jan. 10, 2022, Ercanbrack et al. cited by applicant
U.S. Appl. No. 63,299,357, filed Jan. 13, 2022, Toles et al. cited by applicant
U.S. Appl. No. 17/589,027, filed Jan. 31, 2022, Dalebout et al. cited by applicant
U.S. Appl. No. 17/589,075, filed Jan. 31, 2022, Ashby. cited by applicant

Primary Examiner: Urbiel Goldner; Gary D

Attorney, Agent or Firm: Holland & Hart LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims benefit and priority to U.S. Provisional Patent Application No. 63/321,303, filed on Mar. 18, 2023, which is incorporated herein in its entirety by reference.

BACKGROUND

Background and Relevant Art

(1) Exercise devices simulate many of the aspects of outdoor exercises using a stationary device, which is conventionally used indoors as an alternative to the outdoor exercise. Exercise devices provide a controlled environment with improved safety and less distractions than the outdoor activities simulated by the exercise devices, such as bicycling, running, rowing, or hiking. Exercise devices allow the user to focus on efficiency, comfort, and convenience without the concerns of external factors.

(2) In simulating the outdoor activity, an exercise device may present video and/or audio information of the outdoor activity, such as running on a beach or riding a bicycle on a dirt road, to the user. A disconnect exists, however, between what the user sees and hears in the presented video and audio information and what the user feels through their interaction with the exercise device.

BRIEF SUMMARY

(3) In some embodiments, a haptic simulation exercise device includes a frame, a base supporting the frame, and an actuator. The actuator is configured to move the frame relative to the base to provide haptic simulation during a workout routine.

(4) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter.

(5) Additional features and advantages will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the teachings herein. Features and advantages of the disclosure may be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. Features of the present disclosure will become more fully apparent from the following description and appended claims or may be learned by the practice of the disclosure as set forth hereinafter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to describe the manner in which the above-recited and other features of the disclosure can be obtained, a more particular description will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. For better understanding, the like elements have been designated by like reference numbers throughout the various accompanying figures. While some of the drawings may be schematic or exaggerated representations of concepts, at least some of the drawings may be drawn to scale. Understanding that the drawings depict some example embodiments, the embodiments will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

(2) FIG. 1 is a perspective view of an exercise bicycle including haptic simulation, according to at least one embodiment of the present disclosure;

(3) FIG. 2 is a perspective view of a treadmill including haptic simulation, according to at least one embodiment of the present disclosure;

(4) FIG. 3 is a side view of an exercise device with an incline motor and actuator in series, according to at least one embodiment of the present disclosure;

(5) FIG. 4 is a side view of an exercise bicycle with an incline motor and actuator in series, according to at least one embodiment of the present disclosure;

(6) FIG. 5 is a system diagram of a system for controlling haptic simulation in an exercise device, according to at least one embodiment of the present disclosure;

(7) FIG. 6 is a flowchart illustrating a method of providing haptic simulation in an exercise device, according to at least one embodiment of the present disclosure;

(8) FIG. 7 is a flowchart illustrating another method of providing haptic simulation in an exercise device, according to at least one embodiment of the present disclosure; and

(9) FIG. 8 is an example of a video that is analyzed to provide haptic simulation in an exercise device, according to at least one embodiment of the present disclosure.

DETAILED DESCRIPTION

(10) The present disclosure relates generally to systems and methods for haptic simulations in an exercise device. More particularly, the exercise devices of the present disclosure include a frame that is movable relative to a base of the exercise device to increase the user's immersion in a simulated environment.

(11) An exercise device is any mechanical device that is used to provide or replicate a physical activity in a localized space. Exercise devices can include a treadmill, cable or spring resistance machine, weight resistance machine, dumbbells, elliptical machine, stepper machine, stationary

bicycle, rowing machine, or any other machine or exercise device. In an example, it should be understood that while a road bicycle may not be an exercise device, as used herein, a bicycle positioned on a stationary trainer device should be considered an exercise device as the bicycle remains in one location while the user rides the bicycle on the stationary trainer device.

(12) In some embodiments, an exercise device includes or is in communication with a display. The display allows a user of the exercise device to view video information as the user engages in exercises. In some embodiments, the display presents video information that simulates a route, path, track, road, trail, or other environment associated with the activity replicated by the exercise device. For example, a display integrated in or in communication with a treadmill may present video information simulating traveling down a road in Oahu, Hawaii at a speed approximately equal to the speed at which the tread belt is moving on the treadmill. The resulting experience for the user is a simulated run down the road presented on the display. Similarly, in another example, a display integrated in or in communication with a stationary bicycle may present video information simulating traveling down a mountain trail in Sedona, Arizona at a speed approximately equal to the speed at which the user moves the pedals of the stationary bicycle. The resulting experience for the user is a simulated mountain bike ride down the trail presented on the display. In yet another example, a display integrated in or in communication with a rowing machine may present video information simulating rowing down the Charles River in Cambridge, Massachusetts at a speed approximately equal to the speed at which the user pulls the handle of the rowing machine. The resulting experience for the user is a simulated row down the river presented on the display.

(13) The exercise device simulates the experience based on simulation data that includes video information as described above. In some embodiments, the simulation data includes audio information. For example, the exercise device may offer one or more simulations such as simulate racing in a stage of a bike race or running away from a dinosaur. In such examples, audio information can increase the immersion of a bike race simulation by simulating cheering fans or sound of another racer approaching from behind on a climb. In another example, audio information can increase the immersion of a dinosaur chase by simulating the roar of the dinosaur behind the runner.

(14) In some embodiments, the simulation data includes haptic information. In the previous examples, the exercise device offers simulations that simulate racing in a stage of a bike race or running away from a dinosaur. In such examples, haptic information can increase the immersion of a bike race simulation by rapidly changing inclination of a frame of the exercise bicycle relative to a base of the exercise bicycle simulate the cobblestone road surface of the Paris-Roubaix bicycle race. In another example, haptic information can increase the immersion of the dinosaur chase by rapidly changing the inclination of the tread belt of the treadmill to simulate the ground shaking with the dinosaur footsteps.

(15) The haptic information may be predetermined and stored on a hardware storage device with the video and/or audio information of the simulation data. In some embodiments, the haptic information may be calculated by the exercise device, a client device, or a workout server based on the video information. For example, a recorded video of a mountain bike ride from a rider's viewpoint (such as video information recorded by a GoPro® or other action camera) may include the bicycle handlebars within the frame of the video information. In some embodiments, the system detects the location of the handlebars in the video information and determines the movement of the handlebars relative to the trail surface. The movement of the handlebars may be presented to the exercise device as haptic information and allow the exercise device to simulate the movement of the handlebars in the video information by moving the handlebars of the stationary bicycle relative to a frame of the stationary bicycle.

(16) FIG. 1 is a perspective view of an exercise device **100**, according to some embodiments of the present disclosure. The embodiment of an exercise device **100** in FIG. 1 is a stationary bicycle with a display **102** integrated into the exercise device **100**. In some embodiments, the display **102** may

be independent from, but in data communication with, the exercise device **100** and receive video information from a computing device **104** of the exercise device **100**. The computing device **104** includes a processor and a hardware storage device with instructions stored thereon that, when executed by the processor, cause the exercise device **100** to perform any of the methods described herein.

(17) In some embodiments, the hardware storage device is any non-transient computer readable medium that may store instructions thereon. The hardware storage device may be any type of solid-state memory; volatile memory, such as static random access memory (SRAM) or dynamic random access memory (DRAM); or non-volatile memory, such as read-only memory (ROM) including programmable ROM (PROM), erasable PROM (ERPOM) or EEPROM; magnetic storage media, such as magnetic tape; platen-based storage device, such as hard disk drives; optical media, such as compact discs (CD), digital video discs (DVD), Blu-ray Discs, or other optical media; removable media such as USB drives; non-removable media such as internal SATA or non-volatile memory express (NVMe) style NAND flash memory, or any other non-transient storage media. In some embodiments, the hardware storage device is local to and/or integrated with the computing device. In some embodiments, the hardware storage device is accessed by the computing device through a network connection.

(18) The exercise device **100** includes one or more contact points supported by a frame **106** with which the user touches, contacts, or engages with the exercise device **100** during the exercise. It should be understood that while the user may touch or contact one or more controls of the exercise device **100**, such as a touchscreen of the display **102** or other input devices to provide inputs to the computing device **104** (e.g., volume controls, resistance levels, power buttons), the controls or input devices are not considered the contact points of the exercise device **100** for the purposes of the exercise performed on the exercise device **100**. In the embodiment illustrated in FIG. 1, the exercise device **100** is a stationary bicycle and the intended exercise of the stationary bicycle is cycling, therefor, the components of the stationary bicycle used for cycling are considered to be the contact points of the exercise device **100**. The contact points of the exercise device **100** include the handlebars **108**, the saddle **110**, and the pedals **112**.

(19) In some embodiments, the frame **106** moves relative to a base **114** at a pivot **116**. By moving the frame **106** relative to the base **114**, the exercise device **100** can provide haptic feedback and/or simulations to the user by moving one or more contact points of the exercise device **100**. In some embodiments, the contact points all move together to simulate, for example, a bicycle moving over a surface. In other embodiments, at least one contact point moves relative to another contact point, such as moving handlebars **108** relative to a seat or saddle **110**. In some embodiments, the rotation of the frame **106** around the pivot **116** can simulate cobblestones, washboard roads, mountain bike trails, etc. on an exercise bicycle. In other embodiments, the rotation of the frame **106** can simulate other real-world experiences for other exercise devices, such as rough water on a stationary rower exercise device or rocky running trails on a treadmill exercise device.

(20) In some embodiments, the frame **106** is movable relative to the base **114** by one or more incline motors **118**. The incline motor **118** applies a torque around the pivot **116** to rotate the frame **106** relative to the base **114**. In some embodiments, the incline motor **118** includes gears, worm gears, pinions, etc. to mechanically apply the torque around the pivot **116**. In some embodiments, the incline motor **118** includes a piston-and-cylinder with a pressurized fluid therein to apply pneumatically or hydraulically apply the torque around the pivot **116**. In some embodiments, the incline motor **118** includes an electromagnetic motor to move the frame **106** relative to the base **114**.

(21) The incline motor(s) **118** is in data communication with the computing device **104** to move the frame **106** relative to the base **114** in response to simulation data. In some embodiments, the computing device **104** has stored thereon instruction that, when executed by the computing device **104**, cause the exercise device **100** to perform any of the methods described herein. In some

embodiments, the computing device **104** communicates with the incline motor **118** to move the frame **106** relative to the base by moving at least a portion of the incline motor **118** at a rate of 5 millimeters per second. In contrast to conventional incline motors, an incline motor **118**, according to the present, disclosure is configured to move the frame **106** rapidly and for a period of time at least 5 seconds in duration. For example, a conventional incline motor moves the frame **106** relative to the base **114** slowly and smoothly to provide gradual changes in inclination of the running surface (e.g., treadmill) or inclination of a bicycle frame to replicate riding a hill. However, there is no mechanism by which a conventional incline motor produces rapid, sustained movement to provide haptic simulations to a user.

(22) FIG. 2 is a perspective view of another embodiment of an exercise device **200** configured to provide haptic simulations for a user. In some embodiments, a treadmill exercise device **200** has a display **202** and computing device **204** in communication therewith to provide exercise routines and video information to a user. The exercise device **200** has a tread belt **220** supported by a frame **206** that is movable relative to a base **214** of the exercise device **200**. As described herein, the computing device **204** may move the frame **206**, and, hence, contact points such as the tread belt **220**, relative to the base **214** to produce a haptic simulation for the user. In some embodiments, the frame **206** is movable relative to the base **214** around a pivot **216** by an incline motor. In some embodiments, the incline motor is used to provide haptic simulation through rapid and/or sustained movement of the frame **206**. In other embodiments, the incline motor provides slow and/or smooth changes in inclination of the frame **206** relative to the base **214** to simulate the overall angle of a running surface, while an actuator **222** is additionally provided to move the frame **206** relative to the base **214**.

(23) In some embodiments, the actuator **222** is connected to the incline motor, as will be described in greater detail herein, to move the frame **206** relative to the incline motor (or move the frame **206** and incline motor relative to the base **214**). For example, the incline motor and actuator **222** may be connected in sequence to allow the incline motor to provide macro changes in the position of the frame **206** relative to the base **214**, while the actuator **222** provides smaller, but more rapid, changes in the position of the frame **206** relative to the base **214**.

(24) In some embodiments, the exercise device **200** includes a single actuator **222**. In other embodiments, the exercise device **200** includes a plurality of actuators **222**. Each of the actuators **222** can include one or more individual actuatable devices, such as including a pair of actuatable devices to allow movement of the frame **206** in one or more directions or axes relative to the base **214**. In some embodiments, the actuators **222** are electromagnetic actuators that use permanent magnets, electromagnets, or combinations thereof to apply magnetic force to move the frame **206** in one or more directions or axes relative to the base **214**. In some embodiments, the actuators **222** are fluid piston actuators that use compressible or incompressible fluid in a cylinder to apply a force to a piston that is slidable relative to the cylinder. The fluid may be a gas (e.g., pneumatic piston and cylinder) or a liquid (e.g., hydraulic piston and cylinder) that moves piston relative to the cylinder to move the frame **206** in one or more directions or axes relative to the base **214**. In some embodiments, the actuators **222** are mechanical actuators that use gears, springs, elastic or biasing elements, or combinations thereof to apply a compression and/or tension force to move the frame **206** in one or more directions or axes relative to the base **214**.

(25) In different embodiments, the actuators **222** move the contact points in different path directions and/or shapes. In some embodiments, an actuator **222** moves the frame **206** around the pivot **216** relative to the base **214** to move at least a portion of the tread belt **220** in an arcuate path. In other embodiments, the actuator **222** can move the frame **206** in a linear path relative to the base **214**. For example, one or more actuators **222** may move the frame **206** vertically. In another example, one or more actuators **222** may move the frame **206** horizontally.

(26) The actuators **222** move in response to the simulation data provided by the computing device **204**. The simulation data includes haptic information that instructs one or more actuators **222** to

move a contact point coordinated with audio and/or video information of the simulation data that is presented to the user on the display **202** or other audiovisual devices (e.g., speakers or headphones). The haptic information may include instructions for one or more actuators **222** to move the frame **206** a nominal or relative (to a total range of motion) amount, at a particular speed, for a particular duration, or combination thereof.

(27) For example, the haptic information may instruct the actuator **222** to move the tread belt **220** in coordination with a tree stump presented on the display **202**. The haptic information may instruct the actuator **222** at a 3:26 timestamp to translate the tread belt **220** upward by 35 millimeters (mm) at a rate of 100 millimeters per second (mm/s) and return the tread belt **220** to the original position at a rate of 50 mm/s. The higher rate of upward travel and the lower rate of downward travel may replicate an asymmetry of the tree stump in the video information.

(28) In other examples, the entire surface of the tread belt **220** may displace upward before returning to the original position to simulate an explosion in the video information presented on the display **202**. In at least one example, the exercise device **200** may simulate an action scene and prompt the user of the exercise device **200** to run to safety by evading objects and/or clearing obstacles in the presented video and/or audio information. The action scene may simulate escaping a boobytrapped temple where the user must run along uneven pathways, crumbling walls, and escape a large boulder following the user. The actuator(s) **222** may move the frame **206** around the pivot **216** to simulate the debris from the walls on the running surface and simulate the shaking of the ground as the boulder rolls behind the user.

(29) FIG. 3 is a side view of an embodiment of an actuator **322** and incline motor **318** connected in sequence to provide a cumulative displacement of a frame **306** relative to a base **314**.

(30) The range of motion of the actuator **322** and a range of motion of the connection point of the frame **306** movable by the actuator **322** may be different. For example, the actuator may be connected to the frame (e.g., the actuator **322** that moves the frame **306**) by being coupled to a linkage or lever that moves the frame. In other examples, the range of motion of the actuator and a range of motion of the frame movable by the actuator may be equal, as the actuator and the frame are directly coupled to one another.

(31) In some embodiments, the incline motor **318** has a range of motion that is greater than the actuator **322**. In some embodiments, the actuator **322** moves the frame **306** relative to the base **314** faster than the incline motor **318**.

(32) In some embodiments, the range of motion of the frame is in a range having an upper value, a lower value, or upper and lower values including any of 5 mm, 10 mm, 15 mm, 20 mm, 25 mm, 30 mm, 35 mm, 40 mm, 45 mm, 50 mm, 55 mm, 60 mm, 65 mm, 70 mm, 75 mm, 80 mm, 85 mm, 90 mm, 95 mm, 100 mm, or any values therebetween. In some examples, the range of motion of the connection point is greater than 5 mm. In other examples, the range of motion of the connection point is less than 100 mm. In yet other examples, the range of motion of the connection point is between 5 mm and 100 mm. In yet other examples, the range of motion of the connection point is between 10 mm and 80 mm. In yet other examples, the range of motion of the connection point is about 50 mm.

(33) In some embodiments, the maximum rate of motion of the connection point of the frame is in a range having an upper value, a lower value, or upper and lower values including any of 25 mm/s, 50 mm/s, 100 mm/s, 150 mm/s, 200 mm/s, 250 mm/s, 300 mm/s, 350 mm/s, 400 mm/s, 450 mm/s, 500 mm/s, 550 mm/s, 600 mm/s, 650 mm/s, 700 mm/s, 750 mm/s, 800 mm/s, 850 mm/s, 900 mm/s, 950 mm/s, 1000 mm/s, or any values therebetween. In some examples, the maximum rate of motion of the connection point is greater than 25 mm/s. In other examples, the maximum rate of motion of the connection point is less than 1000 mm/s. In yet other examples, the maximum rate of motion of the connection point is between 25 mm/s and 1000 mm/s. In yet other examples, the maximum rate of motion of the connection point is between 100 mm/s and 750 mm/s. In yet other examples, the maximum rate of motion of the connection point is greater than 500 mm/s.

(34) In some embodiments, the actuator **322** moves the frame **306** relative to the base **314** faster than the incline motor **318**, and the incline motor **318** has a larger range of motion than the actuator **322**. As described herein, in some embodiments, the actuator **322** includes a magnetic actuator, such as a linear magnetic actuator or rotational magnetic actuator. In some embodiments, the actuator **322** includes a piston-and-cylinder actuator, such as a hydraulic or pneumatic piston-and-cylinder actuator. In some embodiments, the actuator **322** includes a mechanical actuator, such as a rack and pinion actuator.

(35) In at least one embodiment, the incline motor has a heat sink that allows the incline motor **318** to move the frame relative to the base **314** faster or for longer durations than a conventional heat sink. In some embodiments, the heat sink is an active heat sink with active cooling, such as a fan, liquid cooling, a thermoelectric cooler (e.g., a Peltier-style cooler), or other active cooling mechanisms. In some embodiments, the heat sink is a passive heat sink, such as cooling fins, pins, rods, heat spreaders, vapor chambers, heat pipes, or other heat sinks that increase surface area and passively exhaust heat to the ambient atmosphere.

(36) In some embodiments, the incline motor heat sink is configured to allow the incline motor **318** to operate at least at a 50% duty cycle. In some embodiments, the incline motor heat sink is configured to allow the incline motor **318** to operate at least at a 90% duty cycle. In some embodiments, the incline motor heat sink is configured to allow the incline motor **318** to operate at a 100% duty cycle.

(37) In some embodiments, the incline motor heat sink is configured to dissipate at least 500 Watts per minute (W/min). In some embodiments, the incline motor heat sink is configured to dissipate at least 750 Watts per minute (W/min). In some embodiments, the incline motor heat sink is configured to dissipate at least 1000 Watts per minute (W/min).

(38) FIG. 4 is a side view of another embodiment of an exercise device **400** with haptic simulation. The exercise device **400** includes an incline motor **418**, and, optionally, an actuator **422**, configured to move a frame **406** of the exercise device **400** relative to a base **414**. The incline motor **418** and/or actuator **422** may move the frame **406** according to haptic information provided by the computing device **404**. In some embodiments, the frame **406** is movable (e.g., tiltable) relative to a base **414** that contacts the ground. In some embodiments, the video information or workout routine includes global positioning satellite (GPS) location information or other location information. The location information may be compared to elevation or profile maps to determine an inclination or declination of the road or trail to be simulated by the tilt of the frame **406**. The frame **406** may connect to the base **414** at a rotational pivot **416** that allows the frame **406** supporting the contact points to move relative to the ground. In some examples, an incline motor **418** provides macro-movements of the frame **406** around the pivot **416** to allow the exercise device **400** to simulate the angle of climbing up a road, while the incline motor **418** and actuator **422** provides smaller movements for haptic simulation to simulate the surface condition of the road. The computing device **404** may be in data communication with the actuator(s) **422** and incline motor **418** to tilt the frame **406** to provide a more immersive simulation.

(39) While the movable frame **406** relative to the base **414** is described herein in relation to an exercise bicycle, it should be understood that a tiltable or movable frame with haptic simulation, where the frame is movable relative to a base, is applicable to other types of exercise devices, such as treadmills, rowing machines, and other devices.

(40) An exercise device, according to the present disclosure, may include a plurality of electronic components in data communication. FIG. 5 is a schematic representation of an electronic system **524** of any exercise device described herein. The electronic system **524** includes a processor **526** and a hardware storage device **528**. In some embodiments, the hardware storage device **528** is any non-transient computer readable medium that may store instructions thereon. The hardware storage device **528** may be any type of solid-state memory; volatile memory, such as static random access memory (SRAM) or dynamic random access memory (DRAM); or non-volatile memory, such as

read-only memory (ROM) including programmable ROM (PROM), erasable PROM (ERPOM) or EEPROM; magnetic storage media, such as magnetic tape; platen-based storage device, such as hard disk drives; optical media, such as compact discs (CD), digital video discs (DVD), Blu-ray Discs, or other optical media; removable media such as USB drives; non-removable media such as internal SATA or non-volatile memory express (NVMe) style NAND flash memory, or any other non-transient storage media. In some embodiments, the hardware storage device **528** is local to and/or integrated with the processor **526**. In some embodiments, the hardware storage device **528** is accessed by the processor **526** through a network connection.

(41) The processor **526** is further in communication with a display controller **530**. The processor **526** receives simulation data from the hardware storage device **528**. In some embodiments, the simulation data includes video information and haptic information. The processor **526** transmits video information to the display controller **530** and instructions based on the haptic information to the incline motor **518** and/or the actuator **522**. The display controller **530** communicates with the display **502** to present the video information to a user, while the incline motor **518** and/or the actuator **522** moves the frame of the exercise device relative to the base to provide haptic simulation to the user. The processor **526** may coordinate the presentation of the video information and haptic information to the user such that the user perceives the exercise device moving in coordination with the displayed video. In some embodiments, the processor **526** is further in communication with the one or more sensors and/or cameras to monitor the position and/or movement of the user. The processor **526** may transmit instructions to one or more actuators of a plurality of actuators based on the measurements from the sensors and/or cameras.

(42) FIG. **6** is a flowchart illustrating a method **632** of providing haptic simulation in an exercise device, according to some embodiments of the present disclosure. The method **632** includes obtaining simulation data for a workout routine performed on an exercise device at **634**. In some embodiments, the simulation data is obtained from local hardware storage device. In some embodiments, the simulation data is obtained from a remote hardware storage device, such as by downloading or streaming the simulation data from a remote server or datacenter. A workout routine is a predetermined set of instructions that may be provided to a user. Following the workout routine can guide, entertain, or encourage the user through one or more exercises to produce workout information. The workout routine may include haptic information, video information, audio information, text information, still images, or combinations thereof to communicate the workout routine to the user.

(43) The method **632** further includes displaying video information of the simulation data on a display (such as display **102** described in relation to FIG. **1**) at **636**. In some embodiments, the method **632** further includes playing audio information of the simulation data at **636**. In some embodiments, the simulation data includes both audio information and video information. The audio and/or video information provides visual and/or auditory immersion to which the haptic simulation(s) add further immersion.

(44) The haptic information of the simulation data is used in actuating an incline motor (and, optionally, an actuator) of the exercise device at **638**, and the method **632** includes moving a frame of the exercise device relative to a base of the exercise device with incline motor (and, optionally, actuator) at **640**. In some embodiments, the frame is further movable relative to the base to change an inclination or declination of the exercise device.

(45) While the method **632** includes actuating an actuator of the exercise device based on the simulation data, in some embodiments, the simulation data does not include haptic information, and the processor may calculate haptic information from the simulation data as described in relation to FIG. **7**.

(46) FIG. **7** is a flowchart illustrating another embodiment of a method **732** of providing haptic simulation in an exercise device. The method **732** includes obtaining simulation data for a workout routine performed on an exercise device at **734**, similar to or the same as described in relation to

FIG. 6. In some embodiments, the simulation data is obtained from local hardware storage device. In some embodiments, the simulation data is obtained from a remote hardware storage device, such as by downloading or streaming the simulation data from a remote server or datacenter.

(47) The method 732 may further include detecting a simulated object in the simulation video or video information at 742 and determining a movement of the simulated object in simulation video or video information at 744. In some embodiments, the simulated object is an object in the simulation video or video information that is analogous to a contact point of the exercise device. For example, the simulation video or video information may be a first-person perspective of a rider riding a mountain bike of a trail. The simulation video or video information may include the handlebars in the frame of the simulation video or video information, and a computing device or processor may detect the presence of the handlebars. In other examples, the simulation video or video information may include a running surface in the frame of the simulation video or video information, allowing the system to detect curbs, rocks, or roots in the video and simulate the running surface with actuators that move the tread belt.

(48) The method 732 further includes displaying video information of the simulation data on a display (such as display 102 described in relation to FIG. 1) at 736. In some embodiments, the method 732 further includes playing audio information of the simulation data at 736. In some embodiments, the simulation data includes both audio information and video information. The audio and/or video information provides visual and/or auditory immersion to which the haptic simulation(s) add further immersion.

(49) In some embodiments, the simulated object in the simulation video or video information is detected relative to a horizon or other reference point to measure the amount of displacement of the simulated object in the video. For example, the horizon may be a horizontal line that provides a consistent reference within the video. In other examples, the horizon is not visible in the video information and another relatively stationary object may be used. In at least one embodiment, the sun is approximated to be stationary in the sky for the purposes of measuring the amount of displacement of the simulated object in the video information. In some examples, the simulated object is measured relative to other stationary objects in the environment to measure the amount of movement. In at least one embodiment, the sun is approximated to be stationary in the sky for the purposes of measuring the amount of displacement of the simulated object in the video information. In some embodiments, the movement of the simulated object is determined by a machine learning (ML) that refines through iterations.

(50) A machine learning model (ML model) according to the present disclosure refers to a computer algorithm or model (e.g., a classification model, a regression model, a language model, an object detection model) that can be tuned (e.g., trained) based on training input to approximate unknown functions. For example, a machine learning model may refer to a neural network or other machine learning algorithm or architecture that learns and approximates complex functions and generate outputs based on a plurality of inputs provided to the machine learning model. In some embodiments, a machine learning system, model, or neural network described herein is an artificial neural network. In some embodiments, a machine learning system, model, or neural network described herein is a convolutional neural network. In some embodiments, a machine learning system, model, or neural network described herein is a recurrent neural network. In at least one embodiment, a machine learning system, model, or neural network described herein is a Bayes classifier. As used herein, a “machine learning system” may refer to one or multiple machine learning models that cooperatively generate one or more outputs based on corresponding inputs. For example, a machine learning system may refer to any system architecture having multiple discrete machine learning components that consider different kinds of information or inputs.

(51) The method 732 further includes actuating an actuator of the exercise device based on the determined movement of the simulated object in the simulation video or video information at 746, and the method 732 includes moving a frame of the exercise device relative to the base of the

exercise device with the actuator at **740**. In some embodiments, the frame is further movable relative to the base to change an inclination or declination of the exercise device.

(52) An example of simulated object detection and image processing is illustrated in FIG. **8**. The video information of FIG. **8** represents a mountain bike trail ride recorded by the user or another rider. The video information includes the handlebars **848** (which may be detected as a simulated object for determining haptic information for actuating the handlebars of the exercise device), the trail **850**, trail surface features **852** (such as rocks and roots), and environmental objects **854** that may be used as reference points. In some embodiments, the system may detect the handlebars **848** through image recognition, edge detection, or other image processing techniques to identify the expected shape of either straight handlebars or drop handlebars. Because part or all of the handlebars **848** may be obscured or out of the video frame during portions of the video information. In some embodiments, the system may identify a stem **858**, which connects the handlebars **848** to a frame of the bicycle as a proxy for the position and orientation of the handlebars **848**.

(53) In some embodiments, the handlebars **848** are a simulated object, and the system may determine the haptic information based on the position and movement of the handlebars **848** relative to one or more reference points, such as the trail **850**, trail surface features **852**, or other environmental objects **854**. In some embodiments, the system may detect more than one simulated object to provide haptic simulation with a plurality of actuators. For example, the handlebars **848** in the video information may be detected and tracked to calculate haptic information used to actuate a first actuator (or actuators) associated with the handlebars of the exercise device, and trail surface features **852** may be detected and tracked to approximate the objects interacting with the rear wheel of the bicycle to provide haptic simulation for the saddle movement.

(54) In at least one embodiment, a system or method according to the present disclosure allows for a user of an exercise device to be more immersed in a video or audio presentation during a workout routine. In some examples, simulation data includes haptic information that is coordinated to the video information and/or audio information. In some examples, the haptic information may be calculated by object detection or other image processing and recognition techniques to create immersive haptic simulation of conventional action camera videos.

INDUSTRIAL APPLICABILITY

(55) The present disclosure relates generally to systems and methods for haptic simulations in an exercise device. More particularly, the exercise devices of the present disclosure include a frame that is movable relative to a base of the exercise device to increase the user's immersion in a simulated environment.

(56) An exercise device is any mechanical device that is used to provide or replicate a physical activity in a localized space. Exercise devices can include a treadmill, cable or spring resistance machine, weight resistance machine, dumbbells, elliptical machine, stepper machine, stationary bicycle, rowing machine, or any other machine or exercise device. In an example, it should be understood that while a road bicycle may not be an exercise device, as used herein, a bicycle positioned on a stationary trainer device should be considered an exercise device as the bicycle remains in one location while the user rides the bicycle on the stationary trainer device.

(57) In some embodiments, an exercise device includes or is in communication with a display. The display allows a user of the exercise device to view video information as the user engages in exercises. In some embodiments, the display presents video information that simulates a route, path, track, road, trail, or other environment associated with the activity replicated by the exercise device. For example, a display integrated in or in communication with a treadmill may present video information simulating traveling down a road in Oahu, Hawaii at a speed approximately equal to the speed at which the tread belt is moving on the treadmill. The resulting experience for the user is a simulated run down the road presented on the display. Similarly, in another example, a display integrated in or in communication with a stationary bicycle may present video information

simulating traveling down a mountain trail in Sedona, Arizona at a speed approximately equal to the speed at which the user moves the pedals of the stationary bicycle. The resulting experience for the user is a simulated mountain bike ride down the trail presented on the display. In yet another example, a display integrated in or in communication with a rowing machine may present video information simulating rowing down the Charles River in Cambridge, Massachusetts at a speed approximately equal to the speed at which the user pulls the handle of the rowing machine. The resulting experience for the user is a simulated row down the river presented on the display.

(58) The exercise device simulates the experience based on simulation data that includes video information as described above. In some embodiments, the simulation data includes audio information. For example, the exercise device may offer one or more simulations such as simulate racing in a stage of a bike race or running away from a dinosaur. In such examples, audio information can increase the immersion of a bike race simulation by simulating cheering fans or sound of another racer approaching from behind on a climb. In another example, audio information can increase the immersion of a dinosaur chase by simulating the roar of the dinosaur behind the runner.

(59) In some embodiments, the simulation data includes haptic information. In the previous examples, the exercise device offers simulations that simulate racing in a stage of a bike race or running away from a dinosaur. In such examples, haptic information can increase the immersion of a bike race simulation by rapidly changing inclination of a frame of the exercise bicycle relative to a base of the exercise bicycle simulate the cobblestone road surface of the Paris-Roubaix bicycle race. In another example, haptic information can increase the immersion of the dinosaur chase by rapidly changing the inclination of the tread belt of the treadmill to simulate the ground shaking with the dinosaur footsteps.

(60) The haptic information may be predetermined and stored on a hardware storage device with the video and/or audio information of the simulation data. In some embodiments, the haptic information may be calculated by the exercise device, a client device, or a workout server based on the video information. For example, a recorded video of a mountain bike ride from a rider's viewpoint (such as video information recorded by a GoPro® or other action camera) may include the bicycle handlebars within the frame of the video information. In some embodiments, the system detects the location of the handlebars in the video information and determines the movement of the handlebars relative to the trail surface. The movement of the handlebars may be presented to the exercise device as haptic information and allow the exercise device to simulate the movement of the handlebars in the video information by moving the handle bars of the stationary bicycle relative to a frame of the stationary bicycle.

(61) In some embodiments, an exercise device is a stationary bicycle with a display integrated into the exercise device. In some embodiments, the display may be independent from, but in data communication with, the exercise device and receive video information from a computing device of the exercise device. The computing device includes a processor and a hardware storage device with instructions stored thereon that, when executed by the processor, cause the exercise device to perform any of the methods described herein.

(62) In some embodiments, the hardware storage device is any non-transient computer readable medium that may store instructions thereon. The hardware storage device may be any type of solid-state memory; volatile memory, such as static random access memory (SRAM) or dynamic random access memory (DRAM); or non-volatile memory, such as read-only memory (ROM) including programmable ROM (PROM), erasable PROM (ERPOM) or EEPROM; magnetic storage media, such as magnetic tape; platen-based storage device, such as hard disk drives; optical media, such as compact discs (CD), digital video discs (DVD), Blu-ray Discs, or other optical media; removable media such as USB drives; non-removable media such as internal SATA or non-volatile memory express (NVMe) style NAND flash memory, or any other non-transient storage media. In some embodiments, the hardware storage device is local to and/or integrated with the computing device.

In some embodiments, the hardware storage device is accessed by the computing device through a network connection.

(63) The exercise device includes one or more contact points supported by a frame with which the user touches, contacts, or engages with the exercise device during the exercise. It should be understood that while the user may touch or contact one or more controls of the exercise device, such as a touchscreen of the display or other input devices to provide inputs to the computing device (e.g., volume controls, resistance levels, power buttons), the controls or input devices are not considered the contact points of the exercise device for the purposes of the exercise performed on the exercise device. In some embodiments, the exercise device is a stationary bicycle and the intended exercise of the stationary bicycle is cycling, therefore, the components of the stationary bicycle used for cycling are considered to be the contact points of the exercise device. The contact points of the exercise device include the handlebars, the saddle, and the pedals.

(64) In some embodiments, the frame moves relative to a base at a pivot. By moving the frame relative to the base, the exercise device can provide haptic feedback and/or simulations to the user by moving one or more contact points of the exercise device. In some embodiments, the contact points all move together to simulate, for example, a bicycle moving over a surface. In other embodiments, at least one contact point moves relative to another contact point, such as moving handlebars relative to a seat or saddle. In some embodiments, the rotation of the frame around the pivot can simulate cobblestones, washboard roads, mountain bike trails, etc. on an exercise bicycle. In other embodiments, the rotation of the frame can simulate other real-world experiences for other exercise devices, such as rough water on a stationary rower exercise device or rocky running trails on a treadmill exercise device.

(65) In some embodiments, the frame is movable relative to the base by one or more incline motors. The incline motor applies a torque around the pivot to rotate the frame relative to the base. In some embodiments, the incline motor includes gears, worm gears, pinions, etc. to mechanically apply the torque around the pivot. In some embodiments, the incline motor includes a piston-and-cylinder with a pressurized fluid therein to apply pneumatically or hydraulically apply the torque around the pivot. In some embodiments, the incline motor includes an electromagnetic motor to move the frame relative to the base.

(66) The incline motor(s) is in data communication with the computing device to move the frame relative to the base in response to simulation data. In some embodiments, the computing device has stored thereon instruction that, when executed by the computing device, cause the exercise device to perform any of the methods described herein. In some embodiments, the computing device **104** communicates with the incline motor to move the frame relative to the base by moving at least a portion of the incline motor at a rate of 5 millimeters per second. In contrast to conventional incline motors, an incline motor according to the present disclosure, is configured to move the frame rapidly and for a period of time at least 5 seconds in duration. For example, a conventional incline motor moves the frame relative to the base slowly and smoothly to provide gradual changes in inclination of the running surface (e.g., treadmill) or inclination of a bicycle frame to replicate riding a hill. However, there is no mechanism by which a conventional incline motor produces rapid, sustained movement to provide haptic simulations to a user.

(67) In some embodiments, a treadmill exercise device has a display and computing device in communication therewith to provide exercise routines and video information to a user. The exercise device has a tread belt supported by a frame that is movable relative to a base of the exercise device. As described herein, the computing device may move the frame, and, hence, contact points such as the tread belt, relative to the base to produce a haptic simulation for the user. In some embodiments, the frame is movable relative to the base around a pivot by an incline motor. In some embodiments, the incline motor is used to provide haptic simulation through rapid and/or sustained movement of the frame. In other embodiments, the incline motor provides slow and/or smooth changes in the inclination of the frame relative to the base to simulate overall angle of a running

surface, while an actuator is additionally provided to move the frame relative to the base.

(68) In some embodiments, the actuator is connected to the incline motor, as will be described in greater detail herein, to move the frame relative to the incline motor (or move the frame and incline motor relative to the base). For example, the incline motor and actuator may be connected in sequence to allow the incline motor to provide macro changes in the position of the frame relative to the base, while the actuator provides smaller, but more rapid, changes in the position of the frame relative to the base.

(69) In some embodiments, the exercise device includes a single actuator. In other embodiments, the exercise device includes a plurality of actuators. Each of the actuators can include one or more individual actuable devices, such as including a pair of actuable devices to allow movement of the frame in one or more directions or axes relative to the base. In some embodiments, the actuators are electromagnetic actuators that use permanent magnets, electromagnets, or combinations thereof to apply magnetic force to move the frame in one or more directions or axes relative to the base. In some embodiments, the actuators are fluid piston actuators that use compressible or incompressible fluid in a cylinder to apply a force to a piston that is slidable relative to the cylinder. The fluid may be a gas (e.g., pneumatic piston and cylinder) or a liquid (e.g., hydraulic piston and cylinder) that moves piston relative to the cylinder to move the frame in one or more directions or axes relative to the base. In some embodiments, the actuators are mechanical actuators that use gears, springs, elastic or biasing elements, or combinations thereof to apply a compression and/or tension force to move the frame in one or more directions or axes relative to the base.

(70) In different embodiments, the actuators move the contact points in different path directions and/or shapes. In some embodiments, an actuator moves the frame around the pivot relative to the base to move at least a portion of the tread belt in an arcuate path. In other embodiments, the actuator can move the frame in a linear path relative to the base. For example, one or more actuators may move the frame vertically. In another example, one or more actuators may move the frame horizontally.

(71) The actuators move in response to the simulation data provided by the computing device. The simulation data includes haptic information that instructs one or more actuators to move a contact point coordinated with audio and/or video information of the simulation data that is presented to the user on the display or other audiovisual devices (e.g., speakers or headphones). The haptic information may include instructions for one or more actuators to move the frame a nominal or relative (to a total range of motion) amount, at a particular speed, for a particular duration, or combination thereof.

(72) For example, the haptic information may instruct the actuator to move the tread belt in coordination with a tree stump presented on the display. The haptic information may instruct the actuator at a 3:26 timestamp to translate the tread belt upward by 35 millimeters (mm) at a rate of 100 millimeters per second (mm/s) and return the tread belt to the original position at a rate of 50 mm/s. The higher rate of upward travel and the lower rate of downward travel may replicate an asymmetry of the tree stump in the video information.

(73) In other examples, the entire surface of the tread belt may displace upward before returning to the original position to simulate an explosion in the video information presented on the display. In at least one example, the exercise device may simulate an action scene and prompt the user of the exercise device to run to safety by evading objects and/or clearing obstacles in the presented video and/or audio information. The action scene may simulate escaping a boobytrapped temple where the user must run along uneven pathways, crumbling walls, and escape a large boulder following the user. The actuator(s) may move the frame around the pivot to simulate the debris from the walls on the running surface and simulate the shaking of the ground as the boulder rolls behind the user.

(74) In some embodiments, an actuator and incline motor are connected in sequence to provide a cumulative displacement of a frame relative to a base.

(75) The range of motion of the actuator and a range of motion of the connection point of the frame

movable by the actuator may be different. For example, the actuator may be connected to the frame (e.g., the actuator that moves the frame) by being coupled to a linkage or lever that moves the frame. In other examples, the range of motion of the actuator and a range of motion of the frame movable by the actuator may be equal, as the actuator and the frame are directly coupled to one another.

(76) In some embodiments, the incline motor has a range of motion that is greater than the actuator. In some embodiments, the actuator moves the frame relative to the base faster than the incline motor.

(77) In some embodiments, the range of motion of the frame is in a range having an upper value, a lower value, or upper and lower values including any of 5 mm, 10 mm, 15 mm, 20 mm, 25 mm, 30 mm, 35 mm, 40 mm, 45 mm, 50 mm, 55 mm, 60 mm, 65 mm, 70 mm, 75 mm, 80 mm, 85 mm, 90 mm, 95 mm, 100 mm, or any values therebetween. In some examples, the range of motion of the connection point is greater than 5 mm. In other examples, the range of motion of the connection point is less than 100 mm. In yet other examples, the range of motion of the connection point is between 5 mm and 100 mm. In yet other examples, the range of motion of the connection point is between 10 mm and 80 mm. In yet other examples, the range of motion of the connection point is about 50 mm.

(78) In some embodiments, the maximum rate of motion of the connection point of the frame is in a range having an upper value, a lower value, or upper and lower values including any of 25 mm/s, 50 mm/s, 100 mm/s, 150 mm/s, 200 mm/s, 250 mm/s, 300 mm/s, 350 mm/s, 400 mm/s, 450 mm/s, 500 mm/s, 550 mm/s, 600 mm/s, 650 mm/s, 700 mm/s, 750 mm/s, 800 mm/s, 850 mm/s, 900 mm/s, 950 mm/s, 1000 mm/s, or any values therebetween. In some examples, the maximum rate of motion of the connection point is greater than 25 mm/s. In other examples, the maximum rate of motion of the connection point is less than 1000 mm/s. In yet other examples, the maximum rate of motion of the connection point is between 25 mm/s and 1000 mm/s. In yet other examples, the maximum rate of motion of the connection point is between 100 mm/s and 750 mm/s. In yet other examples, the maximum rate of motion of the connection point is greater than 500 mm/s.

(79) In some embodiments, the actuator moves the frame relative to the base faster than the incline motor, and the incline motor has a larger range of motion than the actuator. As described herein, in some embodiments, the actuator includes a magnetic actuator, such as a linear magnetic actuator or rotational magnetic actuator. In some embodiments, the actuator includes a piston-and-cylinder actuator, such as a hydraulic or pneumatic piston-and-cylinder actuator. In some embodiments, the actuator includes a mechanical actuator, such as a rack and pinion actuator.

(80) In at least one embodiment, the incline motor has a heat sink that allows the incline motor to move the frame relative to the base faster or for longer durations than a conventional heat sink. In some embodiments, the heat sink is an active heat sink with active cooling, such as a fan, liquid cooling, a thermoelectric cooler (e.g., a Peltier-style cooler), or other active cooling mechanisms. In some embodiments, the heat sink is a passive heat sink, such as cooling fins, pins, rods, heat spreaders, vapor chambers, heat pipes, or other heat sinks that increase surface area and passively exhaust heat to the ambient atmosphere.

(81) In some embodiments, the incline motor heat sink is configured to allow the incline motor to operate at least at a 50% duty cycle. In some embodiments, the incline motor heat sink is configured to allow the incline motor to operate at least at a 90% duty cycle. In some embodiments, the incline motor heat sink is configured to allow the incline motor to operate at a 100% duty cycle.

(82) In some embodiments, the incline motor heat sink is configured to dissipate at least 500 Watts per minute (W/min). In some embodiments, the incline motor heat sink is configured to dissipate at least 750 Watts per minute (W/min). In some embodiments, the incline motor heat sink is configured to dissipate at least 1000 Watts per minute (W/min).

(83) In some embodiments, the exercise device includes an incline motor, and, optionally, an actuator, configured to move a frame of the exercise device relative to a base. The incline motor

and/or actuator may move the frame according to haptic information provided by the computing device. In some embodiments, the frame is movable (e.g., tiltable) relative to a base that contacts the ground. In some embodiments, the video information or workout routine includes global positioning satellite (GPS) location information or other location information. The location information may be compared to elevation or profile maps to determine an inclination or declination of the road or trail to be simulated by the tilt of the frame. The frame may connect to the base at a rotational pivot that allows the frame supporting the contact points to move relative to the ground. In some examples, an incline motor provides macro-movements of the frame around the pivot to allow the exercise device to simulate the angle of climbing up a road, while the incline motor and actuator provides smaller movements for haptic simulation to simulate the surface condition of the road. The computing device may be in data communication with the actuator(s) and incline motor to tilt the frame to provide a more immersive simulation.

(84) While the movable frame relative to the base is described herein in relation to an exercise bicycle, it should be understood that a tiltable or movable frame with haptic simulation, where the frame is movable relative to a base, is applicable to other types of exercise devices, such as treadmills, rowing machines, and other devices.

(85) An exercise device, according to the present disclosure, may include a plurality of electronic components in data communication. In some embodiments, the electronic system includes a processor and a hardware storage device. In some embodiments, the hardware storage device is any non-transient computer readable medium that may store instructions thereon. The hardware storage device may be any type of solid-state memory; volatile memory, such as static random access memory (SRAM) or dynamic random access memory (DRAM); or non-volatile memory, such as read-only memory (ROM) including programmable ROM (PROM), erasable PROM (ERPOM) or EEPROM; magnetic storage media, such as magnetic tape; platen-based storage device, such as hard disk drives; optical media, such as compact discs (CD), digital video discs (DVD), Blu-ray Discs, or other optical media; removable media such as USB drives; non-removable media such as internal SATA or non-volatile memory express (NVMe) style NAND flash memory, or any other non-transient storage media. In some embodiments, the hardware storage device is local to and/or integrated with the processor. In some embodiments, the hardware storage device is accessed by the processor through a network connection.

(86) The processor is further in communication with a display controller. The processor receives simulation data from the hardware storage device. In some embodiments, the simulation data includes video information and haptic information. The processor transmits video information to the display controller and instructions based on the haptic information to the incline motor and/or the actuator. The display controller communicates with the display to present the video information to a user, while the incline motor and/or the actuator moves the frame of the exercise device relative to the base to provide haptic simulation to the user. The processor may coordinate the presentation of the video information and haptic information to the user such that the user perceives the exercise device moving in coordination with the displayed video. In some embodiments, the processor is further in communication with the one or more sensors and/or cameras to monitor the position and/or movement of the user. The processor may transmit instructions to one or more actuators of a plurality of actuators based on the measurements from the sensors and/or cameras.

(87) In some embodiments, a method of providing haptic simulation in an exercise device includes obtaining simulation data for a workout routine performed on an exercise device. In some embodiments, the simulation data is obtained from local hardware storage device. In some embodiments, the simulation data is obtained from a remote hardware storage device, such as by downloading or streaming the simulation data from a remote server or datacenter. A workout routine is a predetermined set of instructions that may be provided to a user. Following the workout routine can guide, entertain, or encourage the user through one or more exercises to produce workout information. The workout routine may include haptic information, video information,

audio information, text information, still images, or combinations thereof to communicate the workout routine to the user.

(88) The method further includes displaying video information of the simulation data on a display. In some embodiments, the method further includes playing audio information of the simulation data. In some embodiments, the simulation data includes both audio information and video information. The audio and/or video information provides visual and/or auditory immersion to which the haptic simulation(s) add further immersion.

(89) The haptic information of the simulation data is used in actuating an incline motor (and, optionally, an actuator) of the exercise device, and the method includes moving a frame of the exercise device relative to a base of the exercise device with incline motor (and, optionally, actuator). In some embodiments, the frame is further movable relative to the base to change an inclination or declination of the exercise device.

(90) While the method includes actuating an actuator of the exercise device based on the simulation data, in some embodiments, the simulation data does not include haptic information, and the processor may calculate haptic information from the simulation data as described herein.

(91) In some embodiments, a method of providing haptic simulation in an exercise device includes obtaining simulation data for a workout routine performed on an exercise device, similar to or the same as described herein. In some embodiments, the simulation data is obtained from local hardware storage device. In some embodiments, the simulation data is obtained from a remote hardware storage device, such as by downloading or streaming the simulation data from a remote server or datacenter.

(92) The method may further include detecting a simulated object in the simulation video or video information and determining a movement of the simulated object in simulation video or video information. In some embodiments, the simulated object is an object in the simulation video or video information that is analogous to a contact point of the exercise device. For example, the simulation video or video information may be a first-person perspective of a rider riding a mountain bike on a trail. The simulation video or video information may include the handlebars in the frame of the simulation video or video information, and a computing device or processor may detect the presence of the handlebars. In other examples, the simulation video or video information may include a running surface in the frame of the simulation video or video information, allowing the system to detect curbs, rocks, or roots in the video and simulate the running surface with actuators that move the tread belt.

(93) The method further includes displaying video information of the simulation data on a display. In some embodiments, the method further includes playing audio information of the simulation data. In some embodiments, the simulation data includes both audio information and video information. The audio and/or video information provides visual and/or auditory immersion to which the haptic simulation(s) add further immersion.

(94) In some embodiments, the simulated object in the simulation video or video information is detected relative to a horizon or other reference point to measure the amount of displacement of the simulated object in the video. For example, the horizon may be a horizontal line that provides a consistent reference within the video. In other examples, the horizon is not visible in the video information and another relatively stationary object may be used. In at least one embodiment, the sun is approximated to be stationary in the sky for the purposes of measuring the amount of displacement of the simulated object in the video information. In some examples, the simulated object is measured relative to other stationary objects in the environment to measure the amount of movement. In at least one embodiment, the sun is approximated to be stationary in the sky for the purposes of measuring the amount of displacement of the simulated object in the video information. In some embodiments, the movement of the simulated object is determined by a machine learning (ML) that refines through iterations.

(95) A machine learning model (ML model) according to the present disclosure refers to a

computer algorithm or model (e.g., a classification model, a regression model, a language model, an object detection model) that can be tuned (e.g., trained) based on training input to approximate unknown functions. For example, a machine learning model may refer to a neural network or other machine learning algorithm or architecture that learns and approximates complex functions and generate outputs based on a plurality of inputs provided to the machine learning model. In some embodiments, a machine learning system, model, or neural network described herein is an artificial neural network. In some embodiments, a machine learning system, model, or neural network described herein is a convolutional neural network. In some embodiments, a machine learning system, model, or neural network described herein is a recurrent neural network. In at least one embodiment, a machine learning system, model, or neural network described herein is a Bayes classifier. As used herein, a “machine learning system” may refer to one or multiple machine learning models that cooperatively generate one or more outputs based on corresponding inputs. For example, a machine learning system may refer to any system architecture having multiple discrete machine learning components that consider different kinds of information or inputs.

(96) The method further includes actuating an actuator of the exercise device based on the determined movement of the simulated object in the simulation video or video information, and the method includes moving a frame of the exercise device relative to the base of the exercise device with the actuator. In some embodiments, the frame is further movable relative to the base to change an inclination or declination of the exercise device.

(97) In an example, a provided video information represents a mountain bike trail ride recorded by the user or another rider. The video information includes the handlebars (which may be detected as a simulated object for determining haptic information for actuating the handlebars of the exercise device), the trail, trail surface features (such as rocks and roots), and environmental objects that may be used as reference points. In some embodiments, the system may detect the handlebars through image recognition, edge detection, or other image processing techniques to identify the expected shape of either straight handlebars or drop handlebars. Because part or all of the handlebars may be obscured or out of the video frame during portions of the video information. In some embodiments, the system may identify a stem, which connects the handlebars to a frame of the bicycle as a proxy for the position and orientation of the handlebars.

(98) In some embodiments, the handlebars are a simulated object, and the system may determine the haptic information based on the position and movement of the handlebars relative to one or more reference points, such as the trail, trail surface features, or other environmental objects. In some embodiments, the system may detect more than one simulated object to provide haptic simulation with a plurality of actuators. For example, the handlebars in the video information may be detected and tracked to calculate haptic information used to actuate a first actuator (or actuators) associated with the handlebars of the exercise device, and trail surface features may be detected and tracked to approximate the objects interacting with the rear wheel of the bicycle to provide haptic simulation for the saddle movement.

(99) In at least one embodiment, a system or method according to the present disclosure allows for a user of an exercise device to be more immersed in a video or audio presentation during a workout routine. In some examples, simulation data includes haptic information that is coordinated to the video information and/or audio information. In some examples, the haptic information may be calculated by object detection or other image processing and recognition techniques to create immersive haptic simulation of conventional action camera videos.

(100) The present disclosure relates to systems and methods for haptic simulation according to at least the examples provided in the sections below:

(101) [A1] In some embodiments, a haptic simulation exercise device includes a frame, a base supporting the frame with at least one pivot point between the frame and the base, and an actuator configured to displace the frame relative to the base around the pivot point.

(102) [A2] In some embodiments, the actuator of [A1] is connected to the base and the frame and

positioned between the base and the frame.

(103) [A3] In some embodiments, the actuator of [A1] or [A2] is an electromagnetic actuator.

(104) [A4] In some embodiments, the actuator of [A1] or [A2] is a fluid piston actuator.

(105) [A5] In some embodiments, the actuator of [A1] or [A2] is a mechanical actuator.

(106) [A6] In some embodiments, the frame of any of [A1] to [A5] supports a tread belt.

(107) [A7] In some embodiments, the frame of any of [A1] to [A5] supports a handlebar.

(108) [A8] In some embodiments, the frame of any of [A1] to [A5] supports a saddle.

(109) [A9] In some embodiments, the exercise device of any of [A1] through [A8] includes an incline motor configured to incline the frame relative to the base. The actuator is coupled to the incline motor to displace one of the frame and base relative to the incline motor.

(110) [A10] In some embodiments, the incline motor of [A9] has a greater range of motion than the actuator.

(111) [A11] In some embodiments, the incline motor of [A9] or [A10] is configured to move the frame with a greater velocity relative to the base than the actuator.

(112) [A12] In some embodiments, the incline motor of any of [A9] through [A11] has a range of motion of at least 10 cm.

(113) [A13] In some embodiments, the incline motor of any of [A9] through [A12] has a heatsink configured to dissipate at least 500 Watts per minute.

(114) [A14] In some embodiments, the heatsink of [A13] includes a passive cooling feature.

(115) [A15] In some embodiments, the heatsink of [A13] includes a vapor chamber.

(116) [A16] In some embodiments, the heatsink of [A13] includes an active cooling feature.

(117) [B1] In some embodiments, a method of haptic simulation for an exercise device includes obtaining simulation data for a workout routine performed on an exercise device, displaying video information of the simulation data on a display, actuating an incline motor of the exercise device based on the simulation data, and displacing a frame of the exercise device relative to a base of the exercise device at least 5 millimeters in no more than one second based at least partially on the simulation data.

(118) [B2] In some embodiments, the simulation data of [B1] includes haptic information.

(119) [B3] In some embodiments, the display of [B1] or [B2] is integrated with the exercise device.

(120) [B4] In some embodiments, the exercise device of any of [B1] through [B3] includes an actuator, and displacing the frame includes providing instructions to the actuator to rotate the frame relative to the base at a pivot point.

(121) [B5] In some embodiments, the exercise device of any of [B1] through [B3] includes an incline motor and an actuator, and displacing the frame includes providing instructions to the actuator and incline motor to rotate the frame relative to the base at a pivot point.

(122) [B6] In some embodiments, the simulation data of any of [B1] through [B5] includes surface profile haptic information, and the incline motor moves the frame relative to the base to simulate a surface in the video information.

(123) [B7] In some embodiments, the method of [B6] further includes tilting the frame with an incline motor based on GPS information.

(124) [B8] In some embodiments, the method of any of [B1] through [B7] further includes determining haptic information from the video information of the simulation data.

(125) [B9] In some embodiments, determining the haptic information of [B8] includes detecting a simulated object in video information of the simulation data, and determining a movement of the simulated object in the video information.

(126) [B10] In some embodiments, detecting a simulated object in [B9] includes detecting one or more edges of the simulated object relative to a horizon.

(127) [B11] In some embodiments, determining a movement of the simulated object in [B9] includes measuring a speed of the simulated object toward a viewpoint of the video information.

(128) [C1] In some embodiments, a system for haptic simulation with an exercise device includes a

frame, a base, an incline motor, a display, and a computing device. The based is configured to support the frame and allow rotation of the frame relative to the base of the exercise device, and the incline motor is configured to displace the frame relative to the base. The computing device is in data communication with the incline motor and the display. The computing device provides instructions to the incline motor based on simulation data accessed by a processor of the computing device.

(129) The articles “a,” “an,” and “the” are intended to mean that there are one or more of the elements in the preceding descriptions. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it should be understood that references to “one embodiment” or “an embodiment” of the present disclosure are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features. For example, any element described in relation to an embodiment herein may be combinable with any element of any other embodiment described herein. Numbers, percentages, ratios, or other values stated herein are intended to include that value, and also other values that are “about” or “approximately” the stated value, as would be appreciated by one of ordinary skill in the art encompassed by embodiments of the present disclosure. A stated value should therefore be interpreted broadly enough to encompass values that are at least close enough to the stated value to perform a desired function or achieve a desired result. The stated values include at least the variation to be expected in a suitable manufacturing or production process, and may include values that are within 5%, within 1%, within 0.1%, or within 0.01% of a stated value.

(130) A person having ordinary skill in the art should realize in view of the present disclosure that equivalent constructions do not depart from the scope of the present disclosure, and that various changes, substitutions, and alterations may be made to embodiments disclosed herein without departing from the scope of the present disclosure. Equivalent constructions, including functional “means-plus-function” clauses are intended to cover the structures described herein as performing the recited function, including both structural equivalents that operate in the same manner, and equivalent structures that provide the same function. It is the express intention of the applicant not to invoke means-plus-function or other functional claiming for any claim except for those in which the words ‘means for’ appear together with an associated function. Each addition, deletion, and modification to the embodiments that falls within the meaning and scope of the claims is to be embraced by the claims.

(131) It should be understood that any directions or reference frames in the preceding description are merely relative directions or movements. For example, any references to “front” and “back” or “top” and “bottom” or “left” and “right” are merely descriptive of the relative position or movement of the related elements.

(132) The present disclosure may be embodied in other specific forms without departing from its characteristics. The described embodiments are to be considered as illustrative and not restrictive. The scope of the disclosure is, therefore, indicated by the appended claims rather than by the foregoing description. Changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope.

Claims

1. A haptic simulation exercise device comprising: a frame; a base supporting the frame with at least one pivot point between the frame and the base; an incline motor configured to provide a first change to an incline of the frame relative to the base; and an actuator coupled to the incline motor, the actuator configured to provide a second change to a position of the base or the frame relative to the base.

2. The haptic simulation exercise device of claim 1, wherein the incline motor has a greater range

of motion than the actuator.

3. The haptic simulation exercise device of claim 1, wherein the actuator is configured to move the frame faster than the incline motor.
 4. The haptic simulation exercise device of claim 1, wherein the incline motor has a range of motion of at least 10 cm.
 5. The haptic simulation exercise device of claim 1, wherein the incline motor has a heatsink configured to dissipate at least 500 Watts per minute.
 6. The haptic simulation exercise device of claim 5, wherein the heatsink includes a passive cooling feature.
 7. The haptic simulation exercise device of claim 6, wherein the heatsink includes a vapor chamber.
 8. The haptic simulation exercise device of claim 5, wherein the heatsink includes an active cooling feature.
 9. The haptic simulation exercise device of claim 1, wherein the second change to the position of the base or the frame relative to the base comprises an additional incline of the frame relative to the base.
 10. The haptic simulation exercise device of claim 1, wherein the second change to the position of the base or the frame relative to the base comprises a linear translation of the base or the frame relative to the base.
-