

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409647
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Takagi; Makoto

Liquid discharge head substrate, liquid discharge head, and liquid discharge apparatus

Abstract

A liquid discharge head substrate includes a substrate, a plurality of liquid discharge elements, a liquid supply port, temperature detection elements, and a driving wiring pattern. The plurality of liquid discharge elements are arranged in a first direction on a major surface of the substrate to discharge a liquid. The liquid supply port is provided in the substrate and is spaced apart from the plurality of liquid discharge elements in a second direction crossing the first direction to supply the liquid to the plurality of liquid discharge elements. The temperature detection elements are arranged on the substrate to detect a temperature. The driving wiring pattern extends in the second direction to an end portion of the substrate to drive the temperature detection elements, is connected to an external connection terminal, and is shared between the temperature detection elements.

Inventors:	Takagi; Makoto (Kanagawa, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	88240648
Assignee:	Canon Kabushiki Kaisha (Tokyo, JP)
Appl. No.:	18/190406
Filed:	March 27, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230321975 A1	Oct. 12, 2023

Foreign Application Priority Data

JP	2022-063544	Apr. 06, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: B41J2/045 (20060101); B41J2/14 (20060101)

U.S. Cl.:

CPC B41J2/04563 (20130101); B41J2/0458 (20130101); B41J2/1433 (20130101);

Field of Classification Search

CPC: B41J (2/04563); B41J (2/0458); B41J (2/1433)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4827294	12/1988	Hanson	347/56	B41J 25/34
2009/0309913	12/2008	Oohashi	N/A	N/A
2011/0292127	12/2010	Oohashi	347/50	B41J 2/04563
2013/0093808	12/2012	Kanno	347/47	B41J 2/0451
2014/0300660	12/2013	Hirayama	347/17	B41J 2/072
2019/0001667	12/2018	Kasai	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2009298107	12/2008	JP	N/A

Primary Examiner: Uhlenhake; Jason S

Attorney, Agent or Firm: Canon U.S.A., Inc. IP Division

Background/Summary

BACKGROUND OF THE INVENTION

Field

(1) The present disclosure relates to a liquid discharge head substrate, a liquid discharge head, and a liquid discharge apparatus.

Description of the Related Art

(2) A liquid discharge head that applies energy to a liquid using a discharge element and discharges the liquid from an orifice is widely used. Japanese Patent Laid-Open No. 2009-298107 discloses an arrangement in which a substrate temperature detection element is provided on a record head substrate to detect the temperature of the record head substrate and control the liquid discharge characteristics.

SUMMARY OF THE INVENTION

(3) A wiring pattern for operating a temperature detection element needs to be connected to the temperature detection element. When a plurality of temperature detection elements are arranged to measure the temperature of each portion of the substrate, a region necessary for the wiring pattern connected to the temperature detection elements widens, and the wiring regions of wiring patterns

connected to discharge elements and other elements narrow. When the wiring region narrows and thus the line width of the wiring pattern connected to the discharge elements is decreased, the wiring resistance may rise, degrading the characteristics of the liquid discharge head.

(4) An embodiment of the present disclosure provides a technique advantageous in measuring the substrate temperature of a liquid discharge head substrate.

(5) According to an aspect of the present disclosure, a liquid discharge head substrate includes a substrate, a plurality of liquid discharge elements arranged in a first direction on a major surface of the substrate to discharge a liquid, a liquid supply port provided in the substrate and spaced apart from the plurality of liquid discharge elements in a second direction crossing the first direction to supply the liquid to the plurality of liquid discharge elements, a plurality of temperature detection elements arranged on the substrate to detect a temperature of the substrate, and a driving wiring pattern that extends in the second direction to drive the plurality of temperature detection elements, wherein the driving wiring pattern extends to an end portion of the substrate in the second direction, is connected to an external connection terminal, and is shared between the plurality of temperature detection elements.

(6) Further features of the present disclosure will become apparent from the following description of exemplary embodiments (with reference to the attached drawings).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic plan view showing an example of the arrangement of a liquid discharge head substrate according to an embodiment;

(2) FIG. 2 is an equivalent circuit diagram showing an example of the arrangement of the temperature detection unit of the liquid discharge head substrate in FIG. 1;

(3) FIG. 3 is a top view showing an example of the arrangement of a wiring pattern in a region A on the liquid discharge head substrate in FIG. 1;

(4) FIG. 4 is an equivalent circuit diagram showing a modification of the temperature detection unit in FIG. 2;

(5) FIG. 5 is a schematic plan view showing a modification of the liquid discharge head substrate in FIG. 1;

(6) FIG. 6 is a perspective view showing a section of the liquid discharge head substrate between B-B' in FIG. 5;

(7) FIG. 7 is a schematic plan view showing a modification of the liquid discharge head substrate in FIG. 1;

(8) FIG. 8 is a schematic plan view showing a modification of the liquid discharge head substrate in FIG. 1;

(9) FIG. 9 is a view showing an example of the arrangement of a wiring pattern in a region C on the liquid discharge head substrate in FIG. 8;

(10) FIG. 10 is an equivalent circuit diagram showing an example of the arrangement of the temperature detection unit of the liquid discharge head substrate in FIG. 8;

(11) FIG. 11 is a schematic plan view showing an example of the arrangement of the control wiring pattern of the liquid discharge head substrate in FIG. 8; and

(12) FIGS. 12A to 12D are views showing an example of the arrangement of a liquid discharge apparatus using the liquid discharge head substrate in FIG. 1, 5, 7, or 8.

DESCRIPTION OF THE EMBODIMENTS

(13) Hereinafter, embodiments will be described in detail with reference to the attached drawings. Note, the following embodiments are not intended to limit the scope of the subject matter of the terms in the claims. Multiple features are described in the embodiments, but limitation is not made

to require all such features, and multiple such features may be combined as appropriate.

Furthermore, in the attached drawings, the same reference numerals are given to the same or similar configurations, and redundant description thereof is omitted.

(14) A liquid discharge head substrate according to an embodiment of this disclosure will be described with reference to FIGS. 1 to 11. FIG. 1 is a schematic plan view showing an example of the arrangement of a liquid discharge head substrate **100** according to the embodiment. The liquid discharge head substrate **100** according to the embodiment includes a substrate **101**, a plurality of liquid discharge elements **123** that are arranged in the X direction on the major surface of the substrate **101** to discharge a liquid, liquid supply ports **102** that are provided on the substrate **101** and spaced apart from the plurality of liquid discharge elements **123** in the Y direction crossing the X direction to supply the liquid to the plurality of liquid discharge elements **123**, a plurality of temperature detection units **108** that are each arranged on the substrate **101** and each include a temperature detection element D1 (shown in FIG. 2) to detect the temperature of the substrate **101**, and a driving wiring pattern **109** for driving the temperature detection elements D1 arranged in the respective temperature detection units **108**. When a specific temperature detection unit **108** out of the plurality of temperature detection units **108** is referred to, a suffix is added to the reference numeral, like a temperature detection unit **108**“a”. When the temperature detection unit **108** need not be discriminated, it will be simply referred to as the “temperature detection unit **108**”. This also applies to the remaining constituent components.

(15) The substrate **101** has a substantially rectangular shape with a long side in the X direction (longitudinal direction) and a short side in the Y direction (widthwise direction). Each liquid supply port **102** has a long groove shape with a long side in the X direction that extends through the substrate **101**. The liquid discharge elements **123** for discharging a liquid are arranged in a line in the X direction along each liquid supply port **102**, and constitute a liquid discharge element array **103**. Driver circuits **104** include one or more circuits for driving the liquid discharge elements **123** are arranged along the liquid supply ports **102**.

(16) In the arrangement shown in FIG. 1, three liquid supply ports **102a** to **102c** are arranged in the substrate **101**. Control circuits **105a** to **105c** include one or more circuits for supplying control signals to the driver circuits **104** are arranged at two ends of the liquid discharge element arrays **103** on the substrate **101** so that the control circuits **105a** to **105c** are spaced apart in the X direction. Further, external connection terminals **106** and **107** are arranged on the substrate **101** to supply power to the liquid discharge head substrate including the control circuits **105** and supply a data signal to the control circuits **105**. The external connection terminals **106** and **107** are arranged at two ends of the substrate **101** in the X direction.

(17) The temperature detection units **108** are arranged in a region between the external connection terminals **106** and the driver circuits **104** in the X direction. In the arrangement shown in FIG. 1, temperature detection units **108a** to **108c** are arranged in correspondence with the liquid supply ports **102a** to **102c**, respectively. The driving wiring pattern **109** for supplying a driving current to drive the temperature detection elements D1 arranged in the temperature detection units **108** is arranged near the temperature detection units **108a** to **108c**. The driving wiring pattern **109** is connected to an external connection terminal **106a**. The driving wiring pattern **109** is shared between the plurality of temperature detection units **108** (plurality of temperature detection elements D1).

(18) FIG. 2 is an equivalent circuit diagram showing an example of the connection relationship between the temperature detection units **108a** to **108c** and the driving wiring pattern **109** according to the embodiment. Each temperature detection unit **108** includes the temperature detection element D1. FIG. 2 shows an example in which a diode sensor is used as the temperature detection element D1. Of two terminals of the temperature detection element D1, an anode terminal is connected to the source terminal of a switching element NM1. FIG. 2 shows an example in which a NMOS transistor is used as the switching element NM1. The drain terminal of the switching element NM1

is connected to the driving wiring pattern **109**. That is, the respective temperature detection elements **D1** arranged in the temperature detection units **108a** to **108c** are connected to the driving wiring pattern **109** via the switching elements **NM1**. The drain terminals of switching elements **NM1a** to **NM1c** of the temperature detection units **108a** to **108c** are commonly connected to the driving wiring pattern **109**. The cathode terminal of the temperature detection element **D1** is connected to the ground potential. The gate terminal of the switching element **NM1** is connected to a control wiring pattern **110**. The switching elements **NM1a** to **NM1c** operate to exclusively connect, to the driving wiring pattern **109**, temperature detection elements **D1a** to **D1c** arranged in the temperature detection units **108a** to **108c** in accordance with the potentials of control wiring patterns **110a** to **110c**.

(19) In the embodiment, a current is supplied from the external connection terminal **106a** to the temperature detection element **D1** of the selected temperature detection unit **108**, and a voltage between the two terminals of the temperature detection element **D1** that changes depending on the temperature is monitored via the external connection terminal **106a**, thereby detecting the temperature. A diode is used as the temperature detection element **D1** in the embodiment, but the temperature detection element **D1** is not limited to this. For example, it suffices to measure a potential between the two terminals of a resistance element having a temperature characteristic, such as a resistance element using polysilicon or TaSiN.

(20) FIG. 3 is a top view showing an example of the arrangement of a wiring pattern in a region A surrounded by a broken line in FIG. 1. A wiring layer **M1** performs wiring in the Y direction and a wiring layer **M2** performs wiring in the X direction in a region I between the external connection terminal **106** and a region of the substrate **101** where the control circuits **105**, the temperature detection units **108**, the liquid supply ports **102**, and the like are arranged.

(21) In the region A, the temperature detection unit **108c** and the control circuit **105** are arranged adjacent to each other. Power supply wiring patterns **111** and a ground wiring pattern **112** for the liquid discharge elements **123** are arranged using the wiring layer **M2**. To stabilize the characteristics of the liquid discharge elements **123**, the power supply wiring pattern **111** and the ground wiring pattern **112** need to connect the external connection terminals **106** and the liquid discharge elements **123** at low resistance. For this purpose, the power supply wiring pattern **111** and the ground wiring pattern **112** can be arranged with wiring widths as maximum as possible. In the embodiment, the driving wiring pattern **109** is laid out to extend in the Y direction in the wiring layer **M1** different from the wiring layer **M2** in which the power supply wiring pattern **111** and the ground wiring pattern **112** for the liquid discharge elements **123** are arranged. Further, the driving wiring pattern **109** extends in the X direction in the wiring layer **M1** at an end portion of the substrate **101** in the Y direction. The driving wiring pattern **109** is connected to the external connection terminal **106a** so as to run round a power supply wiring pattern **117** and a ground wiring pattern **118** for the control circuits **105** that are arranged in the wiring layer **M1** at an end portion of the substrate **101** on the side of the external connection terminals **106** in the X direction.

(22) In the embodiment, the driving wiring pattern **109** for driving the temperature detection elements **D1** of the temperature detection units **108** is extracted collectively in the Y direction, laid out in the X direction at an end portion of the substrate **101** in the Y direction, and connected to the external connection terminal **106a**. As a result, in the region I between the liquid supply ports **102** and the external connection terminals **106**, the driving wiring pattern **109** is extracted up to an end portion of the substrate **101** in the Y direction while avoiding the wiring region of the power supply wiring pattern **117** and ground wiring pattern **118** for the liquid discharge elements **123** that extend in the X direction in the wiring layer **M2**. In the region I, the driving wiring pattern **109** is extracted up to an end portion of the substrate **101** in the Y direction while avoiding the wiring region of the power supply wiring pattern **117** and ground wiring pattern **118** for the control circuits **105** that extend in the Y direction in the wiring layer **M1**. Further, the driving wiring pattern **109** can be laid out in the X direction using a region that may serve as a redundant space at an end portion of the

substrate **101** in the Y direction. Thus, regions for driving wiring patterns extending in the X direction up to the external connection terminals **106** need not be ensured for the temperature detection elements **D1** provided for the respective liquid supply ports **102**. Hence, the wiring region of the power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** can be widened.

(23) In this manner, the driving wiring pattern **109** is shared between the plurality of temperature detection elements **D1** arranged on the substrate **101**. The wiring efficiency of the power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** can be increased in comparison with a case in which lead wires are provided for the external connection terminals **106** from the respective temperature detection elements **D1** arranged in the temperature detection units **108** that are arranged in correspondence with the respective liquid supply ports **102**. Also, the wiring efficiency of the power supply wiring pattern **117** and ground wiring pattern **118** for the control circuits **105** can be increased. More specifically, the driving wiring pattern **109** is shared between the plurality of temperature detection elements **D1**, so the wiring regions of wiring patterns connected to other elements such as the liquid discharge elements **123** and the control circuits **105** are not narrowed, and an increase in wiring resistance can be suppressed. The suppression of an increase in the wiring resistance of the power supply wiring pattern **111** and ground wiring pattern **112** connected to the liquid discharge elements **123** leads to suppression of degradation of the characteristics of a liquid discharge head using the liquid discharge head substrate **100**. By measuring the temperature of the substrate **101** of the liquid discharge head substrate **100** at a plurality of locations, finer control can be performed with respect to a change in the characteristics of the liquid discharge elements **123** by the temperature. This can improve the characteristics of the liquid discharge head using the liquid discharge head substrate **100**.

(24) FIG. 4 is an equivalent circuit diagram showing a modification of the temperature detection unit **108** shown in FIG. 2. Monitoring wiring patterns **113** and **114** may be connected via switching elements **NM2** and **NM3** to two terminals of the temperature detection element **D1** arranged in the temperature detection unit **108**. In the arrangement shown in FIG. 4, the monitoring wiring pattern **113** is connected to the anode terminal of the temperature detection element **D1** via the switching element **NM2**. The monitoring wiring pattern **113** is connected to an external connection terminal **106b**. The monitoring wiring pattern **114** is connected to the cathode terminal of the temperature detection element **D1** via the switching element **NM3**. The monitoring wiring pattern **114** is connected to an external connection terminal **106c**. FIG. 4 shows an example in which NMOS transistors are used as the switching elements **NM2** and **NM3**, similar to the switching element **NM1**. The gate terminals of the switching elements **NM1** to **NM3** are connected to the common control wiring pattern **110**. The switching elements **NM1** to **NM3** are turned on or off at the same timing.

(25) In the arrangement shown in FIG. 2, for example, the measurement voltage value of the temperature detection element **D1** needs to be corrected for each temperature detection unit **108** by using a correction table or the like in accordance with a wiring resistance value from the external connection terminal **106a**. Similarly, the measurement voltage value of the temperature detection element **D1** needs to be corrected for each temperature detection unit **108** in consideration of the ON resistance value of the switching element **NM1** at the time of the ON operation, the temperature characteristic for the ON resistance value, and the like.

(26) In contrast, the arrangement shown in FIG. 4 is used to enable so-called four-terminal sensing of independently measuring a current flowing through the temperature detection element **D1** and a potential applied to the temperature detection element **D1**. The current and potential of the temperature detection element **D1** can be measured without considering a difference in potential arising from nonuniformity of resistance values from the external connection terminal **106a** to the respective temperature detection elements **D1** that is generated by connecting the plurality of temperature detection elements **D1** to one driving wiring pattern **109**. This can improve the

precision of temperature measurement of the substrate **101** of the liquid discharge head substrate **100**.

(27) Although FIG. 4 shows an arrangement for one temperature detection unit **108**, each of the temperature detection units **108a** to **108c** shown in FIG. 2 may have a similar arrangement. In this case, the monitoring wiring patterns **113** and **114** may be shared between the plurality of temperature detection units **108** (temperature detection elements **D1**), similar to the driving wiring pattern **109**. The monitoring wiring patterns **113** and **114** may be arranged in, for example, the wiring layer **M1** in parallel with the driving wiring pattern **109**. The control wiring patterns **110** may be separately connected to the external connection terminals **106** and **107** for the respective temperature detection units **108**. However, when the number of temperature detection units **108** is large and the external connection terminals **106** and **107** are separately prepared for the respective temperature detection units **108**, a larger number of external connection terminals **106** and **107** become necessary. In addition, a large number of control wiring patterns **110** are arranged. To prevent this, for example, the control circuit **105** may control the switching elements **NM1** to **NM3** of the temperature detection units **108**. This can suppress the numbers of external connection terminals **106** and **107** and a region where the control wiring patterns **110** are arranged. That is, this can improve the wiring efficiencies of the power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** and the power supply wiring pattern **117** and ground wiring pattern **118** for the control circuits **105**.

(28) FIG. 5 is a schematic plan view showing an example of the arrangement of a liquid discharge head substrate **500** as a modification of the liquid discharge head substrate **100** shown in FIG. 1. The liquid discharge head substrate **500** shown in FIG. 5 is configured to obtain a temperature near the center of the liquid discharge element array **103** in which the plurality of liquid discharge elements **123** are aligned in the X direction. Temperature detection units **108a** to **108d** each including the temperature detection element **D1** are arranged near the center of the substrate **101** in the X direction so that the temperature detection units **108a** to **108d** are spaced apart from each other in the Y direction. The temperature detection unit **108a** is arranged between a liquid discharge element array **103a** and one end portion (one long side extending in the X direction) of the substrate **101** in the Y direction. The temperature detection unit **108b** is arranged between liquid discharge element arrays **103b** and **103c**. The temperature detection unit **108c** is arranged between liquid discharge element arrays **103d** and **103e**. The temperature detection unit **108d** is arranged between a liquid discharge element array **103f** and the other end portion (the other long side extending in the X direction) of the substrate **101** in the Y direction.

(29) For example, the discharge ability of the liquid discharge element **123** of the liquid discharge element array **103a** may be adjusted based on the measurement result of the temperature detection element **D1** of the temperature detection unit **108a**. Similarly, the discharge ability of the liquid discharge elements **123** of the liquid discharge element arrays **103b** and **103c** may be adjusted based on the measurement result of the temperature detection element **D1** of the temperature detection unit **108b**. The discharge ability of the liquid discharge elements **123** of the liquid discharge element arrays **103d** and **103e** may be adjusted based on the measurement result of the temperature detection element **D1** of the temperature detection unit **108c**. The discharge ability of the liquid discharge elements **123** of the liquid discharge element array **103f** may be adjusted based on the measurement result of the temperature detection element **D1** of the temperature detection unit **108d**. However, the present disclosure is not limited to this, and it is sufficient to properly adjust the discharge ability of the liquid discharge elements **123** arranged in the liquid discharge element arrays **103a** to **103f** based on the measurement results of the temperature detection elements **D1** arranged in the temperature detection units **108a** to **108d**.

(30) In the arrangement shown in FIG. 5, beams **215** formed integrally with the substrate **101** are arranged at the liquid supply ports **102** in order to arrange the driving wiring pattern **109** in the Y direction at the center of the substrate **101** in the X direction. As a result, each liquid supply port

102 is divided into two at the center of the substrate **101** in the X direction. The liquid supply ports **102** may communicate below the beam **215**. The arrangement of the temperature detection units **108** and an arrangement except the beams **215** through which the driving wiring pattern **109** runs may be similar to those of the above-described liquid discharge head substrate **100**. Here, an arrangement of the liquid discharge head substrate **500** that is different from the liquid discharge head substrate **100** will be mainly explained, and a description of an arrangement that can be similar to the liquid discharge head substrate **100** will be properly omitted.

(31) FIG. **6** is a perspective view showing a section between B-B' in FIG. **5**. Wiring layers including the wiring layers **M1** and **M2** are respectively formed on the substrate **101** together with interlayer films (interlayer insulation films). A similar layer structure is also formed at the beams **215** formed integrally with the substrate. The driving wiring pattern **109** extends in the Y direction using the wiring layer **M2** formed on beams **215a** to **215c**. In a region where the driving wiring pattern **109** is sandwiched between the liquid discharge element arrays **103b** and **103c**, the driving wiring pattern **109** extends in the Y direction between the power supply wiring pattern **111** and the ground wiring pattern **112** for the liquid discharge elements **123** that extend in the X direction from the external connection terminals **106** and **107** arranged in the wiring layer **M2**. In this case, for example, of the power supply wiring patterns **111** and the ground wiring patterns **112**, a power supply wiring pattern **111a** and a ground wiring pattern **112a** arranged between the external connection terminals **106** and the driving wiring pattern **109** can be connected to the external connection terminals **106**. Similarly, of the power supply wiring patterns **111** and the ground wiring patterns **112**, a power supply wiring pattern **111b** and a ground wiring pattern **112b** arranged between the driving wiring pattern **109** and the external connection terminals **107** may be connected to the external connection terminals **107**. The above-mentioned monitoring wiring patterns **113** and **114** may be arranged along the driving wiring pattern **109** using the wiring layer **M2**. FIG. **6** shows a wiring pattern in which only the monitoring wiring pattern **113** is provided. The monitoring wiring pattern **114** can be omitted when the impedance of the ground wiring is designed to be low. Therefore, the monitoring wiring pattern **113** may be connected to one (for example, anode terminal) of two terminals of the temperature detection element **D1**.

(32) In this manner, the driving wiring pattern **109** can be extracted up to an end portion of the substrate **101** in the Y direction while suppressing parallel arrangement of the power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** that extend from the external connection terminals **106** and **107** in the X direction. More specifically, of wiring patterns connected to the temperature detection units **108a** to **108d**, the driving wiring pattern **109** for which the wiring width especially needs to be large runs through the beams **215a** to **215c**. The driving wiring pattern **109** is thus shared between the temperature detection elements **D1** of the plurality of temperature detection units **108** and extracted to an end portion of the substrate **101** in the Y direction. A region for the driving wiring pattern **109** extending in the X direction up to the external connection terminal **106** need not be ensured for each temperature detection unit **108** (temperature detection element **D1**). The widths of the power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** can be increased, increasing the wiring efficiency.

(33) In the embodiment, the driving wiring pattern **109** is formed at the beams **215** provided at the center of the liquid supply port **102** by using the wiring layer **M2**, and wiring in the Y direction is performed while avoiding circuit elements arranged in an underlayer below the wiring layer of the driver circuit **104** and the like. To the contrary, the power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** that are connected to the external connection terminals **106** and **107** extend in the X direction up to the center of the liquid supply port **102**. As described above, the power supply wiring pattern **111** and the ground wiring pattern **112** are divided into the power supply wiring pattern **111a** and ground wiring pattern **112a** connected to the external connection terminals **106**, and the power supply wiring pattern **111b** and

ground wiring pattern **112b** connected to the external connection terminals **107**.

(34) To avoid discharge nonuniformity arising from the impedance of the wiring pattern, the numbers of liquid discharge elements **123** respectively connected to the power supply wiring pattern **111** and the ground wiring pattern **112** may be substantially equal. The driving wiring pattern **109** extending in the Y direction runs through the beams **215** provided at the center of the substrate **101**. Along with this, the power supply wiring patterns **111a** and **111b** and the ground wiring patterns **112a** and **112b** become substantially equal in length in the X direction. The numbers of liquid discharge elements **123** connected to the power supply wiring pattern **111a** and ground wiring pattern **112a** extending from the external connection terminals **106** and the power supply wiring pattern **111b** and ground wiring pattern **112b** extending from the external connection terminals **107** can be substantially equal without requiring any special wiring layer.

(35) Even in the liquid discharge head substrate **500**, similar to the above-described liquid discharge head substrate **100**, the wiring regions of the wiring patterns connected to the liquid discharge elements **123** are not narrowed, and an increase in wiring resistance can be suppressed. This suppresses degradation of the characteristics of the liquid discharge head using the liquid discharge head substrate **500**. By measuring the temperature of the substrate **101** of the liquid discharge head substrate **500** at a plurality of locations, finer control can be performed with respect to a change in the characteristics of the liquid discharge elements **123** by the temperature.

(36) FIG. 7 is a schematic plan view showing an example of the arrangement of a liquid discharge head substrate **700** as a modification of the liquid discharge head substrate **100** shown in FIG. 1 and the liquid discharge head substrate **500** shown in FIG. 5. In the above-described liquid discharge head substrates **100** and **500**, the plurality of temperature detection units **108** (temperature detection elements **D1**) are spaced apart from each other in the Y direction. However, the present disclosure is not limited to this arrangement. An arrangement of the liquid discharge head substrate **700** that is different from the liquid discharge head substrates **100** and **500** will be mainly explained.

(37) In the arrangement shown in FIG. 7, a plurality of beams **215** formed integrally with the substrate **101** are arranged at the liquid supply ports **102** extending in the X direction. The driving wiring pattern **109** runs through beams **215a** out of the plurality of beams **215**.

(38) The temperature detection units **108** include not only the temperature detection units **108** (for example, temperature detection units **108a1** and **108b1**) spaced apart from each other in the Y direction, as in the liquid discharge head substrates **100** and **500**, but also the temperature detection units **108** (for example, the temperature detection unit **108a1** and a temperature detection unit **108a2**) spaced apart from each other in the X direction. In this case, the respective temperature detection elements **D1** arranged in the temperature detection units **108** spaced apart in the X direction may be connected to an extending portion **109a** of the driving wiring pattern **109** that extends in the Y direction. In this case, however, the driving wiring pattern **109** extending in the X direction becomes necessary for each of the temperature detection units **108** spaced apart from each other in the X direction, suppressing a region where the power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** are arranged. One extending portion **109a** of the driving wiring pattern **109** that extends in the Y direction means a portion of the driving wiring pattern **109** that extends continuously in the Y direction and does not include a portion substantially extending in the X direction.

(39) As shown in FIG. 7, the plurality of temperature detection elements **D1** (for example, the temperature detection elements **D1.sub.o** arranged in the temperature detection unit **108a1** to a temperature detection unit **108a4**) spaced apart from each other in the Y direction may be connected to the extending portion **109a** via an extending portion **109b** of the driving wiring pattern **109** that extends in the X direction. The extending portion **109b** of the driving wiring pattern **109** that extends in the X direction means a portion of the driving wiring pattern **109** that extends continuously in the X direction and does not include a portion substantially extending in the Y direction.

(40) The power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** are arranged from the external connection terminals **106** and **107** toward the center of the substrate **101** in the X direction in which the liquid discharge element arrays **103** are aligned. When many liquid discharge elements **123** are simultaneously operated, a flowing current amount can increase in the liquid discharge elements **123** closer to the external connection terminals **106** and **107**. In a region from the ends of the liquid discharge element arrays **103** to the external connection terminals **106**, wiring widths necessary for the power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** can be increased. Also in the arrangement shown in FIG. 7, the driving wiring pattern **109** is arranged in the Y direction through the beams **215** arranged near the centers of the liquid discharge element arrays **103** without running through ends of the liquid discharge element arrays **103** in the X direction with respect to the temperature detection units **108** spaced apart in the Y direction. Further, the temperature detection units **108** spaced apart from each other in the X direction are connected to one extending portion **109b** of the driving wiring pattern **109** that extends in the X direction. The driving wiring pattern **109** can be extracted up to the external connection terminal **106** by using a prospective redundant region at an end portion of the substrate **101** in the Y direction, similar to the above-described liquid discharge head substrates **100** and **500**. Even in the liquid discharge head substrate **700** shown in FIG. 7, the wiring widths of the power supply wiring pattern **111** and ground wiring pattern **112** for the liquid discharge elements **123** can be increased, increasing the wiring efficiency. That is, even in the liquid discharge head substrate **700**, similar to the above-described liquid discharge head substrates **100** and **500**, the wiring regions of the wiring patterns connected to the liquid discharge elements **123** are not narrowed, and an increase in wiring resistance can be suppressed. This suppresses degradation of the characteristics of the liquid discharge head using the liquid discharge head substrate **700**. By measuring the temperature of the substrate **101** of the liquid discharge head substrate **700** at a plurality of locations, finer control can be performed with respect to a change in the characteristics of the liquid discharge elements **123** by the temperature.

(41) FIG. 8 is a schematic plan view showing an example of the arrangement of a liquid discharge head substrate **800** as a modification of the above-described liquid discharge head substrates **100**, **500**, and **700**. In the liquid discharge head substrates **100**, **500**, and **700**, the respective temperature detection elements **D1** arranged in the plurality of temperature detection units **108** are connected to one extending portion **109a** of the driving wiring pattern **109** that extends in the Y direction. However, the present disclosure is not limited to this. An arrangement of the liquid discharge head substrate **800** that is different from the liquid discharge head substrates **100**, **500**, and **700** will be mainly explained.

(42) In the above-described liquid discharge head substrates **100**, **500**, and **700**, the external connection terminals **106** and **107** are arranged in the Y direction at two ends of the substrate **101** in the X direction serving as a longitudinal direction. In contrast, in the liquid discharge head substrate **800** shown in FIG. 8, external connection terminals **306** are arranged in the X direction at one end of the substrate **101** in the Y direction serving as a widthwise direction.

(43) The liquid supply ports **102** of two arrays are provided for one liquid discharge element array **103**. For example, liquid supply ports **102a1** and **102a2** spaced apart from each other in the Y direction are arranged for the liquid discharge element array **103a**. The liquid supply port **102** is divided by the beams **215** into a plurality of openings passing through the substrate **101**.

(44) In the arrangement shown in FIG. 8, the three liquid discharge element arrays **103a** to **103c** formed from the plurality of liquid discharge elements **123** aligned in the X direction are arranged on the substrate **101**. The plurality of temperature detection units **108a1** to **108a4** each including the temperature detection element **D1** are arranged in correspondence with the liquid discharge element array **103a**. Similarly, pluralities of temperature detection units **108b1** to **108b4** and **108c1** to **108c4** each including the temperature detection element **D1** are arranged in correspondence with the liquid discharge element arrays **103b** and **103c**.

(45) Also in the arrangement shown in FIG. 8, the control circuit **105** for controlling the driver circuit **104** and the temperature detection units **108** is arranged adjacent to the driver circuit **104**. The control circuit **105a** can be arranged in correspondence with a driver circuit **104a** and the temperature detection units **108a1** to **108a4**. Similarly, the control circuits **105b** and **105c** can be arranged in correspondence with driver circuits **104b** and **104c** and the temperature detection units **108b1** to **108b4** and **108c1** to **108c4**.

(46) Of the temperature detection units **108**, the temperature detection units **108a1**, **108b1**, and **108c1** that are arranged at substantially the same position in the X direction and spaced apart from each other in the Y direction are connected to an extending portion **109c** of the driving wiring pattern **109** that extends in the Y direction. Of the temperature detection units **108**, the temperature detection units **108a2**, **108b2**, and **108c2** that are arranged at substantially the same position in the X direction and spaced apart from each other in the Y direction are connected to an extending portion **109d** of the driving wiring pattern **109** that extends in the Y direction. Of the temperature detection units **108**, the temperature detection units **108a3**, **108b3**, and **108c3** that are arranged at substantially the same position in the X direction and spaced apart from each other in the Y direction are connected to an extending portion **109e** of the driving wiring pattern **109** that extends in the Y direction. Of the temperature detection units **108**, the temperature detection units **108a4**, **108b4**, and **108c4** that are arranged at substantially the same position in the X direction and spaced apart from each other in the Y direction are connected to an extending portion **109f** of the driving wiring pattern **109** that extends in the Y direction. The extending portions **109c** to **109f** of the driving wiring pattern **109** are connected by a portion of the driving wiring pattern **109** that extends in the X direction. Of the temperature detection elements **D1** respectively arranged in the plurality of temperature detection units **108**, temperature detection elements (for example, temperature detection elements **D10** respectively arranged in the temperature detection units **108a1**, **108b1**, and **108c1**) that are arranged at substantially the same position in the X direction and spaced apart in the Y direction are connected to one extending portion (for example, an extending portion **109c0**) of the driving wiring pattern **109** that extends in the Y direction. Of the temperature detection elements **D1** respectively arranged in the temperature detection units **108**, temperature detection elements (for example, temperature detection elements **D10** respectively arranged in the temperature detection units **108a1**, **108a2**, **108a3**, and **108a4**) spaced apart from each other in the X direction are connected to the different extending portions (for example, the extending portions **109c**, **109d**, **109e**, and **109f**) of the driving wiring pattern **109** that extend in the Y direction.

(47) The beams **215** provided at the liquid supply ports **102** are regions between the openings of the liquid supply ports **102** that are densely arranged in the X direction and pass through the substrate **101**. In other words, a region between the liquid supply ports **102** (for example, between the liquid supply ports **102a1** and **102a2**) that are spaced apart in the Y direction to supply a liquid to one liquid discharge element array **103** is not the beam **215**. Similarly, a region between the liquid supply ports **102** (for example, between the liquid supply ports **102a2** and **102b1**) that supply a liquid to the different liquid discharge element arrays **103** is not the beam **215**.

(48) FIG. 9 is a view showing an example of the arrangement of a wiring pattern in the Y direction in a region C surrounded by a dotted line in FIG. 8. As shown in FIG. 8, the substrate **101** includes the external connection terminals **306** on the lower side in FIG. 9. The power supply wiring patterns **111** and ground wiring patterns **112** for the liquid discharge elements **123** are formed to run through the beams **215** and extend in the Y direction by using the wiring layer M2 together with the power supply wiring patterns **117** and ground wiring patterns **118** for the control circuits **105**. The power supply wiring patterns **111** and **117** and the ground wiring patterns **112** and **118** reach an end portion of the substrate **101** in the Y direction on a side opposite to the external connection terminals **306**. These wiring patterns are connected through conductive members arranged via the wiring layer M1 at a plurality of portions in the substrate **101**, and extend in the X direction in the wiring layer M1, forming a mesh-like power supply plane. To prevent an increase in the wiring

resistances of the power supply wiring patterns **111** and ground wiring patterns **112** while arranging many temperature detection units **108**, it is effective to reduce a wiring area necessary for the driving wiring pattern **109** of the temperature detection units **108**.

(49) As shown in FIG. **9**, the temperature detection elements **D1** arranged in the plurality of temperature detection units **108** (temperature detection units **108a2**, **108b2**, and **108c2**) aligned in the Y direction share one extending portion (extending portion **109d**) of the driving wiring pattern **109** that extends in the Y direction. Compared to a case in which the driving wiring pattern **109** is individually connected to the temperature detection element **D1**, a region necessary for the driving wiring pattern **109** can be suppressed, and as a result the wiring efficiencies of the power supply wiring patterns **111** and **117** and ground wiring patterns **112** and **118** can be increased. Even in the liquid discharge head substrate **800**, similar to the above-described liquid discharge head substrates **100**, **500**, and **700**, the wiring regions of the wiring patterns connected to the liquid discharge elements **123** are not narrowed, and an increase in wiring resistance can be suppressed. As a result, this suppresses degradation of the characteristics of the liquid discharge head using the liquid discharge head substrate **800**. By measuring the temperature of the substrate **101** of the liquid discharge head substrate **800** at a plurality of locations, finer control can be performed with respect to a change in the characteristics of the liquid discharge elements **123** by the temperature.

(50) In the liquid discharge head substrate **800**, the substrate **101** is often configured to be long in the X direction in terms of increasing the width by which printing is possible at once, in other words, the width of the liquid discharge element array **103**. That is, extracting the driving wiring pattern **109** of the temperature detection elements **D1** in the X direction leads to an increase in the area of the driving wiring pattern **109**. When the driving wiring pattern **109** is arranged in the Y direction through the plurality of beams **215** provided at the liquid supply ports **102** as in the arrangement shown in FIGS. **8** and **9**, a portion of the driving wiring pattern **109** that extends in the X direction can be reduced in comparison with, for example, the arrangement shown in FIG. **7**. Hence, the liquid discharge head substrate **800** shown in FIGS. **8** and **9** can reduce an area necessary for the driving wiring pattern **109** in the entire substrate **101**. The monitoring wiring patterns **113** and **114** can also be connected to the temperature detection elements **D1** respectively arranged in the plurality of temperature detection units **108** by using an arrangement similar to that of the driving wiring pattern **109**. Even in FIG. **9**, the monitoring wiring patterns **113** and **114** are arranged parallel to the driving wiring pattern **109**.

(51) FIG. **10** is an equivalent circuit diagram showing an example of the connection relationship between the temperature detection unit **108** and the driving wiring pattern **109** in the liquid discharge head substrate **800**. In the temperature detection unit **108**, an output from a decoding unit **322** is commonly input to the switching elements **NM1**, **NM2**, and **NM3** via a wiring pattern **321**. The decoding unit **322** receives inputs from a control wiring pattern **318** for selecting the temperature detection units **108** aligned in the X direction out of the temperature detection units **108**, and a control wiring pattern **319** for selecting the temperature detection units **108** aligned in the Y direction, and generates a control signal. The decoding unit **322** can be constituted using, for example, a combinational circuit such as an AND circuit. In the temperature detection unit **108** shown in FIG. **10**, an arrangement other than that regarding the decoding unit **322** may be similar to the temperature detection unit **108** shown in FIG. **4** described above, and a description of the arrangement that may be similar will be properly omitted.

(52) FIG. **11** is a schematic plan view showing an example of the arrangement of the control wiring patterns **318** and **319** of the liquid discharge head substrate **800**. The arrangement of the liquid supply ports **102**, liquid discharge element arrays **103**, driving wiring pattern **109**, and the like is similar to the arrangement described above with reference to FIGS. **8** and **9**.

(53) In the embodiment, the control circuit **105** has the function of a heater logic circuit for supplying a control signal to the driver circuit **104** that drives the respective liquid discharge elements **123** arranged in the liquid discharge element array **103**, and the function of the column

control circuit of the temperature detection unit **108**. The control circuit **105a** controls, via a control wiring pattern **318a** in accordance with a signal input from an external connection terminal **306c**, activation/non-activation of the temperature detection units **108a1** to **108a4** aligned and spaced apart in the column direction. The control circuit **105b** controls, via a control wiring pattern **318b** in accordance with a signal input from an external connection terminal **306d**, activation/non-activation of the temperature detection units **108b1** to **108b4** aligned and spaced apart in the column direction. The control circuit **105c** controls, via a control wiring pattern **318c** in accordance with a signal input from an external connection terminal **306e**, activation/non-activation of the temperature detection units **108c1** to **108c4** aligned and spaced apart in the column direction.

(54) A control circuit **320** is connected to control wiring patterns **319a** to **319d** and controls, in accordance with an input from an external connection terminal **306b**, activation/non-activation of the temperature detection units **108** aligned and spaced apart in the row direction. The control circuits **105** and **320** include one or more circuits to control, separately for the row and the column, the plurality of temperature detection units **108** (temperature detection elements **D1**) respectively provided along the liquid discharge element arrays **103**, and exclusively connect the temperature detection elements **D1** to the driving wiring pattern **109**.

(55) In the liquid discharge head substrate **800**, the beams **215** through which the driving wiring pattern **109** runs, and the beams **215** through which the driving wiring pattern **109** does not run are arranged. As the beams **215** through which the control wiring pattern **319** runs, the beams **215** different from the beams **215** through which the driving wiring pattern **109** and the monitoring wiring patterns **113** and **114** run can be used. Even when a logical signal flowing through the control wiring pattern **319** is frequently switched to perform measurement, the influence of switching noise on the driving wiring pattern **109** and the monitoring wiring patterns **113** and **114** can be suppressed. As a result, an output from the temperature detection unit **108** can be monitored at high precision.

(56) By selecting temperature detection elements using the control wiring patterns **318** extending in the X direction, the number of control wiring patterns **318** extending in the Y direction can be suppressed in comparison with a case in which all the control wiring patterns **318** extend in the Y direction. More specifically, this will be explained by exemplifying the control circuit **105a** that controls the switching elements **NM1** arranged between the control wiring pattern **318a** and the temperature detection elements **D1** arranged in the temperature detection units **108a1** to **108a4** aligned and spaced apart in the X direction. With the above-described arrangement, the control circuit **105** turns on or off, at the same timing as that of the switching element **NM1**, the switching elements **NM2** and **NM3** arranged in the same temperature detection unit **108** as that of the switching element **NM1**. In this case, when the control wiring patterns **318** are arranged individually for the respective temperature detection units **108a1** to **108a4**, the number of control wiring patterns **318** extending in the Y direction is four. To the contrary, as shown in FIG. **11**, the switching elements **NM1** arranged between the control wiring pattern **318a** and the temperature detection elements **D1** arranged in the temperature detection units **108a1** to **108a4** are connected to an extending portion **318a1** extending in the X direction out of the control wiring pattern **318a** for respectively selecting the switching elements **NM1** (and the switching elements **NM2** and **NM3**) arranged in the temperature detection units **108a1** to **108a4**. The control wiring pattern **318a** thus includes an extending portion **318a2** as a portion extending parallel to the liquid supply ports **102a1** and **102a2** and the liquid discharge element array **103a** constituted by the plurality of liquid discharge elements **123** in the Y direction. The liquid supply ports **102a1** and **102a2** that supply a liquid to the liquid discharge element array **103a** are spaced apart in the Y direction with respect to the liquid discharge element array **103a**.

(57) The dimensions of the substrate **101** of the liquid discharge head substrate **800** are restricted more in the Y direction than in the X direction under restrictions such as the interval of the liquid discharge elements **123** and the like. Therefore, the arrangement shown in FIG. **11** can suppress the

number of control wiring patterns **318** extending in the Y direction. As a result, this can increase the wiring efficiencies of the power supply wiring patterns **111** and **117** and ground wiring patterns **112** and **118** extending in the Y direction.

(58) The temperature detection elements **D1** arranged in the temperature detection units **108** are controlled using the control wiring patterns **318** extending mainly in the X direction and the control wiring patterns **319** extending mainly in the Y direction. The numbers of control wiring patterns **318** and **319** necessary to control the temperature detection units **108** can be minimized. That is, the areas of regions necessary for the control wiring patterns **318** and **319** can be reduced, increasing the wiring efficiencies of the power supply wiring patterns **111** and **117** and ground wiring patterns **112** and **118**.

(59) As shown in FIG. **11**, a logical signal flowing through the control wiring pattern **318** is controlled using the control circuit **105**. In this manner, the control circuit **105** has the function of a heater logic circuit for driving the liquid discharge elements **123** via the driver circuits **104**, and the function of the column control circuit of the temperature detection unit **108**. This arrangement enables sharing a data input between the heater logic circuit and the column control circuit of the temperature detection unit **108**. Thus, the number of external connection terminals **306** can be reduced.

(60) In the liquid discharge head substrate **800**, the liquid supply ports **102** and the liquid discharge element arrays **103** are arranged between the temperature detection units **108** and the driver circuits **104**. For example, the liquid discharge element array **103a** and the liquid supply ports **102a1** and **102a2** are arranged between the driver circuit **104a** that drives the liquid discharge element array **103a** constituted by the liquid discharge elements **123** under the control of the control circuit **105a**, and the temperature detection units **108a1** to **108a4** which are controlled by the control circuit **105a** and includes the temperature detection elements **D1**. In terms of reducing the parasitic resistance, the driver circuit **104** can be arranged as closest to the liquid discharge element array **103** as possible. The temperature detection unit **108** (temperature detection element **D1**) needs to measure a temperature of the substrate **101** near the liquid discharge element array **103** while avoiding the influence of the driver circuit **104**. With the arrangement as shown in FIG. **11**, the temperature detection unit **108** is arranged near the corresponding liquid discharge element array **103** and apart from the driver circuit **104** that drives the corresponding liquid discharge element array **103**. The temperature of the substrate **101** can be detected at higher precision, improving the characteristic of discharging a liquid from the liquid discharge head substrate **800**.

(61) In the arrangement shown in FIG. **11**, one control circuit **105** is used to control all the temperature detection units **108** corresponding to one liquid discharge element array **103**, but the present disclosure is not limited to this example. For example, two control circuits **105** may be used to control the temperature detection units **108** corresponding to one liquid discharge element array **103**.

(62) A liquid discharge apparatus using the above-described liquid discharge head substrate **100**, **500**, **700**, or **800** will be explained with reference to FIGS. **12A** to **12D**. FIG. **12A** exemplifies the internal arrangement of a liquid discharge apparatus **1600** typified by an inkjet printer, a facsimile apparatus, or a copying machine. In this example, the liquid discharge apparatus may also be called a printing apparatus. The liquid discharge apparatus **1600** includes a liquid discharge head **1510** that discharges a liquid (in this example, ink or a printing material) to a predetermined medium **P** (in this example, a printing medium such as paper). In this example, the liquid discharge head may also be called a record head. The liquid discharge head **1510** is mounted on a carriage **1620**, and the carriage **1620** can be attached to a lead screw **1621** having a helical groove **1604**. The lead screw **1621** can rotate in synchronization with rotation of a driving motor **1601** via driving force transmission gears **1602** and **1603**. The liquid discharge head **1510** can move in a direction indicated by an arrow **a** orb along a guide **1619** together with the carriage **1620**.

(63) The medium **P** is pressed by a paper press plate **1605** in the carriage moving direction and

fixed to a platen **1606**. The liquid discharge apparatus **1600** performs liquid discharge (in this example, printing) to the medium P conveyed on the platen **1606** by a conveyance unit (not shown) by reciprocating the liquid discharge head **1510**.

(64) The liquid discharge apparatus **1600** confirms the position of a lever **1609** provided on the carriage **1620** via photocouplers **1607** and **1608**, and switches the rotational direction of the driving motor **1601**. A support member **1610** supports a cap member **1611** for covering the nozzle (liquid orifice or simply orifice) of the liquid discharge head **1510**. A suction portion **1612** performs recovery processing of the liquid discharge head **1510** by sucking the interior of the cap member **1611** via an intra-cap opening **1613**. A lever **1617** is provided to start recovery processing by suction, and moves along with movement of a cam **1618** engaged with the carriage **1620**. A driving force from the driving motor **1601** is controlled by a well-known transmission mechanism such as a clutch switch.

(65) A main body support plate **1616** supports a moving member **1615** and a cleaning blade **1614**. The moving member **1615** moves the cleaning blade **1614** to perform recovery processing of the liquid discharge head **1510** by wiping. The liquid discharge apparatus **1600** includes a controller (not shown) and the controller controls driving of each mechanism described above.

(66) FIG. 12B exemplifies the outer appearance of the liquid discharge head **1510**. The liquid discharge head **1510** can include a head portion **1511** having a plurality of nozzles **1500**, and a tank (liquid storage portion) **1512** that holds a liquid to be supplied to the head portion **1511**. The tank **1512** and the head portion **1511** can be separated at, for example, a broken line K and the tank **1512** is interchangeable. The liquid discharge head **1510** has an electrical contact (not shown) for receiving an electrical signal from the carriage **1620** and discharges a liquid in accordance with the electrical signal. The tank **1512** has a fibrous or porous liquid holding member (not shown) and the liquid holding member can hold a liquid.

(67) FIG. 12C exemplifies the internal arrangement of the liquid discharge head **1510**. The liquid discharge head **1510** includes a base **1508**, flow path wall members **1501** that are arranged on the base **1508** and form flow paths **1505**, and a top plate **1502** having a liquid supply path **1503**. The base **1508** may be either of the above-described liquid discharge head substrates **100**, **500**, **700**, and **800**. As discharge elements or liquid discharge elements, heaters **1506** (to be also referred to as electrothermal transducers or heat generating resistive elements) are arrayed on the substrate (liquid discharge head substrate) of the liquid discharge head **1510** in correspondence with the respective nozzles **1500**. Each heater **1506** is driven to generate heat by turning on a driving element (switching element such as a transistor) provided in correspondence with the heater **1506**.

(68) A liquid from the liquid supply path **1503** is stored in a common liquid chamber **1504** and supplied to each nozzle **1500** via the corresponding flow path **1505**. The liquid supplied to each nozzle **1500** is discharged from the nozzle **1500** in response to driving of the heater **1506** corresponding to the nozzle **1500**.

(69) FIG. 12D exemplifies the system arrangement of the liquid discharge apparatus **1600**. The liquid discharge apparatus **1600** includes an interface **1700**, a MPU **1701**, a ROM **1702**, a RAM **1703**, and a gate array (G.A.) **1704**. The interface **1700** receives from the outside an external signal for executing liquid discharge. The ROM **1702** stores a control program to be executed by the MPU **1701**. The RAM **1703** saves various signals and data such as the above-mentioned external signal for liquid discharge and data supplied to the liquid discharge head **1708**. The gate array **1704** performs supply control of data to the liquid discharge head **1708** and control of data transfer between the interface **1700**, the MPU **1701**, and the RAM **1703**.

(70) The liquid discharge apparatus **1600** further includes a head driver **1705**, motor drivers **1706** and **1707**, a conveyance motor **1709**, and a carrier motor **1710**. The carrier motor **1710** conveys a liquid discharge head **1708**. The conveyance motor **1709** conveys the medium P. The head driver **1705** drives the liquid discharge head **1708**. The motor drivers **1706** and **1707** drive the conveyance motor **1709** and the carrier motor **1710**, respectively.

(71) When a driving signal is input to the interface **1700**, it can be converted into data for liquid discharge between the gate array **1704** and the MPU **1701**. Each mechanism performs a desired operation in accordance with this data. In this manner, the liquid discharge head **1708** is driven.

(72) While the present disclosure has been described with reference to exemplary embodiments, it is to be understood that the disclosure is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(73) This application claims the benefit of Japanese Patent Application No. 2022-063544, filed Apr. 6, 2022, which is hereby incorporated by reference herein in its entirety.

Claims

1. A liquid discharge head substrate comprising: a substrate; a plurality of liquid discharge elements arranged in a first direction on a major surface of the substrate to discharge a liquid; a liquid supply port provided in the substrate and spaced apart from the plurality of liquid discharge elements in a second direction crossing the first direction to supply the liquid to the plurality of liquid discharge elements; a plurality of temperature detection elements arranged on the substrate to detect a temperature of the substrate; and a driving wiring pattern that extends in the second direction to drive the plurality of temperature detection elements, wherein the driving wiring pattern extends to an end portion of the substrate in the second direction, is connected to an external connection terminal, and is shared between the plurality of temperature detection elements, wherein each of the plurality of temperature detection elements is connected to one extending portion of the driving wiring pattern that extends in the second direction, wherein the plurality of temperature detection elements includes a first temperature detection element and a second temperature detection element that are spaced apart from each other in the first direction, and includes a third temperature detection element that is spaced apart from the first temperature detection element in the second direction, wherein each of the plurality of temperature detection elements is connected to the driving wiring pattern via a switching element, and wherein, of a plurality of switching elements, a first switching element is arranged between the first temperature detection element and the driving wiring pattern, and a second switching element is arranged between the second temperature detection element and the driving wiring pattern and the first switching element and the second switching element are connected to an extending portion that extends in the first direction, out of a control wiring pattern for selecting the first switching element and the second switching element.
2. The liquid discharge head substrate according to claim 1, wherein at least one of two terminals of each of the plurality of temperature detection elements is connected to a monitoring wiring pattern.
3. The liquid discharge head substrate according to claim 1, wherein the one extending portion is a first extending portion, and the first temperature detection element and the second temperature detection element are connected to the first extending portion via a second extending portion of the driving wiring pattern that extends in the first direction.
4. The liquid discharge head substrate according to claim 1, wherein of the control wiring pattern, a portion extending in the second direction in parallel with the plurality of liquid discharge elements and the liquid supply port is one.
5. The liquid discharge head substrate according to claim 1, further comprising a control circuit configured to control the first switching element and the second switching element via the control wiring pattern.
6. The liquid discharge head substrate according to claim 5, wherein the control circuit is configured to control driving of the plurality of liquid discharge elements.
7. The liquid discharge head substrate according to claim 5, further comprising a driver circuit configured to drive the plurality of liquid discharge elements under control of the control circuit, wherein the plurality of liquid discharge elements and the liquid supply port are arranged between

the first temperature detection elements and the second temperature detection elements, and the driver circuit.

8. The liquid discharge head substrate according to claim 1, wherein the plurality of temperature detection elements includes a first temperature detection element and a second temperature detection element that are spaced apart from each other in the first direction, and includes a third temperature detection element that is spaced apart from the first temperature detection element in the second direction, wherein the first temperature detection element and the third temperature detection element are connected to a first extending portion of the driving wiring pattern that extends in the second direction, and wherein the second temperature detection element is connected to a second extending portion of the driving wiring pattern that extends in the second direction and is different from the first extending portion.

9. The liquid discharge head substrate according to claim 1, wherein a plurality of beams formed integrally with the substrate are arranged at the liquid supply port, and wherein, of the plurality of beams, a beam through which the driving wiring pattern runs, and a beam through which a wiring pattern for controlling the switching element runs are different from each other.

10. The liquid discharge head substrate according to claim 1, wherein a beam formed integrally with the substrate is arranged at the liquid supply port, and the driving wiring pattern runs through the beam.

11. The liquid discharge head substrate according to claim 1, wherein a plurality of beams formed integrally with the substrate are arranged at the liquid supply port, and the driving wiring pattern runs through at least two beams of the plurality of beams.

12. A liquid discharge head comprising: the liquid discharge head substrate according to claim 1; and an orifice for which discharge of a liquid is controlled by the liquid discharge head substrate.

13. A liquid discharge apparatus comprising: a liquid discharge head having the liquid discharge head substrate according to claim 1, and an orifice for which discharge of a liquid is controlled by the liquid discharge head substrate; and a unit configured to supply a driving signal for discharging a liquid from the liquid discharge head.
