

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12409786

Kind Code

B2

Date of Patent

September 09, 2025

Inventor(s)

Leblanc; Etienne et al.

Mounting clamp, accessory for vehicle having mounting clamp and accessory kit

Abstract

Mounting clamps for coupling an accessory to a structure are disclosed. The mounting clamp includes a body configured to engage the accessory and to receive a portion of the structure, a jaw and an actuator. The jaw has a first member pivotally to the body by a first pivot that is selectively moveable, and a second member pivotally connected to the first member by a second pivot. When the first pivot is in a first position, the mounting clamp is in a first configuration adapted for clamping to a first portion of a first structure. When the first pivot is in a second position, the mounting clamp is in a second configuration adapted for clamping to a second portion of a second structure. The jaw, which is selectively adjustable between open and closed positions, is configured to clamp one of the first and second portions when in the closed position.

Inventors: Leblanc; Etienne (Becancour, CA), Roy; Normand (St-Hugues, CA), Frenette-Marcoux; Jonathan (Drummondville, CA), Charrette; Michael (St-Felix de Kingsey, CA), Lemelin; Manuel (St-Hyacinthe, CA)

Applicant: SOUCY INTERNATIONAL INC. (Drummondville, CA)

Family ID: 87890080

Assignee: SOUCY INTERNATIONAL INC. (Drummondville, CA)

Appl. No.: 18/120233

Filed: March 10, 2023

Prior Publication Data

Document Identifier

Publication Date

US 20230286114 A1

Sep. 14, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: **F16B2/18** (20060101); **B60R7/08** (20060101); **B60R11/00** (20060101); B60R11/04 (20060101); B60R11/06 (20060101); F16B2/10 (20060101)

U.S. Cl.:

CPC **B60R7/08** (20130101); **F16B2/18** (20130101); B60R11/00 (20130101); B60R11/04 (20130101); B60R11/06 (20130101); F16B2/10 (20130101)

Field of Classification Search

CPC: B60R (2011/0059); F16B (2/10); F16B (2/18); F16B (2/185)

USPC: 224/558; 248/230.4; 248/231.51

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3165347	12/1964	Keskitalo	N/A	N/A
3165348	12/1964	Keskitalo	N/A	N/A
3428306	12/1968	Harrison	N/A	N/A
3514091	12/1969	Johnson et al.	N/A	N/A
4213589	12/1979	Kirchgaesser et al.	N/A	N/A
4312488	12/1981	Pierron	N/A	N/A
4629104	12/1985	Jacquet	N/A	N/A
4860980	12/1988	Michot	N/A	N/A
5259690	12/1992	Legge	N/A	N/A
5419479	12/1994	Evels et al.	N/A	N/A
7819448	12/2009	Bates	294/104	B66C 1/48
8021169	12/2010	Smith	N/A	N/A
8038106	12/2010	Magno, Jr.	248/65	H02G 3/32
8085481	12/2010	Hill	N/A	N/A
8292139	12/2011	Golub	224/558	B62J 7/08
8728078	12/2013	Miller	N/A	N/A
9545835	12/2016	Facchinello et al.	N/A	N/A
10166849	12/2018	Facchinello	N/A	B60J 7/106
10436232	12/2018	Burnett	N/A	B25B 5/04
10753513	12/2019	Jung	N/A	N/A
2003/0080267	12/2002	Eslick	N/A	N/A
2004/0211801	12/2003	Barbara	N/A	N/A
2007/0012738	12/2006	Grim	N/A	N/A
2015/0108306	12/2014	Chuang	248/231.51	F16M 11/14
2016/0296401	12/2015	Cole et al.	N/A	N/A
2021/0388864	12/2020	Reymond	N/A	N/A
2023/0286114	12/2022	Leblanc	N/A	B60R 7/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2010260146	12/2013	AU	N/A
108025679	12/2017	CN	N/A
0656501	12/1994	EP	N/A
2701070	12/1993	FR	N/A
3062689	12/2017	FR	N/A
1272342	12/1971	GB	N/A
H06207461	12/1993	JP	N/A
1006117	12/1997	NL	N/A

OTHER PUBLICATIONS

English abstract of NL1006117 retrieved from Espacenet on May 14, 2024. cited by applicant
English abstract of CN108025679 retrieved from Espacenet on May 14, 2024. cited by applicant
English abstract of FR2701070 retrieved from Espacenet on May 14, 2024. cited by applicant
English abstract of FR3062689 retrieved from Espacenet on May 14, 2024. cited by applicant
English abstract of JPH06207461 retrieved from Espacenet on May 14, 2024. cited by applicant

Primary Examiner: Larson; Justin M

Attorney, Agent or Firm: BCF LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) The present application claims priority to U.S. Provisional Patent Application No. 63/318,893, filed Mar. 3, 2022 entitled “Mounting Clamp, Accessory For Vehicle Having Mounting Clamp And Accessory Kit”, which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) The present technology relates to mounting clamps, accessories for vehicles having mounting clamps, and accessory kits.

BACKGROUND

(2) Mounting clamps are used to couple one or more accessories to various structures. In some instances, mounting clamps can be connected to structures of vehicles for coupling accessories to vehicles.

(3) Conventional mounting clamps are generally “size specific”, (i.e., configured to connect to a structure having a given size). This can be problematic when there is a desire for using the mounting clamp on different structures having different sizes or on a given structure having members of different sizes, as more than one type of “size specific” mounting clamps may be required to attach to these structures.

(4) Other mounting clamps that can connect to various sizes of structure members are known. However, the clamping force applied by these other mounting clamps can vary depending on the size of the structure upon which the mounting clamp is clamped or depending on the force that a user applies to the mounting clamp. In some instances, this can result in an accessory being mounted with a weak clamping force which can result in an unsafe attachment. In other instances, this can result in an accessory being mounted with an excessive clamping force which can damage the structure, the accessory and/or the mounting clamp.

(5) Additionally, conventional mounting clamps can be time consuming to connect and disconnect to given structures, sometimes requiring tools for installing and/or removing fasteners. In addition, conventional mounting clamps that are adjustable to different sizes of structure members can typically require manual adjustments, sometimes with a tool, that are arbitrary (i.e., not pre-determined adjustment positions) and thus not necessarily resulting to an optimized and constant clamping condition for a given specific size of structure member.

(6) Therefore, there is a desire for a device that can mitigate the above-mentioned issues.

SUMMARY

(7) It is an object of the present technology to ameliorate at least some of the inconveniences present in the prior art.

(8) According to one aspect of the present technology, there is provided a mounting clamp for coupling an accessory to a structure. The mounting clamp includes a body, a jaw and an actuator. The body has a mounting interface configured to engage the accessory. The body also has a coupling portion configured to selectively at least partially receive one of a first structure member and a second structure member, the first and second structure members having different sizes. The jaw is selectively adjustable between an open position and a closed position. The jaw includes a first member and a second member. The first member is pivotally connected to the body by a first pivot selectively movable between a first position and a second position. The second member is pivotally connected to the first member by a second pivot. The actuator is pivotally connected to the second member of the jaw by a third pivot, and is pivotally connected to the body by a fourth pivot. In response to the first pivot being moved to the first position, the mounting clamp is in a first configuration adapted for clamping to the first structure member. In response to the first pivot being moved to the second position, the mounting clamp is in a second configuration adapted for clamping to the second structure member. The jaw is configured to clamp one of the first portion of the first structure and the second portion of the second structure in response to being adjusted to the closed position.

(9) In some embodiments, the first position is a first predetermined position and the second position is a second predetermined position.

(10) In some embodiments, in response to actuating the actuator, the second pivot pivots about to the first pivot, and the jaw moves between the opened and closed positions.

(11) In some embodiments, the second, third and fourth pivots are configured to provide an overcenter effect when the jaw is in the closed position.

(12) In some embodiments, the actuator includes a lever.

(13) In some embodiments, when the mounting clamp is in the first configuration and the jaw is in the closed position, the jaw is configured to clamp the first structure member with a first clamping force, and when the mounting clamp is in the second configuration, and the jaw is in the closed position, the jaw is configured to clamp the second structure member with a second clamping force. The first clamping force is generally similar to the second clamping force in terms of magnitude.

(14) In some embodiments, when the first pivot is in one of the first and second positions, the first pivot is disposed on a border of a virtual circle, a virtual center of the virtual circle being generally aligned with the second pivot when the jaw is in the closed position.

(15) In some embodiments, when the mounting clamp is in the first configuration and the jaw is in the closed position, the jaw is configured to clamp the first structure member with a first clamping force, and when the mounting clamp is in the second configuration, and the jaw is in the closed position, the jaw is configured to clamp the second structure member with a second clamping force. The first clamping force is generally similar to the second clamping force in terms of orientation.

(16) In some embodiments, the first member has an angled portion, and a virtual bisector line passing through the angled portion is generally parallel to a virtual line passing through the first and second pivots.

(17) In some embodiments, the angled portion is a v-shaped portion.

- (18) In some embodiments, the body has a guide configured to at least partially receive the first pivot, and to guide the first pivot between the first and second positions.
- (19) In some embodiments, the guide is a guiding slot.
- (20) In some embodiments, the guide is arcuate.
- (21) In some embodiments, the guide defines a first recess and a second recess spaced from the first recess, the first pivot is in the first position when the first pivot is in the first recess, and the first pivot is in the second position when the first pivot is in the second recess.
- (22) In some embodiments, the mounting clamp further includes a retaining member selectively moveable between a third position and a fourth position. The retaining member is configured to retain the first pivot in the first position when the retaining member is in the third position, and retain the first pivot in the second position when the retaining member is in the fourth position.
- (23) In some embodiments, the body defines a recess configured to at least partially receive the retaining member, the retaining member being moveable within the recess between the third and fourth positions.
- (24) In some embodiments, the mounting clamp, further includes a resilient member operatively connected to the body and to the first pivot, the resilient member biasing the first pivot toward one of the first and second positions.
- (25) In some embodiments, the mounting clamp further includes a resilient member operatively connected to the body and to the first pivot, the resilient member biasing the first pivot toward the first position. In response to one of the first and second structure members being at least partially received into the coupling portion, the mounting clamp being biased to move to a corresponding one of the first and second configurations. In response to the jaw being adjusted to the closed position, the jaw clamping the one of the first and second structure members.
- (26) In some embodiments, the mounting clamp is a self-adjusting clamp.
- (27) In some embodiments, the first structure member defines a first arc having a first arc radius, the second structure member defines a second arc having a second arc radius, and the first arc radius is greater than the second arc radius.
- (28) In some embodiments, one of the first and second radii is one of $\frac{3}{8}$ ", $\frac{7}{16}$ ", $\frac{1}{2}$ ", $\frac{3}{8}$ ", $\frac{15}{16}$ " and $1\frac{1}{4}$ ".
- (29) In some embodiments, the coupling portion defines a first arcuate section having a first arc radius complementary to the first arc radius, and a second arcuate section having a second arc radius complementary to the second arc radius.
- (30) In some embodiments, the first pivot is selectively movable between the first position, the second position and a fifth position.
- (31) In some embodiments, in response to the first pivot being moved to the fifth position, the mounting clamp is in a third configuration adapted for clamping to a third structure member, and the third structure member defines a third arc having a third arc radius, the third arc radius being different from the first and second arc radii.
- (32) In some embodiments, the fifth position is disposed on the virtual center.
- (33) In some embodiments, the accessory is one of: a bag, a case, a rack, a storage bin, a gas tank, a gun case, a toolbox, a camera, a chainsaw, and a shovel.
- (34) In some embodiments, the structure is on a vehicle.
- (35) In some embodiments, the vehicle is a powersports vehicle.
- (36) In another aspect of the present technology, there is provided an accessory for a vehicle having a mounting clamp according to the above aspect or according to the above aspect and one or more of the above embodiments.
- (37) In some embodiments, the accessory and the at least one mounting clamp are unitary.
- (38) In some embodiments, the accessory is one of: a bag, a case, a rack, a storage bin, a gas tank, a gun case, a toolbox, a camera, a chainsaw, and a shovel.
- (39) In some embodiments, the vehicle is a powersports vehicle.

- (40) In another aspect of the present technology, there is provided an accessory kit. The accessory kit includes an accessory for a vehicle, the accessory having a connecting portion.
- (41) The accessory kit also includes at least one mounting clamp according to the above aspect or according to the above aspect and one or more of the above embodiments. The mounting clamp is engageable to the connecting portion for coupling the accessory to a structure of a vehicle.
- (42) In some embodiments, the connecting portion of the accessory includes a first connecting portion and a second connecting portion, and the at least one mounting clamp is a first mounting clamp and a second mounting clamp, the first mounting clamp connectable to the first connecting portion and the second mounting clamp connectable to the second connecting portion.
- (43) In some embodiments, the vehicle is a powersports vehicle.
- (44) According to another aspect of the present technology, there is provided a mounting clamp for coupling an accessory to a structure. The mounting clamp includes a body, a jaw and an actuator. The body has a mounting interface configured to engage to the accessory, and a coupling portion configured to at least partially receive a first structure member and a second structure member having different sizes. The jaw is selectively adjustable between an open position and a closed position. The jaw is pivotally connected to the body by a first pivot, and is movable between a first position and a second position. The jaw has an engaging portion for positioning the jaw in the open and closed positions. The actuator is pivotally connected to the body by a second pivot and is engageable with the engaging portion of the jaw. In response to the jaw being moved to the first position, the mounting clamp is in a first configuration adapted for clamping to the first structure member. In response to the jaw being moved to the second position, the mounting clamp is in a second configuration adapted for clamping to the second structure member. The jaw is configured to clamp one of the first structure member and the second structure member in response to being adjusted to the closed position.
- (45) In some embodiments, the structure is on a vehicle.
- (46) In some embodiments, the vehicle is a powersports vehicle.
- (47) Implementations of the present technology each have at least one of the above-mentioned objects and/or aspects, but do not necessarily have all of them. It should be understood that some aspects of the present technology that have resulted from attempting to attain the above-mentioned object may not satisfy this object and/or may satisfy other objects not specifically recited herein.
- (48) Additional and/or alternative features, aspects, and advantages of implementations of the present technology will become apparent from the following description, the accompanying drawings, and the appended claims.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a better understanding of the present technology, as well as other aspects and further features thereof, reference is made to the following description which is to be used in conjunction with the accompanying drawings, where:
- (2) FIG. 1A is a perspective view taken from a top, front, left side of an embodiment of a mounting clamp in a leading configuration connected to a connecting portion of a first structure;
- (3) FIG. 1B is a perspective view taken from a top, front, left side of the mounting clamp of FIG. 1A in an intermediate configuration, connected to a connecting portion of a second structure;
- (4) FIG. 1C is a perspective view taken from a top, front, left side of the mounting clamp of FIG. 1A in a trailing configuration, connected to a connecting portion of a third structure;
- (5) FIG. 2 is a perspective view taken from a top, front, left side of the mounting clamp of FIG. 1A;
- (6) FIG. 3 is an exploded perspective view taken from a top, front, left side of the mounting clamp of FIG. 1A;

- (7) FIG. 4 is a perspective view taken from a bottom, rear, right side of a body of the mounting clamp of FIG. 1A;
- (8) FIG. 5 is a cross-sectional view of the mounting clamp of FIG. 1A taken across plane 5-5 of FIG. 2;
- (9) FIG. 6A is a schematic side elevation view of an alternative embodiment of a mounting clamp according to the present technology in a leading configuration with a jaw of the mounting clamp being in an open position;
- (10) FIG. 6B is a schematic side elevation view of the mounting clamp of FIG. 6A with the jaw of the mounting clamp being in a closed position;
- (11) FIG. 7A is a schematic side elevation view of the mounting clamp of FIG. 6A in an intermediate configuration, with a jaw of the mounting clamp being in an open position;
- (12) FIG. 7B is a schematic side elevation view of the mounting clamp of FIG. 7A with the jaw of the mounting clamp being in a closed position;
- (13) FIG. 8A is a schematic side elevation view of the mounting clamp of FIG. 6A in a trailing configuration, with a jaw of the mounting clamp being in an open position;
- (14) FIG. 8B is a schematic side elevation view of the mounting clamp of FIG. 8A with the jaw of the mounting clamp being in a closed position;
- (15) FIG. 9A is a schematic side elevation view of the mounting clamp of FIG. 1A coupling a case to a connecting portion of a structure;
- (16) FIG. 9B is a schematic side elevation view of the mounting clamp of FIG. 1A coupling a toolbox to a connecting portion of a structure;
- (17) FIG. 9C is a schematic side elevation view of the mounting clamp of FIG. 1A coupling a light structure to a connecting portion of a structure;
- (18) FIG. 10 is a schematic side elevation view of an alternative embodiment of a mounting clamp according to the present technology;
- (19) FIG. 11A is a schematic side elevation view of the mounting clamp of FIG. 10 in a trailing configuration, and a jaw of the mounting clamp being in an open position;
- (20) FIG. 11B is a schematic side elevation view of the mounting clamp of FIG. 10 in an intermediate configuration, and a jaw of the mounting clamp being in an open position;
- (21) FIG. 11C is a schematic side elevation view of the mounting clamp of FIG. 10 in a leading configuration, and the jaw of the mounting clamp being in a closed position;
- (22) FIG. 11D is a schematic side elevation view of the mounting clamp of FIG. 10 in an intermediate configuration, and the jaw of the mounting clamp being in a closed position;
- (23) FIG. 11E is a schematic side elevation view of the mounting clamp of FIG. 10 in a trailing configuration, and the jaw of the mounting clamp being in a closed position;
- (24) FIG. 12A is a schematic side elevation view of an alternative embodiment of a mounting clamp according to the present technology, with a connecting portion of a structure engaging a jaw;
- (25) FIG. 12B is a schematic side elevation view of the mounting clamp of FIG. 12A with the connecting portion moving the jaw;
- (26) FIG. 12C is a schematic side elevation view of the mounting clamp of FIG. 12A with the mounting clamp in a leading configuration;
- (27) FIG. 12D is a schematic side elevation view of the mounting clamp of FIG. 12A with the mounting clamp in a leading configuration, and the jaw being in a closed position;
- (28) FIG. 12E is a schematic side elevation view of the mounting clamp of FIG. 12A with the mounting clamp in an intermediate configuration, and the jaw being in a closed position; and
- (29) FIG. 12F is a schematic side elevation view of the mounting clamp of FIG. 12A with the mounting clamp in a trailing configuration, and the jaw being in a closed position.

DESCRIPTION OF EMBODIMENTS

(30) The present disclosure is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the drawings. The

disclosure is capable of other embodiments and of being practiced out in various ways. Also, the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including”, “comprising”, or “having”, “containing”, “involving” and variations thereof herein, is meant to encompass the items listed thereafter as well as, optionally, additional items. In the following description, the same numerical references refer to similar elements.

(31) In the context of the following description, “outwardly” or “outward” means away from a longitudinal center plane of the mounting clamp, and “inwardly” or “inward” means toward the longitudinal center plane. In addition, in the context of the following description, “longitudinally” means in a direction parallel to the longitudinal center plane of the mounting clamp in a plane parallel to flat level ground, “laterally” means in a direction perpendicular to the longitudinal center plane along a width of the mounting clamp, and “generally vertically” means in a direction contained in the longitudinal center plane along a height direction of the mounting clamp. Note that in the Figures, a “+” symbol is used to indicate an axis of rotation. In the context of the present technology, the term “axis” may be used to indicate an axis of rotation. Also, the term “pivot” includes all the necessary structure (bearing structures, pins, axles and other components) to permit a structure to pivot/rotate about an axis, as the case may be.

(32) In the context of the present specification, unless expressly provided otherwise, the words “first”, “second”, “third”, etc. have been used as adjectives only for the purpose of allowing for distinction between the nouns that they modify from one another, and not for the purpose of describing any particular relationship between those nouns.

(33) It must be noted that, as used in this specification and the appended claims, the singular form “a”, “an” and “the” include plural referents unless the context clearly dictates otherwise.

(34) As used herein, the term “about” in the context of a given value or range refers to a value or range that is within 20%, preferably within 10%, and more preferably within 5% of the given value or range.

(35) As used herein, the term “and/or” is to be taken as specific disclosure of each of the two specified features or components with or without the other. For example, “A and/or B” is to be taken as specific disclosure of each of (i) A, (ii) B and (iii) A and B, just as if each is set out individually herein.

(36) Broadly, the present technology relates to a mounting clamp configured to couple an accessory to a plurality of structures (one structure at a time) where each one of the plurality of structures has a connecting portion, and each of the connecting portion varying in size from one structure to another. In some embodiments, the mounting clamp could be configured to connect to various connecting portions of a same structure, where the connecting portions have different sizes. In one example, a vehicle, such as a powersports vehicle (e.g., all-terrain vehicle, utility-task vehicle, side-by-side vehicle, snowmobile) typically provides a structure configured to mount an accessory thereon.

(37) In some cases, as mentioned hereabove, the structure can be part of the vehicle (i.e., vehicle is originally designed with the structure), but in other instances, the structure can be an add-on structure added to the vehicle afterward (i.e., vehicle is not originally designed with the structure). In some cases, the structure includes structure members or connecting portions of a specific size that is selected by the vehicle manufacturer or by the add-on structure manufacturer. In other words, the structures are typically size-specific. In addition, in some cases, there could be a plurality of structures provided on a given vehicle (e.g., a front structure and a rear structure, part of the vehicle or not, that each include structure members of different sizes of).

(38) Broadly, a mounting clamp that is adjustable for clamping to different sizes of structure members is further described below. For example, the mounting clamp is configured to clamp to a plurality of connecting portions having pre-determined sizes or diameters without requiring any tool. In some embodiments, the pre-determined sizes or diameters correspond to diameters of

typically used tubes in the automotive and/or powersports vehicle industries. More specifically, the mounting clamp can be manually adjusted by the user via pre-determined configurations that match with pre-determined sizes or diameters of the connecting portions to be clamped. In some embodiments, the mounting clamp can be automatically adjusted such that the mounting clamp automatically change its configuration ("self-adjusting") for matching with pre-determined sizes or diameters of connecting portions to be clamped. In either way, said mounting clamp is configured to apply a constant clamping force independently of the size or diameter of the connecting portion to which the mounting clamp is clamped, and is configured to, as will be described in greater detail below, provide generally optimal clamping condition.

(39) Referring to FIGS. 1A, 1B, 1C and 2 to 5, a mounting clamp **50** according to an embodiment of the present technology is shown. The mounting clamp **50** includes a body **60**, a jaw **62** and an actuator **64**, all three of which are pivotally connected. The mounting clamp **50** is a quick-action mounting clamp.

(40) As will be described in greater detail below, the mounting clamp **50** is configured to clamp to three structure members or connecting portions of different sizes, namely connecting portion **54a**, connecting portion **54b** and connecting portion **54c**. The connecting portion **54a** can be part of a first structure, the connecting portion **54b** can be part of a second structure and the connecting portion **54c** can be part of a third structure, where each of the first, second and third structures can be separate structures. In some embodiments, the first structure is a front structure provided on a front portion of the vehicle, the second structure is a rear structure provided on a rear portion of the vehicle, and the third structure is an intermediate structure provided on an intermediate portion of the vehicle between the front and rear portions thereof. In some embodiments, two or more of the connecting portions **54a**, **54b**, **54c** could be part of one same structure. For example, in the connecting portion **54a** could be a top portion of a front structure. It is contemplated that in other embodiments, the mounting clamp **50** could be configured to connect to two connecting portions of different sizes or four or more connecting portions of different sizes. While the connecting portions **54a**, **54b**, **54c** are circular in the illustrated embodiment, it is contemplated that in other embodiments, the connecting portions **54a**, **54b**, **54c** could be only partially circular with a section of the connecting portions **54a**, **54b**, **54c** being arcuate. In some instances, the radius of the connecting portion **54a** is greater than the radii of the connecting portions **54b**, **54c**, and the radius of the connecting portion **54b** is greater than the radius of the connecting portion **54c**. The connecting portion **54a** has a radius of about $\frac{1}{2}$ ", connecting portion **54b** has a radius of about $\frac{7}{16}$ ", and connecting portion **54c** has a radius of about $\frac{3}{8}$ ". It is contemplated that the connecting portions **54a**, **54b**, **54c** could have different sizes in other embodiments. It will be understood that other radii are permitted without departing from the present technology.

(41) The mounting clamp **50** is a quick-action mounting clamp that is adjustable in a plurality of configurations to set the jaw **62** in specific positions relative to the body **60**, in accordance with a specific connecting portion (**52a**, **52b** or **52c**) to clamp on. As will be described in more details below, the body **60** provides a plurality of pivots, fixed or mobile relative to the body **60**, that allow the relationship between the body **60**, the jaw **62** and the actuator **64** to be selectively modified, while providing a constant clamping force and an optimal clamping condition, no matter in which configuration the mounting clamp is set.

(42) As best seen in FIG. 5, the body **60** defines a plurality of pivots pivotably connecting the body **60**, jaw **62** and the actuator **64** together. In this embodiment, the plurality of pivots includes a first pivot, a second pivot, a third pivot and a fourth pivot. Each of these pivots will be described in greater detail below.

(43) Referring to FIGS. 1A, 1B, 1C and 2, the body **60** will now be described in detail. The body **60** has a front portion, a rear portion opposite to the front portion, a top surface, a bottom surface opposite to the top surface, a left portion and a right portion opposite to the left portion. Furthermore, the body **60** defines a longitudinal center plane 5.

(44) As best seen in FIG. 4, the body 60 has left and right side recesses 90a, 90b defined on, respectively, the left and right portions of the body 60. Furthermore, the body 60 has a coupling portion 92 configured to engage with connecting portions, which extends upwardly from the bottom portion of the body 60 and extends laterally between the left and right side recesses 90a, 90b. The coupling portion 92 includes left and right members 76a, 76b including left and right body tabs 94a, 94b that project downwardly therefrom, respectively. It is contemplated that in some embodiments, there could be only one tab or there could be three or more tabs. It is also contemplated that in some embodiments, the left and right body tabs 94a, 94b could be omitted. The left and right body tabs 94a, 94b have a profile generally similar to a profile of the left and right side recesses 90a, 90b, which can, in some instances, help enhance engagement between the body 60 and the connecting portions 54a, 54b, 54c. As best seen in FIG. 5, the coupling portion 92 has an arcuate section 93a, an arcuate section 93b and an arcuate section 93c. The arcuate sections 93a, 93b, 93c have an arc radius that is complementary to the radius of the connecting portions 54a, 54b, 54c, respectively.

(45) As best seen in FIG. 2, the front portion of the body 60 has a mounting interface 70 that is configured to engage with an accessory 52 (shown in FIGS. 9A, 9B and 9C). It is contemplated that in some embodiments, the mounting interface 70 could be disposed elsewhere on the body 60, such as, for example, on the top surface thereof. As an example, the mounting interface 70 defines two laterally spaced apertures 72a, 72b that are configured to receive fasteners (not shown) therein. Thus, the fasteners are configured to connect the accessory 52 to the body 60. It is contemplated that in some embodiments, the apertures 72a, 72b could be omitted, and that the mounting interface 70 could be configured to engage with and connect to the accessory 52 differently, such as, for instance, with an adhesive. It is contemplated that the accessory 52 and the mounting clamp 50 could be unitary. For instance, the body 60 can be integrated to the accessory 52 (e.g., the body 60 and the accessory 52 could be molded together, thereby forming one single piece). As further described below, the accessory 52 could include more than one mounting clamp 50 for mounting the accessory 52 on one structure or on a plurality of structures on a vehicle.

(46) Multiple types of accessories are contemplated in the present technology. Examples of accessories are provided in FIGS. 9A to 9C, but the accessory 52 is not limited to these examples. In FIG. 9A, the accessory 52 is a case configured to store objects therein. In FIG. 9B, the accessory 52 is a toolbox. In FIG. 9C, the accessory 52 is a light fixture. It is contemplated that in other embodiments, the accessory 52 could be another item such as a bag, a rack, a storage bin, a gas tank, a gun case, a camera, a chainsaw, a shovel, and/or any accessory to be mounted on a vehicle. In some embodiments, the accessory 52 and the mounting clamp 50 could be provided as a kit. In other embodiments, the accessory 52 could be configured to connect to more than one mounting clamp 50. In other embodiments, the accessory 52 could be configured to connect to more than one structure.

(47) Referring to FIG. 3, the actuator 64 is pivotally connected to the body 60 about the first pivot, which in this embodiment acts as an actuator pivot, defining a first pivot axis 187 via a first pin 87 that is received in two connecting recesses 82a, 82b that are defined in the body 60, generally near the rear portion of the body 60. The first pin 87 is also received in an aperture 138 that is defined in the actuator 64.

(48) Referring to FIGS. 2 to 5, the body 60 defines a rear recess 74 extending through part of the top portion and part of the rear portion of the body 60. As best seen in FIG. 4, the rear recess 74 exposes the left and right members 76a, 76b and a platform 78 that extends between the left and right members 76a, 76b and that is vertically below the top surface of the body 60.

(49) The jaw 62 is pivotally connected to the body 60 about a second pivot, which in this embodiment acts as a jaw pivot, defining a second pivot axis 185 via a second pin 85 sometimes referred to as moveable pivot 85. Parts of the moveable pivot 85 is received in guides 80a, 80b, which are respectively disposed on the left and right members 76a, 76b.

(50) In the present embodiment, the guides **80a**, **80b** are guiding slots **80a**, **80b**. In other embodiments, the guiding slots **80a**, **80b** could be other guides such as, for example, guiding rails. The guiding slots **80a**, **80b** are generally arcuate and define a leading position of the moveable pivot **85**, an intermediate position of the moveable pivot **85** and a trailing position of the moveable pivot **85**. The moveable pivot **85** is selectively moveable from one position to another.

(51) In more detail, in the present embodiment, each of the guiding slots **80a**, **80b** defines a leading recess **77a** corresponding to the leading position of the moveable pivot **85**, an intermediate recess **77b** corresponding to the intermediate position of the moveable pivot **85** and a trailing recess **77c** corresponding to the trailing position of the moveable pivot **85**. As will be described in greater detail below, the leading, intermediate and trailing positions of the moveable pivot **85** and thus the leading, intermediate and trailing recesses **77a**, **77b**, **77c** are generally positioned on a periphery (border) of a virtual circle **150** (shown in FIG. 5). Thus, the intermediate recess **77b** is vertically offset from the leading and trailing recesses **77a**, **77c** and the guiding slots **80a**, **80b** form an “M” shape. Other shapes are contemplated as well, especially in cases where more or less than three positions or recesses are present. As will be described below, this can help ensure that the mounting clamp **50** clamps to connecting portions **54a**, **54b**, **54c** with generally equal clamping forces.

(52) In other embodiments, the guiding slots **80a**, **80b** could be defined elsewhere along the body **60**. For instance, the guiding slots **80a**, **80b** could be defined along the outer sidewalls of the body **60**. It is also contemplated that in some embodiments, the guiding slots **80a**, **80b** could be defined elsewhere along the mounting clamp **50**. For instance, the guiding slots **80a**, **80b** could be defined on the jaw **62**. It is also contemplated that in some embodiments, there could be one guide or there could be three or more guides. In some embodiments, the guiding slots **80a**, **80b** could be omitted altogether. In such embodiments, the body **60** could define leading, intermediate and trailing apertures corresponding to, respectively, the leading, intermediate and trailing positions of the moveable pivot **85**, where the moveable pivot **85** is selectively received in the desired aperture.

(53) Furthermore, the rear recess **74** is configured to receive a retaining member **140**, such as a slider, for selectively setting the mounting clamp **50** in one of the pre-determined configurations adapted for clamping a given one of the connecting portions **54a**, **54b**, **54c**. The retaining member **140** is configured to slide within the rear recess **74** on the platform **78**. The retaining member **140** has, on a top surface thereof, a handling portion **144**, which is configured to project from the rear recess **74** when the retaining member **140** rests on the platform **78**. As such, a user can easily grasp the retaining member **140**. On left and right sides of the handling portion **144**, the retaining member **140** respectively has left and right flat portions **146a**, **146b**. The left and right flat portions **146a**, **146b** are configured to engage with an inner surface of the upper wall of the body **60** and thus maintain the retaining member **140** within the rear recess **74** (i.e., prevent the retaining member **140** from accidentally slipping out through the rear recess **74**). Furthermore, the retaining member **140** also defines a pivot receiving recess **142** extending along an entire width thereof, and from a bottom side of the retaining member **140** towards a top side thereof. Due to the pivot receiving recess **142**, when the moveable pivot **85** is received in the retaining member **140**, the moveable pivot **85** can move along a vertical direction of the retaining member **140** (i.e., moveable pivot **85** is slidably received in the retaining member **140**). Thus, the transition of the moveable pivot **85** from one position to another along the guide slots **80a**, **80b** is facilitated by sliding the retaining member **140** longitudinally within the rear recess **74**, where the retaining member **140** drives the moveable pivot **85** longitudinally. The moveable pivot **85** thus moves simultaneously along the guides **80a**, **80b** and along the pivot receiving recess **142** from one of the leading, intermediate and trailing positions to another, or from one leading, intermediate and trailing positions recesses **77a**, **77b**, **77c** to another. In other words, the user can selectively change the position of the moveable pivot **85** by sliding the retaining member **140** forward or backward, without requiring any tool. It is understood that in some embodiments, the retaining member **140** can be omitted and the moveable pivot **85** could be moved differently along the guides **80a**, **80b** to

adjust the mounting clamp **50**. In addition, it is understood that the retaining member **140** could be replaced by any equivalent structure that can provide a translational movement of the moveable pivot **85** along the guides **80a**, **80b**, such as a worm screw, a knob, a rack and pinion, for example.

(54) At the rear portion of the body **60**, the body **60** includes rear abutting portions **96a**, **96b** configured to abut the actuator **64** when the actuator **64** reaches a closed position.

(55) Still referring to FIGS. **2** to **5**, the jaw **62** will now be described in detail. The jaw **62** has a front member **100** and a rear member **102**.

(56) The front member **100**, which is pivotally connected to the body **60** via the moveable pivot **85**, has an angled portion **110** that extends laterally and that is configured to engage with the connecting portions **54a**, **54b**, **54c**. In this embodiment, the angled portion **110** is v-shaped and defines a virtual bisector line **111** (shown in FIG. **5**). The front member **100** also has left and right laterally spaced members **112a**, **112b** that are arcuate, and that extend upwardly from the angled portion **110**. It is understood that the angled portion **110** could be shaped differently, with one or multiple arcs, for example. The members **112a**, **112b** each define an upper aperture **116** in which the moveable pivot **85** is received. The members **112a**, **112b** also each define a lower aperture **114** in which, as will be described below, a jaw pivot **115** is received. Since the moveable pivot **85** enables a moveable pivotal connection between the jaw **62** and the body **60**, the front member **100** is selectively moveable between a leading position, an intermediate position and a trailing position by moving the moveable pivot **85**, as mentioned above, between the leading, intermediate, and trailing positions.

(57) The rear member **102** is pivotally connected to the front member **100** and pivotally connected to the actuator **64**. More specifically, the rear member **102** is pivotally connected to the front member **100** about a third pivot, which in this embodiment acts as a jaw pivot **115** defining a third pivot axis **215** via a third pin **115**. The jaw pivot **115** is received in a lower aperture **124** of the rear member **102** and the lower apertures **114** of the front member **100**. Furthermore, the rear member **102** is pivotally connected to the actuator **64** at an end opposite to the jaw pivot **115** about a fourth pivot, which in this embodiment acts as a connecting pivot **125**, defining a fourth pivot axis **225** via a fourth pin **125**. The fourth pin **125** is received in an upper aperture **126** defined in the rear member **102**, and apertures **134** defined in the actuator **64**. The rear member **102** is angled to conform to the arcuate shape of the front member **100**. It is contemplated that in some embodiments, the rear member **102** could be shaped differently. For example, the rear member **102** could be curved. In this embodiment, the rear member **102** is laterally sized to fit between the left and right extending members **112a**, **112b** of the front member **100**.

(58) It is understood that the rear member **102** acts as a linkage between the front member **102** and the actuator **64**. It is contemplated that in some embodiments, the jaw **62** could include additional members. It is also contemplated that in some embodiments, the jaw **62** could include a single member pivotally connected to the actuator **64**. It is also further contemplated that the jaw **62** could be a single member engaging the actuator **64**, without being pivotally connected thereto.

(59) The jaw **62** is selectively adjustable between an open position and a closed position. As will be described below, when the jaw **62** is in the closed position, the jaw **62** is configured to clamp to a connecting portion, and when the jaw **62** is in the open position, the jaw **62** is configured to, if the jaw **62** was previously clamping onto the connecting portion, release the connecting portion.

(60) Still referring to FIGS. **2** to **5**, the actuator **64** will now be described. The actuator **64** is a lever **64** that is operable manually (i.e., without the need for any specialized tool). It is contemplated that in other embodiments the actuator **64** could be a handle, a knob or any other equivalent actuation device.

(61) The actuator **64** has two tabs **132** that extend generally perpendicularly away from a surface of the actuator **64**, toward a front side of the body **60**. It is contemplated that in some embodiments, the actuator **64** could have more or less than two tabs. Each of the two tabs **132** defines an aperture **134** configured to receive the connecting pivot **125** therein. The actuator **64** also has an upper

connecting portion **136** (best seen in FIG. 3) that defines an aperture **138** configured to receive the actuator pivot **87**. The actuator pivot **187** provides a pivotal connection between the actuator **64** and the body **60**.

(62) The actuator **64** further has left and right abutting portions **139a**, **139b** that are generally complementary to and configured to abut, respectively, the left and right abutting portions **96a**, **96b** of the body **60**. As will be described below, the actuator **64** can be actuated to selectively open the mounting clamp **50** (open state) and close the mounting clamp **50** (close state) by operatively moving the jaw **62** accordingly. In the embodiment shown in FIGS. 1 to 5, the actuator **64** is said to be in closed position when pointing generally downwardly and in open position when pointing generally upwardly. Other configurations are contemplated as well, such as pointing generally upwardly/downwardly or pointing generally left/right in closed/open positions, respectively, for example.

(63) The operation of the mounting clamp **50** will now be described in detail to illustrate the cooperative action of its parts. As mentioned above, the body **60**, jaw **62**, and actuator **64** form a quick-action mounting clamp that is adjustable to clamp to different connecting portions **54a**, **54b**, **54c** of pre-determined sizes for coupling an accessory to the connecting portion. In addition, it is to be noted that the clamping force applied by the mounting clamp **50** on said different connecting portions is pre-determined, and generally equal for each connecting portion. Furthermore, the mounting clamp **50** can be operated without requiring any tool.

(64) The pivotal connection between the jaw **62** and the actuator **64** is such that in response to the actuator **64** being actuated, the jaw **62** is adjusted between open and closed positions. Additionally, the pivotal connection between the jaw **62** and the body **60** is moveable, because of the moveable pivot **85**. Thus, the mounting clamp **50** can be selectively adjusted between leading, intermediate and trailing configurations. In this embodiment, the mounting clamp **50** has been designed to clamp onto three different connecting portions (i.e., three different sizes of structure member), thus the mounting clamp **50** is adjustable between three configurations, and the moveable pivot **85** is adjustable between three positions. It is contemplated that in some embodiments, the moveable pivot **85** could be adjustable between more or less than three positions such that the mounting clamp **50** would also be adjustable between more or less than three configurations.

(65) In each of the leading, intermediate and trailing configurations, the jaw **62** is adjustable between the open position (shown in FIGS. 6A, 7A, 8A) and the closed position (shown in FIGS. 6B, 7B, 8B).

(66) With continued reference to FIGS. 1 to 5, in order to move the jaw **62** to the open position, the actuator **64** is actuated so as to pivot about the actuator pivot axis **187** in an anti-clockwise direction. In response to the actuator **64** being actuated, the connecting pivot **125** pivots about to the actuator pivot axis **187**, such that the connecting pivot **125** moves away from the front of the body **60**. The jaw pivot **115** pivots about to the moveable pivot axis **185**, such that the jaw pivot **115** also moves away from the front of the body **60**. This results in the jaw **62** being moved away from the coupling portion **92** (i.e., the jaw **62** is moved toward the open position) until the mounting clamp **50** is in the open state. As mentioned above, being that the actuator **64** is a lever, the lever simply has to be manipulated in the correct direction, once again without requiring any specialized tool. It is understood that in this embodiment, actuation of the actuator **64** is required to open the mounting clamp **50** for safety purposes, instead of requiring actuation of the actuator **64** to close the mounting clamp **50**, but other configurations are contemplated as well.

(67) When the mounting clamp **50** is in the open state, before a specific structure member is received in the coupling portion **92**, the mounting clamp **50** is adjusted to a configuration in which the mounting clamp **50** is adapted to clamp said specific structure member. More specifically, the retaining member **140** is moved within the rear recess **74**, which causes the moveable pivot **85** to move along the guides **80a**, **80b** to a predetermined position that corresponds with the size of the specific structure member to be clamped. For instance, referring to FIG. 1A, if the structure

member to be clamped is the connecting portion **54a**, the moveable pivot **85** is moved to the leading position **77a**. In another example, referring to FIG. **1B**, if the structure member to be clamped is the connecting portion **54b**, the moveable pivot **85** is moved to the intermediate position **77b**. In another example, referring to FIG. **1C**, if the structure member to be clamped is the connecting portion **54c**, the moveable pivot **85** is moved to the trailing position **77c**.

(68) In any configuration, to move the jaw **62** to the closed position, the actuator **64** is actuated. In the illustrated embodiment, the actuator **64** is actuated such that the actuator **64** pivots about the actuator pivot axis **187** toward the front of the body **60** (i.e., clockwise direction). Being that the actuator **64** is a lever, the lever simply has to be manipulated in the correct direction by an operator. Thus, actuating the actuator **64** is a quick process that can be done manually, without the use of any specialized tool. In response to the actuator **64** being actuated toward the front of the body **60**, the connecting pivot **125** pivots about to the actuator pivot axis **187**, such that the connecting pivot **125** moves toward the front of the body **60**, and the jaw pivot **115** pivots about to the moveable pivot axis **185**, such that the jaw pivot **115** moves toward the front of the body **60**. Eventually, the abutting portions **139a**, **139b** of the actuator **64** abut the abutting portions **96a**, **96b** of the body **60**, thus indicating that the jaw **62** has reached the closed position.

(69) In the closed state, when a structure member is received in the coupling portion **92**, the mounting clamp **50** clamps said structure member. In other words, when the jaw **62** is in the closed position, the configuration of mounting clamp **50** cannot be changed (e.g., cannot go from a leading configuration to an intermediate configuration).

(70) Furthermore, the mounting clamp **50** is configured to provide optimal clamping conditions for securing an accessory to each of the different pre-determined structure members that the mounting clamp **50** is designed to receive, as will now be described in detail.

(71) When the mounting clamp **50** is in closed position and clamped on a structure member, the moveable pivot **85** is positioned in one of the leading, intermediate and trailing positions (i.e., leading, intermediate and trailing recesses **77a**, **77b**, **77c**) corresponding to the size of the clamped structure member. As best seen on FIG. **5**, these positions are located on the border of the virtual circle **150** (i.e., tangent). More specifically, when the moveable pivot **85** is at one of the leading, intermediate and trailing positions, the moveable pivot **85** is disposed on the border of the virtual circle **150**. A virtual center **152** of the virtual circle **150** is aligned with the jaw pivot **115**. This causes the distance between the jaw pivot **115** and the moveable pivot **85** to remain constant regardless of whether the moveable pivot is in the leading, intermediate and trailing positions. As a result, the mounting clamp **50**, for each configuration, provides an equal or constant clamping force on the structure member.

(72) Additionally, the virtual bisector line **111** (shown in FIG. **5**), which illustrates the orientation of the clamping force that the mounting clamp **50** is configured to apply to the structure member (not shown in FIG. **5**), is oriented from the jaw **62** toward the coupling portion **92** and is generally parallel to a virtual line **154** that extends between the jaw pivot **115** to the moveable pivot **85**. This applies when the moveable pivot **85** is in the leading, intermediate and trailing positions, as shown on FIGS. **6B**, **7B**, and **8B**, respectively. It is understood that the orientation of the virtual bisector line **111** (i.e., orientation of the clamping force) is driven by the position of the moveable pivot **85** within the guides **80a**, **80b**, which is selected based on the specific size of the structure member that is to be clamped. Moreover, the virtual bisector line **111** is thus oriented toward the specific arcuate section (**93a**, **93b**, **93c**) corresponding to said specific size of structure member to be clamped. For example, referring to the FIGS. **1A** and **5**, the mounting clamp **50** is set for clamping the connecting portion **54a**, with the moveable pivot **85** being positioned in the leading position (i.e., moveable pivot **84** is in the leading recess **74a**). When the jaw **62** is closed (i.e., mounting clamp **50** is in the closed state), the connecting portion **54a** is sandwiched between the arcuate section **93a** of the body **60** and the angled portion **110** of the jaw **62**, such that the clamping force applied to the connecting portion **54a** (illustrated by the virtual bisector line **111**) is oriented toward

the arcuate section **93a**, and is generally parallel to a virtual line **154a** extending from the jaw pivot **115** to the moveable pivot **85**. As shown on FIGS. **6B**, **7B**, and **8B**, the same applies to other configurations of the mounting clamp **50**, which ensures that the mounting clamp **50** provides an equal or constant clamping force in terms of orientation in every configuration.

(73) Moreover, the relative positions of the actuator pivot **87**, the jaw pivot **115** and the connecting pivot **125** define an overcenter mechanism that can assist in preventing the mounting clamp **50** being unintentionally unlatched.

(74) It is appreciated that these aspects of the present technology collaborate to provide optimal clamping conditions, regardless of which configuration the mounting clamp **50** is in (i.e., clamping conditions of the mounting clamp **50** do not are not negatively impacted due to position of the moveable pivot **85**).

(75) Referring now to FIGS. **6A**, **6B**, **7A**, **7B**, **8A** and **8B**, an alternative embodiment of the mounting clamp **50**, namely mounting clamp **51**, is depicted. Features of the mounting clamp **51** that are similar to those of the mounting clamp **50** have been labeled with the same reference numerals, and will not be described again in detail. One notable difference between the mounting clamp **51** and the mounting clamp **50**, is that the actuator **64**, when in the mounting clamp **50** is in the closed state, is configured to engage the top surface of the body **60** instead of a rear thereof.

(76) Referring to FIGS. **6A**, **7A** and **8A**, the mounting clamp **51** is shown in the open state. In FIG. **6A**, the moveable pivot **85** is in the leading position, such that the mounting clamp **51** is configured to clamp to the connecting portion **54a**. In FIG. **7A**, the moveable pivot **85** is in the intermediate position, such that the mounting clamp **51** is configured to clamp to the connecting portion **54b**. In FIG. **8A**, the moveable pivot **85** is in the trailing position, such that the mounting clamp **51** is configured to clamp to the connecting portion **54c**.

(77) Referring to FIGS. **6B**, **7B** and **8B**, the mounting clamp **51** is shown in the closed state. In FIG. **6B**, the moveable pivot **85** is in the leading position, and the mounting clamp **51** is clamped to the connecting portion **54a**. The virtual bisector line **111** is generally parallel to virtual line **154a** that extends between the jaw pivot **115** and the moveable pivot **85**.

(78) In FIG. **7B**, the moveable pivot **85** is in the intermediate position, and the mounting clamp **51** is clamped to the connecting portion **54b**. The virtual bisector line **111** is generally parallel to virtual line **154b** that extends between the jaw pivot **115** and the moveable pivot **85**.

(79) In FIG. **8B**, the moveable pivot **85** is in the trailing position, and the mounting clamp **51** is configured to clamp to the connecting portion **54c**. The virtual bisector line **111** is generally parallel to virtual line **154c** that extends between the jaw pivot **115** and the moveable pivot **85**.

(80) It is understood that the adjustment of the mounting clamp **51** from one of the leading, intermediate and trailing configurations to another is similar to the adjustment of the mounting clamp **50**, except that the actuation of the actuator **64** to move the jaw between the open and closed positions is different. It is also understood that the operation of the mounting clamp **51** is similar to the operation of the mounting clamp **50**, such that the mounting clamp **51** is also configured to provide optimal clamping conditions.

(81) Referring now to FIGS. **10**, **11A**, **11B**, **11C**, **11D** and **11E**, an alternative embodiment of the mounting clamps **50**, **51**, namely mounting clamp **251**, will now be described. Features of the mounting clamp **251** that are similar to those of the mounting clamps **50**, **51** have been labeled with the same reference numerals, and will not be described again in detail. One notable difference between the mounting clamps **50**, **51** and the mounting clamp **251**, is that the mounting clamp **251** is a self-adjusting mounting clamp. In other words, the mounting clamp **251** is automatically adjustable between one configuration to another, without any tool nor adjustment action from a user, to accommodate for the size of the connecting portion that is being engaged therewith.

(82) The self-adjustment is notably achieved by the following features. The mounting clamp **251** has a resilient member **254** that replaces the retaining member **140**. The resilient member **254** biases the moveable pivot **85** toward one of the leading, intermediate, and trailing positions such

that the mounting clamp **251** is biased toward a corresponding one of the leading, intermediate, and trailing configurations. In this embodiment, the resilient member **254** biases the moveable pivot **85** toward the trailing position such that the mounting clamp **251** is biased toward the trailing configuration. In this configuration of the mounting clamp **241**, an opening of the jaw **62** is at its maximum. The resilient member **254** is a torsion spring with one end connected to the moveable pivot **85**, and the other end connected to the body **60**. It is contemplated that in other embodiments, the resilient member **254** could be other types of biasing members such as polymeric members, compression springs and/or tension springs and/or that the resilient member **254** could be elsewhere in the assembly (e.g., connected to the front member **110** and to the body **60**).

(83) As best seen in FIGS. **10**, **11A**, **11B**, **11C**, the guiding slots **80a**, **80b** are configured such that when the moveable pivot **85** is in the leading, intermediate, and trailing positions, the moveable pivot **85** is on a border (periphery) of a virtual circle **150** having its center **152** on the jaw pivot **115**, as in mounting clamps **50**, **51**. One notable difference, however, between the mounting clamps **50**, **51**, and **251** is that the guiding slots **80a**, **80b** form 'L-shaped' slots instead of 'M-shaped' slots. This 'L-shape' allows a smooth movement of the moveable pivot **85** as it is being driven by the resilient member **254**, by minimizing blockage and friction of the moveable pivot **85** within the guiding slots **80a**, **80b** in some cases.

(84) In operation, to have the mounting clamp **251** clamp to one of the connecting portions **54a**, **54b**, **54c**, the one of the connecting portions **54a**, **54b**, **54c** is disposed between the jaw **62** and the coupling portion **92**, in an attempt to position the one of the connecting portions **54a**, **54b**, **54c** in a respective one of the arcuate sections **93a**, **93b**, **93c**. If the position of the jaw **62** does not provide enough clearance between the jaw **62** and the coupling portion **92** to let the one of the connecting portions **54a**, **54b**, **54c** from entering in the coupling portion **92**, the jaw **62** further pivots around the moveable pivot **85** until the one of the connecting portions **54a**, **54b**, **54c** is fully engaged in corresponding one of arcuate sections **93a**, **93b**, **93c** and in the angled portion **110** of the jaw **62**. It is understood that due to the pivotal connections between the body **60**, the jaw **62**, and the actuator **64**, same effect is obtained by pivoting the actuator **64** further around the actuator pivot **87**.

(85) The automatic adjustment of the mounting clamp **251** begins when the actuator **64** is partially actuated toward its closed position and the one of connecting portions **54a**, **54b**, **54c** contacts the jaw **102** at a contact point C which is typically at the foremost end of it ('tip') and distal from the angled portion **110**. It is noted that when the one of connecting portions **54a**, **54b**, **54c** contacts the jaw **102** at the contact point C, the one of the connecting portions **54a**, **54b**, **54c** is not yet received in the angled portion **110** and is thus not yet fully engaged by the jaw **102**. By partially actuating the actuator **64** so as to move the jaw **62** to its closed position, the pivotal connections between the body **60**, the jaw **62**, and the actuator **64** cause a preliminary clamping force between the coupling portion **92** and the jaw **102** (since the one of connecting portions **54a**, **54b**, **54c** is sandwiched therebetween). In response to the actuator **64** being rotated further, the jaw **102** rotates further about the jaw pivot. A moving force moves the moveable pivot **85** along the guiding slots **80a**, **80b** toward the leading position until the moveable pivot **85** reaches its final position in accordance with the size of the one of connecting portions **54a**, **54b**, **54c** engaged in the mounting clamp **251**.

(86) For instance, referring to FIGS. **11A**, **11B**, and **11C**, the mounting clamp **251** is initially in the trailing configuration and the jaw **62** is in the open position. In FIG. **11A**, the connecting portion **54a** is engaged in the corresponding arcuate section **93a** of the coupling portion **92** and in contact with the jaw **62**. Then, as shown in FIG. **11B**, the actuator **64** is partially actuated, and the moveable pivot **85** is moved within the guiding slots **80a**, **80b** from its initial position (i.e., the trailing position in this embodiment) to the adjacent one (i.e., the intermediate position in this embodiment) and so on, until the moveable pivot **85** reaches its final position (i.e., the leading position in this embodiment). It is understood that the movement of the moveable pivot **85** counteracts the biasing force of the resilient member **254**, which urges the moveable pivot **85** toward its initial position (i.e., the trailing position in this embodiment). The resilient member **254**

is sufficiently resilient so as to form the preliminary clamping force causing the moving force moving the moveable pivot **85** toward the leading position. More precisely, the resilient member **254** biases the movable pivot **85** until the angled portion **110** effectively engages the connecting portion **54a**. Then, as shown in FIG. **11C**, the actuator **64** can be actuated to move the jaw **62** from the open position to the closed position, thereby clamping the connecting portion **54a**. It is understood that in instances where the connecting portion **54b** is used, the moveable pivot **85** would stop moving once the intermediate position is reached, as shown on FIG. **11D**. In the case of the connecting portion **54c**, it is understood that the moveable pivot **85** would not move since it is already in the trailing position due to biasing force of the resilient member **254**, as shown on FIG. **11E**.

(87) The operation of the mounting clamp **251** is similar to the operation of the mounting clamps **50, 51**, such that the mounting clamp **251** also provides optimal clamping conditions.

(88) Referring now to FIGS. **12A** to **12F**, another alternative embodiment of the mounting clamp, **50, 51, 251**, namely mounting clamp **351**, will now be described. Features of the mounting clamp **351** that are similar to those of the mounting clamps **50, 51, 251** have been labeled with the same reference numerals, and will not be described again in detail.

(89) One notable difference between the mounting clamps **50, 51, 251** and the mounting clamp **351** is that the mounting clamp **351** has a jaw **362** that is made of a single member, as opposed to the jaw **62** having front and rear members **100, 102** as described in prior embodiments. In the present embodiment, the jaw **362**, which is pivotally connected to the body **60** about a pivot axis **360**, is adjustable at least between a leading jaw position (FIG. **12D**), an intermediate jaw position (FIG. **12E**) and a trailing jaw position (FIG. **12F**).

(90) The jaw **362** is connected to a resilient member (not shown) that biases the jaw **362** toward the trailing position. For example, the resilient member can be similar to the resilient member **254** described in prior embodiment. The jaw **362**, toward one end, has the angled portion **110** that is configured to engage the connecting portions **54a, 54b, 54c**. The angled portion **110** generally defines a v-shape. In some embodiments, the angled portion **110** has another shape suitable for partially receiving the connecting portions **54a, 54b, 54c**. Toward the other end, the jaw **362** has an actuator engaging portion **362**. The actuator engaging portion **362** defines three recesses **364a, 364b, 364c**. As will be described in greater detail below, the three recesses **364a, 364b, 364c** are configured to engage the actuator **64** in accordance with reception of the connecting portions **54a, 54b, 54c**, respectively.

(91) The actuator **64**, which is configured to pivot about a pivot axis **366**, is operatively connectable to the jaw **362** such that actuation of the actuator **64** can result in the jaw **362** being adjusted between the open and closed positions. In this embodiment, the actuator **64** has a cam portion **65** configured to selectively engage in the recesses **364a, 364b, 364c** and to selectively lock the movement of jaw **362** around the pivot **360** once the actuator is in closed position. Other configurations are contemplated as well.

(92) Referring to FIG. **12A** to **12D**, the operation of the mounting clamp **351** will now be described. On FIG. **12A**, the jaw **362** of the mounting clamp **351** is in the trailing position and open state, as the jaw **362** is biased toward the trailing position, and the actuator **64** is not actuated. The connecting portion **54a** engages the mounting clamp **351**, causing said jaw **362** to pivot about the pivot axis **360** as shown in FIG. **12B**, thereby allowing insertion of the connecting portion **54a** therein. Then, once the connecting portion **54a** is received in the angled portion **110** (i.e., disposed in the mounting clamp **351**) and in the arcuate section **93a** of the coupling portion **92**, due to the biasing force of the resilient member and the size of the connecting portion **54a**, the jaw **362** moves to the leading position, such that the mounting clamp **351** is in the leading configuration, as shown in FIG. **12C**. Then, the actuator **64** can be actuated to lock the jaw **362** in its position. Indeed, in this embodiment, actuation of the actuator **64** does not cause movement of the jaw **62**, but instead, locks the jaw **62** in the position it is in. When the jaw **62** is locked in position, the mounting clamp

351 applies a clamping force to the connecting portion **54a**, as shown on FIG. **12D**, where the jaw **362** is locked in the leading, so that the mounting clamp **351** is in the leading configuration.

(93) FIG. **12E** shows the jaw **362** locked in the intermediate position to clamp on the connecting portion **54b**, which is sandwiched between the arcuate section **93b** and the angled portion **110**, so that the mounting clamp **351** is in the intermediate configuration.

(94) FIG. **12F** shows the jaw **362** locked in the trailing position to clamp on the connecting portion **54c**, which is sandwiched between the arcuate section **93c** and the angled portion **110**, so that the mounting clamp **351** is in the trailing configuration.

(95) Thus, it is noted that, similarly to the prior embodiment, the mounting clamp **351** is configured so that when one of the connecting portions **54a**, **54b**, **54c** is engaged in the coupling portion **92**, the mounting clamp **351** adjusts its configuration in accordance with the size of the connecting portion being engaged in the coupling portion **92**. In other words, when one of the connecting portions **54a**, **54b**, **54c** is engaged in the coupling portion **92**, the jaw **362** moves to the corresponding one of the leading, intermediate and trailing positions, so that the mounting clamp **351** is in the leading, intermediate or trailing configuration. It is understood that the mounting clamp **351** is said to be automatically adjustable or self-adjusting due to the presence of the resilient member (not shown) that biases the jaw **362** toward the trailing position, as described above. It is also understood that the mounting clamp **351** could be manual, (i.e., not automatically adjustable or self-adjusting if the resilient member is omitted). In such a case, the operator would have to manually adjust the jaw **362** toward the trailing position, until the mounting clamp **351** is configured in one of the leading, intermediate or trailing configurations adapted for clamping one of the connecting portions **54a**, **54b**, **54c**.

(96) Similarly to the prior embodiments, even if not shown on specific FIGS. **12A** to **12F**, it is understood that the mounting clamp **351** also has a virtual circle centered on the pivot axis **360** (i.e., “jaw pivot”) and that the three recesses **364a**, **364b**, **364c** are disposed on said virtual circle. In addition, it is also understood that the mounting clamp **351** has a virtual bisector line that extends toward the arcuate section **93a**, **93b**, **93c** of the coupling portion **92** in accordance with the connecting portion **54a**, **54b**, **54c** that is clamped therein. This results in that the clamping forces applied by the mounting clamp **351**, between the coupling portion **92** and the angled portion **110**, are generally similar in the leading, intermediate and trailing configurations, both in terms of magnitude and orientation. Thus, the mounting clamp **351** provides an optimal clamping condition, no matter which one of the connecting portions **54a**, **54b**, **54c** is clamped.

(97) The various components of the mounting clamps **50**, **51**, **251**, **351** are made of conventional materials (e.g., metallic materials, such as steel or aluminum, non-metallic material, such as plastics, and/or composite materials) via conventional manufacturing processes (e.g., casting, molding, 3d printing, etc.). The present technology does not require any specific materials nor methods of manufacture. The present technology merely requires that each component be suitable for the purpose for which it is intended and the use to which it is to be put. Any material(s) or method(s) of manufacture which produce such components may be used in the present technology.

(98) Modifications and improvements to the above-described embodiments of the present technology may become apparent to those skilled in the art. The foregoing description is intended to be exemplary rather than limiting. The scope of the present technology is therefore intended to be limited solely by the scope of the appended claims.

Claims

1. A mounting clamp for coupling an accessory to a structure, the mounting clamp comprising: a body having a mounting interface configured to engage the accessory, and a coupling portion configured to selectively at least partially receive one of a first structure member and a second structure member, the first and second structure members having different sizes; a jaw selectively

adjustable between an open position and a closed position, the jaw including: a first member pivotally connected to the body by a first pivot selectively movable between a first position and a second position; and a second member pivotally connected to the first member by a second pivot; an actuator pivotally connected to the second member of the jaw by a third pivot, and pivotally connected to the body by a fourth pivot; in response to the first pivot being moved to the first position, the mounting clamp is in a first configuration adapted for clamping to the first structure member; in response to the first pivot being moved to the second position, the mounting clamp is in a second configuration adapted for clamping to the second structure member; and the jaw being configured to clamp one of the first structure member and the second structure member in response to being adjusted to the closed position.

2. The mounting clamp of claim 1, wherein in response to actuating the actuator, the second pivot pivots about to the first pivot, and the jaw moves between the opened and closed positions.

3. The mounting clamp of claim 1, wherein the second, third and fourth pivots are configured to provide an overcenter effect when the jaw is in closed position.

4. The mounting clamp of claim 1, wherein: when the mounting clamp is in the first configuration and the jaw is in the closed position, the jaw is configured to clamp the first structure member with a first clamping force; and when the mounting clamp is in the second configuration, and the jaw is in the closed position, the jaw is configured to clamp the second structure member with a second clamping force, a magnitude of the first clamping force is generally similar to a magnitude of the second clamping force.

5. The mounting clamp of claim 1, wherein: when the mounting clamp is in the first configuration and the jaw is in the closed position, the jaw is configured to clamp the first structure member with a first clamping force; and when the mounting clamp is in the second configuration, and the jaw is in the closed position, the jaw is configured to clamp the second structure member with a second clamping force, an orientation of the first clamping force is generally similar to an orientation of the second clamping force.

6. The mounting clamp of claim 1, wherein when the first pivot is in one of the first and second positions, the first pivot is disposed on a border of a virtual circle, a virtual center of the virtual circle being generally aligned with the second pivot when the jaw is in the closed position.

7. The mounting clamp of claim 1, wherein the first member has an angled portion, and a virtual bisector line passing through the angled portion is generally parallel to a virtual line passing through the first and second pivots.

8. The mounting clamp of claim 1, wherein the body has a guide configured to at least partially receive the first pivot, and to guide the first pivot between the first and second positions.

9. The mounting clamp of claim 8, wherein the guide is a guiding slot.

10. The mounting clamp of claim 8, wherein the guide defines a first recess and a second recess spaced from the first recess, and the first pivot is in the first position when the first pivot is in the first recess, and the first pivot is in the second position when the first pivot is in the second recess.

11. The mounting clamp of claim 1, further including a retaining member selectively moveable between a third position and a fourth position, and wherein: the retaining member is configured to retain the first pivot in the first position when the retaining member is in the third position; and the retaining member is configured to retain the first pivot in the second position when the retaining member is in the fourth position.

12. The mounting clamp of claim 11, wherein the body defines a recess configured to at least partially receive the retaining member, the retaining member being moveable within the recess between the third and fourth positions.

13. The mounting clamp of claim 1, further including a resilient member operatively connected to the body and to the first pivot, the resilient member biasing the first pivot toward one of the first and second positions, and wherein: in response to one of the first and second structure members being at least partially received into the coupling portion, the mounting clamp being biased to move

to a corresponding one of the first and second configurations, and in response to the jaw being adjusted to the closed position, the jaw clamping the one of the first and second structure members.

14. The mounting clamp of claim 13, wherein the mounting clamp is a self-adjusting clamp.

15. The mounting clamp of claim 1, wherein the coupling portion defines: a first arcuate section having a first arc radius complementary to a first arc radius of the first structure member; and a second arcuate section having a second arc radius complementary to a second arc radius of the second structure member.

16. The mounting clamp of claim 1, wherein the first pivot is selectively movable between the first position, the second position and a fifth position, and in response to the first pivot being moved to the fifth position, the mounting clamp is in a third configuration adapted for clamping to a third structure member defining a third arc having a third arc radius different from the first and second arc radii.

17. An accessory for a vehicle comprising at least one mounting clamp according to claim 1.

18. The accessory of claim 17, wherein the accessory and the at least one mounting clamp are unitary.

19. An accessory kit comprising: an accessory for a vehicle, the accessory having a connecting portion; and at least one mounting clamp according to claim 1 engageable to the connecting portion for coupling the accessory to a structure of a vehicle.
