

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410901
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lim; Eay Jin et al.

Lighting device

Abstract

A lighting device disclosed in an embodiment of the invention comprises a substrate; a plurality of light sources arranged in a second direction on the substrate; a lighting module having a light guide portion disposed on the substrate and the light sources; an optical lens disposed on the lighting module, the optical lens having an incident surface having a width greater than a width of the lighting module in a first direction, and an exit surface from which light incident on the incident surface is emitted; and a reflecting member having an insertion hole in which the light guide portion is disposed, a reflective portion extending to both sides of the insertion hole and covering both sides of the light guide portion, and a supporting portion supporting a lower edge of the optical lens, wherein the light guide portion and the insertion hole have a width in the first direction smaller than a length in the second direction, and an upper end of the reflective portion may be positioned higher than an upper end of the light guide portion.

Inventors:	Lim; Eay Jin (Seoul, KR), Ko; Kwang Hyun (Seoul, KR), Yang; Hyun Duck (Seoul, KR), Lee; Dong Hyun (Seoul, KR)
Applicant:	LG INNOTEK CO., LTD. (Seoul, KR)
Family ID:	88243177
Assignee:	LG INNOTEK CO., LTD. (Seoul, KR)
Appl. No.:	18/849054
Filed (or PCT Filed):	April 04, 2023
PCT No.:	PCT/KR2023/004540
PCT Pub. No.:	WO2023/195748
PCT Pub. Date:	October 12, 2023

Prior Publication Data

Foreign Application Priority Data

KR	10-2022-0041872	Apr. 04, 2022
KR	10-2022-0082522	Jul. 05, 2022
KR	10-2023-0027665	Mar. 02, 2023

Publication Classification

Int. Cl.: F21S43/15 (20180101); F21S4/24 (20160101); F21S43/14 (20180101); F21S43/20 (20180101); F21S43/249 (20180101); F21S43/31 (20180101); F21S43/37 (20180101); F21W103/55 (20180101); F21Y103/10 (20160101); F21Y115/10 (20160101)

U.S. Cl.:

CPC F21S43/15 (20180101); F21S4/24 (20160101); F21S43/249 (20180101); F21S43/26241 (20240501); F21S43/31 (20180101); F21S43/37 (20180101); F21S43/14 (20180101); F21W2103/55 (20180101); F21Y2103/10 (20160801); F21Y2115/10 (20160801)

Field of Classification Search

CPC: F21S (4/00-28); F21S (43/14-37); F21W (2103/55); F21Y (2103/10); F21Y (2115/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10240755	12/2018	Huang	N/A	F21V 5/04
10274166	12/2018	Li et al.	N/A	N/A
10405396	12/2018	Gawel	N/A	H05B 45/22
11015790	12/2020	Chen et al.	N/A	N/A
11360255	12/2021	Oh et al.	N/A	N/A
2014/0211449	12/2013	Nomura et al.	N/A	N/A
2015/0319329	12/2014	Matsuzawa et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-2015-0023014	12/2014	KR	N/A
10-2015-0084904	12/2014	KR	N/A
10-2020-0071245	12/2019	KR	N/A
10-2327855	12/2020	KR	N/A

OTHER PUBLICATIONS

International Search Report dated Jul. 13, 2023 issued in Application No. PCT/KR2023/004540. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

(1) This application is a U.S. National Stage Application under 35 U.S.C. § 371 of PCT Application No. PCT/KR2023/004540, filed Apr. 4, 2023, which claims priority to Korean Patent Application Nos. 10-2022-0041872, filed Apr. 4, 2022, 10-2022-0082522, filed Jul. 5, 2022 and 10-2023-0027665, filed Mar. 2, 2023, whose entire disclosures are hereby incorporated by reference.

TECHNICAL FIELD

(2) An embodiment relates to a lighting device having a light source. One embodiment relates to a vehicle lamp having a lighting device.

BACKGROUND ART

(3) Lighting applications include vehicle lights as well as backlights for displays and signs. Light emitting device, such as light emitting diode (LED), have advantages such as low power consumption, semi-permanent life, fast response speed, safety, and environmental friendliness compared to conventional light sources such as fluorescent lamps and incandescent lamps. These light emitting diodes are applied to various display devices, various lighting devices such as indoor or outdoor lights. Recently, as a vehicle light source, a lamp employing a light emitting diode has been proposed. Compared with incandescent lamps, light emitting diodes are advantageous in that power consumption is small. However, since an emission angle of light emitted from the light emitting diode is small, when the light emitting diode is used as a vehicle lamp, there is a demand for increasing the light emitting area of the lamp using the light emitting diode. Light emitting diodes can increase the design freedom of lamps because of their small size, and they are also economical because of their semi-permanent lifespan.

DISCLOSURE

Technical Problem

(4) An embodiment of the invention provides a lighting device having an improved light distribution image. An embodiment of the invention provides a lighting device having a line width and made of a flexible material for a daytime running light (DRL). An embodiment of the invention can provide a lamp for a vehicle such as a mobile body having the lighting device described above.

Technical Solution

(5) The lighting device according to an embodiment of an invention comprises a substrate having a length in a second direction longer than a width in a first direction; a plurality of light sources arranged on the substrate in a second direction; a lighting module having a light guide portion disposed on the substrate and the light sources; an optical lens disposed on the lighting module, the optical lens having an incident surface having a width greater than a width of the lighting module in the first direction, and an exit surface from which light incident on the incident surface is emitted; and a reflective member having an insertion hole in which the light guide portion is disposed, a reflective portion extending to both sides of the insertion hole and covering both sides of the light guide portion, and a support portion supporting a lower edge of the optical lens, wherein the light guide portion and the insertion hole have a width in the first direction smaller than a length in the second direction, and an upper end of the reflective portions may be positioned higher than an upper end of the light guide portion.

(6) According to an embodiment of the invention, the exit surface of the optical lens may refract light incident on the incident surface into parallel light.

(7) According to an embodiment of the invention, a diffusion layer for diffusing light is included on the light guide portion, and an upper end of the diffusion layer may be positioned higher than the

upper end of the reflective portion.

(8) The diffusion layer is spaced apart from an incident surface of the light guide portion, and a width of the diffusion layer in the first direction may be the same as a width of the light guide portion in the first direction, and a length in the second direction may be the same as a length of the light guide portion in the second direction.

(9) According to an embodiment of the invention, the incident surface may be any one of a concave curved surface, a convex curved surface, or a plane in a short axis direction. The exit surface may have a hemispherical shape or a Fresnel lens pattern.

(10) According to an embodiment of the invention, a housing is included under the reflective member, and the reflective member may include a first recess in which the substrate is received and a second recess in which an upper portion of the housing is received. The reflective member may have a concave groove between the support portion and the reflective portion.

(11) According to an embodiment of the invention, a material of the optical lens is PMMA or PC, and the light guide portion may seal the light sources and be formed of a silicone or epoxy material. The width of the light guide portion in the first direction is in a range of 3 mm to 7 mm, and the length of the light guide portion in the second direction may be 50 times or more the width of the first direction.

(12) A lighting device according to an embodiment of the invention comprises a substrate; a plurality of light sources arranged in one direction on the substrate; a lighting module having a light guide portion covering the plurality of light sources and having a length longer than a width and a diffusion layer disposed on the light guide portion; an optical lens disposed on the lighting module and having an incident surface having a width greater than the width of the lighting module, and an exit surface from which light incident on the incident surface is emitted; and a reflective member having an insertion hole into which the light guide is inserted, a reflective member extending to both sides of the insertion hole and disposed along a periphery of the light guide portion, and a support member supporting a lower edge of the optical lens, wherein the light guide portion and the insertion hole have a length that is at least twice as large as a width, the reflective portion of the reflective member are disposed along both long sides and both short sides of the light guide portion, and the lighting module and the optical lens may have flexibility in a thickness direction and a width direction of the lighting module with respect to a length direction.

(13) According to an embodiment of the invention, an upper end of the reflective member may be positioned higher than an upper end of the light guide portion and lower than an upper end of the diffusion layer. The reflective member may have a concave groove between both outer sides of the reflective member at an inner side and both inner sides of the support member at an outer side. The exit surface of the optical lens may emit parallel light.

(14) A lighting device according to an embodiment of the invention comprises a substrate having a length in a second direction that is longer than a width in a first direction; a plurality of light sources disposed in a second direction on the substrate; a light guide portion arranged on the substrate and covering the plurality of light sources; a diffusion layer disposed on the light guide portion; an optical lens having an incident surface spaced apart from the diffusion layer and having a width greater than a width of the diffusion layer in the first direction, and an exit surface from which light incident on the incident surface is emitted; and a reflection member having an insertion hole in which the light guide portion and the diffusion layer are disposed inside, first and second reflective portions covering extensions to both sides of the insertion hole, and a support portion supporting both edges of the optical lens, wherein the diffusion layer may have an upper width in the first direction smaller than a lower width.

(15) According to an embodiment of the invention, the diffusion layer includes a first region having a width equal to the width of the light guide portion, and a second region having a width smaller than the width of the light guide portion on the first region, and an outer surface of the second region of the diffusion layer may include a curved or inclined surface.

(16) According to an embodiment of the invention, a thickness of the second region may be greater than a thickness of the first region. The reflective member includes first and second protrusions protruding inwardly from one side and the other side of the second region, and a region between the first and second protrusions can expose an upper surface of the second region. The width of the first direction of the incident surface of the optical lens can be in a range of 1.5 to 4.5 times an upper width of the diffusion layer.

(17) A vehicle lamp according to an embodiment of the invention includes the lighting device disclosed above, and the lighting device can be arranged as a line-shaped daytime running light.

Advantageous Effects

(18) According to the lighting device according to the embodiment of the invention, a luminous intensity and image can be improved, and various light distribution images can be provided. In addition, the lighting having a line width that can be applied to daytime running lights can be provided, and the light distribution of the line lighting can be provided uniformly.

(19) An embodiment of the invention can improve the light distribution of the lighting device, use the light image in various forms, and improve the optical reliability of the lighting device and the vehicle lamp having the same. The embodiment of the invention can be applied to a light unit having the lighting device, or an external or internal lighting lamp.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a side cross-sectional view of a lighting device according to an embodiment.

(2) FIG. 2 is a partially enlarged view of the lighting device of FIG. 1.

(3) FIG. 3 is an example of a plan view of the lighting device of FIG. 1.

(4) FIG. 4 (A) to (C) are drawings showing examples of optical lenses in the lighting device of FIG. 1.

(5) FIG. 5 is a drawing explaining a light extraction path of the lighting device of FIG. 1.

(6) FIGS. 6 to 8 are drawings showing shapes, luminous intensity, and light distribution images according to each direction or position of the optical lens in the lighting device of the invention.

(7) FIG. 9 is a first modified example of the side cross-sectional view of the lighting device of FIG. 1.

(8) FIG. 10 is a partially enlarged view of FIG. 9.

(9) FIG. 11 is a drawing showing light distribution images according to each direction or position on the optical lens of FIG. 9.

(10) FIG. 12 is a drawing showing the luminous intensity of the lighting device of FIG. 9.

(11) FIG. 13 is a side cross-sectional view showing a second modified example of the lighting device of FIG. 1.

(12) FIG. 14 is a drawing showing a light distribution image according to each direction or position on the optical lens of FIG. 13.

(13) FIG. 15 is a drawing showing the luminous intensity of the lighting device of FIG. 13.

(14) FIG. 16 is a side cross-sectional view showing a third modified example of the lighting device of FIG. 1.

(15) FIG. 17 is a drawing showing a light distribution image according to each direction or position on the optical lens of FIG. 16.

(16) FIG. 18 is a drawing showing the luminous intensity of the lighting device of FIG. 16.

(17) FIG. 19 is a drawing comparing the light uniformity according to the height of the lighting module in the lighting device according to an embodiment of the invention.

(18) FIG. 20 is a drawing showing a lamp having a lighting device according to an embodiment of the invention.

(19) FIG. 21 is an example of a vehicle taillight of FIG. 20.

(20) FIG. 22 is a drawing for explaining a vehicle driving light to which the lighting device of the invention is applied.

BEST MODE

(21) Hereinafter, preferred embodiments of the invention will be described in detail with reference to the accompanying drawings.

(22) The technical idea of the present invention is not limited to some of the described embodiments, but can be implemented in various different forms, and if it is within the scope of the technical idea of the present invention, one or more of its components may be selectively combined and substituted between embodiments. In addition, terms (including technical and scientific terms) used in the embodiments of the present invention, unless explicitly specifically defined and described, may be interpreted as a meaning that may be generally understood by those skilled in the art to which the present invention belongs, and terms generally used, such as terms defined in the dictionary, may be interpreted in consideration of the context of the related technology. Terms used in the embodiments of the present invention are for describing the embodiments and are not intended to limit the present invention. In the present specification, the singular form may include a plural form unless specifically described in the phrase, and may include at least one of all combinations that may be combined as A, B, and C when described as “A and/or at least one (or more than one) of B and C”. Also, terms such as first, second, A, B, (a), and (b) may be used to describe components of an embodiment of the present invention. These terms are intended only to distinguish the components from other components and are not determined by their nature, sequence, or order. Also, when a component is described as being ‘connected’, ‘coupled’ or ‘connected’ to another component, not only when the component is directly connected, coupled or connected to another component, it may also be ‘connected’, ‘coupled’, or ‘connected’ due to another component between that component and the other component. In addition, when each component is described as being formed or disposed “up (above) or down (bottom)”, the up (down) or down (bottom) includes not only when two components are in direct contact with each other, but also when one or more components are formed or disposed between two components. Also, when expressed as “up (above) or down (bottom)”, it may include the meaning of not only the upward direction but also the downward direction based on one component.

(23) The lighting device according to the embodiment can be applied to various lamp devices requiring lighting, such as vehicle lamps, household lighting devices, and industrial lighting devices. For example, when applied to vehicle lamps, it can be applied to head lamps, side mirror lights, side marker lights, fog lights, tail lamps, brake lights, daytime running lights, vehicle interior lights, door scars, rear combination lamps, backup lamps, and the like. The lighting device of the invention can be applied to indoor and outdoor advertising devices, display devices, and various types of electric vehicles, and can also be applied to all lighting-related fields or advertising-related fields that are currently developed and commercialized or can be implemented in the future with technological advancement.

(24) <Lighting Device>

(25) FIG. 1 is a side cross-sectional view of a lighting device according to an embodiment, FIG. 2 is a partially enlarged view of the lighting device of FIG. 1, FIG. 3 is an example of a plan view of the lighting device of FIG. 1, FIG. 4 (A)-(C) is drawings showing examples of optical lenses in the lighting device of FIG. 1, and FIG. 5 is a drawing explaining a light extraction path of the lighting device of FIG. 1.

(26) Referring to FIGS. 1 to 5, a lighting device **100** according to an embodiment of the invention includes a lighting module **10** and an optical lens **51**. The lighting module **10** may include a substrate **11**, a light source **13** arranged on the substrate **11**, and a light guide portion **15** covering the light source **13**. The lighting module **10** may further include a diffusion layer **17** on the light guide portion **15**. The lighting module **10** may have an upper width **D1** in a first direction X smaller

than a length in a second direction Y. The lighting module **10** may provide line light having a narrow upper width **D1** and a long length in the second direction Y, and the line light may have a width equal to the upper width **D1** of the lighting module **10** and may be emitted with a uniform surface light distribution. In the drawing, the X direction may be the first direction, the Y direction may be the second direction orthogonal to the X direction, and the Z direction may be the thickness direction of the lighting module **10** and the third direction orthogonal to the first and second directions.

(27) The height **T1** of the lighting module **10** may be larger than the width **D1** in the first direction X and smaller than the length in the second direction Y. Here, a ratio of the height **T1** and the width **D1** may be arranged as 4:3 to 10:3, and the height **T1** may be 4 mm or more, for example, in a range of 4 mm to 10 mm, and the width **D1** may be 7 mm or less, for example, in a range of 3 mm to 7 mm or in a range of 4 mm to 6.5 mm. The height **T1** may be 1.3 times or more of the width **D1**, for example, 1.3 to 3 times or 1.3 to 2.5 times. Since the lighting module **10** has a thin width **D1**, the lighting module **10** may have a ductility that is convexly or concavely deformed in the first direction X with respect to the second direction Y. In addition, since the lighting module **10** has a low height **T1**, the lighting module **10** may have a ductility that is convexly or concavely deformed in the third direction Z with respect to the second direction Y. In addition, the optical lens **51** may have ductility in the same direction as the lighting module **10**.

(28) The substrate **11** of the lighting module **10** may include a printed circuit board (PCB). The substrate **11** may include, for example, at least one of a resin-based printed circuit board (PCB), a metal core PCB, a flexible PCB, a ceramic PCB, or an FR-4 substrate. When the substrate **11** is a flexible PCB, the lighting device **100** having the lighting module **10** may be provided with flexibility.

(29) The substrate **11** may be electrically connected to the light source **13**. The substrate **11** includes a wiring layer (not shown) on an upper side, and the wiring layer may be electrically connected to the light source **13**. When the light sources **13** are arranged in plurality of light sources on the substrate **11**, the plurality of light sources **13** may be connected in series, in parallel, or in series-parallel by the wiring layer. The substrate **11** may function as a base member or a support member disposed at lower portion of the light source **13** and the light guide portion **15**.

(30) The upper surface of the substrate **11** may have an X-Y plane. The upper surface of the substrate **11** may be a flat plane or a curved surface. The thickness of the substrate **11** may be a height in the vertical direction or the Z direction. When a plurality of light sources **13** are arranged on the substrate **11**, the plurality of light sources **13** may be arranged in the second direction Y.

(31) The substrate **11** may be made of a flexible material, and the flexible substrate may be closely attached to the housing of a lamp in a vehicle. The substrate **11** may include a light-transmitting material through which light is transmitted through the upper surface and the lower surface. The light-transmitting material may include at least one of PET (Polyethylene terephthalate), PS (Polystyrene), and PI (Polyimide).

(32) A reflective layer (not shown) may be arranged on the substrate **11**. The reflective layer is arranged between the substrate **11** and the light guide portion **15** and may reflect incident light. The reflective layer may include a metallic material or a non-metallic material. The metallic material may include a metal such as aluminum, silver, or gold. The non-metallic material may include a plastic material or a resin material.

(33) The width of the substrate **11** in the first direction X within the lighting module **10** may be greater than an upper width **D1** of the lighting module **10**. The width of the substrate **11** in the first direction X may be greater than the width **D1** of the lighting module **10**. Here, the width of the lighting module **10** may be the upper width of the light guide portion **15** or the upper width of the diffusion layer **17**.

(34) The light source **13** is arranged between the substrate **11** and the light guide portion **15**, and emits light through the upper surface or through the upper surface and side surfaces. The plurality

of light sources **13** may be arranged along the length direction or the second direction Y of the substrate **11**. The light sources **13** is arranged at the lower portion of the light guide portion **15**, and may be arranged in a single row or two rows along the length direction of the lighting module **10**. The light source **13** may be embedded in the light guide portion **15**. That is, the light guide portion **15** seals the light source **13**. The upper surface of the light source **13** may be arranged above the lower surface of the light guide portion **15**, and multiple side surfaces and the upper surface of the light source **13** may be in contact with the light guide portion **15**.

(35) The light source **13** emits light with the highest intensity in the third direction Z or the optical axis direction. The light source **13** is electrically connected to the substrate **11** and may be provided as an LED chip or a package that covers the surface of the LED chip with resin. The light source **13** is a light emitting device having a light emitting diode (LED) and may include a package in which a light emitting chip is packaged. The light emitting chip may emit at least one of blue, red, green, ultraviolet (UV), or infrared, and the light source **13** may emit at least one of white, blue, red, green, or infrared light, for example, may emit light in colored colors such as white, blue, or green.

(36) The light guide portion **15** may be arranged on a portion of the upper surface of the substrate **11**. The lower surface of the light guide portion **15** may face or contact the substrate **11**. The width D1 of the first direction X of the light guide portion **15** may be the same as the width of the lighting module **100** and may be smaller than the width of the first direction X of the substrate **11**. When a reflective layer is arranged on the upper surface of the substrate **11**, the light guide portion **15** may be in contact with the reflective layer.

(37) The length of the second direction Y of the light guide portion **15** may be the same as or smaller than the length of the second direction of the substrate **11**. The length of the light guide portion **15** in the second direction Y may be the same as the length of the lighting module **10** or may be 80% or more of the length of the lighting module **10** or the substrate **11**. Since the light guide portion **15** is extended in the length direction, surface light having a line width can be provided through the lighting module **10**. The length of the second direction Y of the light guide portion **15** may be provided as twice or more of the width D1 of the first direction X, for example, in a range of 2 to 200 times or in a range of 50 to 200 times. The width of the first direction X of the light guide portion **15** may be 7 mm or less, for example, in a range of 3 to 7 mm or in a range of 4 to 6.5 mm.

(38) The lower surface area of the light guide portion **15** may be smaller than the upper surface area of the substrate **11**. Both side surfaces of the light guide portion **15** may be arranged further outward than both side surfaces of the light source **13**. Accordingly, the light guide portion **15** may seal the light sources **13**, prevent moisture penetration, and sufficiently diffuse light. Here, the outer region of the upper surface of the substrate **11** can be exposed from the lower surface of the light guide portion **15**.

(39) The height or thickness T4 of the light guide portion **15** may be 80% or more of the height T1 from the lower surface of the substrate **11** to the upper surface of the diffusion layer **17**. That is, the thickness T4 of the light guide portion **15** can be 80% or more and less than 100% of the height T1 of the lighting module **10**. Accordingly, the light guide portion **15** can guide the light emitted from the light source **13** in the emission direction and improve the diffusion efficiency of the light.

(40) Both side surfaces of the light guide portion **15**, that is, long side surfaces, may be provided as vertical planes. Coating layers of a reflective material may be formed on both side surfaces of the light guide portion **15**. The coating layer of the reflective material may reflect the incident light toward the emission side and suppress light loss. The above-described reflective material coating layer can reflect the incident light toward the emission side and suppress light loss.

(41) The light guide portion **15** may be formed of a transparent material. The light guide portion **15** may include a resin material such as silicone or epoxy. The light guide portion **15** can include a thermosetting resin material, and can optionally include, for example, PC, OPS, PMMA, PVC, etc. The light guide portion **15** may be formed of glass, but is not limited thereto. For example, the

main material of the light guide portion **15** may use a resin material whose main ingredient is urethane acrylate oligomer.

(42) Since the light guide portion **15** is provided as a layer that guides light with resin, the light guide portion **15** may be provided with a thin thickness compared to glass material and can be provided as a flexible plate. The light guide portion **15** can emit point light emitted from the light source **13** as line light or area light having a line width.

(43) The light guide portion **15** may include a bead (not shown), and the bead may diffuse and reflect incident light to increase the amount of light. The bead may be composed of any one selected from silicon, silica, glass bubble, PMMA (Polymethyl methacrylate), urethane, Zn, Zr, Al.sub.2O.sub.3, and acryl. The light guide portion **15** may protect the internal light sources **13** and reduce the loss of light emitted from the light sources **13**. The light sources **13** may overlap the emission surface of the light guide portion **15** in a vertical direction.

(44) The diffusion layer **17** may be disposed on the light guide portion **15**. The diffusion layer **17** may diffuse light incident from the light guide portion **15**. The diffusion layer **17** may include a diffusion agent therein, and the diffusion agent may include at least one of Al.sub.2O.sub.3, TiO.sub.2, SiO.sub.2, ZnO, and ZrO.sub.2. The diffusion layer **17** may be formed of a transparent resin or a translucent resin material. The diffusion agent in the diffusion layer **17** may be in a range of 8 wt % or more, for example, 8 wt % to 20 wt %, and a hot spot may be generated if it is less than the range, and if it is greater than the range, light extraction efficiency may be degraded.

(45) The thickness T5 or height of the diffusion layer **17** may be less than the thickness T4 or height of the light guide portion **15**, and may be less than 50% of the thickness T4 of the light guide portion **15**. The thickness T5 or height of the diffusion layer **17** may be 1.5 mm or less, for example, in the range of 0.8 mm to 1.5 mm. When the diffusion layer **17** is within the above range, the diffusion effect may be improved and the decrease in luminous intensity may be suppressed.

(46) The lower surface of the diffusion layer **17** is adhered to the upper surface of the light guide portion **15** and may be extended long along the light guide portion **15**. The width of the diffusion layer **17** in the first direction may be equal to or smaller than the width D1 of the light guide portion **15** in the first direction, and the length in the second direction may be equal to or smaller than the length of the light guide portion **15** in the second direction. Since the diffusion layer **17** is disposed on the upper portion of the lighting module **10**, the problem of a hot spot occurring on the upper portion of the light source **13** may be suppressed.

(47) The upper surface of the diffusion layer **17** may have a convex curve, and for example, the corner portion between the upper surface and the side surface of the diffusion layer **17** may have a curve.

(48) Here, the upper surface of the light guide portion **15** is provided as a flat surface or a horizontal surface, and the upper surface of the diffusion layer **17** is provided as a convex curve, so that the incident light may be transmitted to a wide region of the incident surface **53** of the optical lens **51**.

(49) The optical lens **51** may be disposed on the lighting module **10**. The optical lens **51** may be disposed on the diffusion layer **17** of the lighting module **10**. The optical lens **51** may include an incident surface **53** and an exit surface **55**. A portion of the incident surface **53** faces the lighting module **10**, and light emitted from the lighting module **10** is incident. The incident surface **53** may be a concave curved surface, a convex curved surface, or a horizontal plane in the short axis direction. The exit surface **55** may refract light incident through the incident surface **53** when it is guided through the interior. The exit surface **55** may irradiate or collect parallel light. The exit surface **55** may be provided in a convex hemispherical shape or a shell shape. As another example, the exit surface **55** may include a Fresnel lens pattern. The optical lens **51** may be composed of a condenser lens, a parallel light lens, a collimator lens, or a Fresnel lens.

(50) The incident surface **53** of the optical lens **51** is disposed on the upper portion of the light guide portion **15** and may face the upper surface of the diffusion layer **17**. The incident surface **53**

may be spaced apart from the upper surface of the diffusion layer **17**. Since the incident surface **53** of the optical lens **51** is spaced apart from the upper surface of the diffusion layer **17**, light diffused through the diffusion layer **17** may be incident on a wide region of the incident surface **53**. An interval **G1** between the incident surface **53** and the diffusion layer **17** may be 0.01 mm or more, for example, in the range of 0.01 mm to 0.5 mm. Here, the width **D2** of the incident surface **53** is the lower surface width of the optical lens **51**, may be larger than the upper width **D1** of the lighting module **10**, and may be 1.5 times or more, for example, in the range of 1.5 to 10 times or in the range of 2 to 10 times the upper width **D1** of the lighting module **10**. The maximum width **D2** of the optical lens **51** in the first direction **X** may be smaller than or different from the height **T2**. When the maximum width **D2** of the first direction **X** of the optical lens **51** is greater than the height **T2**, the luminous intensity may decrease and the line width may increase. When the maximum width **D2** of the first direction **X** of the optical lens **51** is smaller than the height **T2**, the luminous intensity may increase and the line width may decrease. Accordingly, the maximum width **D2** and the height **T2** of the optical lens **51** in the first direction **X** may be adjusted to suit the light distribution image.

(51) The length of the optical lens **51** in the second direction **Y** may be equal to or greater than the length of the lighting module **10**. Accordingly, when viewed from the outside of the lighting device **100**, a surface of the optical lens **51** may be exposed, and an upper configuration of the lighting module **10** may not be exposed.

(52) The optical lens **51** may include a light-transmitting material, and may optionally include, for example, PC, OPS, PMMA, PVC, etc. The optical lens **51** may include a resin material such as silicone or epoxy or a thermosetting material. The refractive index of the optical lens **51** may be in the range of 1.4 to 1.6. Since the optical lens **51** has the material and refractive index as described above, it can refract the incident light toward the target without loss. The optical lens **51** may emit light as a surface light having a line width of 30 mm or less in the first direction **X** and a long length in the second direction **Y**. Accordingly, the external image of the lighting device **100** may be provided as an image having the line width. That is, as shown in FIG. **21**, it may emit light as an image having the line width.

(53) As shown in FIG. **4** (A)-(C), the optical lens **51** may have a concave curved shape or a convex curved shape based on the length direction, or may have a shape in which one end and the other end of the optical lens **51** are twisted in opposite directions.

(54) As shown in FIG. **4** (A), an incident surface **53A** of the optical lens **51** has a convex surface having a first radius of curvature in the short-axis direction, as shown in FIG. **4** (B), an incident surface **53B** has a convex surface having a second radius of curvature greater than the first radius of curvature in the short-axis direction, and as shown in FIG. **4**(C), an incident surface **53C** has a concave surface having a third radius of curvature in the short-axis direction. The first and second radii of curvature have a difference of 20 mm or more and have a positive radius of curvature, and the third radius of curvature has a negative radius of curvature, and may have a difference of 20 mm or more from the first radius of curvature in absolute value. The first radius of curvature is 50 mm or more, and the second and third radii of curvature are less than 50 mm, and may be the same as each other or have a difference of 5 mm or less.

(55) The lighting device **100** may include at least one or both of a housing **31** and a reflective member **40** for coupling to a moving body such as a vehicle. The housing **31** may support the lighting module **10** and the reflective member **40**. The housing **31** supports the lower surface of the substrate **11** of the lighting module **10**, and both side extension portions **32** and **33** extending in the width direction support an outer lower surface of the reflective member **40**. The housing **31** may be a heat dissipation member.

(56) The reflective member **40** has an insertion hole **R1** therein and includes first and second bottom portions **41** and **41A** disposed on both sides of the substrate **11**. The first and second bottom portions **41** and **41A** may be connected to each other on both short sides in the length direction of

the lighting module **10**. The reflective member **40** includes first and second reflective portions **42** and **43** on both sides of the insertion hole **R1**, and the first and second reflective portions **42** and **43** have the insertion hole **R1** inside and may protrude from the inside of the first and second bottom portions **41** and **41A** toward the incident surface **53**. The width of the insertion hole **R1** in the first direction **X** may be smaller than the length in the second direction **Y**. The width of the insertion hole **R1** in the first direction corresponds to the width of the light guide portion **15** in the first direction, and the length in the second direction corresponds to the length of the light guide portion **15** in the second direction. The insertion hole **R1** has a line shape in the top view.

(57) The first and second reflective portions **42** and **43** may be disposed on both long sides of the light guide portion **15**. The first and second reflective portions **42** and **43** may be extended to both sides of the insertion hole **R1**. Accordingly, the first and second reflective portions **42** and **43** may reflect light incident on both long sides of the light guide portion **15** and re-incident it into the light guide portion **15**. The first and second reflective portions **42** and **43** may be connected to each other on both short sides of the light guide portion **15** in the length direction.

(58) The reflective member **40** includes a concave portion **C0** that is concavely recessed, and the concave portion **C0** may include a region lower than the incident surface **53** of the optical lens **51**. An interval **G1** between the diffusion layer **17** and the incident surface **53** may be provided at a center interval in the concave portion **C0**. The interval **G1** is a distance spaced in the vertical direction, and the width of the region having the interval **G1** may be smaller than the width of the lower surface of the diffusion layer **17** in the first direction **X**, and the length may be equal to the length of the diffusion layer **17** in the second direction **Y**.

(59) A height **G4** of the upper end of the first and second reflective portions **42** and **43** is a height from the bottom of the concave first and second grooves **C1** and **C2**, and may be positioned higher than the upper end of the light guide portion **15**. Accordingly, the first and second reflective portions **42** and **43** may reflect light leaking through the side of the light guide portion **15**, thereby improving the light extraction efficiency of the lighting module **10**. The first and second grooves **C1** and **C2** may be disposed on both sides of the concave portion **C0**. The first and second grooves **C1** and **C2** may be disposed on both sides of the first direction **X** of the concave portion **C0**. The first and second grooves **C1** and **C2** may be disposed on both sides of the first and second directions of the concave portion **C0**.

(60) The height **G4** of the upper end of the first and second reflective portions **42** and **43** of the reflective member **40** may be arranged lower than the upper end of the diffusion layer **17**. That is, the interval **G2** between the first and second reflective portions **42** and **43** and the incident surface **53** may be greater than the interval **G1** between the diffusion layer **17** and the incident surface **53**. Accordingly, the first and second reflective portions **42** and **43** reflect light incident through the side surface of the light guide portion **15** and enable light emission through the side surface of the diffusion layer **17**. In addition, the upper surfaces of the first and second reflective portions **42** and **43** may reflect light emitted through the diffusion layer **17** to the incident surface **53** of the optical lens **51**.

(61) The reflective member **40** includes first and second lens support portions **45** and **46**, and the first and second lens support portions **45** and **46** may be disposed along the outer edge of the optical lens **51**. The first and second lens support portions **45** and **46** have a stepped structure **45A** and **46A** that is concavely stepped inward from the upper end thereof, and the stepped structure **45A** and **46A** supports the outer edge of the optical lens **51**. As shown in FIG. 3, the first and second lens support portions **45** and **46** may further include a stepped structure **45B** and **46B** that supports the outer edge of the optical lens **51** in a short side.

(62) The upper ends of the first and second lens support portions **45** and **46** may be positioned higher than the lower end or the outer edge of the incident surface **53** of the optical lens. Accordingly, the lower edge of the optical lens **51** may be coupled along the inner upper ends of the first and second lens support portions **45** and **46**. At this time, the lower edge of the optical lens

51 may be bonded to the stepped structure **45A** and **46A** with an adhesive. The height **G3** of the stepped structure **45A** and **46A** may be smaller than the height to the upper ends of the first and second lens support portions **45** and **46** and larger than the height to the upper surface of the diffusion layer **17**. Since the height **G4** from the substrate **11** to the stepped structure **45A** and **46A** is positioned higher than a position of the upper surface of the diffusion layer **17**, the incident surface **53** of the optical lens **51** and the diffusion layer **17** may be spaced apart from each other. (63) The width **D3** of the first direction **X** of the reflective member **40** may be greater than the lower width **D2** of the optical lens **51**. The height **T3** from the lower surface of the substrate **11** to the upper end of the optical lens **51** may be equal to or greater than the width **D3** of the reflective member **40** in the first direction. In this case, the optical lens **51** may have a hemispherical exit surface. As another example, the height **T3** from the lower surface of the substrate **11** to the upper end of the optical lens **51** may be equal to or less than the width **D3** of the reflective member **40** in the first direction. In this case, the exit surface **55** of the optical lens **51** may include a Fresnel lens pattern.

(64) The reflective member **40** includes first and second recesses **R2** and **R3** on the bottom, and the upper portion of the housing **31** may be received or coupled to the second recess **R3**. The second recess **R3** includes the first recess **R2** on the inside, and the substrate **11** may be inserted or received into the first recess **R2**. The first recess **R2** has a depth equal to or greater than the thickness of the substrate **11** from the second recess **R3**, so that the lower surface of the substrate **11** may have a depth that does not protrude outward from the first recess **R2**. The substrate **11** may be adhered to the housing **31** with an adhesive, or may be adhered to the reflective member **40** within the first recess **R2**.

(65) A width of the first recess **R2** may be smaller than a width of the second recess **R3**, and the width of the second recess **R3** may be the width of the upper surface of the housing **31**, which is equal to or greater than 80% of the width **D2** of the lower surface of the optical lens **51**, such that the housing **31** may be supported at the lower portion of the lighting device **100**. As another example, when the housing **31** is a heat dissipation member made of a metal or non-metal material, it can effectively dissipate heat transferred from the substrate **11**. The upper ends of the both side extension portions **32** and **33** of the housing **31** may be in contact with or coupled with the both lower ends of the reflective member **40**, and may prevent the reflective member **40** from being pushed downward or tilted.

(66) The reflective member **40** may include a first groove **C1** on one side of the concave portion **C0** and a second groove **C2** on the other side. The first groove **C1** may be concavely disposed between the first reflective portion **42** and the first lens support portion **45**, and the second groove **C2** may be concavely disposed between the second reflective portion **43** and the second lens support portion **46**. The width **D4** of each of the first and second grooves **C1** and **C2** is disposed in a region that is equal to or larger than the width **D1** of the light guide portion **15**, and the surfaces of the first and second grooves **C1** and **C2** may reflect light reflected through the incident surface **53** of the optical lens **51**. The first and second grooves **C1** and **C2** are extended along the long side of the light guide portion **15** and may be connected to each other on the short side of the light guide portion **15**.

(67) For the purpose of explaining FIGS. **6** to **8**, each optical lens will be defined as a first to sixth lens. FIG. **6(A)** is a shape of the first lens having a convex incident surface and a convex exit surface with a first radius of curvature, and FIG. **6(B)** is a shape of the second lens having a convex incident surface and a convex exit surface with a second radius of curvature. FIG. **7(A)** is a shape of the third lens having a concave incident surface and a convex exit surface with a third radius of curvature, and FIG. **7(B)** is a shape of the fourth lens having a flat incident surface and an exit surface of a Fresnel lens pattern. FIG. **8(A)** is a shape of the fifth lens having a flat incident surface and a convex exit surface, and FIG. **8(B)** is a shape of the sixth lens having the same shape as the fifth lens but a different material.

(68) The material of the first to fifth lenses is PMMA, and the material of the sixth lens is PC. The

difference between the first and second curvature radii is less than 20 mm, and the first curvature radius is 50 mm or more, for example, in a range of 50 mm to 90 mm, and the second curvature radius may be less than 50 mm, for example, in a range of 10 mm to 49 mm. The third curvature radius has a negative curvature radius, and may be less than 20 and less than 50 mm, for example, in a range of 10 mm to 49 mm, in absolute value with respect to the radius of the first lens.

(69) The luminous intensity of the third lens is greater than that of the first, second, fourth, fifth, and sixth lenses, and the second lens may be the smallest. It may be seen that the luminous intensity of the sixth lens is lower than that of the first, third, fourth, and fifth lenses. Accordingly, it may be seen that the optical lens is made of PMMA material and a high luminous intensity when it is the concave incident surface or the flat incident surface and the convex exit surface.

(70) In FIGS. 6 to 8, when the lighting device disclosed above is applied to the front, rear, side, or inside of a moving body, **10U** (Up) is a drawing viewed from 10 degrees upward, **5U** (Up) is a drawing viewed from 5 degrees upward, **HV** is a drawing viewed from the intersection of the horizontal and vertical positions based on the lighting device of the moving body, and **10L** (Left), **20L**, **40L**, **60L**, and **80L** are drawings viewed from the left at 10 degrees, 20 degrees, 40 degrees, 60 degrees, and 80 degrees, respectively.

(71) In FIGS. 6 to 8, it may be seen that the light distribution image at **10U** (Up) shows that the first lens, the third lens, the fifth lens, and the sixth lens uniformly distribute light. The light distribution image at **5U** (Up) shows that the light distribution of the first lens, the third lens, the fourth lens, and the fifth lens is uniform. The light distribution image at **HV** shows that the fourth lens, the fifth lens, and the sixth lens have uniform distributions, and the light distribution images at **10L** (Left), **20L**, **40L**, **60L**, and **80L** show that the fourth lens and the fifth lens have more uniform distributions than the other lenses. Therefore, the light distribution image and the light intensity of the first, third, or fifth lens are higher than those of the other lenses. This can provide a uniform distribution of the light distribution image by using a lens having a concave or convex incident surface with a radius of curvature in the width direction of less than 50 and a convex exit surface.

(72) When comparing the luminous intensity when the width of the lighting module is 3 mm and when it is 4 mm, it may be seen that the luminous intensity at the width of 3 mm is higher than the luminous intensity at the width of 4 mm at the **HV** point and its surroundings **H5L** and **H5R**. When comparing the luminous intensity when the height of the lighting module is 6 mm and when it is 5 mm, it may be seen that the luminous intensity is higher than the reference value in all regions when the heights are 5 mm and 6 mm. When comparing the luminous intensity when the height of the lighting module is 7 mm and when it is 4 mm, it may be seen that even if there is a difference in the height of the lighting module, each lighting module shows the luminous intensity higher than the reference value in all regions.

(73) Hereinafter, modified examples of FIG. 1 will be described, and the configuration of the modified examples may be selectively applied to the same configuration as the configuration of the embodiment disclosed above, and redundant description will be omitted. These lighting modules may have ductility characteristics according to the ductility characteristics of the optical lens, and the configuration of the housing disclosed in FIG. 1 may be optionally included.

(74) FIG. 9 is a first modified example of a side cross-sectional view of the lighting device of FIG. 1, FIG. 10 is a partial enlarged view of FIG. 9, FIG. 11 is a drawing showing a light distribution image according to each direction or position on the optical lens of FIG. 9, and FIG. 12 is a drawing showing the luminous intensity of the lighting device of FIG. 9. Referring to FIGS. 9 and 10, the lighting device **100A** includes a lighting module **10** and an optical lens **51**. The lighting module **10** may include a substrate **11**, a light source **13** arranged on the substrate **11**, and a light guide portion **15** covering the light source **13**. The lighting module **10** may further include a diffusion layer **17** on the light guide portion **15**.

(75) The width **D1** of the first direction **X** of the light guide portion **15** may be the same as the width of the lower surface and the width of the upper surface. The diffusion layer **17** is disposed on

the light guide portion **15** and may be spaced apart from the incident surface **53** of the optical lens **51** by a predetermined interval **G1**.

(76) The upper width **D5** of the diffusion layer **17** in the first direction **X** may be smaller than the width of the lower surface (e.g., **D1**). By providing the upper width **D5** of the diffusion layer **17** in the first direction **X** to be narrower than the width of the lower surface, the diffusion layer **17** can provide higher luminous intensity. In addition, by providing the upper width of the diffusion layer **17** to be narrower than the width of the lower surface, a hot spot in the light emitted through the optical lens **51** can be prevented. That is, when the upper width of the diffusion layer **17** is made the same as the lower width, light emitted from the edge portion of the first direction of the diffusion layer **17** is emitted as a surface light image through the optical lens **51**, and at this time, a hot spot may occur along one side or the edge of the surface light image. Therefore, a modified example of the invention provides the upper width of the diffusion layer **17** to be narrower than the width of the light guide portion **15**, so that a hot spot caused by light traveling to the edge of the diffusion layer **17** can be prevented.

(77) In the diffusion layer **17**, the thickness **T51** of the first region **17B** having the lower width **D1** may be smaller than the thickness **T52** of the second region **17C** having a width smaller than the lower width **D1**. The first region **17B** is a region that is adhered to the upper surface of the light guide portion **15**, and the second region **17C** may include at least one of an inclined surface, a convex curved surface, or a vertically stepped surface from the upper end of the first region **17B**. Preferably, the outer region of the second region **17C** may include an inclined surface or a curved surface.

(78) The upper surface **17A** of the diffusion layer **17** may be provided as a flat surface or the highest surface between the upper ends of the second region **17C**. As another example, the upper surface **17A** of the diffusion layer **17** may be provided as a rough structure. The upper width **D5** of the diffusion layer **17** is a width of a region exposed to the upper portion **R11** of the through hole **R1**, and may be larger than the width **D6** of the upper surface **17A**. In addition, since the width **D6** of the upper surface **17A** of the diffusion layer **17** is provided to be smaller than the width (i.e., **D5**) of the upper portion **R11** of the through hole **R1** of the second region **17C**, light traveling toward the lower edge of the diffusion layer **17** can be guided toward the center or in the direction of the optical axis. The width **D1** of the light guide portion **55** may be 7 mm or less, for example, in a range of 3 mm to 7 mm or in a range of 4 mm to 6.5 mm. A width of the lower surface of the diffusion layer **17** may be 7 mm or less, for example, in a range of 3 mm to 7 mm or in a range of 4 mm to 6.5 mm. The upper surface width **D5** of the diffusion layer **17** may be 6 mm or less, for example, in a range of 3 mm to 6 mm or in a range of 4 mm to 5.5 mm. The width **D6** of the upper surface of the diffusion layer **17** may have a difference of 1 mm or less from the upper width **D5**.

(79) The width **D2** of the incident surface **53** of the optical lens **51** in the first direction **X** may be 1.5 times or more the upper width **D5** of the lighting module **10** or the upper width **D5** of the diffusion layer **17**, for example, in the range of 1.5 to 2.5 times or 1.7 to 2.3 times. This reduces the upper width **D5** of the diffusion layer **17**, thereby reducing the width **D2** of the incident surface **53** of the optical lens **51**. The width **D2** of the incident surface **53** of the optical lens **51** in the first direction **X** may be greater than 5 mm.

(80) The lighting device **100A** may include at least one or both of a housing **31** (see FIG. 1) and a reflective member **40** in order to be coupled to a moving body such as a vehicle. The housing **31** (see FIG. 1) may support the lighting module **10** and the reflective member **40**.

(81) The reflective member **40** includes a concave portion **C0** that is concavely recessed at the upper portion thereof, and the concave portion **C0** may include a region lower than the incident surface **53** of the optical lens **51**. The concave portion **C0** may be provided with an interval **G1** between the diffusion layer **17** and the incident surface **53** as a center interval. The interval **G1** is a distance spaced in the vertical direction, and the width of the region having the interval **G1** may be smaller than the width of the lower surface of the diffusion layer **17** in the first direction **X**, and the

length may be equal to the length of the diffusion layer **17** in the second direction **Y**.

(82) The reflective member **40** may have an insertion hole **R1** therein, and may include first and second reflective portions **42A** and **43A** on both sides of the insertion hole **R1**. The first and second reflective portions **42A** and **43A** may have the insertion hole **R1** therein, and may protrude toward the incident surface **53** of the optical lens **51**. The width of the insertion hole **R1** in the first direction **X** may be smaller than the length in the second direction **Y**. The width of the insertion hole **R1** in the first direction may correspond to the width of the light guide portion **15** in the first direction, and the length in the second direction may correspond to the length of the light guide portion **15** in the second direction. The insertion hole **R1** has a top-view shape of a long line in the second direction.

(83) The first and second reflective portions **42A** and **43A** may be disposed on both long sides of the light guide portion **15**. The first and second reflective portions **42A** and **43A** may be extended to both sides of the insertion hole **R1**. Accordingly, the first and second reflective portions **42A** and **43A** may reflect light incident on both long sides of the light guide portion **15** and re-incident it into the light guide portion **15**. The first and second reflective portions **42A** and **43A** may be connected to each other on both short sides of the light guide portion **15** in the length direction.

(84) The upper width (i.e., **D5**) of the insertion hole **R1** in the first direction **X** may be smaller than the lower width (e.g., **D1**). Here, the reflective member **40** may include a first protrusion **P1** and a second protrusion **P2** that protrude inwardly from the upper end of the insertion hole **R1**. The first protrusion **P1** may extend obliquely inwardly from one upper side of the first region **17B** of the diffusion layer **17**. The second protrusion **P2** may extend obliquely inwardly from the other upper side of the first region **17B** of the diffusion layer **17**.

(85) The second region **17C** of the diffusion layer **17** may be exposed as a region between the first and second protrusions **P1** and **P2**. The upper surface **17A** of the diffusion layer **17** may be the same plane as the upper surfaces of the first and second protrusions **P1** and **P2**, or may be arranged within a range of $+0.5$ mm based on the upper surfaces of the first and second protrusions **P1** and **P2**. A protrusion length **D7** of each of the first and second protrusions **P1** and **P2** is a distance between the inner surface and the straight line extending from the side surface of the light guide portion **15**, and may be in the range of 0.5 mm $+0.1$ mm. By using this protrusion length **D7**, the upper width of the diffusion layer **17** can be reduced, thereby preventing a hot spot.

(86) The inner surface of the first and second protrusions **P1** and **P2** may include an inclined surface or a concave curved surface. The minimum interval between the first and second protrusions **P1** and **P2** may be greater than the width **D6** of the upper surface of the diffusion layer **17**, and may be equal to the upper width **D5** of the diffusion layer **17**. The minimum interval between the first and second protrusions **P1** and **P2** is a width for exposing the upper portion of the diffusion layer **17**, and may be a width at which the second region **17C** is exposed to the upper portion **R11** of the insertion hole **R1**.

(87) The reflective member **40** has first and second lens support members **45** and **46** on both sides of the concave portion **C0**, and is structured to be able to remove the first and second grooves **C1** and **C2** disclosed in FIG. 1. Since the entire region of the concave portion **C0** of the reflective member **40** faces the incident surface **53** of the optical lens **51** at a constant interval, light loss within the concave portion **C0** can be reduced.

(88) The first lens support member **45** may extend or protrude on the first reflective portion **42A**, and the second lens support member **46** may extend or protrude on the second reflective portion **43A**.

(89) The width **D2** of the incident surface **53** of the optical lens **51** in the first direction **X** may be greater than the height **T2**. The length of the incident surface **53** of the optical lens **51** in the second direction **Y** may be greater than the width **D2**, and the lengths of the incident surface **53** and the exit surface **55** in the second direction may be the same. As another example, the length of the incident surface **53** in the second direction may be greater than the length of the exit surface **55**.

(90) As shown in FIG. 11, when the lighting device of FIG. 9 is applied to the front, rear, side or inside of a moving body, 2U (Up) is a drawing viewed from 2 degrees upward based on the intersection point where the horizontal and vertical intersect with respect to the lighting device of the moving body, 10U (Up) is a drawing viewed from 10 degrees upward, 20U (Up) is a drawing viewed from 20 degrees upward, and H-V is a drawing viewed from the intersection point of the horizontal and vertical positions. As shown in these drawings, the lighting device may be provided as a line image having a constant width, and the line width may be smaller when viewed from 10 degrees or 20 degrees upward rather than from 2 degrees. As shown in FIG. 12, it may be seen that the luminous intensity of the lighting device of FIG. 9 does not differ greatly between the center luminous intensity and the edge luminous intensity, and the full width at half maximum (FWHM) of the luminous intensity is 40 degrees or more, for example, about 45 ± 2 degrees.

(91) FIG. 13 is a cross-sectional view showing a second modified example of the lighting device of FIG. 1, FIG. 14 is a drawing showing a light distribution image according to each direction or position on the optical lens of FIG. 13, and FIG. 15 is a drawing showing the luminous intensity of the lighting device of FIG. 13. The second modified example is structurally the same as the first modified example, and is an example in which the width of the incident surface 51 of the optical lens 51 is increased.

(92) Referring to FIG. 13, the lighting device 100A includes a lighting module 10 and an optical lens 51. The lighting module 10 may include a substrate 11, a light source 13 arranged on the substrate 11, and a light guide portion 15 covering the light source 13. The lighting module 10 may further include a diffusion layer 17 on the light guide portion 15.

(93) The width D1 of the first direction X of the light guide portion 15 may be the same as the width of the lower surface and the width of the upper surface. The diffusion layer 17 is arranged on the light guide portion 15 and may be spaced apart from the incident surface 53 of the optical lens 51 by a predetermined interval G1. The width D2 of the incident surface 53 of the optical lens 51 in the first direction X is more than 10 mm and may be 2.5 times or more, for example, 2.5 to 3.5 times, of the upper width D5 of the diffusion layer 17.

(94) The lighting device 100A may include at least one or both of a housing (31 of FIG. 1) and a reflective member 40 in order to be coupled to a moving body such as a vehicle. The housing (31 of FIG. 1) may support the lighting module 10 and the reflective member 40.

(95) As shown in FIG. 14, when the lighting device of FIG. 13 is applied to the front, rear, side or inside of a moving body, 2U (Up) is a drawing viewed from 2 degrees upward based on the intersection point where the horizontal and vertical intersect with respect to the lighting device of the moving body, 10U (Up) is a drawing viewed from 10 degrees upward, 20U (Up) is a drawing viewed from 20 degrees upward, and H-V is a drawing viewed from the intersection point of the horizontal and vertical positions. As shown in these drawings, the lighting device may be provided as a line image having a constant width, and the line width may be smaller when viewed from 10 degrees or 20 degrees upward than from 2 degrees. As shown in FIG. 15, it can be seen that the luminous intensity of the lighting device of FIG. 13 does not differ greatly between the center luminous intensity and the edge luminous intensity, and FWHM of the luminous intensity is less than 40 degrees, for example, approximately 34 ± 2 degrees.

(96) FIG. 16 is a cross-sectional view showing a third modified example of the lighting device of FIG. 1, FIG. 17 is a drawing showing a light distribution image according to each direction or position on the optical lens of FIG. 16, and FIG. 18 is a drawing showing the luminous intensity of the lighting device of FIG. 16. The third modified example is structurally the same as the first modified example, and is a configuration in which the width of the incident surface 51 of the optical lens 51 is increased, and the shape of the reflective member 40 is changed due to the increased width of the incident surface 51 of the optical lens 51.

(97) Referring to FIG. 16, the lighting device 100A includes a lighting module 10 and an optical lens 51. The lighting module 10 may include a substrate 11, a light source 13 arranged on the

substrate **11**, and a light guide portion **15** covering the light source **13**. The lighting module **10** may further include a diffusion layer **17** on the light guide portion **15**.

(98) The width **D1** of the light guide portion **15** in the first direction **X** may be the same as the width of the lower surface and the width of the upper surface. The diffusion layer **17** is arranged on the light guide portion **15** and may be spaced apart from the incident surface **53** of the optical lens **51** by a predetermined interval **G1**. The width **D2** of the incident surface **53** of the optical lens **51** in the first direction **X** is greater than 15 mm and less than 25 mm, and may be 3.5 times or more, for example, 3.5 to 4.5 times, of the upper width **D5** of the diffusion layer **17**.

(99) The lighting device **100A** may include at least one or both of a housing (**31** of FIG. **1**) and a reflective member **40** in order to be coupled to a moving body such as a vehicle. The housing (**31** in FIG. **1**) above can support the lighting module **10** and the reflective member **40**.

(100) As shown in FIG. **17**, when the lighting device of FIG. **16** is applied to the front, rear, side or inside of the moving body, **2U** (Up) is a drawing viewed from 2 degrees above based on the intersection point where the horizontal and vertical intersect with respect to the lighting device of the moving body, **10U** (Up) is a drawing viewed from 10 degrees above, **20U** (Up) is a drawing viewed from 20 degrees above, and **H-V** is a drawing viewed from the intersection point of the horizontal and vertical positions. As shown in these drawings, the lighting device may be provided as a line image having a constant width, and the line width may be smaller when viewed from 10 degrees above than from 2 degrees, and the line width may be smaller than 50% when viewed from 20 degrees above. As shown in FIG. **18**, the luminous intensity of the lighting device of FIG. **16** is not significantly different from the center luminous intensity and the edge luminous intensity, and the FWHM of the luminous intensity is less than 30 degrees, for example, about 27 ± 2 degrees. FIG. **19(A)** shows the brightness uniformity when the height of the lighting module disclosed above is 7 mm, and FIG. **19(B)** shows the brightness uniformity when the height of the lighting module is 4 mm, and it may be seen that both are 120000 cd/m².

(101) FIG. **20** is a plan view of a vehicle to which a lighting device according to an embodiment is applied, and FIG. **21** is a drawing showing an example of a tail lamp of the vehicle of FIG. **20**.

(102) Referring to FIGS. **20** and **21**, a front lamp **2100** in a mobile or vehicle **2000** may include one or more lighting modules, and the driving timing of these lighting modules may be individually controlled to provide not only a function as a conventional headlight, but also additional functions such as a welcome light or a celebration effect when a driver opens a vehicle door. The lamp may be applied to a daytime running light, a high beam, a low beam, a fog light, or a turn signal. A tail lamp **2200** and **800** in a vehicle **2000** may be arranged as a plurality of lamp units **810**, **812**, **814** and **816** supported by a housing. For example, the lamp units **810**, **812**, **814** and **816** may include a first lamp unit **810** arranged on the outside, a second lamp unit **814** arranged on the inside periphery of the first lamp unit **810**, and third and fourth lamp units **814** and **816** arranged on the inside of the second lamp unit **814**, respectively. The first to fourth lamp units **810**, **812**, **814** and **816** may selectively apply the lighting device disclosed in the embodiment, and a red lens cover or a white lens cover may be arranged on the outside of the lighting device for the lighting characteristics of the lamp unit **810**, **812**, **814** and **816**. The lighting device disclosed in the embodiment applied to the lamp units **810**, **812**, **814**, and **816** may emit surface light with a uniform distribution.

(103) The first and second lamp units **810** and **812** may be provided in at least one of a curved shape, a straight shape, an angular shape, an inclined shape, or a flat shape, or a mixed structure thereof. The first and second lamp units **810** and **812** may be arranged one or more in each tail lamp. The first lamp unit **810** may be provided as a tail lamp, the second lamp unit **812** may be provided as a stop lamp, the third lamp unit **814** may be provided as a reverse light, and the fourth lamp unit **816** may be provided as a turn signal lamp. Such a lighting lamp may provide a higher luminous intensity in the rearward direction than in the lateral direction, and thus may comply with the lighting distribution regulations for stop lamps or tail lamps, etc.

(104) As shown in FIG. 22, a plurality of lighting devices **100** may be arranged as daytime running lights at the front of the vehicle **2000**, and may be provided in a line shape each having a convex curve.

(105) Features, structures, effects, etc. described in the embodiments are included in at least one embodiment of the invention, and are not necessarily limited to only one embodiment. Furthermore, features, structures, effects, etc. illustrated in each embodiment can be combined or modified for other embodiments by those of ordinary skill in the art to which the embodiments belong. Accordingly, the contents related to such combinations and modifications should be interpreted as being included in the scope of the invention. In addition, although the embodiments have been mainly described above, this is only an example and does not limit the present invention, and one of ordinary skill in the field to which the present invention belongs will appreciate that various modifications and applications not illustrated above may be possible without departing from the essential characteristics of the present embodiment. For example, each component specifically shown in the embodiment can be implemented by modification. And differences related to such modifications and applications should be construed as being included in the scope of the invention defined in the appended claims.

Claims

1. A lighting device comprising: a lighting module including a substrate having a length in a second direction longer than a width in a first direction; a plurality of light sources arranged in the second direction on the substrate; a light guide portion disposed on the substrate and the light sources; an optical lens disposed on the lighting module, the optical lens having an incident surface having a width greater than a width in the first direction of the lighting module, and an exit surface from which light incident on the incident surface is emitted; and a reflective member including an insertion hole in which the light guide portion is disposed, a reflective portion to both sides of the insertion hole and covering both sides of the light guide portion, and a support member supporting a lower edge of the optical lens, wherein the light guide portion and the insertion hole have a width in the first direction smaller than a length in the second direction, and wherein an upper end of the reflective portion is positioned higher than an upper end of the light guide portion.
2. The lighting device of claim 1, wherein the exit surface of the optical lens refracts light incident on the incident surface into parallel light.
3. The lighting device of claim 1, comprising a diffusion layer that diffuses light on the light guide portion, wherein an upper end of the diffusion layer is positioned higher than the upper end of the reflective portion.
4. The lighting device of claim 3, wherein the diffusion layer is spaced apart from the incident surface of the light guide portion, and wherein a width of the diffusion layer in the first direction is the same as the width of the light guide portion in the first direction, and a length in the second direction is the same as the length of the light guide portion in the second direction.
5. The lighting device of claim 1, wherein the incident surface is any one of a concave curved surface, a convex curved surface, or a flat surface in a short axis direction.
6. The lighting device of claim 1, wherein the width of the light guide portion in the first direction is in a range of 3 mm to 7 mm, wherein the length of the light guide portion in the second direction is 50 times or more the width in the first direction.
7. A lighting device comprising: a lighting module including a substrate; a plurality of light sources arranged in one direction on the substrate; a light guide portion covering the plurality of light sources and having a length longer than a width; and a diffusion layer disposed on the light guide portion; an optical lens disposed on the lighting module, the optical lens having an incident surface having a width greater than the width of the lighting module, and an exit surface from which light incident on the incident surface is emitted; and a reflective member including an insertion hole in

which the light guide portion is disposed, a reflective member extending to both sides of the insertion hole and disposed along a periphery of the light guide portion, and a support member supporting a lower edge of the optical lens, wherein the light guide portion and the insertion hole have a length greater than twice a width, wherein the reflective portion of the reflective member is disposed along both long sides and both short sides of the light guide portion, and wherein the lighting module and the optical lens have flexibility in a thickness direction and a width direction of the lighting module with respect to a length direction.

8. The lighting device of claim 7, wherein an upper end of the reflective member is positioned higher than an upper end of the light guide portion and lower than the upper end of the diffusion layer.

9. The lighting device of claim 7, wherein the reflective member has a concave groove between both outer sides of the reflective member at an inner side and both inner sides of the support member at an outer side.

10. A lighting device comprising: a substrate including a length in a second direction longer than a width in a first direction; a plurality of light sources arranged in the second direction on the substrate; a light guide portion disposed on the substrate and covering the plurality of light sources; a diffusion layer disposed on the light guide portion; an optical lens having an incident surface spaced apart from the diffusion layer and having a width larger than a width of the diffusion layer in the first direction, and an exit surface from which light incident on the incident surface is emitted; and a reflective member having an insertion hole in which the light guide portion and the diffusion layer are disposed inside, first and second reflective portions extending to both sides of the insertion hole and covering both sides of the light guide portion and the diffusion layer, and a support portion supporting both edges of the optical lens, wherein the diffusion layer has an upper width in the first direction smaller than a width of a lower surface.

11. The lighting device of claim 10, wherein the diffusion layer includes a first region having a width equal to a width of the light guide portion, and a second region having a width smaller than the width of the light guide portion on the first region, wherein an outer surface of the second region of the diffusion layer includes a curved or inclined surface.

12. The lighting device of claim 11, wherein a width of the first direction of the incident surface of the optical lens is in a range of 1.5 to 4.5 times the upper width of the diffusion layer.

13. The lighting device of claim 11, wherein the optical lens provides a line light having the width of 30 mm or less in the first direction, and wherein the exit surface of the optical lens has a convex hemispherical shape with respect to the first direction of the optical lens.

14. The lighting device of claim 10, wherein the optical lens and the light guide portion have flexibility with respect to at least one of the first and second directions.

15. The lighting device of claim 10, wherein upper surfaces of the light sources is positioned higher than the lower surface of the light guide portion.

16. The lighting device of claim 10, wherein a width of the substrate in the first direction is greater than a width of the light guide portion in the first direction.

17. The lighting device of claim 11, wherein the diffusion layer is adhered to an upper surface of the light guide portion.

18. The lighting device of claim 10, comprising: a first recess in which the substrate is inserted on a bottom of the reflective member.

19. The lighting device of claim 10, wherein the reflective member includes a concave portion facing the incident surface of the optical lens and disposed between the first and second reflective portions and the support portion.

20. The lighting device of claim 10, comprising: a housing disposed under the reflective member and the substrate.
