

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412174
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Droege; James Ryan et al.

Systems and methods for generating a one-time use token for item purchase

Abstract

Systems and methods are disclosed for payment system that uses one-time use tokens for securely facilitating and controlling user purchases using company funds. A user (e.g., driver) may generate a request to make a purchase using a user application. The request may be sent to a server running a payment system that may generate a one-time use token for the purchase of an item (e.g., fuel). The one-time use token may have an expiration time and may only be redeemable at certain locations (e.g., fueling stations) that have been preapproved. The system may send the user application running on the user device the token for purchasing fuel and approved locations. The user may input the token to a controller at an approved location which may request that the server authenticate the token and approve the purchase. Once authenticated and approved, the controller may permit the purchase of the desired item.

Inventors: Droege; James Ryan (Atlanta, GA), Barkoff; Spencer (Atlanta, GA), Koval; Sergii (Atlanta, GA)

Applicant: Relay Payments, Inc. (Atlanta, GA)

Family ID: 88309433

Assignee: Relay Payments, Inc. (Atlanta, GA)

Appl. No.: 18/480894

Filed: October 04, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240412205 A1	Dec. 12, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **G06Q20/38** (20120101); **B67D7/04** (20100101); **B67D7/14** (20100101); **B67D7/34** (20100101); **G06Q50/06** (20120101)

U.S. Cl.:

CPC **G06Q20/385** (20130101); **B67D7/04** (20130101); **B67D7/145** (20130101); **B67D7/348** (20130101); **G06Q50/06** (20130101);

Field of Classification Search

CPC: G06Q (20/38); G06Q (50/06); B67D (7/04); B67D (7/145); B67D (7/348)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3631506	12/1970	Nielsen	235/94R	G07F 7/025
8267317	12/2011	Gulli	705/28	G06Q 30/0185
9792632	12/2016	Betancourt	N/A	G06Q 30/0601
11519770	12/2021	Morris	N/A	N/A
2013/0304544	12/2012	Gillis et al.	N/A	N/A
2015/0316406	12/2014	Gale	701/123	G06Q 10/047
2015/0332264	12/2014	Bondesen et al.	N/A	N/A
2016/0307185	12/2015	Betancourt	N/A	G07F 13/00
2017/0357996	12/2016	Jones	N/A	N/A
2018/0018669	12/2017	Goldberg	N/A	G06Q 20/34
2018/0315040	12/2017	Isaacson	N/A	G06Q 20/12
2019/0205468	12/2018	Barnes, Jr.	N/A	G06F 16/635
2019/0251562	12/2018	Dabiri	N/A	G06Q 50/01
2019/0295077	12/2018	Mardikar	N/A	N/A
2022/0114584	12/2021	Conley et al.	N/A	N/A

Primary Examiner: Anderson; Scott C

Attorney, Agent or Firm: Eversheds Sutherland (US) LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 18/343,381, filed Jun. 28, 2023, which is a continuation of U.S. application Ser. No. 18/333,481, filed Jun. 12, 2023, both of which are hereby incorporated by reference in their entireties.

BACKGROUND

(1) Often in industries like the trucking industry, companies will give their employees or contractors a cost allotment or per diem for purchases related to their job. For example, in the trucking industry, drivers may be given a certain cost allotment for fuel for their truck as well as for trucking supplies (e.g., straps, flaps, locks, etc.). Similarly companies may give their drivers a certain per diem amount for food, snacks and/or coffee. To make these purchases, a driver may be given a credit or debit card (e.g., with a magnetic strip), which may be associated with the company. The card may have certain pay limits (e.g., a set amount per day). While the companies can set rudimentary constraints on the payments (e.g., only 20 dollars per day) a company is limited in its ability to control what is purchased with the card, when the purchases are made, and where. Further, such a payment system is susceptible to fraud as drivers can use their card to make purchases for other drivers. Also, a lost card could be used by a non-authorized individual to make purchases. Similar payment risks and concerns exist in other industries such as delivery and repair services. Accordingly, there is a need for a company payment system permitting companies or other entities more control over the purchases made using company funds and reducing the risk of unauthorized purchases.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The detailed description is set forth with reference to the accompanying drawings. The drawings are provided for purposes of illustration only and merely depict example embodiments of the disclosure. The drawings are provided to facilitate understanding of the disclosure and shall not be deemed to limit the breadth, scope, or applicability of the disclosure. The use of the same reference numerals indicates similar, but not necessarily the same or identical components. However, different reference numerals may be used to identify similar components as well. Various embodiments may utilize elements or components other than those illustrated in the drawings, and some elements and/or components may not be present in various embodiments. The use of singular terminology to describe a component or element may, depending on the context, encompass a plural number of such components or elements and vice versa.

(2) FIG. 1A is a schematic illustration of an example use case of a payment system for generating a token for use at a fuel station, in accordance with one or more exemplary embodiments of the disclosure.

(3) FIG. 1B is a schematic illustration of exemplary modules included in the payment system, in accordance with one or more exemplary embodiments of the disclosure.

(4) FIG. 2 is a schematic illustration of data flow in an example use case of the payment system for purchasing fuel, in accordance with one or more exemplary embodiments of the disclosure.

(5) FIG. 3 is a schematic illustration of data flow in an example use case of the payment system for purchasing items, in accordance with one or more exemplary embodiments of the disclosure.

(6) FIG. 4 is an example process flow for an example use case of the payment system for generating a token, in accordance with one or more exemplary embodiments of the disclosure.

(7) FIG. 5 is an example process flow for a use case of the payment system for authenticating a purchase, in accordance with one or more exemplary embodiments of the disclosure.

(8) FIG. 6 is an example process flow for an example use case of the payment system for requesting a token, in accordance with one or more exemplary embodiments of the disclosure.

(9) FIG. 7 is a schematic block diagram of a server in accordance with one or more exemplary embodiments of the disclosure.

DETAILED DESCRIPTION

(10) Overview

(11) Payment systems and methods are provided herein for facilitating purchase of fuel, services, and/or items in conformity with parameters set by a company or other overseeing entity. In one example, the payment system may be a fuel payment system and may generate a one-time token for purchasing fuel for drivers such as truck drivers. The one-time token may be received by the driver and input into or otherwise communicated to a pump controller. The pump controller may request that the system authenticate a purchase request using the token and may permit the purchase upon authentication and/or approval from the payment system.

(12) The payment system may include a cloud based system (e.g., run on a server) and a user (e.g., driver) application run on a user device (e.g., smart phone) that may communicate with the server. A user may request a token for an upcoming purchase, such as a purchase of fuel. The user device may send the request to the server, which may also include information such as a driver identifier, a company identifier, a vehicle identifier, a device identifier, location data, time data, and/or information about the requested purchase (e.g., what item is being purchased). The payment system may compare the request with information associated with the driver identifier and/or company identifier to determine whether to generate a one-time use token to facilitate the requested purchase.

(13) The system may determine a fuel allotment amount corresponding to the driver identifier or a company parameter limiting fuel purchases (e.g., one purchase per day, one purchase per distance traveled, a fuel allotment for a given week, or any other limiting parameter). The system may compare the request to the restrictions and/or parameters associated with the user and/or company identifiers to determine whether to generate a token. If a token is generated, it will be communicated back to the user device. The token may be associated with approved fueling stations and an expiration time.

(14) The user may then input the token or otherwise communicate the token and a driver identifier at an approved station before the time expiration. A pump controller may communicate the token and the driver identifier to the server to authenticate and/or approve the purchase. The server may compare the token to the user identifier and any constraints or rules associated with the driver identifier and/or company identifier. If the constraints and/or rules are satisfied the, server may send a message to the pump controller authorizing and/or approving the transaction.

(15) It is understood that a similar process may be used to authorize and/or approve purchases other than fuel. For example, purchases at a store (e.g., fuel station store), market, restaurant, repair garage, port of entry, or the like may be made. For such purchases involving different categories or types of products, items, fees, costs and/or services, the system may track and consider certain rules and/or constraints specific to these categories. For example, the number of coffees or tires purchased in a given time period may be limited by amount or quantity.

(16) Referring now to FIG. 1A, an exemplary payment system for fuel purchases is illustrated in accordance with one or more exemplary embodiments of the disclosure. Payment system **100** may include a cloud based system (e.g., software, platform, application) run on server **102**, which may be in communication with user devices, such as user device **104** and controllers at various stations such as pump controller **106** at fuel station **108**.

(17) User device **104** may be any computing device with a processor and a display. For example, user device **104** be one or more smart phones, smart devices (e.g., smart watch), laptop or desktop computers, and/or any other suitable electronic or computing device. Server **102** may be any computing device with a processor. For example, server **102** may be one or more servers, computers, desktop computers, controllers, laptop computers, datastores, and/or any other electronic or computing device. Pump controller **106** may be any computing device. For example pump controller may be one or more servers, computers, desktop computers, controllers, laptop computers, datastores, and/or any other electronic or computing device.

(18) It is understood that pump controller may be located at pump station **108**, which may be any type of fueling station for dispensing fuel to vehicles (e.g., trucks). Pump station **108** may include

one or several pump controllers **106**. Further, user device **104** and/or server **102** may be positioned in different locations. For example, the user device may be traveling with a driver in truck and server **102** may be positioned several (e.g., hundreds or thousands) miles away.

(19) User device **104** and server **102** may communicate via any suitable wireless system (e.g., cellular network, satellite network, Bluetooth, Bluetooth Low Energy (BLE), near field communication protocol, Wi-Fi, etc.). Similarly, server **102** and pump controller **106** may communicate via any suitable wireless system (e.g., cellular network, satellite network, Wi-Fi, etc.). Optionally, user device **104** may communicate with pump controller **106** via any suitable wireless system (e.g., cellular network, satellite network, Bluetooth, Bluetooth Low Energy (BLE), near field communication protocol, Wi-Fi, etc.).

(20) The payment system illustrated in FIG. 1A may be initiated at block **152** which starts with the user application sending request **112** to server **102** to purchase fuel. Server **102** may be one or more components and/or modules discussed in greater detail with respect to FIG. 1B. This may be a request for a token such as a fuel token. More specifically, a user using user device **104** which may run user application **115** on user device **104** may be a driver of truck **105** and may be in need of fuel for truck **105**. The user may use user application **115** to contact server **102** with request **112** to purchase fuel nearby.

(21) At block **154**, if the request is approved, server **102** may send a one-time use token (e.g., token **114**) to user application **115** running on user device **115** (e.g., via a cellular network). For example, the system may confirm a driver corresponding to a driver identifier is eligible for fuel (e.g., eligible to receive a fuel token). The system running on server **102** may consider certain rules and constraints associated with the driver identifier and/or a company identifier associated with the driver identifier. For example, the driver may be limited to a certain amount of fuel per day or week or a certain amount of fuel per miles driven, or any other restraint relating to fuel purchasing or consumption.

(22) If the request satisfies the rules and constraints associated with the driver identifier and/or company identifier, server **102** will then send one-time use token to purchase fuel (e.g., fuel token) to user device **104** running user application **115**. Server **102** may also include an expiration time associated with the token specifying a time for which the token must be used before expiring. Also, sever **102** may send user device **115** one or more approved fueling stations within a certain distance of user device **104** (e.g., 5 miles, 10 miles, 15 miles, etc.).

(23) User application **115** may present the fueling stations on a display of user device **104** and/or may present the token and expiration time. In one example, the token may be an alphanumeric code, but it understood that the token may be any other code or value. Alternatively, or additionally, the token may be a computer readable image or code (e.g., QR code, bar code, etc.), a token generated using blockchain technology, a digitized message, or any other suitable code or token. The fueling stations may be preapproved by the company (e.g., in-network stations). User device **104** may also present a map showing the stations. In one embodiment, a user may select a station to initiate navigation to the station on user device **115**.

(24) At block **156**, a driver may input or otherwise communicate the token to fuel controller **106** and the fuel controller may communicate the token and a request for authentication and/or approval to server **102**. For example, a driver may manually input the token alphanumeric value into a keypad or touchscreen into pump controller **106** or a fuel pump in communication with pump controller **106**. Alternatively, a driver may scan a QR code, bar code, or otherwise wirelessly communicate a code or token to pump controller **106**. The driver may also input other information such as a driver identifier, company identifier, vehicle identifier, and the like. Pump controller **106** may communicate token **116** and/or any other information provided by the driver and/or a station identifier to server **102**.

(25) Server **102** running the payment system may authenticate and/or approve the token and authorize the transaction. For example, server **102** may confirm token **116** is the same as token **114**,

that the token is associated with the driver and/or company identifier, that the token has not expired, and that the station identifier is approved for that token. Then upon authenticating the token and confirming that certain rules and/or constraints are satisfied, server **102** may send pump controller **106** a message approving and/or authorizing (e.g., approval message **118**) the transaction, permitting the purchase of fuel. Server **102** may also send pump controller **106** certain rules and/or constraints, such as a fuel limit (e.g., 100 gallons).

(26) At block **160**, a fuel pump in communication with pump controller **106** and/or incorporated with pump controller **106** may be activated by pump controller **106**. Pump controller **106** may cause the fuel pump to cease after a certain amount of gallons have been dispensed (e.g., 100 gallons) based the constraints and/or rules provided by server **102**. It is understood that one or more of the steps in FIG. **1A** may be optional and/or may be performed in a different order.

(27) Referring now to FIG. **1B**, a schematic illustration of exemplary modules included in the payment platform of the payment system, in accordance with one or more exemplary embodiments of the disclosure is illustrated. One or more of the modules and/or components illustrated in FIG. **1B** may be run on and/or executed by server **102** and/or controller **106** of FIG. **1A**. It is understood that one or more modules and/or components of FIG. **1B** may be optional and/or that other modules and/or components may be included.

(28) As shown in FIG. **1B**, pump site **135** may include several pumps (e.g., pump **131**). Each pump may be connected to pump center **132** which may be a fuel pump (e.g., diesel pump). Pump center **132** may include a display (e.g., any suitable digital display) and/or user input such as a touch pad, RFID sensor, contactless information sensor, and/or any other suitable communication and/or input/out device, sensor, or component. The pump center may include a computing device and/or an information chip for sending and receiving information (e.g., via a wired or wireless connection).

(29) Pump center **132** may communicate with controller **134**, which alone or together with the computing device of pump center **132** may be a pump controller. Controller **134** may be tasked with communicating with other components of FIG. **1B**. Controller **134** may be in communication with a database **137** for saving and receiving information about transactions, users, purchases, and the like. Point of sale **136** may be a computing device for executing overseeing, and/or facilitating transactions. In one example, point of sale **135** may be a computing device at a checkout counter and/or may be responsible for executing a purchase.

(30) Merchant **140** may including remote or onsite (e.g., at site **135**) computing devices including processing center **141** and/or database **140**. Merchant **140** may, in one example, receive a token (e.g., from payment system **170**) and/or may optionally share the token with site **135**. Processing center **141** may be any computing device that may process operations and/or tasks at site **135** and/or may oversee operation of site and communicate with payment system **170**. Processing center may save and/or retrieve information at database **142**.

(31) Payment system **170** may be any suitable computing device and may communicate with only merchant **140** or may communicate with merchant **140** and site **135**. Payment system **170** may include processing center **171** which may oversee operation of payment system **170** and/or process information received by merchant **140**, site **135** and/or carrier **180**. Payment system **170** may include ledger **173** which maintain purchases (e.g., of fuel) and other related information and decision engine **172**, which may be used to make decisions and/or oversee tasks and operations on payment system **170**. Processing center **171** may communicate with database **174**, which maintain and save information used by processing center **171**.

(32) Configuration engine **176** may communicate with processing center **171** and may configure user information, carrier information, broker information, and/or any other relevant information. Configuration engine **176** may communicate with database **175** which may save and/or maintain any such information. Configuration engine **176** may further oversee portal **178** which may be a web port for payment system **170** and/or app **177**, which may be a user application of payment

system **170**. Payment system **170** may be in communication with carrier **180**, which may include the electronic logging devices (ELD) and/or transportation management systems.

(33) Referring now to FIG. **2**, an exemplary data flow for a payment system for purchasing fuel is illustrated, in accordance with one or more exemplary embodiments of the disclosure. It is understood that any steps in FIG. **2** may be optional and/or that the steps may be performed in a different order. As shown in FIG. **2**, data flow **200** may include communication between user device **204**, electronic logging device (ELD) **207**, server **202**, and/or pump controller **206**. User device **204** may be the same as or similar to user device **104** of FIG. **1A**, server **202** may be the same as or similar to server **102** of FIG. **1A**, and/or pump controller **206** may be the same as or similar to pump controller **106** of FIG. **1A**.

(34) ELD **207** may be any suitable electronic logging device used in the trucking and/or shipping industry for collecting data regarding vehicle operation and/or performance (e.g., fuel level, miles traveled, location, load weight, vehicle identifier, equipment type and/or maintenance records, etc.). It is understood that the ELD may be optional in data flow **200**. Pump controller **206** may optionally incorporate both pump controller **106** and a fuel pump.

(35) Data flow **200** may be initiated by user device **204** running a user application (e.g., user application **115** of FIG. **1A**). At step **212** a request for a fuel token is sent to server **202**, which is running the payment system. The request may include a driver identifier, a company identifier, that the request is for fuel, a location and/or a time stamp. At step **214**, a server **202** may send user device **204** a request for driver data. Driver data may include information about the last fuel stop (e.g., when, where, how much fuel), information about the vehicle's fuel capacity, additional location information, direction of travel information (e.g., navigation information), refueling history, and the like.

(36) At step **216**, user device **218** may optionally communicate with ELD **207** to request certain user data known only by ELD. For example, ELD may have information about a current fuel level or a fuel measurement that may not be known by user device **204**. At step **218**, ELD **207** may send the driver data either to user device **204** or, alternatively, may send the driver data to server **202** (e.g., by any suitable wireless connection). At step **220**, user device may send driver data to server **202**. For example, this information may be saved locally on user device **204** and/or provided by ELD **207**.

(37) At optional step **222**, server **202** may optionally request driver data directly from ELD **207**. For example, server **202** may determine that additional driver data is required. At optional step **225**, ELD **207** may send the additional data to server **202**. Alternatively, in steps **222** and **224** ELD **207** and/or server **202** may communicate via user device **204**.

(38) Server **202** may analyze the driver data and compare the driver data to certain rules and/or constraints (e.g., associated with the driver identifier and company identifier). For example, server **202** may compare a fuel level to a fuel capacity value to determine the amount of fuel required to fill the tank and determine whether the amount of fuel required to fill the tank is within a fuel allotment amount for that specific driver. In another example, server **202** may consider a distance traveled since the last fuel stop and determine whether the distance traveled satisfies a threshold for a fuel stop.

(39) At step **225**, server **202** may send a one-time use token to user device **204**. Server **202** may also send an expiration time associated with the token, and one or more fueling stations in certain radius (e.g., 5, 10, 15 miles) that have been approved for use of the token. At step **226**, server **202** may receive a request for authorization from pump controller **206**, which may be a pump controller at one of the approved fueling stations. The request for authorization may include the token (e.g., alphanumeric number) and/or a representation of the token (e.g., portion of alphanumeric number) and the user identifier (e.g., driver identifier). Alternatively, at step **228**, the token or representation of the token may be sent separately from the request for authorization at step **226**.

(40) At step **230**, server **102** may process the request for authorization of the token and authenticate

that the token is valid and is associated with the driver identifier. If the request satisfies certain rules and/or constraints (e.g., based on fuel allotment data) corresponding to the driver identifier and/or company identifier, then the sever will send an authorization and/or approval acknowledgement. Fuel allotment data may include, for example, a tank capacity value, an initial fueling location, a gallon allotment for a set period of time, a fuel measurement, an initial fueling time, and/or average fuel consumption. Server **232** may also send token parameters (e.g., expiration time, fuel limit, etc.) to pump controller **206**. Once the transaction is complete, pump controller **206** may share purchase data with server **202**, which may include for example an amount of fuel pump, a fuel price per gallon, a time stamp, and/or any other relevant information about the transaction.

(41) Referring now to FIG. **3**, an exemplary data flow for a payment system for purchasing an item (e.g., product, item, food, service) is illustrated, in accordance with one or more exemplary embodiments of the disclosure. It is understood that any steps in FIG. **3** may be optional and/or that the steps may be performed in a different order. As shown in FIG. **3**, data flow **300** may include communication between user device **204**, electronic logging device (ELD) **207**, server **202**, and/or pump controller **209**. Store controller **209** may be similar to pump controller **206** but may be any type of computing device in a store (e.g., computer at the checkout counter) It is understood the ELD **207** may be optional.

(42) Data flow **300** may be initiated by user device **204** running a payment system application. At step **312** a request for a purchase token is sent to server **202**, which is running the payment system. The request may include a driver identifier, a company identifier, that the request is for an item (e.g., non-fuel purchase), a location, and/or a time stamp. At step **314**, a server **202** may send user device **204** a request for driver data. Driver data may include information about the last purchase (e.g., when, where, what, amount, etc.), additional location information, purchase history, and the like. For example, driver data may include a purchase history of what items were purchased, the price, where, and/or when.

(43) At step **316**, user device **204** may optionally communicate with ELD **207** to request certain driver data maintained by the ELD. For example, ELD may have information regarding prior service and maintenance and/or sensor data corresponding to parts (e.g., oil sensor) and/or may have information about time estimates for replacing certain parts. At step **318**, ELD **207** may send the driver data either to user device **204** or alternatively, may send the driver data to server **202** (e.g., by any suitable wireless connection). At step, **320**, user device may send driver data to server **202**. For example, this information may be saved locally on user device **204** and/or provided by ELD **207**.

(44) At optional step **322**, server **202** may request driver data directly from ELD **207**. For example, server **202** may determine that additional driver data is required. At optional step **324**, ELD **207** may send the additional driver data to server **202**. Alternatively, in steps **322** and **324** ELD **207** and/or server **202** may communicate via user device **204**.

(45) Server **202** may analyze the driver data and compare the driver data to certain rules and/or constraints (e.g., associated with the driver identifier, vehicle identifier, and company identifier). For example, server **202** may compare a request to purchase with a per diem amount, an item allotment, a time of last purchase, and/or other purchase history data). In one example, a company may limit the user to a certain number of items in a time period (e.g., only four coffees per day) or may include an amount allotment for a category of food (e.g., 3 dollars a day for snacks). Server **202** may also, or alternatively, consider company parameters such as cost allotment per time period, cost allotment per item category, cost allotment per meal period, repair allotment, and supply allotment.

(46) At step **325**, server **202** may send a one-time use token to user device **104**. Server **202** may also send an expiration time associated with the token, and one or more stores (e.g., fuel station stores) in certain a radius (e.g., 5, 10, 15 miles) that have been approved for use of the token. At step **326**, server **202** may receive a request for authorization from store controller **209**, which may

be a controller onsite at the store (e.g., computer at checkout counter). The request for authorization may include the token (e.g., alphanumeric number) and/or a representation of the token (e.g., portion of alphanumeric number) and the user identifier (e.g., driver identifier). Alternatively, at step **328**, the token or representation of the token may be sent separately from the request for authorization at step **226**.

(47) At step **330**, server **202** may process the request for authorization and token and authenticate that the token is valid and is associated with the driver identifier. If the request satisfies certain rules and/or constraints (e.g., based on purchase history data) corresponding to the driver identifier and/or company identifier, then the sever will send an authorization and/or approval acknowledgement. Purchase history data may include, for example, prior purchase amounts, prior purchase items, prior purchase categories, prior purchase dates, prior purchase times, and/or prior purchase locations. Server **332** may also send token parameters (e.g., expiration time, item limit, cost limit, etc.) to store controller **209**. Once the transaction is complete, store controller **209** may share purchase data with server **202**, which may include, for example, the items purchased, the cost, a time stamp, and/or any other relevant information about the transaction.

(48) Referring now to FIG. **4**, example process flow **400** of a payment system is depicted for purchasing fuel, items and/or services, for example, in accordance with one or more exemplary embodiments of the disclosure. It is understood that one or more steps of process flow **400** may be optional and/or one or more steps of process flow **400** may be performed in a different order. Process flow may be performed by a server (e.g., server **102** of FIG. **1A**), for example, alone or together with any other devices described herein.

(49) To initiate process flow **400**, at block **402** computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to determine a request for a one-time use token for purchase from a user device. The request may include a driver identifier (e.g., user identifier), a company identifier, and a location (e.g., a location of the user device), for example. The request may also be associated with a time stamp.

(50) At optional block **404** computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to send a request for driver data to the user device and/or an ELD. The driver data may include, for example, a company identifier, a vehicle identified, fuel history, location data, location history, fuel data and/or history, and/or the like. At optional block **406**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to receive or otherwise retrieve the driver data.

(51) At block **408** computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to authenticate the request based on the driver identifier and/or driver data. For example, the system may confirm the driver identifier is in the system. Additionally, the request may include a device identifier to authenticate that the user device is associated with the driver identifier

(52) At decision **410**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to determine if the request conforms to or satisfies certain rules and/or constraints. For example, the request may be authenticated based on a calculated fuel velocity, a measurement of current fuel levels, time from last fueling, and/or a distance traveled. Fuel velocity may be an estimated fuel consumption based on the distance traveled. The rules and constraints may be associated on the system with the driver identifier, the vehicle identifier, and/or the company identifier for example.

(53) If the request does not conform to the rules and/or constraints (e.g., the request is premature based on the estimated fuel velocity or an allotment for gallons of fuel for a given time has been exceeded) then the user device will be cause the user device to present a message indicative of the denied request. Alternatively, if the request conforms to or satisfies the rules and/or constraints (e.g., the request is consistent with a fuel velocity estimation, the fuel allotment has not been consumed, the time since last fuel up has exceeded a threshold value) then computer-executable

instructions stored on a memory of a device, such as a computing device and/or server, may be executed to determine certain token parameters.

(54) Token parameters may include for example, a limit on the cost or number of gallons of fuel to be dispensed (e.g., limit 100 gallons max), an expiration time, after which fuel may no longer be dispensed, an expiration time for inputting the token into the controller, and the like. At block **416**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to determine approved locations for purchase. For example, fueling stations that are in-network or otherwise pre-approved may be determined. The location associated with the request and/or driver data may be compared to the list of pre-approved fueling stations to determine stations within a certain radius (e.g., 2 miles, 5 miles, 10 miles, 15 miles, etc.)

(55) At block **418**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to generate a one-time token associated (e.g. on the server) with the driver identifier, token parameters and/or approved locations. At block **420**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to send the token, token parameters and/or approved locations to a user application running on a user device to present the token, expiration time, token parameters, and/or approved locations on the user device.

(56) Referring now to FIG. 5, example process flow **500** of a payment system is depicted for authorizing and/or approving a purchase request, in accordance with one or more exemplary embodiments of the disclosure. It is understood that one or more steps of process flow **500** may be optional and/or one or more steps of process flow **500** may be performed in a different order. Process flow **500** may be performed by a server (e.g., server **102** of FIG. 1A), for example, alone or together with any other devices described herein.

(57) To initiate process flow **500**, at block **502** computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to receive an authorization from a controller (e.g., a pump controller or store controller). The request may include a controller location, a controller identifier, a driver identifier, and/or the token. At block **504**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to authenticate the request. For example, the system may confirm that the token is associated with the user identifier and/or may confirm that the controller identifier is associated with one of the approved locations and the request is before the expiration time associated with the token.

(58) At decision **506**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to determine if the purchase is approved. This decision may be based solely on the authentication factors at block **504** and/or may be based on whether certain rules and/or constraints associated with the token and/or user identifier are satisfied. For example, the request may include purchase information and the system may confirm that the purchase information conforms to or is consistent with the token. Purchase information may include an amount of gallons, a type of items being purchased (e.g., coffee, alcohol, non-diesel fuel), a category of the item to be purchased (e.g., snacks) and/or any other information relevant to the item.

(59) If the purchase is not approved, at block **508**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to inform the controller and/or user application that the purchase and/or token is denied. Alternatively, if the purchase is approved, at block **512**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to send the controller purchase authorization and/or applicable token parameters for a given purchase (e.g., limit on a number of gallons to be dispensed or limit on cost).

(60) At block **514**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to receive purchase data from a controller, which

may include the items purchased, an amount of gallons dispensed, a cost for the purchased, and the like. At block **516**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to associate (on the server) the purchase data with the driver identifier.

(61) Referring now to FIG. **6**, example process flow **600** of a user application of a payment system running on a user device is depicted for requesting a token, in accordance with one or more exemplary embodiments of the disclosure. It is understood that one or more steps of process flow **600** may be optional and/or one or more steps of process flow **600** may be performed in a different order. Process flow **500** may be performed by a server (e.g., server **102** of FIG. **1A**), for example, alone or together with any other devices described herein.

(62) To initiate process flow **600**, at block **602**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to receive user input indicative of a request for a token. For example a user may enter user input on a graphic user interface displayed by a user application on a user device (e.g., user application **115** on user device **104** of FIG. **1A**) to request to purchase fuel or another item. At block **604**, the application may determine driver data (e.g., driver identifier, vehicle identifier, location, a fuel level or measurement, etc.).

(63) At block **606**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to generate a request for a token which may include the driver data, a location of the user device and/or a time stamp. At block **608**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to send the request for a token and any associated information to a system controller.

(64) At block **610**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to receive the requested token and/or any token parameters (e.g., expiration time, approved locations, approved fuel amount). At block **612**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to present on a display of the user device a list and/or map of approved locations (e.g., fueling stations), the expiration time, and/or other token parameters.

(65) At optional block **614**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to receive user input indicative of a selection of a certain approved location (e.g., fueling station). At optional block **616**, computer-executable instructions stored on a memory of a device, such as a computing device and/or server, may be executed to present on the user device navigation instructions to the desired location.

(66) FIG. **7** is a schematic block diagram of an illustrative server **700** of the payment system in accordance with one or more exemplary embodiments of the disclosure. Server **700** may be any suitable computing device capable of receiving and/or sending data and/or overseeing the payment system. Server **700** may optionally be coupled to and/or communicate with devices including, but not limited to, controllers, computing devices and/or one or more datastores, or the like. Server **700** may correspond to server **102** of FIG. **1A**, and/or any other servers of FIGS. **1-6**. It is understood that tasks and operations described herein may be performed by both server **700**, a user device and/or controller (e.g., user device **104** and controller **106** of FIG. **1A**).

(67) Server **700** may be configured to communicate via one or more networks with one or more servers, user devices, controllers, or the like. Example network(s) may include, but are not limited to, any one or more different types of communications networks such as, for example, cable networks, public networks (e.g., the Internet), private networks (e.g., frame-relay networks), wireless networks, cellular networks, telephone networks (e.g., a public switched telephone network), or any other suitable private or public packet-switched or circuit-switched networks. Further, such network(s) may have any suitable communication range associated therewith and may include, for example, global networks (e.g., the Internet), metropolitan area networks (MANs),

wide area networks (WANs), local area networks (LANs), or personal area networks (PANs). In addition, such network(s) may include communication links and associated networking devices (e.g., link-layer switches, routers, etc.) for transmitting network traffic over any suitable type of medium including, but not limited to, coaxial cable, twisted-pair wire (e.g., twisted-pair copper wire), optical fiber, a hybrid fiber-coaxial (HFC) medium, a microwave medium, a radio frequency communication medium, a satellite communication medium, or any combination thereof.

(68) In an illustrative configuration, the computing device **700** may include one or more processors (processor(s)) **702**, one or more memory devices **704** (generically referred to herein as memory **704**), one or more input/output (I/O) interface(s) **706**, one or more network interface(s) **708**, one or more transceivers **710**, one or more optional speakers, one or more optional microphones, and one or more antenna(s) **734**. The computing device **700** may further include one or more buses **718** that functionally couple various components of the computing device **700**. The computing device **700** may further include one or more antenna (e) **734** that may include, without limitation, a cellular antenna for transmitting or receiving signals to/from a cellular network infrastructure, an antenna for transmitting or receiving Wi-Fi signals to/from an access point (AP), a Global Navigation Satellite System (GNSS) antenna for receiving GNSS signals from a GNSS satellite, a Bluetooth antenna for transmitting or receiving Bluetooth signals including BLE signals, a Near Field Communication (NFC) antenna for transmitting or receiving NFC signals, a 900 MHz antenna, and so forth. These various components will be described in more detail hereinafter.

(69) The bus(es) **718** may include at least one of a system bus, a memory bus, an address bus, or a message bus, and may permit exchange of information (e.g., data (including computer-executable code), signaling, etc.) between various components of the computing device **700**. The bus(es) **718** may include, without limitation, a memory bus or a memory controller, a peripheral bus, an accelerated graphics port, and so forth. The bus(es) **718** may be associated with any suitable bus architecture including, without limitation, an Industry Standard Architecture (ISA), a Micro Channel Architecture (MCA), an Enhanced ISA (EISA), a Video Electronics Standards Association (VESA) architecture, an Accelerated Graphics Port (AGP) architecture, a Peripheral Component Interconnects (PCI) architecture, a PCI-Express architecture, a Personal Computer Memory Card International Association (PCMCIA) architecture, a Universal Serial Bus (USB) architecture, and so forth.

(70) The memory **704** of the computing device may include volatile memory (memory that maintains its state when supplied with power) such as random access memory (RAM) and/or non-volatile memory (memory that maintains its state even when not supplied with power) such as read-only memory (ROM), flash memory, ferroelectric RAM (FRAM), and so forth. Persistent data storage, as that term is used herein, may include non-volatile memory. In certain example embodiments, volatile memory may enable faster read/write access than non-volatile memory. However, in certain other example embodiments, certain types of non-volatile memory (e.g., FRAM) may enable faster read/write access than certain types of volatile memory.

(71) In various implementations, the memory **704** may include multiple different types of memory such as various types of static random access memory (SRAM), various types of dynamic random access memory (DRAM), various types of unalterable ROM, and/or writeable variants of ROM such as electrically erasable programmable read-only memory (EEPROM), flash memory, and so forth. The memory **704** may include main memory as well as various forms of cache memory such as instruction cache(s), data cache(s), translation lookaside buffer(s) (TLBs), and so forth. Further, cache memory such as a data cache may be a multi-level cache organized as a hierarchy of one or more cache levels (L1, L2, etc.).

(72) The data storage **720** may include removable storage and/or non-removable storage including, but not limited to, magnetic storage, optical disk storage, and/or tape storage. The data storage **720** may provide non-volatile storage of computer-executable instructions and other data. The memory **704** and the data storage **720**, removable and/or non-removable, are examples of computer-readable

storage media (CRSM) as that term is used herein.

(73) The data storage **720** may store computer-executable code, instructions, or the like that may be loadable into the memory **704** and executable by the processor(s) **702** to cause the processor(s) **702** to perform or initiate various operations. The data storage **720** may additionally store data that may be copied to memory **704** for use by the processor(s) **702** during the execution of the computer-executable instructions. Moreover, output data generated as a result of execution of the computer-executable instructions by the processor(s) **702** may be stored initially in memory **704**, and may ultimately be copied to data storage **720** for non-volatile storage.

(74) More specifically, the data storage **720** may store one or more operating systems (O/S) **722**; one or more optional database management systems (DBMS) **724**; and one or more implementation module(s) **725**, one or more token generator module(s) **727**, one or more communication module(s) **728**, one or authentication module(s) **729**, and/or one or more token parameter module **730**. Some or all of these module(s) may be sub-module(s). Any of the components depicted as being stored in data storage **720** may include any combination of software, firmware, and/or hardware. The software and/or firmware may include computer-executable code, instructions, or the like that may be loaded into the memory **704** for execution by one or more of the processor(s) **702**. Any of the components depicted as being stored in data storage **720** may support functionality described in reference to correspondingly named components earlier in this disclosure.

(75) The data storage **720** may further store various types of data utilized by components of the computing device **700**. Any data stored in the data storage **720** may be loaded into the memory **704** for use by the processor(s) **702** in executing computer-executable code. In addition, any data depicted as being stored in the data storage **720** may potentially be stored in one or more datastore(s) and may be accessed via the DBMS **724** and loaded in the memory **704** for use by the processor(s) **702** in executing computer-executable code. The datastore(s) may include, but are not limited to, databases (e.g., relational, object-oriented, etc.), file systems, flat files, distributed datastores in which data is stored on more than one node of a computer network, peer-to-peer network datastores, or the like. In FIG. 7, the datastore(s) may include, for example, user preference information, user contact data, device pairing information, and other information.

(76) The processor(s) **702** may be configured to access the memory **704** and execute computer-executable instructions loaded therein. For example, the processor(s) **702** may be configured to execute computer-executable instructions of the various program module(s), applications, engines, or the like of the computing device **700** to cause or facilitate various operations to be performed in accordance with one or more embodiments of the disclosure. The processor(s) **702** may include any suitable processing unit capable of accepting data as input, processing the input data in accordance with stored computer-executable instructions, and generating output data. The processor(s) **702** may include any type of suitable processing unit including, but not limited to, a central processing unit, a microprocessor, a Reduced Instruction Set Computer (RISC) microprocessor, a Complex Instruction Set Computer (CISC) microprocessor, a microcontroller, an Application Specific Integrated Circuit (ASIC), a Field-Programmable Gate Array (FPGA), a System-on-a-Chip (SoC), an application-specific integrated circuit, a digital signal processor (DSP), and so forth. Further, the processor(s) **702** may have any suitable microarchitecture design that includes any number of constituent components such as, for example, registers, multiplexers, arithmetic logic units, cache controllers for controlling read/write operations to cache memory, branch predictors, or the like. The microarchitecture design of the processor(s) **702** may be capable of supporting any of a variety of instruction sets.

(77) Referring now to functionality supported by the various program module(s) depicted in FIG. 7, the implementation module(s) **725** may include computer-executable instructions, code, or the like that responsive to execution by one or more of the processor(s) **702** may perform functions including, but not limited to, overseeing coordination and interaction between one or more modules and computer executable instructions in data storage **720**, determining user selected actions and

tasks, determining actions associated with user interactions, determining actions associated with user input, sending and receiving signals and/or data to and from one or more user devices, controllers, other computing devices, servers, datastores and the like, initiating commands locally or at remote computing devices, and the like.

(78) Token generator module **727** may include computer-executable instructions, code, or the like that responsive to execution by one or more of the processor(s) **702** may perform functions including, but not limited to generating token in response to a purchase request. The tokens may be alphanumeric values, computer readable codes (e.g., QR codes, bar codes, etc.), blockchain tokens, and/or any other token or code.

(79) The communication module(s) **728** may include computer-executable instructions, code, or the like that responsive to execution by one or more of the processor(s) **702** may perform functions including, but not limited to, communicating with one or more user devices and controllers, for example, via wired or wireless communication, communicating with electronic devices, communicating with one or more user devices, computing devices, servers (e.g., servers), communicating with remote datastores and/or databases, sending or receiving notifications or commands/directives, communicating with cache memory data, and the like.

(80) The authentication module **729** may include computer-executable instructions, code, or the like that responsive to execution by one or more of the processor(s) **702** may perform functions including, but not limited to, authenticating a request by comparing a user identifier and/or device identifier to known user identifiers and/or device identifiers. Authentication module **729** may further authenticate a token based on a user identifier, a store or station location, and/or a time.

(81) The token parameter module **730** may include computer-executable instructions, code, or the like that responsive to execution by one or more of the processor(s) **702** may perform functions including, but not limited to, determining token parameters which may be limits on the purchase (e.g., limit on cost, number of gallons limit, limit on number of items) and/or an expiration time for example.

(82) Referring now to other illustrative components depicted as being stored in the data storage **720**, the O/S **722** may be loaded from the data storage **720** into the memory **704** and may provide an interface between other application software executing on the computing device **700** and hardware resources of the computing device **700**. More specifically, the O/S **722** may include a set of computer-executable instructions for managing hardware resources of the computing device **700** and for providing common services to other application programs (e.g., managing memory allocation among various application programs). In certain example embodiments, the O/S **722** may control execution of the other program module(s) to for content rendering. The O/S **722** may include any operating system now known or which may be developed in the future including, but not limited to, any server operating system, any mainframe operating system, or any other proprietary or non-proprietary operating system.

(83) The optional DBMS **724** may be loaded into the memory **704** and may support functionality for accessing, retrieving, storing, and/or manipulating data stored in the memory **704** and/or data stored in the data storage **720**. The DBMS **724** may use any of a variety of database models (e.g., relational model, object model, etc.) and may support any of a variety of query languages. The DBMS **724** may access data represented in one or more data schemas and stored in any suitable data repository including, but not limited to, databases (e.g., relational, object-oriented, etc.), file systems, flat files, distributed datastores in which data is stored on more than one node of a computer network, peer-to-peer network datastores, or the like. As the computing device **700** is a mobile electronic device, the DBMS **724** may be any suitable light-weight DBMS optimized for performance on a mobile device.

(84) Referring now to other illustrative components of the computing device **700**, the optional input/output (I/O) interface(s) **706** may facilitate the receipt of input information by the computing device **700** from one or more I/O devices as well as the output of information from the computing

device **700** to the one or more I/O devices. The I/O devices may include any of a variety of components such as a display or display screen having a touch surface or touchscreen; an audio output device for producing sound, such as a speaker; an audio capture device, such as a microphone; an image and/or video capture device, such as a camera; a haptic unit; and so forth. Any of these components may be integrated into the computing device **700** or may be separate. The I/O devices may further include, for example, any number of peripheral devices such as data storage devices, printing devices, and so forth.

(85) The I/O interface(s) **706** may also include an interface for an external peripheral device connection such as universal serial bus (USB), FireWire, Thunderbolt, Ethernet port or other connection protocol that may connect to one or more networks. The I/O interface(s) **706** may also include a connection to one or more of the antenna (e) **734** to connect to one or more networks via a wireless local area network (WLAN) (such as Wi-Fi®) radio, Bluetooth, ZigBee, and/or a wireless network radio, such as a radio capable of communication with a wireless communication network such as a Long Term Evolution (LTE) network, WiMAX network, 3G network, ZigBee network, etc.

(86) The computing device **700** may further include one or more network interface(s) **708** via which the computing device **700** may communicate with any of a variety of other systems, platforms, networks, devices, and so forth. The network interface(s) **708** may enable communication, for example, with one or more wireless routers, one or more host servers, one or more web servers, and the like via one or more of networks.

(87) The antenna (c) **734** may include any suitable type of antenna depending, for example, on the communications protocols used to transmit or receive signals via the antenna (e) **734**. Non-limiting examples of suitable antennas may include directional antennas, non-directional antennas, dipole antennas, folded dipole antennas, patch antennas, multiple-input multiple-output (MIMO) antennas, or the like. The antenna (e) **734** may be communicatively coupled to one or more transceivers **710** or radio components to which or from which signals may be transmitted or received.

(88) As previously described, the antenna (e) **734** may include a Bluetooth antenna configured to transmit or receive signals in accordance with established standards and protocols, such as Bluetooth and/or BLE. Alternatively, or in addition to, antenna (e) **734** may include cellular antenna configured to transmit or receive signals in accordance with established standards and protocols, such as or cellular antenna configured to transmit or receive signals in accordance with established standards and protocols, such as Global System for Mobile Communications (GSM), 3G standards (e.g., Universal Mobile Telecommunications System (UMTS), Wideband Code Division Multiple Access (W-CDMA), CDMA2000, etc.), 4G standards (e.g., Long-Term Evolution (LTE), WiMax, etc.), direct satellite communications, or the like. The antenna (c) **734** may additionally, or alternatively, include a Wi-Fi antenna configured to transmit or receive signals in accordance with established standards and protocols, such as the IEEE 802.11 family of standards, including via 2.4 GHz channels (e.g., 802.11b, 802.11g, 802.11n), 5 GHz channels (e.g., 802.11n, 802.11ac), or 60 GHz channels (e.g., 802.11ad). In alternative example embodiments, the antenna (e) **734** may be configured to transmit or receive radio frequency signals within any suitable frequency range forming part of the unlicensed portion of the radio spectrum (e.g., 900 MHz).

(89) The antenna (c) **734** may additionally, or alternatively, include a GNSS antenna configured to receive GNSS signals from three or more GNSS satellites carrying time-position information to triangulate a position therefrom. Such a GNSS antenna may be configured to receive GNSS signals from any current or planned GNSS such as, for example, the Global Positioning System (GPS), the GLONASS System, the Compass Navigation System, the Galileo System, or the Indian Regional Navigational System.

(90) The transceiver(s) **710** may include any suitable radio component(s) for—in cooperation with the antenna (e) **734**—transmitting or receiving radio frequency (RF) signals in the bandwidth

and/or channels corresponding to the communications protocols utilized by the computing device **700** to communicate with other devices. The transceiver(s) **710** may include hardware, software, and/or firmware for modulating, transmitting, or receiving—potentially in cooperation with any of antenna (c) **734**—communications signals according to any of the communications protocols discussed above including, but not limited to, one or more Wi-Fi and/or Wi-Fi direct protocols, as standardized by the IEEE 802.11 standards, one or more non-Wi-Fi protocols, or one or more cellular communications protocols or standards. The transceiver(s) **710** may further include hardware, firmware, or software for receiving GNSS signals. The transceiver(s) **710** may include any known receiver and baseband suitable for communicating via the communications protocols utilized by the computing device **700**. The transceiver(s) **710** may further include a low noise amplifier (LNA), additional signal amplifiers, an analog-to-digital (A/D) converter, one or more buffers, a digital baseband, or the like.

(91) It should be appreciated that the program module(s), applications, computer-executable instructions, code, or the like depicted in FIG. 7 as being stored in the data storage **720** are merely illustrative and not exhaustive and that processing described as being supported by any particular module may alternatively be distributed across multiple module(s) or performed by a different module. In addition, various program module(s), script(s), plug-in(s), Application Programming Interface(s) (API(s)), or any other suitable computer-executable code hosted locally on the computing device **700** and/or hosted on other computing device(s) accessible via one or more networks, may be provided to support functionality provided by the program module(s), applications, or computer-executable code depicted in FIG. 7 and/or additional or alternate functionality. Further, functionality may be modularized differently such that processing described as being supported collectively by the collection of program module(s) depicted in FIG. 7 may be performed by a fewer or greater number of module(s), or functionality described as being supported by any particular module may be supported, at least in part, by another module. In addition, program module(s) that support the functionality described herein may form part of one or more applications executable across any number of systems or devices in accordance with any suitable computing model such as, for example, a client-server model, a peer-to-peer model, and so forth. In addition, any of the functionality described as being supported by any of the program module(s) depicted in FIG. 7 may be implemented, at least partially, in hardware and/or firmware across any number of devices.

(92) It should further be appreciated that the computing device **700** may include alternate and/or additional hardware, software, or firmware components beyond those described or depicted without departing from the scope of the disclosure. More particularly, it should be appreciated that software, firmware, or hardware components depicted as forming part of the computing device **700** are merely illustrative and that some components may not be present or additional components may be provided in various embodiments. While various illustrative program module(s) have been depicted and described as software module(s) stored in data storage **720** it should be appreciated that functionality described as being supported by the program module(s) may be enabled by any combination of hardware, software, and/or firmware. It should further be appreciated that each of the above-mentioned module(s) may, in various embodiments, represent a logical partitioning of supported functionality. This logical partitioning is depicted for ease of explanation of the functionality and may not be representative of the structure of software, hardware, and/or firmware for implementing the functionality. Accordingly, it should be appreciated that functionality described as being provided by a particular module may, in various embodiments, be provided at least in part by one or more other module(s). Further, one or more depicted module(s) may not be present in certain embodiments, while in other embodiments, additional module(s) not depicted may be present and may support at least a portion of the described functionality and/or additional functionality. Moreover, while certain module(s) may be depicted and described as sub-module(s) of another module, in certain embodiments, such module(s) may be provided as independent

module(s) or as sub-module(s) of other module(s).

(93) Program module(s), applications, or the like disclosed herein may include one or more software components including, for example, software objects, methods, data structures, or the like. Each such software component may include computer-executable instructions that, responsive to execution, cause at least a portion of the functionality described herein (e.g., one or more operations of the illustrative methods described herein) to be performed.

(94) A software component may be coded in any of a variety of programming languages. An illustrative programming language may be a lower-level programming language such as an assembly language associated with a particular hardware architecture and/or operating system platform. A software component comprising assembly language instructions may require conversion into executable machine code by an assembler prior to execution by the hardware architecture and/or platform.

(95) Another example programming language may be a higher-level programming language that may be portable across multiple architectures. A software component comprising higher-level programming language instructions may require conversion to an intermediate representation by an interpreter or a compiler prior to execution.

(96) Other examples of programming languages include, but are not limited to, a macro language, a shell or command language, a job control language, a script language, a database query or search language, or a report writing language. In one or more exemplary embodiments, a software component comprising instructions in one of the foregoing examples of programming languages may be executed directly by an operating system or other software component without having to be first transformed into another form.

(97) A software component may be stored as a file or other data storage construct. Software components of a similar type or functionally related may be stored together such as, for example, in a particular directory, folder, or library. Software components may be static (e.g., pre-established or fixed) or dynamic (e.g., created or modified at the time of execution).

(98) Software components may invoke or be invoked by other software components through any of a wide variety of mechanisms. Invoked or invoking software components may comprise other custom-developed application software, operating system functionality (e.g., device drivers, data storage (e.g., file management) routines, other common routines and services, etc.), or third party software components (e.g., middleware, encryption, or other security software, database management software, file transfer or other network communication software, mathematical or statistical software, image processing software, and format translation software).

(99) Software components associated with a particular solution or system may reside and be executed on a single platform or may be distributed across multiple platforms. The multiple platforms may be associated with more than one hardware vendor, underlying chip technology, or operating system. Furthermore, software components associated with a particular solution or system may be initially written in one or more programming languages, but may invoke software components written in another programming language.

(100) Computer-executable program instructions may be loaded onto a special-purpose computer or other particular machine, a processor, or other programmable data processing apparatus to produce a particular machine, such that execution of the instructions on the computer, processor, or other programmable data processing apparatus causes one or more functions or operations specified in the flow diagrams to be performed. These computer program instructions may also be stored in a computer-readable storage medium (CRSM) that upon execution may direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable storage medium produce an article of manufacture including instruction means that implement one or more functions or operations specified in the flow diagrams. The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational elements or steps to be

performed on the computer or other programmable apparatus to produce a computer-implemented process.

(101) Additional types of CRSM that may be present in any of the devices described herein may include, but are not limited to, programmable random access memory (PRAM), SRAM, DRAM, RAM, ROM, electrically erasable programmable read-only memory (EEPROM), flash memory or other memory technology, compact disc read-only memory (CD-ROM), digital versatile disc (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the information and which can be accessed. Combinations of any of the above are also included within the scope of CRSM. Alternatively, computer-readable communication media (CRCM) may include computer-readable instructions, program module(s), or other data transmitted within a data signal, such as a carrier wave, or other transmission. However, as used herein, CRSM does not include CRCM.

(102) Although embodiments have been described in language specific to structural features and/or methodological acts, it is to be understood that the disclosure is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as illustrative forms of implementing the embodiments. Conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments could include, while other embodiments do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements, and/or steps are included or are to be performed in any particular embodiment.

Claims

1. A method comprising: determining, by a server from a mobile device, a request for a first authentication value for purchasing fuel at a fuel pump, the request comprising a first user identifier; determining a fuel measurement corresponding to a vehicle associated with the first user identifier; determining fuel allotment data based on the fuel measurement; determining that the request for the first authentication value is approved based on the fuel allotment data; causing the first authentication value to be sent to the mobile device; receiving, from a fuel controller located at a first fuel station, a request to activate a particular fuel pump, the request comprising the first authentication value, wherein the particular fuel pump comprises a physical input device, and wherein the fuel controller is configured to receive the first authentication value via the physical input device; determining an input at the physical input device; determining that the input matches the first authentication value; determining that the request to activate the particular fuel pump is approved based at least in part on determining that the input matches the first authentication value; causing the fuel controller to activate the particular fuel pump based on the fuel allotment data; and determining that a dispensed amount of fuel is within a threshold amount of the fuel allotment data.
2. The method of claim 1, wherein the request comprises location data, the method further comprising: determining the first fuel station based on the location data, wherein the first fuel station is within a set mile radius of the location data; wherein the first authentication value is exclusively associated with the first fuel station.
3. The method of claim 1, wherein the request comprises location data, the method further comprising: determining an expiration time for the first authentication value based at least in part on a distance between the first fuel station and the location data.
4. The method of claim 1, further comprising: determining, while the particular fuel pump is activated, that the dispensed amount of fuel equals the fuel allotment; and causing the fuel controller to deactivate the particular fuel pump.

5. The method of claim 1, wherein the first authentication value is at least one of an alphanumeric code or a wirelessly transmitted value.
 6. The method of claim 1, further comprising: receiving, from the fuel controller, dispensed fuel data after the particular fuel pump is deactivated; and determining remaining fuel allotment data for the first user identifier based at least in part on the dispensed fuel data.
 7. The method of claim 1, wherein the fuel allotment data comprises one or more of a tank capacity value, an initial fueling location, a gallon allotment for a set period of time, a fuel measurement, an initial fueling time, and average fuel consumption.
 8. The method of claim 1, wherein the fuel controller is associated with a plurality of fuel pumps.
 9. A system comprising: memory configured to store computer-executable instructions; and at least one computer processor configured to access memory and execute the computer-executable instructions to: determine, from a mobile device, a request for a first authentication value for purchasing fuel at a fuel pump, the request comprising a first user identifier; determine a fuel measurement corresponding to a vehicle associated with the first user identifier; determine fuel allotment data based on the fuel measurement; determine that the request for the first authentication value is approved based on the fuel allotment data; cause the first authentication value to be sent to the mobile device; receive, from a fuel controller associated with a first fuel station, a request to activate a particular fuel pump, the request comprising the first authentication value, wherein the particular fuel pump comprises a physical input device, and wherein the fuel controller is configured to receive the first authentication value via the physical input device; determine an input at the physical input device; determine that the input matches the first authentication value; determine that the request to activate the particular fuel pump is approved based at least in part on determining that the input matches the first authentication value; cause the fuel controller to activate the particular fuel pump based on the fuel allotment data; and determine that a dispensed amount of fuel is within a threshold amount of the fuel allotment data.
 10. The system of claim 9, wherein the request comprises location data, and wherein the at least one computer processor is further configured to execute the computer-executable instructions to: determine the first fuel station based on the location data, wherein the first fuel station is within a set mile radius of the location data; wherein the first authentication value is exclusively associated with the first fuel station.
 11. The system of claim 9, wherein the request comprises location data, and wherein the at least one computer processor is further configured to execute the computer-executable instructions to: determine an expiration time for the first authentication value based at least in part on a distance between the first fuel station and the location data.
 12. The system of claim 9, wherein the at least one computer processor is further configured to execute the computer-executable instructions to: determine, while the particular fuel pump is activated, that the dispensed amount of fuel equals the fuel allotment; and cause the fuel controller to deactivate the particular fuel pump.
 13. The system of claim 9, wherein the first authentication value is at least one of an alphanumeric code or a wirelessly transmitted value.
 14. The system of claim 9, wherein the at least one computer processor is further configured to execute the computer-executable instructions to: receive, from the fuel controller, dispensed fuel data after the particular fuel pump is deactivated; and determine remaining fuel allotment data for the first user identifier based at least in part on the dispensed fuel data.
 15. The system of claim 9, wherein the fuel allotment data comprises one or more of a tank capacity value, an initial fueling location, a gallon allotment for a set period of time, a fuel measurement, an initial fueling time, and average fuel consumption.
 16. The system of claim 9, wherein the fuel controller is associated with a plurality of fuel pumps.
-