

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412818
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Chiu; Pei-Liang

Structure of package substrate

Abstract

A structure of a package substrate includes: a first multi-layer substrate including a plurality of dielectric layers and a plurality of metal wiring layers and having a first surface and a second surface which are opposite to each other; and a supporting substrate having a first surface and a second surface which are opposite to each other, wherein the first surface of the supporting substrate is disposed on the second surface of the first multi-layer substrate and electrically connected to the first multi-layer substrate, there is no gap between the first surface of the supporting substrate and the second surface of the first multi-layer substrate, the supporting substrate includes a plurality of vertical vias, and the vertical vias are used for electrically connecting the first surface of the supporting substrate to the second surface of the supporting substrate.

Inventors:	Chiu; Pei-Liang (Hsinchu, TW)
Applicant:	PRINCO CORP. (Hsinchu, TW)
Family ID:	87803182
Assignee:	PRINCO CORP. (Hsinchu, TW)
Appl. No.:	18/115865
Filed:	March 01, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230317587 A1	Oct. 05, 2023

Foreign Application Priority Data

TW	111109272	Mar. 14, 2022
----	-----------	---------------

Publication Classification

Int. Cl.: H01L23/49 (20060101); H01L23/15 (20060101); H01L23/498 (20060101)

U.S. Cl.:

CPC H01L23/49822 (20130101); H01L23/15 (20130101); H01L23/49827 (20130101);

Field of Classification Search

CPC: H01L (23/49822); H01L (23/15); H01L (23/49827); H01L (23/49833); H01L (23/49838); H01L (23/49866)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
827856	12/1905	Fatch	294/51	A01B 1/022
9159648	12/2014	Koizumi et al.	N/A	N/A
10297521	12/2018	Abe	N/A	H01L 23/15
10299374	12/2018	Shashkov	N/A	H05K 1/028
11516911	12/2021	Kijima	N/A	N/A
12057410	12/2023	Wu	N/A	H01L 21/4853
2005/0126818	12/2004	Kojima	174/262	H05K 3/4602
2014/0167255	12/2013	Shaue	257/737	H01L 23/4985
2015/0334823	12/2014	Hu	N/A	N/A
2021/0202332	12/2020	Hu	N/A	H01L 21/6835
2021/0391269	12/2020	Park	N/A	H01L 23/5385
2022/0051957	12/2021	Koh	N/A	H01L 21/561
2022/0344250	12/2021	Choi	N/A	H01L 21/486
2022/0359354	12/2021	Lin	N/A	H01L 23/49816
2023/0011941	12/2022	Jung	N/A	H01L 21/4853
2023/0300983	12/2022	Umehara	174/261	H05K 3/426

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2010532924	12/2009	JP	N/A
2014022465	12/2013	JP	N/A
2019204921	12/2018	JP	N/A
20160121506	12/2015	KR	N/A
20210148846	12/2020	KR	N/A
200901847	12/2008	TW	N/A
201426924	12/2013	TW	N/A
202201667	12/2021	TW	N/A
202209518	12/2021	TW	N/A
2016175206	12/2015	WO	N/A
2022024907	12/2021	WO	N/A

Background/Summary

FIELD OF DISCLOSURE

(1) The present disclosure relates to the technical field of package substrates, and more particularly to a structure of a package substrate.

BACKGROUND

(2) With the continuous development of wafer miniaturization technology, external electrical connection points of a chip in the future will become smaller and thinner, and a distance between two electrical connection points will also become smaller and smaller. Under such a trend, in a circuit board connected to the chip, it is necessary to achieve no height difference between each pad layer and a surface dielectric layer connected to a corresponding connected surface of the chip, so as to eliminate bubbles which are generated due to the height difference between each pad layer and the surface dielectric layer when the chip and the circuit board are completely bonded to each other. Furthermore, the circuit board itself which is connected to the chip must also be very precise. That is, a distance between two adjacent pad layers which are connected to the corresponding connected surface of the chip is very small, and the circuit board itself should be extremely thin to meet the needs of package in the future. Mechanical support of the circuit board must also be made very flat to ensure a high success rate of chip package. There are often more than 20,000 electrical connection points in a 2 cm (centimeter)×2 cm die. These electrical connection points will become thinner and thinner (that is, smaller). When the die is pasted on a surface of an uneven circuit board, it causes poor bonding or even failure.

(3) From the perspective of a traditional printed circuit board (PCB), the above-mentioned two requirements are more and more unsatisfactory. One reason is that a body of the circuit board is constituted by an organic material such as FR4, which cannot be ground or polished to achieve high flatness.

(4) As shown in FIG. 1, an existing better solution is to use a ceramic substrate produced by a co-firing method as the body of the circuit board. FIG. 1 illustrates a manufacturing process and a structure in co-fired ceramic technology in the prior art. However, regardless in a high-temperature co-fired ceramic (HTCC) process or a low-temperature co-fired ceramic (LTCC) process, ceramic powder is mixed with a 4%~8% organic binder during a sintering process, so that the ceramic powder can be combined with each other during the sintering process (30%~50% more low-melting point glass frit is added in the low-temperature co-fired ceramic process than in the high-temperature co-fired ceramic process). During the sintering process (the high-temperature co-fired ceramic process is about 1600° C., and the low-temperature co-fired ceramic process is about 850~900° C.), the organic binder is vaporized to form a relatively pure ceramic material, but it also causes holes and stresses in the sintered ceramic substrate and inevitably leads to coexistence of holes and deformation in the sintered ceramic substrate.

(5) When the ceramic substrate produced by the above-mentioned co-fired ceramic method is applied to the above-mentioned package substrate (the circuit board), only a small-area co-fired ceramic substrate can be selected. This is because its area is small, and a vertical deformation is relatively small. That is, the above-mentioned co-fired ceramic method can only be applied to smaller chips.

(6) Accordingly, traditional PCB circuit boards or co-fired ceramic substrates will have problems when facing high flatness requirements of high-end package circuit boards in the future.

SUMMARY OF DISCLOSURE

(7) The present disclosure provides a structure of a package substrate capable of solving the problems in the prior art.

(8) The structure of the package substrate includes: a first multi-layer substrate including a plurality of dielectric layers and a plurality of metal wiring layers and having a first surface and a second surface which are opposite to each other, wherein the dielectric layers and the metal wiring layers are alternately stacked, the dielectric layers are adhered each other, the metal wiring layers are individually embedded in the corresponding dielectric layers, and a dielectric layer located in the first surface of the multi-layer substrate is used as a solder mask layer which is embedded with at least one pad layer; and a supporting substrate having a first surface and a second surface which are opposite to each other, wherein the first surface of the supporting substrate is disposed on the second surface of the first multi-layer substrate and electrically connected to the first multi-layer substrate, there is no gap between the first surface of the supporting substrate and the second surface of the first multi-layer substrate, the supporting substrate includes a plurality of vertical vias, the vertical vias are used for electrically connecting the first surface of the supporting substrate to the second surface of the supporting substrate, and at least one electrical connection point is disposed on the second surface of the supporting substrate to electrically connect to a circuit board or an electronic component.

(9) In the structure of the package substrate of the present disclosure, the first multi-layer substrate covers the extremely flat supporting substrate, and there is no gap between the supporting substrate and the first multi-layer substrate. As long as a thickness uniformity of the first multi-layer substrate is controlled, the very thin first multi-layer substrate faithfully reflects flatness of the supporting substrate to a surface of the structure of the package substrate, so that the surface of the structure of the package substrate is very flat and beneficial to a bonding state with a chip.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 illustrates a manufacturing process and a structure in co-fired ceramic technology in the prior art.

(2) FIG. 2 illustrates a schematic cross-sectional view of a structure of a package substrate in accordance with one embodiment of the present disclosure.

(3) FIG. 3 illustrates a detailed cross-sectional view of a supporting substrate in the structure of the package substrate in FIG. 2.

(4) FIG. 4A to FIG. 4C illustrate a flow chart of manufacturing a multi-layer substrate according to one embodiment of the present disclosure.

(5) FIG. 5A to FIG. 5C illustrate a flow chart that there is no height difference between a pad layer and a dielectric layer in a first surface of a first multi-layer substrate manufactured in FIG. 2.

(6) FIG. 6 illustrates a schematic cross-sectional view of a structure of a package substrate in accordance with another embodiment of the present disclosure.

DETAILED DESCRIPTION

(7) To make the objectives, technical schemes, and technical effects of the present disclosure clearer and more definitely, the present disclosure will be described in detail below by using embodiments in conjunction with the appending drawings. It should be understood that the specific embodiments described herein are merely for explaining the present disclosure, and as used herein, the term “embodiment” refers to an instance, an example, or an illustration but is not intended to limit the present disclosure. In addition, the articles “a” and “an” as used in the specification and the appended claims should generally be construed to mean “one or more” unless specified otherwise or clear from the context to be directed to a singular form. Also, in the appending drawings, the components having similar or the same structure or function are indicated by the

same reference number.

(8) Structures of package substrates in accordance with various embodiments of the present disclosure will be described below with reference to FIG. 2 to FIG. 6.

(9) Please refer to FIG. 2. FIG. 2 illustrates a schematic cross-sectional view of a structure **10** of a package substrate in accordance with one embodiment of the present disclosure. The structure **10** of the package substrate includes a first multi-layer substrate **100** and a supporting substrate **102**. The first multi-layer substrate **100** is a multi-layer film substrate and has a first surface **1000** and a second surface **1002** opposite to each other. In the present embodiment, the supporting substrate **102** can be a crystal-grown ceramic substrate, a glass substrate, or a rigid substrate which can provide a flat surface. A material of the crystal-grown ceramic substrate includes aluminum oxide (Al.sub.2O.sub.3) crystals or aluminum nitride (AlN) crystals. The supporting substrate **102** also has a first surface **1020** and a second surface **1022** opposite to each other. The supporting substrate **102** has a plurality of vertical vias **1024**. The supporting substrate **102** has an electrically conductive material **1026** (shown by oblique lines) filled in the vertical vias **1024**, so that the first surface **1020** of the supporting substrate **102** is electrically connected to the second surface **1022**. The first surface **1020** of the supporting substrate **102** is disposed on the second surface **1002** of the first multi-layer substrate **100** and electrically connected to the first multi-layer substrate **100**. There is no gap between the first surface **1020** of the supporting substrate **102** and the second surface **1002** of the first multi-layer substrate **100**, so that the supporting substrate **102** can provide a flat surface to control the first multi-layer substrate **100** to have a flat surface. At least one electrical connection point **1028** (plural electrical connection points **1028** are shown in FIG. 2) is disposed on the second surface **1022** of the supporting substrate **102** to electrically connect to another circuit board (not shown) or another electronic component (not shown).

(10) As mentioned above, the supporting substrate **102** can be made of aluminum oxide, aluminum nitride or other ceramic materials formed by a crystal growth method. Since the ceramic substrate is generated by the crystal growth method, there are no holes. Furthermore, an extremely smooth and rigid surface can be formed through grinding and polishing. This can effectively solve disadvantages of co-fired ceramic substrates. Moreover, the supporting substrate **102** can also be a glass substrate, and the glass substrate can also provide an extremely flat and rigid surface.

(11) In the present disclosure, the structure **10** of the package substrate is formed by covering the extremely flat supporting substrate **102** with the first multi-layer substrate **100** of which a body can be made of a flexible dielectric material, such as polyimide. There is no gap between the supporting substrate **102** and the first multi-layer substrate **100**. As long as a thickness uniformity of the first multi-layer substrate **100** is controlled, the very thin first multi-layer substrate **100** faithfully reflects flatness of the supporting substrate **102** to a surface of the structure **10** of the package substrate, so that the surface of the structure **10** of the package substrate is very flat and beneficial to a bonding state with a chip.

(12) As shown in FIG. 2, the first multi-layer substrate **100** includes a first body **1004**, at least one pad layer **1006** (plural pad layers **1006** are shown in FIG. 2), at least one electrical connection point **1008** (plural electrical connection points **1008** are shown in FIG. 2), and at least one inner metal layer **1010** (plural inner metal layers **1010** are shown in FIG. 2). A material of the first body **1004** is polyimide (PI). The pad layers **1006** are all embedded (i.e., buried) in the first body **1004** and located inside the first surface of the first multi-layer substrate **100**. The electrical connection points **1008** are formed inside the second surface **1002** of the first multi-layer substrate **100**. The inner metal layers **1010** are disposed inside the first body **1004**. At least one of the pad layers **1006** is electrically connected to at least one of the electrical connection points **1008** through the at least one inner metal layer **1010**. The first body **1004** includes a dielectric layer **1012**. The pad layers **1006** are all embedded (i.e., buried) in the dielectric layer **1012**. Surfaces of the pad layers **1006** and a surface of the dielectric layer **1012** together form the first surface **1000** of the first multi-layer substrate **100**. It should be noted that in the present embodiment, the pad layers **1006** are

completely embedded in the dielectric layer **1012**. In another embodiment, the pad layers **1006** are partially embedded in the dielectric layer **1012**.

(13) A number of layers of the first multi-layer substrate **100** can be 2 to 20 layers. The dielectric layer **1012** has a thickness of 5 micrometers (μm) to 20 micrometers, and its material can be an organic dielectric material, such as polyimide. A height of each of the pad layers **1006**, a thickness of each of the inner metal layers **1010**, and a height of each of the electrical connection points **1008** are 1 micron to 10 microns, and a line width of each of the inner metal layers **1010** is 2 microns to 100 microns. It should be noted that at least one of the inner metal layers **1010** can be in a form of an entire metal layer to serve as a power layer or a ground layer. A size of a via of each of the inner metal layers **1010** is 2 microns to 50 microns.

(14) An implementation of connecting electrical connection points of a bare die (not shown) to the pad layers **1006** of the first surface **1000** of the multi-layer substrate **100** in the structure **10** of the package substrate **10** can be achieved by ultrasonic welding through an alignment mechanism. However, the present disclosure is not limited thereto.

(15) The bare die packaged on the package **10** of the substrate structure is easy to discharge the heat because a heating part of the bare die of the heating part is not sealed. When copper wires, metal fins, or heat pipes are connected to a backside of the bare die to enhance the heat dissipation, the best heat conduction function can be achieved. The heat conduction performance is becoming more and more important on a chip with increasingly powerful functions.

(16) Please refer to FIG. 3. FIG. 3 illustrates a detailed cross-sectional view of the supporting substrate **102** in the structure **10** of the package substrate in FIG. 2. The supporting substrate **102** includes a second body **1030**, the vertical vias **1024**, the electrically conductive material **1026**, and the electrical connection points **1028**. A material of the second body **1030** is aluminum oxide (Al.sub.2O.sub.3). The vertical vias **1024** penetrate the second body **1030** to communicate the first surface **1020** of the supporting substrate **102** and the second surface **1022** of the supporting substrate **102**. The vertical vias **1024** can be formed by a laser method or an etching method. The electrically conductive material substances **1026** is filled in the vertical vias **1024**, and its material is copper. The conductive material **1026** in the vertical vias **1024** contacts the electrical connection points **1008** of the first multi-layer substrate **100** and the electrical connection points **1028** on the second surface **1022**. The conductive material **1026** can be formed by placing copper wires into the vertical vias **1024** or injecting liquid copper into the vertical vias **1024**.

(17) Please refer to FIG. 4A to FIG. 4C. FIG. 4A to FIG. 4C illustrate a flow chart of manufacturing a multi-layer substrate according to one embodiment of the present disclosure.

(18) In FIG. 4A, a carrier **400** is provided. The carrier **400** is the supporting substrate **102** in FIG. 2. A first dielectric layer **402** is formed on the carrier **400**. In FIG. 4B, a metal wiring layer **404** is formed on the first dielectric layer **402**. After the metal wiring layer **404** is patterned, a second dielectric layer **406** is formed on the metal wiring layers **404**. A via **408** is formed in the second dielectric layer **406**. In FIG. 4C, another metal wiring layer **410** is formed on the second dielectric layer **406**. After the another metal wiring layer **410** is patterned, another second dielectric layer **412** and another via **414** are formed on the another metal wiring layer **410**. Metal is filled her metal wiring layer **410**. A surface of the another via **414** is filled with metal to form a pad layer **416**. The rest can be deduced to form the first multi-layer substrate **100** as shown in FIG. 2.

(19) In the present embodiment, after the first dielectric layer **402**, the second dielectric layer **406**, and the another second dielectric layer **412** are formed by spin coating, these dielectric layers are dried to be hardened. For the fabrication of the metal wiring layers, the metal wiring layer **404** and the another metal wiring layer **410** can be formed by vacuum sputtering copper (Cu). Then, the fabrication of the wirings is completed by photolithography, development, and etching processes. As for the via **408** and the another via **414** between the metal layers, they can be formed by drilling holes in the second dielectric layer **406** and the another second dielectric layer **412** by laser and then filling copper by electroplating.

(20) As mentioned above, in FIG. 4C, a structure formed by the first dielectric layer **402**, the metal wiring layer **404**, the second dielectric layer **406**, the via **408**, the another metal wiring layer **410**, the another second dielectric layer **412**, the another via **414**, and the pad layer **416** is the first multi-layer substrate **100** in FIG. 2. Accordingly, as shown in FIG. 2, the first multi-layer substrate **100** includes at least one dielectric layer **1012** and at least one pad layer **1006** formed in the dielectric layer **1012**. There is no height difference between an upper surface of the pad layer **1006** and an upper surface of the dielectric layer **1012**. When the pad layer **1006** of the structure **10** of the package substrate is correspondingly connected to electrical connection points of a chip (not shown), there is no gap between the package substrate **10** and the electrical connection points of the chip. Accordingly, bubble are not generated between the chip and the structure **10** of the package substrate.

(21) Since the structure formed in FIG. 4C is the first multi-layer substrate **100** in FIG. 2, it can be seen from FIG. 4C that the first multi-layer substrate **100** in FIG. 2 includes a plurality of dielectric layers and a plurality of metal wiring layers. The dielectric layers and the metal wiring layers are alternately stacked, and the dielectric layers are adhered each other. As such, the metal wiring layers are individually embedded in the corresponding dielectric layers. The dielectric layer **1012** located in the first surface **1000** of the multi-layer substrate **100** is used as a solder mask layer which is embedded with the at least one pad layer **1006**.

(22) Please refer to FIG. 5A to FIG. 5C. FIG. 5A to FIG. 5C illustrate a flow chart that there is no height difference between the pad layer **1006** and the dielectric layer **1012** in the first surface **1000** of the first multi-layer substrate **100** manufactured in FIG. 2.

(23) In FIG. 5A, a silicon wafer with good surface flatness is provided as a carrier **500**. A solder mask layer **502** is formed on the carrier **500** by a coating method. Then, at least one pad layer **504** is formed on the solder mask layer by an etching method, an electroplating method, or a lithography method.

(24) In FIG. 5B, a dielectric layer **506** is formed on the solder make layer **502** and the at least one pad layer **504**. The dielectric layer **506** covers the at least one pad layer **504** and the solder mask layer **502**. More specifically, the at least one pad layer **504** is completely embedded in the dielectric layer **506** (as shown in FIG. 5C). After the dielectric layer **506** is formed, subsequent manufacturing processes can be further performed according to design requirements of the multi-layer substrate to complete the overall multi-layer substrate.

(25) In FIG. 5C, the dielectric layer **506** is separated from the solder mask layer **502**. The dielectric layer **506** and the at least one pad layer **504** embedded in the dielectric layer **506** are reversed to obtain a multi-layer substrate with no level difference between an upper surface of the at least one pad layer **504** and an upper surface of the dielectric layer **506**.

(26) In the present embodiment, the method for separating the multi-layer substrate (including the dielectric layer **506** and the at least one pad layer **504**) from the surface of the solder mask layer **502** can be a sacrificial layer method or a carrier surface adhesion weakening method.

(27) Please refer to FIG. 6. FIG. 6 illustrates a schematic cross-sectional view of a structure **60** of a package substrate in accordance with another embodiment of the present disclosure. The structure **60** of the package substrate includes a first multi-layer substrate **600**, a supporting substrate **602**, and a second multi-layer substrate **604**. The first multi-layer substrate **600** is a multi-layer film substrate and has a first surface **6000** and a second surface **6002** opposite to each other. In the present embodiment, the supporting substrate **602** can be a crystal-grown ceramic substrate, a glass substrate, or a rigid substrate which can provide a flat surface. A material of the crystal-grown ceramic substrate includes aluminum oxide crystals or aluminum nitride crystals. The supporting substrate **602** also has a first surface **6020** and a second surface **6022** opposite to each other. The supporting substrate **602** has a plurality of vertical vias **6024**. The supporting substrate **602** has an electrically conductive material **6026** (shown by oblique lines) filled in the vertical vias **6024**, so that the first surface **6020** of the supporting substrate **602** is electrically connected to the second

surface **6022**. The first surface **6020** of the supporting substrate **602** is disposed on the second surface **6002** of the first multi-layer substrate **600** and electrically connected to the first multi-layer substrate **600**. There is no gap between the first surface **6020** of the supporting substrate **602** and the second surface **6002** of the first multi-layer substrate **600**. The second surface **6022** of the supporting substrate **602** is electrically connected to the second multi-layer substrate **604**. The second multi-layer substrate **604** is used for electrically connecting to a circuit board (not shown) or an electronic component (not shown). That is, at least one electrical connection point **6028** is disposed on the second surface **6022** of the supporting substrate **602** to electrically connect to the second multi-layer substrate **604**.

(28) The first multi-layer substrate **600** and the supporting substrate **602** of the structure **60** of the package substrate are respectively the same as the first multi-layer substrate **100** and the supporting substrate **102** of the structure **10** of the package substrate in FIG. 2. Implementations of the second multi-layer substrate **604** can refer to the related descriptions in FIG. 2, FIG. 4A to FIG. 4C, and FIG. 5A to FIG. 5C and are not repeated herein.

(29) As shown in FIG. 6, the first multi-layer substrate **600** and the second multi-layer substrate **604** are electrically connected to the supporting substrate **602**. There is no gap between the first multi-layer substrate **600** and the supporting substrate **602**, and there is no gap between the second multi-layer substrate **604** and the supporting substrate **602**. Horizontal stress of the first multi-layer substrate **600** against the supporting substrate **602** and horizontal stress of the second multi-layer substrate **604** against the supporting substrate **602** are substantially the same. By controlling the horizontal stress of the first multi-layer substrate **600** against the supporting substrate **602** to be substantially the same as the horizontal stress of the second multi-layer substrate **604** against the supporting substrate **602**, deformation of the supporting substrate **602** can be minimized, thereby maintaining excellent flatness.

(30) In one embodiment, by adjusting the structures of the first multi-layer substrate **600** and the second multi-layer substrate **604**, a total thickness of the dielectric layers of the first multi-layer substrate **600** and a total thickness of the dielectric layers of the second multi-layer substrate **604** are substantially the same, and a total thickness of the metal wiring layers of the first multi-layer substrate **600** and a total thickness of the metal wiring layers of the second multi-layer substrate **604** are substantially the same, thereby controlling the structure **60** of the package substrate to have a substantially symmetrical structure to improve the strength of the structure.

(31) An implementation of connecting electrical connection point of a bare die (not shown) to the pad layer of the first surface **6000** of the first multi-layer substrate **600** in the structure **60** of the package substrate is the same as that of the structure **10** of the package substrate in FIG. 2, and technical effect of the structure **60** of the package substrate is the same as that of the structure **10** of the package substrate.

(32) Compared with conventional co-fired ceramic substrates, the present disclosure has no holes and excellent flatness to meet the needs of high-level package in the future. The wirings in the present disclosure can be disposed in the first multi-layer substrate **600** and the second multi-layer substrate **604**. Organic polyimide is used as a dielectric material as an example. Compared with 9.4 of a conventional co-fired ceramic aluminum oxide or other ceramic materials, a dielectric constant of the organic polyimide is about 3 which is much lower. Apparently, compared with a conventional co-fired ceramic substrate or a FR4 PCB, the structure of the package substrate disclosed by the present disclosure has advantage of less attenuation of high-frequency signals. This also conforms with the development trend of semiconductors in the future.

(33) A bare die on each structure of the package substrate of the present disclosure can be a single bare die or a plurality of bare dies. Types of bare die(s) can include various semiconductors, such as logic chips, memories, image sensor chips or the like. It is also possible to connect various passive components, various sensors, various antennae, and various electronic component circuits to the same structure of the package substrate to form an entire high-performance electronic system.

(34) While the preferred embodiments of the present disclosure have been illustrated and described in detail, various modifications and alterations can be made by persons skilled in this art. The embodiment of the present disclosure is therefore described in an illustrative but not restrictive sense. It is intended that the present disclosure should not be limited to the particular forms as illustrated, and that all modifications and alterations which maintain the spirit and realm of the present disclosure are within the scope as defined in the appended claims.

Claims

1. A structure of a package substrate, comprising: a first multi-layer substrate comprising a plurality of dielectric layers and a plurality of metal wiring layers and having a first surface and a second surface which are opposite to each other, wherein the dielectric layers and the metal wiring layers are alternately stacked, the dielectric layers are adhered to each other, the metal wiring layers are individually embedded in the corresponding dielectric layers, and a dielectric layer of the plurality of dielectric layers located in the first surface of the multi-layer substrate is used as a solder mask layer which is embedded with at least one pad layer; and a supporting substrate having a first surface and a second surface which are opposite to each other, wherein the first surface of the supporting substrate is disposed on the second surface of the first multi-layer substrate and electrically connected to the first multi-layer substrate, there is no gap between the first surface of the supporting substrate and the second surface of the first multi-layer substrate, the supporting substrate comprises a plurality of vertical vias, the vertical vias are used for electrically connecting the first surface of the supporting substrate to the second surface of the supporting substrate, and at least one electrical connection point is disposed on the second surface of the supporting substrate to electrically connect to a circuit board or an electronic component.
2. The structure of the package substrate according to claim 1, further comprising a second multi-layer substrate, wherein at least one electrical connection point is disposed on the second surface of the supporting substrate to electrically connect to the second multi-layer substrate, and the second multi-layer substrate is used for electrically connecting to a circuit board or an electronic component.
3. The structure of the package substrate according to claim 1, wherein the supporting substrate is a crystal-grown ceramic substrate, and a material of the crystal-grown ceramic substrate includes aluminum oxide crystals or aluminum nitride crystals.
4. The structure of the package substrate according to claim 1, wherein at least one electrical connection point of a bare die is electrically and correspondingly connected to the at least one pad layer in the first surface of the first multi-layer substrate to complete an electrical connection.
5. The structure of the package substrate according to claim 2, wherein there is no gap between the second surface of the second multi-layer substrate and the supporting substrate, and horizontal stress of the first multi-layer substrate against the supporting substrate and horizontal stress of the second multi-layer substrate against the supporting substrate are substantially the same.
6. The structure of the package substrate according to claim 2, wherein at least one electrical connection point of a bare die is electrically and correspondingly connected to the at least one pad layer in the first surface of the first multi-layer substrate to complete an electrical connection.
7. The structure of the package substrate according to claim 1, wherein the at least one pad layer is completely or partially embedded in the dielectric layer in the first surface of the first multi-layer substrate, and there is no height difference between an upper surface of the at least one pad layer and an upper surface of the dielectric layer in the first surface of the first multi-layer substrate.
8. The structure of the package substrate according to claim 1, wherein a material of each of the dielectric layers of the first multi-layer substrate is polyimide.
9. The structure of the package substrate according to claim 1, wherein the first multi-layer

substrate further comprises a plurality of vias disposed in the dielectric layers and used for connecting the metal wiring layers.
