

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396482
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Tucker; Christopher S. et al.

Electronic vaping device including transfer pad with oriented fibers

Abstract

A cartridge for an electronic vaping device includes an outer housing extending in a longitudinal direction and a reservoir configured to contain a pre-vapor formulation. The reservoir is in the outer housing. The cartridge also includes at least two transfer pads at a reservoir end, and a wick in contact with the transfer pads. The transfer pads include a plurality of fibers. Each of the plurality of fibers is substantially parallel to the longitudinal direction.

Inventors: Tucker; Christopher S. (Midlothian, VA), Crowe; William J. (Richmond, VA), Jordan; Geoffrey Brandon (Midlothian, VA), Patil; Bipin R. (Richmond, VA), Keen; Jarrett (Richmond, VA), Roberts; Michael (Richmond, VA)

Applicant: Altria Client Services LLC (Richmond, VA)

Family ID: 1000008777346

Assignee: Altria Client Services LLC (Richmond, VA)

Appl. No.: 16/049450

Filed: July 30, 2018

Prior Publication Data

Document Identifier	Publication Date
US 20190104766 A1	Apr. 11, 2019

Related U.S. Application Data

continuation-in-part parent-doc US 15729895 20171011 US 10772356 child-doc US 16049450

Publication Classification

Int. Cl.: A24F13/00 (20060101); A24B15/167 (20200101); A24F40/42 (20200101); A24F40/10 (20200101)

U.S. Cl.:

CPC A24F40/42 (20200101); A24B15/167 (20161101); A24F40/10 (20200101); H05B2203/021 (20130101)

Field of Classification Search

CPC: A24F (47/00)

USPC: 131/328-329

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4083372	12/1977	Boden	N/A	N/A
5034721	12/1990	Benedictus	N/A	N/A
5388594	12/1994	Counts et al.	N/A	N/A
5665262	12/1996	Hajaligol et al.	N/A	N/A
5750964	12/1997	Counts et al.	N/A	N/A
6155268	12/1999	Takeuchi	N/A	N/A
6603924	12/2002	Brown et al.	N/A	N/A
6719405	12/2003	Powers	N/A	N/A
8191555	12/2011	Herbrich et al.	N/A	N/A
8375957	12/2012	Hon	N/A	N/A
8393331	12/2012	Hon	N/A	N/A
D688415	12/2012	Kim	N/A	N/A
8499766	12/2012	Newton	N/A	N/A
8528569	12/2012	Newton	N/A	N/A
D693053	12/2012	Chen	N/A	N/A
D695450	12/2012	Benassayag et al.	N/A	N/A
8746240	12/2013	Terry et al.	N/A	N/A
8757147	12/2013	Terry et al.	N/A	N/A
8794231	12/2013	Thorens et al.	N/A	N/A
8833364	12/2013	Buchberger	N/A	N/A
8851068	12/2013	Cohen et al.	N/A	N/A
D720095	12/2013	Alima	N/A	N/A
D720496	12/2013	Alima	N/A	N/A
D720881	12/2014	Liu	N/A	N/A
D724782	12/2014	Wu	N/A	N/A
D728155	12/2014	Liu	N/A	N/A
D728156	12/2014	Wu	N/A	N/A
D729441	12/2014	Hua	N/A	N/A
9055617	12/2014	Thorens et al.	N/A	N/A
9072321	12/2014	Liu	N/A	N/A
9095175	12/2014	Terry et al.	N/A	N/A
9101729	12/2014	Liu	N/A	N/A

9210738	12/2014	Ward et al.	N/A	N/A
9210739	12/2014	Chabach et al.	N/A	N/A
D748852	12/2015	Wu	N/A	N/A
D749260	12/2015	Wu	N/A	N/A
D751249	12/2015	Chen	N/A	N/A
9271525	12/2015	Liu	N/A	N/A
9282772	12/2015	Tucker et al.	N/A	N/A
9289014	12/2015	Tucker et al.	N/A	N/A
D758649	12/2015	Liu	N/A	N/A
D764703	12/2015	Liu	N/A	N/A
D765307	12/2015	Liu	N/A	N/A
9420829	12/2015	Thorens et al.	N/A	N/A
9427711	12/2015	Terry et al.	N/A	N/A
D765907	12/2015	Liu	N/A	N/A
9439455	12/2015	Alarcon et al.	N/A	N/A
D774247	12/2015	Chen	N/A	N/A
9510623	12/2015	Tucker et al.	N/A	N/A
D778492	12/2016	Liu	N/A	N/A
D778493	12/2016	Scott	N/A	N/A
D780372	12/2016	Liu	N/A	N/A
D784610	12/2016	Bosch	N/A	N/A
D785859	12/2016	Pang	N/A	N/A
9949510	12/2017	Liu	N/A	N/A
D827195	12/2017	Chen	N/A	N/A
D833064	12/2017	Verleur et al.	N/A	N/A
D834246	12/2017	Qiu	N/A	N/A
D835337	12/2017	Beer et al.	N/A	N/A
D835574	12/2017	Trongone	N/A	N/A
10226076	12/2018	Althorpe	N/A	A24F 40/42
10440997	12/2018	Borkovec	N/A	A24F 40/42
10506827	12/2018	Guo	N/A	A24F 40/05
10687557	12/2019	Tucker et al.	N/A	N/A
10772356	12/2019	Tucker et al.	N/A	N/A
10932496	12/2020	Tucker et al.	N/A	N/A
11930843	12/2023	Tasselli	N/A	A24B 15/167
2006/0231641	12/2005	Uchiyama et al.	N/A	N/A
2010/0293979	12/2009	Shei et al.	N/A	N/A
2011/0126848	12/2010	Zuber et al.	N/A	N/A
2011/0155153	12/2010	Thorens et al.	N/A	N/A
2013/0019887	12/2012	Liu	N/A	N/A
2013/0192623	12/2012	Tucker et al.	N/A	N/A
2013/0213419	12/2012	Tucker et al.	N/A	N/A
2013/0255675	12/2012	Liu	N/A	N/A
2013/0306064	12/2012	Thorens et al.	N/A	N/A
2013/0306065	12/2012	Thorens et al.	N/A	N/A
2014/0048086	12/2013	Zhanghua	N/A	N/A
2014/0053856	12/2013	Liu	N/A	N/A
2014/0261487	12/2013	Chapman et al.	N/A	N/A
2014/0270729	12/2013	DePiano et al.	N/A	N/A

2014/0283855	12/2013	Hawes et al.	N/A	N/A
2014/0283859	12/2013	Minskoff et al.	N/A	N/A
2014/0345635	12/2013	Rabinowitz et al.	N/A	N/A
2015/0020823	12/2014	Lipowicz et al.	N/A	N/A
2015/0027470	12/2014	Kane et al.	N/A	N/A
2015/0083147	12/2014	Schiff et al.	N/A	N/A
2015/0101625	12/2014	Newton et al.	N/A	N/A
2015/0128973	12/2014	Li et al.	N/A	N/A
2015/0144145	12/2014	Chang et al.	N/A	N/A
2015/0181930	12/2014	Liu	N/A	N/A
2015/0181944	12/2014	Li et al.	N/A	N/A
2015/0216233	12/2014	Sears et al.	N/A	N/A
2015/0216234	12/2014	Chung	N/A	N/A
2015/0216236	12/2014	Bless et al.	N/A	N/A
2015/0245654	12/2014	Memari et al.	N/A	N/A
2015/0245658	12/2014	Worm et al.	N/A	N/A
2015/0245669	12/2014	Cadieux et al.	N/A	N/A
2015/0272217	12/2014	Chen	N/A	N/A
2015/0305408	12/2014	Liu	N/A	N/A
2015/0305410	12/2014	Liu	N/A	N/A
2015/0313275	12/2014	Anderson et al.	N/A	N/A
2015/0313282	12/2014	Ademe et al.	N/A	N/A
2015/0328415	12/2014	Minskoff et al.	N/A	N/A
2015/0335075	12/2014	Minskoff et al.	N/A	N/A
2015/0351456	12/2014	Johnson et al.	N/A	N/A
2015/0359265	12/2014	Liu	N/A	N/A
2016/0057811	12/2015	Alarcon et al.	N/A	N/A
2016/0073694	12/2015	Liu	N/A	N/A
2016/0091194	12/2015	Liu	N/A	N/A
2016/0100633	12/2015	Gao	N/A	N/A
2016/0106153	12/2015	Zhu	N/A	N/A
2016/0135505	12/2015	Li	131/329	A24F 47/008
2016/0150828	12/2015	Goldstein et al.	N/A	N/A
2016/0183596	12/2015	Rado	N/A	N/A
2016/0192709	12/2015	Liu	N/A	N/A
2016/0227837	12/2015	Hammel et al.	N/A	N/A
2016/0242466	12/2015	Lord et al.	N/A	N/A
2016/0262453	12/2015	Ampolini et al.	N/A	N/A
2016/0309785	12/2015	Holtz	N/A	N/A
2016/0309786	12/2015	Holtz et al.	N/A	N/A
2016/0309787	12/2015	Hawes et al.	N/A	N/A
2016/0309788	12/2015	Hawes et al.	N/A	N/A
2016/0324216	12/2015	Li et al.	N/A	N/A
2016/0331037	12/2015	Cameron	N/A	N/A
2016/0345633	12/2015	DePiano et al.	N/A	N/A
2016/0360789	12/2015	Hawes et al.	N/A	N/A
2016/0363917	12/2015	Blackley	N/A	N/A
2016/0366931	12/2015	Zhang	N/A	N/A
2016/0366947	12/2015	Monsees et al.	N/A	N/A

2017/0000192	12/2016	Li	N/A	N/A
2017/0013880	12/2016	O'Brien et al.	N/A	N/A
2017/0027227	12/2016	Lipowicz	N/A	N/A
2017/0042240	12/2016	Murison	N/A	N/A
2017/0064999	12/2016	Perez et al.	N/A	N/A
2017/0079323	12/2016	Wang	N/A	N/A
2017/0105450	12/2016	Reed et al.	N/A	N/A
2017/0135405	12/2016	Reevell	N/A	N/A
2017/0150757	12/2016	Worm et al.	N/A	N/A
2017/0174914	12/2016	Matsumura et al.	N/A	N/A
2017/0224016	12/2016	Reevell	N/A	N/A
2017/0231283	12/2016	Gadas	N/A	N/A
2017/0231286	12/2016	Borkovec et al.	N/A	N/A
2017/0265523	12/2016	Lipowicz	N/A	N/A
2017/0273354	12/2016	Tucker et al.	N/A	N/A
2017/0325502	12/2016	Nelson et al.	N/A	N/A
2018/0007966	12/2017	Li et al.	N/A	N/A
2018/0027879	12/2017	Gavrielov et al.	N/A	N/A
2018/0077967	12/2017	Hatton et al.	N/A	N/A
2018/0161525	12/2017	Liu et al.	N/A	N/A
2018/0303163	12/2017	Baker et al.	N/A	N/A
2019/0133187	12/2018	Spencer et al.	N/A	N/A
2019/0269178	12/2018	Karles et al.	N/A	N/A
2019/0373679	12/2018	Fu et al.	N/A	N/A
2019/0387805	12/2018	Rostami	N/A	N/A
2020/0029619	12/2019	Sundberg et al.	N/A	N/A
2020/0120984	12/2019	Rogan	N/A	A24F 40/42
2021/0176826	12/2020	Tucker et al.	N/A	N/A
2024/0058557	12/2023	Alarcon et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202489175	12/2011	CN	N/A
203446525	12/2013	CN	N/A
203538371	12/2013	CN	N/A
203762291	12/2013	CN	N/A
104219973	12/2013	CN	N/A
104244749	12/2013	CN	N/A
104720115	12/2014	CN	N/A
105101507	12/2014	CN	N/A
105188428	12/2014	CN	N/A
105455198	12/2015	CN	N/A
105530825	12/2015	CN	N/A
106231933	12/2015	CN	N/A
106455711	12/2016	CN	N/A
205947122	12/2016	CN	N/A
107072293	12/2016	CN	N/A
107072314	12/2016	CN	N/A
107752129	12/2017	CN	N/A
207613205	12/2017	CN	N/A

000244	12/1998	EA	N/A
002337410-0009	12/2012	EM	N/A
002337410-0012	12/2012	EM	N/A
002403444-0003	12/2013	EM	N/A
002412106-0001	12/2013	EM	N/A
001420327-0005	12/2016	EM	N/A
0973419	12/1999	EP	N/A
2404515	12/2011	EP	N/A
2574247	12/2012	EP	N/A
3015010	12/2015	EP	N/A
3075270	12/2015	EP	N/A
3135139	12/2016	EP	N/A
3348154	12/2017	EP	N/A
D0518506-03	12/2012	ES	N/A
D0517952-09	12/2012	ES	N/A
D0518082-12	12/2012	ES	N/A
D0518097-04	12/2012	ES	N/A
D0518201-12	12/2012	ES	N/A
D0518036-03	12/2012	ES	N/A
D0518299-03	12/2012	ES	N/A
D0518462-09	12/2013	ES	N/A
D0519904-04	12/2013	ES	N/A
719318	12/1953	GB	N/A
4032478	12/2012	GB	N/A
2016-511008	12/2015	JP	N/A
2017-512470	12/2016	JP	N/A
3210447	12/2016	JP	N/A
3213257	12/2016	JP	N/A
2019-524121	12/2018	JP	N/A
10-1486294	12/2014	KR	N/A
10-2017-0044158	12/2016	KR	N/A
10-2018-0048846	12/2017	KR	N/A
10-2018-0083316	12/2017	KR	N/A
21430-0001	12/2014	PL	N/A
3429-0001	12/2012	PT	N/A
3428-0003	12/2012	PT	N/A
3771-0007	12/2013	PT	N/A
9612-0001	12/1999	RS	N/A
2604313	12/2015	RU	N/A
2607067	12/2016	RU	N/A
2620754	12/2016	RU	N/A
2627002	12/2016	RU	N/A
2638514	12/2016	RU	N/A
2639972	12/2016	RU	N/A
2644314	12/2017	RU	N/A
201307255-0001	12/2013	TR	N/A
WO-94/06314	12/1993	WO	N/A
WO-2007/078273	12/2006	WO	N/A
WO-2014/066730	12/2013	WO	N/A
WO-2014/150979	12/2013	WO	N/A

WO-2015/027470	12/2014	WO	N/A
WO-2015/114327	12/2014	WO	N/A
WO-2015/124688	12/2014	WO	N/A
WO-2015131428	12/2014	WO	N/A
WO-2015/144822	12/2014	WO	N/A
WO-2016/065926	12/2015	WO	N/A
WO-2016/079152	12/2015	WO	N/A
WO-2016/144966	12/2015	WO	N/A
WO-2016/156509	12/2015	WO	N/A
WO-2016/172441	12/2015	WO	N/A
WO-2016/172448	12/2015	WO	N/A
WO-2016154994	12/2015	WO	N/A
WO-2016162492	12/2015	WO	N/A
WO-2017/017970	12/2016	WO	N/A
WO-2017021536	12/2016	WO	N/A
WO-2017/055802	12/2016	WO	N/A
WO-2017/084849	12/2016	WO	N/A
WO-2017/144703	12/2016	WO	N/A
WO-2017/162691	12/2016	WO	N/A
2017/205692	12/2016	WO	N/A
WO-2017/186477	12/2016	WO	N/A
2018102696	12/2017	WO	N/A

OTHER PUBLICATIONS

United States Office Action for U.S. Appl. No. 15/858,425, dated Oct. 10, 2019. cited by applicant
International Preliminary Report on Patentability for Application No. PCT/EP2019/070556, dated Jun. 30, 2020. cited by applicant

U.S. Notice of Allowance dated Jan. 29, 2020 for corresponding U.S. Appl. No. 15/858,425. cited by applicant

Atomizer & Coil: Authentic GS-H5L 3.0 ml BCC Atomizer with LED light,
<http://www.ecigaretteb2c.com> (Year: 2014). cited by applicant

United States Office Action for U.S. Appl. No. 15/729,895, dated Jan. 23, 2020. cited by applicant
International Preliminary Report on Patentability and Written Opinion thereof dated Jul. 9, 2020 for International Application No. PCT/EP2018/086849. cited by applicant

U.S. Notice of Allowance dated Oct. 27, 2020 for corresponding U.S. Appl. No. 15/931,999. cited by applicant

U.S. Notice of Allowance dated Feb. 24, 2020 for corresponding U.S. Appl. No. 15/858,425. cited by applicant

International Search Report and Written Opinion thereof dated Jan. 22, 2019 for corresponding International Application No. PCT/EP2018/077806. cited by applicant

Innokin Recommends New Electronic Cigarette to Smokers, last updated May 18, 2017. cited by applicant

T Spindle, "Examination of Electronic Cigarette User Puff Topography: The Effect of a Mouthpiece-Based Topography Measurement Device on Plasma Nicotine and Subjective Effects", VCU Scholars Compass, Sep. 2015. cited by applicant

International Search Report and Written Opinion thereof dated Jan. 21, 2019 for corresponding International Application No. PCT/EP2018/077799. cited by applicant

International Preliminary Report on Patentability dated Apr. 23, 2020 for corresponding International Application No. PCT/EP2018/077806. cited by applicant

U.S. Notice of Allowance dated May 6, 2020 for corresponding U.S. Appl. No. 15/729,895. cited

by applicant

International Search Report and Written Opinion dated Mar. 20, 2019 for International Application No. PCT/EP2018/086849. cited by applicant

United States Notice Of Allowance for U.S. Appl. No. 29/621,730, dated Aug. 14, 2019. cited by applicant

Written Opinion of the International Preliminary Examining Authority dated Jun. 10, 2020 for corresponding International Application No. PCT/EP2019/070559. cited by applicant

U.S. Appl. No. 15/349,377, filed Nov. 11, 2016. cited by applicant

“The Stunning High Tech PCC Love eCig Smart Pod Starter Kit”—<http://www.sbwire.com/press-releases/the-stunning-high-tech-pcc-love-ecig-smart-pod-starter-kit-147288.htm>. cited by applicant

United States Office Action for corresponding U.S. Appl. No. 29/621,730 dated Dec. 17, 2018. cited by applicant

International Search Report and Written Opinion for corresponding Application No. PCT/EP2019/070559, dated Dec. 12, 2019. cited by applicant

International Search Report and Written Opinion for corresponding Application No. PCT/EP2019/070556, dated Nov. 22, 2019. cited by applicant

U.S. Office Action dated Apr. 28, 2021 for corresponding U.S. Appl. No. 15/729,909. cited by applicant

U.S. Office Action dated Oct. 21, 2021 for corresponding U.S. Appl. No. 15/729,909. cited by applicant

European Notice of Allowance dated Aug. 25, 2021 for corresponding European Application No. 18829884.8. cited by applicant

Russian Office Action and Search Report dated Dec. 23, 2021 for corresponding Russian Application No. 2020123230, and English-language translation thereof. cited by applicant

U.S. Office Action dated Nov. 3, 2021 for corresponding U.S. Appl. No. 16/049,346. cited by applicant

Russian Office Action and Search Report dated Nov. 26, 2021 for corresponding Russian Application No. 2020114678, and English-language translation thereof. cited by applicant

Russian Office Action and Search Report dated Nov. 25, 2021 for corresponding Russian Application No. 2020115145, and English-language translation thereof. cited by applicant

U.S. Office Action dated Mar. 16, 2022, for corresponding U.S. Appl. No. 15/729,909. cited by applicant

European Office Action dated Mar. 29, 2022, for corresponding European Application No. 19752663.5. cited by applicant

Russian Office Action dated Apr. 8, 2022, for corresponding Russian Application No. 2020115145, and English-language translation thereof. cited by applicant

Russian Notice of Allowance dated Apr. 14, 2022, for corresponding Russian Application No. 2020114678, and English-language translation thereof. cited by applicant

U.S. Office Action dated May 16, 2022 for corresponding U.S. Appl. No. 16/049,346. cited by applicant

Russian Notice of Allowance dated Apr. 28, 2022, for corresponding Russian Application No. 2020123230, and English-language translation thereof. cited by applicant

Russian Notice of Allowance dated Jul. 14, 2022, for corresponding Russian Application No. 2020115145, and English-language translation thereof. cited by applicant

Brazilian Office Action dated Jul. 21, 2022, for corresponding Brazilian Application No. BR112020010419-1, and English-language translation thereof. cited by applicant

U.S. Office Action dated Sep. 1, 2022, for corresponding U.S. Appl. No. 16/992,810. cited by applicant

Brazilian Office Action dated Aug. 9, 2022, for corresponding Brazilian Application No. BR112020005293-0, and English-language translation thereof. cited by applicant

Brazilian Office Action published in the Brazilian Industry Property Journal dated Sep. 20, 2022, for corresponding Brazilian Application No. 112020006347-9, and English-language translation thereof. cited by applicant

U.S. Notice of Allowance dated Oct. 7, 2022, for corresponding U.S. Appl. No. 16/049,346. cited by applicant

U.S. Office Action dated Oct. 5, 2022, for corresponding U.S. Appl. No. 15/729,909. cited by applicant

U.S. Notice of Allowance dated Sep. 29, 2022, for corresponding U.S. Appl. No. 16/049,346. cited by applicant

Japanese Office Action for corresponding Application No. 2020-517203, dated Oct. 13, 2022, English translation included. cited by applicant

Japanese Office Action dated Oct. 19, 2022, for corresponding Japanese Application No. 2020-518434, and English-language translation thereof. cited by applicant

U.S. Notice of Allowance dated Nov. 18, 2022, for corresponding U.S. Appl. No. 16/049,346. cited by applicant

U.S. Notice of Allowance dated Nov. 21, 2022, for corresponding U.S. Appl. No. 16/049,346. cited by applicant

U.S. Notice of Allowance dated Nov. 25, 2022, for corresponding U.S. Appl. No. 17/155,246. cited by applicant

Russian Office Action and Search Report dated Nov. 17, 2022, for corresponding Russian Application No. 2021104907, and English-language translation thereof. cited by applicant

U.S. Notice of Allowance dated Dec. 27, 2022, for corresponding U.S. Appl. No. 16/049,346. cited by applicant

Japanese Notice of Allowance dated Jan. 30, 2023, for corresponding Japanese Application No. 2020-518434, and English-language translation thereof. cited by applicant

U.S. Office Action dated Feb. 15, 2023 for correspondong U.S. Appl. No. 15/729,909. cited by applicant

Japanese Office Action dated Dec. 12, 2022 for corresponding Japanese Application No. 2020-533704, and English-language translation thereof. cited by applicant

Chinese Office Action dated Jan. 29, 2023 for corresponding Chinese Application No. 201880060406.5, and English-language translation thereof. cited by applicant

Notice of Allowance dated Mar. 2, 2023 issued in related U.S. Appl. No. 16/992,810. cited by applicant

Russian Decision to Grant and Search Report dated Mar. 1, 2023 for corresponding Russian Application No. 2021103129, and English-language translation thereof. cited by applicant

Office Action and Search Report dated Feb. 18, 2023 issued in related Chinese Patent Application No. 201880060418.8. cited by applicant

Notice of Allowance dated Mar. 13, 2023 issued in related Japanese Patent Application No. 2020-533704. cited by applicant

Brazilian Office Action dated Jan. 5, 2023 and published in the Brazilian Industrial Property Journal on Feb. 28, 2023 for corresponding Brazilian Application No. BR112020026871-2. cited by applicant

U.S. Notice of Allowance dated Apr. 3, 2023 for corresponding U.S. Appl. No. 16/049,346. cited by applicant

Decision to Grant dated Apr. 10, 2023 for corresponding Russian Application No. 2021104907, and English-language translation thereof. cited by applicant

Chinese Office Action dated Mar. 1, 2023 for corresponding Chinese Application No. 201880078750.7 and English-language translation thereof. cited by applicant

Office Action dated May 15, 2023 issued in related Japanese patent application No. 2021-503600. cited by applicant

Office Action dated Jun. 2, 2023 issued in related U.S. Appl. No. 16/992,810. cited by applicant

Office Action dated May 29, 2023 issued in related Japanese patent application No. 2020-517203. cited by applicant

Chinese Office Action dated Jun. 28, 2023 for corresponding Chinese Application No. 201880060406.5, and English-language translation thereof. cited by applicant

Office Action dated Jun. 15, 2023 issued in related Japanese patent application No. 2021-500282. cited by applicant

Office Action dated Jul. 13, 2023 issued in related Korean patent application No. 10-2020-7012756. cited by applicant

Notice of Allowance dated Sep. 14, 2023 issued in related U.S. Appl. No. 16/992,810. cited by applicant

Office Action dated Sep. 27, 2023 issued in related U.S. Appl. No. 15/729,909. cited by applicant

Korean Office Action dated Aug. 18, 2023 for corresponding Korean Application No. 10-2020-7012757, and English-language translation thereof. cited by applicant

Japanese Decision to Grant dated Oct. 5, 2023 for corresponding Japanese Application No. 2021-503600, and English-language translation thereof. cited by applicant

Japanese Notice of Allowance dated Oct. 26, 2023 for corresponding Japanese Application No. 2021-500282, and English-language translation thereof. cited by applicant

Office Action and Search Report dated Oct. 21, 2023 issued in related Chinese patent application No. 201980045676.3. cited by applicant

Notice of Allowance dated Nov. 14, 2023 issued in U.S. Appl. No. 16/049,346. cited by applicant

Chinese Office Action dated Nov. 9, 2023 for corresponding Chinese Application No. 201880060418.8, and English-language translation thereof. cited by applicant

Chinese Office Action dated Nov. 30, 2023 for corresponding Chinese Application No. 201880078750.7, and English-language translation thereof. cited by applicant

Korean Office Action dated Nov. 24, 2023 for corresponding Korean Application No. 10-2020-7019287, and English language thereof. cited by applicant

Office Action dated Nov. 23, 2023 issued in related Chinese patent application No. 201980045660.2. cited by applicant

Notice of Allowance dated Feb. 14, 2024 for corresponding U.S. Appl. No. 16/992,810. cited by applicant

Notice of Allowance dated Feb. 16, 2024 for corresponding U.S. Appl. No. 15/729,909. cited by applicant

Notice of Allowance issued Feb. 21, 2024 for corresponding U.S. Appl. No. 16/049,346. cited by applicant

Notice of Allowance issued Apr. 3, 2024 in U.S. Appl. No. 17/155,246. cited by applicant

Chinese Notice of Allowance for Chinese Patent Application No. 201880078750.7 mailed on Apr. 1, 2024. cited by applicant

Office Action dated Feb. 28, 2024 issued in Korean patent application No. 10-2020-7012756. cited by applicant

Notice of Allowance dated Feb. 26, 2024 issued in Korean patent application No. 10-2020-7012757. cited by applicant

Notice of Allowance issued Mar. 14, 2024 in U.S. Appl. No. 16/992,810. cited by applicant

Notice of Allowance issued Mar. 13, 2024 in U.S. Appl. No. 18/352,407. cited by applicant

Notice of Allowance issued Apr. 25, 2024 in U.S. Appl. No. 15/729,909. cited by applicant

Office Action dated Mar. 31, 2024 issued in Chinese patent application No. 201880060418.8. cited by applicant

Decision of Rejection dated Dec. 4, 2023 issued in related Japanese patent application No. 2020-517203. cited by applicant

Korean Notice of Allowance for Korean Patent Application No. 10-2020-7019287 dated May 1,

2024 and English translation thereof. cited by applicant
Notice of Allowance issued May 22, 2024 in U.S. Appl. No. 17/155,246. cited by applicant
Notice of Allowance dated Jun. 11, 2024 issued in U.S. Appl. No. 16/049,346. cited by applicant
Office Action dated Jun. 13, 2024 issued in U.S. Appl. No. 18/480,586. cited by applicant
Notice of Allowance dated Jun. 17, 2024 issued in Japanese Patent Application No. 2020-517203. cited by applicant
Decision to Refuse dated Jun. 27, 2024 issued in European patent application No. 19752663.5. cited by applicant
Notice of Allowance issued Jul. 26, 2024 in U.S. Appl. No. 16/992,810. cited by applicant
Notice of Allowance dated Jul. 22, 2024 issued in U.S. Appl. No. 15/729,909. cited by applicant
Office Action dated Aug. 7, 2024 issued in U.S. Appl. No. 18/411,538. cited by applicant
Office Action dated Aug. 7, 2024 issued in U.S. Appl. No. 16/992,810. cited by applicant
Notice of Allowance dated Aug. 7, 2024 issued in U.S. Appl. No. 16/049,346. cited by applicant
Notice of Allowance dated Jul. 24, 2024 issued in Korean patent application No. 10-2020-7012756. cited by applicant
Result of Consultation dated Jun. 5, 2024 issued in European Patent Application No. 19752663.5. cited by applicant
Notice of Allowance dated Jun. 20, 2024 issued in Chinese Patent Application No. 20188060418.8. cited by applicant
Office Action mailed Aug. 20, 2024 issued in Brazilian Application No. 1120200052930. cited by applicant
Notice of Allowance dated Sep. 18, 2024 issued in U.S. Appl. No. 16/049,346. cited by applicant
Notice of Allowance dated Aug. 28, 2024 issued in U.S. Appl. No. 15/729,909. cited by applicant
Office Action dated Sep. 26, 2024 issued in U.S. Appl. No. 18/480,586. cited by applicant
Notice of Allowance dated Oct. 1, 2024 issued in U.S. Appl. No. 17/893,614. cited by applicant
Office Action dated Sep. 14, 2024 issued in Korean patent application No. 10-2021-7004399. cited by applicant
Notice of Allowance dated Nov. 21, 2024 issued in U.S. Appl. No. 15/729,909. cited by applicant
Notice of Allowance dated Nov. 27, 2024 issued in U.S. Appl. No. 16/049,346. cited by applicant
Notice of Allowance dated Nov. 29, 2024 issued in U.S. Appl. No. 16/992,810. cited by applicant
Extended European Search Report for European Patent Application No. 24196619.1 issued on Dec. 9, 2024. cited by applicant
Notice of Allowance dated Dec. 18, 2024 issued in U.S. Appl. No. 18/411,538. cited by applicant
Notice of Allowance dated Dec. 20, 2024 issued in U.S. Appl. No. 18/411,538. cited by applicant
Corrected Notice of Allowability dated Jan. 22, 2025 issued in U.S. Appl. No. 16/049,346. cited by applicant
Office Action dated Jan. 13, 2025 issued in U.S. Appl. No. 18/480,586. cited by applicant
Notice of Allowance dated Feb. 8, 2025 issued in Korean patent application No. 10-2021-7004862. cited by applicant
Notice of Allowance dated Feb. 24, 2025 issued in Korean patent application No. 10-2021-7004399. cited by applicant
Notice of Allowance dated Mar. 11, 2025 issued in U.S. Appl. No. 15/411,538. cited by applicant
Notice of Allowance dated Mar. 25, 2025 issued in U.S. Appl. No. 16/992,810. cited by applicant
Notice of Allowance dated Mar. 24, 2025 issued in U.S. Appl. No. 17/893,614. cited by applicant

Primary Examiner: Dinh; Phuong K

Attorney, Agent or Firm: Harness, Dickey & Pierce, P.L.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation-in-part of U.S. application Ser. No. 15/729,895, filed Oct. 11, 2017, the entire content of which is hereby incorporated by reference.

BACKGROUND

Field

(1) The present disclosure relates to an electronic vaping or e-vaping device.

Description of Related Art

(2) An e-vaping device includes a heater element which vaporizes a pre-vapor formulation to produce a “vapor.”

(3) The e-vaping device includes a power supply, such as a rechargeable battery, arranged in the device. The battery is electrically connected to the heater, such that the heater heats to a temperature sufficient to convert a pre-vapor formulation to a vapor. The vapor exits the e-vaping device through a mouthpiece including at least one outlet.

SUMMARY

(4) At least one example embodiment relates to a cartridge of an electronic vaping device.

(5) In at least one example embodiment, a cartridge for an electronic vaping device comprises an outer housing extending in a longitudinal direction and a reservoir configured to contain a pre-vapor formulation. The reservoir is in the outer housing. The reservoir has a first reservoir end and a second reservoir end. The cartridge also includes a seal at the first reservoir end, a transfer pad at the second reservoir end, and a wick in contact with the transfer pad. The transfer pad includes a plurality of fibers. Each of the plurality of fibers is substantially parallel to the longitudinal direction.

(6) In at least one example embodiment, the reservoir is under atmospheric pressure.

(7) In at least one example embodiment, the transfer pad has a density ranging from about 0.08 g/cc to about 0.3 g/cc.

(8) In at least one example embodiment, the transfer pad has a length of about 5.0 mm to about 10.0 mm and a density of about 0.08 g/cc to about 0.1 g/cc.

(9) In at least one example embodiment, the transfer pad has a length of about 0.5 mm to about 5.0 mm and a density of about 0.1 g/cc to about 0.3 g/cc.

(10) In at least one example embodiment, the transfer pad includes a plurality of channels. Each of the plurality of channels is between adjacent ones of the plurality of fibers.

(11) In at least one example embodiment, the transfer pad includes an outer side wall. The outer side wall has a coating thereon.

(12) In at least one example embodiment, the transfer pad has a length ranging from about 0.5 mm to about 10.0 mm.

(13) In at least one example embodiment, the cartridge further includes an inner tube within the outer housing. The reservoir is between an outer surface of the inner tube and an inner surface of the outer housing.

(14) In at least one example embodiment, the transfer pad defines a channel extending through the transfer pad. The channel is sized and configured to fit around the outer surface of the inner tube at the second end of the reservoir.

(15) In at least one example embodiment, the plurality of fibers includes at least one of polypropylene and polyester.

(16) In at least one example embodiment, the cartridge further includes at least one heater in fluid communication with the wick. The at least one heater does not contact the transfer pad.

(17) In at least one example embodiment, about 50% to about 100% of the plurality of fibers

extend substantially in the longitudinal direction. In at least one example embodiment, about 75% to about 95% of the plurality of fibers extend substantially in the longitudinal direction.

(18) At least one example embodiment relates to an electronic vaping device.

(19) In at least one example embodiment, an electronic vaping device comprises an outer housing extending in a longitudinal direction and a reservoir configured to contain a pre-vapor formulation. The reservoir is in the outer housing, and the reservoir has a first reservoir end and a second reservoir end. The electronic vaping device also includes a seal at the first reservoir end, a transfer pad at the second reservoir end, a wick in contact with the transfer pad, at least one heater in fluid communication with the wick, and a power supply electrically connectable to the at least one heater. The transfer pad includes a plurality of fibers. The plurality of fibers is substantially parallel to the longitudinal direction.

(20) In at least one example embodiment, the reservoir is under atmospheric pressure.

(21) In at least one example embodiment, the transfer pad has a density ranging from about 0.08 g/cc to about 0.3 g/cc.

(22) In at least one example embodiment, the transfer pad has a length of about 5.0 mm to about 10.0 mm and a density of about 0.08 g/cc to about 0.1 g/cc.

(23) In at least one example embodiment, the transfer pad has a length of about 0.5 mm to about 5.0 mm and a density of about 0.1 g/cc to about 0.3 g/cc.

(24) In at least one example embodiment, the transfer pad includes a plurality of channels. Each of the plurality of channels is between adjacent ones of the plurality of fibers.

(25) In at least one example embodiment, the transfer pad includes an outer side wall. The outer side wall has a coating thereon.

(26) In at least one example embodiment, the transfer pad has a length ranging from about 0.5 mm to about 10.0 mm.

(27) In at least one example embodiment, the electronic vaping further comprises an inner tube within the outer housing. The reservoir is between an outer surface of the inner tube and an inner surface of the outer housing. The transfer pad is between the outer surface of the inner tube and the inner surface of the outer housing.

(28) In at least one example embodiment, the transfer pad defines a channel extending through the transfer pad, and the channel is sized and configured to fit around the outer surface of the inner tube at the second end of the reservoir.

(29) In at least one example embodiment, the plurality of fibers includes at least one of polypropylene and polyester.

(30) In at least one example embodiment, the at least one heater does not contact the transfer pad.

(31) In at least one example embodiment, about 50% to about 100% of the plurality of fibers extend substantially in the longitudinal direction. In at least one example embodiment, about 75% to about 95% of the plurality of fibers extend substantially in the longitudinal direction.

(32) At least one example embodiment relates to a method of forming a cartridge of an electronic vaping device.

(33) In at least one example embodiment, a method of forming a cartridge of an electronic vaping device comprises positioning an inner tube within an outer housing to establish a reservoir between an outer surface of the inner tube and an inner surface of the outer housing, the inner tube defining an air passage therethrough; inserting a gasket at a first end of the inner tube, the gasket defining a channel in communication with the air passage, the gasket sealing a first reservoir end; and positioning a transfer pad at a second end of the inner tube, the transfer pad including a plurality of fibers, the plurality of fibers being substantially parallel to the longitudinal direction.

(34) In at least one example embodiment, the transfer pad has an outer diameter that is larger than an inner diameter of the outer housing.

(35) In at least one example embodiment, the transfer pad is formed by a melt blowing process.

(36) In at least one example embodiment, the method further comprises positioning a mouth-end

insert at a first end of the outer housing.

(37) In at least one example embodiment, the method also includes positioning a wick in contact with the transfer pad; and positioning a heater in contact with the wick, the heater not in physical contact with the transfer pad.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The various features and advantages of the non-limiting embodiments herein may become more apparent upon review of the detailed description in conjunction with the accompanying drawings. The accompanying drawings are merely provided for illustrative purposes and should not be interpreted to limit the scope of the claims. The accompanying drawings are not to be considered as drawn to scale unless explicitly noted. For purposes of clarity, various dimensions of the drawings may have been exaggerated.

(2) FIG. 1 is a side view of an electronic vaping device according to at least one example embodiment.

(3) FIG. 2 is a cross-sectional view along line II-II of the electronic vaping device of FIG. 1 according to at least one example embodiment.

(4) FIG. 3A is a cross-sectional view of a cartridge according to at least one example embodiment.

(5) FIG. 3B is a perspective view of a heating element and a wick of the cartridge of FIG. 3A according to at least one example embodiment.

(6) FIG. 4 is a graph comparing electronic vaping devices including transfer pads having different densities and/or lengths according to at least one example embodiment.

(7) FIG. 5 is a graph comparing electronic vaping devices including transfer pads having different densities and/or lengths according to at least one example embodiment.

(8) FIG. 6 is a photograph of cross-section of a transfer pad according to at least one example embodiment.

(9) FIG. 7 is an enlarged photograph of a transfer pad according to at least one example embodiment.

(10) FIG. 8 is a side view of an electronic vaping device according to at least one example embodiment.

(11) FIG. 9 is a perspective view of a transfer pad in a cartridge, a housing the cartridge being transparent, according to at least one example embodiment.

(12) FIG. 10 is a perspective view of the transfer pad of FIG. 9 according to at least one example embodiment.

(13) FIG. 11 is a longitudinal cross-sectional view along line of an electronic vaping device according to at least one example embodiment.

(14) FIG. 12 is an exploded view of the cartridge of FIG. 11 according to at least one example embodiment.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

(15) Some detailed example embodiments are disclosed herein. However, specific structural and functional details disclosed herein are merely representative for purposes of describing example embodiments. Example embodiments may, however, be embodied in many alternate forms and should not be construed as limited to only the example embodiments set forth herein.

(16) Accordingly, while example embodiments are capable of various modifications and alternative forms, example embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that there is no intent to limit example embodiments to the particular forms disclosed, but to the contrary, example embodiments are to cover all modifications, equivalents, and alternatives falling within the scope of example

embodiments. Like numbers refer to like elements throughout the description of the figures.

(17) It should be understood that when an element or layer is referred to as being “on,” “connected to,” “coupled to,” or “covering” another element or layer, it may be directly on, connected to, coupled to, or covering the other element or layer or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. Like numbers refer to like elements throughout the specification. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

(18) It should be understood that, although the terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers, and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer, or section from another region, layer, or section. Thus, a first element, component, region, layer, or section discussed below could be termed a second element, component, region, layer, or section without departing from the teachings of example embodiments.

(19) Spatially relative terms (e.g., “beneath,” “below,” “lower,” “above,” “upper,” and the like) may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It should be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the term “below” may encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

(20) The terminology used herein is for the purpose of describing various example embodiments only and is not intended to be limiting of example embodiments. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(21) Example embodiments are described herein with reference to cross-sectional illustrations that are schematic illustrations of idealized embodiments (and intermediate structures) of example embodiments. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, example embodiments should not be construed as limited to the shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing.

(22) Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which example embodiments belong. It will be further understood that terms, including those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

(23) FIG. 1 is a side view of an e-vaping device according to at least one example embodiment.

(24) In at least one example embodiment, as shown in FIG. 1, an electronic vaping device (e-vaping device) **10** may include a replaceable cartridge (or first section) **15** and a reusable battery section (or second section) **20**, which may be coupled together at a threaded connector **25**. It should be appreciated that the connector **25** may be any type of connector, such as a snug-fit, detent,

clamp, bayonet, and/or clasp. An air inlet **55** extends through a portion of the connector **25**.

(25) In at least one example embodiment, the connector **25** may be the connector described in U.S. application Ser. No. 15/154,439, filed May 13, 2016, the entire contents of which is incorporated herein by reference thereto. As described in U.S. application Ser. No. 15/154,439, the connector **25** may be formed by a deep drawn process.

(26) In at least one example embodiment, the first section **15** may include a first housing **30** and the second section **20** may include a second housing **30'**. The e-vaping device **10** includes a mouth-end insert **35** at a first end **45**.

(27) In at least one example embodiment, the first housing **30** and the second housing **30'** may have a generally cylindrical cross-section. In other example embodiments, the housings **30** and **30'** may have a generally triangular cross-section along one or more of the first section **15** and the second section **20**. Furthermore, the housings **30** and **30'** may have the same or different cross-section shape, or the same or different size. As discussed herein, the housings **30**, **30'** may also be referred to as outer or main housings.

(28) In at least one example embodiment, the e-vaping device **10** may include an end cap **40** at a second end **50** of the e-vaping device **10**. The e-vaping device **10** also includes a light **60** between the end cap **40** and the first end **45** of the e-vaping device **10**.

(29) FIG. **2** is a cross-sectional view along line II-II of the e-vaping device of FIG. **1**.

(30) In at least one example embodiment, as shown in FIG. **2**, the first section **15** may include a reservoir **95** configured to store a pre-vapor formulation and a vaporizer **80** that may vaporize the pre-vapor formulation. The vaporizer **80** includes a heating element **85** and a wick **90**. The wick **90** may draw the pre-vapor formulation from the reservoir **95**. The heating element **85** may be a planar heating element including a filament portion, and the wick **90** may be a disk of wicking material as described in U.S. Patent Publication No. 2016/0309786 to Holtz et al. filed on Apr. 22, 2016, the entire content of which is incorporated herein by reference.

(31) The e-vaping device **10** may include the features set forth in U.S. Patent Application Publication No. 2013/0192623 to Tucker et al. filed Jan. 31, 2013, the entire contents of each of which are incorporated herein by reference thereto. In other example embodiments, the e-vaping device may include the features set forth in U.S. Patent Application Publication No. 2016/0309785 filed Apr. 22, 2016, and/or U.S. Pat. No. 9,289,014 issued Mar. 22, 2016, the entire contents of each of which is incorporated herein by reference thereto.

(32) In at least one example embodiment, the pre-vapor formulation is a material or combination of materials that may be transformed into a vapor. For example, the pre-vapor formulation may be a liquid, solid and/or gel formulation including, but not limited to, water, beads, solvents, active ingredients, ethanol, plant extracts, plant material, natural or artificial flavors, and/or vapor formers such as glycerin and propylene glycol. The plant material may include tobacco and/or non-tobacco plant material.

(33) In at least one example embodiment, the first section **15** may include the housing **30** extending in a longitudinal direction and an inner tube (or chimney) **70** coaxially positioned within the housing **30**. The inner tube **70** has a first end **240** and a second end **260**.

(34) A transfer pad **200** abuts the second end **260** of the inner tube **70**. An outer perimeter of the transfer pad **200** may provide a seal with an interior surface of the housing **30**. The transfer pad **200** reduces and/or prevents leakage of liquid from the reservoir **95** that is established between the inner tube **70** and the housing **30**.

(35) In at least one example embodiment, the transfer pad **200** includes a central, longitudinal air passage **235** defined therein. The air passage **235** is in fluid communication with an inner passage (also referred to as a central channel or central inner passage) **120** defined by the inner tube **70**.

(36) In at least one example embodiment, the transfer pad **200** includes a plurality of fibers. Each of the plurality of fibers is substantially parallel to the longitudinal direction. The transfer pad **200** may be formed of at least one of polypropylene and polyester. In at least one example embodiment,

the transfer pad **200** may be formed of polyolefin. Other polymers may be used to form the transfer pad **200**.

(37) The transfer pad **200** may be formed by a melt blowing process, where micro- and/or nano-fibers are formed from at least one polymer that is melted and extruded through small nozzles surrounded by high speed blowing gas and/or air.

(38) The polymers used in the melt blowing process do not include any processing aids, such as antistatics, lubricants, bonding agents, and/or surfactants. Thus, the polymers are substantially pure and the transfer pad **200** is inert to the pre-vapor formulation. In other example embodiments, the polymers may be mixed with processing aids, such as antistatics, lubricants, bonding agents, and/or surfactants. The transfer pad **200** may be obtained from Essentra PLC.

(39) In at least one example embodiment, the transfer pad **200** includes an outer side wall. The outer side wall may have a coating thereon that aids in reducing leakage and/or forming a seal between the transfer pad **200** and an inner surface of the housing **30**. The coating may include a hydrophobic or hydrophilic surface texture and/or be a parylene coating.

(40) While not wishing to be bound by theory, melt blowing polymers to form the transfer pad **200** may provide a melted outer surface that also aids in reducing leakage.

(41) In at least one example embodiment, the transfer pad **200** includes a plurality of channels. Each of the plurality of channels is between adjacent ones of the plurality of fibers. The channels may have a diameter ranging from about 0.01 mm to about 0.3 mm (e.g., about 0.02 mm to about 0.2 mm, about 0.03 mm to about 0.1 mm, about 0.04 mm to about 0.09 mm, or about 0.05 mm to about 0.08 mm).

(42) In at least one example embodiment, about 50% to about 100% (e.g., about 55% to about 95%, about 60% to about 90%, about 65% to about 85%, or about 70% to about 75%) of the plurality of fibers extend substantially in the longitudinal direction. In at least one example embodiment, about 75% to about 95% (e.g., about 80% to about 90% or about 82% to about 88%) of the plurality of fibers extend substantially in the longitudinal direction.

(43) The transfer pad may be generally cylindrical or disc shaped, but the transfer pad is not limited to cylindrical or disc shaped forms and a shape of the transfer pad may depend on a shape of the reservoir and housing. An outer diameter of the transfer pad **200** may range from about 3.0 mm to about 20.0 mm (e.g., about 5.0 mm to about 18.0 mm, about 7.0 mm to about 15.0 mm, about 9.0 mm to about 13.0 mm, or about 10.0 mm to about 12.0 mm). The air passage **235** within the transfer pad **200** may have an inner diameter that is substantially the same as an inner diameter of the inner tube **70**. In at least one example embodiment, the inner diameter of the air passage **235** ranges from about 1.0 mm to about 10.0 mm (about 2.0 mm to about 8.0 mm or about 4.0 mm to about 8.0 mm).

(44) In at least one example embodiment, the transfer pad **200** is oriented, such that the channels mostly transverse to the longitudinal direction of the housing **30**. In other example embodiments, the transfer pad **200** is oriented, such that the channels do not run transverse to the longitudinal direction of the housing **30**.

(45) While not wishing to be bound by theory, it is believed that the pre-vapor formulation travels through the channels, and a diameter of the channels is such that a liquid surface tension and pressurization within the reservoir moves and holds the pre-vapor formulation within the channel without leaking.

(46) In at least one example embodiment, the transfer pad **200** may be in a vaping device that does not include a reservoir in a closed system and/or at atmospheric pressure.

(47) In at least one example embodiment, the reservoir is sealed at a first end thereof and the transfer pad **200** is at a second end thereof.

(48) In at least one example embodiment, the transfer pad **200** has a density ranging from about 0.08 g/cc to about 0.3 g/cc (e.g., about 0.01 g/cc to about 0.25 g/cc or about 0.1 g/cc to about 0.2 g/cc). The transfer pad **200** has a length ranging from about 0.5 millimeter (mm) to about 10.0 mm

(e.g., about 1.0 mm to about 9.0 mm, about 2.0 mm to about 8.0 mm, about 3.0 mm to about 7.0 mm, or about 4.0 mm to about 6.0 mm). In at least one example embodiment, as the density of the transfer pad **200** increases, the length of the transfer pad decreases. Thus, transfer pads **200** having lower densities within the above-referenced range may be longer than transfer pads **200** having higher densities.

(49) In at least one example embodiment, the transfer pad **200** has a length of about 5.0 mm to about 10.0 mm and a density of about 0.08 g/cc to about 0.1 g/cc.

(50) In at least one example embodiment, the transfer pad **200** has a length of about 0.5 mm to about 5.0 mm and a density of about 0.1 g/cc to about 0.3 g/cc.

(51) In at least one example embodiment, the density and/or length of the transfer pad **200** is chosen based on the viscosity of a liquid flowing therethrough. Moreover, the density of the transfer pad **200** is chosen based on desired vapor mass, desired flow rate of the pre-vapor formulation flow rate, and the like.

(52) In at least one example embodiment, the first connector piece **155** may include a male threaded section for effecting the connection between the first section **15** and the second section **20**.

(53) In at least one example embodiment, at least two air inlets **55** may be included in the housing **30**. Alternatively, a single air inlet **55** may be included in the housing **30**. Such arrangement allows for placement of the air inlet **55** close to the connector **25** without occlusion by the presence of the first connector piece **155**. This arrangement may also reinforce the area of air inlets **55** to facilitate precise drilling of the air inlets **55**.

(54) In at least one example embodiment, the air inlets **55** may be provided in the connector **25** instead of in the housing **30**. In other example embodiments, the connector **25** may not include threaded portions.

(55) In at least one example embodiment, the at least one air inlet **55** may be formed in the housing **30**, adjacent the connector **25** to reduce and/or minimize the chance of an adult vaper's fingers occluding one of the ports and to control the resistance-to-draw (RTD) during vaping. In at least one example embodiment, the air inlet **55** may be machined into the housing **30** with precision tooling such that their diameters are closely controlled and replicated from one e-vaping device **10** to the next during manufacture.

(56) In at least one example embodiment, the air inlets **55** may be sized and configured such that the e-vaping device **10** has a resistance-to-draw (RTD) in the range of from about 60 mm H.sub.2O to about 150 mm H.sub.2O.

(57) In at least one example embodiment, a nose portion **110** of a gasket **65** may be fitted into a first end portion **105** of the inner tube **70**. An outer perimeter of the gasket **65** may provide a substantially tight seal with an inner surface **125** of the housing **30**. The gasket **65** may include a central channel **115** disposed between the inner passage **120** of the inner tube **70** and the interior of the mouth-end insert **35**, which may transport the vapor from the inner passage **120** to the mouth-end insert **35**. The mouth-end insert **35** includes at least two outlets **100**, which may be located off-axis from the longitudinal axis of the e-vaping device **10**. The outlets **100** may be angled outwardly in relation to the longitudinal axis of the e-vaping device **10**. The outlets **100** may be substantially uniformly distributed about the perimeter of the mouth-end insert **35** so as to substantially uniformly distribute vapor.

(58) In at least one example embodiment, the space defined between the gasket **65**, the transfer pad **200**, the housing **30**, and the inner tube **70** may establish the confines of the reservoir **95**. The reservoir **95** may contain the pre-vapor formulation, and optionally a storage medium (not shown) configured to store the pre-vapor formulation therein. The storage medium may include a winding of cotton gauze or other fibrous material about the inner tube **70**. The reservoir is under atmospheric pressure.

(59) In at least one example embodiment, the reservoir **95** may at least partially surround the inner passage **120**. Thus, the reservoir **95** may at least partially surround the inner passage **120**. The

heating element **85** may extend transversely across the inner passage **120** between opposing portions of the reservoir **95**. In some example embodiments, the heater **85** may extend parallel to a longitudinal axis of the inner passage **120**.

(60) In at least one example embodiment, the reservoir **95** may be sized and configured to hold enough pre-vapor formulation such that the e-vaping device **10** may be configured for vaping for at least about 200 seconds. Moreover, the e-vaping device **10** may be configured to allow each puff to last a maximum of about 5 seconds.

(61) In at least one example embodiment, the storage medium may be a fibrous material including at least one of cotton, polyethylene, polyester, rayon and combinations thereof. The fibers may have a diameter ranging in size from about 6 microns to about 15 microns (e.g., about 8 microns to about 12 microns or about 9 microns to about 11 microns). The storage medium may be a sintered, porous or foamed material. Also, the fibers may be sized to be irrespirable and may have a cross-section which has a Y-shape, cross shape, clover shape or any other suitable shape. In at least one example embodiment, the reservoir **95** may include a filled tank lacking any storage medium and containing only pre-vapor formulation.

(62) During vaping, pre-vapor formulation may be transferred from the reservoir **95** and/or storage medium to the proximity of the heating element **85** via capillary action of the wick **90**, which pulls the pre-vapor formulation from the transfer pad **200**. The wick **90** may be a generally tubular, and may define an air channel **270** therethrough. The heating element **85** abuts one end of the wick **90**. In other example embodiment, the heating element may at least partially surround a portion of the wick **90**. When the heating element **85** is activated, the pre-vapor formulation in the wick **90** may be vaporized by the heating element **85** to form a vapor.

(63) In at least one example embodiment, the wick **90** is in direct physical contact with the transfer pad **200**, but the heating element **85** does not directly contact the transfer pad **200**. In other example embodiments, the heating element **85** may contact the wick **90** and the transfer pad **200** (not shown).

(64) In at least one example embodiment, the wick **90** includes one or more layers of a sheet of wicking material. The sheet of wicking material may be formed of borosilicate or glass fiber. The sheet of wicking material may be folded and/or the wick **90** includes two or more layers of the sheet of wicking material. The sheet of wicking material may have a thickness ranging from about 0.2 mm to about 2.0 mm (e.g., about 0.3 mm to about 1.75 mm, about 0.5 mm to about 1.5 mm, or about 0.75 mm to about 1.0 mm).

(65) In other example embodiments, the wick **90** may include filaments (or threads) having a capacity to draw the pre-vapor formulation. For example, the wick **90** may be a bundle of glass (or ceramic) filaments, a bundle including a group of windings of glass filaments, etc., all of which arrangements may be capable of drawing pre-vapor formulation via capillary action by interstitial spacings between the filaments. The filaments may be generally aligned in a direction perpendicular (transverse) to the longitudinal direction of the e-vaping device **10**. In at least one example embodiment, the wick **90** may include one to eight filament strands, each strand comprising a plurality of glass filaments twisted together. The end portions of the wick **90** may be flexible and foldable into the confines of the reservoir **95**. The filaments may have a cross-section that is generally cross-shaped, clover-shaped, Y-shaped, or in any other suitable shape.

(66) In at least one example embodiment, the wick **90** may include any suitable material or combination of materials. Examples of suitable materials may be, but not limited to, glass, ceramic- or graphite-based materials. The wick **90** may have any suitable capillarity drawing action to accommodate pre-vapor formulations having different physical properties such as density, viscosity, surface tension and vapor pressure. The wick **90** may be non-conductive.

(67) In at least one example embodiment, the heating element **85** may include a planar sheet of metal that abuts the wick **90**. The planar sheet may extend fully or partially along the length of the wick **90**. In some example embodiments, the heating element **85** may not be in contact with the

wick **90**.

(68) In other example embodiment, not shown, the heating element **85** can be in the form of a wire coil, a ceramic body, a single wire, a cage of resistive wire, or any other suitable form. The heating element **85** may be any heater that is configured to vaporize a pre-vapor formulation.

(69) In at least one example embodiment, the heating element **85** may be formed of any suitable electrically resistive materials. Examples of suitable electrically resistive materials may include, but not limited to, copper, titanium, zirconium, tantalum and metals from the platinum group. Examples of suitable metal alloys include, but not limited to, stainless steel, nickel, cobalt, chromium, aluminum-titanium-zirconium, hafnium, niobium, molybdenum, tantalum, tungsten, tin, gallium, manganese and iron-containing alloys, and super-alloys based on nickel, iron, cobalt, stainless steel. For example, the heating element **85** may be formed of nickel aluminide, a material with a layer of alumina on the surface, iron aluminide and other composite materials, the electrically resistive material may optionally be embedded in, encapsulated or coated with an insulating material or vice-versa, depending on the kinetics of energy transfer and the external physicochemical properties required. The heating element **85** may include at least one material selected from the group consisting of stainless steel, copper, copper alloys, nickel-chromium alloys, super alloys and combinations thereof. In an example embodiment, the heating element **85** may be formed of nickel-chromium alloys or iron-chromium alloys. In another example embodiment, the heating element **85** may be a ceramic heater having an electrically resistive layer on an outside surface thereof.

(70) The inner tube **70** may include a pair of opposing slots, such that the wick **90** and the first and second electrical leads **225**, **225'** or ends of the heating element **85** may extend out from the respective opposing slots. The provision of the opposing slots in the inner tube **70** may facilitate placement of the heating element **85** and wick **90** into position within the inner tube **70** without impacting edges of the slots and the coiled section of the heating element **85**. Accordingly, edges of the slots may not be allowed to impact and alter the coil spacing of the heating element **85**, which would otherwise create potential sources of hotspots. In at least one example embodiment, the inner tube **70** may have a diameter of about 4 mm and each of the opposing slots may have major and minor dimensions of about 2 mm by about 4 mm.

(71) In at least one example embodiment, the first lead **225** is physically and electrically connected to the male threaded connector piece **155**. As shown, the male threaded first connector piece **155** is a hollow cylinder with male threads on a portion of the outer lateral surface. The connector piece is conductive, and may be formed or coated with a conductive material. The second lead **225'** is physically and electrically connected to a first conductive post **130**. The first conductive post **130** may be formed of a conductive material (e.g., stainless steel, copper, etc.), and may have a T-shaped cross-section as shown in FIG. 2. The first conductive post **130** nests within the hollow portion of the first connector piece **155**, and is electrically insulated from the first connector piece **155** by an insulating shell **135**. The first conductive post **130** may be hollow as shown, and the hollow portion may be in fluid communication with the air passage **120**. Accordingly, the first connector piece **155** and the first conductive post **130** form respective external electrical connection to the heating element **85**.

(72) In at least one example embodiment, the heating element **85** may heat pre-vapor formulation in the wick **90** by thermal conduction. Alternatively, heat from the heating element **85** may be conducted to the pre-vapor formulation by means of a heat conductive element or the heating element **85** may transfer heat to the incoming ambient air that is drawn through the e-vaping device **10** during vaping, which in turn heats the pre-vapor formulation by convection.

(73) It should be appreciated that, instead of using a wick **90**, the heating element **85** may include a porous material which incorporates a resistance heater formed of a material having a high electrical resistance capable of generating heat quickly.

(74) As shown in FIG. 2, the second section **20** includes a power supply **145**, a control circuit **185**,

and a sensor **190**. As shown, the control circuit **185** and the sensor **190** are disposed in the housing **30'**. A female threaded second connector piece **160** forms a second end. As shown, the second connector piece **160** has a hollow cylinder shape with threading on an inner lateral surface. The inner diameter of the second connector piece **160** matches that of the outer diameter of the first connector piece **155** such that the two connector pieces **155**, **160** may be threaded together to form the connection **25**. Furthermore, the second connector piece **160**, or at least the other lateral surface is conductive, for example, formed of or including a conductive material. As such, an electrical and physical connection occurs between the first and second connector pieces **155**, **160** when connected.

(75) As shown, a first lead **165** electrically connects the second connector piece **160** to the control circuit **185**. A second lead **170** electrically connects the control circuit **185** to a first terminal **180** of the power supply **145**. A third lead **175** electrically connects a second terminal **140** of the power supply **145** to the power terminal of the control circuit **185** to provide power to the control circuit **185**. The second terminal **140** of the power supply **145** is also physically and electrically connected to a second conductive post **150**. The second conductive post **150** may be formed of a conductive material (e.g., stainless steel, copper, etc.), and may have a T-shaped cross-section as shown in FIG. 2. The second conductive post **150** nests within the hollow portion of the second connector piece **160**, and is electrically insulated from the second connector piece **160** by a second insulating shell **215**. The second conductive post **150** may also be hollow as shown. When the first and second connector pieces **155**, **160** are mated, the second conductive post **150** physically and electrically connects to the first conductive post **130**. Also, the hollow portion of the second conductive post **150** may be in fluid communication with the hollow portion of the first conductive post **130**.

(76) While the first section **15** has been shown and described as having the male connector piece and the second section **20** has been shown and described as having the female connector piece, an alternative embodiment includes the opposite where the first section **15** has the female connector piece and the second section **20** has the male connector piece.

(77) In at least one example embodiment, the power supply **145** includes a battery arranged in the e-vaping device **10**. The power supply **145** may be a Lithium-ion battery or one of its variants, for example a Lithium-ion polymer battery. Alternatively, the power supply **145** may be a nickel-metal hydride battery, a nickel cadmium battery, a lithium-manganese battery, a lithium-cobalt battery or a fuel cell. The e-vaping device **10** may be vapable by an adult vaper until the energy in the power supply **145** is depleted or in the case of lithium polymer battery, a minimum voltage cut-off level is achieved.

(78) In at least one example embodiment, the power supply **145** is rechargeable. The second section **20** may include circuitry configured to allow the battery to be chargeable by an external charging device. To recharge the e-vaping device **10**, an USB charger or other suitable charger assembly may be used as described below.

(79) In at least one example embodiment, the sensor **190** is configured to generate an output indicative of a magnitude and direction of airflow in the e-vaping device **10**. The control circuit **185** receives the output of the sensor **190**, and determines if (1) the direction of the airflow indicates a draw on the mouth-end insert **8** (versus blowing) and (2) the magnitude of the draw exceeds a threshold level. If these vaping conditions are met, the control circuit **185** electrically connects the power supply **145** to the heating element **85**; thus, activating the heating element **85**. Namely, the control circuit **185** electrically connects the first and second leads **165**, **170** (e.g., by activating a heater power control transistor forming part of the control circuit **185**) such that the heating element **85** becomes electrically connected to the power supply **145**. In an alternative embodiment, the sensor **190** may indicate a pressure drop, and the control circuit **185** activates the heating element **85** in response thereto.

(80) In at least one example embodiment, the control circuit **185** may also include a light **60**, which the control circuit **185** activates to glow when the heating element **85** is activated and/or the battery

145 is recharged. The light **60** may include one or more light-emitting diodes (LEDs). The LEDs may include one or more colors (e.g., white, yellow, red, green, blue, etc.). Moreover, the light **60** may be arranged to be visible to an adult vaper during vaping, and may be positioned between the first end **45** and the second end **50** of the e-vaping device **10**. In addition, the light **60** may be utilized for e-vaping system diagnostics or to indicate that recharging is in progress. The light **60** may also be configured such that the adult vaper may activate and/or deactivate the heater activation light **60** for privacy.

(81) In at least one example embodiment, the control circuit **185** may include a time-period limiter. In another example embodiment, the control circuit **185** may include a manually operable switch for an adult vaper to initiate heating. The time-period of the electric current supply to the heating element **85** may be set or pre-set depending on the amount of pre-vapor formulation desired to be vaporized.

(82) Next, operation of the e-vaping device to create a vapor will be described. For example, air is drawn primarily into the first section **15** through the at least one air inlet **55** in response to a draw on the mouth-end insert **35**. The air passes through the air inlet **55**, into the space **250**, through the air channel **270**, through the central passage **235**, into the inner passage **120**, and through the outlet **100** of the mouth-end insert **35**. If the control circuit **185** detects the vaping conditions discussed above, the control circuit **185** initiates power supply to the heating element **85**, such that the heating element **85** heats pre-vapor formulation in the wick **90**. The vapor and air flowing through the inner passage **120** combine and exit the e-vaping device **10** via the outlet **100** of the mouth-end insert **35**.

(83) When activated, the heating element **85** may heat a portion of the wick **90** for less than about 10 seconds.

(84) In at least one example embodiment, the first section **15** may be replaceable. In other words, once the pre-vapor formulation of the cartridge is depleted, only the first section **15** may be replaced. An alternate arrangement may include an example embodiment where the entire e-vaping device **10** may be disposed once the reservoir **95** is depleted. In at least one example embodiment, the e-vaping device **10** may be a one-piece e-vaping device.

(85) In at least one example embodiment, the e-vaping device **10** may be about 80 mm to about 110 mm long and about 7 mm to about 8 mm in diameter. For example, in one example embodiment, the e-vaping device **10** may be about 84 mm long and may have a diameter of about 7.8 mm.

(86) FIG. 3A is a cross-sectional view of a cartridge according to at least one example embodiment.

(87) In at least one example embodiment, as shown in FIG. 3A, the first section **15** includes the transfer pad **200** that abuts the wick **90**, and the heater **85** is folded around three sides of the wick **90**.

(88) In at least one example embodiment, the wick **90** may include one or more sheets of material, such as a sheet formed of borosilicate fibers. The sheet of material may be folded, braided, twisted, adhered together, etc. to form the wick **90**. The sheet of material may include one or more layers of material. The sheet of material may be folded and/or twisted. If multiple layers of material are included, each layer may have a same density or a different density than other layers. The layers may have a same thickness or a different thickness. The wick **90** may have a thickness ranging from about 0.2 mm to about 2.0 mm (e.g., about 0.5 mm to about 1.5 mm or about 0.75 mm to about 1.25 mm). In at least one example embodiment, the wick **90** includes braided amorphous silica fibers.

(89) A thicker wick **90** may deliver a larger quantity of pre-vapor formulation to the heating element **85** so as to produce a larger amount of vapor, while a thinner wick **90** may deliver a smaller quantity of pre-vapor formulation to the heating element **85** so as to produce a smaller amount of vapor.

(90) In at least one example embodiment, the wick **90** may include a stiff, structural layer and at least one additional less rigid layer. The addition of a stiff, structural layer may aid in automated manufacture of the cartridge. The stiff, structural layer could be formed of a ceramic or other

substantially heat resistant material.

(91) FIG. 3B is a perspective view of a heating element and a wick of the cartridge of FIG. 3A according to at least one example embodiment.

(92) In at least one example embodiment, as shown in FIG. 3B, the heating element **85** may include a folded metal sheet, which at least partially surrounds the wick **90**. In at least one example embodiment, the folded heating element **85** is a single integral member that is cut and/or laser etched from a sheet of metal, which is folded about at least a portion of a wick **90**. The folded heating element **85** contacts the wick **90** on three sides.

(93) In at least one example embodiment, the folded heating element **85** includes a first plurality of U-shaped segments arranged in a first direction and defining a first side of the heating element **85**. The folded heating element **85** also includes a second plurality of U-shaped segments arranged in the first direction and defining a second side of the heating element **85**. The second side is substantially parallel to the first side.

(94) In at least one example embodiment, the folded heating element **85** also includes ends, which form a first lead portion and a second lead portion.

(95) FIG. 4 is a graph comparing electronic vaping devices including transfer pads having different densities and/or lengths according to at least one example embodiment.

(96) Aerosol mass of three different electronic vaping devices were compared. The first electronic vaping device (the first device) was a MARK TEN® electronic vaping device with about 0.9 g of pre-vapor formulation. The second electronic vaping device (the second device) included a cartridge having the configuration as set forth FIGS. 3A and 3B, and included an inner tube having a 1.6 mm inner diameter and the transfer pad **200** as described herein. The transfer pad had a length of about 5 mm and a density of about 0.152 g/cc. The third electronic vaping device (the third device) included a cartridge having the configuration as set forth FIGS. 3A and 3B, and included the transfer pad **200** as described herein. The transfer pad of the third electronic vaping device had a length of about 3 mm and a density of about 0.152 g/cc. The heater of each of the three devices had a resistance of about 3.5 ohms. The resistance-to-draw (RTD) of the first device was about 103 mm H.sub.2O, the RTD of the second device was about 128 mm H.sub.2O, and the RTD of the third device was about 129 mm H.sub.2O.

(97) To determine the aerosol mass, the machine smoking parameters are verified. The puff profile, puff volume, puff duration, puff time, puff frequency and number of puffs are all checked for accuracy before testing. Typical settings are: Square wave puff profile [08], puff volume 55.0 ml [64]%, puff duration 5 seconds [50], puff time 4.9 seconds [49], puff frequency 25 seconds [10], and number of puffs preset [10].

(98) As shown in FIG. 3, the third vaping device provides a larger aerosol mass over time than the second device including the transfer pad having a longer length. Thus, delivery of the pre-vapor formulation is improved in a vaping device in which the transfer pad is shorter. Moreover, the aerosol mass of the third device was greater than the aerosol mass of the first device for about 150 puffs.

(99) FIG. 5 is a graph comparing electronic vaping devices including transfer pads having different densities and/or lengths according to at least one example embodiment.

(100) Aerosol mass of four different electronic vaping devices were compared. The electronic vaping device A (device A) was a MARK TEN® electronic vaping device with about 0.9 g of pre-vapor formulation, which was the control device. The electronic vaping device B (device B) included a cartridge having the configuration as set forth FIGS. 3A and 3B, but included an inner tube having a 1.6 mm inner diameter and the transfer pad **200** as described herein. The transfer pad of device B had a length of about 4 mm and a density of about 0.100 g/cc. The electronic vaping device C (device C) included a cartridge having the configuration as set forth FIGS. 3A and 3B, but included the transfer pad **200** as described herein. The transfer pad of device C had a length of about 3 mm and a density of about 0.144 g/cc. The electronic vaping device D (device D) included

a cartridge having the configuration as set forth FIGS. 3A and 3B, but included the transfer pad **200** as described herein. The transfer pad of device D had a length of about 3 mm and a density of about 0.144 g/cc. The heater of each of the three devices had a resistance of about 3.5 ohms.

(101) The aerosol mass of each device is tested as set forth above.

(102) As shown in FIG. 5, device B performs similarly to device D having a shorter length and higher density. Moreover, both device B and device D provide a greater aerosol mass over 140 puffs than the control device.

(103) Accordingly, while not wishing to be bound by theory, it is believed that including a transfer pad having a shorter length and a higher density may perform similarly to an electronic vaping device including a transfer pad having a longer length and a lower density.

(104) FIG. 6 is a photograph of cross-section of a transfer pad according to at least one example embodiment.

(105) In at least one example embodiment, as shown in FIG. 6, the transfer pad **200** includes the plurality of fibers. When viewing the transfer pad **200**, it the plurality of fibers are substantially parallel.

(106) FIG. 7 is an enlarged photograph of a transfer pad according to at least one example embodiment.

(107) In at least one example embodiment, as shown in FIG. 7, the transfer pad **200** includes the plurality of fibers. When viewing an enlarged view of the transfer pad **200**, it is shown that the plurality of fibers are substantially parallel so as to form channels between adjacent ones of the plurality of fibers.

(108) FIG. 8 is a side view of an electronic vaping device according to at least on example embodiment.

(109) In at least one example embodiment, as shown in FIG. 8, the electronic vaping device is the same as in FIG. 2 except that the heating element **85** is a heating coil that surrounds a portion of the wick **90**.

(110) FIG. 9 is a perspective view of a transfer pad in a cartridge, a housing of the cartridge being transparent, according to at least one example embodiment.

(111) In at least one example embodiment, as shown in FIG. 9, the cartridge **15** is the same as in FIG. 8, except that the housing **30** of the cartridge **15** and the transfer pad **200** each have a generally square-shaped cross-section with generally rounded corners (“squircle”). The transfer pad **200** is about 3.0 mm in length so as to substantially prevent and/or reduce a weight of the transfer pad **200** from becoming too heavy when the transfer pad **200** becomes saturated with the pre-vapor formulation, and to substantially avoid and/or reduce movement of the transfer pad **200** within the cartridge **15** resulting from the weight thereof.

(112) FIG. 10 is a perspective view of the transfer pad of FIG. 9 according to at least one example embodiment.

(113) In at least one example embodiment, as shown in FIG. 10, the transfer pad **200** is the same as in FIG. 89, but it shown as having a length L_t of about 3.0 mm. The transfer pad **200** defines the air passage **235** therethrough. As shown, the air passage **235** has a generally circular cross-section and the cross-section of an outer surface of transfer pad **200** is different than a cross-section of the air passage **235**.

(114) FIG. 11 is a longitudinal cross-sectional view along line of an electronic vaping device according to at least one example embodiment.

(115) In at least one example embodiment, as shown in FIG. 11, instead of a single transfer pad **200**, the electronic vaping device may include cartridge and battery section having a structure that differs from the cartridge of FIGS. 1-10. The cartridge of this structure may include two or more transfer pads **200-1**, **200-2**.

(116) In at least one example embodiment, as shown in FIG. 11, the electronic vaping device (e-vaping device) **1100** may include a replaceable cartridge (or first section) **1110**, sometimes referred

to herein as an “e-vaping tank,” and a reusable battery section (or second section, also referred to herein as a power supply assembly) **1170**, which may be coupled together. The cartridge **1110** includes a reservoir **1120** holding a pre-vapor formulation and a vaporizer assembly **1140** configured to heat pre-vapor formulation drawn from the reservoir **1120** to generate the vapor. The power supply assembly **1170** includes a power supply **1172** and is configured to, when coupled to the cartridge **1110**, supply electrical power to the vaporizer assembly **1140** to enable the vaporizer assembly **1140** to generate the vapor.

(117) The power supply assembly **1170** and the cartridge **1110** may be coupled together via respective coupling interfaces to comprise the e-vaping device **1100**. The coupling interfaces may be configured to be removably coupled together, such that the power supply assembly **1170** and the cartridge **1110** are configured to be removably coupled together. It should be appreciated that each coupling interface (also referred to herein as a connector) of the coupling interfaces may include any type of interface, including a snug-fit, detent, clamp, bayonet, clasp sliding fit, sleeve fit, alignment fit, threaded connector, magnetic, clasp, or any other type of connection and/or combinations thereof. In the example embodiments shown in FIG. **11**, respective inlets **1182**, **1132** extend through the respective coupling interfaces to enable air to be drawn into the cartridge **1110** from the external environment (“ambient environment”). In some example embodiments, the air is drawn via an interior **1175** and an inlet **1178** of the power supply assembly **1170**. The air inlet **1178** may be the only air inlet. In other example embodiments, the device may include multiple air inlets.

(118) As shown in FIG. **11**, the cartridge **1110** may include a reservoir housing **1112** at least partially defining a reservoir **1120**, a vapor generator assembly **1130**, and an outlet assembly **1114**. As illustrated herein, the vapor generator assembly **1130** is shown to protrude from at least a portion of the reservoir **1120**, but example embodiments are not limited thereto: in some example embodiments, an end of the vapor generator assembly **1130** that is distal to outlet **1118** is flush or substantially flush (e.g., flush within manufacturing tolerances and/or material tolerances) with an end of the reservoir housing **1112** that is distal to the outlet, an end of the vapor generator assembly **1130** that is proximal to outlet is flush or substantially flush with an end of the reservoir housing that is proximal to outlet, and/or vapor generator assembly **1130** may be in whole or in part within a space occupied by reservoir housing **1112**. In some example embodiments, vapor generator assembly **1130** may form in whole or in part an inner tubular element of reservoir housing **1112**, defining in whole or in part reservoir **1120** between outside walls of **1130** and inside walls of **1112**.

(119) In some example embodiments, a separate housing that is separate from the reservoir housing **1112** may define the vapor generator assembly **1130** and may be directly or indirectly coupled to the reservoir housing **1112**. In some example embodiments, the one or more transfer pads **200-1**, **200-2** may extend through both a portion of the reservoir housing **1112** and a portion of the separate housing of the vapor generator assembly **1130**. In some example embodiments, the vapor generator assembly **1130** may be fixedly coupled to the reservoir housing **1112**. In other example embodiments, the vapor generator assembly **1130** may be removable from and/or detachably coupled to the reservoir housing **1112**. In some example embodiments, one or more seals and/or gaskets may be between the coupled housings.

(120) The cartridge **1110** may include a structural element (also referred to herein as an inner tube **1122**) within a space at least partially defined by the reservoir housing **1112**. The reservoir housing **1112** and the inner tube **1122** may each be configured to at least partially define the reservoir **1120**. For example, an inner surface of reservoir housing **1112** may define an outer boundary of reservoir **1120**. In another example, as shown, an outer surface of inner tube **1122** may define an inner boundary of reservoir **1120**. As shown, the reservoir **1120** may be defined as a space between an outer surface of inner tube **1122** and an inner surface of reservoir housing **1112**. In some example embodiments, vapor generator assembly **1130**, in whole or in part, may form a part of inner tube **1122**.

(121) In some example embodiments, cap structure **1198** may be coupled to ends of reservoir housing **1112** and inner tube **1122** that are proximal to outlet **1118** and thus complete the enclosure of the reservoir **1120**. As shown, cap structure may be further coupled to an outlet structure **1114**, and cap structure **1198** may include a port extending therethrough which is configured to enable fluid communication between the interior of inner tube **1122** (e.g., channel **1124**) and channel **1116** of outlet structure **1114**. In some example embodiments, cap structure **1198** may be fixedly coupled to outlet structure **1114** and/or to reservoir housing **1112**. In some example embodiments, cap structure **1198** may be detachably coupled to the cap structure **1198**, thereby enabling the outlet structure **1114** to be coupled or detached from a remainder of the e-vaping device **100** without further exposing the reservoir **120**. In some example embodiments, reservoir housing **112** and inner tube **122** can be parts of a unitary piece (i.e., parts of a single piece). In some example embodiments, reservoir housing **112** and cap structure **1198** can be parts of a unitary piece. In some example embodiments, inner tube **122** and cap structure **1198** can be parts of a unitary piece. In some example embodiments, cap structure **1198**, reservoir housing **112** and/or inner tube **122** can be individual parts coupled together, or parts of a unitary piece.

(122) In further example embodiments, cap structure **1198** and outlet structure **1114** can be parts of a unitary piece. In further example embodiments, cap structure **1198** and reservoir housing **112** can be parts of a unitary piece. In other words, cap structure **1198** may simply be a part of outlet structure **1114** or of reservoir housing **112**, or all may be parts of the same unitary piece. In yet further example embodiments, outlet structure **1114**, cap structure **1198**, reservoir housing **112** and/or inner tube **112** can be individual parts coupled together, or parts of a unitary piece.

(123) The inner surface of inner tube **1122** at least partially defines a channel **1124**. As shown in FIG. **11**, the inner tube **1122** may extend through at least one end of the reservoir housing **1112** so that the channel **1124** is in fluid communication with vaporizer assembly **1140** within an interior of the vapor generator assembly **1130**, an inlet **1132**, and outlet **1118**.

(124) Still referring to FIG. **11**, the vapor generator assembly **1130** includes a vaporizer assembly **1140** configured to draw pre-vapor formulation from the reservoir **1120** and to heat the drawn pre-vapor formulation to generate a vapor. The vaporizer assembly **1140** may include one or more transfer pads **200-1**, **200-2** that extend through at least one structure that at least partially defines the reservoir **1120**. In some example embodiments, transfer pads **200-1**, **200-2** may also extend through at least one structure that at least partially defines the vapor generator assembly **1130**. In some embodiment, transfer pads **200-1**, **200-3** may also extend into the vapor generator assembly **1130**, such that a first part of transfer pad **200-1** and a first part of transfer pad **200-2** reside inside reservoir **1120**, and also a second part of transfer pad **200-1** and a second part of transfer pad **200-2** reside inside the vapor generator assembly **1130**. In some example embodiments, as shown in FIG. **11**, vapor generator assembly **1130** includes transfer pads **200-1**, **200-2** that extend through an end portion **1115** of reservoir housing **1112**, where the end portion **1115** of reservoir housing **1112** at least partially defines the end of reservoir **1120** and an end of the generator assembly **1130**, so that the transfer pads **200-1**, **200-2** are in fluid communication with the reservoir **1120**. Each transfer pad **200-1**, **200-2** is configured to draw pre-vapor formulation from the reservoir **1120** at the respective ends that are inside the reservoir, and through an interior of the respective transfer pads **200-1**, **200-2** to respective opposite ends thereof. In some example embodiments, including the example embodiments shown in at least FIG. **11**, the transfer pads **200-1**, **200-2** may be cylindrical in shape, but it will be understood that other shapes and sizes of the transfer pads **200-1**, **200-2** may be possible (for example, the transfer pads may be flat and/or may have other cross-sectional forms such as square, rectangular, oval, triangular, irregular, others, etc. and/or combinations thereof). Each transfer pad may also have a different shape. In some example embodiments, one or more of the transfer pads may have a cylindrical shape such that the one or more transfer pads is about 2.5 mm in diameter and about 4.0 in height. Any other dimensions may be used depending on the application. In some example embodiments, one or more of the transfer pads may at least partially

comprise polyethylene terephthalate (PET), polypropylene (PP), a mixture of PET and PP, or the like. In some example embodiments, the transfer pads may be made of any materials with capabilities to transfer pre-vapor formulation from one location to another either through wicking or through other mechanisms. In some example embodiments, only one transfer pad may be used, or more than two transfer pads may be used.

(125) The vaporizer assembly **1140** further includes a dispensing interface **1144** (e.g., a “wick”) and a heating element **1142**. The dispensing interface **1144** is in contact with the respective ends of the one or more transfer pads **200-1**, **200-2**, such that pre-vapor formulation drawn from the reservoir **1120** by the one or more transfer pads **200-1**, **200-2** may be drawn through the one or more transfer pads **200-1**, **200-2** to the dispensing interface **1144**. Thus, the dispensing interface **1144** may draw pre-vapor formulation from the reservoir **1120** via the one or more transfer pads **200-1**, **200-2** (as noted above, less or more transfer pads may be used). The heating element **1142** is configured to generate heat that heats the pre-vapor formulation drawn into the dispensing interface **1144** from the reservoir **1120** via the one or more transfer pads **200-1**, **200-2**. In some example embodiments, the heating element **1142** is in contact with the dispensing interface **1144**. In some example embodiments, the heating element is isolated from direct contact with the dispensing interface **1144**. In some example embodiments, one or more transfer pads and the dispensing interface can be individual parts that contact each other, or can be parts of a unitary piece. In some example embodiments, the heating element **1142** may be on (e.g., may at least partially cover) each side of opposite sides of the dispensing interface **1144**. In some example embodiments, the heating element **1142** may at least partially extend around (e.g., may at least partially wrap around) the dispensing interface.

(126) In some example embodiments, the vapor generator assembly **1130** includes a circuit **1148** and an interface **1149** that is configured to couple with an interface **1180** of the power supply assembly **1170**. The interface **1149** is configured to electrically couple the vaporizer assembly **1140** and the circuit **1148** with the power supply assembly **1170** via interface **1180** of the power supply assembly **1170**.

(127) In some example embodiments, including the example embodiments shown in FIG. **11**, the interior of vapor generator assembly **1130** is at least partially defined by the same reservoir housing **1112** that at least partially defines the reservoir **1120**. In some example embodiments, the interior of vapor generator assembly **1130** is at least partially defined by a different housing relative to reservoir housing **1112**, such that reservoir housing **1112** does not at least partially define the interior of vapor generator assembly **1130**.

(128) The interface **1149** includes an inlet **1132** that extends through the interface **1149**, and may at least partially extend through the circuit **1148**, so that the vaporizer assembly **1140** in the interior of vapor generator assembly **1130** is in fluid communication with an exterior of the cartridge **1110** via the inlet **1132**. As shown in FIG. **11**, an end of the inner tube **1122** may be in fluid communication with an interior of the vapor generator assembly **1130** and thus may be in fluid communication with the vaporizer assembly **1140** located within the vapor generator assembly **1130**. Air entering the cartridge **1110** via inlet **1132** may flow through the interior of the vapor generator assembly **1130**, in fluid communication with the vaporizer assembly **1140**, to flow into channel **1124** defined by inner tube **1122**.

(129) Referring to FIG. **11**, the e-vaping device **1100** includes electrical pathways that may electrically couple the heating element **1142** to the interface, thereby enabling the heating element **1142** to be electrically coupled to power supply **1172** based on the interface of cartridge **1110** being coupled with the interface of power supply assembly **1170**. The electrical pathways may include one or more electrical connectors.

(130) If and/or when the interfaces are coupled together, one or more electrical circuits (“pathways”) through the cartridge **1110** and the power supply assembly **1710** may be established (“closed”). The established electrical circuits may include the vaporizer assembly **1140**, electrical

pathways, circuit **1148**, interfaces, control circuitry **1176**, power supply **1172**, sensor **1174**, light source **1177** (e.g., a light-emitting diode (“LED”)), and/or the one or more light-emitting devices **1188-1** and **1188-2**. As described further herein, the light source **1177** and/or the one or more light-emitting devices **1188-1** and **1188-2** are configured to emit light having a selected one or more properties (“light properties”) of a plurality of properties (e.g., a selected color of a plurality of colors, a selected brightness of a plurality of brightness levels, a selected pattern of a plurality of patterns, a selected duration of a plurality of durations, some combination thereof, or the like).

(131) Referring now to the outlet assembly **1114** as shown in FIG. **11**, the outlet assembly **1114** includes a channel **1116** extending therethrough to establish the outlet **1118**. In example embodiments where cap structure **1198** is simply a part of outlet assembly **1114**, or a part of reservoir housing **1112**, or where cap structure **1198** is omitted from the cartridge **1110**, the outlet assembly **1114** may be coupled, at an end thereof, to reservoir housing **1112** and/or inner tube **1122** to couple channel **1116** with inner tube **1122**, thereby enabling vapor to flow through the channel **1124** of the inner tube **1122** to the channel **1116** to the outlet **1118**. In example embodiments where cap structure **1198** is a separate piece in between outlet assembly **1114** and reservoir housing **1112**, the outlet assembly **1114** may be coupled to cap structure **1198** at an end of cap structure **1198**, and cap structure **1198** will be coupled on an opposing end to reservoir housing **1112** and/or inner tube **1122**, to enable vapor to flow through to the outlet **1118**.

(132) Referring now to cartridge **1110** as a whole, in view of the above, the cartridge **1110** may be configured to receive a flow of air into the vapor generator assembly **1130** via inlet **1132**, generate a vapor at vaporizer assembly **1140**, enable the generated vapor to be entrained in the flow of air through the interior of vapor generator assembly **1130**, direct the flow of air with generated vapor into the channel **1124** from the vapor generator assembly **1130**, and direct the flow of air with generated vapor to flow through the channel **1124** and channel **1116** (and through **1198a** if **1198** is a separate piece in between **1112** and **1114**) to the exterior environment via outlet **1118**.

(133) FIG. **12** is an exploded view of the cartridge of FIG. **11** according to at least one example embodiment.

(134) In at least one example embodiment as shown in FIG. **12**, the cartridge **1110** is generally the same as in FIG. **11**, but the transfer pads **200-1**, **200-2** are shown as being generally cylindrical bodies. Further, as shown in FIG. **12**, cap structure **1198** may be used to at least partially seal an open end of the reservoir housing **1112**.

(135) In other example embodiments, not shown, the housing of the electronic vaping device and/or the at least one transfer pad **200** may have other cross-sectional shapes, including triangular, rectangular, oval, or any other suitable shape.

(136) To test the cartridges for leaks, the following procedure was followed to determine t.sub.0 (time before incubation), t.sub.end (time after incubation), Δ .sub.weight (mg)=wt.sub.0(mg)−wt.sub.end(mg), and Δ .sub.weight (%)=((wt.sub.0(mg)−t.sub.end(mg))/fill weight)*100. The test utilized a vacuum oven (VO-200 Memmert or equivalent with a vacuum pump) and an analytical balance (OHAUS PA214C or equivalent).

(137) To determine leakage, empty cartridges are weighed together with the parts used for assembly if needed (e.g. mouthpiece, sealing ring). Each cartridge is filled with a pre-vapor formulation. The full Cartridges are assembled if needed (e.g. mouthpiece, sealing ring) and weighed. The full Cartridges stand for about 30 minutes at least prior to analysis. The full cartridges are then sealed inside foil bag and inserted into the Vacuum Oven: Ambient/500 mbar. The cartridges are incubated for about 24 hours. Then the foil bag is opened and visually inspected for drops. Each cartridge is then wiped down and weighed. Each cartridge is then puffed 50 puffs (5 second draw/55 ml, 30 sec total). The cartridges are then incubated at about 55° C. overnight in a horizontal position. The cartridges are then wiped and then weighed.

(138) When tested for leakage as set forth above, the cartridge of FIGS. **3A** and **3B**, including a transfer pad having a density of 0.100 g/cc and no gasket between the liquid reservoir and the

heating element and wick showed no leaks. As compared to control cartridge including no transfer pad, but including a seal/gasket between the reservoir and the heating element, the cartridge of FIGS. 3A and 3B performed substantially the same as the control cartridges as shown in Table 1 below.

(139) TABLE-US-00001 TABLE 1 Before After Ratio of Oven Oven Weight Weight Tank Weight Weight Difference Change No. Orientation (g) (g) (g) (%) 1 Horizontal 8.1735 8.1741 0.0006 0.01% 2 Horizontal 8.1658 8.1671 0.0013 0.02% 3 Horizontal 8.1631 8.1639 0.0008 0.01% C1 Horizontal 8.4910 8.4932 0.0022 0.03% C2 Horizontal 8.4631 8.4645 0.0014 0.02% C3 Horizontal 8.4952 8.4968 0.0016 0.02%

(140) Example embodiments have been disclosed herein, it should be understood that other variations may be possible. Such variations are not to be regarded as a departure from the spirit and scope of the present disclosure, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

Claims

1. A cartridge for an electronic vaping device comprising: an outer housing extending in a longitudinal direction; a reservoir configured to contain a pre-vapor formulation, the reservoir in the outer housing, the reservoir including, a reservoir housing in the outer housing and defining two orifices therein; at least two transfer pads at a reservoir end, the transfer pads including a plurality of fibers, each of the plurality of fibers being substantially parallel to the longitudinal direction, and each of the transfer pads extending through a respective one of the two orifices in the reservoir housing; a cap structure coupled to the reservoir housing opposite the reservoir end and defining a port; an outlet assembly coupled to the cap structure and defining a channel, the channel fluidly coupled to the port of the cap structure; and a vapor generator assembly in contact with the transfer pads, the vapor generator assembly including, a wick in contact with the transfer pads, and at least one heater in fluid communication with the wick, the vapor generator assembly configured to direct air flow in the longitudinal direction across the at least one heater.
2. The cartridge of claim 1, wherein the reservoir is under atmospheric pressure.
3. The cartridge of claim 1, wherein the transfer pads have a density ranging from about 0.08 g/cc to about 0.3 g/cc.
4. The cartridge of claim 1, wherein the transfer pads have a length of about 2.0 mm to about 10.0 mm.
5. The cartridge of claim 1, wherein the transfer pads have a density of about 0.08 g/cc to about 0.1 g/cc.
6. The cartridge of claim 1, wherein the transfer pads have a length of about 0.5 mm to about 10.0 mm.
7. The cartridge of claim 1, wherein the transfer pads have a density of about 0.1 g/cc to about 0.3 g/cc.
8. The cartridge of claim 1, wherein the transfer pads have a length of about 3.0 mm.
9. The cartridge of claim 1, wherein the transfer pads have a generally cylindrical cross-section.
10. The cartridge of claim 1, wherein the transfer pads each include a plurality of channels, one or more of the plurality of channels between adjacent ones of the plurality of fibers.
11. The cartridge of claim 1, wherein each of the transfer pads includes an outer side wall, the outer side wall having a coating thereon.
12. The cartridge of claim 1, further comprising: an inner tube within the outer housing, the reservoir between an outer surface of the inner tube and an inner surface of the outer housing.
13. The cartridge of claim 1, wherein the plurality of fibers include polypropylene, polyester, or both polypropylene and polyester.
14. The cartridge of claim 1, wherein the at least one heater does not contact the transfer pads.

15. The cartridge of claim 1, wherein about 50% to about 100% of the plurality of fibers extend substantially in the longitudinal direction.
16. The cartridge of claim 15, wherein about 75% to about 95% of the plurality of fibers extend substantially in the longitudinal direction.
17. An electronic vaping device comprising: an outer housing extending in a longitudinal direction; a reservoir configured to contain a pre-vapor formulation, the reservoir in the outer housing, the reservoir including, a reservoir housing in the outer housing and defining two orifices therein; at least two transfer pads at a reservoir end, each of the transfer pads including a plurality of fibers, the plurality of fibers being substantially parallel to the longitudinal direction, and each of the transfer pads extending through a respective one of the two orifices in the reservoir housing; a cap structure coupled to the reservoir housing opposite the reservoir end and defining a port; an outlet assembly coupled to the cap structure and defining a channel, the channel fluidly coupled to the port of the cap structure; a vapor generator assembly in contact with the transfer pads, the vapor generator assembly including, a wick in contact with the transfer pads; at least one heater in fluid communication with the wick, the vapor generator assembly configured to direct air flow in the longitudinal direction across the at least one heater; and a power supply electrically connectable to the at least one heater.
18. The electronic vaping device of claim 17, wherein the reservoir is under atmospheric pressure.
19. The electronic vaping device of claim 17, wherein the transfer pads have a density ranging from about 0.08 g/cc to about 0.3 g/cc.
20. The electronic vaping device of claim 17, wherein the transfer pads have a length of about 2.0 mm to about 10.0 mm.
21. The electronic vaping device of claim 17, wherein the transfer pads have a density of about 0.08 g/cc to about 0.1 g/cc.
22. The electronic vaping device of claim 17, wherein the transfer pads have a length of about 0.5 mm to about 5.0 mm.
23. The electronic vaping device of claim 17, wherein the transfer pads have a density of about 0.1 g/cc to about 0.3 g/cc.
24. The electronic vaping device of claim 17, wherein the transfer pads include a plurality of channels, one or more of the plurality of channels between adjacent ones of the plurality of fibers.
25. The electronic vaping device of claim 17, wherein the transfer pads include an outer side wall, the outer side wall having a coating thereon.
26. The electronic vaping device of claim 17, wherein the transfer pads have a length of about 3.0 mm.
27. The electronic vaping device of claim 17, wherein the transfer pads have a generally cylindrical cross-section.
28. The electronic vaping device of claim 17, further comprising: an inner tube within the outer housing, the reservoir between an outer surface of the inner tube and an inner surface of the outer housing.
29. The electronic vaping device of claim 17, wherein the plurality of fibers include polypropylene, polyester, or both polypropylene and polyester.
30. The electronic vaping device of claim 17, wherein the at least one heater does not contact the transfer pads.
31. The electronic vaping device of claim 17, wherein about 50% to about 100% of the plurality of fibers extend substantially in the longitudinal direction.
32. The electronic vaping device of claim 17, wherein about 75% to about 95% of the plurality of fibers extend substantially in the longitudinal direction.
33. The cartridge of claim 1, wherein, the vapor generator assembly further includes an interface configured to be coupled to a power supply, and a first end of the at least two transfer pads is

configured to extend into the reservoir and a second end of the at least two transfer pads is configured to extend into the vapor generator assembly.
