

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396485
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Chen; Liqian

Electronic atomizer

Abstract

The present disclosure provides an electronic atomizer, including: a housing, provided with a first accommodating cavity, a second accommodating cavity, and an assembly cavity, where the first accommodating cavity extends facing an end part of the housing to form a first opening, the second accommodating cavity extends facing the end part of the housing to form a second opening, and the assembly cavity extends facing the end part of the housing to form a third opening; a cigarette paste cup and a paste cutting knife, the cigarette paste cup being disposed in the first accommodating cavity through the first opening, and the paste cutting knife being disposed in the second accommodating cavity through the second opening; and an atomization device, disposed in the assembly cavity through the third opening, where a first air passage is disposed in the assembly cavity, one end of which is communicated with the atomization device.

Inventors:	Chen; Liqian (Guangdong, CN)
Applicant:	Shenzhen Impetus Technology Co., Ltd. (Guangdong, CN)
Family ID:	1000008340767
Assignee:	Shenzhen Impetus Technology Co., Ltd. (Shenzhen, CN)
Appl. No.:	18/979711
Filed:	December 13, 2024

Foreign Application Priority Data

CN	202411414806.5	Oct. 11, 2024
----	----------------	---------------

Publication Classification

Int. Cl.: A24F40/42 (20200101); A24B7/00 (20060101); A24F7/02 (20060101); A24F9/00 (20060101); A24F40/20 (20200101); A24F40/485 (20200101)

U.S. Cl.:

CPC **A24F40/42** (20200101); **A24B7/00** (20130101); **A24F7/02** (20130101); **A24F9/00** (20130101); **A24F40/20** (20200101); **A24F40/485** (20200101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2013/0032159	12/2012	Capuano	131/329	A24F 1/30
2018/0213847	12/2017	Reevell	N/A	A24F 40/30
2019/0223503	12/2018	Liu	N/A	A24F 7/00
2020/0237000	12/2019	Stura	N/A	H05B 6/108
2023/0100436	12/2022	Tran	131/329	A24F 40/46

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2019184468	12/2018	WO	A24F 47/008

OTHER PUBLICATIONS

WO-2019184468-A1 English Translation obtained from Espacenet, pp. 1-16 (Year: 2025). cited by examiner

Primary Examiner: Louie; Philip Y

Assistant Examiner: Bieger; Virginia R

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) The present application claims the benefit of Chinese Patent Application No. 202411414806.5 filed on Oct. 11, 2024, the contents of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

(2) The present disclosure relates to the technical field of electronic atomizers, and in particular, to an electronic atomizer.

BACKGROUND

(3) A current electronic atomizer generally atomizes cigarette oil to generate smoke to be then smoked by a user. As the development of electronic atomizer products, an electronic atomizer for atomizing a cigarette paste is researched and developed. At present, the cigarette paste is generally stored in an independent cigarette paste cup. When there is a need for smoking, a small piece is cut

by a paste cutting knife from the cigarette paste cup into a cigarette paste atomizer of the electronic atomizer, but the cigarette paste cup and the paste cutting knife are both independent from the electronic atomizer, which is convenient for the user to use and carry.

SUMMARY

(4) The present disclosure aims at providing an electronic atomizer, to solve the technical problem mentioned in the background art above.

(5) The technical solution adopted by the present disclosure is an electronic atomizer, including: a housing, provided with a first accommodating cavity, a second accommodating cavity, and an assembly cavity, where the first accommodating cavity extends facing an end part of the housing to form a first opening, the second accommodating cavity extends facing the end part of the housing to form a second opening, and the assembly cavity extends facing the end part of the housing to form a third opening; a cigarette paste cup and a paste cutting knife, where the cigarette paste cup is disposed in the first accommodating cavity through the first opening, and the paste cutting knife is disposed in the second accommodating cavity through the second opening; an atomization device, disposed in the assembly cavity through the third opening, where a first air passage is disposed in the assembly cavity, one end of the first air passage is communicated with the atomization device, and the other end of the first air passage extends to a second end of the housing to form an air inlet hole; and a mouthpiece, detachably disposed on the housing, and communicated with a flue of the atomization device.

(6) That is to say, in the electronic atomizer of the present application, the cigarette paste cup and the paste cutting knife can both be disposed in the housing, so that the cigarette paste cup and the paste cutting knife as well as the electronic atomizer are formed as a whole; when there is a need for smoking a cigarette, the paste cutting knife can be taken out from the second accommodating cavity of the housing, the mouthpiece is detached from the housing, the cigarette paste in the cigarette paste cup on the housing is cut by the paste cutting knife, the cut cigarette paste is placed in the atomization device, and the mouthpiece is mounted back on the housing. In this way, the user can suction the smoke generated through atomization by the atomization device by means of the mouthpiece. This structure can facilitate the user to carry the electronic atomizer capable of atomizing the cigarette paste.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) In order to more clearly illustrate the technical solutions in the embodiments of the present disclosure, the accompanying drawings required to be used in the embodiments or prior art description are briefly introduced below. Obviously, the accompanying drawings described below are only some embodiments of the present disclosure. For a person having ordinary skill in the art, without creative effort, other accompanying drawings can also be obtained according to these accompanying drawings.

(2) FIG. 1 is a decomposition schematic diagram of an electronic atomizer provided by the present disclosure;

(3) FIG. 2 is a top view of an electronic atomizer provided by the present disclosure;

(4) FIG. 3 is a sectional view at spot A-A in FIG. 2;

(5) FIG. 4 is a sectional view after a cigarette paste cup, an atomization device, and a paste cutting knife are hidden in FIG. 3;

(6) FIG. 5 is a schematic structural diagram of a paste cutting knife in an electronic atomizer provided by the present disclosure;

(7) FIG. 6 is a top view of a paste cutting knife provided by the present disclosure;

(8) FIG. 7 is a sectional view at spot B-B in FIG. 6;

(9) FIG. 8 is a schematic structural diagram of an atomization device in an electronic atomizer provided by the present disclosure;

(10) FIG. 9 is a top view of the atomization device provided by the present disclosure; and

(11) FIG. 10 a sectional view at spot C-C in FIG. 9.

REFERENCE NUMERALS

(12) **100**, housing; **110a**, first accommodating cavity; **110b**, second accommodating cavity; **110c**, assembly cavity; **120**, first air passage; **130a**, first threaded seat; **130b**, first electrode; **130c**, first insulating member; **130d**, vent hole; **140**, second connecting member; **150**, cover body; **160**, second elastic contact point; **170**, second clamping and holding portion; **180**, blocking member; **181**, clearance hole; **200**, cigarette paste cup; **210**, carrying cup body; **220**, cup cover; **230a**, first magnetic member; **230b**, second magnetic member; **240**, avoidance slot; **300**, paste cutting knife; **310**, first elastic contact point; **320**, outer shell; **330**, blade; **340**, control board; **350**, second battery; **360**, first clamping and holding portion; **370**, friction portion; **400**, atomization device; **410**, first atomization cup; **420**, second atomization cup; **430**, heating body; **440**, smoke forming chamber; **450**, first atomization passage; **460a**, first atomization hole; **460b**, second atomization hole; **460c**, third atomization hole; **460d**, fourth atomization hole; **470a**, second threaded seat; **470b**, second electrode; **470c**, second insulating member; **500**, mouthpiece; **510**, mouth cover; **520**, nozzle; **530**, air passage member; **540**, second air passage; **550**, air inlet portion; **560**, smoke inlet passage; **600**, main board; **700**, first battery; and **800**, adapter; **810**, first connecting member; **811**, adapter ring; **812**, first clamping and holding slot; **8121**, first clamping slot; **8122**, second clamping slot.

DETAILED DESCRIPTION

(13) To make the technical problem to be solved, technical solutions, and beneficial effects of the present disclosure clearer and more understandable, the present disclosure is further explained in detail in conjunction with the accompanying drawings and embodiments. It should be understood that the specific embodiments described herein are merely intended to illustrate the present disclosure, and are not used to limit the present disclosure.

(14) It should be explained that, when a component is referred to as “fixed to” or “disposed on” another component, it can be directly or indirectly placed on the other component. When a component is referred to as “connected to” another component, it can be directly or indirectly connected to the other component.

(15) It should be understood that, orientation or position relationships indicated by terms “length”, “width”, “up”, “down”, “front”, “rear”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “inside”, “outside”, and the like are orientation or position relationships shown in the drawings, and are only intended to facilitate to describe the present disclosure and simplify the description, rather than indicating or implying that a device or component referred to necessarily has a specific orientation and is configured or operated at a specific orientation, and therefore, they cannot be understood as limiting to the present disclosure.

(16) In addition, terms “first” and “second” are only intended for the purpose of description, and cannot be understood as indicating or implying relative importance or implying or pointing out the number of the indicated technical features. Hence, there may clearly or impliedly be one or more of the features defined by “first” and “second”. In some invention descriptions, the meaning of “a plurality of” refers to two or more, unless otherwise clearly and specifically defined.

(17) With reference to FIG. 1 to FIG. 4, an electronic atomizer includes a housing **100**, a cigarette paste cup **200**, a paste cutting knife **300**, an atomization device **400**, and a mouthpiece **500**.

(18) With reference to FIG. 4, the housing **100** is provided with a first accommodating cavity **110a**, a second accommodating cavity **110b**, and an assembly cavity **110c**, where the first accommodating cavity **110a** extends facing an end part of the housing **100** to form a first opening, the second accommodating cavity **110b** extends facing the end part of the housing **100** to form a second opening, and the assembly cavity **110c** extends facing the end part of the housing **100** to form a third opening.

(19) With reference to FIG. 1 and FIG. 3, the cigarette paste cup **200** is disposed in the first accommodating cavity **110a** through the first opening, and the paste cutting knife **300** is disposed in the second accommodating cavity **110b** through the second opening. The cigarette paste cup **200** is used for carrying a cigarette paste. The paste cutting knife **300** is used for cutting the cigarette paste in the cigarette paste cup **200**, and placing the cut cigarette paste into the atomization device **400**.

(20) The atomization device **400** is disposed in the assembly cavity **110c** through the third opening, and a first air passage **120** is disposed in the assembly cavity **110c**, where one end of the first air passage **120** is communicated with the atomization device **400**, and the other end of the first air passage **120** extends to a second end of the housing **100** to form an air inlet hole.

(21) The mouthpiece **500** is detachably disposed at the end part of the housing **100**, where the mouthpiece **500** is communicated with a flue of the atomization device **400**.

(22) For example, when there is a need for smoking a cigarette, the paste cutting knife **300** can be taken out from the second accommodating cavity **110b**, and the mouthpiece **500** is detached from the housing **100**; the cigarette paste in the cigarette paste cup **200** is cut by the paste cutting knife **300**, the cut cigarette paste is placed into the atomization device **400**, and then the mouthpiece **500** is mounted back on the housing **100**, so that the mouthpiece **500** is communicated with the flue of the atomization device **400**; the atomization device **400** heats the cigarette paste to generate smoke in the flue of the atomization device **400**; during suction of the user, an external air flow enters the first air passage **120** of the assembly cavity **110c** through the air inlet hole; and the air flow in the first air passage **120** flows into the flue of the atomization device **400**, and drives smoke to flow to the mouthpiece **500** for user suction.

(23) That is to say, in the electronic atomizer of the present application, the cigarette paste cup and the paste cutting knife **300** can both be disposed in the housing **100**, so that the cigarette paste cup and the paste cutting knife **300** as well as the electronic atomizer are formed as a whole; when there is a need for smoking the cigarette, the paste cutting knife **300** can be taken out from the second accommodating cavity **110b** of the housing **100**, the mouthpiece **500** is detached from the housing **100**, the cigarette paste in the cigarette paste cup **200** on the housing **100** is cut by the paste cutting knife **300**, the cut cigarette paste is placed in the atomization device **400**, and the mouthpiece **500** is mounted back on the housing **100**. In this way, the user can suction the smoke generated through atomization by the atomization device **400** by means of the mouthpiece **500**. This structure can facilitate the user to carry the electronic atomizer capable of atomizing the cigarette paste.

(24) With reference to FIG. 4, in some implementations, the first accommodating cavity **110a** can extend facing a first end of the housing **100** to form a first opening, the second accommodating cavity **110b** can extend facing a second end of the housing **100** to form a second opening, the assembly cavity **110c** can extend facing the first end of the housing **100** to form a third opening, and the mouthpiece **500** is detachably disposed at the first end of the housing **100**.

(25) Preferably, when the mouthpiece **500** is disposed at the first end of the housing **100**, the mouthpiece **500** can accommodate the cigarette paste cup **200** and the atomization device **400**, and protect the cigarette paste cup **200** and the atomization device **400**.

(26) With reference to FIG. 3, to facilitate mounting and exchanging the atomization device **400** in the assembly cavity **110c**, the assembly cavity **110c** can further be internally provided with a first threaded seat **130a** and a first electrode **130b** disposed in the first threaded seat **130a**, and a first insulating member **130c** is disposed between the first threaded seat **130a** and the first electrode **130b**. The atomization device **400** is in threaded connection with the first threaded seat **130a**, and the atomization device **400** is in contact with the first electrode **130b**, so that the first threaded seat **130a** and the first electrode **130b** become positive and negative poles of the atomization device **400**, to implement an electric connection after the atomization device **400** is mounted in the assembly cavity **110c**.

(27) Specifically, the electronic atomizer may further include a main board **600** and a first battery

700; the main board **600** and the first battery **700** are respectively disposed in the assembly cavity **110c**, the first battery **700** is eclectically connected to the main board **600**, and the main board **600** is electrically connected to the first threaded seat **130a** and the first electrode **130b**, respectively. By electrically connecting the main board **600** to the first threaded seat **130a** and the first electrode **130b**, the first battery **700** can supply power to the atomization device **400**.

(28) Further, a vent hole **130d** is disposed at the first electrode **130b**, and the vent hole **130d** is communicated with the first air passage **120** and the flue of the atomization device **400**, respectively. Specifically, the air flow in the first air passage **120** can flow into the flue of the atomization device **400** through the vent hole **130d**.

(29) In addition, in some implementations, the atomization device **400** of the present application can be a cigarette paste atomization device **400** or a cigarette oil atomization device **400**. When the atomization device **400** is the cigarette paste atomization device **400**, the cigarette paste atomization device **400** can be used for atomizing the cigarette paste. When the atomization device **400** is the cigarette oil atomization device **400** (a cigarette bomb), the cigarette oil atomization device **400** can be used for atomizing the cigarette oil.

(30) That is to say, in some implementations, the electronic atomizer can implement atomization of the cigarette paste to generate smoke for user suction, and can also generate smoke from the cigarette oil for user suction. The user can select to mount different atomization devices **400** as needed, so that the user suction experience can be improved.

(31) With reference to FIG. 1 and FIG. 3, the electronic atomizer may further include an adapter **800**, where the adapter **800** is provided with a first connecting member **810**, one end of the first air passage **120** close to the air inlet hole is provided with a second connecting member **140**, the adapter **800** is disposed in the air inlet hole, and the adapter **800** is detachably connected to the second connecting member **140** through the first connecting member **810**, and the adapter **800** is communicated with the first air passage **120** and the outside, respectively.

(32) As can be understood, when the user normally uses the electronic atomizer, the user may make suction through the mouthpiece **500**, and during suction, the external air flow may enter the first air passage **120** of the assembly cavity **110c** through the air inlet hole; and the air flow in the first air passage **120** flows into the flue of the atomization device **400**, and drives the smoke to flow to the mouthpiece **500** for user suction.

(33) When the user wants to use an external filtering device (for example, a kettle) for filtering the smoke generated by the electronic atomizer first before suction, the adapter **800** can be mounted in the air inlet hole, and the adapter **800** is connected to the second connecting member **140** in the first air passage **120** through the first connecting member **810**; and since the adapter **800** is further communicated with the first air passage **120** and the outside, respectively, at this time, the electronic atomizer can be connected to the filtering device through the adapter **800**. In this way, when the user suctions a nozzle **520** on the filtering device, the external air flow enters the flue of the atomization device **400** through the mouthpiece **500**; the smoke generated by the atomization device **400** flows into the filtering device along with the air flow through the first air passage **120** and the adapter **800**; and after the smoke is filtered by the filtering device, it is suctioned by the user through the mouthpiece **500** of the filtering device, that is, a reverse cigarette suction of the electronic atomizer is implemented.

(34) That is to say, when the user wants to normally suction the electronic atomizer, the air flow can flow through the air inlet hole, flows out through the first air passage **120** and the flue of the atomization device **400** in sequence, and is finally suctioned by the user through the mouthpiece **500**.

(35) When the electronic atomizer needs to be externally connected to one filtering device, one adapter **800** can be mounted at the air inlet hole; the adapter **800** can facilitate the connection to the filtering device. At this time, the air flow can flow out through the mouthpiece **500**, the flue of the atomization device **400**, the first air passage **120**, and the adapter **800** in sequence, and finally flow

to the filtering device, so as to implement the reverse cigarette suction of the electronic atomizer.

(36) In some implementations, to facilitate connection between the adapter **800** and the second connecting member **140** through the first connecting member **810**, the first connecting member **810** may include an adapter ring **811**; the adapter ring **811** is disposed on the adapter **800**; a periphery wall of the adapter ring **811** is provided with a first clamping and holding slot **812**; and when the adapter **800** rotates, the first clamping and holding slot **812** and the second connecting member **140** are clamped with each other. In this way, by clamping the first clamping and holding slot **812** with the second connecting member **140**, detaching of the adapter **800** can be facilitated.

(37) In addition, in some implementations, the second connecting member **140** may be a protrusion disposed on a side wall within one end of the first air passage **120** close to the air inlet hole, and the protrusion and the first clamping and holding slot **812** are clamped with each other. The first clamping and holding slot **812** may include a first clamping slot **8121** and a second clamping slot **8122** connected to each other. The first clamping slot **8121** extends in a flowing direction of an air flow, and the second clamping slot **8122** and the first clamping slot **8121** are vertical to each other. At this time, the second connecting member **140** (the protrusion) can be first inserted into the first clamping slot **8121**, and then the second connecting member **140** (the protrusion) is clamped in the second clamping slot **8122** by means of rotating the adapter **800**.

(38) Further, a second end of the housing **100** may also be provided with a cover body **150** for opening or closing the air inlet hole; the cover body **150** is provided with a through hole (not shown in the drawings); and when the cover body **150** closes the air inlet hole, the through hole is communicated with the first air passage **120**.

(39) As can be understood that, since the air inlet hole can be mounted with the adapter **800**, a hole diameter of the air inlet hole would generally be large. Hence, when no adapter **800** is mounted at the air inlet hole, the air inlet hole can be closed by the cover body **150**, and the external air flow can flow into the first air passage **120** through the through hole. In this way, it can avoid excessive air flow amounts, while avoiding or reducing pollutants entering the first air passage **120** at the same time.

(40) With reference to FIG. 3, FIG. 4, and FIG. 5, in some implementations, when the paste cutting knife **300** further has a heating function; a side wall of the paste cutting knife **300** can be provided with a first elastic contact point **310**; a side wall of the first accommodating cavity **110a** can be provided with a second elastic contact point **160**; the second elastic contact point **160** is electrically connected to the main board **600**; and when the paste cutting knife **300** is placed in the second accommodating cavity **110b**, the first elastic contact point **310** is in contact with the second elastic contact point **160** to charge the paste cutting knife **300**.

(41) Specifically, with reference to FIGS. 6 and 7, in some implementations, the paste cutting knife **300** may include an outer shell **320**, a blade **330**, a control board **340**, a first elastic contact point **310**, and a second battery **350**. The blade **330** is disposed at one end of the outer shell **320**, and protrudes out of the outer shell **320**, and the blade **330** is used for cutting an article; the control board **340** is disposed in the outer shell **320**, and the control board **340** is electrically connected to the blade **330**, so that the blade **330** is capable of emitting heat. The first elastic contact point **310** is disposed on a side wall of the outer shell **320**, the second battery **350** is disposed in the outer shell **320**, and the first elastic contact point **310** and the second battery **350** are electrically connected to the control board **340**, respectively.

(42) Specifically, the blade **330** can be disposed at one end of the outer shell **320**; one end of the blade **330** extends to the outside of the outer shell **320** for cutting an article; and the other end of the blade **330** is used for being electrically connected to the control board **340**.

(43) After the paste cutting knife **300** is placed in the second accommodating cavity **110b**, the first elastic contact point **310** is in contact with the second elastic contact point **160**, so that the first battery **700** in the assembly cavity **110c** can charge the second battery **350** of the paste cutting knife **300** through the control of the main board **600**.

(44) Further, the outer shell **320** may also be provided with a first clamping and holding portion **360**; the housing **100** may further be provided with a second clamping and holding portion **170**; when the paste cutting knife **300** is placed in the second accommodating cavity **110b**, the first clamping and holding portion **360** and the second clamping and holding portion **170** are clamped with each other, to fix the paste cutting knife **300** in the second accommodating cavity **110b**, to prevent the paste cutting knife **300** from falling from the second opening of the second accommodating cavity **110b**.

(45) Specifically, in some implementations, the first clamping and holding portion **360** may include a protrusion portion disposed on one side of the outer shell **320**, and a second clamping and holding slot is disposed on an end surface of the protrusion portion. The housing **100** is provided with a clearance slot for avoidance of the protrusion portion; a second clamping and holding portion **170** is disposed at an end surface of the clearance slot; and when the paste cutting knife **300** is placed in the accommodating cavity, the second clamping and holding portion **170** and the second clamping and holding slot are clamped with each other.

(46) Further, a friction portion **370** can also be disposed on a side surface of the protrusion portion. The friction portion **370** helps taking the paste cutting knife **300** clamped and fixed by the first clamping and holding portion **360** and the second clamping and holding portion **170** out from the second accommodating cavity **110b**.

(47) Specifically, the friction portion **370** may be a plurality of protrusions disposed at the side surface of the protrusion portion.

(48) Further, a blocking member **180** may further be disposed in the second accommodating cavity **110b**. When the paste cutting knife **300** is placed in the second accommodating cavity **110b**, the blocking member **180** blocks one end, away from the first clamping and holding portion **360**, in the paste cutting knife **300**.

(49) As can be understood, after the paste cutting knife **300** is placed in the second accommodating cavity **110b**, one end of the paste cutting knife **300** is blocked and positioned through the blocking member **180**, and the other end of the paste cutting knife **300** is clamped, cooperated, and fixed with the second clamping and holding portion **170** through the first clamping and holding portion **360**, so as to fix the paste cutting knife **300** in the accommodating cavity, thereby avoiding wobble of the paste cutting knife **300** in the accommodating cavity.

(50) Further, the blocking member **180** may be provided with a clearance hole **181**; and when the blocking member **180** blocks the paste cutting knife **300**, the clearance hole **181** allows the blade **330** of the paste cutting knife **300** to pass through, so as to prevent the blade **330** of the paste cutting knife **300** from being crushed by the blocking member **180**.

(51) With reference to FIG. 3, the cigarette paste cup **200** may include a carrying cup body **210**, the carrying cup body **210** is disposed in the first assembly cavity **110c**, a side wall of the carrying cup body **210** is provided with a cup cover **220** for opening or closing a cup opening of the carrying cup body **210**, and the cup cover **220** is provided with a first magnetic member **230a**. A side wall of the housing **100** is provided with a second magnetic member **230b**; and when the cup cover **220** opens the cup opening of the carrying cup body **210**, the first magnetic member **230a** is mutually magnetized with the second magnetic member **230b**.

(52) As can be understood, the cigarette paste can be carried in the carrying cup body **210**; after the cup cover **220** closes the cup opening of the carrying cup body **210**, the cigarette paste can be sealed. After the cup cover **220** opens the cup opening of the carrying cup body **210**, to avoid the cup cover **220** blocking the paste cutting knife **300** from cutting the cigarette paste, the first magnetic member **230a** on the cup cover **220** can be magnetized with the second magnetic member **230b** of the side wall of the housing **100**, so that the cup cover **220** is fixed on the housing **100**.

(53) Further, a first end of the housing **100** can further be provided with an avoidance slot **240** for avoidance of the cup cover **220**; and the avoidance slot **240** can facilitate opening of the cup opening of the cup cover **220**, and avoid interferences with the housing **100** when the cup cover

220 is opened.

(54) With reference to FIG. 3, the mouthpiece **500** may include a mouth cover **510**, a nozzle **520**, and an air passage member **530**; the nozzle **520** and a ceramic member are detachably disposed on the mouth cover **510**, respectively; and a second air passage **540** is formed at the nozzle **520** and the air passage member **530**. The mouth cover **510** is detachably connected to the housing **100**, and the mouth cover **510** is capable of covering the atomization device **400** and the cigarette paste cup **200**. The second air passage **540** is communicated with the flue of the atomization device **400**.

(55) Specifically, the smoke in the flue of the atomization device **400** flows into the second air passage **540**, and the user suctions the smoke in the second air passage **540** through the mouthpiece **500**.

(56) Further, the air passage member **530** may further be provided with a smoke inlet portion. When the mouth cover **510** is connected to the housing **100**, the smoke inlet portion extends into the flue of the atomization device **400**, and the smoke inlet portion is provided with a smoke inlet passage **560** for communicating the second air passage **540** and the flue of the atomization device **400**.

(57) Specifically, the smoke in the flue of the atomization device **400** flows into the second air passage **540** through the smoke inlet passage **560** to be suctioned by the user.

(58) As can be understood, since the smoke inlet portion extends into the flue of the atomization device **400**, it is ensured that the smoke in the flue can enter the smoke inlet passage **560** and flow into the second air passage **540**.

(59) In addition, since the nozzle **520** and the ceramic member are detachably disposed on the mouth cover **510**, respectively, the nozzle **520** and the ceramic member can be detached from the mouth cover **510** for cleaning.

(60) Further, in some implementations, a third magnetic member (not shown in the drawings) can be disposed on the mouth cover **510**; a fourth magnetic member (not shown in the drawings) may be disposed on the housing **100**; the mouth cover **510** implements detachable connection between the mouth cover **510** and the housing **100** through magnetism between the third magnetic member and the fourth magnetic member.

(61) With reference to FIG. 8 to FIG. 10, for example, in some implementations, when the atomization device **400** is the cigarette paste atomization device **400**, the cigarette paste atomization device **400** may include a first atomization cup **410**, a second atomization cup **420**, and a heating body **430**. The second atomization cup **420** is disposed in the first atomization cup **410**, the heating body **430** is disposed in the second atomization cup **420**, the second atomization cup **420** is used for placing the cigarette paste, and the heating body **430** heats and atomizes the cigarette paste to generate smoke.

(62) Further, the heating body **430** may include a porous member (not shown in the drawings), the porous member is provided with a heating piece (not shown in the drawings); the porous member is disposed in the second atomization cup **420** and forms a smoke forming chamber **440** with a bottom of the second atomization cup **420**; the porous member is used for carrying the cigarette paste; and after the cigarette paste is liquefied, it can enter the porous member to be in contact with the heating piece to generate smoke. The porous member may be integrally formed with the heating piece. For example, when the porous member is a porous ceramic, the porous member and the heating piece can be integrally sintered and formed.

(63) Specifically, the cigarette paste can be placed into the second atomization cup **420** at the cup opening of the second atomization cup **420**; the porous member located in the second atomization cup **420** carries the cigarette paste; when the heating piece emits heat, heat energy can be transferred onto the porous member; the heat energy on the porous member enables the smoke to be liquefied; the liquefied cigarette paste can enter the porous member from holes on the porous member to be in contact with the heating piece; the smoke is generated by atomization after the cigarette paste is in contact with the heating piece; and the smoke is gathered in the smoke forming

chamber **440**.

(64) Further, a first atomization passage **450** is further disposed between the first atomization cup **410** and the second atomization cup **420**; a first atomization hole **460a** is disposed on the first atomization cup **410**; a second atomization hole **460b** and a third atomization hole **460c** are respectively disposed on the second atomization cup **420**; the second atomization hole **460b** enables the first atomization hole **460a** to be communicated with the smoke forming chamber **440**, and the third atomization hole **460c** enables the first atomization passage **450** to be communicated with the smoke forming chamber **440**.

(65) The air flow of the first air passage **120** enters the smoke forming chamber **440** through the first atomization hole **460a** and the second atomization hole **460b** in sequence, and drives the smoke in the smoke forming chamber **440** to discharge from the smoke forming chamber **440** to the mouthpiece **500** through the third atomization hole **460c** and the first atomization passage **450** in sequence.

(66) As can be understood that the first atomization hole **460a**, the second atomization hole **460c**, the smoke forming chamber **440**, the third atomization hole **460c**, and the first atomization passage **450** may form the flue of the cigarette paste atomization device **400**.

(67) The cigarette paste atomization device above could implement atomization of the cigarette paste to generate the smoke; the heating piece in a smoke sensing atomizer is not in direct contact with the cigarette paste; and by heating the cigarette paste through the porous member, the cigarette paste is liquefied to flow into the porous member and then in contact with the heating piece. In this way, an atomization speed of the heating piece on the cigarette paste can be controlled, and an excessive atomization speed of the heating piece on the cigarette paste affecting a taste and experience of smoking is avoided.

(68) Further, to better control the atomization speed of the heating piece on the liquefied cigarette paste, and to facilitate gathering of the smoke in the smoke forming chamber **440**, the heating piece can be disposed close to the smoke forming chamber **440**.

(69) For example, in some implementations, the heating piece can be located on an end surface of one end, close to the smoke forming chamber **440**, of the porous piece. In other implementations, the heating piece can also be located, inside the porous piece, at one end of the porous piece close to the smoke forming chamber **440**.

(70) Further, in some implementations, to facilitate discharging of the smoke by the cigarette paste atomization device **400**, and to facilitate the smoke discharged by the cigarette paste atomization device **400** entering the nozzle **520** at the same time, a fourth atomization hole **460d** can also be formed in the side wall of the second atomization cup **420**, the fourth atomization hole **460d** is located on a side, away from the bottom of the second atomization cup **420**, of the porous member, and the fourth atomization cup **460d** enables the first atomization passage **450** to be communicated with a chamber of the second atomization cup **420**.

(71) Specifically, the smoke in the smoke forming chamber **440** is discharged from the third atomization hole **460c**, the first atomization passage **450**, and the fourth atomization hole **460d** in sequence into the chamber of the second atomization cup **420**, and finally flows from the cup opening of the second atomization cup **420** to the mouthpiece **500**.

(72) In the implementations above, the first atomization hole **460a**, the second atomization hole **460b**, the smoke forming chamber **440**, the third atomization hole **460c**, the first atomization passage **450**, the fourth atomization hole **460d**, the chamber of the second atomization cup **420**, and the cup opening of the second atomization cup **420** may form the flue of the cigarette paste atomization device **400**.

(73) In some implementations, to facilitate the cigarette atomization device **400** to be detachably disposed in the assembly cavity **110c**, the first atomization cup **410** may be provided with a second threaded seat **470a**, a second electrode **470b** is sleeved in the second threaded seat **470a**, a second insulating member **470c** is disposed between the second electrode **470b** and the second threaded

seat **470a**, and the second electrode **470b** is provided with the first atomization hole **460a**. The heating piece is electrically connected to the second threaded seat **470a** and the second electrode **470b**, respectively, so that the second threaded seat **470a** and the second electrode **470b** form positive and negative poles of the heating piece. The heating piece can extend to form two conductive portions to be electrically connected to the second threaded seat **470a** and the second electrode **470b**, respectively.

(74) When the cigarette paste atomization device **400** is connected to the assembly cavity **110c**, the second threaded seat **470a** can be in threaded connection with the first threaded seat **130a** in the assembly cavity **110c**; and at the same time, the second electrode **470b** is in contact with the first electrode **130b**, so as to achieve electric connection between the cigarette paste atomization device **400** and the main board **600** in the assembly cavity **110c**.

(75) The above-mentioned contents are only preferable embodiments of the present disclosure and are not intended to limit the present disclosure, and any modification, equivalent substitution, improvement, etc. made within the spirit and principles of some inventions shall all be included in the scope of protection of some inventions.

Claims

1. An electronic atomizer, comprising: a housing, provided with a first accommodating cavity, a second accommodating cavity, and an assembly cavity, wherein the first accommodating cavity extends facing an end part of the housing to form a first opening, the second accommodating cavity extends facing the end part of the housing to form a second opening, and the assembly cavity extends facing the end part of the housing to form a third opening; a cigarette paste cup and a paste cutting knife, wherein the cigarette paste cup is disposed in the first accommodating cavity through the first opening, and the paste cutting knife is disposed in the second accommodating cavity through the second opening; an atomization device, disposed in the assembly cavity through the third opening, wherein a first air passage being disposed in the assembly cavity, one end of the first air passage is communicated with the atomization device, and the other end of the first air passage extends to a second end of the housing to form an air inlet hole; a mouthpiece, detachably disposed on the housing, and communicated with a flue of the atomization device; a main board and a first battery, wherein the main board and the first battery are respectively disposed in the assembly cavity, the first battery is electrically connected to the main board; and wherein a side wall of the paste cutting knife is provided with a first elastic contact point; a side wall of the first accommodating cavity is provided with a second elastic contact point; the second elastic contact point is electrically connected to the main board; and when the paste cutting knife is placed in the second accommodating cavity, the first elastic contact point is in contact with the second elastic contact point to charge the paste cutting knife.

2. The electronic atomizer of claim 1, wherein the assembly cavity is internally provided with a first threaded seat and a first electrode disposed in the first threaded seat, and a first insulating member is disposed between the first threaded seat and the first electrode; the atomization device is in threaded connection with the first threaded seat, and the atomization device is in contact with the first electrode, so that the first threaded seat and the first electrode become positive and negative poles of the atomization device; a vent hole is disposed at the first electrode, and the vent hole is communicated with the first air passage and the flue of the atomization device, respectively; and the main board, and the main board is electrically connected to the first threaded seat and the first electrode, respectively.

3. The electronic atomizer of claim 1, wherein the atomization device is a cigarette paste atomization device or a cigarette oil atomization device, the cigarette paste atomization device is used for atomizing a cigarette paste, and the cigarette oil atomization device is used for atomizing cigarette oil.

4. The electronic atomizer of claim 1, further comprising an adapter, wherein the adapter is provided with a first connecting member, one end of the first air passage close to the air inlet hole is provided with a second connecting member, the adapter is disposed in the air inlet hole, and the adapter is detachably connected to the second connecting member through the first connecting member, and the adapter is communicated with the first air passage and the outside, respectively.
5. The electronic atomizer of claim 4, wherein the first adapting member comprises an adapter ring, the adapter ring is disposed on the adapter, a periphery wall of the adapter ring is provided with a first clamping and holding slot, and when the adapter rotates, the first clamping and holding slot and the second connecting member are clamped with each other; and a second end of the housing is provided with a cover body for opening or closing the air inlet hole, the cover body is provided with a through hole, and when the cover body closes the air inlet hole, the through hole is communicated with the first air passage.
6. The electronic atomizer of claim 1, wherein the first accommodating cavity extends facing a first end of the housing to form a first opening, the second accommodating cavity extends facing a second end of the housing to form a second opening, the assembly cavity extends facing the first end of the housing to form a third opening, and the mouthpiece is detachably disposed at the first end of the housing; and when the mouthpiece is disposed at the first end of the housing, the mouthpiece is capable of accommodating the cigarette paste cup and the atomization device.
7. The electronic atomizer of claim 1, wherein the paste cutting knife comprises: an outer shell; a blade, disposed at one end of the outer shell, and protruding out of the outer shell, the blade being used for cutting an article; a control board, disposed in the outer shell, the control board being electrically connected to the blade, so that the blade is capable of emitting heat; and a first elastic contact point and a second battery, wherein the first elastic contact point is disposed on a side wall of the outer shell, the second battery is disposed in the outer shell, and the first elastic contact point and the second battery are electrically connected to the control board, respectively.
8. The electronic atomizer of claim 1, wherein the cigarette paste cup comprises a carrying cup body disposed in the first assembly cavity, a side wall of the carrying cup body is provided with a cup cover for opening or closing a cup opening of the carrying cup body, and the cup cover is provided with a first magnetic member; a side wall of the housing is provided with a second magnetic member, and when the cup cover opens the cup opening of the carrying cup body, the first magnetic member is mutually magnetized with the second magnetic member; and a first end of the housing is provided with an avoidance slot for avoiding the cup cover.
9. The electronic atomizer of claim 1, wherein the mouthpiece comprises a mouth cover, a nozzle, and an air passage member, the nozzle and a ceramic member are detachably disposed on the mouth cover, respectively, and a second air passage is formed at the nozzle and the air passage member; the mouth cover is detachably connected to the housing, and the mouth cover is capable of covering the atomization device and the cigarette paste cup; the second air passage is communicated with the flue of the atomization device; and the air passage member is further provided with a smoke inlet portion, when the mouth cover is connected to the housing, the smoke inlet portion extends into the flue of the atomization device, and the smoke inlet portion is provided with a smoke inlet passage for communicating the second air passage and the flue of the atomization device.
-