

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396507
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Davis; JaLidia Denise

Reinforced separable waistband for uniform garments

Abstract

A uniform garment having a top and bottom. The bottom garment has an upper portion including a waistband, and a lower portion forming a skirt or pair of trousers. Between the upper and lower portions, a device for selectively separating the upper portion from the lower portion. The upper portion includes a supporting structure for attaching a utility or tactical belt thereto. In this manner, the utility/tactical belt is kept in place, and readily accessible, while the lower portion is selectively separated from the upper portion. The supporting structure includes a channel, anchors slidably disposed therewithin, and brackets for attaching to the anchors. The brackets support the utility/tactical belt, keeping the components thereof readily accessible. The channel may be formed on a belt that is threaded through the belt loops of the waistband portion.

Inventors:	Davis; JaLidia Denise (Montgomery, AL)
Applicant:	Davis; JaLidia Denise (Montgomery, AL)
Family ID:	1000008382495
Appl. No.:	18/786889
Filed:	July 29, 2024

Publication Classification

Int. Cl.: A41F9/00 (20060101); A41F17/00 (20060101); A41F17/02 (20060101)

U.S. Cl.:

CPC A41F9/007 (20130101); A41F9/002 (20130101); A41F17/00 (20130101); A41F17/02 (20130101);

Field of Classification Search

CPC: A41F (9/007); A41F (9/002); A41F (17/00); A41F (17/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
709823	12/1901	Mehlfeld	2/312	A41F 9/002
1037518	12/1911	Paull	2/273	A41F 17/00
1558228	12/1924	Botkin	2/300	A41F 9/002
1958643	12/1933	Silverman	24/337	A41F 17/00
3872518	12/1974	Zaoui	2/271	A41F 9/007
9015867	12/2014	Kenney	2/229	A41D 13/0017
10051948	12/2017	Carver	N/A	A45F 5/021
11147328	12/2020	Fayle	N/A	B65D 33/28
12070091	12/2023	Rodgers	N/A	A41F 17/04
2004/0083525	12/2003	Wells, Jr.	2/2.5	F41H 1/02
2005/0246820	12/2004	Davenport	2/227	A41F 9/02
2009/0070915	12/2008	Hill	2/311	A41B 1/00
2014/0317832	12/2013	Allen	2/236	A41D 1/06
2020/0390163	12/2019	Eder	N/A	A41D 15/00

Primary Examiner: Annis; Khaled

Background/Summary

(1) This application claims the benefit under 35 U.S.C. § 119(e) of U.S. Provisional Patent Application No. 63/529,347 filed on Jul. 27, 2023, and entitled “REINFORCED SEPARABLE WAISTBAND FOR UNIFORM GARMENTS,” the entire contents of which are hereby incorporated by reference herein and made part of this specification for all that they disclose.

BACKGROUND

(2) A uniform typically consists of a shirt or blouse, and a pair of trousers or a skirt. In special instances, the trousers or skirt, has a normal support belt, that is fed through belt loops spaced around the top of the trousers or skirt. In many instances, the support belt also supports an attachment belt, typically carrying a multiplicity of job-related accessories, namely referred to as an accessory belt, a utility belt, and/or tactical belt. With respect to law enforcement and military applications the attachment belt would be a tactical belt carrying, inter alia, a weapon holster.

(3) It is well known for the professional that it is a regular ordeal to become fully dressed, including the tactical belt, in uniform and be able to function within the job details. However, one

aspect of the job details, particularly with professions that require the carrying of a weapon, namely a sidearm, that the sidearm be always ready and accessible on the tactical belt. The drawback is if the professional has to take a moment to use the restroom, often the tactical belt must be removed and placed in a position that is not preferable to the job.

BRIEF SUMMARY OF THE INVENTION

(4) The present disclosure provides a relief for the uniformed professionals that allow the ability to take a restroom break without relinquishing or severely reducing the accessibility of their weapon. The present disclosure offers an improved garment, typically the trousers or skirt, hereafter the uniform bottom, to be separable. The uniform bottom will have an upper portion and a lower portion. The lower portion consists of a skirt, skort, shorts, trousers, pants, or the like. The upper portion primarily consists of a waistband. The waistband has a plurality of belt loops for threading a standard belt therethrough. The standard belt provides support of the uniform bottom about the waist/hips of the professional. The standard belt has also provided some support of the tactical belt; thus the professional would have to remove the tactical belt to access the standard belt to remove the bottom garment. By the instant disclosure, the waistband with the standard belt and the tactical belt are maintained in position about the professional, so as to allow the professional to have ready access at all times to their weapon. Moreover, the waistband of the uniform garment is further enhanced so as to support the tactical belt without interfering with the separating and attaching of the lower portion of the bottom garment.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 shows an elevational view of the preferred aspect of the invention.
- (2) FIG. 2 shows a rear elevational view of the preferred aspect of the invention.
- (3) FIG. 3 shows an elevational view of another preferred aspect of the invention.
- (4) FIG. 4 shows a diagrammatic exploded view of interior of the waistband of the preferred aspect of the invention.
- (5) FIG. 5 illustrates the separable waistband separated from the lower section of the preferred aspect of the invention.
- (6) FIG. 6 illustrates the separable waistband connected to the lower section in the preferred aspect of the invention.
- (7) FIG. 7 illustrates an alternate aspect of the invention.
- (8) FIG. 8 illustrates another embodiment of the invention.

DETAILED DESCRIPTION AND BEST MODE OF IMPLEMENTATION

(9) In FIG. 2, a uniform garment **100** having two sections, an upper section **20** and a lower section **10**. The upper section **20** contains a waistband **20**. The lower section **10** contains skirt or trousers, both **10**. It is well within the purview of this disclosure that a skirt **10** includes any garment that depends from a waistband that is not gathered between the legs. Likewise, it is within the purview of this disclosure trousers **10** include any of pants, shorts, chinos, slacks, flares, cords, breeches, strides, britches, and culottes. It is without saying that also included herein with these groupings, the skort (the combination shorts and skirt). It is noted that the specifics of this disclosure are not limited to uniform bottom garments, rather any garment that has a waistband **20** and fabric **10** depending therefrom.

(10) Between the upper **20** and lower **10** sections, as seen in FIGS. 2, 5, and 6 of the uniform bottom garment **100**, is a device **40A/B** for selectively separating the lower section **10** from the upper section **20**. The device **40A/B** for selectively separating is primarily a zipper configuration, including zipper pulls **42**, discussed herein below. It is to be understood that this disclosure is not limited to the zipper configuration **40A/B**, but rather includes a plethora of similar devices such as

buttons and button holes/loops, hook and loop fasteners, magnetic strip connectors, snaps, or clasps, or the like. For the understanding of the instant disclosure, a zipper configuration is described.

(11) The preferred zipper configuration **40** with a first zipper component **40A** attached to the lower edge of waistband **20** and a second zipper component **40B** attached to the upper edge of trousers **10**. The zipper configuration **40A/B**, in accordance with the preferred aspect of the invention, has a pair of semi-circumferential zippers **40** extending from the rear of the trousers to the front. The zipper pair is substantially hidden from view (see FIG. **6**) when the upper and lower sections are connected together. Likewise, the zipper configuration includes a single zipper that extends the entire circumference of the uniform bottom garment. Upon demand, each one of the zipper pair is disengaged via zipper pull **42**, allowing the lower section **10** of the garment **100** to be removed while maintaining the waistband **20** supporting the utility or tactical belt (not shown) intact. Upon the return of the lower section zipper parts to reengage with the waistband zipper parts, the garment is restored and the professional has maintained accessibility to the tactical belt at all times.

(12) The upper section **20** of the uniform garment has a waistband **20**, a length of material forming the waistband that encircles the waist of the professional, and with a connector **14** securing the ends together. The waistband has an interior and exterior formed by two layers of fabric material joined together at the edges. The exterior has a plurality of band members serving as belt loops spaced and permanently attached around the exterior of the waistband. The exterior has a slit extending substantially the entire length of the waistband. The slit, or aperture allows access to the interior of the waistband.

(13) The interior is equipped with a substantially rigid member **22**, as seen in FIG. **4** extending around the interior waistband. The substantially rigid member **22** is similar to a track being designed and configured as a substantially C-shaped channel. The substantially rigid member is affixed to the interior of the waistband, the opening of the substantially C-shaped channel being aligned with and accessible via the aperture of the exterior.

(14) As seen in FIG. **1**, disposed with and cooperating therein are a plurality of anchors **36**. The anchors **36** are slidably received into the substantially rigid member **22** (see FIG. **4**). The anchors **36** are selectively positioned around the C-shaped channel **22** of the rigid member. Each one of the anchors has flanges for engaging the sides of the channel, thus retaining the anchors securely in the interior of the channel. Albeit the flanges prevent the plurality of anchors **36** from exiting the opening of the C-shaped channel and the aperture, the flanges also are designed and configured to be snapped into the channel **22** via the aperture. The anchors receive a plurality of support members **30** via mechanical coupling, such as threaded bolt, snap fasteners, expandable inserts, and the like. The support members **30** are thus respectively releasably attached to each one of the anchors **36**. Each of the support members **30** has a pair of flexible straps extending therefrom, having releasable couplings **32** at the ends thereof. The flexible straps are designed and configured to encircle a utility/tactical belt, to support thereon.

(15) In an alternate configuration, as seen in FIG. **7** the substantially rigid member **22** is replaced by a pair of boning strips **22A** and **22B**. Boning strips **22A** and **22B** are attached to the interior of the waistband, in a parallel alignment about the waistband. The boning strips **22A** and **22B** are secured to the interior of the waistband and forming a receiver for the flanges of the anchors **36**. The boning strips **22A** and **22B**, along with the attachment to the interior of the waistband effectively form a C-shaped channel, having more flexibility than the aforementioned C-shaped channel **22**, yet with the same tensile strength for supporting the anchors **36** therein. Boning strips **22A** and **22B** are attached via stitching, adhesive, or any known bonding technique, as long as the anchors **36** are received therebetween. Boning strips **22A** and **22B** are fabricated from plastics or metals, as commonly recognized in the art. The boning strips **22A** and **22B** are preferably disposed within the slit, attached to the interior of the waistband however, boning strips **22A** and **22B** may be disposed along the exterior of the waistband, for easier access for inserting the anchors **36**.

(16) Upon positioning the anchors **36** and support members **30** about the waistband **20**; the professional inserts a standard belt through the belt loops **24** of the waistband **20**, superimposed to the support members **30**, and underlying the belt loops **24**. The standard belt is fashioned with any known buckle or latch for snugly yet comfortably seated upon the waist of the professional, in order to maintain the garment, i.e., the uniform garment, in proper disposition.

(17) In FIG. **8**, another aspect of the invention, the boning strips **22A** and **22B** are disposed about the standard belt **50** in order to form the channel along the length of the belt **50**. The belt **50** is threaded through the belt loops **24** of the waistband **20**, the support anchors **36** are placed within the channel formed by the boning strips **22A** and **22B**, and are preferentially distributed therearound. The channel **22** (as seen in FIG. **1**), formed by the boning strips **22A'** and **22B'**, the flanges of anchors **36** also are designed and configured to be snapped into the channel **22** between boning strips **22A'** and **22B'**. The anchors receive a plurality of support members **30** via mechanical coupling, such as threaded bolt, snap fasteners, expandable inserts, and the like. The support members **30** are thus respectively releasably attached to each one of the anchors **36**. Each of the support members **30** has a pair of flexible straps **34** extending therefrom, having releasable couplings **32** at the ends thereof. The flexible straps **34** are designed and configured to encircle a utility/tactical belt, to support thereon.

(18) The professional is provided with an accessory or a tactical belt. The accessory/tactical belt has a plethora of attachments for the professional to use, and these attachments are easily and quickly accessible when needed while the professional performs their duty or work function. The accessory/tactical belt is secured to the upper member of the garment by the plurality of support members. This securing is accomplished by the ends of the extensions of the support members being coupled together, each encircling the accessory/tactical belt about the waistband. It is well within the purview of this disclosure that the accessory/tactical belt is independently supported on the exterior of the upper portion of the garment by the plurality of support members, which are likewise supported by the plurality of anchors in the C-shaped channel.

(19) The professional has better access to the lower section of the garment for removal, if needed, by selectively disengaging the lower portion of the garment. Such needs are for toilet access, undergarment replacement, and, in the case of a professional on a menstrual cycle, or the like, without having to remove accessory/tactical belt attached to the upper portion of the garment. This is clearly evident when in circumstances of law enforcement or military professional on duty, needing to have such a toilet break, and an incident arises, the professional, though uniquely undressed, is still prepared, and has their weapon or other necessary accoutrements readily accessible because the accessory/tactical belt has not been removed. In previous instances, the accessory/tactical belt would have been removed rendering the professional vulnerable and unready for the incident.

(20) Groupings of alternative elements or embodiments disclosed herein are not to be construed as limitations. Each group member may be referred to and claimed individually or in any combination with other members of the group or other elements disclosed herein. One or more members of a group may be included in, or deleted from, a group for reasons of convenience and/or patentability. When any such inclusion or deletion occurs, the specification is deemed to contain the group as modified thus fulfilling the written description of all Markush groups used in the appended claims.

(21) The use of any and all examples, or exemplary language (e.g., "such as") provided herein is intended merely for clarification and does not pose a limitation on the scope of the present disclosure. No language in the specification should be construed as indicating any non-claimed element essential to the practice of any embodiments discussed herein. The apparatus, methods, and articles of manufacture described herein may be implemented in a variety of embodiments, and the foregoing description of some of these embodiments does not necessarily represent a complete description of all possible embodiments. Instead, the description of the drawings, and the drawings themselves, disclose at least one embodiment, and may disclose alternative embodiments.

(22) The term “substantially” when used to describe a characteristic, parameter, property, or value of an element may represent deviations or variations that do not diminish the characteristic, parameter, property, or value that the element may be intended to provide. Deviations or variations in a characteristic, parameter, property, or value of an element may be based on, for example, tolerances, measurement errors, measurement accuracy limitations and other factors. The term “proximate” is synonymous with terms such as “adjacent,” “close,” “immediate,” “nearby”, “neighboring”, etc., and such terms may be used interchangeably as appearing in this disclosure.

(23) Although certain example apparatus, methods, and articles of manufacture have been described herein, the scope of coverage of this disclosure is not limited thereto. On the contrary, this disclosure covers all apparatus, methods, and articles of articles of manufacture fairly falling within the scope of the appended claims either literally or under the doctrine of equivalents.

Claims

1. A garment comprising: an upper portion containing a waistband; the waistband having an interior and exterior; the exterior having a plurality of band members forming belt loops around the exterior of the waistband; and the exterior having an aperture to the interior of the waistband; the interior having a substantially rigid member extending around the waistband, the rigid member having a substantially C-shaped channel, the opening of the substantially C-shaped channel being accessible through the aperture of the exterior; a plurality of anchors slidably received into the substantially rigid member, each one of the anchors being selectively positioned around the C-shaped channel of the rigid member; wherein each one of the anchors have flanges, the flanges prevent the plurality of anchors from exiting the opening of the C-shaped channel and the aperture; a plurality of support members, each one of the support members respectively releasably attached to each one of the anchors; an accessory belt secured to the upper member of the garment by the plurality of support members; wherein the accessory belt is independently supported on the exterior of the upper portion by the plurality of support members and the plurality of anchors in the C-shaped channel; a lower portion extending from the waist band; a separable connector between the upper portion and the lower portion; the separable connector allowing the lower portion to be selectively disengaged from waistband of the upper portion; wherein the wearer selectively disengages the lower portion of the garment for toilet access without having to remove accessory belt attached to the upper portion of the garment.

2. The garment according to claim 1, wherein the lower portion is a pair of trousers.

3. The garment according to claim 1, wherein the lower portion is a skirt.

4. The garment according to claim 1, wherein the lower portion is a pair of shorts.

5. The garment according to claim 4, wherein the pair of shorts include a skort.

6. A utility belt support system comprising: a garment having an upper portion and a lower portion; a releasable fastener between the upper portion and the lower portion; the upper portion containing at least a waistband portion; a plurality of belt loops disposed around the waistband portion; a channel defined about the waistband portion; a plurality of anchors designed and configured to slidably engage the channel, each anchor having a pair of extensions for maintaining the anchors in the channel; wherein the plurality of anchors is selectively distributed about the channel; and a pair of support straps extending from each anchor, each pair of support straps matingly engage forming a loop from each one of the anchors; wherein each pair of the support straps encircle a utility belt, engaging the holding and maintaining the utility belt in close proximity to and about the waistband portion; whereby the releasable fastener allows the upper portion of the garment and the lower portion of the garment to be separated such that the utility belt is maintained around the waistband of the upper portion.

7. The utility belt support system according to claim 6, further comprising: a port defined in the waistband portion, the port extending substantially about the waistband portion; wherein the

channel is disposed in the interior of the waistband portion, the port providing access to the channel, the anchors being selectively placed in the channel and the support straps extending out of the port, thereby securing and supporting the utility belt to the waistband portion.

8. The utility belt support system according to claim 6, further comprising: a belt for threading through the belt loops on the waistband portion, the belt being designed and configured to have a channel thereon; wherein the channel is formed by a pair of boning strips parallelly attached to the belt.

9. The utility belt support system of claim 8, wherein the boning strips are parallelly attached to the belt, such that the channel is formed therebetween; whereby the anchors are selectively and slidably disposed about the belt and retained therein by the flange ends engaging the channel formed by the boning strips; and whereby the support straps are engaged around the utility belt, supporting and maintaining the utility belt about the waistband.
