

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396918
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Huang; Minyi et al.

Negative pressure masturbator cup

Abstract

A negative pressure masturbator cup includes an accommodating cavity, a cup main body, and a control structure. The accommodating cavity is configured to accommodate a soft colloid. The cup main body has an elastically deformable body. The control structure has a negative pressure generator. When the control structure controls the negative pressure generator to generate a negative pressure, the soft colloid is pulled by the negative pressure generated by the negative pressure generator, and the elastically deformable body is deformed in a direction towards the accommodating cavity.

Inventors:	Huang; Minyi (Shenzhen, CN), Luo; Jian (Shenzhen, CN)
Applicant:	Shenzhen Alltokee Technology Co., Ltd (Shenzhen, CN)
Family ID:	1000008431199
Assignee:	Shenzhen Alltokee Technology Co., Ltd (Shenzhen, CN)
Appl. No.:	19/038880
Filed:	January 28, 2025

Foreign Application Priority Data

CN	202520097284.4	Jan. 15, 2025
CN	202520100621.0	Jan. 15, 2025

Publication Classification

Int. Cl.: A61H19/00 (20060101); A61H9/00 (20060101)

U.S. Cl.:

CPC A61H19/32 (20130101); A61H9/0057 (20130101); A61H2201/1238 (20130101);

Field of Classification Search

CPC: A61H (2205/087); A61H (2201/1695); A61H (2201/1238); A61H (19/34); A61H (19/32); A61H (19/30); A61H (19/00); A61F (5/41)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11344470	12/2021	Sedic	N/A	A61F 5/41
11571358	12/2022	Shahoian	N/A	A61F 5/451
2023/0044372	12/2022	Liu	N/A	A61H 9/0007

Primary Examiner: Gilbert; Samuel G

Attorney, Agent or Firm: ScienBiziP, P.C.

Background/Summary

CROSS-REFERENCE

(1) This application claims the benefit of priorities from the following patent applications filed in China: Chinese Patent Application Ser. No. CN 202520100621.0, filed on Jan. 15, 2025, and Chinese Patent Application Ser. No. CN 202520097284.4, filed on Jan. 15, 2025.

TECHNICAL FIELD

(2) The present invention relates to the field of adult products, in particular to a negative pressure masturbator cup.

BACKGROUND ART

(3) In a background of continuing development of the adult product market, a masturbator cup is a common and widely used sexual product. However, most of the masturbator cups on the market have certain limitations in the cup structure. For example, the cup diameter is usually fixed, which means that in the process of use, the masturbator cup only provides relatively single and monotonous stimulation manners, and may not provide a favorable experience.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a three-dimensional diagram showing a negative pressure masturbator cup of the present disclosure.
- (2) FIG. 2 is an exploded three-dimensional diagram showing main components of the negative pressure masturbator cup shown in FIG. 1.
- (3) FIG. 3 is a sectional view showing the negative pressure masturbator cup shown in FIG. 1.
- (4) FIG. 4 is a schematic three-dimensional diagram showing a sectioned portion of the negative pressure masturbator cup of shown in FIG. 1.
- (5) FIG. 5 is an enlarged view showing part III of FIG. 3.
- (6) FIG. 6 is a schematic diagram showing a state of use of the negative pressure masturbator cup.

DETAIL DESCRIPTION

(7) Referring to FIG. 1 to FIG. 6, the negative pressure masturbator cup **1000** with an adjustable inner diameter in the embodiment of the present disclosure is of a cylinder structure as a whole, and includes an outer cylinder **50**, a cup main body **101**, a soft colloid **70**, and a control structure **80**.

(8) As shown in FIG. 3 to FIG. 6, a clearance cavity **300** is formed inside the outer cylinder **50**, and the clearance cavity **300** is configured to accommodate and mount the cup main body **101** and the control structure **80**. End edges at each side of the outer cylinder **50** and the cup main body **101** are open and are removably connected, and the bottom of the outer cylinder **50** and the bottom of the cup main body **101** are spaced apart, such that the above clearance cavity **310** is formed between the outer cylinder **50** and the cup main body **101**. The clearance cavity **310** includes a first cavity **310a** arranged between a bottom wall **101a** of the cup main body **101** and a bottom wall **50a** of the outer cylinder **50** and a second cavity **310b** arranged between a side wall **101b** of the cup main body **101** and a side wall **50b** of the outer cylinder **50**, and the two cavities **310a** and **310b** are connected to each other. In the present embodiment, the outer cylinder body **50** further includes an opening portion **501** corresponding to the opening of the cylinder body and a bottom **502** corresponding to the bottom wall **50a**, and the depth of the cup main body **101** is less than the depth of the outer cylinder body **50**, and the inner diameter decreases gradually from the opening portion **501** towards the bottom **502**, thereby forming the first cavity **310a** and the second cavity **310b**. It should be appreciated that, in other embodiments, the cup main body and the outer cylinder may also have other structures and shapes. A first vent **1011** and a second vent **1012** are formed on the bottom wall **101a** of the cup main body **101**, and the first vent **1011** and the second vent **1012** penetrate through the bottom wall **101a**, respectively, such that the second cavity **310b** is connected with an inner cavity **500** of the cup main body **101**, and a gas channel is formed between the first cavity **310a**, the second cavity **310b** and the inner cavity **500** of the cup main body **101**.

(9) The inner cavity **500** of the cup main body **101** is formed as an accommodating cavity for accommodating the soft colloid **70**. The gap between the cup main body **101** and the soft colloid **70** is formed as a controllable gas cavity **100**. Specifically, the controllable gas cavity **100** is formed by clamping gas between a first wall surface **1001**, which is the outer surface **1001** of the soft colloid **70**, and a second wall surface **1002**, which is the inner surface **1002** of the cup main body **101**. The first wall surface **1001** and the second wall surface **1002** are spaced apart from each other. The controllable gas cavity **100** becomes a negative pressure state by discharging gas through the control structure **80**, so that a portion of the side wall **101b** of the cup main body **101** has a function of adjusting the inner diameter. The cup main body **101** includes a hard material portion and an elastically deformable body **20** exposed to the accommodating cavity and forming a portion of a side wall of the cup main body **101**, and the hard material portion and the elastically deformable body **20** are connected in a sealing manner to connect the elastically deformable body **20** to the outer cylinder **50**. The elastically deformable body **20** may be deformed concavely towards the side of the cup main body **101** under the effect of a gas pressure difference, thereby changing the inner diameter of the side wall **101b** of the cup main body **101**. In the present embodiment, the elastically deformable body **20** is an annular elastic material layer having a pre-determined width, and acts as a portion of the side wall **101b** of the cup main body **101**. A thickness of the elastic material layer at a periphery region of the elastically deformable body **20** is greater than a material thickness of the elastic material layer at a middle region of the elastically deformable body **20**, thereby forming a concave region X with a U-shaped cross-section in the middle region between the two peripheries. This structure is more conducive to maintaining a certain shape of the elastically deformable body, and is more conducive to fixation and shrinkage deformation thereof. The hard material portion is sleeved on the elastically deformable body **20** and is adapted to the periphery of the elastically deformable body **20**. In the present embodiment, the hard material portion includes a clamping member **40** sleeved to the middle region of the elastically deformable body **20**, the clamping member **40** includes a first clamping portion **40a** and a second clamping portion **40b**, the first

clamping portion **40a** and the second clamping portion **40b** are arranged opposite to each other and are sleeved to the middle region of the elastically deformable body **20** corresponding to the concave region X. In some embodiments, a convex rib is arranged at the middle region of the elastically deformable body **20**, and two opposite ends of the first clamping portion **40a** and the second clamping portion **40b** are arranged in close proximity on two opposite sides of the convex rib.

(10) The hard material portion further includes a cup body portion **10**, and the elastically deformable body **20** are sandwiched between the cup body portion **10** and the clamping member **40**, such that the hard material portion and the elastically deformable body **20** are connected tightly.

(11) The cup body portion **10** covers each end edge of the elastically deformable body **20** from one side of the elastically deformable body **20**, e.g., an inner side, and the material hardness of the cup body portion **10** is greater than that of the elastically deformable body **20**. The clamping member **40** covers the end edge of the elastically deformable body **20** from the other side of the elastically deformable body **20**, e.g., an outer side, and the hardness of the clamping member **40** is also greater than that of the elastically deformable body **20**. The cup body portion **10** has a hardness higher than a hardness of the elastically deformable body **20**, and the clamping member **40** has a hardness higher than the hardness of the elastically deformable body **20**, such that the cup body portion **10** and the clamping member **40** stably maintain the elastically deformable body **20**.

(12) Each end edges of the elastically deformable body **20** is sealed by being sandwiched between the cup body portion **10** and the clamping member **40**, such that a wall surface of the cup body portion **10** is sealed. The elastically deformable body **20** is provided with a first upper clamping portion **21** at the periphery of the upper end and is provided with a first lower clamping portion **22** at the periphery of the lower end. At one side of the elastically deformable body **20**, the first hard material portion is provided with a cup mouth portion **110** at an upper end of the elastically deformable body **20** and is provided with a cup bottom portion **130** at a lower end of the elastically deformable body **20**. The cup mouth portion **110** forms the cup mouth of the cup main body **101** and covers the upper end of the elastically deformable body **20**, and the cup mouth portion **110** is provided with a second upper clamping portion **111** corresponding to the first upper clamping portion **21**. The cup bottom portion **30** forms a cup bottom of the cup main body **101** and covers the lower end of the elastically deformable body **20**, and the cup bottom portion **30** is provided with a second lower clamping portion **131** corresponding to the first lower clamping portion **22**. At the other side of the elastically deformable body **20**, a third upper clamping portion **41** is arranged at an upper end of the second hard material portion **40** corresponding to the first upper clamping portion **21**, and a third lower clamping portion **42** is arranged at a lower end of the second hard material portion **40** corresponding to the first lower clamping portion **22**, such that the second upper clamping portion **111** and the third upper clamping portion **41** are buckled to both sides of the first upper clamping portion **21** of the elastically deformable body **20** in a clamping manner, and the second lower clamping portion **131** and the third lower clamping portion **42** are buckled to both sides of the first lower clamping portion **22** of the elastically deformable body **20** in a clamping manner, then the hard material portion and the elastically deformable body **20** are tightly connected, and the cup main body **101** has a simple structure and is easy to mount.

(13) Herein, an airbag space **200** may be formed between the side, opposite to a side of the controllable gas cavity **100**, of the elastically deformable body **20** and the clamping member **40**. The airbag space **200** may be in an atmospheric pressure state, but the airbag space **200** may also not be limited to the atmospheric pressure state as long as the pressure in the airbag space **200** is higher than that in the controllable gas cavity **100** and is sufficiently high to allow the elastically deformable body **20** to be deformed concavely.

(14) The soft colloid **70** is accommodated in the accommodating cavity **500** of the cup main body **101**, and is made of soft materials such as silicone, rubber, and other soft materials with good skin-friendliness and high softness. The soft colloid **70** is internally provided with an accommodating

channel **700** connected to the outside, and one end of the accommodating channel **700** is open to form an accommodating port **701**, and the other end is closed. The accommodating channel **700** is configured to accommodate the penis (sexual organ) **1**. The soft colloid **70**, due to its own material properties, effectively blocks the cup mouth of the cup main body **101**, ensuring effective sealing between the soft colloid **70** and the cup main body **101**. This facilitates the control of the gas pressure in the controllable gas cavity **100** between the soft colloid **70** and the cup main body **101** by the control structure **80**, and therefore the gas between the soft colloid **70** and the cup main body **101** is sometimes also called the controllable gas cavity **100**. In the outer cylinder **50**, the accommodating channel **700** is located at the center, and the controllable gas cavity **100** is arranged on the periphery with the accommodating channel **700** at the center. Moreover, the gap cavity **300** is arranged on the periphery of the controllable gas cavity **100**.

(15) In the controllable gas cavity **100**, the first wall surface **1001** is closer to the accommodating channel **700** than the second wall surface **1002**. Under atmospheric pressure, one side of the elastically deformable body **20** communicates with the controllable gas cavity **100** and the first wall surface **1001** is spaced apart from the second wall surface **1002**. In other words, a gap defines between the elastically deformable body **20** and the soft colloid **70**, thereby ensuring a space for the elastically deformable body **20** to be deformed concavely. Another side of the elastically deformable body **20** is isolated from the controllable gas cavity **100**. When the controllable gas cavity **100** is controlled to have a gas pressure lower than the gas pressure at the other side of the elastically deformable body **20**, the controllable gas cavity **100** becomes a negative pressure, and under this negative pressure, the elastically deformable body **20** is deformed concavely towards the side of the cup main body **101** under a gas pressure difference, and with an increase in the gas pressure difference, the elastically deformable body **20** gradually contacts with and squeezes the accommodating channel **700** of the soft colloid **70** to deform the accommodating channel **700**. Specifically, the elastically deformable body **20** squeezes the first wall surface **1001** to move towards the center of the accommodating channel **700**, forcing a portion of the accommodating channel **700** to recess towards the center (i.e., to narrow). On the other hand, the part of the soft colloid **70** that is not arranged opposite to the elastically deformable body **20** bulges and deforms to moves closer to the second wall surface **1002** in a direction away from the accommodating channel **700** under the effect of the negative pressure. At this time, the bottom surface **702** of the soft colloid **70** may be pulled by the negative pressure to approach the bottom wall **101a** of the cup main body **101**. Therefore, in addition to the radial deformation, the depth (i.e., length) of the accommodating channel **700** may also become longer under the negative pressure.

(16) In some embodiments of the present disclosure, in order to further ensure sealing between the soft colloid **70** and the cup main body **101**, a sealing ring **60** is arranged between the soft colloid **70** and the cup main body **101**.

(17) In some embodiments of the present disclosure, the inner wall of the accommodating channel **700** may be designed to present a shape of wrinkles, bumps and the like, thereby enriching sexual experience from a tactile level by contacting with and rubbing against the penis **1**, and providing the user with delicate and layered stimulation feelings.

(18) The control structure **80** is accommodated within the first cavity **310a**. The control structure **80** includes a negative pressure generator **81** controlled by the control structure **80**, an electromagnetic valve **82** controlled by the control structure **80**, a battery **83**, a control circuit **84**, and other electronic components. The negative pressure generator **81** is connected to the controllable gas cavity **100**, and the negative pressure generator **81** is controlled by the control structure **80** to generate a negative pressure, such that when the negative pressure generator **81** is controlled to operate, gas in the controllable gas cavity **100** is discharged, so as to gradually form a negative pressure, i.e., forming a vacuum cavity. In the present disclosure, "vacuum cavity" includes a vacuum state and a near-vacuum state. When the negative pressure generator **81** operates to form a vacuum cavity in the controllable gas cavity **100**, the soft colloid **70** is stretched inside

the controllable gas cavity **100** through its own material properties, and an inner wall of the soft colloid **70** exerts a tensile force on the penis **1** towards a direction of the cup body of the cup main body **101**, so as to stimulate the penis **1**.

(19) In some embodiment of the present disclosure, the negative pressure generator **81** is connected to the controllable gas cavity **100** through the first vent **1011**.

(20) When the negative pressure generator **81** is controlled to generate the negative pressure, a gas discharge channel to discharge is formed from an interior of the cup main body **101** to the first vent **1011**, and the electromagnetic valve **82** is controlled to close the second vent **1012** to block air flow from an exterior of the cup main body **101** into the interior of the cup main body. As time passes, the controllable gas cavity **100** becomes the negative pressure state.

(21) When the negative pressure generator **81** is not controlled (i.e. turned off) to generate the discharge to generate the negative pressure, the electromagnetic valve **82** is controlled to establish a connection between the controllable gas cavity **100** and the clearance cavity **310**, opens the second vent **1012** to facilitate the air flow gas from the exterior of the cup main body **101** into the interior of the cup main body **101** through the second vent **1012**. As time passes, the amount of gas in the controllable gas cavity **100** gradually increases, and the controllable gas cavity **100** restores to the atmospheric pressure state.

(22) The battery **83** provides power required for operation to various electronic components. The control circuit **84** controls the action of each electronic component and may include an operation portion **841** such as control buttons, switch buttons.

(23) The elastically deformable body **20** is annularly arranged on the side wall **101b** of the cup main body **101**, exerting a squeezing force on the soft colloid **70** in its circumferential direction, thereby bringing a sexually stimulating experience that is different from a pulling force of the negative pressure exerted directly on the soft colloid **70**. Owing to tight connection between the hard material portion and the elastically deformable body **20**, gas between the elastically deformable body **20** and the hard material portion is effectively sealed, and since gas between the soft colloid **70** and the cup main body **101** is effectively sealed, gas in the controllable gas cavity **100** can be controlled reliably.

(24) In some embodiments of the present disclosure, the cup main body **101** may be a whole body, the hard material portion is an integrated structure, the hard material portion is connected to the elastically deformable body **20** and the connecting portion is fused to be integrated, such that the hard material portion and the elastically deformable body **20** are tightly connected, and the structure in this manner is simpler.

(25) In some embodiments of the present disclosure, the elastically deformable body **20** is annularly arranged on the side wall **101b** of the cup main body **101**, and the hard material portion includes a cup mouth wall portion forming a cup mouth of the cup main body and a cup bottom wall portion forming a cup bottom of the cup main body. By using the elasticity of the elastically deformable body **20**, the elastically deformable body **20** is elastically sleeved between the cup mouth wall portion and the cup bottom wall portion, and the hard material portion and the elastically deformable body **20** are tightly connected, and in this method, the structure is simple and mounting is easy.

(26) In some embodiments of the present disclosure, the airbag space **200** may define one or more regions as desired, such that the elastically deformable body **20** forms one or more structures corresponding to each of the one or more regions of the airbag space **200**, the one or more structures of the deformable body **20** are deformed concavely toward the side of the cup main body **101**, and such structures play an important role in subsequent use. The height, size and shape of the recesses may be the same or different between the plurality of regions.

(27) In some embodiments of the present disclosure, the elastically deformable body **20** comprises a plurality of elastically deformable sub-bodies **20** which are arranged on a side wall **101b** of the cup main body **101**, e.g., a plurality of elastically deformable bodies **20** may be spaced apart along

a direction that is intersected with the radial direction, thereby realizing diversified stimulation feelings and satisfying the needs of different users.

(28) In some embodiments of the present disclosure, the side wall **50b** of the outer cylinder **50** is provided with a light-transmitting viewable window **51**, and an opening is formed to penetrate through the overlapping portion of the viewable window **51** of the soft colloid **70**, such that the soft colloid **70** will not block the viewable window **51**, and the user can observe the changing state of the accommodating channel **700** through the viewable window **51**. In particular, when the elastically deformable body **20** is arranged facing towards the viewable window **51**, the user can visually observe a change in the state of the soft colloid **70** as the soft colloid **70** gradually rises under the squeezing of the elastically deformable body **20** through the viewable window **51**, so as to enrich the sexual experience from a visual level. When the negative pressure masturbator cup **1000** of the present disclosure is used, as shown in FIG. 6, the penis **1** is placed in the accommodating channel **700** of the soft colloid **70**. The button **841** is operated to trigger the negative pressure generator **81** to operate, and the electromagnetic valve **82** seals the controllable gas cavity **100** from the external gas. Gas in the controllable gas cavity **100** within the cup main body **101** is discharged by the negative pressure generator **81** such that the gas pressure in the controllable gas cavity **100** gradually decreases. A negative pressure is generated at one side of the elastically deformable body **20**, and the two sides of the elastically deformable body **20** are under a pressure higher than the negative pressure, that is, in the atmospheric pressure state, therefore a gas pressure difference is generated between the two sides. Under the negative pressure, the elastically deformable body **20** is elastically deformed towards the side of the accommodating channel **700**, and the accommodating channel **700** of the soft colloid **70** is squeezed and deformed. As a result, the soft colloid **70** is stretched and moves towards the bottom of the cup main body **101**, and the inner diameter of the soft colloid **70** narrows, providing diversified stimulating experiences to the user. In addition, since the negative pressure masturbator cup **1000** of the present disclosure has a simple structure, the hand-held operation is durable.

(29) After use, the button **841** is operated to trigger the negative pressure generator **81** to stop operating, the electromagnetic valve **82** connects the controllable gas cavity **100** to the external gas, and the external gas flows into the controllable gas cavity **100** under a gas pressure difference until the controllable gas cavity **100** restores to the atmospheric pressure state. At this time, the soft colloid **70** is removed for easy cleaning.

(30) The negative pressure masturbator cup **1000** of the present disclosure has an adjustable inner diameter and provide adult users with a rich and diversified sexual experience under the premise of lawfulness, privacy and compliance with public order and morality.

Claims

1. A negative pressure masturbator cup comprising: an accommodating cavity configured to accommodate a soft colloid, the soft colloid provided with an accommodating channel connected to an exterior of the negative pressure masturbator cup, and the accommodating channel configured to accommodate a sexual organ; a cup main body comprising an elastically deformable body, the elastically deformable body exposed to the accommodating cavity and acting as a portion of a side wall of the cup main body; and a control structure comprising a negative pressure generator, the control structure controlling the negative pressure generator to generate a negative pressure, wherein when the control structure controls the negative pressure generator to generate the negative pressure, the soft colloid is pulled by the negative pressure generated by the negative pressure generator, and the elastically deformable body is deformed in a direction towards the accommodating cavity.

2. The negative pressure masturbator cup according to claim 1, further comprising a controllable gas cavity between the cup main body and the soft colloid, the controllable gas cavity being sealed;

wherein the negative pressure generator is connected to the controllable gas cavity, when the negative pressure generator is controlled to generate the negative pressure, gas in the controllable gas cavity is discharged, and the elastically deformable body is deformed concavely towards a side of the controllable gas cavity while the soft colloid is squeezed into the accommodating channel thereby changing an inner diameter of the accommodating channel.

3. The negative pressure masturbator cup according to claim 1, wherein when the negative pressure generator is controlled to generate the negative pressure, a gas pressure difference is generated between two sides of the elastically deformable body, and the elastically deformable body deforms towards a side of the two sides having a lower gas pressure, and when the negative pressure generator is not controlled to generate the negative pressure, a gap is defined between the elastically deformable body and the soft colloid.

4. The negative pressure masturbator cup according to claim 1, wherein the elastically deformable body is annularly arranged on the side wall of the cup main body.

5. The negative pressure masturbator cup according to claim 1, wherein the elastically deformable body comprises a plurality of elastically deformable sub-bodies, the plurality of elastically deformable sub-bodies is arranged on the side wall of the cup main body.

6. The negative pressure masturbator cup according to claim 1, wherein the elastically deformable body is made of an elastic material layer having a pre-determined width, and a thickness of the elastic material layer at a periphery region of the elastically deformable body is greater than a thickness of the elastic material layer at a middle region of the elastically deformable body, thereby forming a concave region in the middle region.

7. The negative pressure masturbator cup according to claim 1, wherein the cup main body further comprises a hard material portion connected to the elastically deformable body.

8. The negative pressure masturbator cup according to claim 7, wherein the elastically deformable body is annularly arranged on the side wall of the cup main body, the hard material portion comprises: a cup body portion having a hardness higher than a hardness of the elastically deformable body; and a clamping member having a hardness higher than the hardness of the elastically deformable body, each end edges of the elastically deformable body is sealed by being sandwiched between the cup body portion and the clamping member, such that a wall surface of the cup body portion is sealed; the negative pressure masturbator cup further comprising a controllable gas cavity between the cup main body and the soft colloid, the controllable gas cavity is sealed, wherein one side of the elastically deformable body communicates with the controllable gas cavity; an airbag space is formed between another side of the elastically deformable body and the clamping member; when the negative pressure generator is controlled to generate the negative pressure, the negative pressure is formed in the controllable gas cavity, a gas pressure in the airbag space is greater than the negative pressure in the controllable gas cavity, and the airbag space defines one or more regions, such that the elastically deformable body forms one or more structures corresponding to each of the one or more regions of the airbag space, the one or more structures of the deformable body are deformed concavely toward the side of the cup main body.

9. The negative pressure masturbator cup according to claim 8, wherein the cup body portion comprises: a cup mouth portion forming an opening of the cup main body and covering an upper end of the elastically deformable body; and a cup bottom portion forming a cup bottom of the cup main body and covering a lower end of the elastically deformable body.

10. The negative pressure masturbator cup according to claim 1, further comprising: a first vent and a second vent, each of the first and the second vents penetrating through the cup main body; and the control structure further comprising an electromagnetic valve, wherein when the negative pressure generator is controlled to generate the negative pressure, a gas discharge channel to discharge gas is formed from an interior of the cup main body to the first vent, and the electromagnetic valve closes the second vent to prevent air from flowing from an exterior of the cup main body into the interior of the cup main body; and when the negative pressure generator is

not controlled to generate the negative pressure, the electromagnetic valve opens the second vent to allow the air to flow from the exterior of the cup main body into the interior of the cup main body through the second vent.

11. A negative pressure masturbator cup comprising: an outer cylinder, an interior of the outer cylinder comprising an accommodating channel located at a center of the outer cylinder, wherein the accommodating channel is configured to accommodate a sexual organ; a controllable gas cavity disposed adjacent to the accommodating channel and isolated from the accommodating channel; a first wall surface and a second wall surface which cooperatively define the controllable gas cavity, wherein the first wall surface is opposite to the second wall surface, and the first wall surface is disposed closer to the accommodating channel than the second wall surface; and a negative pressure generator connected to the controllable gas cavity, when the negative pressure generator operates to generate a negative pressure in the controllable gas cavity, a portion of the second wall surface bulges and deforms towards the accommodating channel and squeezes the first wall surface, the first wall surface then recesses towards the center of the outer cylinder.

12. The negative pressure masturbator cup according to claim 11, further comprising: a cup main body accommodated inside the outer cylinder and comprising an elastically deformable body, the second wall surface is an inner surface of the cup main body; and a soft colloid accommodated inside the cup main body, the first wall surface is an outer surface of the soft colloid, wherein when the negative pressure generator operates to generate the negative pressure in the controllable gas cavity, the elastically deformable body elastically deforms towards the accommodating channel, such that the inner surface of the cup main body bulges and deforms towards the accommodating channel and squeezes the first wall surface; when the negative pressure generator turns off, the first wall surface and the elastically deformable body separate from each other.

13. The negative pressure masturbator cup according to claim 11, wherein the first wall surface has an unsqueezed portion that is not squeezed by the second wall surface when the negative pressure generator operates to generate the negative pressure in the controllable gas cavity, and the unsqueezed portion is configured to move closer to the second wall surface in a direction away from the accommodating channel when the negative pressure generator operates to generate the negative pressure in the controllable gas cavity.

14. The negative pressure masturbator cup according to claim 11, wherein the elastically deformable body is annularly arranged on a side wall of the cup main body.

15. The negative pressure masturbator cup according to claim 11, wherein the elastically deformable body comprises a plurality of elastically deformable sub-bodies, the plurality of elastically deformable sub-bodies is arranged on the side wall of the cup main body.

16. The negative pressure masturbator cup according to claim 11, wherein the elastically deformable body is made of an elastic material layer having a pre-determined width, and a thickness of the elastic material layer at a periphery region of the elastically deformable body is greater than a thickness of the elastic material layer at a middle region of the elastically deformable body, thereby forming a concave region in the middle region.

17. The negative pressure masturbator cup according to claim 11, wherein the cup main body further comprises a hard material portion connected to the elastically deformable body.

18. The negative pressure masturbator cup according to claim 17, wherein the elastically deformable body is annularly arranged on the side wall of the cup main body, the hard material portion comprises: a cup body portion having a hardness higher than a hardness of the elastically deformable body; and a clamping member having a hardness higher than the hardness of the elastically deformable body, each end edges of the elastically deformable body is sealed by being sandwiched between the cup body portion and the clamping member, such that a wall surface of the cup body portion is sealed; the negative pressure masturbator cup further comprising a controllable gas cavity between the cup main body and the soft colloid, the controllable gas cavity is sealed, wherein one side of the elastically deformable body communicates with the controllable gas cavity;

an airbag space is formed between another side of the elastically deformable body and the clamping member; when the negative pressure generator is controlled to generate the negative pressure, the negative pressure is formed in the controllable gas cavity, a gas pressure in the airbag space is greater than the negative pressure in the controllable gas cavity, and the airbag space defines one or more regions, such that the elastically deformable body forms one or more structures corresponding to each of the one or more regions of the airbag space, the one or more structures of the deformable body are deformed concavely toward the side of the cup main body.

19. The negative pressure masturbator cup according to claim 18, wherein the cup body portion comprises: a cup mouth portion forming an opening of the cup main body and covering an upper end of the elastically deformable body; and a cup bottom portion forming a cup bottom of the cup main body and covering a lower end of the elastically deformable body.

20. The negative pressure masturbator cup according to claim 11, further comprising: a first vent and a second vent, each of the first and the second vents penetrating through the cup main body; and an electromagnetic valve, wherein when the negative pressure generator is controlled to generate the negative pressure, a gas discharge channel to discharge gas is formed from an interior of the cup main body to the first vent, and the electromagnetic valve closes the second vent to prevent air from flowing from an exterior of the cup main body into the interior of the cup main body; and when the negative pressure generator is not controlled to generate the negative pressure, the electromagnetic valve opens the second vent to allow the air to flow from the exterior of the cup main body into the interior of the cup main body through the second vent.
