

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399763
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Bell; Debra M et al.

Persistent health monitoring for volatile memory systems

Abstract

Methods, systems, and devices for persistent health monitoring for volatile memory devices are described. A memory device may determine that an operating condition associated with an array of memory cells on the device, such as a temperature, current, voltage, or other metric of health status is outside of a range associated with a risk of device degradation. The memory device may monitor a duration over which the operating condition is outside of the range, and may determine whether the duration satisfies a threshold. In some cases, the memory device may store an indication of when (e.g., each time) the duration satisfied the threshold. The memory device may store the one or more indications in one or more non-volatile storage elements, such as fuses, which may enable the memory device to maintain a persistent indication of a cumulative duration over which the memory device is operated with operating conditions outside of the range.

Inventors: Bell; Debra M (Boise, ID), Hopper; Kristen M. (Boise, ID), Prosser; Erika (Boise, ID), Boehm; Aaron P. (Boise, ID)

Applicant: Micron Technology, Inc. (Boise, ID)

Family ID: 1000008777375

Assignee: Micron Technology, Inc. (Boise, ID)

Appl. No.: 17/956551

Filed: September 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230028176 A1	Jan. 26, 2023

Related U.S. Application Data

continuation parent-doc US 16433820 20190606 US 11481265 child-doc US 17956551

Publication Classification

Int. Cl.: **G06F11/00** (20060101); **G06F1/20** (20060101); **G06F1/30** (20060101); **G06F3/06** (20060101); **G06F11/07** (20060101); **G06F11/30** (20060101)

U.S. Cl.:

CPC **G06F11/0766** (20130101); **G06F1/206** (20130101); **G06F1/305** (20130101); **G06F3/0616** (20130101); **G06F11/3037** (20130101);

Field of Classification Search

CPC: G06F (11/0766); G06F (11/3037); G06F (1/305); G06F (3/0616)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6456928	12/2001	Johnson	714/48	F02B 77/08
7350046	12/2007	Sicola	711/170	G06F 11/0751
7852692	12/2009	Zhang	365/189.11	G11C 29/50012
7882394	12/2010	Hosek	714/48	G06F 11/008
7908606	12/2010	Depro	705/412	G06Q 50/06
8078918	12/2010	Diggs	714/42	G06F 11/008
8175254	12/2011	Li	379/265.14	H04L 41/147
8374823	12/2012	Williams	714/728	G06F 11/3058
8949181	12/2014	Stokkan	707/618	G06N 5/04
9152568	12/2014	Seigler et al.	N/A	N/A
9224456	12/2014	Cometti	N/A	G11C 16/06
9280200	12/2015	Glassburn et al.	N/A	N/A
11869619	12/2023	Lee	N/A	G11C 29/52
2007/0180328	12/2006	Cornwell	714/E11.038	G11C 29/56
2007/0263444	12/2006	Gorobets	365/185.09	G11C 16/349
2009/0175076	12/2008	Cho	365/189.011	G11C 16/349
2009/0204852	12/2008	Diggs et al.	N/A	N/A
2010/0061168	12/2009	Aakjer	365/201	G11C 29/4401
2012/0239991	12/2011	Melik-Martirosian	N/A	N/A
2013/0289909	12/2012	Lin	702/182	G06F 17/00
2013/0338450	12/2012	Osorio	600/300	A61B 5/746
2014/0229774	12/2013	Melik-Martirosian	714/704	G06F 3/0634

2014/0245108	12/2013	Gaertner et al.	N/A	N/A
2014/0247665	12/2013	Avila	365/185.17	G11C 29/02
2014/0269083	12/2013	Mui et al.	N/A	N/A
2016/0048347	12/2015	Rangarajan	711/156	G06F 11/2092
2017/0097779	12/2016	Steinmacher- Burow	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103176748	12/2012	CN	N/A
105027215	12/2014	CN	N/A
10-2008-0021853	12/2007	KR	N/A
2009/032945	12/2008	WO	N/A

OTHER PUBLICATIONS

European Patent Office, “Supplementary European Search report and Search Opinion,” issued in connection with European Patent Application No. 20817669.3 dated Dec. 15, 2022 4 pages. cited by applicant

Chinese patent office, “China Office Action,” issued in connection with China Patent Application No. 202080047463.7 dated Dec. 20, 2024 (29 pages) (16 pages of English Translation and 13 pages of Original Document). cited by applicant

Primary Examiner: Riad; Amine

Attorney, Agent or Firm: Holland & Hart LLP

Background/Summary

CROSS REFERENCE (1) The present Application for Patent is a continuation of U.S. patent application Ser. No. 16/433,820 by Bell, et al., entitled “PERSISTENT HEALTH MONITORING FOR VOLATILE MEMORY SYSTEMS”, filed Jun. 6, 2019, assigned to the assignee hereof, and is expressly incorporated by reference in its entirety herein.

BACKGROUND

(1) The following relates generally to systems that include at least one memory device and more specifically to persistent health monitoring for volatile memory devices.

(2) Memory devices are widely used to store information in various electronic devices such as computers, wireless communication devices, cameras, digital displays, and the like. Information is stored by programing different states of a memory device. For example, binary devices most often store one of two states, often denoted by a logic 1 or a logic 0. In other devices, more than two states may be stored. To access the stored information, a component of the device may read, or sense, at least one stored state in the memory device. To store information, a component of the device may write, or program, the state in the memory device.

(3) Various types of memory devices exist, including magnetic hard disks, random access memory (RAM), read-only memory (ROM), dynamic RAM (DRAM), synchronous dynamic RAM (SDRAM), ferroelectric RAM (FeRAM), magnetic RAM (MRAM), resistive RAM (RRAM), flash memory, phase change memory (PCM), and others. Memory devices may be volatile or non-volatile. Non-volatile memory, e.g., FeRAM, may maintain their stored logic state for extended

periods of time even in the absence of an external power source. Volatile memory devices, e.g., DRAM, may lose their stored state when disconnected from an external power source.

(4) In some cases, a memory device may be used within a system that is configured for or specifies a high level of reliability. Such systems may include, for example, automotive or other safety-related systems. The health of a memory device may degrade over time, however, which may lead to memory errors.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an example of a system that supports persistent health monitoring for volatile memory devices in accordance with examples as disclosed herein.

(2) FIG. 2 illustrates an example of a memory die that supports persistent health monitoring for volatile memory devices in accordance with examples as disclosed herein.

(3) FIG. 3 illustrates an example of a system **300** that supports persistent health monitoring for volatile memory devices in accordance with examples as disclosed herein.

(4) FIG. 4 shows a block diagram of a memory array that supports persistent health monitoring for volatile memory devices in accordance with aspects of the present disclosure.

(5) FIG. 5 shows a flowchart illustrating a method or methods that support persistent health monitoring for volatile memory devices in accordance with examples as disclosed herein.

DETAILED DESCRIPTION

(6) In some cases, a memory device may be used within a system that is configured for or specifies a high level of reliability. Such systems may include, for example, automotive or other systems where safety is a substantial concern. A memory device may degrade over time due to various factors. Such degradation may cause errors in the memory device, which may be particularly problematic for these systems. Thus, in some cases, it may be desirable to monitor the health of a memory device to identify or predict degradation of the memory device before it reaches a significant or dangerous level.

(7) In some cases, a memory device may degrade more quickly when it is operated under relatively demanding or severe operating conditions, such as when it is operated at higher temperatures, higher voltages, higher workloads, etc. Such operating conditions may be considered higher-risk operating conditions because a memory device may degrade more quickly when it is operated under severe operating conditions than when it is operated under less demanding conditions. In some cases, even operating a memory device in the upper portion of its rated operating range may be considered as operating under severe conditions and may result in faster degradation over time than operating the memory device in a more moderate portion of its rated operating range. Thus, in some cases, it may be possible to determine or identify a lower-risk range of operating conditions for a memory device that is associated with slower device degradation, and a higher-risk range of operating conditions (possibly including portions of the rated operating range) associated with faster device degradation.

(8) In some cases, the degradation of a memory device may be predicted by monitoring the amount of time during which the device is operated under severe operating conditions; e.g., when the device is operated under operating conditions that are outside of a low-risk range. For example, a memory device may include one or more sensors, such as temperature or voltage sensors, to detect when the memory device is operated under severe operating conditions (e.g., one or more operating conditions is outside of a low-risk range), and a timer to determine the duration over which the memory device is operated under the severe operating conditions.

(9) In some cases, it may be useful to store a record of the cumulative duration over which a memory device is operated under severe operating conditions. However, volatile memory devices,

such as memory devices based on DRAM, may lose their state information each time the memory device is turned off. Such memory devices may lack a mechanism for tracking the cumulative amount of time during which the memory device is operated under severe operating conditions across periods during which the device is powered off. For example, if a memory device is operated under severe conditions for some quantity of minutes each time it is active, but loses this information when it is powered down, the cumulative duration over which the memory device is operated under severe conditions may not be known. Over time, such as over months or years, the cumulative duration may become significant, and may indicate that the memory device may begin (or may already have begun) degrading.

(10) To address this issue, in some cases, the memory device may monitor a duration over which the device is operated under severe conditions and if the duration reaches or exceeds (e.g., satisfies) a threshold, the memory device may store, in a non-volatile storage element, an indication that the device has been operated under severe conditions for the threshold duration. The memory device may store the indication by, for example, blowing a fuse or writing the indication to external non-volatile memory. This approach may enable a memory device to maintain a persistent indicator of its health status across time periods when the memory device is powered off.

(11) In some cases, a memory device may store an indication that the memory device has been operated under severe conditions for the threshold duration in an on-die volatile storage element, such as in a register, in addition to or instead of storing the indication in a non-volatile storage element. In this case, an external device, such as a host processor, may be configured to poll (e.g., read) the volatile storage element at various times. The external device may then determine how to respond to the information retrieved from the volatile storage element. For example, the external processor may be configured to retrieve the information from the volatile storage element and store the information in a non-volatile storage element (e.g., to non-volatile memory that is external to the memory die), or adjust an operating characteristic associated with the memory die (e.g., reduce a clock speed), or switch to another memory device, or alert a user, or take some other action based on the indication. The external device may itself maintain (or cause to be maintained) a persistent record of the cumulative duration over which the memory device has been operated under severe operating conditions, and may perform various actions based on the cumulative duration.

(12) In some cases, the memory device may store an indication in a non-volatile storage element each time the duration exceeds the threshold. In some cases, a memory device may use a timer to determine whether the duration has reached or exceeded a threshold, and may restart the timer after storing the indication in the non-volatile storage element. For example, a memory device may blow a fuse in an on-die fuse array each time a timer indicates that the memory device has been operated under severe conditions for a period of time (e.g., 5, 10, 15, 20, 25 or 30 minutes), and may restart the timer after blowing each fuse.

(13) In this manner, the non-volatile storage elements may maintain a persistent record of the cumulative duration across periods when the device is powered off. In some cases, the threshold duration may be relatively short compared to the frequency with which the memory device is typically powered off. For example, if a memory device is used within a system in which the memory device is typically powered on for about an hour before being powered off, the threshold duration may be (for example) 5 minutes, 10 minutes, 30 minutes, etc., so that the device may be more likely to capture information about the duration over which it is operated under severe conditions.

(14) In some cases, the memory device may store the indication in consecutive non-volatile storage elements within an array of non-volatile storage elements. Returning to the previous example, a memory device may include an array of fuses and may blow a first fuse after the device has operating under severe operating conditions for 30 minutes, a second fuse after the device has operated under severe operating conditions for another 30 minutes, a third fuse after another 30 minutes, etc. In this manner, each non-volatile storage element may be associated with a particular

cumulative duration over which the memory device has been operated under severe operating conditions.

(15) In some cases, a particular non-volatile storage element may be associated with an alert such that if the memory device stores an indication in that particular non-volatile storage element, the memory device may transmit the alert to an external device (such as a host processor) to notify the external device that the memory device has reached the duration associated with the particular non-volatile storage element. The alert may provide a notification to the external device that the memory device may be degrading, allowing the external device to adjust various operating characteristics of the memory device or of the overall system, or issue a notification to a user, or take some other action.

(16) Returning to the previous example, if the memory device blows a third fuse associated with operating under severe operating conditions for a cumulative duration of 90 minutes and that fuse is associated with an alert, the memory device may transmit the alert to the external device.

(17) Thus, techniques described herein may enable a volatile memory device to maintain a persistent indication of its own health across periods during which the device is powered down, and to send alerts to an external device as needed to indicate critical operational thresholds that may be associated with degradation of the memory device. Techniques further allow an external device to monitor the health status of the memory device by, for example, polling a register of the memory device that may contain an indication that the memory device has been operated under severe operating conditions for a threshold duration.

(18) Although the techniques described herein are primarily discussed in the context of volatile memory devices, such techniques may also be used for non-volatile memory devices without departing from the scope of the disclosure. For example, the use of separate non-volatile storage elements (such as fuses) for saving an indication that a non-volatile memory device has been operated with one or more operating conditions outside of a range (e.g., a low-risk range) for a threshold duration may be useful for providing a persistent record of the device's operating conditions after a catastrophic failure of the non-volatile memory device.

(19) Features of the disclosure are initially described in the context of a memory system and memory die as described with reference to FIGS. 1 and 2. Features of the disclosure are described in the context of a system including a memory device as described with reference to FIG. 3. These and other features of the disclosure are further illustrated by and described with reference to an apparatus diagram and flowcharts that relate to persistent health monitoring for volatile memory devices as described with references to FIGS. 4-6.

(20) FIG. 1 illustrates an example of a system **100** that utilizes one or more memory devices in accordance with examples as disclosed herein. The system **100** may include an external memory controller **105**, a memory device **110**, and a plurality of channels **115** coupling the external memory controller **105** with the memory device **110**. The system **100** may include one or more memory devices, but for ease of description the one or more memory devices may be described as a single memory device **110**.

(21) The system **100** may include portions of an electronic device, such as a computing device, a mobile computing device, a wireless device, or a graphics processing device. The system **100** may be an example of a portable electronic device. The system **100** may be an example of a computer, a laptop computer, a tablet computer, a smartphone, a cellular phone, a wearable device, an internet-connected device, or the like. The memory device **110** may be component of the system configured to store data for one or more other components of the system **100**. In some examples, the system **100** is capable of machine-type communication (MTC), machine-to-machine (M2M) communication, or device-to-device (D2D) communication.

(22) At least portions of the system **100** may be examples of a host device. Such a host device may be an example of a device that uses memory to execute processes such as a computing device, a mobile computing device, a wireless device, a graphics processing device, a computer, a laptop

computer, a tablet computer, a smartphone, a cellular phone, a wearable device, an internet-connected device, some other stationary or portable electronic device, or the like. In some cases, the host device may refer to the hardware, firmware, software, or a combination thereof that implements the functions of the external memory controller **105**. In some cases, the external memory controller **105** may be referred to as a host or host device. In some examples, system **100** is a graphics card.

(23) In some cases, a memory device **110** may, based on saving an indication that the memory device has been operated under severe conditions (e.g., operated under operating conditions that are outside of a range) for a particular threshold duration, transmit an alert to a host device indicating that the memory device has been operated under severe operating conditions for the threshold duration. In this case, the host device may determine whether to change the operation of various system features, such as by switching to a different memory device, reducing the quantity or frequency of memory accesses, reducing the clock speed, issuing an alert to another system, etc.

(24) In some cases, a host device may poll a volatile memory element on memory device **110** to determine whether the memory device **110** has been operated with one or more operating conditions outside of a range for the threshold duration. In some cases, the host device may poll the volatile memory element by synchronously or asynchronously reading the volatile memory element. In some cases, the host device may then store the indication in a non-volatile storage element that is off of the memory device **110** (e.g., off-die), for example. In some cases, the volatile storage element may be a register on memory device **110** or another type of volatile storage element that may be based on, for example, volatile memory cells, flip-flops, or latches.

(25) In some cases, a memory device **110** may be an independent device or component that is configured to be in communication with other components of the system **100** and provide physical memory addresses/space to potentially be used or referenced by the system **100**. In some examples, a memory device **110** may be configurable to work with at least one or a plurality of different types of systems **100**. Signaling between the components of the system **100** and the memory device **110** may be operable to support modulation schemes to modulate the signals, different pin designs for communicating the signals, distinct packaging of the system **100** and the memory device **110**, clock signaling and synchronization between the system **100** and the memory device **110**, timing conventions, and/or other factors.

(26) The memory device **110** may be configured to store data for the components of the system **100**. In some cases, the memory device **110** may act as a slave-type device to the system **100** (e.g., responding to and executing commands provided by the system **100** through the external memory controller **105**). Such commands may include an access command for an access operation, such as a write command for a write operation, a read command for a read operation, a refresh command for a refresh operation, or other commands. In some cases, a memory device **110** may include a single memory die **160**. In some cases, a memory device **110** may include two or more memory dice **160** (e.g., memory chips) to support a desired or specified capacity for data storage. The memory device **110** including two or more memory dice **160** may be referred to as a multi-die memory or package (also referred to as multi-chip memory or package).

(27) The system **100** may further include a processor **120**, a basic input/output system (BIOS) component **125**, one or more peripheral components **130**, and an input/output (I/O) controller **135**. The components of system **100** may be in electronic communication with one another using a bus **140**.

(28) The processor **120** may be configured to control at least portions of the system **100**. The processor **120** may be a general-purpose processor, a digital signal processor (DSP), an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or it may be a combination of these types of components. In such cases, the processor **120** may be an example of a central processing unit (CPU), a graphics processing unit (GPU), a general purpose GPU

(GPGPU), or a system on a chip (SoC), among other examples.

(29) The BIOS component **125** may be a software component that includes a BIOS operated as firmware, which may initialize and run various hardware components of the system **100**. The BIOS component **125** may also manage data flow between the processor **120** and the various components of the system **100**, e.g., the peripheral components **130**, the I/O controller **135**, etc. The BIOS component **125** may include a program or software stored in read-only memory (ROM), flash memory, or any other non-volatile memory.

(30) The peripheral component(s) **130** may be any input device or output device, or an interface for such devices, that may be integrated into or with the system **100**. Examples may include disk controllers, sound controller, graphics controller, Ethernet controller, modem, universal serial bus (USB) controller, a serial or parallel port, or peripheral card slots, such as peripheral component interconnect (PCI) or specialized graphics ports. The peripheral component(s) **130** may be other components understood by those skilled in the art as peripherals.

(31) The I/O controller **135** may manage data communication between the processor **120** and the peripheral component(s) **130**, input devices **145**, or output devices **150**. The I/O controller **135** may manage peripherals that are not integrated into or with the system **100**. In some cases, the I/O controller **135** may represent a physical connection or port to external peripheral components.

(32) The input **145** may represent a device or signal external to the system **100** that provides information, signals, or data to the system **100** or its components. This may include a user interface or interface with or between other devices. In some cases, the input **145** may be a peripheral that interfaces with system **100** via one or more peripheral components **130** or may be managed by the I/O controller **135**.

(33) The output **150** may represent a device or signal external to the system **100** configured to receive an output from the system **100** or any of its components. Examples of the output **150** may include a display, audio speakers, a printing device, or another processor on printed circuit board, and so forth. In some cases, the output **150** may be a peripheral that interfaces with the system **100** via one or more peripheral components **130** or may be managed by the I/O controller **135**.

(34) The components of system **100** may be made up of general-purpose or special purpose circuitry designed to carry out their functions. This may include various circuit elements, for example, conductive lines, transistors, capacitors, inductors, resistors, amplifiers, or other active or passive elements, configured to carry out the functions described herein.

(35) The memory device **110** may include a device memory controller **155** and one or more memory dice **160**. In some cases, memory dice **160** may be fabricated using a semiconductor fabrication process associated with volatile memory cells. For example, memory dice **160** may be fabricated using a stacked DRAM process, a trench DRAM process, or a fin DRAM process, or another process. In some cases, a semiconductor process associated with fabrication of volatile memory cells may not support features of non-volatile memory cells, such as EEPROM or flash memory cells. For example, a volatile memory fabrication process may not support construction of tunneling diodes, devices capable of hot-electron injection for storing or discharging a floating gate, and the like. In addition, a DRAM process may not support high-voltage transistors (e.g., greater than a native voltage of a given process) for the internally boosted voltages used by EEPROM, flash, and other non-volatile memories. Thus, in some cases it may be impractical or unfeasible to fabricate non-volatile memory cells on a memory die **160** fabricated with a process conducive to high-density volatile memory cells.

(36) Each memory die **160** may include a local memory controller **165** (e.g., local memory controller **165-a**, local memory controller **165-b**, and/or local memory controller **165-N**) and a memory array **170** (e.g., memory array **170-a**, memory array **170-b**, and/or memory array **170-N**). A memory array **170** may be a collection (e.g., a grid) of memory cells, with each memory cell being configured to store at least one bit of digital data. Features of memory arrays **170** and/or memory cells are described in more detail with reference to FIG. 2.

- (37) In some cases, a memory die **160** may include one or more sensors for detecting that an operating condition of the memory device **110** is outside of a range, indicating that memory device **110** may be operating under severe operating conditions. For example, a memory die **160** may include one or more temperature sensors, voltage sensors, etc. that may be configured to detect corresponding operating conditions of memory device **110**.
- (38) In some cases, a memory die **160** may include one or more timers for monitoring (e.g., measuring) a duration over which a memory device **110** has been operated outside of a range (e.g., a low-risk range). For example, memory die **160** may include a timer coupled with a sensor on memory die **160**. When the sensor detects that an operating condition of memory die **160** is outside of the range, the sensor may transmit a signal to the timer, which may initiate timing. If the timer reaches a threshold duration before the sensor indicates that the operating condition has returned to within a normal range, the timer may transmit a signal that causes the memory die **160** or memory device **110** to save an indication that the threshold duration has been satisfied (e.g., met or exceeded) in a non-volatile storage component, such as by blowing a fuse. In some cases, the timer may then be reset.
- (39) In some cases, a memory die **160** or memory device **110** may include an array of non-volatile storage elements, such as fuses, that may be used to store one or more indications that the memory device **110** has been operated with one or more operating conditions outside of a range for the threshold duration.
- (40) In some cases, values for the range and/or threshold duration may be programmed in memory device **110** and/or may be received from (e.g., configured by) an external device, such as a host processor. For example, the memory device **110** may have registers that hold values for ranges for voltage, power, temperature, or current, and may have a register for the duration. The registers may have default values that may be overridden by the device memory control **155** or external memory controller **105**.
- (41) The memory device **110** may be an example of a two-dimensional (2D) array of memory cells or may be an example of a three-dimensional (3D) array of memory cells. For example, a 2D memory device may include a single memory die **160**. A 3D memory device may include two or more memory dice **160** (e.g., memory die **160-a**, memory die **160-b**, and/or any quantity of memory dice **160-N**). In a 3D memory device, a plurality of memory dice **160-N** may be stacked on top of one another or next to one another. In some cases, memory dice **160-N** in a 3D memory device may be referred to as decks, levels, layers, or dies. A 3D memory device may include any quantity of stacked memory dice **160-N** (e.g., two high, three high, four high, five high, six high, seven high, eight high). This may increase the quantity of memory cells that may be positioned on a substrate as compared with a single 2D memory device, which in turn may reduce production costs or increase the performance of the memory array, or both. In some 3D memory device, different decks may share at least one common access line such that some decks may share at least one of a word line, a digit line, and/or a plate line.
- (42) The device memory controller **155** may include circuits or components configured to control operation of the memory device **110**. As such, the device memory controller **155** may include the hardware, firmware, and software that enables the memory device **110** to perform commands and may be configured to receive, transmit, or execute commands, data, or control information related to the memory device **110**. The device memory controller **155** may be configured to communicate with the external memory controller **105**, the one or more memory dice **160**, or the processor **120**. In some cases, the memory device **110** may receive data and/or commands from the external memory controller **105**. For example, the memory device **110** may receive a write command indicating that the memory device **110** is to store certain data on behalf of a component of the system **100** (e.g., the processor **120**) or a read command indicating that the memory device **110** is to provide certain data stored in a memory die **160** to a component of the system **100** (e.g., the processor **120**). In some cases, the device memory controller **155** may control operation of the

memory device **110** described herein in conjunction with the local memory controller **165** of the memory die **160**. Examples of the components included in the device memory controller **155** and/or the local memory controllers **165** may include receivers for demodulating signals received from the external memory controller **105**, decoders for modulating and transmitting signals to the external memory controller **105**, logic, decoders, amplifiers, filters, or the like.

(43) The local memory controller **165** (e.g., local to a memory die **160**) may be configured to control operations of the memory die **160**. Also, the local memory controller **165** may be configured to communicate (e.g., receive and transmit data and/or commands) with the device memory controller **155**. The local memory controller **165** may support the device memory controller **155** to control operation of the memory device **110** as described herein. In some cases, the memory device **110** does not include the device memory controller **155**, and the local memory controller **165** or the external memory controller **105** may perform the various functions described herein. As such, the local memory controller **165** may be configured to communicate with the device memory controller **155**, with other local memory controllers **165**, or directly with the external memory controller **105** or the processor **120**.

(44) The external memory controller **105** may be configured to enable communication of information, data, and/or commands between components of the system **100** (e.g., the processor **120**) and the memory device **110**. The external memory controller **105** may act as a liaison between the components of the system **100** and the memory device **110** so that the components of the system **100** may not need to know the details of the memory device's operation. The components of the system **100** may present requests to the external memory controller **105** (e.g., read commands or write commands) that the external memory controller **105** satisfies. The external memory controller **105** may convert or translate communications exchanged between the components of the system **100** and the memory device **110**. In some cases, the external memory controller **105** may include a system clock that generates a common (source) system clock signal. In some cases, the external memory controller **105** may include a common data clock that generates a common (source) data clock signal.

(45) In some cases, the external memory controller **105** or other component of the system **100**, or its functions described herein, may be implemented by the processor **120**. For example, the external memory controller **105** may be hardware, firmware, or software, or some combination thereof implemented by the processor **120** or other component of the system **100**. While the external memory controller **105** is depicted as being external to the memory device **110**, in some cases, the external memory controller **105**, or its functions described herein, may be implemented by a memory device **110**. For example, the external memory controller **105** may be hardware, firmware, or software, or some combination thereof implemented by the device memory controller **155** or one or more local memory controllers **165**. In some cases, the external memory controller **105** may be distributed across the processor **120** and the memory device **110** such that portions of the external memory controller **105** are implemented by the processor **120** and other portions are implemented by a device memory controller **155** or a local memory controller **165**. Likewise, in some cases, one or more functions ascribed herein to the device memory controller **155** or local memory controller **165** may in some cases be performed by the external memory controller **105** (either separate from or as included in the processor **120**).

(46) The components of the system **100** may exchange information with the memory device **110** using a plurality of channels **115**. In some examples, the channels **115** may enable communications between the external memory controller **105** and the memory device **110**. Each channel **115** may include one or more signal paths or transmission mediums (e.g., conductors) between terminals associated with the components of system **100**. For example, a channel **115** may include a first terminal including one or more pins or pads at external memory controller **105** and one or more pins or pads at the memory device **110**. A pin may be an example of a conductive input or output point of a device of the system **100**, and a pin may be configured to act as part of a channel.

(47) In some cases, a pin or pad of a terminal may be part of a signal path of the channel **115**. Additional signal paths may be coupled with a terminal of a channel for routing signals within a component of the system **100**. For example, the memory device **110** may include signal paths (e.g., signal paths internal to the memory device **110** or its components, such as internal to a memory die **160**) that route a signal from a terminal of a channel **115** to the various components of the memory device **110** (e.g., a device memory controller **155**, memory dice **160**, local memory controllers **165**, memory arrays **170**).

(48) Channels **115** (and associated signal paths and terminals) may be dedicated to communicating specific types of information. In some cases, a channel **115** may be an aggregated channel and thus may include multiple individual channels. For example, a data channel **190** may be $\times 4$ (e.g., including four signal paths), $\times 8$ (e.g., including eight signal paths), $\times 16$ (including sixteen signal paths), and so forth. Signals communicated over the channels may use double data rate (DDR) signaling. For example, some symbols of a signal may be registered on a rising edge of a clock signal and other symbols of the signal may be registered on a falling edge of the clock signal. Signals communicated over channels may use single data rate (SDR) signaling. For example, one symbol of the signal may be registered for each clock cycle.

(49) In some cases, the channels **115** may include one or more command and address (CA) channels **186**. The CA channels **186** may be configured to communicate commands between the external memory controller **105** and the memory device **110** including control information associated with the commands (e.g., address information). For example, the CA channel **186** may include a read command with an address of the desired data. In some cases, the CA channels **186** may be registered on a rising clock signal edge and/or a falling clock signal edge. In some cases, a CA channel **186** may include any quantity of signal paths to decode address and command data (e.g., eight or nine signal paths).

(50) In some cases, the channels **115** may include one or more clock signal (CK) channels **188**. The CK channels **188** may be configured to communicate one or more common clock signals between the external memory controller **105** and the memory device **110**. Each clock signal may be configured to oscillate between a high state and a low state and coordinate the actions of the external memory controller **105** and the memory device **110**. In some cases, the clock signal may be a differential output (e.g., a CK_t signal and a CK_c signal) and the signal paths of the CK channels **188** may be configured accordingly. In some cases, the clock signal may be single ended. A CK channel **188** may include any quantity of signal paths. In some cases, the clock signal CK (e.g., a CK_t signal and a CK_c signal) may provide a timing reference for command and addressing operations for the memory device **110**, or other system-wide operations for the memory device **110**. The clock signal CK therefore may be variously referred to as a control clock signal CK, a command clock signal CK, or a system clock signal CK. The system clock signal CK may be generated by a system clock, which may include one or more hardware components (e.g., oscillators, crystals, logic gates, transistors, or the like).

(51) In some cases, an external memory controller **105** may synchronously poll a volatile storage element of memory device **100** to check for an indication that the memory device **110** has been operated with operating conditions outside of a range for a threshold duration. That is, an external memory controller **105** may read the contents of the volatile storage element at times that are based on timing associated with one or more clock signals. In some cases, an external memory controller **105** may asynchronously read a volatile storage element of memory device **100** to check for an indication that the memory device **110** has been operated with operating conditions outside of a range for a threshold duration. That is, an external memory controller **105** may read the contents of the volatile storage element at times that are not based on one or more clock signals.

(52) In some cases, the channels **115** may include one or more data (DQ) channels **190**. The data channels **190** may be configured to communicate data and/or control information between the external memory controller **105** and the memory device **110**. For example, the data channels **190**

may communicate information (e.g., bi-directional) to be written to the memory device **110** or information read from the memory device **110**.

(53) In some cases, the channels **115** may include one or more other channels **192** that may be dedicated to other purposes. These other channels **192** may include any quantity of signal paths.

(54) In some cases, the other channels **192** may include one or more write clock signal (WCK) channels. While the 'W' in WCK may nominally stand for "write," a write clock signal WCK (e.g., a WCK_t signal and a WCK_c signal) may provide a timing reference for access operations generally for the memory device **110** (e.g., a timing reference for both read and write operations). Accordingly, the write clock signal WCK may also be referred to as a data clock signal WCK. The WCK channels may be configured to communicate a common data clock signal between the external memory controller **105** and the memory device **110**. The data clock signal may be configured to coordinate an access operation (e.g., a write operation or read operation) of the external memory controller **105** and the memory device **110**. In some cases, the write clock signal may be a differential output (e.g., a WCK_t signal and a WCK_c signal) and the signal paths of the WCK channels may be configured accordingly. A WCK channel may include any quantity of signal paths. The data clock signal WCK may be generated by a data clock, which may include one or more hardware components (e.g., oscillators, crystals, logic gates, transistors, or the like).

(55) In some cases, the other channels **192** may include one or more error detection code (EDC) channels. The EDC channels may be configured to communicate error detection signals, such as checksums, to improve system reliability. An EDC channel may include any quantity of signal paths.

(56) In some cases, one or more channels, such as CA channels **186** or other channels **192**, may be configured to transmit (e.g., to an external device) an indication that the duration over which an operating condition is outside a range satisfies (e.g., meets or exceeds) a threshold duration.

(57) The channels **115** may couple the external memory controller **105** with the memory device **110** using a variety of different architectures. Examples of the various architectures may include a bus, a point-to-point connection, a crossbar, a high-density interposer such as a silicon interposer, or channels formed in an organic substrate or some combination thereof. For example, in some cases, the signal paths may at least partially include a high-density interposer, such as a silicon interposer or a glass interposer.

(58) Signals communicated over the channels **115** may be modulated using a variety of different modulation schemes. In some cases, a binary-symbol (or binary-level) modulation scheme may be used to modulate signals communicated between the external memory controller **105** and the memory device **110**. A binary-symbol modulation scheme may be an example of a M-ary modulation scheme where M is equal to two. Each symbol of a binary-symbol modulation scheme may be configured to represent one bit of digital data (e.g., a symbol may represent a logic 1 or a logic 0). Examples of binary-symbol modulation schemes include, but are not limited to, non-return-to-zero (NRZ), unipolar encoding, bipolar encoding, Manchester encoding, pulse amplitude modulation (PAM) having two symbols (e.g., PAM2), and/or others.

(59) In some cases, a multi-symbol (or multi-level) modulation scheme may be used to modulate signals communicated between the external memory controller **105** and the memory device **110**. A multi-symbol modulation scheme may be an example of a M-ary modulation scheme where M is greater than or equal to three. Each symbol of a multi-symbol modulation scheme may be configured to represent more than one bit of digital data (e.g., a symbol may represent a logic 00, a logic 01, a logic 10, or a logic 11). Examples of multi-symbol modulation schemes include, but are not limited to, PAM3, PAM4, PAM8, etc., quadrature amplitude modulation (QAM), quadrature phase shift keying (QPSK), and/or others. A multi-symbol signal (e.g., a PAM3 signal or a PAM4 signal) may be a signal that is modulated using a modulation scheme that includes at least three levels to encode more than one bit of information. Multi-symbol modulation schemes and symbols may alternatively be referred to as non-binary, multi-bit, or higher-order modulation schemes and

symbols.

(60) FIG. 2 illustrates an example of a memory die **200** in accordance with examples as disclosed herein. The memory die **200** may be an example of the memory dice **160** described with reference to FIG. 1. In some cases, the memory die **200** may be referred to as a memory chip, a memory device, or an electronic memory apparatus. The memory die **200** may include one or more memory cells **205** that are programmable to store different logic states. Each memory cell **205** may be programmable to store two or more states. For example, the memory cell **205** may be configured to store one bit of digital logic at a time (e.g., a logic 0 and a logic 1). In some cases, a single memory cell **205** (e.g., a multi-level memory cell) may be configured to store more than one bit of digit logic at a time (e.g., a logic 00, logic 01, logic 10, or a logic 11).

(61) A memory cell **205** may store a charge representative of the programmable states in a capacitor. DRAM architectures may include a capacitor that includes a dielectric material to store a charge representative of the programmable state. In other memory architectures, other storage devices and components are possible. For example, nonlinear dielectric materials may be employed.

(62) Operations such as reading and writing may be performed on memory cells **205** by activating or selecting access lines such as a word line **210** and/or a digit line **215**. In some cases, digit lines **215** may also be referred to as bit lines. References to access lines, word lines and digit lines, or their analogues, are interchangeable without loss of understanding or operation. Activating or selecting a word line **210** or a digit line **215** may include applying a voltage to the respective line.

(63) The memory die **200** may include the access lines (e.g., the word lines **210** and the digit lines **215**) arranged in a grid-like pattern. Memory cells **205** may be positioned at intersections of the word lines **210** and the digit lines **215**. By biasing a word line **210** and a digit line **215** (e.g., applying a voltage to the word line **210** or the digit line **215**), a single memory cell **205** may be accessed at their intersection.

(64) Accessing the memory cells **205** may be controlled through a row decoder **220** or a column decoder **225**. For example, a row decoder **220** may receive a row address from the local memory controller **260** and activate a word line **210** based on the received row address. A column decoder **225** may receive a column address from the local memory controller **260** and may activate a digit line **215** based on the received column address. For example, the memory die **200** may include multiple word lines **210**, labeled WL_1 through WL_M, and multiple digit lines **215**, labeled DL_1 through DL_N, where M and N depend on the size of the memory array. Thus, by activating a word line **210** and a digit line **215**, e.g., WL_1 and DL_3, the memory cell **205** at their intersection may be accessed. The intersection of a word line **210** and a digit line **215**, in either a two-dimensional or three-dimensional configuration, may be referred to as an address of a memory cell **205**.

(65) The memory cell **205** may include a logic storage component, such as capacitor **230** and a switching component **235**. The capacitor **230** may be an example of a dielectric capacitor or a ferroelectric capacitor. A first node of the capacitor **230** may be coupled with the switching component **235** and a second node of the capacitor **230** may be coupled with a voltage source **240**. In some cases, the voltage source **240** may be the cell plate reference voltage, such as V_{pl}, or may be ground, such as V_{ss}. In some cases, the voltage source **240** may be an example of a plate line coupled with a plate line driver. The switching component **235** may be an example of a transistor or any other type of switch device that selectively establishes or de-establishes electronic communication between two components.

(66) Selecting or deselecting the memory cell **205** may be accomplished by activating or deactivating the switching component **235**. The capacitor **230** may be in electronic communication with the digit line **215** using the switching component **235**. For example, the capacitor **230** may be isolated from digit line **215** when the switching component **235** is deactivated, and the capacitor **230** may be coupled with digit line **215** when the switching component **235** is activated. In some cases, the switching component **235** is a transistor and its operation may be controlled by applying

a voltage to the transistor gate, where the voltage differential between the transistor gate and transistor source may be greater or less than a threshold voltage of the transistor. In some cases, the switching component **235** may be a p-type transistor or an n-type transistor. The word line **210** may be in electronic communication with the gate of the switching component **235** and may activate/deactivate the switching component **235** based on a voltage being applied to word line **210**. (67) A word line **210** may be a conductive line in electronic communication with a memory cell **205** that is used to perform access operations on the memory cell **205**. In some architectures, the word line **210** may be in electronic communication with a gate of a switching component **235** of a memory cell **205** and may be configured to control the switching component **235** of the memory cell. In some architectures, the word line **210** may be in electronic communication with a node of the capacitor of the memory cell **205** and the memory cell **205** may not include a switching component.

(68) A digit line **215** may be a conductive line that connects the memory cell **205** with a sense component **245**. In some architectures, the memory cell **205** may be selectively coupled with the digit line **215** during portions of an access operation. For example, the word line **210** and the switching component **235** of the memory cell **205** may be configured to couple and/or isolate the capacitor **230** of the memory cell **205** and the digit line **215**. In some architectures, the memory cell **205** may be in electronic communication (e.g., constant) with the digit line **215**.

(69) The sense component **245** may be configured to detect a state (e.g., a charge) stored on the capacitor **230** of the memory cell **205** and determine a logic state of the memory cell **205** based on the stored state. The charge stored by a memory cell **205** may be extremely small, in some cases. As such, the sense component **245** may include one or more sense amplifiers to amplify the signal output by the memory cell **205**. The sense amplifiers may detect small changes in the charge of a digit line **215** during a read operation and may produce signals corresponding to a logic state 0 or a logic state 1 based on the detected charge. During a read operation, the capacitor **230** of memory cell **205** may output a signal (e.g., discharge a charge) to its corresponding digit line **215**. The signal may cause a voltage of the digit line **215** to change. The sense component **245** may be configured to compare the signal received from the memory cell **205** across the digit line **215** to a reference signal **250** (e.g., reference voltage). The sense component **245** may determine the stored state of the memory cell **205** based on the comparison. For example, in binary signaling, if digit line **215** has a higher voltage than the reference signal **250**, the sense component **245** may determine that the stored state of memory cell **205** is a logic 1 and, if the digit line **215** has a lower voltage than the reference signal **250**, the sense component **245** may determine that the stored state of the memory cell **205** is a logic 0. The sense component **245** may include various transistors or amplifiers to detect and amplify a difference in the signals. The detected logic state of the memory cell **205** may be provided as an output of the sense component **245** (e.g., to an input/output **255**), and may indicate the detected logic state to another component of a memory device **110** that includes the memory die **200**, such as a device memory controller **155** (e.g., directly or using the local memory controller **260**).

(70) The local memory controller **260** may control the operation of memory cells **205** through the various components (e.g., row decoder **220**, column decoder **225**, and sense component **245**). The local memory controller **260** may be an example of the local memory controller **165** described with reference to FIG. 1. In some cases, one or more of the row decoder **220**, column decoder **225**, and sense component **245** may be co-located with the local memory controller **260**. The local memory controller **260** may be configured to receive commands and/or data from an external memory controller **105** (or a device memory controller **155** described with reference to FIG. 1), translate the commands and/or data into information that can be used by the memory die **200**, perform one or more operations on the memory die **200**, and communicate data from the memory die **200** to the external memory controller **105** (or the device memory controller **155**) in response to performing the one or more operations. The local memory controller **260** may generate row and column

address signals to activate the target word line **210** and the target digit line **215**. The local memory controller **260** may also generate and control various voltages or currents used during the operation of the memory die **200**. In general, the amplitude, shape, or duration of an applied voltage or current discussed herein may be adjusted or varied and may be different for the various operations discussed in operating the memory die **200**.

(71) In some cases, the local memory controller **260** may be configured to perform a write operation (e.g., a programming operation) on one or more memory cells **205** of the memory die **200**. During a write operation, a memory cell **205** of the memory die **200** may be programmed to store a desired logic state. In some cases, a plurality of memory cells **205** may be programmed during a single write operation. The local memory controller **260** may identify a target memory cell **205** on which to perform the write operation. The local memory controller **260** may identify a target word line **210** and a target digit line **215** in electronic communication with the target memory cell **205** (e.g., the address of the target memory cell **205**). The local memory controller **260** may activate the target word line **210** and the target digit line **215** (e.g., applying a voltage to the word line **210** or digit line **215**), to access the target memory cell **205**. The local memory controller **260** may apply a specific signal (e.g., voltage) to the digit line **215** during the write operation to store a specific state (e.g., charge) in the capacitor **230** of the memory cell **205**, the specific state (e.g., charge) may be indicative of a desired logic state.

(72) In some cases, the local memory controller **260** may be configured to perform a read operation (e.g., a sense operation) on one or more memory cells **205** of the memory die **200**. During a read operation, the logic state stored in a memory cell **205** of the memory die **200** may be determined. In some cases, a plurality of memory cells **205** may be sensed during a single read operation. The local memory controller **260** may identify a target memory cell **205** on which to perform the read operation. The local memory controller **260** may identify a target word line **210** and a target digit line **215** in electronic communication with the target memory cell **205** (e.g., the address of the target memory cell **205**). The local memory controller **260** may activate the target word line **210** and the target digit line **215** (e.g., applying a voltage to the word line **210** or digit line **215**), to access the target memory cell **205**. The target memory cell **205** may transfer a signal to the sense component **245** in response to biasing the access lines. The sense component **245** may amplify the signal. The local memory controller **260** may fire the sense component **245** (e.g., latch the sense component) and thereby compare the signal received from the memory cell **205** to the reference signal **250**. Based on that comparison, the sense component **245** may determine a logic state that is stored on the memory cell **205**. The local memory controller **260** may communicate the logic state stored on the memory cell **205** to the external memory controller **105** (or the device memory controller **155**) as part of the read operation.

(73) In some memory architectures, accessing the memory cell **205** may degrade or destroy the logic state stored in a memory cell **205**. For example, activation of a word line in DRAM architectures may partially or completely discharge the capacitor of the target memory cell. The sense component **245** may restore the voltage on the digit line **215** according to the sensed logic state, which may restore the voltage on the memory cell **205** to a same or similar voltage as used in the write operation. Thus, read operations performed in DRAM architectures may restore the logic state of memory cells **205**, as long as a sufficient level is present for the sense component **245** to resolve the stored logic state.

(74) In some memory architectures based on volatile memory cells, such as DRAM, the state of a memory cell **205** may need to be periodically refreshed to maintain the state of the memory cell **205** when the memory cell **205** is not accessed for a period of time (and therefore is not restored as part of a read or write operation). Thus, memory die **200** may include logic circuitry that may be configured to periodically perform a refresh procedure on memory cells **205** of one or more rows **275** by reading and restoring (e.g., firing sense component **245** to amplify the voltage on the memory cells **205** back to the originally written voltage levels) the states of the memory cells **205**.

In some cases, such logic circuitry may be part of local memory controller **260** or may be separate circuitry. In some cases, memory die **200** may perform a refresh procedure on memory cells **205** of one or more rows **275** in response to receiving a refresh command from an external host device or based on internal timing that specifies a frequency with which memory cells **205** may be refreshed. (75) In some cases, a memory die **200** may include one or more sensors **265** that may be configured to sense one or more operating conditions associated with memory die **200**, such as a temperature, voltage, power, etc. associated with memory die **200**. In some cases, sensors **265** may include one or more temperatures sensors, one or more voltage sensors, one or more power sensors, or other types of sensors or circuits that may be configured to detect a value of the operating condition. Sensors **265** may be located at various physical locations on memory die **200** to enable sensors **265** to detect the operating conditions at the locations.

(76) In some cases, the operating condition may include one or more metrics based on a quantity of bit errors associated with the memory device, which may provide an indication of a health status of the memory device. For example, a memory die **200** may be configured to monitor (e.g., determine, detect) a value of the quantity of bit errors in a memory array of the memory die **200** over time by performing error detection procedures, such as error correcting code (ECC) procedures, rather than by sensing a value using a sensor **320**. In some cases, a health status of the device may be determined based on the detected quantity of bit errors or change in the quantity of bit errors. In some examples, the memory die **200** may indicate the health status to an external memory controller.

(77) In some cases, a memory die **200** may be configured to determine that an operating condition associated with an array of memory cells (such as memory cells **205**, which may be within a memory array **170** and reside on memory die **200**) is outside a range, and monitor, based on determining that the operating condition is outside the range, a duration over which the operating condition is outside the range. Memory die **200** may be configured to determine whether the duration satisfies (e.g., meets or exceeds) a threshold duration and store, in one or more storage elements **270** associated with the threshold duration, an indication that the duration satisfies the threshold duration. Storage elements **270** may be on memory die **200**, for example, and may be or may include non-volatile storage elements or volatile storage elements.

(78) In some cases, storage elements **270** may include one-time programmable storage elements, such as fuses or non-volatile memory cells that may be written only once. In some cases, a fuse may include an electrical element, such as a polysilicon wire, that is “blown” by applying a relatively large current to the element, thereby causing a change in the electrical properties of the element that, for example, increases the resistance across the electrical element. In some cases, blowing the electrical element may cause the electrical element to behave as an open circuit, which may be detectable by current or voltage sensing circuitry.

(79) In some cases, storage elements **270** may include re-programmable non-volatile storage elements, such as non-volatile memory cells that may be re-written multiple times. Non-volatile storage elements may be fabricated using a different fabrication process than volatile storage elements, however, and thus it may be challenging to fabricate both types of storage elements on a single die.

(80) In some cases, storage elements **270** may include volatile storage elements, such as volatile memory cells, registers, counters, etc.

(81) FIG. 3 illustrates an example of a system **300** that supports persistent health monitoring for volatile memory devices in accordance with examples as disclosed herein.

(82) System **300** includes memory device **305**, which may be an example of memory device **110** and/or memory die **200** as depicted in FIGS. 1 and 2, respectively. Memory device **305** includes an array of memory cells **310**, may include memory cells **205** that may be part of a memory array **170** as discussed with reference to FIGS. 1 and 2. Array of memory cells **310** may include volatile memory cells, such as DRAM memory cells, or non-volatile memory cells, such as FeRAM or

flash memory cells.

(83) Memory device **305** may include a set of one or more storage elements **345** for maintaining a persistent record of a cumulative amount of time over which the memory device **305** is operated under severe operating conditions, such as when one or more operating conditions of memory device **305** are outside of a corresponding range.

(84) Memory device **305** may include one or more sensors **320**. Sensor **320** may be configured to sense (e.g., determine) a value of an operating condition associated with the array of memory cells **310**. In some cases, sensor **320** may be located on the same die as array of memory cells **310**. Sensor **320** may be, for example, a temperature sensor, voltage sensor (e.g., for sensing an input voltage to the memory device such as a VDD voltage), current sensor, power sensor, vibration sensor, acceleration sensor, radiation sensor, or another type of sensor.

(85) In some cases, memory device **305** may include multiple sensors **320**, which may be the same or different types of sensors. For example, memory device **305** may include multiple temperature sensors at different locations on memory device **305** to enable memory device **305** to monitor the temperature associated with the array of memory cells **310** at multiple locations. For example, memory device **305** may include a temperature sensor and a voltage sensor to monitor both the temperature and voltage associated with the array of memory cells **310**.

(86) In some cases, sensor **320** may be configured to output a signal indicating the value of the sensed operating condition, for example.

(87) Memory device **305** may include comparison element **325**. Comparison element **325** may be coupled with sensor **320** and configured to receive a signal from sensor **320** that indicates a value of a sensed operating condition. In some cases, comparison element **325** may be located on a memory die with the array of memory cells **310**. In some cases, comparison element **325** may be included in a local memory controller **165**, **260** or in a device memory controller **155**, or in a sensor **320**, or may be separate circuitry.

(88) In some cases, comparison element **325** may be configured to determine, based on the signal received from sensor **320**, that an operating condition associated with array of memory cells **310** is outside of a range, and output a signal indicating that the operating condition is outside of the range. For example, comparison element **325** may determine that the operating condition is outside of the range when the sensed value of an operating condition (e.g., as received in a signal from sensor **320**) is above an upper threshold value for the operating condition or below a lower threshold value for an operating condition. In some cases, comparison element **325** may include a comparator that is configured to compare the signal received from sensor **320** with one or more threshold values (e.g., stored in the comparator) and output a signal based on the comparison. For example, a comparator may output a signal indicating the operating condition is outside of the range, or a signal indicating that the comparison is within the range or no signal, depending on the comparison.

(89) In some cases, comparison element **325** (or other components of memory die **200**) may include circuitry capable of determining an amount by which the operating condition is outside of the range, which may quantify the severity of the operating conditions, for example. In some cases, comparison element may be configured to output (e.g., to timer **330**, or logic circuitry **340**, or another component) a signal indicating an amount by which the operating condition is outside of the range.

(90) Memory device **305** may include timer **330**. Timer **330** may be coupled with comparison element **325** and configured to receive the signal indicating that the operating condition is outside of the operating range from comparison element **325**. In some cases, when comparison element **325** outputs a signal indicating that an operating condition of memory device **305** is outside of the operating range, timer **330** may start measuring (monitoring) an elapsed time over which the operating condition is outside the operating range based on the signal received from comparison element **325**. In some cases, timer **330** may be started (e.g., initiated) based on receiving a signal

from comparison element **325**, and may continue timing the duration (e.g., the elapsed time) as long as (e.g., while) timer **330** continues to receive a signal indicating that the operating condition is outside of the range. In some cases, if timer **330** ceases to receive the signal from comparison element **325**, timer **330** may cease timing the duration. In some cases, if timer **330** subsequently receives the signal indicating that the operating condition is again outside of the operating range, timer **330** may continue timing the duration from the previous time value, or may be reset and begin timing the duration again from an initial time of zero.

(91) In some cases, if timer **330** determines, based on the signal received from comparison element **325**, that the duration over which the operating condition is outside of the operating range satisfies (e.g., meets or exceeds) a threshold, timer **330** may output a signal indicating that the duration satisfies the threshold. Timer **330** may then be reset and may, if comparison element **325** continues to output a signal indicating that an operating condition is outside a range, re-initiate timing the duration over which the operating is outside the range based on the signal received from comparison element **325**. In some cases, timer **330** may output a signal indicating that the duration satisfies a threshold each time (e.g., each occurrence) timer **330** determines that the duration satisfies the threshold.

(92) In some cases, timer **330** may be configured to initiate timing a duration if any one of multiple operating conditions are outside a range. For example, a memory device **305** may include multiple sensors **320** and in some cases, multiple comparison elements **325** that may be configured to determine whether any of the sensed operating conditions are outside of a corresponding range. In some cases, timer **330** may be configured to receive a single signal (e.g., from a comparison element **325** or from a multiplexer) indicating when any one of multiple operating conditions is outside of their respective range. In some cases, timer **330** may be configured to receive separate signals (e.g., from separate comparison elements **325**) indicating when each operating condition is outside of its corresponding range.

(93) In some cases, the threshold duration may be determined by (e.g., may depend on) various factors or combinations of factors related to the likelihood of device degradation. For example, in some cases, each sensor **320** or each type of sensor **320** may be associated with a different threshold duration; that is, the threshold duration may depend on the particular operating condition being sensed. For example, a threshold duration for temperature may be different than a threshold duration for voltage.

(94) In some cases, the threshold duration may be based on an amount by which the operating condition is outside of the range. For example, the threshold duration may be shorter when the operating condition is far outside of the range than when the operating condition is slightly outside of the range. The timer **330** may, for example, integrate the amount by which the operating condition is outside of the range and compare the integrated value to one or more thresholds.

(95) In some cases, the threshold duration may be based on the status of multiple operating conditions. For example, the threshold duration may be shorter if both the temperature and voltage are outside of their respective ranges than if the temperature or voltage were outside of its respective range.

(96) In some cases, the threshold duration may be based on a weighted combination of factors that may include, for example, the quantity of operating conditions that are outside of their respective ranges, and/or an amount by which various operating conditions are outside of their respective ranges, or various other combinations of factors.

(97) In some cases, one or more threshold durations may be stored on memory device **305**, such as in registers, and accessed by timer **330** for determining whether the duration satisfies the threshold. In some cases, a threshold duration may be configured by an external controller.

(98) In some cases, timer **330** may output the signal indicating that the duration satisfies the threshold to logic circuitry **340** on memory device **305**. In some cases, logic circuitry **340** may be configured to store an indication that the duration satisfies the threshold in one or more storage

elements **345-a**, **345-b**, **345-c**, **345-d**, **345-e**, **345-f** that may be included in a set of storage elements **345** on memory device **305**.

(99) In some cases, the set of storage elements **345** may include a set of one-time programmable storage elements, such as a set of fuses or one-time programmable memory cells. In some cases, the set of storage elements **345** may include a set of volatile storage elements, such as volatile memory cells. Although the set of storage elements **345** is depicted in FIG. 3 as being included in memory device **305**, in some cases, the set of storage elements **345** may be external to memory device **305** (e.g., off-chip or off-die). In some cases, the set of storage elements **345** may be coupled with the memory device **305** and/or may be coupled with an external device.

(100) In some cases, logic circuitry **340** may identify a particular storage element in the set of storage elements **345** for storing the indication. In some cases, each storage element **345** in the set of storage elements **345** may be associated with a particular threshold duration, and logic circuitry **340** may select, based on the signal indicating that the duration has satisfied a particular threshold duration, the storage element **345** that is associated with the particular threshold duration. For example, one storage element **345** may be associated with a threshold duration of 10 minutes and another storage element **345** may be associated with a threshold duration of 30 minutes.

(101) In some cases, logic circuitry **340** may select storage elements consecutively, such as from left to right or top to bottom in an array (set) of storage elements. For example, logic circuitry **340** may receive a signal indicating that the duration satisfies the threshold, and may select the next consecutive unused storage element in the set of storage elements **345** to store the indication that the duration satisfies the threshold. In some cases, the quantity of consecutive storage elements that contain an indication that the duration satisfies the threshold may provide an indication of a cumulative duration over which one or more operating conditions were outside of a range.

(102) In some cases, logic circuitry **340** may select storage elements non-consecutively, such as by skipping consecutive storage elements. For example, skipping a storage element may indicate that the threshold duration has been satisfied 5×, or 10×, or based on some other multiplier or exponential function. In some cases, skipping consecutive storage elements may save storage elements and reduce the power to store an indication that the duration has satisfied a threshold. In some cases, logic circuitry **340** may select non-consecutive storage elements when it is provided with time to store the indication(s) during a power down cycle.

(103) Thus, in some cases, the quantity and/or position of a storage element in the set of storage elements **345** that have been used to store an indication that the duration satisfies the threshold may provide an indication of a cumulative amount of time a memory device **305** has been operated with one or more operating conditions outside of a range, as detected by sensor **320** and measured by timer **330**.

(104) In some cases, memory device **305** may include counter **335** that is coupled with timer **330**. Counter **335** may be configured to count a quantity of times that the duration satisfies the threshold based on a quantity of instances when counter **335** receives a signal from timer **330**. In some cases, counter **335** may be configured to output, to logic circuitry **340**, a signal indicating the quantity of times the duration satisfied the threshold. In some cases, logic circuitry **340** may select the one or more storage elements **345** based on the signal received from counter **335**. For example, if counter **335** outputs a signal indicating that the duration satisfied the threshold three (3) times (or indicating an equivalent duration), logic circuitry **340** may select three (3) storage elements **345** and store an indication that the duration satisfied the threshold in each of the selected storage elements **345**. In some cases, logic circuitry **340** may store the indications in the selected storage elements **345** each time a duration satisfies the threshold, or may store the indications in the selected storage elements **345** at a later time, such as during a power down procedure. The quantity of storage elements **345** need not match the quantity of times the duration satisfied the threshold, however. In some cases, different storage elements **345** may be associated with different thresholds. For example, logic circuitry **340** may select a single storage element **345** that corresponds to a total duration indicated

by the quantity of times the duration satisfied the threshold.

(105) In some cases, the set of storage elements **345** may include a set of fuses for storing the indications that the duration satisfies the threshold. Blowing a fuse on memory device **305** may consume a significant amount of power, however, which may disrupt or degrade normal operations of memory device **305**. Thus, in some cases, memory device **305** may wait to blow a fuse (or to store the indication in another type of storage element) until memory device **305** is idle or otherwise operating under suitable conditions.

(106) For example, logic circuitry **340** may receive a signal from timer **330** or counter **335** indicating that the duration satisfies a threshold, and may wait for a subsequent storage opportunity to save the indication in one or more storage elements **345**. A storage opportunity may be a time period during which memory device **305** is idle or is performing operations that consume less than a threshold amount of power, etc.

(107) In some cases, logic circuitry **340** may identify a storage opportunity based on a signal received from a controller **350**. For example, controller **350** may provide, to logic circuitry **340**, a signal indicating that memory device **305** is operating in an idle state to enable logic circuitry **340** to identify the storage opportunity. Controller **350** may be (or may be included in) a local memory controller **165**, **260**, device memory controller **155**, or external memory controller **105** as described with reference to FIGS. **1** and **2**. In some cases, logic circuitry **340** may be included in controller **350**.

(108) In some cases, one or more storage elements **345** may be associated with an alert, such that when an indication is stored in the storage element **345**, the alert is transmitted to an external device **355**, such as a host processor or other device. For example, in some cases, blowing a particular fuse in a set of fuses may cause an alert to be transmitted to the external device **355**. Such alerts may be associated with the memory device **305** approaching or reaching a critical or notable duration over which it has been operated with operating conditions outside of an operating range, and may enable memory device **305** to notify an external device **355** that memory device **305** may be degrading. In some cases, multiple storage elements **345** may be associated with alerts, such that memory device **305** may transmit successive alerts to an external device indicating an increasing likelihood that memory device **305** may be degrading.

(109) In some cases, the set of storage elements **345** may include one or more registers that may comprise volatile storage elements. In some cases, memory device **305** may track the quantity of times the duration satisfies the threshold, and may store an indication of the quantity of times in a register. In some cases, an external device may read the register to determine the health status of the memory device **305**. In some cases, a memory device **305** may clear the register when it is read, or modify a value in a separate status register (e.g., a register that may be commonly polled to read other status information) to indicate when the quantity of times stored in the register has been updated.

(110) In some cases, memory device **305** may provide, to an external device, an indication each time the threshold is met (e.g., via a pin) so that the external device doesn't have to continually read a register to determine if the value has changed, for example.

(111) In some cases, one or more sensors **320** may be off-die or off of the memory device, such as at another location within a system that includes a memory device and a host processor. In some cases, the host processor may determine that an operating condition associated with the system and/or with an array of memory cells on a memory device is outside a range, and monitor, based on determining that the operating condition is outside the range, a duration over which the operating condition is outside the range. The host processor may determine that the duration satisfies a threshold based on monitoring the duration, and may store, in a storage element based on determining that the duration satisfies the threshold, an indication that the duration satisfies the threshold. The storage element may be on a memory device or on a memory die, for example.

(112) FIG. **4** shows a block diagram **400** of a memory device **405** that supports persistent health

monitoring for volatile memory devices in accordance with examples as disclosed herein. The memory device **405** may be an example of aspects of a memory device or memory die as described with reference to FIGS. 1-3. The memory device **405** may include a determination component **410**, a duration monitoring component **415**, a threshold component **420**, a storage component **425**, a storage opportunity identification component **430**, an alert determination component **435**, and an interface component **440**. Each of these modules may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(113) The determination component **410** may determine that an operating condition associated with an array of memory cells is outside a range. In some examples, the determination component **410** may determine that a second operating condition associated with the array of memory cells is outside of a second range. In some examples, the determination component **410** may determine an amount by which the operating condition is outside of the range. In some cases, the operating condition includes one or more of a temperature, a power, a voltage, a current, or a health status determined based on detection of memory errors of the array of memory cells

(114) The duration monitoring component **415** may monitor, based on determining that the operating condition is outside the range, a duration over which the operating condition is outside the range. In some examples, the duration monitoring component **415** may start a timer based on the determination that the operating condition is outside of the range, where the duration is monitored based on an elapsed time after starting the timer. In some examples, the duration monitoring component **415** may restart the timer when the duration satisfies the threshold.

(115) The threshold component **420** may determine that the duration satisfies a threshold based on monitoring the duration. In some examples, the threshold component **420** may determine the threshold based on the determination that the operating condition is outside of the range and the determination that the second operating condition is outside of the second range. In some examples, the threshold component **420** may determine the threshold based on the amount by which the operating condition is outside of the range.

(116) The storage component **425** may store, in a storage element based on determining that the duration satisfies the threshold, an indication that the duration satisfies the threshold. In some examples, the storage component **425** may select, based on the threshold, the storage element from a set of storage elements, where each storage element of the set of storage elements is associated with a respective threshold.

(117) In some examples, the storage component **425** may store the indication in a volatile storage element.

(118) In some examples, the storage component **425** may store the indication in a non-volatile storage element. In some examples, storing the indication in the storage element includes programming a one-time programmable storage element.

(119) In some examples, the storage component **425** may store, based on a determination that an elapsed time after restarting the timer satisfies the threshold, a second indication in a second non-volatile storage element. In some examples, storing the indication in the non-volatile storage element includes programming a first one-time programmable storage element and storing the second indication in the second non-volatile storage element includes programming a second one-time programmable storage element. In some cases, the first one-time programmable storage element and the second one-time programmable storage element are consecutive one-time programmable storage elements within an array of one-time programmable storage elements.

(120) In some cases, the non-volatile storage element includes one or more programmable non-volatile memory cells, and where storing the indication in the non-volatile storage element includes adjusting a value stored in the one or more programmable non-volatile memory cells.

(121) In some cases, a storage opportunity identification component **430** may identify a storage opportunity after storing the indication in the volatile storage element, where storing the indication in the non-volatile storage element includes reading the indication from the volatile storage

element, and storing the indication in the non-volatile storage element during the storage opportunity. The storage opportunity identification component **430** may identify the storage opportunity by identifying a time period during which the array of memory cells is idle.

(122) The alert determination component **435** may determine that the non-volatile storage element is associated with an alert. In some examples, the alert determination component **435** may transmit the alert to an external device based on the determination that the non-volatile storage element is associated with the alert.

(123) The interface component **440** may receive, from an external device, a request for the indication. In some examples, the interface component **440** may transfer the indication from the storage element to the external device based on the request.

(124) FIG. 5 shows a flowchart illustrating a method or methods **500** that supports persistent health monitoring for volatile memory devices in accordance with aspects of the present disclosure. The operations of method **500** may be implemented by a memory device or its components as described herein. For example, the operations of method **500** may be performed by a memory device as described with reference to FIG. 4. In some examples, a memory device may execute a set of instructions to control the functional elements of the memory device to perform the described functions. Additionally or alternatively, a memory device may perform aspects of the described functions using special-purpose hardware.

(125) At **505**, the memory device may determine that an operating condition associated with an array of memory cells is outside a range. The operations of **505** may be performed according to the methods described herein. In some examples, aspects of the operations of **505** may be performed by a sensor, comparison element, and/or logic circuitry as described with reference to FIG. 3. In some examples, aspects of the operations of **505** may be performed by a determination component as described with reference to FIG. 4.

(126) At **510**, the memory device may monitor, based on determining that the operating condition is outside the range, a duration over which the operating condition is outside the range. The operations of **510** may be performed according to the methods described herein. In some examples, aspects of the operations of **510** may be performed by a timer as described with reference to FIG. 3. In some examples, aspects of the operations of **510** may be performed by a duration monitoring component as described with reference to FIG. 4.

(127) At **515**, the memory device may determine that the duration satisfies a threshold based on monitoring the duration. The operations of **515** may be performed according to the methods described herein. In some examples, aspects of the operations of **515** may be performed by a timer and/or logic circuitry as described with reference to FIG. 3. In some examples, aspects of the operations of **515** may be performed by a threshold component as described with reference to FIG. 4.

(128) At **520**, the memory device may store, in a storage element based on determining that the duration satisfies the threshold, an indication that the duration satisfies the threshold. The operations of **520** may be performed according to the methods described herein. In some examples, aspects of the operations of **520** may be performed by a controller, logic circuitry, and/or a set of storage elements as described with reference to FIG. 3. In some examples, aspects of the operations of **520** may be performed by a storage component as described with reference to FIG. 4.

(129) In some examples, an apparatus as described herein may perform a method or methods, such as the method **500**. The apparatus may include features, means, or instructions (e.g., a non-transitory computer-readable medium storing instructions executable by a processor) for determining that an operating condition associated with an array of memory cells is outside a range, monitoring, based on determining that the operating condition is outside the range, a duration over which the operating condition is outside the range, determining that the duration satisfies a threshold based on monitoring the duration, and storing, in a storage element and based on determining that the duration satisfies the threshold, an indication that the duration satisfies the

threshold.

(130) In some examples of the method **500** and the apparatus described herein, the array of memory cells may be an array of volatile memory cells and the storage element may be a non-volatile storage element.

(131) In some examples of the method **500** and the apparatus described herein, operations, features, means, or instructions for storing the indication in the non-volatile storage element may include operations, features, means, or instructions for selecting, based on the threshold, the non-volatile storage element from a set of non-volatile storage elements, where each non-volatile storage element of the set of non-volatile storage elements may be associated with a respective threshold.

(132) In some examples of the method **500** and the apparatus described herein, operations, features, means, or instructions for storing the indication in the non-volatile storage element may include operations, features, means, or instructions for programming a one-time programmable storage element.

(133) Some examples of the method **500** and the apparatus described herein may further include operations, features, means, or instructions for storing the indication in a volatile storage element, and identifying a storage opportunity after storing the indication in the volatile storage element, where storing the indication in the non-volatile storage element includes reading the indication from the volatile storage element, and storing the indication in the non-volatile storage element during the storage opportunity.

(134) In some examples of the method **500** and the apparatus described herein, operations, features, means, or instructions for identifying the storage opportunity may include operations, features, means, or instructions for identifying a time period during which the array of volatile memory cells may be idle.

(135) In some examples of the method **500** and the apparatus described herein, the non-volatile storage element includes one or more programmable non-volatile memory cells, and storing the indication in the non-volatile storage element includes adjusting a value stored in the one or more programmable non-volatile memory cells.

(136) Some examples of the method **500** and the apparatus described herein may further include operations, features, means, or instructions for determining that the non-volatile storage element may be associated with an alert, and transmitting the alert to an external device based on the determination that the non-volatile storage element may be associated with the alert.

(137) Some examples of the method **500** and the apparatus described herein may further include operations, features, means, or instructions for determining that a second operating condition associated with the array of volatile memory cells may be outside of a second range, and determining the threshold based on the determination that the operating condition may be outside of the range and the determination that the second operating condition may be outside of the second range.

(138) Some examples of the method **500** and the apparatus described herein may further include operations, features, means, or instructions for determining an amount by which the operating condition may be outside of the range, and determining the threshold based on the amount by which the operating condition may be outside of the range.

(139) In some examples of the method **500** and the apparatus described herein, operations, features, means, or instructions for monitoring the duration may include operations, features, means, or instructions for starting a timer based on the determination that the operating condition may be outside of the range, where the duration may be monitored based on an elapsed time after starting the timer.

(140) Some examples of the method **500** and the apparatus described herein may further include operations, features, means, or instructions for restarting the timer when the duration satisfies the threshold, and storing, based on a determination that an elapsed time after restarting the timer satisfies the threshold, a second indication in a second non-volatile storage element.

(141) In some examples of the method **500** and the apparatus described herein, storing the indication in the non-volatile storage element may include operations, features, means, or instructions for programming a first one-time programmable storage element and storing the second indication in the second non-volatile storage element.

(142) In some examples of the method **500** and the apparatus described herein, the first one-time programmable storage element and the second one-time programmable storage element may be consecutive one-time programmable storage elements within an array of one-time programmable storage elements.

(143) In some examples of the method **500** and the apparatus described herein, the operating condition includes one or more of a temperature, a power, a voltage, a current, or a health status determined based on detection of memory errors of the array of volatile memory cells.

(144) Some examples of the method **500** and the apparatus described herein may further include operations, features, means, or instructions for receiving, from an external device, a request for the indication, and transferring the indication from the storage element to the external device based on the request.

(145) It should be noted that the methods described above describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Furthermore, portions from two or more of the methods may be combined.

(146) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof. Some drawings may illustrate signals as a single signal; however, it will be understood by a person of ordinary skill in the art that the signal may represent a bus of signals, where the bus may have a variety of bit widths.

(147) As used herein, the term “virtual ground” refers to a node of an electrical circuit that is held at a voltage of approximately zero volts (0V) but that is not directly coupled with ground. Accordingly, the voltage of a virtual ground may temporarily fluctuate and return to approximately 0V at steady state. A virtual ground may be implemented using various electronic circuit elements, such as a voltage divider consisting of operational amplifiers and resistors. Other implementations are also possible. “Virtual grounding” or “virtually grounded” means connected to approximately 0V.

(148) The terms “electronic communication,” “conductive contact,” “connected,” and “coupled” may refer to a relationship between components that supports the flow of signals between the components. Components are considered in electronic communication with (or in conductive contact with or connected with or coupled with) one another if there is any conductive path between the components that can, at any time, support the flow of signals between the components. At any given time, the conductive path between components that are in electronic communication with each other (or in conductive contact with or connected with or coupled with) may be an open circuit or a closed circuit based on the operation of the device that includes the connected components. The conductive path between connected components may be a direct conductive path between the components or the conductive path between connected components may be an indirect conductive path that may include intermediate components, such as switches, transistors, or other components. In some cases, the flow of signals between the connected components may be interrupted for a time, for example, using one or more intermediate components such as switches or transistors.

(149) The term “coupling” refers to condition of moving from an open-circuit relationship between components in which signals are not presently capable of being communicated between the components over a conductive path to a closed-circuit relationship between components in which

signals are capable of being communicated between components over the conductive path. When a component, such as a controller, couples other components together, the component initiates a change that allows signals to flow between the other components over a conductive path that previously did not permit signals to flow.

(150) The term “isolated” refers to a relationship between components in which signals are not presently capable of flowing between the components. Components are isolated from each other if there is an open circuit between them. For example, two components separated by a switch that is positioned between the components are isolated from each other when the switch is open. When a controller isolates two components, the controller affects a change that prevents signals from flowing between the components using a conductive path that previously permitted signals to flow.

(151) As used herein, the term “substantially” means that the modified characteristic (e.g., a verb or adjective modified by the term substantially) need not be absolute but is close enough to achieve the advantages of the characteristic.

(152) As used herein, the term “electrode” may refer to an electrical conductor, and in some cases, may be employed as an electrical contact to a memory cell or other component of a memory array. An electrode may include a trace, wire, conductive line, conductive layer, or the like that provides a conductive path between elements or components of memory array.

(153) The devices discussed herein, including a memory array, may be formed on a semiconductor substrate, such as silicon, germanium, silicon-germanium alloy, gallium arsenide, gallium nitride, etc. In some cases, the substrate is a semiconductor wafer. In other cases, the substrate may be a silicon-on-insulator (SOI) substrate, such as silicon-on-glass (SOG) or silicon-on-sapphire (SOP), or epitaxial layers of semiconductor materials on another substrate. The conductivity of the substrate, or sub-regions of the substrate, may be controlled through doping using various chemical species including, but not limited to, phosphorous, boron, or arsenic. Doping may be performed during the initial formation or growth of the substrate, by ion-implantation, or by any other doping means.

(154) A switching component or a transistor discussed herein may represent a field-effect transistor (FET) and comprise a three terminal device including a source, drain, and gate. The terminals may be connected to other electronic elements through conductive materials, e.g., metals. The source and drain may be conductive and may comprise a heavily-doped, e.g., degenerate, semiconductor region. The source and drain may be separated by a lightly-doped semiconductor region or channel. If the channel is n-type (i.e., majority carriers are electrons), then the FET may be referred to as a n-type FET. If the channel is p-type (i.e., majority carriers are holes), then the FET may be referred to as a p-type FET. The channel may be capped by an insulating gate oxide. The channel conductivity may be controlled by applying a voltage to the gate. For example, applying a positive voltage or negative voltage to an n-type FET or a p-type FET, respectively, may result in the channel becoming conductive. A transistor may be “on” or “activated” when a voltage greater than or equal to the transistor's threshold voltage is applied to the transistor gate. The transistor may be “off” or “deactivated” when a voltage less than the transistor's threshold voltage is applied to the transistor gate.

(155) The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “exemplary” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details to providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form to avoid obscuring the concepts of the described examples.

(156) In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference

label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

(157) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(158) The various illustrative blocks and modules described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(159) The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations. Also, as used herein, including in the claims, “or” as used in a list of items (for example, a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

(160) Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, non-transitory computer-readable media can comprise RAM, ROM, electrically erasable programmable read only memory (EEPROM), compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that can be used to carry or store desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks

usually reproduce data magnetically, while discs reproduce data optically with lasers.

Combinations of the above are also included within the scope of computer-readable media.

(161) The description herein is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein, but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. A method, comprising: operating a memory device with an operating condition that is associated with an operating range, wherein the operating condition is one of a plurality of operating conditions supported by the memory device; detecting, based at least in part on operating the memory device, that a duration over which the operating condition is outside the operating range exceeds a threshold duration, wherein the threshold duration is based at least in part on a type of the operating condition; and storing an indication that the duration over which the operating condition is outside the operating range exceeds the threshold duration based at least in part on the detecting.
2. The method of claim 1, further comprising: transmitting, based at least in part on the storing, an alert to an external device indicating that the duration over which the operating condition is outside the operating range exceeds the threshold duration.
3. The method of claim 1, further comprising: detecting that the operating condition of the memory device is outside the operating range based at least in part on operating the memory device; and initiating a timer based at least in part on detecting that the operating condition is outside the operating range, wherein detecting that the duration over which the operating condition is outside the operating range exceeds the threshold duration is based at least in part on initiating the timer.
4. The method of claim 1, further comprising: identifying, from a plurality of storage elements and based at least in part on the detecting, a storage element that is associated with the duration over which the operating condition is outside the operating range, wherein each of the plurality of storage elements are associated with respective threshold durations, and wherein the storing further comprises storing the indication in the identified storage element.
5. The method of claim 1, further comprising: monitoring the operating condition of the memory device based at least in part on operating the memory device, wherein the detecting is based at least in part on the monitoring.
6. The method of claim 1, further comprising: identifying the threshold duration based at least in part on the operating condition, an amount that the operating condition is outside the operating range, a quantity of operating conditions of the memory device that are outside respective operating ranges, or a combination thereof, wherein the detecting is based at least in part on identifying the threshold duration.
7. The method of claim 1, wherein storing the indication further comprises: storing the indication in a one-time programmable storage element.
8. The method of claim 7, wherein the one-time programmable storage element is at the memory device or external to the memory device.
9. The method of claim 1, wherein the operating condition comprises one or more of a temperature, a power, a voltage, a current, or a health status determined based at least in part on detection of memory errors of one or more arrays of volatile memory cells of the memory device.
10. A non-transitory computer-readable medium storing code, the code comprising instructions executable by one or more processors to: operate a memory device with an operating condition that is associated with an operating range, wherein the operating condition is one of a plurality of

operating conditions supported by the memory device; detect, based at least in part on operating the memory device, that a duration over which the operating condition is outside the operating range exceeds a threshold duration, wherein the threshold duration is based at least in part on a type of the operating condition; and store an indication that the duration over which the operating condition is outside the operating range exceeds the threshold duration based at least in part on the detecting.

11. The non-transitory computer-readable medium of claim 10, wherein the instructions are further executable by the one or more processors to: transmit, based at least in part on the storing, an alert to an external device indicating that the duration over which the operating condition is outside the operating range exceeds the threshold duration.

12. The non-transitory computer-readable medium of claim 10, wherein the instructions are further executable by the one or more processors to: detect that the operating condition of the memory device is outside the operating range based at least in part on operating the memory device; and initiate a timer based at least in part on detecting that the operating condition of the memory device is outside the operating range, wherein detecting that the duration over which the operating condition is outside the operating range exceeds the threshold duration is based at least in part on initiating the timer.

13. The non-transitory computer-readable medium of claim 10, wherein the instructions are further executable by the one or more processors to: identify, from a plurality of storage elements and based at least in part on the detecting, a storage element that is associated with the duration over which the operating condition is outside the operating range, wherein each of the plurality of storage elements are associated with respective threshold durations, and wherein the instructions to store the indication are further executable by the one or more processors to store the indication at the identified storage element.

14. The non-transitory computer-readable medium of claim 10, wherein the instructions are further executable by the one or more processors to: monitor the operating condition of the memory device based at least in part on operating the memory device, wherein the detecting is based at least in part on the monitoring.

15. The non-transitory computer-readable medium of claim 10, wherein the instructions are further executable by the one or more processors to: identify the threshold duration based at least in part on the operating condition, an amount that the operating condition is outside the operating range, a quantity of other operating conditions of the memory device that are outside respective operating ranges, or a combination thereof, wherein the detecting is based at least in part on identifying the threshold duration.

16. The non-transitory computer-readable medium of claim 10, wherein the instructions to store the indication are further executable by the one or more processors to: store the indication in a one-time programmable storage element.

17. The non-transitory computer-readable medium of claim 16, wherein the one-time programmable storage element is at the memory device or external to the memory device.

18. The non-transitory computer-readable medium of claim 10, wherein the operating condition comprises one or more of a temperature, a power, a voltage, a current, or a health status that is based at least in part on a detection of errors at the memory device.

19. A memory system, comprising: one or more memory devices; and processing circuitry coupled with the one or more memory devices and configured to cause the memory system to: operate the one or more memory devices with an operating condition that is associated with an operating range, wherein the operating condition is one of a plurality of operating conditions supported by the one or more memory devices; detect, based at least in part on operating the one or more memory devices, that a duration over which the operating condition is outside the operating range exceeds a threshold duration, wherein the threshold duration is based at least in part on a type of the operating condition; and store an indication that the duration over which the operating condition is outside the operating range exceeds the threshold duration based at least in part on the detecting.

20. The memory system of claim 19, wherein the processing circuitry is further configured to cause the memory system to: transmit, based at least in part on the storing, an alert to an external device indicating that the duration over which the operating condition is outside the operating range exceeds the threshold duration.
